



# TEST REPORT

**KCTL KCTL Inc.**

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR20-SRF0243

Page (1) of (34)

**KCTL**

## 1. Client

- Name : SUPREMA INC
- Address : 17F-5, Parkview officetower,, 248, Jeongjail-ro, Bundang-gu, Seongnam-si, Gyeonggi-do 13554 Korea (Republic Of)
- Date of Receipt : 2020-08-31

**2. Use of Report** : Certification

**3. Name of Product / Model** : FaceStation F2 / FSF2-AB

**4. Manufacturer / Country of Origin** : SUPREMA INC / Korea

**5. FCC ID** : TKWFSF2-AB

**6. IC Certificate No.** : 23080-FSF2AB

**7. Date of Test** : 2020-09-18 to 2020-09-23

**8. Location of Test** : ☒ Permanent Testing Lab ☐ On Site Testing (Address: Address of testing location)

**9. Test method used** : FCC Part 15 Subpart C, 15.247  
RSS-247 Issue 2 February 2017  
RSS-Gen Issue 5 March 2019

**10. Test Results** : Refer to the test result in the test report

|             |                                |                              |
|-------------|--------------------------------|------------------------------|
| Affirmation | Tested by                      | Technical Manager            |
|             | Name : Jungwon Seo (Signature) | Name : Heesu Ahn (Signature) |

2020-09-29

**KCTL Inc.**

As a test result of the sample which was submitted from the client, this report does not guarantee the whole product quality. This test report should not be used and copied without a written agreement by KCTL Inc.

## REPORT REVISION HISTORY

| Date       | Revision          | Page No |
|------------|-------------------|---------|
| 2020-09-29 | Originally issued | -       |
|            |                   |         |
|            |                   |         |
|            |                   |         |
|            |                   |         |

*This report shall not be reproduced except in full, without the written approval of KCTL Inc. This document may be altered or revised by KCTL Inc. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KCTL Inc. will constitute fraud and shall nullify the document. This test report is a general report that does not use the KOLAS accreditation mark and is not related to KS Q ISO/IEC 17025 and KOLAS accreditation.*

## General remarks for test reports

Nothing significant to report.



## CONTENTS

|      |                                                        |    |
|------|--------------------------------------------------------|----|
| 1.   | General information .....                              | 4  |
| 2.   | Device information .....                               | 4  |
| 2.1. | Accessory information .....                            | 4  |
| 2.2. | Information about derivative model.....                | 5  |
| 2.3. | Frequency/channel operations.....                      | 5  |
| 2.4. | Duty Cycle Factor .....                                | 5  |
| 3.   | Antenna requirement .....                              | 6  |
| 4.   | Summary of tests .....                                 | 7  |
| 5.   | Measurement uncertainty .....                          | 8  |
| 6.   | Measurement results explanation example .....          | 9  |
| 7.   | Test results .....                                     | 10 |
| 7.1. | Maximum peak output power.....                         | 10 |
| 7.2. | Peak Power Spectral Density .....                      | 13 |
| 7.3. | 6 dB Bandwidth(DTS Channel Bandwidth) .....            | 15 |
| 7.4. | Spurious Emission, Band Edge and Restricted bands..... | 18 |
| 7.5. | Conducted Spurious Emission.....                       | 32 |
| 8.   | Measurement equipment.....                             | 34 |



## 2.2. Information about derivative model

The difference between basic model and derivative models is:

Based on the base model, derivative model removes the SAM IC to support a specific card.

- FSF2-DB : Removed SAM IC

- FSF2-ABT10, FSF2-DBT10 : FSF2-AB with customer's mark & label

The firmware is the same for each model, but the SAM IC operation is activated / deactivated by registering the model name.

## 2.3. Frequency/channel operations

This device contains the following capabilities:

NFC, 125 kHz (RFID), Bluetooth Low Energy

| Ch. | Frequency (MHz) |
|-----|-----------------|
| 00  | 2 402           |
| .   | .               |
| 19  | 2 440           |
| .   | .               |
| 39  | 2 480           |


Table 2.2.1. Bluetooth Low Energy

## 2.4. Duty Cycle Factor

| Test mode            | Period (ms) | On time (ms) | Duty cycle |       | Duty Cycle Factor (dB) |
|----------------------|-------------|--------------|------------|-------|------------------------|
|                      |             |              | (Linear)   | (%)   |                        |
| 1M Bits/s, 37 Packet | 0.625       | 0.395        | 0.645 2    | 64.52 | 1.90                   |

### Notes.

1. Duty cycle (Linear) = Ton time / Period
2. DCF(Duty cycle factor) =  $10\log(1/\text{duty cycle})$



### 3. Antenna requirement

#### **Requirement of FCC part section 15.203:**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

#### **Requirement of RSS-Gen Section 6.8:**

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

- The transmitter has permanently attached PCB Pattern antenna (internal antenna) on board.
- The E.U.T Complies with the requirement of §15.203, §15.247.

#### 4. Summary of tests

| FCC Part section(s)                   | IC Rule Reference                     | Parameter                   | Test mode | Test results           |
|---------------------------------------|---------------------------------------|-----------------------------|-----------|------------------------|
| 15.247(b)(3)                          | RSS-247 (5.4)(d)                      | Maximum Peak Output Power   | Conducted | Pass                   |
| 15.247(e)                             | RSS-247 (5.2)(b)                      | Peak Power Spectral Density |           | Pass                   |
| 15.247(a)(2)                          | RSS-247 (5.2)(a)                      | 6 dB Channel Bandwidth      |           | Pass                   |
| -                                     | RSS-Gen (6.7)                         | Occupied Bandwidth          |           | Pass                   |
| 15.207(a)                             | RSS-Gen (8.8)                         | Conducted Emissions         |           | N/A <sup>(Note2)</sup> |
| 15.247(d),<br>15.205(a),<br>15.209(a) | RSS-Gen (8.9), (8.10)<br>RSS-247(5.5) | Spurious emission           | Radiated  | Pass                   |
|                                       |                                       | Band-edge, restricted band  |           | Pass                   |

#### Notes:

1. All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
2. This test is not applicable because the EUT only connects DC power line
3. According to exploratory test no any obvious emission were detected from 9 kHz to 30 MHz. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30 m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.
4. The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z. It was determined that Y orientation was worst-case orientation. Therefore, all final radiated testing was performed with the EUT in Y orientation
5. All the radiated tests have been performed two modes (with charger and without charger) and the with charger is the worst case mode.
6. The worst-case data rate were: Packet length 37 Bytes
7. The test procedure(s) in this report were performed in accordance as following.
  - ◆ ANSI C63.10-2013
  - ◆ KDB 558074 D01 v05r02



## 5. Measurement uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of  $k=2$  to indicated a 95 % level of confidence. The measurement data shown herein meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and thus, can be compared directly to specified limits to determine compliance.

| Parameter                    | Expanded uncertainty ( $\pm$ ) |        |
|------------------------------|--------------------------------|--------|
| Conducted RF power           | 1.3 dB                         |        |
| Conducted spurious emissions | 1.3 dB                         |        |
| Radiated spurious emissions  | 9 kHz ~ 30 MHz:                | 2.3 dB |
|                              | 30 MHz ~ 300 MHz               | 5.4 dB |
|                              | 300 MHz ~ 1 000 MHz            | 5.5 dB |
|                              | Above 1 GHz                    | 6.7 dB |
| Conducted emissions          | 9 kHz ~ 150 kHz                | 3.7 dB |
|                              | 150 kHz ~ 30 MHz               | 3.3 dB |

**KCTL**



## 6. Measurement results explanation example


| Frequency (MHz) | Factor(dB) | Frequency (MHz) | Factor(dB) |
|-----------------|------------|-----------------|------------|
| 30              | 10.41      | 9 000           | 12.97      |
| 50              | 10.33      | 10 000          | 13.31      |
| 100             | 10.36      | 11 000          | 13.84      |
| 200             | 10.44      | 12 000          | 14.06      |
| 300             | 10.56      | 13 000          | 14.65      |
| 400             | 10.62      | 14 000          | 14.56      |
| 500             | 10.67      | 15 000          | 14.35      |
| 600             | 10.68      | 16 000          | 14.31      |
| 700             | 10.73      | 17 000          | 13.76      |
| 800             | 10.87      | 18 000          | 14.11      |
| 900             | 10.91      | 19 000          | 13.44      |
| 1 000           | 10.81      | 20 000          | 13.83      |
| 2 000           | 11.21      | 21 000          | 12.08      |
| 3 000           | 11.51      | 22 000          | 14.05      |
| 4 000           | 11.68      | 23 000          | 15.12      |
| 5 000           | 11.92      | 24 000          | 14.47      |
| 6 000           | 12.17      | 25 000          | 15.17      |
| 7 000           | 12.44      | 26 000          | 14.69      |
| 8 000           | 12.66      | 26 500          | 15.08      |

**Note :** Offset(dB) = RF cable loss(dB) + Attenuator(dB)

## 7. Test results

### 7.1. Maximum peak output power

#### Test setup



#### Limit

##### FCC

According to §15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2 400-2 483.5 MHz, and 5 725-5 850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

According to §15.247(b)(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

##### IC

According to RSS-247 5.4(d), For DTSSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1 W. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e).

#### Test procedure

ANSI C63.10 - Section 11.9

Used test method is section 11.9.1.3 and 11.9.2.3.1

## **Test settings**

### **General**

Section 15.247 permits the maximum conducted (average) output power to be measured as an alternative to the maximum peak conducted output power for demonstrating compliance to the limit. When this option is exercised, the measured power is to be referenced to the OBW rather than the DTS bandwidth (see ANSI C63.10 for measurement guidance).

When using a spectrum analyzer or EMI receiver to perform these measurements, it shall be capable of utilizing a number of measurement points in each sweep that is greater than or equal to twice the span/RBW to set a bin-to-bin spacing of  $\leq \text{RBW}/2$  so that narrowband signals are not lost between frequency bins.

If possible, configure or modify the operation of the EUT so that it transmits continuously at its maximum power control level. The intent is to test at 100 % duty cycle; however a small reduction in duty cycle (to no lower than 98 %) is permitted, if required by the EUT for amplitude control purposes. Manufacturers are expected to provide software to the test lab to permit such continuous operation.

If continuous transmission (or at least 98 % duty cycle) cannot be achieved due to hardware limitations (e.g., overheating), the EUT shall be operated at its maximum power control level, with the transmit duration as long as possible, and the duty cycle as high as possible during which sweep triggering/signal gating techniques may be used to perform the measurement over the transmission duration.

### **11.9.1. Maximum peak conducted output power**

One of the following procedures may be used to determine the maximum peak conducted output power of a DTS EUT.

#### **11.9.1.1. RBW $\geq$ DTS bandwidth**

The following procedure shall be used when an instrument with a resolution bandwidth that is greater than the DTS bandwidth is available to perform the measurement:

- a) Set the RBW  $\geq$  DTS bandwidth.
- b) Set VBW  $\geq [3 \times \text{RBW}]$ .
- c) Set span  $\geq [3 \times \text{RBW}]$ .
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

#### **11.9.1.3. PKPM1 Peak power meter method**

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

**11.9.2.3.1. Measurement using a power meter (PM)**

Method AVGPM is a measurement using an RF average power meter, as follows:

- a) As an alternative to spectrum analyzer or EMI receiver measurements, measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied:
  - 1) The EUT is configured to transmit continuously, or to transmit with a constant duty cycle.
  - 2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
  - 3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- b) If the transmitter does not transmit continuously, measure the duty cycle, D, of the transmitter output signal as described in 11.6.
- c) Measure the average power of the transmitter. This measurement is an average over both the ON and OFF periods of the transmitter.
- d) Adjust the measurement in dBm by adding  $[10 \log(1/D)]$ , where D is the duty cycle

**Notes:**

A peak responding power sensor is used, where the power sensor system video bandwidth is greater than the occupied bandwidth of the EUT.

**Test results**

| Frequency<br>(MHz) | Data rate | Packet length | Conducted output power (dBm) |         | Conducted power Limit (dBm) | Ant. Gain (dB i) | Max. e.i.r.p.(dB m) |         | Max. e.i.r.p. Limit (dB m) |
|--------------------|-----------|---------------|------------------------------|---------|-----------------------------|------------------|---------------------|---------|----------------------------|
|                    | (Bits/s)  | (Bytes)       | Peak                         | Average |                             |                  | Peak                | Average |                            |
| 2 402              | 1M        | 37            | -11.82                       | -12.66  | 30.00                       | 3.03             | -8.79               | -9.63   | 36.02                      |
| 2 440              | 1M        | 37            | -12.01                       | -13.27  |                             | 3.03             | -8.98               | -10.24  |                            |
| 2 480              | 1M        | 37            | -12.59                       | -13.08  |                             | 3.03             | -9.56               | -10.05  |                            |


**Notes:**

Measured output power(Average) = reading value of average power + D.C.F

e.i.r.p. Calculation: e.i.r.p. (dBm) = Conducted output power (dBm) + Antenna gain (dBi)

## 7.2. Peak Power Spectral Density

### Test setup



### Limit

According to §15.247(e) and RSS-247(5.2), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

### Test procedure

ANSI C63.10 - Section 11.10.2

### Test settings




#### Method PKPSD (peak PSD)

The following procedure shall be used if maximum peak conducted output power was used to determine compliance, and it is optional if the maximum conducted (average) output power was used to determine compliance:

- 1) Set analyzer center frequency to DTS channel center frequency.
- 2) Set the span to 1.5 times the DTS bandwidth.
- 3) Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- 4) Set the VBW  $\geq 3 \times \text{RBW}$ .
- 5) Detector = peak.
- 6) Sweep time = auto couple.
- 7) Trace mode = max hold.
- 8) Allow trace to fully stabilize.
- 9) Use the peak marker function to determine the maximum amplitude level within the RBW.
- 10) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

**Test results**


| Frequency(MHz) | Data rate | Packet length | PSD(dBm/3 kHz) | Limit(dBm/3 kHz) |
|----------------|-----------|---------------|----------------|------------------|
|                | (Bits/s)  | (Bytes)       |                |                  |
| 2 402          | 1M        | 37            | -25.36         | 8.00             |
| 2 440          |           |               | -25.39         |                  |
| 2 480          |           |               | -26.41         |                  |

**BLE\_1 Mbits/s**

Blank

### 7.3. 6 dB Bandwidth(DTS Channel Bandwidth)

#### Test setup



#### Limit

According to §15.247(a)(2) and RSS-247(5.2) For Systems using digital modulation techniques may operate in the 902–928 MHz, 2 400–2 483.5 MHz, and 5 725–5 850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

#### Test procedure

ANSI C63.10 – Section 11.8.2

#### Test settings

##### **DTS bandwidth**

One of the following procedures may be used to determine the modulated DTS bandwidth.

##### **Option 1**

- 1) Set RBW = 100 kHz.
- 2) Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
- 3) Detector = Peak.
- 4) Trace mode = max hold.
- 5) Sweep = auto couple.
- 6) Allow the trace to stabilize.
- 7) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

##### **Option 2**

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e., RBW = 100 kHz, VBW  $\geq 3 \times$  RBW, and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be  $\geq 6$  dB.



**Test results**

| Frequency(MHz) | Data rate<br>(Bits/s) | Packet length<br>(Bytes) | 6 dB bandwidth<br>(MHz) | 99 % Bandwidth<br>(MHz) |
|----------------|-----------------------|--------------------------|-------------------------|-------------------------|
| 2 402          | 1M                    | 37                       | 0.709                   | 1.046                   |
| 2 440          |                       |                          | 0.704                   | 1.048                   |
| 2 480          |                       |                          | 0.709                   | 1.049                   |

**6 dB bandwidth****BLE\_1Mbits/s**

Blank


**99% bandwidth****BLE\_1Mbits/s**

Blank


## 7.4. Spurious Emission, Band Edge and Restricted bands

### Test setup


The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz Emissions



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 1 GHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz emissions, whichever is lower.



## Limit

### FCC

According to section 15.209(a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency (MHz) | Field strength ( $\mu V/m$ ) | Measurement distance (m) |
|-----------------|------------------------------|--------------------------|
| 0.009 - 0.490   | 2 400/F(kHz)                 | 300                      |
| 0.490 - 1.705   | 24 000/F(kHz)                | 30                       |
| 1.705 - 30      | 30                           | 30                       |
| 30 - 88         | 100**                        | 3                        |
| 88 - 216        | 150**                        | 3                        |
| 216 - 960       | 200**                        | 3                        |
| Above 960       | 500                          | 3                        |

\*\*Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54–72 MHz, 76–88 MHz, 174–216 MHz or 470–806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., Section 15.231 and 15.241.

According to section 15.205(a) and (b), only spurious emissions are permitted in any of the frequency bands listed below:

| MHz                   | MHz                   | MHz               | GHz           |
|-----------------------|-----------------------|-------------------|---------------|
| 0.009 - 0.110         | 16.42 - 16.423        | 399.9 - 410       | 4.5 - 5.15    |
| 0.495 - 0.505         | 16.694 75 - 16.695 25 | 608 - 614         | 5.35 - 5.46   |
| 2.173 5 - 2.190 5     | 16.804 25 - 16.804 75 | 960 - 1 240       | 7.25 - 7.75   |
| 4.125 - 4.128         | 25.5 - 25.67          | 1 300 - 1 427     | 8.025 - 8.5   |
| 4.177 25 - 4.177 75   | 37.5 - 38.25          | 1 435 - 1 626.5   | 9.0 - 9.2     |
| 4.207 25 - 4.207 75   | 73 - 74.6             | 1 645.5 - 1 646.5 | 9.3 - 9.5     |
| 6.215 - 6.218         | 74.8 - 75.2           | 1 660 - 1 710     | 10.6 - 12.7   |
| 6.267 75 - 6.268 25   | 108 - 121.94          | 1 718.8 - 1 722.2 | 13.25 - 13.4  |
| 6.311 75 - 6.312 25   | 123 - 138             | 2 200 - 2 300     | 14.47 - 14.5  |
| 8.291 - 8.294         | 149.9 - 150.05        | 2 310 - 2 390     | 15.35 - 16.2  |
| 8.362 - 8.366         | 156.524 75 - 156.525  | 2 483.5 - 2 500   | 17.7 - 21.4   |
| 8.376 25 - 8.386 75   | 25                    | 2 690 - 2 900     | 22.01 - 23.12 |
| 8.414 25 - 8.414 75   | 156.7 - 156.9         | 3 260 - 3 267     | 23.6 - 24.0   |
| 12.29 - 12.293        | 162.012 5 - 167.17    | 3 332 - 3 339     | 31.2 - 31.8   |
| 12.519 75 - 12.520 25 | 167.72 - 173.2        | 3 345.8 - 3 358   | 36.43 - 36.5  |
| 12.576 75 - 12.577 25 | 240 - 285             | 3 600 - 4 400     | Above 38.6    |
| 13.36 - 13.41         | 322 - 335.4           |                   |               |

The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in section 15.209. At frequencies equal to or less than 1 000 MHz, compliance with the limits in section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1 000 MHz, compliance with the emission limits in section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in section 15.35 apply to these measurements.

**IC**

According to RSS-247(5.5), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

According to RSS-Gen(8.9), Except where otherwise indicated in the applicable RSS, radiated emissions shall comply with the field strength limits shown in table 5 and table 6. Additionally, the level of any transmitter unwanted emission shall not exceed the level of the transmitter's fundamental emission.

**Table 5- General field strength limits at frequencies above 30 MHz**

| Frequency(MHz) | Field strength<br>( $\mu\text{V/m}$ at 3 m) |
|----------------|---------------------------------------------|
| 30 to 88       | 100                                         |
| 88 to 216      | 150                                         |
| 216 to 960     | 200                                         |
| Above 960      | 500                                         |

**Table 6- General field strength limits at frequencies below 30 MHz**

| Frequency                 | Magnetic field strength (H-Field)<br>( $\mu\text{A/m}$ ) | Measurement<br>distance(m) |
|---------------------------|----------------------------------------------------------|----------------------------|
| 9 – 490 kHz <sup>1)</sup> | 6.37/F (F in kHz)                                        | 300                        |
| 490 – 1705 kHz            | 63.7/F (F in kHz)                                        | 30                         |
| 1.705 - 30 MHz            | 0.08                                                     | 30                         |

**Note 1:** The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

According to RSS-Gen(8.10), Restricted frequency bands, identified in table 7, are designated primarily for safety-of-life services (distress calling and certain aeronautical activities), certain satellite downlinks, radio astronomy and some government uses. Except where otherwise indicated, the following conditions related to the restricted frequency bands apply:

- The transmit frequency, including fundamental components of modulation, of licence-exempt radio apparatus shall not fall within the restricted frequency bands listed in table 7 except for apparatus compliant with RSS-287, Emergency Position Indicating Radio Beacons (EPIRB), Emergency Locator Transmitters (ELT), Personal Locator Beacons (PLB), and Maritime Survivor Locator Devices (MSLD).
- Unwanted emissions that fall into restricted frequency bands listed in table 7 shall comply with the limits specified in table 5 and table 6.
- Unwanted emissions that do not fall within the restricted frequency bands listed in table 7 shall comply either with the limits specified in the applicable RSS or with those specified in table 5 and table 6.

**Table 7- Restricted frequency bands\***

| MHz                 | MHz                   | GHz           |
|---------------------|-----------------------|---------------|
| 0.090 - 0.110       | 149.9 - 150.05        | 9.0 - 9.2     |
| 0.495 - 0.505       | 156.52475 - 156.52525 | 9.3 - 9.5     |
| 2.1735 - 2.1905     | 156.7 - 156.9         | 10.6 - 12.7   |
| 3.020 - 3.026       | 162.0125 - 167.17     | 13.25 - 13.4  |
| 4.125 - 4.128       | 167.72 - 173.2        | 14.47 - 14.5  |
| 4.17725 - 4.17775   | 240 - 285             | 15.35 - 16.2  |
| 4.20725 - 4.20775   | 322 - 335.4           | 17.7 - 21.4   |
| 5.677 - 5.683       | 399.9 - 410           | 22.01 - 23.12 |
| 6.215 - 6.218       | 608 - 614             | 23.6 - 24.0   |
| 6.26775 - 6.26825   | 960 - 1427            | 31.2 - 31.8   |
| 6.31175 - 6.31225   | 1435 - 1626.5         | 36.43 - 36.5  |
| 8.291 - 8.294       | 1645.5 - 1646.5       | Above 38.6    |
| 8.362 - 8.366       | 1660 - 1710           |               |
| 8.37625 - 8.38675   | 1718.8 - 1722.2       |               |
| 8.41425 - 8.41475   | 2200 - 2300           |               |
| 12.29 - 12.293      | 2310 - 2390           |               |
| 12.51975 - 12.52025 | 2483.5 - 2500         |               |
| 12.57675 - 12.57725 | 2655 - 2900           |               |
| 13.36 - 13.41       | 3260 - 3267           |               |
| 16.42 - 16.423      | 3332 - 3339           |               |
| 16.69475 - 16.69525 | 3345.8 - 3358         |               |
| 16.80425 - 16.80475 | 3500 - 4400           |               |
| 25.5 - 25.67        | 4500 - 5150           |               |
| 37.5 - 38.25        | 5350 - 5460           |               |
| 73 - 74.6           | 7250 - 7750           |               |
| 74.8 - 75.2         | 8025 - 8500           |               |
| 108 - 138           | --                    |               |

\* Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.



**Test procedure**

ANSI C63.10-2013

**Test settings****Peak field strength measurements**

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = as specified in table
3. VBW  $\geq$  (3 $\times$ RBW)
4. Detector = peak
5. Sweep time = auto
6. Trace mode = max hold
7. Allow sweeps to continue until the trace stabilizes

**Table. RBW as a function of frequency**

| Frequency           | RBW                |
|---------------------|--------------------|
| 9 kHz to 150 kHz    | 200 Hz to 300 Hz   |
| 0.15 MHz to 30 MHz  | 9 kHz to 10 kHz    |
| 30 MHz to 1 000 MHz | 100 kHz to 120 kHz |
| > 1 000 MHz         | 1 MHz              |

**Average field strength measurements****Trace averaging with continuous EUT transmission at full power**

If the EUT can be configured or modified to transmit continuously ( $D \geq 98\%$ ), then the average emission levels shall be measured using the following method (with EUT transmitting continuously):

1. RBW = 1 MHz (unless otherwise specified).
2. VBW  $\geq$  (3 $\times$ RBW).
3. Detector = RMS (power averaging), if  $[\text{span} / (\# \text{ of points in sweep})] \leq (\text{RBW} / 2)$ . Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
4. Averaging type = power (i.e., rms):
  - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
  - 2) Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.
5. Sweep time = auto.
6. Perform a trace average of at least 100 traces.

**Trace averaging across ON and OFF times of the EUT transmissions followed by duty cycle correction**

If continuous transmission of the EUT ( $D \geq 98\%$ ) cannot be achieved and the duty cycle is constant (duty cycle variations are less than  $\pm 2\%$ ), then the following procedure shall be used:

1. The EUT shall be configured to operate at the maximum achievable duty cycle.
2. Measure the duty cycle D of the transmitter output signal as described in 11.6.
3. RBW = 1 MHz (unless otherwise specified).
4. VBW  $\geq [3 \times \text{RBW}]$ .
5. Detector = RMS (power averaging), if  $[\text{span} / (\# \text{ of points in sweep})] \leq (\text{RBW} / 2)$ . Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.




6. Averaging type = power (i.e., rms):
  - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
  - 2) Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.
7. Sweep time = auto.
8. Perform a trace average of at least 100 traces.
9. A correction factor shall be added to the measurement results prior to comparing with the emission limit to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:
  - 1) If power averaging (rms) mode was used in step f), then the applicable correction factor is  $[10 \log (1 / D)]$ , where D is the duty cycle.
  - 2) If linear voltage averaging mode was used in step f), then the applicable correction factor is  $[20 \log (1 / D)]$ , where D is the duty cycle.
  - 3) If a specific emission is demonstrated to be continuous ( $D \geq 98\%$ ) rather than turning ON and OFF with the transmit cycle, then no duty cycle correction is required for that emission.

**Notes:**

1.  $f < 30$  MHz, extrapolation factor of 40 dB/decade of distance.  $F_d = 40 \log(D_m/D_s)$   
 $f \geq 30$  MHz, extrapolation factor of 20 dB/decade of distance.  $F_d = 20 \log(D_m/D_s)$   
Where:  
 $F_d$  = Distance factor in dB  
 $D_m$  = Measurement distance in meters  
 $D_s$  = Specification distance in meters
2. Factors(dB) = Antenna factor(dB/m) + Cable loss(dB) + or Amp. gain(dB) + or  $F_d$ (dB)
3. The worst-case emissions are reported however emissions whose levels were not within 20 dB of respective limits were not reported.
4. Average test would be performed if the peak result were greater than the average limit.
5. <sup>1)</sup> means restricted band.

**Test results (Below 30 MHz) –Worst case: 1 MBits/s(37 Bytes) Lowest frequency**


| Frequency                                                      | Pol.  | Reading  | Cable Loss | Amp Gain | Antenna Factor | DCF  | Result     | Limit      | Margin |
|----------------------------------------------------------------|-------|----------|------------|----------|----------------|------|------------|------------|--------|
| [MHz]                                                          | [V/H] | [dB(μV)] | [dB]       | [dB]     | [dB]           | [dB] | [dB(μV/m)] | [dB(μV/m)] | [dB]   |
| No spurious emissions were detected within 20 dB of the limit. |       |          |            |          |                |      |            |            |        |

**Horizontal/Vertical**

Note. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω. For example, the measurement frequency X KHz resulted in a level of Y dBuV/m, which is equivalent to  $Y-51.5 = Z$  dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to the 15.209(a) limit.


**Test results (Below 1 000 MHz) –Worst case: 1 Mbits/s(37 Bytes) Lowest frequency**




| Frequency              | Pol.  | Reading  | Antenna Factor | Amp. + Cable | DCF  | Result     | Limit      | Margin |
|------------------------|-------|----------|----------------|--------------|------|------------|------------|--------|
| (MHz)                  | (V/H) | (dB(μV)) | (dB)           | (dB)         | (dB) | (dB(μV/m)) | (dB(μV/m)) | (dB)   |
| <b>Quasi peak data</b> |       |          |                |              |      |            |            |        |
| 52.07                  | V     | 38.10    | 18.26          | -30.26       | -    | 26.10      | 40.00      | 13.90  |
| 117.06 <sup>1)</sup>   | V     | 29.40    | 16.73          | -29.13       | -    | 17.00      | 43.50      | 26.50  |
| 149.55                 | V     | 29.20    | 18.85          | -28.68       | -    | 19.37      | 43.50      | 24.13  |
| 333.37 <sup>1)</sup>   | V     | 23.90    | 20.03          | -26.54       | -    | 17.39      | 46.00      | 28.61  |
| 375.08 <sup>1)</sup>   | H     | 22.80    | 20.95          | -26.16       | -    | 17.59      | 46.00      | 28.41  |
| 562.65                 | V     | 24.30    | 24.95          | -24.49       | -    | 24.76      | 46.00      | 21.24  |

**Horizontal/Vertical**

**Test results (Above 1 000 MHz)\_1 Mbits/s(37 Bytes)****Low Channel**

| Frequency                                                      | Pol.  | Reading  | Antenna Factor | Amp. + Cable | DCF  | Result     | Limit      | Margin |
|----------------------------------------------------------------|-------|----------|----------------|--------------|------|------------|------------|--------|
| [MHz]                                                          | [V/H] | [dB(μV)] | [dB]           | [dB]         | [dB] | [dB(μV/m)] | [dB(μV/m)] | [dB]   |
| <b>Peak data</b>                                               |       |          |                |              |      |            |            |        |
| 1 803.52                                                       | V     | 74.21    | 29.88          | -49.59       | -    | 54.50      | 74.00      | 19.50  |
| 2 378.03 <sup>1)</sup>                                         | H     | 41.33    | 31.86          | -29.10       | -    | 44.09      | 74.00      | 29.91  |
| 4 200.08 <sup>1)</sup>                                         | V     | 67.28    | 33.32          | -54.71       | -    | 45.89      | 74.00      | 28.11  |
| 4 803.64 <sup>1)</sup>                                         | H     | 62.69    | 33.92          | -53.00       | -    | 43.61      | 74.00      | 30.39  |
| 7 206.56                                                       | V     | 62.99    | 35.40          | -53.08       | -    | 45.31      | 74.00      | 28.69  |
| <b>Average Data</b>                                            |       |          |                |              |      |            |            |        |
| No spurious emissions were detected within 20 dB of the limit. |       |          |                |              |      |            |            |        |




**Horizontal/Vertical for Band-edge**

**Horizontal/Vertical for 1 GHz ~ 3.5 GHz****Horizontal/Vertical for 3.5 GHz ~ 18 GHz****Horizontal/Vertical for 18 GHz ~ 26.5 GHz**

### Middle Channel

| Frequency                                                      | Pol.  | Reading  | Antenna Factor | Amp. + Cable | DCF  | Result     | Limit      | Margin |
|----------------------------------------------------------------|-------|----------|----------------|--------------|------|------------|------------|--------|
| [MHz]                                                          | [V/H] | [dB(μV)] | [dB]           | [dB]         | [dB] | [dB(μV/m)] | [dB(μV/m)] | [dB]   |
| <b>Peak data</b>                                               |       |          |                |              |      |            |            |        |
| 1 799.92                                                       | V     | 73.35    | 29.86          | -49.58       | -    | 53.63      | 74.00      | 20.37  |
| 4 200.08 <sup>1)</sup>                                         | H     | 66.55    | 33.32          | -54.71       | -    | 45.16      | 74.00      | 28.84  |
| 4 852.58 <sup>1)</sup>                                         | H     | 64.08    | 33.94          | -54.39       | -    | 43.63      | 74.00      | 30.37  |
| 7 321.20 <sup>1)</sup>                                         | H     | 62.25    | 35.40          | -52.65       | -    | 45.00      | 74.00      | 29.00  |
| <b>Average Data</b>                                            |       |          |                |              |      |            |            |        |
| No spurious emissions were detected within 20 dB of the limit. |       |          |                |              |      |            |            |        |







**Horizontal/Vertical for 1 GHz ~ 3.5 GHz****Horizontal/Vertical for 3.5 GHz ~ 18 GHz****Horizontal/Vertical for 18 GHz ~ 26.5 GHz**



**High Channel**


| Frequency                                                      | Pol.  | Reading  | Antenna Factor | Amp. + Cable | DCF  | Result     | Limit      | Margin |
|----------------------------------------------------------------|-------|----------|----------------|--------------|------|------------|------------|--------|
| [MHz]                                                          | [V/H] | [dB(μV)] | [dB]           | [dB]         | [dB] | [dB(μV/m)] | [dB(μV/m)] | [dB]   |
| <b>Peak data</b>                                               |       |          |                |              |      |            |            |        |
| 1 809.69                                                       | H     | 73.35    | 29.92          | -49.61       | -    | 53.66      | 74.00      | 20.34  |
| 2 484.53 <sup>1)</sup>                                         | H     | 39.80    | 32.07          | -29.22       | -    | 42.65      | 74.00      | 31.35  |
| 4 199.63 <sup>1)</sup>                                         | H     | 66.95    | 33.32          | -54.72       | -    | 45.55      | 74.00      | 28.45  |
| 4 971.75 <sup>1)</sup>                                         | V     | 62.96    | 33.99          | -54.45       | -    | 42.50      | 74.00      | 31.50  |
| 7 439.92 <sup>1)</sup>                                         | H     | 63.96    | 35.40          | -52.20       | -    | 47.16      | 74.00      | 26.84  |
| <b>Average Data</b>                                            |       |          |                |              |      |            |            |        |
| No spurious emissions were detected within 20 dB of the limit. |       |          |                |              |      |            |            |        |

**Horizontal/Vertical for Band-edge**

**Horizontal/Vertical for 1 GHz ~ 3.5 GHz****Horizontal/Vertical for 3.5 GHz ~ 18 GHz****Horizontal/Vertical for 18 GHz ~ 26.5 GHz**

## 7.5. Conducted Spurious Emission

### Test setup



### Limit

According to §15.247(d) and RSS-247(5.5), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operation, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation specified in §15.209(a) is not required. In addition, radiated emission limits specified in §15.209(a) (see §15.205(c)).

Limit : 20 dBc

### Test procedure

ANSI C63.10-2013 - Section 11.11.3

KDB 558074 D01 v05 - Section 8.5



KDB 662911 D01 v02r01 – section (E)(3)(b)

### Test settings



Establish an emission level by using the following procedure:

- 1) Set the center frequency and span to encompass frequency range to be measured.
- 2) Set the RBW = 100 kHz
- 3) Set the VBW  $\geq$  [3 x RBW]
- 4) Detector = peak
- 5) Sweep time = auto couple
- 6) Trace mode = max hold
- 7) Allow trace to fully stabilize.
- 8) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

**Test results****BLE\_1 MBit/s(37 Bytes)****Conducted band-edge / Low ch.****Conducted spurious / Low ch.****Conducted band-edge / Mid ch.**

Blank

**Conducted spurious / Mid ch.****Conducted band-edge / High ch.****Conducted spurious / High ch.**

## 8. Measurement equipment

| Equipment Name           | Manufacturer    | Model No.              | Serial No.  | Next Cal. Date |
|--------------------------|-----------------|------------------------|-------------|----------------|
| Vector Signal Generator  | R&S             | SMBV100A               | 257566      | 21.07.13       |
| Signal Generator         | R&S             | SMB100A                | 176206      | 21.01.21       |
| Spectrum Analyzer        | R&S             | FSW50                  | 101013      | 21.07.13       |
| DC Power Supply          | AGILENT         | E3632A                 | MY40008800  | 21.07.28       |
| EMI TEST RECIEVER        | R&S             | ESCI7                  | 100732      | 21.03.04       |
| Bilog Antenna            | Teseq GmbH      | CBL6112D               | 37876       | 22.09.02       |
| Loop Antenna             | R&S             | HFH2-Z2                | 100355      | 22.08.21       |
| Attenuator               | AGILENT         | 8491B-006              | MY37270292  | 22.09.02       |
| Amplifier                | SONOMA          | 310N                   | 284608      | 21.08.20       |
| Antenna Mast             | Innco Systems   | MA4000-EP              | 303         | N/A            |
| Turn Table               | Innco Systems   | DT2000                 | 79          | N/A            |
| Spectrum Analyzer        | R&S             | FSW26                  | 101353      | 21.04.01       |
| COAXIAL FIXED ATTENUATOR | Agilent         | 8491B-003              | 2708A18758  | 21.04.23       |
| Horn antenna             | ETS.lindgren    | 3117                   | 155787      | 20.10.24       |
| Horn antenna             | ETS.lindgren    | 3116                   | 86632       | 21.02.17       |
| Attenuator               | API Inmet       | 40AH2W-10              | 13          | 21.05.12       |
| Broadband PreAmplifier   | SCHWARZBECK     | BBV9718                | 216         | 21.07.28       |
| AMPLIFIER                | L-3 Narda-MITEQ | AMF-7D-01001800-22-10P | 2031196     | 21.02.12       |
| AMPLIFIER                | L-3 Narda-MITEQ | JS44-18004000-33-8P    | 2000996     | 21.01.22       |
| Highpass Filter          | WT              | WT-A1698-HS            | WT160411001 | 21.05.11       |
| Cable Assembly           | RadiAll         | 2301761768000PJ        | 1724.659    | -              |
| Cable Assembly           | gigalane        | RG-400                 | -           | -              |
| Cable Assembly           | HUER+SUHNER     | SUCOFLEX 104           | MY4342/4    | -              |
| Antenna Mast             | Innco Systems   | MA4640-XP-ET           | -           | -              |
| Turn Table               | Innco Systems   | DT2000                 | 79          | -              |

**End of test report**