



SK TECH CO., LTD.

Page 1 of 14

FCC-Certificate of Compliance

Test Report No.:	SKTFCE-070517-059		
NVLAP CODE :	200220-0		
Applicant:	NAVIasis Co., Ltd.		
Applicant Address:	Teletron BD, 1459-2, Kwanyang-Dong, Dong-An Gu, Anyang-si, Kyungki-Do, Korea		
Manufacturer :	NAVIasis Co., Ltd.		
Manufacturer Address:	Teletron BD, 1459-2, Kwanyang-Dong, Dong-An Gu, Anyang-si, Kyungki-Do, Korea		
Product:	Tablet Mouse		
FCC ID:	TLXNVS-838	Model No.:	NVS-838
Buyer Model/ Multi Model No.:	NVS838XLN, NVS838XLY, NVS838XMY, NVS838XMN, NVS838XSY, NVS838XSA		
Receipt No.:	SKTEU07-0318	Date of receipt:	Apr. 13, 2007
Date of Issue:	May. 17, 2007		
Testing location:	SK TECH CO., LTD. 820-2, Wolmoon-Ri, Wabu-Up, Namyangju-Si, Kyunggi-Do, Korea		
Test Standards:	ANSI C63.4 / 2003		
Rule Parts:	FCC part 15 Subpart B, CISPR 22		
Equipment Class :	Class B Digital Device Peripheral		
Other Aspects :	This Class B Digital apparatus complies with Canadian IECS-003		
Test Result:	The above mentioned product has been tested and passed.		

Prepared by: S.Y.Ye

Tested by: S.H.Yoon/Engineer

Approved by: D.H.Kang
/Manager & Chief Engineer

Signature	Date	Signature	Date	Signature	Date
Other Aspects :					
Abbreviations :					· OK, Pass = passed · Fail = failed · N/A = not applicable

• This test report is not permitted to copy partly without our permission.

☞ • This test result is dependent on only equipment to be used.

• This test result is based on a single evaluation of one sample of the above mentioned.

• This test report must not be used by the client to claim product endorsement by NVLAP or any agency of the U.S Government.

• We certify that this test report has been based on the measurement standards that is traceable to the national or International standards.

• This test report is the accredited testing items by Korea Laboratory Accreditation Scheme, which signed the ILAC-MRA.

NVLAP Lab. Code: 200220-0



» » Contents « «

Contents	2
List of Tables	2
List of Figures	2
1. General	3
2. Test Site	3
2.1 Location	3
2.2 List of Test and Measurement Instruments	4
2.3 Test Date	4
2.4 Test Environment	4
3. Description of the tested samples	5
3.1 Rating and Physical Characteristics	5
3.2 Submitted Documents	5
4. Measurement Conditions	6
4.1 Modes of Operation	6
4.2 List of Peripherals	6
4.3 Type of Used cables	6
4.4 Test Setup	7
4.5 Uncertainty	8
5. EMISSION Test	9
5.1 Conducted Emissions	9
5.2 Radiated Emissions	13

» List of Tables

Table 1	List of test and measurement Equipment	4
Table 2	Test Data, Conducted Disturbance	10
Table 3	Test Data, Radiated Emissions	14

» List of Figures

Figure 1	Spectral Diagram, LINE-PE	11
Figure 2	Spectral Diagram, NEUTRAL-PE	12



1. General

This equipment has been shown to be capable of compliance with the applicable technical standards and was tested in accordance with the measurement procedures as indicated in this report.

We attest to the accuracy of data. All measurements reported herein were performed by SK TECH Co., Ltd. and were made under Chief Engineer's supervision.

We assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

2. Test Site

SK TECH Co., Ltd.



2.1 Location

820-2, Wolmoon Ri, Wabu-Up, Namyangju-Si, Kyunggi-Do, Korea

The test site is in compliance with ISO/IEC 17025 for general requirements for the competence of testing and calibration laboratories. This laboratory is recognized as a Conformity Assessment Body(CAB) for CAB's Designation Number: **KR0007** by FCC, is accredited by NVLAP for NVLAP Lab. Code : **200220-0** and DATech for DAR-Registration No.**DAT-P-076/97-01** and KOLAS for Accreditation No.:**KT191**.



2.2 List of Test and Measurement Instruments

Table 1 : List of Test and Measurement Equipment

- Conducted Disturbance

Kind of Equipment	Type	S/N	Calibrated until
EMI Receiver	ESHS10	862970/019	09.2007
Artificial Mains Network	ESH2-Z5	834549/011	07.2007

- Radiated Disturbance

Kind of Equipment	Type	S/N	Calibrated until
EMI Receiver	ESVS10	834468/008	09.2007
Amplifier	8447F	3113A05153	07.2007
Trilog-Broadband Antenna	VULB9168	9168-230	07.2007
Antenna Turntable Driver	5907	91X518	N/A
Antenna Turntable controller	5906	91X519	N/A
Spectrum Analyzer	R3361A	11730187	09.2007

2.3 Test Date

Date of Application : Apr. 13, 2007

Date of Test : May. 03, 2007 ~ May. 09, 2007

2.4 Test Environment

See each test item's description.



3. Description of the tested samples

The EUT is a Tablet Mouse.

The basic model name is NVS-838, and the others(NVS838XLN, NVS838XLY, NVS838XMY, NVS838XMN, NVS838XSY, NVS838XSA)are multi listing model name.

The difference of basic M/N and multi listing M/N

-Station: The color of appearance

-Pen Mouse: wire or wireless

-Cradle: with Cradle or without Cradle

3.1 Rating and Physical Characteristics

Specification	
Operating Area	:A4, A5, A6, 14.3", 10.1", 7.1
RAM	:128MB RAM or more
Resolution	:400 DPI
Power	:Station USB Port(5V), Wireles pen 1.5V cell battery x 3EA-Optional Model, Wired pen USB Port (5V)
Software	:"NAVIboard 2.0" MS Office Annotator"
Interface	:USB port, CD-ROM drive
Dimensions	:Station W43 x L140 x H22mm/ 64g, Pen W13 x L150mm/ 13g

3.2 Submitted Documents

N/A



4. Measurement Conditions

Operating voltage of the EUT is supplied from AC Line.

The rating is AC 120V/ 60Hz at input.

4.1 Modes of Operation

The EUT was connected to PC with USB.

The Mouse cursor was observed during test.

4.2 List of Peripherals

Equipment	Manufacturer	Model Name	Serial No.
Keyboard (PS/2)	YET FOUNDATE LTD.	SK-1688	C0509035926
LCD Monitor	TOP VICTORY ELECTRONICS(FUJIAN) CO., LTD.	ELM-728	2925CJA021461
Adaptor (For LCD Monitor)	TPV Electronics Co., Ltd.	ADPC12416BB	12416BG54737993
PC	Samsung Electronics	ZMP35	X71498DX900234E


4.3 Type of Used Cables

#	START		END		Cable	
	Name	I/O Port	Name	Name	Length	Shielded
1	EUT	USB (Pen Mouse)	PC		1.0	Unshielded
2	EUT	USB(Station)	PC		1.1	Shielded
3	PC	VGA	LCD Monitor		1.6	Shielded
4	PC	PS/2	Keyboard		1.4	Shielded
5	PC	AC Line	AC Line		1.5	Unshielded
6	LCD Monitor	AC Line	AC Line		1.4	Unshielded



4.4 Test Setup

The test setup photographs showed the external supply connections and interfaces.



[System Block Diagram of Test Configuration]



4.5 Uncertainty

1) Radiated disturbances from 30 MHz to 1000 MHz at a distance of 3m and 10 m

Expanded Uncertainty

$$U = k * U_c(x_i) = 2 * 2.3 = 4.60\text{dB}$$

The coverage factor $k = 2$ yields approximately a 95% level of confidence.

2) Conducted disturbance from 150 KHz to 30 MHz using a $50 \Omega/50 \mu\text{H}$ AMN

Expanded uncertainty

$$U = k * U_c(x_i) = 2 * 1.96 = 3.92\text{dB}$$

The coverage factor $k = 2$ yields approximately a 95% level of confidence.

※ When the measured emission is positioned within the range of the uncertainty of measurement from the emission limit, the uncertainty of measurement shall be concerned as follow.

Compliance or non-compliance with a disturbance limit shall be determined in the following manner.

If U_{lab} is less than or equal to U_{cisp}

- compliance is deemed to occur if no measured disturbance exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance exceeds the disturbance limit.

If U_{lab} is greater than U_{cisp}

- compliance is deemed to occur if no measured disturbance, increased by $(U_{\text{lab}} - U_{\text{cisp}})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance, increased by $(U_{\text{lab}} - U_{\text{cisp}})$, exceeds the disturbance limit.

※ If the measurement value is lower or equal to the limit, the EUT is considered to pass the test.



5. EMISSION Test

5.1 Conducted Emissions

Result: **PASS**

The line-conducted facility is located inside a 2.6M x 3.6M x 7.0M shielded enclosure.

The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 604-05. A 1 m x 1.5 m wooden table 80 cm high is placed 40 cm. away from the vertical wall and 1.5 m away from the side wall of the shielded room. ROHDE & SCHWARZ Model ESH3-Z5 (10 kHz-30 MHz) 50 ohm/50 uH Line-Impedance Stabilization Networks(LISNs) are bonded to the shielded room.

The EUT is powered from the ROHDE & SCHWARZ LISN and the support equipment is powered from the ROHDE & SCHWARZ LISN. Power to the LISNs are filtered by a high-current high-insertion loss Lindgren enclosures power line filters (100dB 14 kHz-10 GHz).

The purpose of the filter is to attenuate ambient signal interference and this filter is also bonded to the shielded enclosure.

All electrical cables are shielded by braided tinned copper zipper tubing with inner diameter of 1/2". If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply lines will be connected to the ROHDE & SCHWARZ LISN.

All interconnecting cables more than 1 meter were shortened by non-inductive bundling (serpentine fashion) to a 1-meter length.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer to determine the frequency producing the maximum EME from the EUT.

The spectrum was scanned from 150 kHz to 30 MHz with 100msec. sweep time.

The frequency producing the maximum level was reexamined using EMI/field Intensity Meter (ESHS 10) and Quasi-Peak adapter. The detector function was set to CISPR quasi-peak mode.

The bandwidth of the receiver was set to 10 kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each EME emission.

Each emission was maximized by: switching power lines; varying the mode of operation or resolution;clock or data exchange speed; if applicable; whichever determined the worst-case emission.

Photographs of the worst-case emission can be seen in photograph of conducted test.

Each EME reported was calibrated using self-calibrating mode.

**Table 2: Test Data, Conducted Disturbance****<Quasi-Peak>**

Frequency (MHz)	Reading (dBuV)	Line	C/F (dB)	C/L (dB)	Actual (dBuV)	Limit (dBuV)	Margin (dB)
0.350	47.61	N	0.13	0.02	47.76	58.96	11.20
0.520	42.70	N	0.15	0.05	42.90	56.00	13.10
1.075	44.00	N	0.17	0.07	44.24	56.00	11.76
1.770	42.96	N	0.17	0.07	43.20	56.00	12.80
3.055	43.23	L	0.18	0.10	43.51	56.00	12.49
3.065	42.60	N	0.21	0.10	42.91	56.00	13.09

<Average>

Frequency (MHz)	Reading (dBuV)	Line	C/F (dB)	C/L (dB)	Actual (dBuV)	Limit (dBuV)	Margin (dB)
0.350	43.67	N	0.13	0.02	43.82	48.96	5.14
1.075	37.84	N	0.17	0.07	38.08	46.00	7.92
1.770	36.70	N	0.17	0.07	36.94	46.00	9.06
2.515	36.43	N	0.21	0.10	36.74	46.00	9.26
3.055	38.03	L	0.18	0.10	38.31	46.00	7.69
3.065	37.88	N	0.21	0.10	38.19	46.00	7.81

► NOTE

- * **C/F = Correction Factor**
- * **C/L = Cable Loss**
- * **LINE : L = Line-PE, N = Neutral-PE**
- * **Margin Calculation**

$$\text{Margin(Q.P)} = \text{Limit} - \text{Actual}$$

$$[\text{Actual(Q.P)} = \text{Reading(Q.P)} + \text{C/F} + \text{C/L}]$$



SK TECH CO., LTD.

Page 11 of 14

Figure 1: Spectral Diagram, LINE – PE

SK TECH Co., Ltd.
CONDUCTED DISTURBANCE

09 May 2007 14:00

EUT: NVS-838
Manuf:
Op Cond:
Operator:
Test Spec: FCC Part15 Subpart B
Comment: LINE-PE

Result File: NVS-838_L.dat : NVS-838


Scan Settings

(1 Range)

Frequencies

Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge
150kHz	30MHz	5kHz	10kHz	PK+AV	20msec	Auto	OFF	60dB

Final Measurement: Detectors: X QP / + AV
Meas Time: 1sec
Peaks: 8
Acc Margin: 35 dB





SK TECH CO., LTD.

Page 12 of 14

Figure 2: Spectral Diagram, NEUTRAL – PE

SK TECH Co., Ltd.
CONDUCTED DISTURBANCE

09 May 2007 13:42

EUT: NVS-838
Manuf:
Op Cond:
Operator:
Test Spec: FCC Part15 Subpart B
Comment: NEUTRAL-PE


Result File: NVS-838_N.dat : NVS-838

Scan Settings

(1 Range)

Frequencies			Receiver Settings					
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge
150kHz	30MHz	5kHz	10kHz	PK+AV	20msec	Auto	OFF	60dB

Final Measurement: Detectors: X QP / + AV
Meas Time: 1sec
Peaks: 8
Acc Margin: 35 dB





5.2 Radiated Emissions

Result :**PASS**

Preliminary measurements were made indoors at 3 meter using broadband antennas, broadband amplifier, and spectrum analyzer to determine the frequency producing the maximum EME.

Appropriate precaution was taken to ensure that all EME from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, turntable azimuth with respect to the antenna were noted for each frequency found.

The spectrum was scanned from 30 to 300 MHz using biconical antenna and from 300 to 1000 MHz using log-periodic antenna. Above 1 GHz, linearly polarized double ridge horn antennas were used.

Final measurements were made outdoors at 3-meter test range using SCHWARZBECK dipole antennas.

The test equipment was placed on a wooden table situated on a 4x4 meter area adjacent to the measurement area. Turntable was to protect from weather in the dome that made with FRP.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. Each frequency found during pre-scan measurements was re-examined and investigated using EMI/Field Intensity Meter(ESVS 10) and Quasi-Peak Adapter.

The detector function was set to CISPR quasi-peak mode and the bandwidth of the receiver was set to 100 kHz or 1 MHz depending on the frequency or type of signal.

The half-wave dipole antenna was tuned to the frequency found during preliminary radiated measurements. The EUT, support equipment and interconnecting cables were re-configured to the set-up producing the maximum emission for the frequency and were placed on top of a 0.8-meter high non-metallic 1 x 1.5 meter table.

The EUT, support equipment, and interconnecting cables were re-arranged and manipulated to maximize each EME emission. The turntable containing the system was rotated; the antenna height was varied 1 to 4 meters and stopped at the azimuth or height producing the maximum emission.

Each emission was maximized by: varying the mode of operation or resolution; clock or data exchange speed, and/or support equipment, if applicable; and changing the polarity of the antenna, whichever determined the worst-case emission.

Photographs of the worst-case emission can be seen in photograph of radiated emission test.

Each EME reported was calibrated using self-calibrating mode.



Table 3 : Test Data, Radiated Emissions

Frequency [MHz]	Pol.	Height [m]	Real Reading	Correction Factor		T-Fact [dB]	Data [dBuV/m]	Limits [dBuV/m]	Margin [dB]
				Antenna	Cable				
240.02	H	1.0	20.9	9.3	1.3	10.6	31.5	46.0	14.5
384.02	H	1.0	17.2	14.1	1.8	15.9	33.1	46.0	12.9
696.31	V	1.3	10.3	20.2	2.5	22.7	33.0	46.0	13.0
720.04	H	1.1	10.7	20.5	3.1	23.6	34.3	46.0	11.7
888.07	H	1.2	10.2	22.9	2.9	25.8	36.0	46.0	10.0
960.24	H	1.5	15.9	24.1	3.1	27.2	43.1	54.0	10.9

Table. Radiated Measurements at 3-meters

NOTES:

1. All modes of operation were investigated and the worst-case emission are reported.
2. All other emission are non-significant.
3. All readings are calibrated by self-mode in receiver.
4. Measurements using CISPR Quasi-Peak mode.
5. H = Horizontal, V = Vertical Polarization
6. Data = Real Reading + T - Fact(Antenna+Cable)
7. Margin = Limits – Data