

FCC TEST REPORT

REPORT NO.: RF990924C13

MODEL NO.: AW-NU153H

FCC ID: TLZ-NU153H

RECEIVED: Sep. 24, 2010

TESTED: Sep. 27 ~ Oct. 26, 2010

ISSUED: Oct. 28, 2010

APPLICANT: AzureWave Technologies, Inc.

ADDRESS: 8F, No. 94, Baozhong Rd., Xindian, Taipei,
Taiwan 231.

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou
Hsiang, Taipei Hsien 244, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan,
R.O.C.

This test report consists of 108 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product, certification, approval or endorsement by TAF or any government agency. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.



TABLE OF CONTENTS

1.	CERTIFICATION	4
2.	SUMMARY OF TEST RESULTS	5
2.1	MEASUREMENT UNCERTAINTY	5
3.	GENERAL INFORMATION	6
3.1	GENERAL DESCRIPTION OF EUT	6
3.2	DESCRIPTION OF TEST MODES	7
3.2.1	CONFIGURATION OF SYSTEM UNDER TEST	8
3.2.2	TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	9
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS	13
3.4	DESCRIPTION OF SUPPORT UNITS	13
4.	TEST TYPES AND RESULTS	14
4.1	RADIATED EMISSION MEASUREMENT	14
4.1.1	LIMITS OF RADIATED EMISSION MEASUREMENT	14
4.1.2	TEST INSTRUMENTS	15
4.1.3	TEST PROCEDURES	16
4.1.4	DEVIATION FROM TEST STANDARD	16
4.1.5	TEST SETUP	17
4.1.6	EUT OPERATING CONDITIONS	17
4.1.7	TEST RESULTS	18
4.2	CONDUCTED EMISSION MEASUREMENT	57
4.2.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	57
4.2.2	TEST INSTRUMENTS	57
4.2.3	TEST PROCEDURES	58
4.2.4	DEVIATION FROM TEST STANDARD	58
4.2.5	TEST SETUP	59
4.2.6	EUT OPERATING CONDITIONS	59
4.2.7	TEST RESULTS	60
4.3	6dB BANDWIDTH MEASUREMENT	66
4.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT	66
4.3.2	TEST INSTRUMENTS	66
4.3.3	TEST PROCEDURE	66
4.3.4	DEVIATION FROM TEST STANDARD	66
4.3.5	TEST SETUP	67
4.3.6	EUT OPERATING CONDITIONS	67
4.3.7	TEST RESULTS	68
4.4	MAXIMUM OUTPUT POWER	72
4.4.1	LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT	72
4.4.2	INSTRUMENTS	72
4.4.3	TEST PROCEDURES	72



A D T

4.4.4	DEVIATION FROM TEST STANDARD	72
4.4.5	TEST SETUP.....	73
4.4.6	EUT OPERATING CONDITIONS	73
4.4.7	TEST RESULTS	74
4.5	POWER SPECTRAL DENSITY MEASUREMENT.....	75
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	75
4.5.2	TEST INSTRUMENTS.....	75
4.5.3	TEST PROCEDURE.....	75
4.5.4	DEVIATION FROM TEST STANDARD	75
4.5.5	TEST SETUP.....	76
4.5.6	EUT OPERATING CONDITION	76
4.5.7	TEST RESULTS	77
4.6	BAND EDGES MEASUREMENT	81
4.6.1	LIMITS OF BAND EDGES MEASUREMENT.....	81
4.6.2	TEST INSTRUMENTS.....	81
4.6.3	TEST PROCEDURE.....	81
4.6.4	DEVIATION FROM TEST STANDARD	81
4.6.5	EUT OPERATING CONDITION	81
4.6.6	TEST RESULTS	82
5.	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	106
6.	INFORMATION ON THE TESTING LABORATORIES	107
7.	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB.....	108

1. CERTIFICATION

PRODUCT: IEEE 802.11b/g/n USB Half-Mini-Card Wireless Module

MODEL: AW-NU153H

BRAND: AzureWave

APPLICANT: AzureWave Technologies, Inc.

TESTED: Sep. 27 ~ Oct. 26, 2010

TEST SAMPLE: ENGINEERING SAMPLE

STANDARDS: FCC Part 15, Subpart C (Section 15.247)
ANSI C63.4-2003

The above equipment (model: AW-NU153H) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Ivy Lin , **DATE:** Oct. 28, 2010
Ivy Lin / Specialist

TECHNICAL ACCEPTANCE : Long Chen , **DATE:** Oct. 28, 2010
Responsible for RF Long Chen / Senior Engineer

APPROVED BY : Gary Chang , **DATE:** Oct. 28, 2010
Gary Chang / Assistant Manager

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
Standard Section	Test Type and Limit	Result	Remark
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -6.73dB at 0.310MHz.
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit.
15.247(b)	Maximum Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit.
15.247(d)	Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit. Minimum passing margin is -1.0dB at 2483.50 & 2390.0MHz.
15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit.
15.247(d)	Band Edge Measurement Limit: 20dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	Antenna connector is Hirose U.FL-R-SMT not a standard connector.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	150kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	3.34 dB
	200MHz ~1000MHz	3.35 dB
	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	IEEE 802.11b/g/n USB Half-Mini-Card Wireless Module
MODEL NO.	AW-NU153H
FCC ID	TLZ-NU153H
POWER SUPPLY	3.3Vdc
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
MODULATION TECHNOLOGY	DSSS, OFDM
TRANSFER RATE	802.11b: 11.0/ 5.5/ 2.0/ 1.0Mbps 802.11g: 54.0/ 48.0/ 36.0/ 24.0/ 18.0/ 12.0/ 9.0/ 6.0Mbps 802.11n: up to 135Mbps
OPERATING FREQUENCY	2412MHz ~ 2462MHz
NUMBER OF CHANNEL	11 for 802.11b, 802.11g, 802.11n (20MHz) 7 for 802.11n (40MHz)
OUTPUT POWER	169.8mW
ANTENNA TYPE	Refer to NOTE for more details
ANTENNA CONNECTOR	Hirose U.FL-R-SMT
DATA CABLE	NA
I/O PORTS	NA
ACCESSORY DEVICES	NA

NOTE:

- The EUT provides one completed transmitter and two receivers or one receiver.

MODULATION MODE	TX FUNCTION
802.11b	1TX
802.11g	1TX
802.11n (20MHz)	1TX
802.11n (40MHz)	1TX

- The antenna connector of EUT has two kinds of designs:
 - Two antenna connectors, 1TX & 2RX, RX with diversity function.
 - One antenna connector, 1TX & 1RX, RX without diversity function and without RLC component for RX path 2 BALUN & METCING.

Difference between these two designs is only non transmitter portions.
Transmitter portions are identical to each other.

*After pre-testing, "two antenna connectors" is the worst case and for final test.

- The EUT uses with following antennas:

ANTENNA	BRAND	MODEL NO.	TYPE	GAIN (dBi)	CONNECTOR
1	Cortec	AN2400-5776RS	Dipole	2.86	Hirose U.FL-R-SMT
2	ACON	ADP6P-700003	PCB	2.14	Hirose U.FL-R-SMT
3	ACON	APM8P-700015	PIFA	2.00	Hirose U.FL-R-SMT
4	MAG.LAYERS	MSA-4008-25GC1-A1	PIFA	2.98	Hirose U.FL-R-SMT

- The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided for 802.11b, 802.11g and 802.11n (20MHz):


CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

Seven channels are provided for 802.11n (40MHz):


CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2422MHz	5	2442MHz
2	2427MHz	6	2447MHz
3	2432MHz	7	2452MHz
4	2437MHz		

3.2.1 CONFIGURATION OF SYSTEM UNDER TEST

TEST MODE A



TEST MODE B, C



3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE	APPLICABLE TO				DESCRIPTION
MODE	RE $\geq$ 1G	RE<1G	PLC	APCM	ANTENNA TYPE
A	√	√	√	√	Antenna 1 type: Dipole
B	√	√	√	-	Antenna 2 type: PCB
C	√	√	√	-	Antenna 4 type: PIFA

Where **PLC**: Power Line Conducted Emission

RE<1G: Radiated Emission below 1GHz

RE $\geq$ 1G: Radiated Emission above 1GHz

APCM: Antenna Port Conducted Measurement

NOTE: "-": Means no effect.

RADIATED EMISSION TEST (ABOVE 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	ANT. AXIS
A	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0	-
	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0	-
	802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	6.5	-
	802.11n (40MHz)	1 to 7	1, 4, 7	OFDM	BPSK	13.5	-
B	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0	Z
	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0	Z
	802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	6.5	Z
	802.11n (40MHz)	1 to 7	1, 4, 7	OFDM	BPSK	13.5	Z
C	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0	Y
	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0	Y
	802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	6.5	Y
	802.11n (40MHz)	1 to 7	1, 4, 7	OFDM	BPSK	13.5	Y

RADIATED EMISSION TEST (BELOW 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	ANT. AXIS
A	802.11g	1 to 11	11	OFDM	BPSK	6.0	-
B	802.11g	1 to 11	11	OFDM	BPSK	6.0	Z
C	802.11g	1 to 11	11	OFDM	BPSK	6.0	Y

POWER LINE CONDUCTED EMISSION TEST:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A, B, C	802.11g	1 to 11	11	OFDM	BPSK	6.0

BANDEDGE MEASUREMENT:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	ANT. AXIS
A	802.11b	1 to 11	1, 11	DSSS	DBPSK	1.0	-
	802.11g	1 to 11	1, 11	OFDM	BPSK	6.0	-
	802.11n (20MHz)	1 to 11	1, 11	OFDM	BPSK	6.5	-
	802.11n (40MHz)	1 to 7	1, 7	OFDM	BPSK	13.5	-
B	802.11b	1 to 11	1, 11	DSSS	DBPSK	1.0	Z
	802.11g	1 to 11	1, 11	OFDM	BPSK	6.0	Z
	802.11n (20MHz)	1 to 11	1, 11	OFDM	BPSK	6.5	Z
	802.11n (40MHz)	1 to 7	1, 7	OFDM	BPSK	13.5	Z
C	802.11b	1 to 11	1, 11	DSSS	DBPSK	1.0	Y
	802.11g	1 to 11	1, 11	OFDM	BPSK	6.0	Y
	802.11n (20MHz)	1 to 11	1, 11	OFDM	BPSK	6.5	Y
	802.11n (40MHz)	1 to 7	1, 7	OFDM	BPSK	13.5	Y

ANTENNA PORT CONDUCTED MEASUREMENT:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
A	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
A	802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
A	802.11n (40MHz)	1 to 7	1, 4, 7	OFDM	BPSK	13.5

TEST CONDITION:

APPLICABLE TO	TEST MODE	ENVIRONMENTAL CONDITIONS	INPUT POWER (SYSTEM)	TESTED BY
RE $\geq$ 1G	A	26deg. C, 65%RH, 1011 hPa	120Vac, 60Hz	Long Chen
	B	25deg. C, 65%RH, 1014 hPa	120Vac, 60Hz	Brad Wu
	C	25deg. C, 65%RH, 1001 hPa	120Vac, 60Hz	Frank Wang
RE<1G	A	26deg. C, 65%RH, 1011 hPa	120Vac, 60Hz	Long Chen
	B	25deg. C, 65%RH, 1014 hPa	120Vac, 60Hz	Long Chen
	C	26deg. C, 65%RH, 1005 hPa	120Vac, 60Hz	Long Chen
PLC	A, B	28deg. C, 68%RH, 1010 hPa	120Vac, 60Hz	Sun Lin
	C	25deg. C, 65%RH, 999 hPa	120Vac, 60Hz	Brad Wu
APCM	A	23deg. C, 68%RH, 1014 hPa	120Vac, 60Hz	Long Chen

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)

ANSI C63.4-2003

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK	DELL	D830	4C53R1S	E2K4965AGNM

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA

NOTE: All power cords of the above support units are non shielded (1.8m).

4. TEST TYPES AND RESULTS

4.1 RADIATED EMISSION MEASUREMENT

4.1.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400 / F(kHz)	300
0.490 ~ 1.705	24000 / F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESIB7	100188	Dec. 21, 2009	Dec. 20, 2010
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100269	Dec. 31, 2009	Dec. 30, 2010
BILOG Antenna SCHWARZBECK	VULB9168	9168-160	Apr. 27, 2010	Apr. 26, 2011
HORN Antenna SCHWARZBECK	9120D	9120D-405	Feb. 03, 2010	Feb. 02, 2011
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170243	Dec. 25, 2009	Dec. 24, 2010
Preamplifier Agilent	8447D	2944A10633	Nov. 10, 2009	Nov. 09, 2010
Preamplifier Agilent	8449B	3008A01964	Nov. 09, 2009	Nov. 08, 2010
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	238141/4	May 14, 2010	May 13, 2011
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	12738/6	May 14, 2010	May 13, 2011
Software ADT.	ADT_Radiated_ V7.6.15.9.2	NA	NA	NA
Antenna Tower inn-co GmbH	MA 4000	013303	NA	NA
Antenna Tower Controller inn-co GmbH	CO2000	017303	NA	NA
Turn Table ADT.	TT100.	TT93021703	NA	NA
Turn Table Controller ADT.	SC100.	SC93021703	NA	NA

- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Chamber 3.
3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 988962.
5. The IC Site Registration No. is IC 7450F-3.

4.1.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation.

4.1.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo)

4.1.6 EUT OPERATING CONDITIONS

- The EUT was inserted into a notebook and placed on a testing table.
- The notebook system ran a test program (provided by manufacturer) to enable EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.

4.1.7 TEST RESULTS

802.11b

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	26deg. C, 65%RH 1011 hPa	TESTED BY	Long Chen
TEST MODE	A		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2386.00	58.5 PK	74.0	-15.5	1.00 H	216	28.00	30.50
2	2386.00	46.1 AV	54.0	-7.9	1.00 H	216	15.60	30.50
3	*2412.00	102.1 PK			1.02 H	197	71.50	30.60
4	*2412.00	97.3 AV			1.02 H	197	66.70	30.60
5	4824.00	50.1 PK	74.0	-23.9	1.43 H	47	14.00	36.10
6	4824.00	40.1 AV	54.0	-13.9	1.43 H	47	4.00	36.10
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2386.00	61.3 PK	74.0	-12.7	1.29 V	106	30.80	30.50
2	2386.00	50.4 AV	54.0	-3.6	1.29 V	106	19.90	30.50
3	*2412.00	111.8 PK			1.27 V	106	81.20	30.60
4	*2412.00	106.9 AV			1.27 V	106	76.30	30.60
5	4824.00	50.8 PK	74.0	-23.2	1.00 V	216	14.70	36.10
6	4824.00	43.5 AV	54.0	-10.5	1.00 V	216	7.40	36.10

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	26deg. C, 65%RH 1011 hPa	TESTED BY	Long Chen
TEST MODE	A		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	103.0 PK			1.00 H	218	72.40	30.60
2	*2437.00	98.2 AV			1.00 H	218	67.60	30.60
3	4874.00	49.0 PK	74.0	-25.0	1.00 H	349	12.80	36.20
4	4874.00	38.9 AV	54.0	-15.1	1.00 H	349	2.70	36.20
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	112.2 PK			1.26 V	81	81.60	30.60
2	*2437.00	107.3 AV			1.26 V	81	76.70	30.60
3	4874.00	53.0 PK	74.0	-21.0	1.14 V	91	16.80	36.20
4	4874.00	46.6 AV	54.0	-7.4	1.14 V	91	10.40	36.20

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	26deg. C, 65%RH 1011 hPa	TESTED BY	Long Chen
TEST MODE	A		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	102.3 PK			1.00 H	221	71.60	30.70
2	*2462.00	97.4 AV			1.00 H	221	66.70	30.70
3	2483.50	56.3 PK	74.0	-17.7	1.00 H	207	25.50	30.80
4	2483.50	45.3 AV	54.0	-8.7	1.00 H	207	14.50	30.80
5	4924.00	49.1 PK	74.0	-24.9	1.56 H	46	12.80	36.30
6	4924.00	37.9 AV	54.0	-16.1	1.56 H	46	1.60	36.30
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	111.5 PK			1.03 V	76	80.80	30.70
2	*2462.00	106.6 AV			1.03 V	76	75.90	30.70
3	2484.60	61.6 PK	74.0	-12.4	1.00 V	78	30.80	30.80
4	2484.60	49.6 AV	54.0	-4.4	1.00 V	78	18.80	30.80
5	4924.00	52.4 PK	74.0	-21.6	1.13 V	86	16.10	36.30
6	4924.00	46.6 AV	54.0	-7.4	1.13 V	86	10.30	36.30

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH 1014 hPa	TESTED BY	Brad Wu
TEST MODE	B		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	54.6 PK	74.0	-19.4	1.23 H	41	24.10	30.50
2	2390.00	44.1 AV	54.0	-9.9	1.23 H	41	13.60	30.50
3	*2412.00	100.2 PK			1.23 H	41	69.60	30.60
4	*2412.00	95.5 AV			1.23 H	41	64.90	30.60
5	4824.00	50.0 PK	74.0	-24.0	1.11 H	181	13.90	36.10
6	4824.00	40.1 AV	54.0	-13.9	1.11 H	181	4.00	36.10
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	60.4 PK	74.0	-13.6	1.18 V	171	29.90	30.50
2	2390.00	47.4 AV	54.0	-6.6	1.18 V	171	16.90	30.50
3	*2412.00	111.1 PK			1.18 V	171	80.50	30.60
4	*2412.00	106.5 AV			1.18 V	171	75.90	30.60
5	4824.00	52.1 PK	74.0	-21.9	1.19 V	213	16.00	36.10
6	4824.00	46.0 AV	54.0	-8.0	1.19 V	213	9.90	36.10

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH 1014 hPa	TESTED BY	Brad Wu
TEST MODE	B		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	100.5 PK			1.24 H	42	69.90	30.60
2	*2437.00	95.8 AV			1.24 H	42	65.20	30.60
3	4874.00	49.2 PK	74.0	-24.8	1.12 H	186	13.00	36.20
4	4874.00	39.4 AV	54.0	-14.6	1.12 H	186	3.20	36.20
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	111.5 PK			1.16 V	179	80.90	30.60
2	*2437.00	106.9 AV			1.16 V	179	76.30	30.60
3	4874.00	50.9 PK	74.0	-23.1	1.18 V	213	14.70	36.20
4	4874.00	44.0 AV	54.0	-10.0	1.18 V	213	7.80	36.20

- REMARKS:** 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH 1014 hPa	TESTED BY	Brad Wu
TEST MODE	B		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	100.3 PK			1.22 H	42	69.60	30.70
2	*2462.00	95.6 AV			1.22 H	42	64.90	30.70
3	2483.50	56.9 PK	74.0	-17.1	1.22 H	42	26.10	30.80
4	2483.50	46.4 AV	54.0	-7.6	1.22 H	42	15.60	30.80
5	4924.00	50.4 PK	74.0	-23.6	1.18 H	31	14.10	36.30
6	4924.00	40.3 AV	54.0	-13.7	1.18 H	31	4.00	36.30
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	111.3 PK			1.16 V	170	80.60	30.70
2	*2462.00	106.7 AV			1.16 V	170	76.00	30.70
3	2483.50	62.8 PK	74.0	-11.2	1.16 V	170	32.00	30.80
4	2483.50	50.2 AV	54.0	-3.8	1.16 V	170	19.40	30.80
5	4924.00	50.6 PK	74.0	-23.4	1.16 V	161	14.30	36.30
6	4924.00	43.1 AV	54.0	-10.9	1.16 V	161	6.80	36.30

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ”: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH 1011 hPa	TESTED BY	Frank Wang
TEST MODE	C		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	56.2 PK	74.0	-17.8	1.29 H	34	25.70	30.50
2	2390.00	47.1 AV	54.0	-6.9	1.29 H	34	16.60	30.50
3	*2412.00	109.8 PK			1.29 H	34	79.20	30.60
4	*2412.00	105.8 AV			1.29 H	34	75.20	30.60
5	4824.00	49.5 PK	74.0	-24.5	1.00 H	203	13.40	36.10
6	4824.00	40.4 AV	54.0	-13.6	1.00 H	203	4.30	36.10
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	56.9 PK	74.0	-17.1	1.16 V	330	26.40	30.50
2	2390.00	48.2 AV	54.0	-5.8	1.16 V	330	17.70	30.50
3	*2412.00	111.0 PK			1.16 V	330	80.40	30.60
4	*2412.00	107.1 AV			1.16 V	330	76.50	30.60
5	4824.00	50.6 PK	74.0	-23.4	1.31 V	267	14.50	36.10
6	4824.00	41.9 AV	54.0	-12.1	1.31 V	267	5.80	36.10

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH 1011 hPa	TESTED BY	Frank Wang
TEST MODE	C		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	110.0 PK			1.31 H	40	79.40	30.60
2	*2437.00	106.0 AV			1.31 H	40	75.40	30.60
3	4874.00	50.6 PK	74.0	-23.4	1.13 H	218	14.40	36.20
4	4874.00	41.8 AV	54.0	-12.2	1.13 H	218	5.60	36.20
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	111.2 PK			1.15 V	328	80.60	30.60
2	*2437.00	107.3 AV			1.15 V	328	76.70	30.60
3	4874.00	51.8 PK	74.0	-22.2	1.06 V	29	15.60	36.20
4	4874.00	43.3 AV	54.0	-10.7	1.06 V	29	7.10	36.20

- REMARKS:** 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH 1011 hPa	TESTED BY	Frank Wang
TEST MODE	C		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	110.3 PK			1.30 H	35	79.60	30.70
2	*2462.00	106.4 AV			1.30 H	35	75.70	30.70
3	2483.50	57.6 PK	74.0	-16.4	1.30 H	35	26.80	30.80
4	2483.50	48.5 AV	54.0	-5.5	1.30 H	35	17.70	30.80
5	4924.00	51.0 PK	74.0	-23.0	1.10 H	209	14.70	36.30
6	4924.00	42.6 AV	54.0	-11.4	1.10 H	209	6.30	36.30
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	111.5 PK			1.19 V	332	80.80	30.70
2	*2462.00	107.4 AV			1.19 V	332	76.70	30.70
3	2483.50	58.2 PK	74.0	-15.8	1.19 V	332	27.40	30.80
4	2483.50	49.3 AV	54.0	-4.7	1.19 V	332	18.50	30.80
5	4924.00	53.0 PK	74.0	-21.0	1.05 V	222	16.70	36.30
6	4924.00	44.9 AV	54.0	-9.1	1.05 V	222	8.60	36.30

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.

802.11g

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	26deg. C, 65%RH 1011 hPa	TESTED BY	Long Chen
TEST MODE	A		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	67.2 PK	74.0	-6.8	1.00 H	218	36.70	30.50
2	2390.00	49.6 AV	54.0	-4.4	1.00 H	218	19.10	30.50
3	*2412.00	102.7 PK			1.00 H	208	72.10	30.60
4	*2412.00	91.6 AV			1.00 H	208	61.00	30.60
5	4824.00	47.7 PK	74.0	-26.3	1.13 H	300	11.60	36.10
6	4824.00	33.5 AV	54.0	-20.5	1.13 H	300	-2.60	36.10
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	71.5 PK	74.0	-2.5	1.04 V	55	41.00	30.50
2	2390.00	52.8 AV	54.0	-1.2	1.04 V	55	22.30	30.50
3	*2412.00	111.2 PK			1.03 V	77	80.60	30.60
4	*2412.00	99.6 AV			1.03 V	77	69.00	30.60
5	4824.00	49.1 PK	74.0	-24.9	1.02 V	88	13.00	36.10
6	4824.00	35.0 AV	54.0	-19.0	1.02 V	88	-1.10	36.10

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	26deg. C, 65%RH 1011 hPa	TESTED BY	Long Chen
TEST MODE	A		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	103.5 PK			1.00 H	218	72.90	30.60
2	*2437.00	92.1 AV			1.00 H	218	61.50	30.60
3	4874.00	48.0 PK	74.0	-26.0	1.19 H	333	11.80	36.20
4	4874.00	33.6 AV	54.0	-20.4	1.19 H	333	-2.60	36.20
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	111.5 PK			1.04 V	74	80.90	30.60
2	*2437.00	100.2 AV			1.04 V	74	69.60	30.60
3	4874.00	49.7 PK	74.0	-24.3	1.04 V	86	13.50	36.20
4	4874.00	34.8 AV	54.0	-19.2	1.04 V	86	-1.40	36.20

- REMARKS:** 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	26deg. C, 65%RH 1011 hPa	TESTED BY	Long Chen
TEST MODE	A		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	102.9 PK			1.01 H	191	72.20	30.70
2	*2462.00	91.7 AV			1.01 H	191	61.00	30.70
3	2483.50	61.3 PK	74.0	-12.7	1.01 H	207	30.50	30.80
4	2483.50	47.5 AV	54.0	-6.5	1.01 H	207	16.70	30.80
5	4924.00	47.4 PK	74.0	-26.6	1.23 H	325	11.10	36.30
6	4924.00	33.1 AV	54.0	-20.9	1.23 H	325	-3.20	36.30
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	110.7 PK			1.01 V	78	80.00	30.70
2	*2462.00	99.5 AV			1.01 V	78	68.80	30.70
3	2483.50	67.3 PK	74.0	-6.7	1.00 V	77	36.50	30.80
4	2483.50	53.0 AV	54.0	-1.0	1.00 V	77	22.20	30.80
5	4924.00	48.5 PK	74.0	-25.5	1.00 V	87	12.20	36.30
6	4924.00	35.3 AV	54.0	-18.7	1.00 V	87	-1.00	36.30

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH 1014 hPa	TESTED BY	Brad Wu
TEST MODE	B		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	62.1 PK	74.0	-11.9	1.05 H	5	31.60	30.50
2	2390.00	45.3 AV	54.0	-8.7	1.05 H	5	14.80	30.50
3	*2412.00	101.1 PK			1.05 H	5	70.50	30.60
4	*2412.00	89.8 AV			1.05 H	5	59.20	30.60
5	4824.00	50.1 PK	74.0	-23.9	1.02 H	211	14.00	36.10
6	4824.00	35.6 AV	54.0	-18.4	1.02 H	211	-0.50	36.10
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	70.9 PK	74.0	-3.1	1.17 V	304	40.40	30.50
2	2390.00	52.4 AV	54.0	-1.6	1.17 V	304	21.90	30.50
3	*2412.00	110.4 PK			1.20 V	171	79.80	30.60
4	*2412.00	98.9 AV			1.20 V	171	68.30	30.60
5	4824.00	50.5 PK	74.0	-23.5	1.04 V	215	14.40	36.10
6	4824.00	36.0 AV	54.0	-18.0	1.04 V	215	-0.10	36.10

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH 1014 hPa	TESTED BY	Brad Wu
TEST MODE	B		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	101.5 PK			1.04 H	6	70.90	30.60
2	*2437.00	90.2 AV			1.04 H	6	59.60	30.60
3	4874.00	50.3 PK	74.0	-23.7	1.11 H	29	14.10	36.20
4	4874.00	35.8 AV	54.0	-18.2	1.11 H	29	-0.40	36.20
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	110.8 PK			1.19 V	174	80.20	30.60
2	*2437.00	99.3 AV			1.19 V	174	68.70	30.60
3	4874.00	51.0 PK	74.0	-23.0	1.14 V	21	14.80	36.20
4	4874.00	36.4 AV	54.0	-17.6	1.14 V	21	0.20	36.20

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH 1014 hPa	TESTED BY	Brad Wu
TEST MODE	B		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	100.9 PK			1.04 H	6	70.20	30.70
2	*2462.00	89.6 AV			1.04 H	6	58.90	30.70
3	2483.50	62.6 PK	74.0	-11.4	1.04 H	6	31.80	30.80
4	2483.50	45.9 AV	54.0	-8.1	1.04 H	6	15.10	30.80
5	4924.00	50.4 PK	74.0	-23.6	1.11 H	36	14.10	36.30
6	4924.00	35.9 AV	54.0	-18.1	1.11 H	36	-0.40	36.30
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	110.2 PK			1.18 V	170	79.50	30.70
2	*2462.00	98.7 AV			1.18 V	170	68.00	30.70
3	2483.50	71.4 PK	74.0	-2.6	1.18 V	159	40.60	30.80
4	2483.50	53.0 AV	54.0	-1.0	1.18 V	159	22.20	30.80
5	4924.00	50.8 PK	74.0	-23.2	1.05 V	33	14.50	36.30
6	4924.00	36.2 AV	54.0	-17.8	1.05 V	33	-0.10	36.30

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ”: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH 1011 hPa	TESTED BY	Frank Wang
TEST MODE	C		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	70.2 PK	74.0	-3.8	1.24 H	35	39.70	30.50
2	2390.00	51.5 AV	54.0	-2.5	1.24 H	35	21.00	30.50
3	*2412.00	107.4 PK			1.24 H	35	76.80	30.60
4	*2412.00	97.5 AV			1.24 H	35	66.90	30.60
5	4824.00	47.6 PK	74.0	-26.4	1.01 H	88	11.50	36.10
6	4824.00	35.0 AV	54.0	-19.0	1.01 H	88	-1.10	36.10
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	71.0 PK	74.0	-3.0	1.25 V	300	40.50	30.50
2	2390.00	52.4 AV	54.0	-1.6	1.25 V	300	21.90	30.50
3	*2412.00	108.6 PK			1.25 V	300	78.00	30.60
4	*2412.00	98.7 AV			1.25 V	300	68.10	30.60
5	4824.00	48.1 PK	74.0	-25.9	1.05 V	219	12.00	36.10
6	4824.00	35.6 AV	54.0	-18.4	1.05 V	219	-0.50	36.10

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH 1011 hPa	TESTED BY	Frank Wang
TEST MODE	C		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	107.8 PK			1.22 H	39	77.20	30.60
2	*2437.00	97.9 AV			1.22 H	39	67.30	30.60
3	4874.00	47.8 PK	74.0	-26.2	1.00 H	91	11.60	36.20
4	4874.00	35.2 AV	54.0	-18.8	1.00 H	91	-1.00	36.20
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	109.1 PK			1.28 V	295	78.50	30.60
2	*2437.00	99.2 AV			1.28 V	295	68.60	30.60
3	4874.00	48.4 PK	74.0	-25.6	1.04 V	221	12.20	36.20
4	4874.00	35.9 AV	54.0	-18.1	1.04 V	221	-0.30	36.20

- REMARKS:** 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH 1011 hPa	TESTED BY	Frank Wang
TEST MODE	C		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	108.1 PK			1.24 H	45	77.40	30.70
2	*2462.00	98.2 AV			1.24 H	45	67.50	30.70
3	2483.50	67.6 PK	74.0	-6.4	1.24 H	45	36.80	30.80
4	2483.50	50.9 AV	54.0	-3.1	1.24 H	45	20.10	30.80
5	4924.00	48.1 PK	74.0	-25.9	1.10 H	85	11.80	36.30
6	4924.00	35.4 AV	54.0	-18.6	1.10 H	85	-0.90	36.30
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	109.5 PK			1.32 V	288	78.80	30.70
2	*2462.00	99.5 AV			1.32 V	288	68.80	30.70
3	2483.50	68.8 PK	74.0	-5.2	1.32 V	288	38.00	30.80
4	2483.50	52.1 AV	54.0	-1.9	1.32 V	288	21.30	30.80
5	4924.00	48.6 PK	74.0	-25.4	1.00 V	34	12.30	36.30
6	4924.00	36.2 AV	54.0	-17.8	1.00 V	34	-0.10	36.30

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.

802.11n (20MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	26deg. C, 65%RH 1011 hPa	TESTED BY	Long Chen
TEST MODE	A		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	65.6 PK	74.0	-8.4	1.00 H	218	35.10	30.50
2	2390.00	47.7 AV	54.0	-6.3	1.00 H	218	17.20	30.50
3	*2412.00	101.2 PK			1.00 H	207	70.60	30.60
4	*2412.00	89.9 AV			1.00 H	207	59.30	30.60
5	4824.00	47.1 PK	74.0	-26.9	1.22 H	312	11.00	36.10
6	4824.00	33.2 AV	54.0	-20.8	1.22 H	312	-2.90	36.10
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	71.1 PK	74.0	-2.9	1.04 V	94	40.60	30.50
2	2390.00	52.5 AV	54.0	-1.5	1.04 V	94	22.00	30.50
3	*2412.00	109.3 PK			1.28 V	106	78.70	30.60
4	*2412.00	97.4 AV			1.28 V	106	66.80	30.60
5	4824.00	49.3 PK	74.0	-24.7	1.00 V	90	13.20	36.10
6	4824.00	34.6 AV	54.0	-19.4	1.00 V	90	-1.50	36.10

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ”: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	26deg. C, 65%RH 1011 hPa	TESTED BY	Long Chen
TEST MODE	A		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	101.5 PK			1.00 H	215	70.90	30.60
2	*2437.00	90.0 AV			1.00 H	215	59.40	30.60
3	4874.00	48.1 PK	74.0	-25.9	1.25 H	314	11.90	36.20
4	4874.00	33.5 AV	54.0	-20.5	1.25 H	314	-2.70	36.20
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	109.5 PK			1.26 V	79	78.90	30.60
2	*2437.00	97.2 AV			1.26 V	79	66.60	30.60
3	4874.00	49.8 PK	74.0	-24.2	1.06 V	95	13.60	36.20
4	4874.00	34.7 AV	54.0	-19.3	1.06 V	95	-1.50	36.20

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	26deg. C, 65%RH 1011 hPa	TESTED BY	Long Chen
TEST MODE	A		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	101.1 PK			1.00 H	208	70.40	30.70
2	*2462.00	89.4 AV			1.00 H	208	58.70	30.70
3	2483.50	60.7 PK	74.0	-13.3	1.00 H	206	29.90	30.80
4	2483.50	46.7 AV	54.0	-7.3	1.00 H	206	15.90	30.80
5	4924.00	47.2 PK	74.0	-26.8	1.25 H	314	10.90	36.30
6	4924.00	33.5 AV	54.0	-20.5	1.25 H	314	-2.80	36.30
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	108.5 PK			1.02 V	81	77.80	30.70
2	*2462.00	96.7 AV			1.02 V	81	66.00	30.70
3	2483.50	70.0 PK	74.0	-4.0	1.02 V	79	39.20	30.80
4	2483.50	53.0 AV	54.0	-1.0	1.02 V	79	22.20	30.80
5	4924.00	49.5 PK	74.0	-24.5	1.00 V	90	13.20	36.30
6	4924.00	34.8 AV	54.0	-19.2	1.00 V	90	-1.50	36.30

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH 1014 hPa	TESTED BY	Brad Wu
TEST MODE	B		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	62.5 PK	74.0	-11.5	1.09 H	21	32.00	30.50
2	2390.00	45.6 AV	54.0	-8.4	1.09 H	21	15.10	30.50
3	*2412.00	99.3 PK			1.09 H	21	68.70	30.60
4	*2412.00	88.0 AV			1.09 H	21	57.40	30.60
5	4824.00	49.0 PK	74.0	-25.0	1.01 H	66	12.90	36.10
6	4824.00	34.2 AV	54.0	-19.8	1.01 H	66	-1.90	36.10
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	71.3 PK	74.0	-2.7	1.17 V	303	40.80	30.50
2	2390.00	52.1 AV	54.0	-1.9	1.17 V	303	21.60	30.50
3	*2412.00	108.8 PK			1.18 V	177	78.20	30.60
4	*2412.00	96.9 AV			1.18 V	177	66.30	30.60
5	4824.00	49.6 PK	74.0	-24.4	1.15 V	24	13.50	36.10
6	4824.00	34.9 AV	54.0	-19.1	1.15 V	24	-1.20	36.10

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH 1014 hPa	TESTED BY	Brad Wu
TEST MODE	B		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	99.6 PK			1.10 H	22	69.00	30.60
2	*2437.00	88.3 AV			1.10 H	22	57.70	30.60
3	4874.00	49.2 PK	74.0	-24.8	1.05 H	96	13.00	36.20
4	4874.00	34.4 AV	54.0	-19.6	1.05 H	96	-1.80	36.20
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	109.1 PK			1.19 V	176	78.50	30.60
2	*2437.00	97.2 AV			1.19 V	176	66.60	30.60
3	4874.00	49.8 PK	74.0	-24.2	1.05 V	213	13.60	36.20
4	4874.00	35.1 AV	54.0	-18.9	1.05 V	213	-1.10	36.20

- REMARKS:** 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH 1014 hPa	TESTED BY	Brad Wu
TEST MODE	B		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	99.1 PK			1.10 H	23	68.40	30.70
2	*2462.00	87.8 AV			1.10 H	23	57.10	30.70
3	2483.50	62.8 PK	74.0	-11.2	1.10 H	23	32.00	30.80
4	2483.50	46.0 AV	54.0	-8.0	1.10 H	23	15.20	30.80
5	4924.00	49.2 PK	74.0	-24.8	1.15 H	23	12.90	36.30
6	4924.00	34.5 AV	54.0	-19.5	1.15 H	23	-1.80	36.30
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	108.6 PK			1.16 V	175	77.90	30.70
2	*2462.00	96.7 AV			1.16 V	175	66.00	30.70
3	2483.50	71.5 PK	74.0	-2.5	1.15 V	156	40.70	30.80
4	2483.50	52.8 AV	54.0	-1.2	1.15 V	156	22.00	30.80
5	4924.00	49.3 PK	74.0	-24.7	1.15 V	221	13.00	36.30
6	4924.00	34.6 AV	54.0	-19.4	1.15 V	221	-1.70	36.30

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH 1011 hPa	TESTED BY	Frank Wang
TEST MODE	C		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	66.4 PK	74.0	-7.6	1.20 H	40	35.90	30.50
2	2390.00	51.5 AV	54.0	-2.5	1.20 H	40	21.00	30.50
3	*2412.00	106.1 PK			1.20 H	40	75.50	30.60
4	*2412.00	96.2 AV			1.20 H	40	65.60	30.60
5	4824.00	47.4 PK	74.0	-26.6	1.05 H	266	11.30	36.10
6	4824.00	35.0 AV	54.0	-19.0	1.05 H	266	-1.10	36.10
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	67.2 PK	74.0	-6.8	1.29 V	286	36.70	30.50
2	2390.00	52.2 AV	54.0	-1.8	1.29 V	286	21.70	30.50
3	*2412.00	107.4 PK			1.29 V	286	76.80	30.60
4	*2412.00	97.4 AV			1.29 V	286	66.80	30.60
5	4824.00	47.8 PK	74.0	-26.2	1.10 V	26	11.70	36.10
6	4824.00	35.4 AV	54.0	-18.6	1.10 V	26	-0.70	36.10

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH 1011 hPa	TESTED BY	Frank Wang
TEST MODE	C		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	106.3 PK			1.18 H	39	75.70	30.60
2	*2437.00	96.4 AV			1.18 H	39	65.80	30.60
3	4874.00	47.8 PK	74.0	-26.2	1.14 H	230	11.60	36.20
4	4874.00	35.4 AV	54.0	-18.6	1.14 H	230	-0.80	36.20
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	107.6 PK			1.30 V	288	77.00	30.60
2	*2437.00	97.6 AV			1.30 V	288	67.00	30.60
3	4874.00	48.1 PK	74.0	-25.9	1.05 V	29	11.90	36.20
4	4874.00	35.6 AV	54.0	-18.4	1.05 V	29	-0.60	36.20

- REMARKS:** 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH 1011 hPa	TESTED BY	Frank Wang
TEST MODE	C		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	106.6 PK			1.20 H	41	75.90	30.70
2	*2462.00	96.6 AV			1.20 H	41	65.90	30.70
3	2483.50	67.0 PK	74.0	-7.0	1.20 H	41	36.20	30.80
4	2483.50	51.8 AV	54.0	-2.2	1.20 H	41	21.00	30.80
5	4924.00	48.0 PK	74.0	-26.0	1.10 H	59	11.70	36.30
6	4924.00	35.6 AV	54.0	-18.4	1.10 H	59	-0.70	36.30
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	108.0 PK			1.33 V	298	77.30	30.70
2	*2462.00	98.1 AV			1.33 V	298	67.40	30.70
3	2483.50	67.5 PK	74.0	-6.5	1.33 V	298	36.70	30.80
4	2483.50	52.4 AV	54.0	-1.6	1.33 V	298	21.60	30.80
5	4924.00	48.3 PK	74.0	-25.7	1.11 V	56	12.00	36.30
6	4924.00	35.8 AV	54.0	-18.2	1.11 V	56	-0.50	36.30

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.

802.11n (40MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	26deg. C, 65%RH 1011 hPa	TESTED BY	Long Chen
TEST MODE	A		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	61.4 PK	74.0	-12.6	1.00 H	214	30.90	30.50
2	2390.00	47.7 AV	54.0	-6.3	1.00 H	214	17.20	30.50
3	*2422.00	94.6 PK			1.00 H	218	64.00	30.60
4	*2422.00	82.9 AV			1.00 H	218	52.30	30.60
5	4844.00	48.0 PK	74.0	-26.0	1.02 H	345	11.80	36.20
6	4844.00	33.4 AV	54.0	-20.6	1.02 H	345	-2.80	36.20
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	70.1 PK	74.0	-3.9	1.00 V	101	39.60	30.50
2	2390.00	53.0 AV	54.0	-1.0	1.00 V	101	22.50	30.50
3	*2422.00	102.6 PK			1.01 V	80	72.00	30.60
4	*2422.00	90.7 AV			1.01 V	80	60.10	30.60
5	4844.00	48.4 PK	74.0	-25.6	1.10 V	5	12.20	36.20
6	4844.00	34.4 AV	54.0	-19.6	1.10 V	5	-1.80	36.20

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 4	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	26deg. C, 65%RH 1011 hPa	TESTED BY	Long Chen
TEST MODE	A		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	94.2 PK			1.00 H	217	63.60	30.60
2	*2437.00	82.5 AV			1.00 H	217	51.90	30.60
3	4874.00	48.2 PK	74.0	-25.8	1.05 H	331	12.00	36.20
4	4874.00	33.7 AV	54.0	-20.3	1.05 H	331	-2.50	36.20
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	102.2 PK			1.04 V	76	71.60	30.60
2	*2437.00	90.7 AV			1.04 V	76	60.10	30.60
3	4874.00	48.9 PK	74.0	-25.1	1.10 V	8	12.70	36.20
4	4874.00	34.8 AV	54.0	-19.2	1.10 V	8	-1.40	36.20

- REMARKS:** 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 7	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	26deg. C, 65%RH 1011 hPa	TESTED BY	Long Chen
TEST MODE	A		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	94.0 PK			1.00 H	218	63.30	30.70
2	*2452.00	82.0 AV			1.00 H	218	51.30	30.70
3	2483.50	62.8 PK	74.0	-11.2	1.00 H	217	32.00	30.80
4	2483.50	48.2 AV	54.0	-5.8	1.00 H	217	17.40	30.80
5	4904.00	48.5 PK	74.0	-25.5	1.06 H	336	12.30	36.20
6	4904.00	33.5 AV	54.0	-20.5	1.06 H	336	-2.70	36.20
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	102.5 PK			1.04 V	74	71.80	30.70
2	*2452.00	90.3 AV			1.04 V	74	59.60	30.70
3	2483.50	69.2 PK	74.0	-4.8	1.01 V	76	38.40	30.80
4	2483.50	52.8 AV	54.0	-1.2	1.01 V	76	22.00	30.80
5	4904.00	48.5 PK	74.0	-25.5	1.14 V	10	12.30	36.20
6	4904.00	34.7 AV	54.0	-19.3	1.14 V	10	-1.50	36.20

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH 1014 hPa	TESTED BY	Brad Wu
TEST MODE	B		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	61.0 PK	74.0	-13.0	1.10 H	24	30.50	30.50
2	2390.00	47.2 AV	54.0	-6.8	1.10 H	24	16.70	30.50
3	*2422.00	93.0 PK			1.10 H	24	62.40	30.60
4	*2422.00	81.6 AV			1.10 H	24	51.00	30.60
5	4844.00	48.0 PK	74.0	-26.0	1.09 H	21	11.80	36.20
6	4844.00	33.9 AV	54.0	-20.1	1.09 H	21	-2.30	36.20
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	70.1 PK	74.0	-3.9	1.18 V	303	39.60	30.50
2	2390.00	52.2 AV	54.0	-1.8	1.18 V	303	21.70	30.50
3	*2422.00	102.4 PK			1.16 V	170	71.80	30.60
4	*2422.00	90.4 AV			1.16 V	170	59.80	30.60
5	4844.00	48.2 PK	74.0	-25.8	1.10 V	16	12.00	36.20
6	4844.00	34.2 AV	54.0	-19.8	1.10 V	16	-2.00	36.20

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ”: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 4	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH 1014 hPa	TESTED BY	Brad Wu
TEST MODE	B		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	93.2 PK			1.09 H	30	62.60	30.60
2	*2437.00	81.8 AV			1.09 H	30	51.20	30.60
3	4874.00	48.2 PK	74.0	-25.8	1.01 H	35	12.00	36.20
4	4874.00	34.1 AV	54.0	-19.9	1.01 H	35	-2.10	36.20
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	102.6 PK			1.15 V	171	72.00	30.60
2	*2437.00	90.5 AV			1.15 V	171	59.90	30.60
3	4874.00	48.6 PK	74.0	-25.4	1.13 V	22	12.40	36.20
4	4874.00	34.5 AV	54.0	-19.5	1.13 V	22	-1.70	36.20

- REMARKS:** 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 7	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH 1014 hPa	TESTED BY	Brad Wu
TEST MODE	B		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	92.8 PK			1.09 H	26	62.10	30.70
2	*2452.00	81.4 AV			1.09 H	26	50.70	30.70
3	2483.50	61.3 PK	74.0	-12.7	1.09 H	26	30.50	30.80
4	2483.50	47.6 AV	54.0	-6.4	1.09 H	26	16.80	30.80
5	4904.00	48.3 PK	74.0	-25.7	1.06 H	201	12.10	36.20
6	4904.00	34.2 AV	54.0	-19.8	1.06 H	201	-2.00	36.20
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	102.2 PK			1.18 V	181	71.50	30.70
2	*2452.00	90.2 AV			1.18 V	181	59.50	30.70
3	2483.50	70.4 PK	74.0	-3.6	1.16 V	301	39.60	30.80
4	2483.50	52.8 AV	54.0	-1.2	1.16 V	301	22.00	30.80
5	4904.00	48.8 PK	74.0	-25.2	1.02 V	43	12.60	36.20
6	4904.00	34.6 AV	54.0	-19.4	1.02 V	43	-1.60	36.20

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH 1011 hPa	TESTED BY	Frank Wang
TEST MODE	C		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	68.1 PK	74.0	-5.9	1.15 H	34	37.60	30.50
2	2390.00	51.0 AV	54.0	-3.0	1.15 H	34	20.50	30.50
3	*2422.00	99.2 PK			1.15 H	34	68.60	30.60
4	*2422.00	89.2 AV			1.15 H	34	58.60	30.60
5	4844.00	47.1 PK	74.0	-26.9	1.10 H	285	10.90	36.20
6	4844.00	34.0 AV	54.0	-20.0	1.10 H	285	-2.20	36.20
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	69.5 PK	74.0	-4.5	1.21 V	324	39.00	30.50
2	2390.00	52.2 AV	54.0	-1.8	1.21 V	324	21.70	30.50
3	*2422.00	100.5 PK			1.21 V	324	69.90	30.60
4	*2422.00	90.4 AV			1.21 V	324	59.80	30.60
5	4844.00	47.4 PK	74.0	-26.6	1.13 V	296	11.20	36.20
6	4844.00	34.2 AV	54.0	-19.8	1.13 V	296	-2.00	36.20

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 4	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH 1011 hPa	TESTED BY	Frank Wang
TEST MODE	C		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	99.5 PK			1.13 H	36	68.90	30.60
2	*2437.00	89.4 AV			1.13 H	36	58.80	30.60
3	4874.00	47.4 PK	74.0	-26.6	1.05 H	312	11.20	36.20
4	4874.00	34.2 AV	54.0	-19.8	1.05 H	312	-2.00	36.20
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	100.8 PK			1.20 V	329	70.20	30.60
2	*2437.00	90.8 AV			1.20 V	329	60.20	30.60
3	4874.00	47.9 PK	74.0	-26.1	1.09 V	216	11.70	36.20
4	4874.00	34.6 AV	54.0	-19.4	1.09 V	216	-1.60	36.20

- REMARKS:** 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 7	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH 1011 hPa	TESTED BY	Frank Wang
TEST MODE	C		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	99.8 PK			1.12 H	39	69.10	30.70
2	*2452.00	89.7 AV			1.12 H	39	59.00	30.70
3	2483.50	69.6 PK	74.0	-4.4	1.12 H	39	38.80	30.80
4	2483.50	50.9 AV	54.0	-3.1	1.12 H	39	20.10	30.80
5	4904.00	47.8 PK	74.0	-26.2	1.03 H	91	11.60	36.20
6	4904.00	34.6 AV	54.0	-19.4	1.03 H	91	-1.60	36.20
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	101.1 PK			1.18 V	315	70.40	30.70
2	*2452.00	91.0 AV			1.18 V	315	60.30	30.70
3	2483.50	71.2 PK	74.0	-2.8	1.18 V	315	40.40	30.80
4	2483.50	52.2 AV	54.0	-1.8	1.18 V	315	21.40	30.80
5	4904.00	48.2 PK	74.0	-25.8	1.11 V	252	12.00	36.20
6	4904.00	34.8 AV	54.0	-19.2	1.11 V	252	-1.40	36.20

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.

BELOW 1GHz WORST-CASE DATA : 802.11g

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	Below 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	26deg. C, 65%RH 1011 hPa	TESTED BY	Long Chen
TEST MODE	A		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	129.06	27.8 QP	43.5	-15.7	3.00 H	31	14.70	13.10
2	199.49	37.7 QP	43.5	-5.8	1.72 H	171	27.40	10.30
3	270.99	28.6 QP	46.0	-17.4	1.00 H	286	15.00	13.60
4	471.25	26.9 QP	46.0	-19.1	1.25 H	358	7.80	19.10
5	665.68	38.8 QP	46.0	-7.2	1.00 H	307	15.70	23.10
6	986.49	34.1 QP	54.0	-19.9	3.00 H	190	7.10	27.00
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	30.00	33.1 QP	40.0	-6.9	1.25 V	241	20.60	12.50
2	123.23	29.4 QP	43.5	-14.1	1.00 V	316	16.80	12.60
3	199.05	39.4 QP	43.5	-4.1	1.75 V	103	29.10	10.30
4	469.31	26.0 QP	46.0	-20.0	1.25 V	301	7.00	19.00
5	667.63	39.8 QP	46.0	-6.2	1.00 V	235	16.70	23.10
6	918.44	33.7 QP	46.0	-12.3	1.00 V	256	7.50	26.20

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	Below 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH 1011 hPa	TESTED BY	Long Chen
TEST MODE	B		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	84.34	29.0 QP	40.0	-11.0	2.50 H	106	20.10	8.90
2	199.05	35.4 QP	43.5	-8.1	1.25 H	25	25.10	10.30
3	333.21	27.2 QP	46.0	-18.8	4.00 H	136	11.70	15.50
4	399.31	30.5 QP	46.0	-15.5	1.00 H	22	13.40	17.10
5	665.68	37.8 QP	46.0	-8.2	1.00 H	133	14.70	23.10
6	770.67	31.6 QP	46.0	-14.4	1.00 H	64	7.30	24.30
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	80.45	33.3 QP	40.0	-6.7	1.25 V	115	24.10	9.20
2	333.21	25.3 QP	46.0	-20.7	2.50 V	85	9.80	15.50
3	471.25	27.3 QP	46.0	-18.7	2.00 V	58	8.20	19.10
4	599.58	29.2 QP	46.0	-16.8	1.25 V	22	7.20	22.00
5	665.68	35.8 QP	46.0	-10.2	1.00 V	355	12.70	23.10
6	768.73	31.4 QP	46.0	-14.6	2.50 V	175	7.10	24.30

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	Below 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	26deg. C, 65%RH 1005 hPa	TESTED BY	Long Chen
TEST MODE	C		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	166.00	37.2 QP	43.5	-6.3	1.50 H	355	23.40	13.80
2	239.88	36.0 QP	46.0	-10.0	1.50 H	10	23.70	12.30
3	300.16	35.3 QP	46.0	-10.7	1.00 H	25	20.60	14.70
4	500.42	25.5 QP	46.0	-20.5	1.75 H	142	5.70	19.80
5	700.68	30.9 QP	46.0	-15.1	1.00 H	112	7.30	23.60
6	998.16	36.2 QP	54.0	-17.8	1.25 H	124	9.10	27.10
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	31.84	32.0 QP	40.0	-8.0	1.25 V	199	19.50	12.50
2	80.45	23.9 QP	40.0	-16.1	1.91 V	245	14.70	9.20
3	113.56	29.3 QP	43.5	-14.2	1.08 V	160	17.60	11.70
4	222.38	31.0 QP	46.0	-15.0	1.25 V	196	19.60	11.40
5	722.07	31.2 QP	46.0	-14.8	1.25 V	205	7.40	23.80
6	778.45	31.9 QP	46.0	-14.1	1.25 V	145	7.50	24.40

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

4.2 CONDUCTED EMISSION MEASUREMENT

4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCS30	100289	Nov. 23, 2009	Nov. 22, 2010
RF signal cable Woken	5D-FB	Cable-HYCO2-01	Dec. 31, 2009	Dec. 30, 2010
LISN ROHDE & SCHWARZ	ESH2-Z5	100100	Dec. 25, 2009	Dec. 24, 2010
LISN ROHDE & SCHWARZ	ESH3-Z5	100311	Jul. 08, 2010	Jul. 07, 2011
Software ADT	ADT_Cond_ V7.3.7	NA	NA	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Shielded Room 2.
 3. The VCCI Site Registration No. is C-2047.

4.2.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

4.2.5 TEST SETUP



Note: 1.Support units were connected to second LISN.
 2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6.


4.2.7 TEST RESULTS

CONDUCTED WORST-CASE DATA: 802.11g

PHASE	Line 1	6dB BANDWIDTH	9kHz
TEST MODE	A		

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.162	0.16	48.74	-	48.90	-	65.38	55.38	-16.48	-
2	0.306	0.17	48.96	-	49.13	-	60.07	50.07	-10.94	-
3	0.447	0.18	39.97	-	40.15	-	56.93	46.93	-16.78	-
4	0.619	0.20	42.58	-	42.78	-	56.00	46.00	-13.22	-
5	0.861	0.22	35.75	-	35.97	-	56.00	46.00	-20.03	-
6	1.898	0.30	27.07	-	27.37	-	56.00	46.00	-28.63	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



PHASE	Line 2	6dB BANDWIDTH	9kHz
TEST MODE	A		

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.213	0.13	48.81	-	48.94	-	63.11	53.11	-14.17	-
2	0.310	0.15	50.27	43.09	50.42	43.24	59.97	49.97	-9.55	-6.73
3	0.455	0.17	43.02	-	43.19	-	56.79	46.79	-13.60	-
4	0.584	0.18	41.58	-	41.76	-	56.00	46.00	-14.24	-
5	0.869	0.21	36.00	-	36.21	-	56.00	46.00	-19.79	-
6	1.848	0.29	32.60	-	32.89	-	56.00	46.00	-23.11	-


- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



PHASE	Line 1	6dB BANDWIDTH	9kHz
TEST MODE	B		

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.150	0.16	49.12	-	49.28	-	66.00	56.00	-16.72	-
2	0.310	0.17	50.11	43.07	50.28	43.24	59.97	49.97	-9.69	-6.73
3	0.439	0.18	38.88	-	39.06	-	57.08	47.08	-18.02	-
4	0.623	0.20	40.78	-	40.98	-	56.00	46.00	-15.02	-
5	0.877	0.22	33.94	-	34.16	-	56.00	46.00	-21.84	-
6	1.504	0.27	29.96	-	30.23	-	56.00	46.00	-25.77	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



PHASE	Line 2	6dB BANDWIDTH	9kHz
TEST MODE	B		

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.162	0.13	50.26	-	50.39	-	65.38	55.38	-14.99	-
2	0.310	0.15	50.25	43.05	50.40	43.20	59.97	49.97	-9.57	-6.77
3	0.463	0.17	41.15	-	41.32	-	56.65	46.65	-15.33	-
4	0.588	0.18	41.80	-	41.98	-	56.00	46.00	-14.02	-
5	0.865	0.21	36.99	-	37.20	-	56.00	46.00	-18.80	-
6	1.398	0.25	34.05	-	34.30	-	56.00	46.00	-21.70	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



PHASE	Line 1	6dB BANDWIDTH	9kHz
TEST MODE	C		

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.166	0.16	50.87	-	51.03	-	65.18	55.18	-14.15	-
2	0.314	0.17	46.66	-	46.83	-	59.86	49.86	-13.03	-
3	0.564	0.19	38.96	-	39.15	-	56.00	46.00	-16.85	-
4	0.845	0.22	35.14	-	35.36	-	56.00	46.00	-20.64	-
5	1.645	0.28	29.54	-	29.82	-	56.00	46.00	-26.18	-
6	13.613	0.46	39.29	-	39.75	-	60.00	50.00	-20.25	-

- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




PHASE	Line 2	6dB BANDWIDTH	9kHz
TEST MODE	C		

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.173	0.13	48.81	-	48.94	-	64.79	54.79	-15.86	-
2	0.236	0.14	44.86	-	45.00	-	62.24	52.24	-17.24	-
3	0.642	0.18	40.81	-	40.99	-	56.00	46.00	-15.01	-
4	1.465	0.26	33.76	-	34.02	-	56.00	46.00	-21.98	-
5	3.152	0.33	26.51	-	26.84	-	56.00	46.00	-29.16	-
6	13.676	0.60	39.28	-	39.88	-	60.00	50.00	-20.12	-

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
R&S SPECTRUM ANALYZER	FSP40	100039	Jan. 11, 2010	Jan. 10, 2011

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100kHz RBW and 100kHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation.

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 TEST RESULTS

802.11b

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	12.57	0.5	PASS
6	2437	12.10	0.5	PASS
11	2462	12.12	0.5	PASS


CH 1



802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	16.46	0.5	PASS
6	2437	16.43	0.5	PASS
11	2462	16.44	0.5	PASS


CH 1



802.11n (20MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	17.70	0.5	PASS
6	2437	17.64	0.5	PASS
11	2462	17.67	0.5	PASS


CH 1



802.11n (40MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2422	36.47	0.5	PASS
4	2437	36.45	0.5	PASS
7	2452	36.46	0.5	PASS

CH 1



4.4 MAXIMUM OUTPUT POWER

4.4.1 LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT

The Maximum Output Power Measurement is 30dBm.

4.4.2 INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
High Speed Peak Power Meter	ML2495A	0842014	Apr. 21, 2010	Apr. 20, 2011
Power Sensor	MA2411B	0738404	Apr. 21, 2010	Apr. 20, 2011

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Measurement Bandwidth of ML2495A is 65MHz greater than 6dB bandwidth of emission.


4.4.3 TEST PROCEDURES

A power sensor was used on the output port of the EUT. A power meter was used to read the response of the power sensor. Record the power level.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation.

4.4.5 TEST SETUP



4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6.

4.4.7 TEST RESULTS

802.11b

CHAN.	CHANNEL FREQUENCY (MHz)	POWER OUTPUT (mW)	POWER OUTPUT (dBm)	POWER LIMIT (dBm)	PASS/FAIL
1	2412	91.2	19.6	30	PASS
6	2437	89.1	19.5	30	PASS
11	2462	87.1	19.4	30	PASS

802.11g

CHAN.	CHANNEL FREQUENCY (MHz)	POWER OUTPUT (mW)	POWER OUTPUT (dBm)	POWER LIMIT (dBm)	PASS/FAIL
1	2412	147.9	21.7	30	PASS
6	2437	162.2	22.1	30	PASS
11	2462	169.8	22.3	30	PASS

802.11n (20MHz)

CHAN.	CHANNEL FREQUENCY (MHz)	POWER OUTPUT (mW)	POWER OUTPUT (dBm)	POWER LIMIT (dBm)	PASS/FAIL
1	2412	107.2	20.3	30	PASS
6	2437	114.8	20.6	30	PASS
11	2462	112.2	20.5	30	PASS

802.11n (40MHz)

CHAN.	CHANNEL FREQUENCY (MHz)	POWER OUTPUT (mW)	POWER OUTPUT (dBm)	POWER LIMIT (dBm)	PASS/FAIL
1	2422	45.7	16.6	30	PASS
4	2437	44.7	16.5	30	PASS
7	2452	43.7	16.4	30	PASS

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
R&S SPECTRUM ANALYZER	FSP40	100039	Jan. 11, 2010	Jan. 10, 2011

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.5.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3kHz RBW and 30kHz VBW, set sweep time = span/3kHz. The power spectral density was measured and recorded.

The sweep time is allowed to be longer than span/3kHz for a full response of the mixer in the spectrum analyzer.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation.

4.5.5 TEST SETUP



4.5.6 EUT OPERATING CONDITION


Same as Item 4.3.6.

4.5.7 TEST RESULTS

802.11b

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3 kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-5.5	8	PASS
6	2437	-5.6	8	PASS
11	2462	-5.5	8	PASS


CH 1



802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3 kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-11.6	8	PASS
6	2437	-11.1	8	PASS
11	2462	-10.8	8	PASS


CH 11



802.11n (20MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3 kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-13.5	8	PASS
6	2437	-13.0	8	PASS
11	2462	-13.2	8	PASS


CH 6



802.11n (40MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3 kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2422	-21.1	8	PASS
4	2437	-21.0	8	PASS
7	2452	-21.3	8	PASS

CH 4



4.6 BAND EDGES MEASUREMENT

4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
R&S SPECTRUM ANALYZER	FSP40	100039	Jan. 11, 2010	Jan. 10, 2011

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100kHz with suitable frequency span including 300kHz bandwidth from band edge. The band edges was measured and recorded.

The spectrum plots (Peak RBW =100kHz, VBW = 300kHz; Average RBW = 1MHz, VBW = 10Hz) are attached on the following pages.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation.

4.6.5 EUT OPERATING CONDITION

Same as Item 4.3.6.

4.6.6 TEST RESULTS

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement in part 15.247(d).

802.11b TEST MODE A

RESTRICT BAND (2310 ~ 2390 MHz)

FREQUENCY (MHz)	FUNDAMENTAL EMISSION (dBuV/m)	DELTA (dB)	MAXIMUM FIELD STRENGTH IN RESTRICT BAND (dBuV/m)	LIMIT (dBuV/m)
2412.00 (PK)	111.8	53.54	58.26	74.00
2412.00 (AV)	106.9	58.50	48.40	54.00

RESTRICT BAND (2483.5 ~ 2500 MHz)

FREQUENCY (MHz)	FUNDAMENTAL EMISSION (dBuV/m)	DELTA (dB)	MAXIMUM FIELD STRENGTH IN RESTRICT BAND (dBuV/m)	LIMIT (dBuV/m)
2462.00 (PK)	111.5	54.20	57.30	74.00
2462.00 (AV)	106.6	58.68	47.92	54.00

NOTE:

- Delta = Amplitude between the peak of the fundamental and the peak of the band edge emission. Please check following 3 pages.
- Maximum field strength in restrict band = Fundamental emission – Delta.

TEST MODE B

RESTRICT BAND (2310 ~ 2390 MHz)

FREQUENCY (MHz)	FUNDAMENTAL EMISSION (dBuV/m)	DELTA (dB)	MAXIMUM FIELD STRENGTH IN RESTRICT BAND (dBuV/m)	LIMIT (dBuV/m)
2412.00 (PK)	111.1	53.54	57.56	74.00
2412.00 (AV)	106.5	58.50	48.00	54.00

RESTRICT BAND (2483.5 ~ 2500 MHz)

FREQUENCY (MHz)	FUNDAMENTAL EMISSION (dBuV/m)	DELTA (dB)	MAXIMUM FIELD STRENGTH IN RESTRICT BAND (dBuV/m)	LIMIT (dBuV/m)
2462.00 (PK)	111.3	54.20	57.10	74.00
2462.00 (AV)	106.7	58.68	48.02	54.00

NOTE:

1. Delta = Amplitude between the peak of the fundamental and the peak of the band edge emission.
Please check following 3 pages.
2. Maximum field strength in restrict band = Fundamental emission – Delta.

TEST MODE C

RESTRICT BAND (2310 ~ 2390 MHz)

FREQUENCY (MHz)	FUNDAMENTAL EMISSION (dBuV/m)	DELTA (dB)	MAXIMUM FIELD STRENGTH IN RESTRICT BAND (dBuV/m)	LIMIT (dBuV/m)
2412.00 (PK)	111.0	53.54	57.46	74.00
2412.00 (AV)	107.1	58.50	48.60	54.00

RESTRICT BAND (2483.5 ~ 2500 MHz)

FREQUENCY (MHz)	FUNDAMENTAL EMISSION (dBuV/m)	DELTA (dB)	MAXIMUM FIELD STRENGTH IN RESTRICT BAND (dBuV/m)	LIMIT (dBuV/m)
2462.00 (PK)	111.5	54.20	57.30	74.00
2462.00 (AV)	107.4	58.68	48.72	54.00


NOTE:

1. Delta = Amplitude between the peak of the fundamental and the peak of the band edge emission. Please check following 3 pages.
2. Maximum field strength in restrict band = Fundamental emission – Delta.






A D T




A D T




A D T



A D T



A D T



A D T

802.11g

TEST MODE A

RESTRICT BAND (2310 ~ 2390 MHz)

FREQUENCY (MHz)	FUNDAMENTAL EMISSION (dBuV/m)	DELTA (dB)	MAXIMUM FIELD STRENGTH IN RESTRICT BAND (dBuV/m)	LIMIT (dBuV/m)
2412.00 (PK)	111.2	46.26	64.94	74.00
2412.00 (AV)	99.6	48.88	50.72	54.00

RESTRICT BAND (2483.5 ~ 2500 MHz)

FREQUENCY (MHz)	FUNDAMENTAL EMISSION (dBuV/m)	DELTA (dB)	MAXIMUM FIELD STRENGTH IN RESTRICT BAND (dBuV/m)	LIMIT (dBuV/m)
2462.00 (PK)	110.7	49.47	61.23	74.00
2462.00 (AV)	99.5	50.48	49.02	54.00

NOTE:

1. Delta = Amplitude between the peak of the fundamental and the peak of the band edge emission. Please check following 3 pages.
2. Maximum field strength in restrict band = Fundamental emission – Delta.

TEST MODE B

RESTRICT BAND (2310 ~ 2390 MHz)

FREQUENCY (MHz)	FUNDAMENTAL EMISSION (dBuV/m)	DELTA (dB)	MAXIMUM FIELD STRENGTH IN RESTRICT BAND (dBuV/m)	LIMIT (dBuV/m)
2412.00 (PK)	110.4	46.26	64.14	74.00
2412.00 (AV)	98.9	48.88	50.02	54.00

RESTRICT BAND (2483.5 ~ 2500 MHz)

FREQUENCY (MHz)	FUNDAMENTAL EMISSION (dBuV/m)	DELTA (dB)	MAXIMUM FIELD STRENGTH IN RESTRICT BAND (dBuV/m)	LIMIT (dBuV/m)
2462.00 (PK)	110.2	49.47	60.73	74.00
2462.00 (AV)	98.7	50.48	48.22	54.00

NOTE:

1. Delta = Amplitude between the peak of the fundamental and the peak of the band edge emission.
Please check following 3 pages.
2. Maximum field strength in restrict band = Fundamental emission – Delta.

TEST MODE C

RESTRICT BAND (2310 ~ 2390 MHz)

FREQUENCY (MHz)	FUNDAMENTAL EMISSION (dBuV/m)	DELTA (dB)	MAXIMUM FIELD STRENGTH IN RESTRICT BAND (dBuV/m)	LIMIT (dBuV/m)
2412.00 (PK)	108.6	46.26	62.34	74.00
2412.00 (AV)	98.7	48.88	49.82	54.00

RESTRICT BAND (2483.5 ~ 2500 MHz)


FREQUENCY (MHz)	FUNDAMENTAL EMISSION (dBuV/m)	DELTA (dB)	MAXIMUM FIELD STRENGTH IN RESTRICT BAND (dBuV/m)	LIMIT (dBuV/m)
2462.00 (PK)	109.5	49.47	60.03	74.00
2462.00 (AV)	99.5	50.48	49.02	54.00

NOTE:


- Delta = Amplitude between the peak of the fundamental and the peak of the band edge emission.
Please check following 3 pages.
- Maximum field strength in restrict band = Fundamental emission – Delta.



A D T





A D T



A D T




A D T






A D T



A D T



A D T

802.11n (20MHz)

TEST MODE A

RESTRICT BAND (2310 ~ 2390 MHz)

FREQUENCY (MHz)	FUNDAMENTAL EMISSION (dBuV/m)	DELTA (dB)	MAXIMUM FIELD STRENGTH IN RESTRICT BAND (dBuV/m)	LIMIT (dBuV/m)
2412.00 (PK)	109.3	45.72	63.58	74.00
2412.00 (AV)	97.4	48.71	48.69	54.00

RESTRICT BAND (2483.5 ~ 2500 MHz)

FREQUENCY (MHz)	FUNDAMENTAL EMISSION (dBuV/m)	DELTA (dB)	MAXIMUM FIELD STRENGTH IN RESTRICT BAND (dBuV/m)	LIMIT (dBuV/m)
2462.00 (PK)	108.5	45.77	62.73	74.00
2462.00 (AV)	96.7	49.45	47.25	54.00

NOTE:

1. Delta = Amplitude between the peak of the fundamental and the peak of the band edge emission.
Please check following 3 pages.
2. Maximum field strength in restrict band = Fundamental emission – Delta.

TEST MODE B

RESTRICT BAND (2310 ~ 2390 MHz)

FREQUENCY (MHz)	FUNDAMENTAL EMISSION (dBuV/m)	DELTA (dB)	MAXIMUM FIELD STRENGTH IN RESTRICT BAND (dBuV/m)	LIMIT (dBuV/m)
2412.00 (PK)	108.8	45.72	63.08	74.00
2412.00 (AV)	96.9	48.71	48.19	54.00

RESTRICT BAND (2483.5 ~ 2500 MHz)

FREQUENCY (MHz)	FUNDAMENTAL EMISSION (dBuV/m)	DELTA (dB)	MAXIMUM FIELD STRENGTH IN RESTRICT BAND (dBuV/m)	LIMIT (dBuV/m)
2462.00 (PK)	108.6	45.77	62.83	74.00
2462.00 (AV)	96.7	49.45	47.25	54.00

NOTE:

1. Delta = Amplitude between the peak of the fundamental and the peak of the band edge emission.
Please check following 3 pages.
2. Maximum field strength in restrict band = Fundamental emission – Delta.

TEST MODE C

RESTRICT BAND (2310 ~ 2390 MHz)

FREQUENCY (MHz)	FUNDAMENTAL EMISSION (dBuV/m)	DELTA (dB)	MAXIMUM FIELD STRENGTH IN RESTRICT BAND (dBuV/m)	LIMIT (dBuV/m)
2412.00 (PK)	107.4	45.72	61.68	74.00
2412.00 (AV)	97.4	48.71	48.69	54.00

RESTRICT BAND (2483.5 ~ 2500 MHz)


FREQUENCY (MHz)	FUNDAMENTAL EMISSION (dBuV/m)	DELTA (dB)	MAXIMUM FIELD STRENGTH IN RESTRICT BAND (dBuV/m)	LIMIT (dBuV/m)
2462.00 (PK)	108.0	45.77	62.23	74.00
2462.00 (AV)	98.1	49.45	48.65	54.00

NOTE:


1. Delta = Amplitude between the peak of the fundamental and the peak of the band edge emission.
Please check following 3 pages.
2. Maximum field strength in restrict band = Fundamental emission – Delta.



A D T




A D T




A D T



A D T



A D T



A D T



802.11n (40MHz)

TEST MODE A

RESTRICT BAND (2310 ~ 2390 MHz)

FREQUENCY (MHz)	FUNDAMENTAL EMISSION (dBuV/m)	DELTA (dB)	MAXIMUM FIELD STRENGTH IN RESTRICT BAND (dBuV/m)	LIMIT (dBuV/m)
2422.00 (PK)	102.6	38.66	63.94	74.00
2422.00 (AV)	90.7	42.35	48.35	54.00

RESTRICT BAND (2483.5 ~ 2500 MHz)

FREQUENCY (MHz)	FUNDAMENTAL EMISSION (dBuV/m)	DELTA (dB)	MAXIMUM FIELD STRENGTH IN RESTRICT BAND (dBuV/m)	LIMIT (dBuV/m)
2452.00 (PK)	102.5	39.74	62.76	74.00
2452.00 (AV)	90.3	42.79	47.51	54.00

NOTE:

- Delta = Amplitude between the peak of the fundamental and the peak of the band edge emission. Please check following 3 pages.
- Maximum field strength in restrict band = Fundamental emission – Delta.

TEST MODE B

RESTRICT BAND (2310 ~ 2390 MHz)

FREQUENCY (MHz)	FUNDAMENTAL EMISSION (dBuV/m)	DELTA (dB)	MAXIMUM FIELD STRENGTH IN RESTRICT BAND (dBuV/m)	LIMIT (dBuV/m)
2422.00 (PK)	102.4	38.66	63.74	74.00
2422.00 (AV)	90.4	42.35	48.05	54.00

RESTRICT BAND (2483.5 ~ 2500 MHz)

FREQUENCY (MHz)	FUNDAMENTAL EMISSION (dBuV/m)	DELTA (dB)	MAXIMUM FIELD STRENGTH IN RESTRICT BAND (dBuV/m)	LIMIT (dBuV/m)
2452.00 (PK)	102.2	39.74	62.46	74.00
2452.00 (AV)	90.2	42.79	47.41	54.00

NOTE:

1. Delta = Amplitude between the peak of the fundamental and the peak of the band edge emission. Please check following 3 pages.
2. Maximum field strength in restrict band = Fundamental emission – Delta.

TEST MODE C

RESTRICT BAND (2310 ~ 2390 MHz)

FREQUENCY (MHz)	FUNDAMENTAL EMISSION (dBuV/m)	DELTA (dB)	MAXIMUM FIELD STRENGTH IN RESTRICT BAND (dBuV/m)	LIMIT (dBuV/m)
2422.00 (PK)	100.5	38.66	61.84	74.00
2422.00 (AV)	90.4	42.35	48.05	54.00

RESTRICT BAND (2483.5 ~ 2500 MHz)


FREQUENCY (MHz)	FUNDAMENTAL EMISSION (dBuV/m)	DELTA (dB)	MAXIMUM FIELD STRENGTH IN RESTRICT BAND (dBuV/m)	LIMIT (dBuV/m)
2452.00 (PK)	101.1	39.74	61.36	74.00
2452.00 (AV)	91.0	42.79	48.21	54.00

NOTE:


- Delta = Amplitude between the peak of the fundamental and the peak of the band edge emission.
Please check following 3 pages.
- Maximum field strength in restrict band = Fundamental emission – Delta.



A D T





A D T



A D T



A D T



5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

6. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

www.adt.com.tw/index.5/phtml. If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/TPCI Lab:

Tel: 886-3-3183232

Fax: 886-3-3185050

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.

7. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

--- END ---