

MPE CALCULATION**FCC ID : TMB-CONN2000****RF Exposure Requirements:**

47 CFR §1.1307(b)

RF Radiation Exposure Limits:

47 CFR §1.1310

RF Radiation Exposure Guidelines:

FCC OST/OET Bulletin Number 65

EUT Frequency Band: 2412-2462 MHz, 5260-5700 MHz, 5745-5825 MHz**Limits for General Population/Uncontrolled Exposure in the band of:**

Frequency Range (MHz)	Power Density (mW/cm ²)
1,500-100,000	1.0
300-1,500	f/1500

Equation: $S = PG / 4\pi R^2$ or $R = \sqrt{PG / 4\pi S}$

Where, S = Power Density

P = Power Input to Antenna

G = Antenna Gain

R = distance to the center of radiated antenna

Product Name : SecureMesh Wan Connector**Model: CONN-2000**

Prediction distance 65cm

(WLAN 2.4GHz): Output Power = 22.73 dBm, Antenna Gain = 2 dBi, Power density = 0.005598 mW/cm²

Type	CH Freq (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Tune-Up Tolerance	Max Power (dBm)	Measurement Distance (cm)	Calculated MPE (mW/cm ²)	MPE Limit (mW/cm ²)	Pass/Fail
WLAN 802.11n HT20 2.4 GHz	2412	22.23	2	±0.5dB	24.73	65	0.005598	1	Pass

(WLAN 5GHz): Output Power = 29.55 dBm, Antenna Gain = 17 dBi, Power density = 0.85122 mW/cm²

Type	CH Freq (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Tune-Up Tolerance	Max Power (dBm)	Measurement Distance (cm)	Calculated MPE (mW/cm ²)	MPE Limit (mW/cm ²)	Pass/Fail
WLAN 802.11HT40 5 GHz	5755	29.05	17	±0.5dB	46.55	65	0.85122	1	Pass

If WLAN (2.4GHz) and WLAN (5GHz) transmit simultaneously.

Total MPE = 0.5598% + 85.122% = 85.68%

The Above Result had shown that the Device complied with MPE requirement.

Gary Chou

Completed By: Gary Chou

SIEMIC, Inc

775 Montague Expressway, Milpitas, CA 95035

Phone: (408) 526-1188

Date: 03/22/2019