

# Johnson Health Tech. Co., Ltd.

## MPE ASSESSMENT REPORT

**Report Type:**

FCC Part §2.1091 and §1.1307(b) assessment report

**Model:**

LED-C, GTLED-C

**REPORT NUMBER:**

191201856SHA-003

**ISSUE DATE:**

January 9, 2025

**DOCUMENT CONTROL NUMBER:**

TTRFFCCMPE-01\_V1 © 2018 Intertek



**Applicant:** **Johnson Health Tech. Co., Ltd.**  
**No. 999, Sec. 2, Dongda Rd., Daya Dist., Taichung City 428**

**Manufacturer:** **Johnson Health Tech. Co., Ltd.**  
**No. 999, Sec. 2, Dongda Rd., Daya Dist., Taichung City 428**

**FCC ID:** **TN7LEDRF-02**

**SUMMARY:**

The equipment complies with the requirements according to the following standard(s) or Specification:

KDB447498 D01 General RF Exposure Guidance v06

FCC Part2.1091, FCC Part1.1307(b)

**PREPARED BY:**

---

Project Engineer  
Eric Li**REVIEWED BY:**

---

Reviewer  
Wakeyou Wang

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

**TEST REPORT****Revision History**

Report No.	Version	Description	Issued Date
191201856SHA-003	Rev. 01	Initial issue of report	January 9, 2025

**TEST REPORT**

## 1 GENERAL INFORMATION

### 1.1 Description of Equipment Under Test (EUT)

Product name:	Fitness Equipment LED Console
Type/Model:	LED-C, GTLED-C
Description of EUT:	BL-8811AF1
Rating:	EUT is control meters, it can match with Fitness Equipment. There are two models, the only difference is overlay, so we test the model of LED-C as representative and list the worst results in this report.
EUT type:	<input checked="" type="checkbox"/> Table top <input type="checkbox"/> Floor standing
Software Version:	/
Hardware Version:	/
Sample received date:	November 22, 2024
Date of test:	November 22, 2024~ November 29, 2024

### 1.2 Technical Specification

Frequency Band:	2400MHz ~ 2483.5MHz
Support Standards:	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n(HT20), IEEE 802.11n(HT40)
Operating Frequency:	2412MHz to 2462MHz for IEEE 802.11b/g/n(HT20) 2422MHz to 2452MHz for IEEE 802.11n(HT40)
Type of Modulation:	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64-QAM, 16-QAM, QPSK, BPSK) IEEE 802.11n(HT20): OFDM (64-QAM, 16-QAM, QPSK, BPSK) IEEE 802.11n(HT40): OFDM (64-QAM, 16-QAM, QPSK, BPSK)
Channel Number:	11 Channels for 802.11b, 802.11g and 802.11n(HT20) 7 Channels for 802.11n(HT40)
Channel Separation:	5 MHz
Antenna Information:	PCB Antenna, gain is 4.0dBi

Frequency Range:	5150 ~ 5250MHz
Support Standards:	802.11a, 802.11n(HT20), 802.11n(HT40), 802.11ac(VHT20), 802.11ac(VHT40), 802.11ac(VHT80)
Type of Modulation:	OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)
Channel Number:	For 5150 ~ 5250MHz band: Channel 36 - 48
Antenna Information:	PCB Antenna, gain is 4.0dBi

Frequency Range:	13.56 MHz ~ 13.56 MHz
Type of Modulation:	ASK
Antenna Information:	Refer to modular test report

**TEST REPORT****1.3 Description of Test Facility**

Name:	Intertek Testing Services (Shanghai FTZ) Co., Ltd.
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L21189
	FCC Accredited Lab Designation Number: CN0175
	IC Registration Lab CAB identifier.: CN0014
	VCCI Registration Lab Registration No.: R-14243, G-10845, C-14723, T-12252
	A2LA Accreditation Lab Certificate Number: 3309.02

**TEST REPORT****2 MPE Assessment****Test result:** Pass**2.1 MPE Assessment Limit**

Mobile device exposure for standalone operations:

Frequency range	E-field strength (V/m)	H-field strength (A/m)	B-field (uT)	Equivalent plane wave power density $S_{eq}$ (W/m <sup>2</sup> )
0-1 Hz	-	$3,2 \times 10^4$	$4 \times 10^4$	-
1-8 Hz	10 000	$3,2 \times 10^4/f^2$	$4 \times 10^4/f^2$	-
8-25 Hz	10 000	$4 000/f$	$5 000/f$	-
0,025-0,8 kHz	250/f	4/f	5/f	-
0,8-3 kHz	250/f	5	6,25	-
3-150 kHz	87	5	6,25	-
0,15-1 MHz	87	0,73/f	0,92/f	-
1-10 MHz	$87/f^{1/2}$	0,73/f	0,92/f	-
10-400 MHz	28	0,073	0,092	2
400-2 000 MHz	$1,375 f^{1/2}$	$0,0037 f^{1/2}$	$0,0046 f^{1/2}$	$f/200$
2-300 GHz	61	0,16	0,20	10

Mobile device exposure for simultaneous transmission operations: **the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in a host device is  $\leq 1.0$**

**TEST REPORT****2.2 Assessment Results**

Power density (S) is calculated according to the formula:

$$S = PG / (4\pi R^2)$$

Where S = power density in mW/cm<sup>2</sup>

P = Radiated transmit power in mW

G = numeric gain of transmit antenna

R = distance (cm)

The product contains three certified module, the certified module's FCC ID number and relevant MPE report number are as following:

Certified Module FCC ID:	Model number	Relevant report
2AO06-WLT7150	WLT7150	BTL-FCCP-1-2404H025

As we can see from the test report BTL-FCCP-1-2404H025:

$$63.82 \text{ dBuV/m} @ 3 \text{ m}, @ 20 \text{ cm} = @ 3 \text{ m} + 40 \log(3/0.2) = 110.86 \text{ dBuV/m} = 0.35 \text{ V/m} < 60.77 \text{ V/m}.$$

As we can see from the test report 191201856SHA-001, 191201856SHA-002:

The calculations in the table below use the highest gain of antenna for client EUT. These calculations represent worst case in terms of the exposure levels.

The WiFi can support simultaneous transmission.

Mode	Frequency band	Max Power	Antenna Gain	R	S	Limits
	(MHz)	dBm	dBi	(cm)	(mW/cm <sup>2</sup> )	(mW/cm <sup>2</sup> )
WiFi BL-R8811AF1	2400 -2483.5	14.90	4.0	20	0.0155	1
	5150-5250	18.10	4.0	20	0.0323	1

Note: 1 mW/cm<sup>2</sup> from 1.310 Table 1

The sum of the MPE ratios for all simultaneously transmitting is  $0.0155/1 + 0.0323/1 + 0.35/60.77 = 0.0536 \leq 1.0$

For the device can support simultaneous transmission, according to 447498 D01 General RF Exposure Guidance v06,

**TEST REPORT****Appendix I**

Definition below must be outlined in the User Manual:

To satisfy FCC RF exposure requirements, a separation distance of 20 cm or more should be maintained between the antenna of this device and persons during device operation.

To ensure compliance, operations at closer than this distance is not recommended.

\*\*\*\*\* END \*\*\*\*\*