TEST REPORT

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-5008-1021 FAX: 82-505-299-8311 www.kctl.co.kr

Page (1) of (49)

Report No.:

KR16-SPF0002



1. Client

Name

: Starnex Co., Ltd.

Address

#201, Kolon Digital Tower Aston, 212, Gasan Digital 1-ro,

Geumcheon-gu, Seoul, South Korea

Date of Receipt

: 2016-10-04

2. Use of Report

3. Name of Product and Model : Wearable digital communicator / DOMINO S1

4. Manufacturer and Country of Origin: Starnex Co., Ltd. / Korea

5. FCC ID

: TN9DOMINOS1

6. Date of Test

: 2016-10-07

7. Test method used : IEEE 1528-2013, ANSI/IEEE C95.1, KDB Publication

8. Test Results

: Refer to the test result in the test report

Tested by

Affirmation

Name: Kyounghoo, Min (Signature)

Technical Manager

Name: Cheonsig, Choi (Signature)

2016-10-19

KCTL Inc.

As a test result of the sample which was submitted from the client, this report does not guarantee the whole product quality. This test report should not be used and copied without a written agreement by KCTL Inc.

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-5008-1021 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR16-SPF0002

Page (2) of (49)



REPORT REVISION HISTORY

Date	Revision	Page No
2016-10-19	Originally issued	-

This report shall not be reproduced except in full, without the written approval of KCTL Inc. This document may be altered or revised by KCTL Inc. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KCTL Inc. will constitute fraud and shall nullify the document.

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-5008-1021 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR16-SPF0002

Page (3) of (49)



Contents

1. Client information	4
2. Laboratory information	5
3. Identification of Sample	6
4.Test Result Summary	8
5. Report Overview	8
6. Test Lab Declaration or Comments	8
7. Applicant Declaration or Comments	8
9. The SAR Measurement System	10
10. System Verification	14
11. Operation Configurations	16
12. SAR Measurement Procedures	17
13. Test Equipment Information	
14. RF Average Conducted Output Power	20
15. SAR Test Results	
16. Test System Verification Results	
17. Test Results	23
Appendix A. Calibration certificate	24
Appendix B. EUT Photo	43
Appendix C. Test Photo	46

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-5008-1021 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR16-SPF0002

Page (4) of (49)



1. Client information

Client: Starnex Co., Ltd.

Address: #201, Kolon Digital Tower Aston, 212, Gasan Digital 1-ro,

Geumcheon-gu, Seoul, South Korea

Telephone: +82-2-837-9700

Fax: +82-2-2082-8585

E-mail: csw324@starnex.co.kr

Contact name: Seokwoo Choi

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-5008-1021 FAX: 82-505-299-8311 www.kctl.co.kr

Report No.: KR16-SPF0002

Page (5) of (49)



2. Laboratory information

Address

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea

TEL: 82 70 5008 1021 FAX: 82 505 299 8311

Certificate

KOLAS No.: KT231


FCC Site Designation No.: KR0040

FCC Site Registration No.: 687132

VCCI Site Registration No.: R-3327, G-198, C-3706, T-1849

IC Site Registration No.: 8035A-2

SITE MAP



65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-5008-1021 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR16-SPF0002 Page (6) of (49)



3. Identification of Sample


EUT Type	Wearable digital communicator
Brand Name	Starnex Co., Ltd.
Mode of Operation	Half, Hi-fi
Model Number	DOMINO S1
Serial Number	2415b305566eb783
Max. Power	27 dBm
Tx Freq.Range	902.6 MHz ~ 927.5 MHz
Rx Freq.Range	902.6 MHz ~ 927.5 MHz
Antenna Type	FPCB Antenna
Antenna Size	23.16 mm x 24.10 mm
Normal Voltage	DC 5 V
H/W Version	V05
S/W Version	01.02.25

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-5008-1021 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR16-SPF0002

Page (7) of (49)



3.1 Antenna Diagram



65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-5008-1021 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR16-SPF0002

Page (8) of (49)



4.Test Result Summary

4.1 Body SAR

Frequency (MHz)	Average Power (dBm)	Max. tune up power (dBm)	Scaling Factor	EUT Position	Distance (mm)	Measured 1 g SAR (W/kg) Duty 100 %	Measured 1 g SAR (W/kg) Duty 50 %	Scaled 1 g SAR (W/kg)
902.6	25.79	27.00	1.321	Front	0	0.338	0.169	0.223

^{*} Contain the results of the worst test SAR including battery.

5. Report Overview

This report details the results of testing carried out on the samples listed in section 3, the results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this test report is used in any configuration other than that detailed in the test report, the manufacturer must ensure the new configuration complies with all relevant standards and certification requirements. Any mention of KCTL Inc. Wireless lab or testing done by KCTL Inc. Wireless lab made in connection with the distribution or use of the tested product must be approved in writing by KCTL Inc. Wireless lab.

6. Test Lab Declaration or Comments

None

7. Applicant Declaration or Comments

None

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-5008-1021 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR16-SPF0002

Page (9) of (49)



8. Measurement Uncertainty

All measurements and results are recorded and maintained at the laboratory performing the tests and measurement uncertainties are taken into account when comparing measurements to pass/ fail criteria.

SAR Measurement Uncertainty


A	ь	С	D	e = f(d,k)	g	$i = c \times g/e$	k
Source of Uncertainty	Description IEEE P1528 BODY	Tolerance/ Uncertainty value	Probability Distribution	Div.	Cl	Standard uncertainty	Vi or Veff
	(0.3 ~ 3 GHz)	± %			(1 g)	± %, (1 g)	
Measurement System	ACT TO SHE						
Probe calibration(k=1)	E.2.1	6.30	N	1	1	6.30	60
Axial isotropy	E.2.2	0.50	R	1.73	0.71	0.20	10
Hemispherical isotropy	E.2.2	2.60	R	1.73	0.71	1.06	60
Linearity	E.2.4	0.60	R	1.73	1	0.35	40
Boundary effect	E.2.3	1.00	R	1.73	1	0.58	100
System detection limits	E.2.5	1.00	R	1.73	1	0.58	60
Readout electronics	E.2.6	0.30	N	1	1	0.30	10
Response time	E.2.7	0.80	R	1.73	1	0.46	60
Integration time	E.2.8	2.60	R	1.73	1	1.50	
RF ambient conditions-noise	E.6.1	3.00	R	1.73	1	1.73	100
RF ambient conditions-	E.6.1	3.00	R	1.73	1	1.73	wo
Probe positioner mechanical tolerance	E.6.2	0.40	R	1.73	Û	+0.23	-
Probe positioning with respect to phantom shell	E.6.3	2.90	R	1.73	1	1.67	8
Extrapolation, interpolation, and integration algorithms for max. SAR evaluation	E.5	2,00	R	1.73	i.	1.15	
Test Sample Related				3323	Maril Fra	I had been	
Test sample positioning	E.4.2	4,71	N	- 1	1	4.71	9
Device holder uncertainty	E.4.1	3.60	N	1	1	3.60	5
Output power variation—SAR drift measurement	6.6.2	5.00	R	1.73	1	2.89	
Phantom and Tissue Par	rameters		THE VIEW	SVO ALI			
Phantom uncertainty (shape and thickness tolerances)	E.3.1	7.50	R	1.73	1	4.33	00
Liquid conductivity-measurement uncertainty	E.3.3	1.53	N	1	0.64	0.98	5
Liquid permittivity-measurement uncertainty	E.3.3	3.07	N	1	0.6	1.84	5
Liquid conductivity-deviation from target values	E.3.2	5.00	R	1.73	0.64	1.85	***
Liquid permittivity-deviation from target values	E.3.2	5.00	R	1.73	0.6	1.73	80
Combined standard uncertainty				RSS		11.29	183
Expanded uncertainty				Great Control		V CONTRACTOR OF THE PARTY OF TH	
(95% CONFIDENCE INTERVAL)				K=2		22.57	

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-5008-1021 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR16-SPF0002

Page (10) of (49)



9. The SAR Measurement System



<SAR System Configuration>

- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension foraccommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- Data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, ADconversion,offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered withstandard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digitalcommunication to the DAE. To use optical surface detection, a special version of the EOC is required. TheEOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering,
 control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-5008-1021 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR16-SPF0002

Page (11) of (49)



9.1 Isotropic E-field Probe

ES3DV3 Isotropic E-Field Probe for Dosimetric Measurements					
	Symmetrical design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)				
Calibration	ISO/IEC 17025 <u>calibration service</u> available.				
Frequency	10 MHz to 4 GHz; Linearity: ± 0.2 dB (30 MHz to 4 GHz)				
Directivity	± 0.2 dB in TSL (rotation around probe axis) ± 0.3 dB in TSL (rotation normal to probe axis)				
Dynamic Range	$5 \mu W/g$ to > 100 mW/g; Linearity: \pm 0.2 dB				
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 3.9 mm (Body: 12 mm) Distance from probe tip to dipole centers: 2.0 mm				
Application	General dosimetry up to 4 GHz Dosimetry in strong gradient fields Compliance tests of mobile phones				
Compatibility	DASY3, DASY4, DASY52 SAR and higher, EASY4/MRI				

EX3DV4 Smallest Isotropic E-Field Probe for Dosimetric Measurements (Preliminary Specifications)					
	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)				
Calibration	ISO/IEC 17025 calibration service available.				
Frequency	10 MHz to > 6 GHz Linearity: ± 0.2 dB (30 MHz to 6 GHz)				
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)				
Dynamic Range	10 μ W/g to > 100 mW/g Linearity: \pm 0.2 dB (noise: typically < 1 μ W/g)				
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm				
Application	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields); the only probe that enables compliance testing for frequencies up to 6 GHz with precision of better 30%.				
Compatibility	DASY3, DASY4, DASY52 SAR and higher, EASY4/MRI				

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-5008-1021 FAX: 82-505-299-8311 www.kctl.co.kr

Page (12) of (49)

Report No.:

KR16-SPF0002



9.2 Phantom

Twin SAM	
	The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot. Twin SAM V5.0 has the same shell geometry and is manufactured from the same material as Twin SAM V4.0, but has reinforced top structure.
Material	Vinylester, glass fiber reinforced (VE-GF)
Liquid Compatibility	Compatible with all SPEAG tissue simulating liquids (incl. DGBE type)
Shell Thickness	2 ± 0.2 mm (6 ± 0.2 mm at ear point)
Dimensions (incl. Wooden Support)	Length: 1000 mm Width: 500 mm Height: adjustable feet
Filling Volume	approx. 25 liters
Wooden Support	SPEAG standard phantom table
Accessories	Mounting Device and Adaptors

ELI	
	Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.
	ELI V5.0 has the same shell geometry and is manufactured from the same material as ELI4, but has reinforced top structure. ELI V6.0, released in August 2014, has the same shell geometry as ELI4 but offers increased longterm stability.
Material	Vinylester, glass fiber reinforced (VE-GF)
Liquid Compatibility	Compatible with all SPEAG tissue simulating liquids (incl. DGBE type)
Shell Thickness	2.0 ± 0.2 mm (bottom plate)
Dimensions	Major axis: 600 mm Minor axis: 400 mm
Filling Volume	approx. 30 liters
Wooden Support	SPEAG standard phantom table
Accessories	Mounting Device and Adaptors

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-5008-1021 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR16-SPF0002

Page (13) of (49)



9.3 Device Holder for Transmitters

Mounting Devices and Adaptors



Mounting Device for Hand-Held Transmitters

MD4HHTV5 - Mounting Device for Hand-Held Transmitters

In combination with the Twin SAM V5.0/V5.0c or ELI Phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat).

Material: Polyoxymethylene (POM)



MD4LAPV5 - Mounting Device for Laptops and other Body-Worn Transmitters

In combination with the Twin SAM V5.0/V5.0c or ELI Phantoms, the Mounting Device (Body-Worn) enables testing of ransmitter devices according to IEC 62209-2 specifications. The device holder can be locked for positioning at flat phantom section.

Material: Polyoxymethylene (POM), PET-G, Foam

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-5008-1021 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR16-SPF0002

Page (14) of (49)



10. System Verification

10.1 Tissue Verification

The dielectric properties for this Tissue Simulant Liquids were measured by using the SPEAG Model DAK3.5 Dielectric Probe in conjunction with Agilent E5071B Network Analyzer (300 kHz - 8 500 MHz). The Conductivity (σ) and Permittivity (σ) are listed in Table 1.For the SAR measurement given in this report.

Freq. (MHz)	Tissue Type	Limit/Measured	Permittivity (ρ)	Conductivity (σ)	Temp (°C)	
		Recommended Limit	55.00 ± 5 %	1.05 ± 5 %	22 ± 2	
900	MSL	Recommended Limit	(52.25 ~ 57.75)	(1.00 ~ 1.10)	22 ± 2	
		Measured, 2016-10-07	54.60	1.04	22.07	
	902.6 MSL	Dagammandad Limit	55.00 ± 5 %	1.05 ± 5 %	22 ± 2	
902.6		Recommended Limit	(52.25 ~ 57.75)	(1.00 ~ 1.10)	22 ± 2	
		Measured, 2016-10-07	54.62	1.04	22.07	
	MSL	Recommended Limit	55.00 ± 5 %	1.06 ± 5 %	22 ± 2	
915		Recommended Limit	(52.25 ~ 57.75)	(1.01 ~ 1.11)	22 ± 2	
		Measured, 2016-10-07	54.49	1.05	22.07	
	927.5 MSL	De common de del insit	54.98 ± 5 %	1.07 ± 5 %	00 0	
927.5		Recommended Limit	(52.23 ~ 57.73)	(1.02 ~ 1.12)	22 ± 2	
		Measured, 2016-10-07	54.46	1.07	22.07	

<Table 1.Measurement result of Tissue electric parameters>


65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-5008-1021 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR16-SPF0002

Page (15) of (49)



10.2 Test System Verification

The microwave circuit arrangement for system verification is sketched below picture. The daily system accuracy verification occurs within the flat section of the SAM phantom. A SAR measurement was performed to see if the measured SAR was within \pm 10% from the target SAR values. These tests were done at 900 MHz. The tests were conducted on the samedays as the measurement of the EUT. The obtained results from the system acc uracy verification are displayed in the table Table 2 (A power level of 250mW was input to the dipole antenna). During the tests, the ambient temperature of the laboratory was in the range (22 \pm 2) °C, the relative humidity was in the range (50 \pm 20)% and the liquid depth above the ear/grid reference points was above 15 cm in all the cases. It is seen that the system is operating within its specification, as the results are within acceptable tolerance of the reference values.



Validation	Dipole Ant.	Frequency	Tissue	Limit/Measurement (Normalized to 1 W)		
Kit	S/N	(MHz)	Туре		1 g	10 g
				Recommended Limit	11.10 ± 10 %	7.20 ± 10 %
D900V2	1d138	900	MSL	(Normalized)	(9.99 ~ 12.21)	(6.48 ~ 7.92)
				Measured, 2016-10-07	11.04	7.24

<Table 2.Test System Verification Result>

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-5008-1021 FAX: 82-505-299-8311 www.kctl.co.kr

KR16-SPF0002

Report No.:

Page (16) of (49)



11. Operation Configurations

Measurements were performed at the lowest, middle and highest channels of the operating band. The EUT was set to maximum power level during all tests and at the beginning of each test the battery was fully charged.

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-5008-1021 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR16-SPF0002

Page (17) of (49)



12. SAR Measurement Procedures

Step 1: Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The Minimum distance of probe sensors to surfacedetermines the closest measurement point to phantom surface. The minimum distance of probe sensors to surface is 2 mm. This distance cannot be smaller than the Distance of sensor calibration points toprobe tip as defined in the probe properties.

Step 2: Area Scan

The Area Scan is used as a fast scan in two dimensions to find the area of high field values, before doing fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASYsoftware can find the maximum locations even in relatively coarse grids. When an Area Scan hasmeasured all reachable points, it computes the field maximal found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE Standard 1528 and IEC 62209 standards, whereby 3 dB is arequirement when compliance is assessed in accordance with the ARIB standard (Japan). If only one Zoom Scan follows the Area Scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of Zoom Scans has to be increased accordingly.

Area Scan Parameters extracted from KDB 865664 D01 SAR Measument 100 MHz to 6 GHz v01r04.

•	≤3 GHz	> 3 GHz	
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5 \text{ mm}$	
Maximum probe angle from probe axis to phantom surface normal at the measurement location	30° ± 1°	20° ± 1°	
	\leq 2 GHz: \leq 15 mm 2 – 3 GHz: \leq 12 mm	$3 - 4 \text{ GHz:} \le 12 \text{ mm}$ $4 - 6 \text{ GHz:} \le 10 \text{ mm}$	
Maximum area scan spatial resolution: $\Delta x_{\text{Area}},\Delta y_{\text{Area}}$	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.		

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-5008-1021 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR16-SPF0002

Page (18) of (49)



Step 3: Zoom Scan

Zoom Scans are used to assess the peak spatial SAR values within a cubic averaging volume containing1 g and 10 g of simulated tissue. The Zoom Scan measures 5x5x7 points within a cube whose base faces are centered on the maxima found in a preceding area scanjob within the same procedure. When the measurement is done, the Zoom Scan evaluates theaveraged SAR for 1 g and 10 g and displays these values next to the job's label.

Zoom Scan Parameters extracted from KDB 865664 D01 SAR Measument 100 MHz to 6 GHz v01r04.

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: Δx_{Zoom} , Δy_{Zoom}			\leq 2 GHz: \leq 8 mm 2 - 3 GHz: \leq 5 mm [*]	$3 - 4 \text{ GHz: } \le 5 \text{ mm}^*$ $4 - 6 \text{ GHz: } \le 4 \text{ mm}^*$
	uniform grid: $\Delta z_{Zoom}(n)$		≤ 5 mm	$3 - 4 \text{ GHz: } \le 4 \text{ mm}$ $4 - 5 \text{ GHz: } \le 3 \text{ mm}$ $5 - 6 \text{ GHz: } \le 2 \text{ mm}$
Maximum zoom scan spatial resolution, normal to phantom surface	graded grid	$\Delta z_{Zoom}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	$3 - 4 \text{ GHz: } \le 3 \text{ mm}$ $4 - 5 \text{ GHz: } \le 2.5 \text{ mm}$ $5 - 6 \text{ GHz: } \le 2 \text{ mm}$
		Δz _{Zoom} (n>1): between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	$3 - 4 \text{ GHz: } \ge 28 \text{ mm}$ $4 - 5 \text{ GHz: } \ge 25 \text{ mm}$ $5 - 6 \text{ GHz: } \ge 22 \text{ mm}$

Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.

Step 4: Power drift measurement

The Power Drift Measurement measures the field at the same location as the most recent powerreference measurement within the same procedure, and with the same settings. The Power DriftMeasurement gives the field difference in dB from the reading conducted within the last PowerReference Measurement. This allows a user to monitor the power drift of the device under test within abatch process. The measurement procedure is the same as Step 1.

Step 5: Z-Scan

The Z Scan measures points along a vertical straight line. The line runs along the Z-axis of a onedimensionalgrid. In order to get a reasonable extrapolation, the extrapolated distance should not belarger than the step size in Z-direction.

* Z Scan Report on Liquid Measure the height Annex C Liquid Depth photo to replace

^{*} When zoom scan is required and the <u>reported</u> SAR from the <u>area scan based 1-g SAR estimation</u> procedures of KDB 447498 is $\leq 1.4 \text{ W/kg}$, $\leq 8 \text{ mm}$, $\leq 7 \text{ mm}$ and $\leq 5 \text{ mm}$ zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-5008-1021 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR16-SPF0002

Page (19) of (49)



13. Test Equipment Information

Test Platform	SPEAG DASY5 System						
Version	DASY5 : Version 52.8.8.1222						
version	SEMCAD : Version 14.6.10 (7331)						
Location	KCTL Inc.						
Manufacture	SPEAG						
Hardware Reference							
Carrie and and	Model	Serial Number	Date	Due date of			
Equipment		Serial Number	of Calibration	next Calibration			
Shield Room	Shield Room	None	N/A	N/A			
DASY5 Robot	TX90XL Speag	F12/5L7FA1/A/01	N/A	N/A			
DASY5 Controller	TX90XL Speag	F12/5L7FA1/C/01	N/A	N/A			
Phantom	Twin SAM Phantom	vin SAM Phantom 1724		N/A			
Mounting Device	Mounting Device None		N/A	N/A			
DAE	DAE4	1342	2016-07-26	2017-07-26			
Probe	EX3DV4	3928	2016-01-28	2017-01-28			
Dipole Validation Kits	D900V2	1d138	2016-05-25	2018-05-25			
Network Analyzer	E5071B	MY42403524	2016-02-11	2017-02-11			
Dual Directional Coupler	778D	16059	2016-07-15	2017-07-15			
Signal Generator	E4438C	MY42080486	2016-01-08	2017-01-08			
Power Amplifier	GRF5039	1062	2016-07-12	2017-07-12			
LP Filter	LA-15N	36543	2016-07-12	2017-07-12			
Dual Power Meter	E4419B	GB43312301	2016-07-12	2017-07-12			
Power Sensor	8481H	3318A19377	2016-07-20	2017-07-20			
Power Sensor	8481H	3318A19379	2016-07-20	2017-07-20			
Dielectric Assessment Kit	DAK-3.5	1078	2016-08-25	2017-08-25			
Humidity/Baro/Temp. Data Recorder	MHB-382SD 73871 2016-07-15 2017-07-15						

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-5008-1021 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR16-SPF0002

Page (20) of (49)



14. RF Average Conducted Output Power

14.1 Average Conducted Output Power

Channel	1	125	250	
Frequency(MHz)	902.6	915	927.5	
Half	25.79	26.11	26.13	

Channel	5	125	250	
Frequency(MHz)	903	915	927.5	
Hi-fi	25.42	25.77	25.91	

14.2 Max. tune up power

Mode	Target Power	Tolerance	Max. Allowed Power	
Half, Hi-fi	26 dBm	± 1 dB	27 dBm	

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-5008-1021 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR16-SPF0002

Page (21) of (49)



15. SAR Test Results

15.1 Body SAR Test Results

Mode	Frequency (MHz)	Average Power (dBm)	Max. tune up power (dBm)	Scaling Factor	EUT Position	Distance (mm)	Measured 1 g SAR (W/kg) Duty 100 %	Measured 1 g SAR (W/kg) Duty 50 %	Scaled 1 g SAR (W/kg)
	915	26.11	27.00	1.227	Front	0	0.361	0.181	0.222
	915	26.11	27.00	1.227	Rear	0	0.056	0.028	0.034
Liek	915	26.11	27.00	1.227	Left	0	0.095	0.048	0.059
	915	26.11	27.00	1.227	Right	0	0.152	0.076	0.093
Half	915	26.11	27.00	1.227	Тор	0	0.160	0.080	0.098
	915	26.11	27.00	1.227	Bottom	0	0.017	0.009	0.011
	902.6	25.79	27.00	1.321	Front	0	0.338	0.169	0.223
	927.5	26.13	27.00	1.222	Front	0	0.187	0.094	0.115
Hi-fi	915	25.77	27.00	1.327	Front	0	0.225	0.113	0.150

<Note>

^{*} SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v06.

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-5008-1021 www.kctl.co.kr

FAX: 82-505-299-8311 Page (22) of (49)

Report No.:



16. Test System Verification Results

Procedure Name: d=10 mm, Pin=250 mW, dist=2.0mm (EX-Probe)


Frequency: 900 MHz; Duty Cycle: 1:1 Medium parameters used: f = 900 MHz; $\sigma = 1.036 \text{ S/m}$; $\epsilon_r = 54.603$; $\rho = 1000 \text{ kg/m}^3$ Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 SN3928; ConvF(9.09, 9.09, 9.09); Calibrated: 2016-01-28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1342; Calibrated: 2016-07-26
- Phantom: SAM twin SN1724; Type: QD000P40CD; Serial: TP:1724
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

System Performance Check (without Area Scan)/d=10 mm, Pin=250 mW, dist=2.0mm (EX-Probe)/Area Scan (51x111x1): Interpolated grid: dx=2.000 mm, dy=2.000 mm Maximum value of SAR (interpolated) = 3.33 W/kg

System Performance Check (without Area Scan)/d=10 mm, Pin=250 mW, dist=2.0mm (EX-Probe)/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 58.91 V/m; Power Drift = 0.14 dB Peak SAR (extrapolated) = 4.04 W/kg SAR(1 g) = 2.76 W/kg; SAR(10 g) = 1.81 W/kgMaximum value of SAR (measured) = 3.48 W/kg



65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-5008-1021 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR16-SPF0002

Page (23) of (49)



17. Test Results

Procedure Name: Half_f.902.6_Front_0 mm

Frequency: 902.6 MHz; Duty Cycle: 1:1 Medium parameters used: f=902.6 MHz; $\sigma=1.038$ S/m; $\epsilon_r=54.62$; $\rho=1000$ kg/m³ Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 SN3928; ConvF(9.09, 9.09, 9.09); Calibrated: 2016-01-28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1342; Calibrated: 2016-07-26

Maximum value of SAR (measured) = 0.465 W/kg

- Phantom: SAM twin SN1724; Type: QD000P40CD; Serial: TP:1724
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Half_f.902.6_Front_0 mm/Area Scan (71x91x1): Interpolated grid: dx=2.000 mm, dy=2.000 mm Maximum value of SAR (interpolated) = 0.527 W/kg

 $\label{localization} $$Configuration/Half_f.902.6_Front_0\ mm/Zoom\ Scan\ (5x5x7)/Cube\ 0: \ $$Measurement\ grid: dx=8mm,\ dy=8mm,\ dz=5mm $$ Reference\ Value=13.95\ V/m;\ Power\ Drift=0.17\ dB$$ Peak\ SAR\ (extrapolated)=0.736\ W/kg $$ SAR(1\ g)=0.338\ W/kg;\ SAR(1\ g)=0.206\ W/kg$

