



# FCC TEST REPORT (WIRELESS LAN)

**REPORT NO.:** RF961219L14-1

**MODEL NO.:** SC700  
(refer to item 3.1 for more details)

**RECEIVED :** Dec. 20, 2007

**TESTED :** Feb. 29 ~ Mar. 17, 2008

**ISSUED :** Mar. 20, 2008

**APPLICANT :** Shin Chuan Computer Co., Ltd.

**ADDRESS:** 6F-2, 268, LianCheng Rd., ZhongHe City, Taipei  
County 23553, Taiwan (R.O.C.)

**ISSUED BY:** Advance Data Technology Corporation

**LAB ADDRESS:** No. 47, 14<sup>th</sup> Ling, Chia Pau Tsuen, Lin Kou  
Hsiang 244, Taipei Hsien, Taiwan, R.O.C.

**TEST LOCATION:** No. 19, Hwa Ya 2<sup>nd</sup> Rd., Wen Hwa Tsuen, Kwei  
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This test report consists of 59 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by TAF, A2LA or any government agencies. The test results in the report only apply to the tested sample.





## TABLE OF CONTENTS

1. CERTIFICATION.....	4
2. SUMMARY OF TEST RESULTS .....	5
2.1 MEASUREMENT UNCERTAINTY .....	5
3. GENERAL INFORMATION.....	6
3.1 GENERAL DESCRIPTION OF EUT.....	6
3.2 DESCRIPTION OF TEST MODES.....	8
3.2.1 CONFIGURATION OF SYSTEM UNDER TEST .....	8
3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	9
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS .....	11
3.4 DESCRIPTION OF SUPPORT UNITS .....	11
4. TEST TYPES AND RESULTS .....	12
4.1 RADIATED EMISSION MEASUREMENT .....	12
4.1.1 LIMITS OF RADIATED EMISSION MEASUREMENT.....	12
4.1.2 TEST INSTRUMENTS .....	13
4.1.3 TEST PROCEDURES .....	14
4.1.4 DEVIATION FROM TEST STANDARD .....	14
4.1.5 TEST SETUP .....	15
4.1.6 EUT OPERATING CONDITIONS .....	15
4.1.7 TEST RESULTS .....	16
4.2 CONDUCTED EMISSION MEASUREMENT .....	25
4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT.....	25
4.2.2 TEST INSTRUMENTS .....	25
4.2.3 TEST PROCEDURES .....	26
4.2.4 DEVIATION FROM TEST STANDARD .....	26
4.2.5 TEST SETUP .....	27
4.2.6 EUT OPERATING CONDITIONS .....	27
4.2.7 TEST RESULTS .....	28
4.3 6dB BANDWIDTH MEASUREMENT .....	32
4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT.....	32
4.3.2 TEST INSTRUMENTS .....	32
4.3.3 TEST PROCEDURE .....	32
4.3.4 DEVIATION FROM TEST STANDARD .....	32
4.3.5 TEST SETUP .....	33
4.3.6 EUT OPERATING CONDITIONS .....	33
4.3.7 TEST RESULTS .....	34
4.4 MAXIMUM PEAK OUTPUT POWER .....	38
4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT.....	38
4.4.2 INSTRUMENTS.....	38
4.4.3 TEST PROCEDURES .....	38
4.4.4 DEVIATION FROM TEST STANDARD .....	39
4.4.5 TEST SETUP .....	39
4.4.6 EUT OPERATING CONDITIONS .....	39



4.4.7	TEST RESULTS .....	40
4.5	POWER SPECTRAL DENSITY MEASUREMENT .....	41
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT .....	41
4.5.2	TEST INSTRUMENTS .....	41
4.5.3	TEST PROCEDURE .....	41
4.5.4	DEVIATION FROM TEST STANDARD .....	42
4.5.5	TEST SETUP .....	42
4.5.6	EUT OPERATING CONDITION .....	42
4.5.7	TEST RESULTS .....	43
4.6	BAND EDGES MEASUREMENT .....	47
4.6.1	LIMITS OF BAND EDGES MEASUREMENT .....	47
4.6.2	TEST INSTRUMENTS .....	47
4.6.3	TEST PROCEDURE .....	47
4.6.4	DEVIATION FROM TEST STANDARD .....	47
4.6.5	EUT OPERATING CONDITION .....	47
4.6.6	TEST RESULTS .....	48
4.7	ANTENNA REQUIREMENT .....	56
4.7.1	STANDARD APPLICABLE .....	56
4.7.2	ANTENNA CONNECTED CONSTRUCTION .....	56
5.	PHOTOGRAPHS OF THE TEST CONFIGURATION .....	57
6.	INFORMATION ON THE TESTING LABORATORIES .....	58
7.	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB .....	59



## 1. CERTIFICATION

**PRODUCT:** Portable Data Terminal

**MODEL:** SC700 (refer to item 3.1 for more details)

**BRAND:** SCC

**APPLICANT:** Shin Chuan Computer Co., Ltd.

**TESTED:** Feb. 29 ~ Mar. 17, 2008

**TEST SAMPLE:** ENGINEERING SAMPLE

**STANDARDS:** FCC Part 15, Subpart C (Section 15.247)

ANSI C63.4-2003

The above equipment (Model: SC700) has been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**PREPARED BY** : Rennie Wang , **DATE:** Mar. 20, 2008  
Rennie Wang / Senior Specialist

**TECHNICAL  
ACCEPTANCE** : Long Chen , **DATE:** Mar. 20, 2008  
Responsible for RF      Long Chen / Senior Engineer

**APPROVED BY** : Gary Chang , **DATE:** Mar. 20, 2008  
Gary Chang / Assistant Manager



## 2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C (Section 15.247)			
Standard Section	Test Type and Limit	Result	Remark
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -10.69dB at 2.270MHz.
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit.
15.247(d)	Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit. Minimum passing margin is -1.04dB at 4874.00MHz.
15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit.
15.247(d)	Band Edge Measurement Limit: 30dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit.

### 2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	3.34 dB
	200MHz ~1000MHz	3.35 dB
	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .



### 3. GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

<b>EUT</b>	Portable Data Terminal
<b>MODEL NO.</b>	SC700 (refer to NOTE for more details)
<b>FCC ID</b>	TQ2-SC700PDT-BWG
<b>POWER SUPPLY</b>	3.7Vdc from rechargeable lithium battery 5.0Vdc from power adapter
<b>MODULATION TYPE</b>	Wireless LAN: CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM Bluetooth: GFSK, $\pi/4$ -DQPSK, 8-DPSK for FHSS
<b>MODULATION TECHNOLOGY</b>	DSSS, OFDM, FHSS
<b>TRANSFER RATE</b>	Wireless LAN: 802.11b: 11/5.5/2/1Mbps 802.11g: 54/48/36/24/18/12/9/6Mbps Bluetooth: 1/2/3Mbps
<b>FREQUENCY RANGE</b>	2400 ~ 2483.5MHz
<b>NUMBER OF CHANNEL</b>	Wireless LAN: 11 Bluetooth: 79
<b>OUTPUT POWER</b>	Wireless LAN: 10.186mW Bluetooth: 0.234mW
<b>ANTENNA TYPE(S)</b>	Wireless LAN: PIFA antenna with 2.2dBi gain Bluetooth: Chip antenna with 0.5dBi gain
<b>DATA CABLE</b>	1.9m shielded USB cable with one core
<b>I/O PORTS</b>	Refer to user's manual
<b>ACCESSORY DEVICES</b>	Battery, Adapter, Earphone (1.2m), Stylus, CF support guide, Holster

**NOTE:**

1. The models as below are identical to each other except for their model name and outer appearance due to marketing requirement.

MODEL NAME	DESCRIPTION
SC700	Short button board
SC720	Long button board, add buttons (Button interface add extension cable)
TP700	
AZ8700	Based on model SC700, for marketing difference
MARS-1031N	
MARS-1031F	

2. The EUT is a Portable Data Terminal. The functions of EUT listed as below:

	TEST STANDARD	REFERENCE REPORT
WLAN 802.11b/g	FCC Part 15	RF961219L14-1
BLUETOOTH		RF961219L14-2
GSM 850	FCC Part 22	RF961219L14
PCS 1900	FCC Part 24	RF961219L14-3

3. The EUT have a lithium battery listed as below:

MODEL:	BP05-000500
RATING:	3.7Vdc, 3000mAh

4. The EUT was operated with following power adapter:

BRAND:	ENG
MODEL:	3A-161DN05
INPUT:	100-240Vac, 50-60Hz, 0.6A
OUTPUT:	5.0Vdc, 2.6A
POWER LINE:	AC 1.8m non-shielded cable without core DC 1.05m non-shielded cable with one core


5. Hardware version: ES4.
6. Software version: ES4.
7. IMEI code: IMEI code: 35563400\*\*\*\*\*.
8. The above EUT information was declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

### 3.2 DESCRIPTION OF TEST MODES

11 channels are provided for 802.11b, 802.11g:

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

#### 3.2.1 CONFIGURATION OF SYSTEM UNDER TEST





### 3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE $\geq$ 1G	RE $<$ 1G	PLC	APCM	
A	✓	✓	✓	✓	For model SC700
B	-	✓	✓	-	For model SC720

Where **RE $\geq$ 1G**: Radiated Emission above 1GHz

**PLC**: Power Line Conducted Emission

**RE $<$ 1G**: Radiated Emission below 1GHz

**APCM**: Antenna Port Conducted Measurement

**NOTE:** “-“ means no effect.

#### RADIATED EMISSION TEST (ABOVE 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	AXIS
A	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0	X
A	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0	X

#### RADIATED EMISSION TEST (BELOW 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	AXIS
A	802.11g	1 to 11	6	OFDM	BPSK	6.0	X
B	802.11g	1 to 11	6	OFDM	BPSK	6.0	X



#### **POWER LINE CONDUCTED EMISSION TEST:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11g	1 to 11	6	OFDM	BPSK	6.0
B	802.11g	1 to 11	6	OFDM	BPSK	6.0

#### **BANDEdge MEASUREMENT:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11b	1 to 11	1, 11	DSSS	DBPSK	1.0
A	802.11g	1 to 11	1, 11	OFDM	BPSK	6.0

#### **ANTENNA PORT CONDUCTED MEASUREMENT:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
A	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0



### 3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

#### FCC Part 15, Subpart C (15.247)

#### ANSI C63.4-2003

All test items have been performed and recorded as per the above standards.

**NOTE:** The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

### 3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK COMPUTER	DELL	PP05L	12130898320	E2K24CLNS
2	PRINTER	EPSON	LQ-300+	DCGY054147	FCC DoC Approved
3	MODEM	ACEEX	1414V/3	0401008269	IFAXDM1414

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	1.8m braid shielded wire , DB25 connector , w/o core.
3	1.2m braid shielded wire , DB25 & DB9 connector , w/o core.

**NOTE:** All power cords of the above support units are non shielded (1.8m).



## 4. TEST TYPES AND RESULTS

### 4.1 RADIATED EMISSION MEASUREMENT

#### 4.1.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB<sub>u</sub>V/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



#### 4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESCI	100424	Jul. 27, 2008
Spectrum Analyzer Agilent	E4446A	MY44360128	Dec. 06, 2008
BILOG Antenna SCHWARZBECK	VULB9168	9168-160	May 31, 2008
HORN Antenna SCHWARZBECK	9120D	9120D-209	Jun. 28, 2008
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170243	Dec. 24, 2008
Preamplifier Agilent	8447D	2944A10633	Oct. 28, 2008
Preamplifier Agilent	8449B	3008A01964	Oct. 23, 2008
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	283402/4	Dec. 06, 2008
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	251644/4	Dec. 06, 2008
Software ADT.	ADT_Radiated_V7.6	NA	NA
Antenna Tower inn-co GmbH	MA 4000	013303	NA
Antenna Tower Controller inn-co GmbH	CO2000	017303	NA
Turn Table ADT.	TT100.	TT93021703	NA
Turn Table Controller ADT.	SC100.	SC93021703	NA

**NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Chamber 3.
3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The VCCI Site Registration No. is R-237.
5. The IC Site Registration No. is IC3789B-3.



#### 4.1.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


**NOTE:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.1.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.6 EUT OPERATING CONDITIONS

- Connected the EUT to a notebook and placed on a testing table.
- The notebook system run a test program (provided by manufacturer) to enable EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the system in full functions.



#### 4.1.7 TEST RESULTS

##### 802.11b DSSS MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL		FREQUENCY RANGE		1 ~ 25GHz
INPUT POWER (SYSTEM)		DETECTOR FUNCTION		Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS		TESTED BY		Dean Wang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	59.18 PK	74.00	-14.82	1.06 H	343	26.94	32.24
2	2390.00	47.81 AV	54.00	-6.19	1.06 H	343	15.57	32.24
3	*2412.00	94.17 PK			1.06 H	343	61.85	32.32
4	*2412.00	89.62 AV			1.06 H	343	57.30	32.32
5	4824.00	56.54 PK	74.00	-17.46	1.06 H	189	18.41	38.13
6	4824.00	52.32 AV	54.00	-1.68	1.06 H	189	14.19	38.13

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	59.22 PK	74.00	-14.78	1.26 V	9	26.98	32.24
2	2390.00	46.76 AV	54.00	-7.24	1.26 V	9	14.52	32.24
3	*2412.00	90.20 PK			1.26 V	10	57.88	32.32
4	*2412.00	85.44 AV			1.26 V	10	53.12	32.32
5	4824.00	56.73 PK	74.00	-17.27	1.14 V	226	18.60	38.13
6	4824.00	52.94 AV	54.00	-1.06	1.14 V	226	14.81	38.13

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “\*”: Fundamental frequency.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	23deg. C, 66%RH 993hPa	TESTED BY	Dean Wang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M							
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)
1	*2437.00	94.84 PK			1.03 H	341	62.44
2	*2437.00	90.24 AV			1.03 H	341	57.84
3	4874.00	56.98 PK	74.00	-17.02	1.03 H	175	18.66
4	4874.00	52.45 AV	54.00	-1.55	1.03 H	175	14.13
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M							
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)
1	*2437.00	90.49 PK			1.26 V	17	58.09
2	*2437.00	85.90 AV			1.26 V	17	53.50
3	4874.00	57.53 PK	74.00	-16.47	1.29 V	85	19.21
4	4874.00	52.96 AV	54.00	-1.04	1.29 V	85	14.64

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “\*”: Fundamental frequency.



EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL		Channel 11		FREQUENCY RANGE 1 ~ 25GHz
INPUT POWER (SYSTEM)		120Vac, 60 Hz		DETECTOR FUNCTION Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS		23deg. C, 66%RH 993hPa		TESTED BY Dean Wang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	94.82 PK			1.02 H	344	62.34	32.48
2	*2462.00	90.27 AV			1.02 H	344	57.79	32.48
3	2483.50	59.74 PK	74.00	-14.26	1.02 H	344	27.18	32.56
4	2483.50	48.39 AV	54.00	-5.61	1.02 H	344	15.83	32.56
5	4924.00	56.03 PK	74.00	-17.97	1.00 H	167	17.57	38.46
6	4924.00	52.16 AV	54.00	-1.84	1.00 H	167	13.70	38.46
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	90.82 PK			1.21 V	13	58.34	32.48
2	*2462.00	86.11 AV			1.21 V	13	53.63	32.48
3	2483.50	58.53 PK	74.00	-15.47	1.21 V	13	25.97	32.56
4	2483.50	47.16 AV	54.00	-6.84	1.21 V	13	14.60	32.56
5	4924.00	56.67 PK	74.00	-17.33	1.00 V	204	18.21	38.46
6	4924.00	52.82 AV	54.00	-1.18	1.00 V	204	14.36	38.46

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “\*”: Fundamental frequency.



### 802.11g OFDM MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL		Channel 1		FREQUENCY RANGE 1 ~ 25GHz
INPUT POWER (SYSTEM)		120Vac, 60 Hz		DETECTOR FUNCTION Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS		23deg. C, 66%RH 993hPa		TESTED BY Dean Wang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	59.11 PK	74.00	-14.89	1.02 H	346	26.87	32.24
2	2390.00	47.37 AV	54.00	-6.63	1.02 H	346	15.13	32.24
3	*2412.00	94.80 PK			1.02 H	346	62.48	32.32
4	*2412.00	84.71 AV			1.02 H	346	52.39	32.32
5	4824.00	57.91 PK	74.00	-16.09	1.19 H	48	19.78	38.13
6	4824.00	44.86 AV	54.00	-9.14	1.19 H	48	6.73	38.13
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	58.45 PK	74.00	-15.55	1.16 V	7	26.21	32.24
2	2390.00	46.89 AV	54.00	-7.11	1.16 V	7	14.65	32.24
3	*2412.00	94.21 PK			1.16 V	7	61.89	32.32
4	*2412.00	84.49 AV			1.16 V	7	52.17	32.32
5	4824.00	60.62 PK	74.00	-13.38	1.10 V	253	22.49	38.13
6	4824.00	47.36 AV	54.00	-6.64	1.10 V	253	9.23	38.13

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “\*”: Fundamental frequency.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	23deg. C, 66%RH 993hPa	TESTED BY	Dean Wang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M							
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)
1	*2437.00	95.11 PK			1.03 H	348	62.71
2	*2437.00	85.09 AV			1.03 H	348	52.69
3	4874.00	56.37 PK	74.00	-17.63	1.15 H	61	18.05
4	4874.00	43.89 AV	54.00	-10.11	1.15 H	61	5.57
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M							
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)
1	*2437.00	94.69 PK			1.17 V	8	62.29
2	*2437.00	84.68 AV			1.17 V	8	52.28
3	4874.00	58.65 PK	74.00	-15.35	1.09 V	4	20.33
4	4874.00	46.02 AV	54.00	-7.98	1.09 V	4	7.70

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “\*”: Fundamental frequency.



EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL		Channel 11		FREQUENCY RANGE 1 ~ 25GHz
INPUT POWER (SYSTEM)		120Vac, 60 Hz		DETECTOR FUNCTION Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS		23deg. C, 66%RH 993hPa		TESTED BY Dean Wang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	94.69 PK			1.03 H	344	62.21	32.48
2	*2462.00	84.43 AV			1.03 H	344	51.95	32.48
3	2483.50	59.13 PK	74.00	-14.87	1.03 H	344	26.57	32.56
4	2483.50	48.05 AV	54.00	-5.95	1.03 H	344	15.49	32.56
5	4924.00	55.13 PK	74.00	-18.87	1.21 H	56	16.67	38.46
6	4924.00	42.15 AV	54.00	-11.85	1.21 H	56	3.69	38.46
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	94.06 PK			1.16 V	14	61.58	32.48
2	*2462.00	83.89 AV			1.16 V	14	51.41	32.48
3	2483.50	58.61 PK	74.00	-15.39	1.15 V	14	26.05	32.56
4	2483.50	47.69 AV	54.00	-6.31	1.15 V	14	15.13	32.56
5	4924.00	57.32 PK	74.00	-16.68	1.08 V	18	18.86	38.46
6	4924.00	44.38 AV	54.00	-9.62	1.08 V	18	5.92	38.46

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “\*”: Fundamental frequency.

**BELOW 1GHz WORST-CASE DATA : 802.11g OFDM MODULATION**

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	Below 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH 993hPa	TESTED BY	Dean Wang
TEST MODE	A		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	125.17	35.48 QP	43.50	-8.02	2.50 H	208	22.95	12.53
2	156.28	32.50 QP	43.50	-11.00	2.00 H	208	17.97	14.53
3	167.94	32.52 QP	43.50	-10.98	2.00 H	226	18.62	13.90
4	195.16	33.25 QP	43.50	-10.25	1.50 H	214	21.58	11.67
5	245.72	37.02 QP	46.00	-8.98	1.00 H	331	23.52	13.50
6	272.94	38.92 QP	46.00	-7.08	1.00 H	271	24.74	14.18
7	298.21	35.25 QP	46.00	-10.75	1.00 H	271	20.55	14.70
8	340.99	34.52 QP	46.00	-11.48	1.00 H	292	18.71	15.81
9	389.59	34.12 QP	46.00	-11.88	1.00 H	151	17.06	17.06
10	403.20	37.84 QP	46.00	-8.16	1.00 H	280	20.41	17.43
11	733.73	34.62 QP	46.00	-11.38	1.00 H	235	8.98	25.64
12	819.28	35.14 QP	46.00	-10.86	1.50 H	124	8.43	26.71
13	846.50	35.59 QP	46.00	-10.41	1.50 H	118	8.49	27.10
14	945.66	34.88 QP	46.00	-11.12	1.00 H	133	6.41	28.47

**REMARKS:** 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).

2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).

3. The other emission levels were very low against the limit.

4. Margin value = Emission level – Limit value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	Below 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH 993hPa	TESTED BY	Dean Wang
TEST MODE	A		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	74.62	28.29 QP	40.00	-11.71	1.50 V	202	16.61	11.68
2	119.34	32.06 QP	43.50	-11.44	1.00 V	349	19.91	12.15
3	403.20	34.05 QP	46.00	-11.95	2.00 V	169	16.61	17.43
4	665.68	36.04 QP	46.00	-9.96	1.00 V	10	11.46	24.57
5	733.73	34.90 QP	46.00	-11.10	2.00 V	52	9.26	25.64
6	819.28	43.79 QP	46.00	-2.21	1.00 V	181	17.08	26.71
7	854.28	35.21 QP	46.00	-10.79	1.50 V	4	7.99	27.22
8	949.55	35.45 QP	46.00	-10.55	1.50 V	178	6.94	28.51

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL		Channel 6		FREQUENCY RANGE
INPUT POWER (SYSTEM)		120Vac, 60 Hz		DETECTOR FUNCTION
ENVIRONMENTAL CONDITIONS		18deg. C, 60%RH 993hPa		TESTED BY
TEST MODE		B		Dean Wang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	103.78	33.08 QP	43.50	-10.42	2.50 H	196	22.58	10.49
2	181.55	33.43 QP	43.50	-10.07	2.50 H	79	20.82	12.61
3	403.20	40.08 QP	46.00	-5.92	1.00 H	331	22.65	17.43
4	480.97	38.56 QP	46.00	-7.44	2.00 H	70	18.65	19.91
5	585.97	33.94 QP	46.00	-12.06	1.50 H	238	11.17	22.77
6	819.28	34.42 QP	46.00	-11.58	1.00 H	163	7.71	26.71
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	53.23	29.48 QP	40.00	-10.52	1.00 V	319	15.31	14.17
2	96.01	32.96 QP	43.50	-10.54	1.00 V	94	23.42	9.54
3	455.70	36.70 QP	46.00	-9.30	1.00 V	202	17.62	19.09
4	500.42	41.39 QP	46.00	-4.61	1.25 V	298	20.85	20.54
5	819.28	36.85 QP	46.00	-9.15	1.50 V	190	10.14	26.71
6	899.00	35.75 QP	46.00	-10.25	2.00 V	244	7.81	27.94

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



## 4.2 CONDUCTED EMISSION MEASUREMENT

### 4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB $\mu$ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

**NOTE:** 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

### 4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESCS30	100288	Sep. 21, 2008
RF signal cable Woken	5D-FB	Cable-HYCO3-01	Jan. 06, 2009
LISN ROHDE & SCHWARZ	ESH2-Z5	100100	Jan. 09, 2009
LISN SCHWARZBECK	NNBL 8226-2	8226-142	May 07, 2008
Software ADT	ADT_Cond_V3	NA	NA

**NOTE:**

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Shielded Room 2.
3. The VCCI Site Registration No. is C-2047.



#### 4.2.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

**NOTE:** All modes of operation were investigated and the worst-case emissions are reported.

#### 4.2.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.2.5 TEST SETUP



**Note:**

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

#### 4.2.7 TEST RESULTS


##### CONDUCTED WORST-CASE DATA: 802.11g OFDM MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL			
CHANNEL	Channel 6	PHASE		Line 1	
INPUT POWER	120Vac, 60 Hz	6dB BANDWIDTH		9kHz	
ENVIRONMENTAL CONDITIONS	20deg. C, 60%RH, 991hPa	TESTED BY		Match Tsui	
TEST MODE	A				

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
			Factor	[dB (uV)]	[dB (uV)]	[dB (uV)]	[dB (uV)]	[dB (uV)]	(dB)	
		[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.
1	0.455	0.10	42.42	-	42.52	-	56.79	46.79	-14.27	-
2	0.650	0.10	41.56	-	41.66	-	56.00	46.00	-14.34	-
3	0.908	0.11	42.05	-	42.16	-	56.00	46.00	-13.84	-
4	1.621	0.18	41.55	-	41.73	-	56.00	46.00	-14.27	-
5	2.332	0.23	44.34	-	44.57	-	56.00	46.00	-11.43	-
6	12.059	0.39	39.58	-	39.97	-	60.00	50.00	-20.03	-

**REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




EUT TEST CONDITION			MEASUREMENT DETAIL		
CHANNEL	Channel 6		PHASE	Line 2	
INPUT POWER	120Vac, 60 Hz		6dB BANDWIDTH	9kHz	
ENVIRONMENTAL CONDITIONS	20deg. C, 60%RH, 991hPa		TESTED BY	Match Tsui	
TEST MODE	A				

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
			Factor	[dB (uV)]	[dB (uV)]	[dB (uV)]	(dB)			
		[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.
1	0.388	0.10	45.95	-	46.05	-	58.10	48.10	-12.05	-
2	0.646	0.15	41.01	-	41.16	-	56.00	46.00	-14.84	-
3	0.908	0.19	41.38	-	41.57	-	56.00	46.00	-14.43	-
4	1.492	0.21	42.50	-	42.71	-	56.00	46.00	-13.29	-
5	2.332	0.23	44.20	-	44.43	-	56.00	46.00	-11.57	-
6	11.477	0.44	37.93	-	38.37	-	60.00	50.00	-21.63	-

**REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




EUT TEST CONDITION			MEASUREMENT DETAIL		
CHANNEL	Channel 6		PHASE	Line 1	
INPUT POWER	120Vac, 60 Hz		6dB BANDWIDTH	9kHz	
ENVIRONMENTAL CONDITIONS	20deg. C, 60%RH, 991hPa		TESTED BY	Match Tsui	
TEST MODE	B				

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
			Factor	[dB (uV)]	[dB (uV)]	[dB (uV)]	[dB (uV)]	[dB (uV)]	(dB)	
		[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.
1	0.455	0.10	44.46	-	44.56	-	56.79	46.79	-12.23	-
2	0.908	0.11	43.93	-	44.04	-	56.00	46.00	-11.96	-
3	1.168	0.13	44.11	-	44.24	-	56.00	46.00	-11.76	-
4	1.426	0.16	44.98	-	45.14	-	56.00	46.00	-10.86	-
5	<b>2.270</b>	<b>0.23</b>	<b>45.08</b>	-	<b>45.31</b>	-	<b>56.00</b>	<b>46.00</b>	<b>-10.69</b>	-
6	12.057	0.39	42.67	-	43.06	-	60.00	50.00	-16.94	-

**REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




EUT TEST CONDITION			MEASUREMENT DETAIL		
CHANNEL	Channel 6		PHASE	Line 2	
INPUT POWER	120Vac, 60 Hz		6dB BANDWIDTH	9kHz	
ENVIRONMENTAL CONDITIONS	20deg. C, 60%RH, 991hPa		TESTED BY	Match Tsui	
TEST MODE	B				

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
			Factor	[dB (uV)]	[dB (uV)]	[dB (uV)]	[dB (uV)]	[dB (uV)]	(dB)	
		[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.
1	0.455	0.11	42.62	-	42.73	-	56.79	46.79	-14.06	-
2	0.650	0.15	42.14	-	42.29	-	56.00	46.00	-13.71	-
3	0.908	0.19	42.94	-	43.13	-	56.00	46.00	-12.87	-
4	1.426	0.21	43.79	-	44.00	-	56.00	46.00	-12.00	-
5	2.270	0.23	44.40	-	44.63	-	56.00	46.00	-11.37	-
6	11.926	0.45	41.80	-	42.25	-	60.00	50.00	-17.75	-

**REMARKS:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.





## 4.3 6dB BANDWIDTH MEASUREMENT

### 4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

### 4.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSP40	100040	Jun. 28, 2008

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


### 4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100kHz RBW and 300kHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

### 4.3.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.3.5 TEST SETUP



#### 4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.


#### 4.3.7 TEST RESULTS



##### 802.11b DSSS MODULATION

MODULATION TYPE	DBPSK	ENVIRONMENTAL CONDITIONS	26deg.C, 67%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60Hz	TESTED BY	Brad Wu

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	9.71	0.5	PASS
6	2437	10.03	0.5	PASS
11	2462	9.88	0.5	PASS

CH 1



**CH 6**

**CH 11**





### 802.11g OFDM MODULATION


MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	26deg.C, 67%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60Hz	TESTED BY	Brad Wu

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	16.62	0.5	PASS
6	2437	16.60	0.5	PASS
11	2462	16.59	0.5	PASS


### CH 1



### CH 6



### CH 11





## 4.4 MAXIMUM PEAK OUTPUT POWER

### 4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

### 4.4.2 INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSP40	100040	Jun. 28, 2008
AGILENT SYNTHESIZED SIGNAL GENERATOR	E8257C	MY43320668	Dec. 25, 2008
DIGITAL RT OSCILLOSCOPE	TDS1012	C037299	Nov. 21, 2008
NARDA DETECTOR	4503A	FSCM99899	NA

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.4.3 TEST PROCEDURES

- a. A detector was used on the output port of the EUT. An oscilloscope was used to read the response of the detector.
- b. Replaced the EUT by the signal generator. The center frequency of the S.G was adjusted to the center frequency of the measured channel.
- c. Adjusted the power to have the same reading on oscilloscope. Record the power level.

#### 4.4.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.4.5 TEST SETUP



#### 4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6



#### 4.4.7 TEST RESULTS

##### 802.11b DSSS MODULATION

MODULATION TYPE	DBPSK	ENVIRONMENTAL CONDITIONS	26deg.C, 67%RH, 991hPa
INPUT POWER	120Vac, 60Hz	TESTED BY	Brad Wu

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS / FAIL
1	2412	10.069	10.03	30	PASS
6	2437	10.186	10.08	30	PASS
11	2462	10.023	10.01	30	PASS

##### 802.11g OFDM MODULATION

MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	26deg.C, 67%RH, 991hPa
INPUT POWER	120Vac, 60Hz	TESTED BY	Brad Wu

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS / FAIL
1	2412	10.023	10.01	30	PASS
6	2437	10.069	10.03	30	PASS
11	2462	10.093	10.04	30	PASS



## 4.5 POWER SPECTRAL DENSITY MEASUREMENT

### 4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

### 4.5.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSP40	100040	Jun. 28, 2008

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.5.3 TEST PROCEDURE


The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3kHz RBW and 30kHz VBW, set sweep time = span/3kHz. The power spectral density was measured and recorded.

The sweep time is allowed to be longer than span/3kHz for a full response of the mixer in the spectrum analyzer.

#### 4.5.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.5.5 TEST SETUP



#### 4.5.6 EUT OPERATING CONDITION

Same as Item 4.3.6




#### 4.5.7 TEST RESULTS

##### 802.11b DSSS MODULATION

MODULATION TYPE	DBPSK	ENVIRONMENTAL CONDITIONS	26deg.C, 67%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60Hz	TESTED BY	Brad Wu


CHANNEL	CHANNEL FREQUENCY (MHz )	RF POWER LEVEL IN 3kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS / FAIL
1	2412	-20.29	8	PASS
6	2437	-20.19	8	PASS
11	2462	-20.34	8	PASS

CH 1






## CH 6



## CH 11






### 802.11g OFDM MODULATION

MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	26deg.C, 67%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60Hz	TESTED BY	Brad Wu


CHANNEL	CHANNEL FREQUENCY (MHz )	RF POWER LEVEL IN 3kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS / FAIL
1	2412	-23.43	8	PASS
6	2437	-23.22	8	PASS
11	2462	-23.33	8	PASS

#### CH 1






## CH 6



## CH 11





## 4.6 BAND EDGES MEASUREMENT

### 4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

### 4.6.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSP40	100040	Jun. 28, 2008

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. Set both RBW and VBW of spectrum analyzer to 100kHz and 300kHz with suitable frequency span including 100MHz bandwidth from band edge. The band edges was measured and recorded.

The spectrum plots (Peak RBW =100kHz, VBW = 300kHz; Average RBW = 1MHz, VBW = 10Hz) are attached on the following pages.

### 4.6.4 DEVIATION FROM TEST STANDARD

No deviation

### 4.6.5 EUT OPERATING CONDITION

Same as Item 4.3.6



#### 4.6.6 TEST RESULTS

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement in part 15.247(d).



#### 802.11b DSSS MODULATION



**NOTE 1:** The band edge emission plot on the next page shows 44.84dBc between carrier maximum power and local maximum emission in restrict band (2.34020GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 94.17dBuV/m (Peak), so the maximum field strength in restrict band is  $94.17 - 44.84 = 49.33$ dBuV/m which is under 74dBuV/m limit.



The band edge emission plot on the next page shows 57.89dBc between carrier maximum power and local maximum emission in restrict band (2.37100GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 89.62dBuV/m (Peak), so the maximum field strength in restrict band is  $89.62 - 57.89 = 31.73$ dBuV/m which is under 54dBuV/m limit.

**NOTE 2:** The band edge emission plot on the next second page shows 45.38dBc between carrier maximum power and local maximum emission in restrict band (2.49840GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 94.82dBuV/m (Peak), so the maximum field strength in restrict band is  $94.82 - 45.38 = 49.44$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot on the next third page shows 56.71dBc between carrier maximum power and local maximum emission in restrict band (2.50000GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 90.27dBuV/m (Peak), so the maximum field strength in restrict band is  $90.27 - 56.71 = 33.56$ dBuV/m which is under 54dBuV/m limit.











## 802.11g OFDM MODULATION



**NOTE 1:** The band edge emission plot on the next page shows 37.72dBc between carrier maximum power and local maximum emission in restrict band (2.38520GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 94.80dBuV/m (Peak), so the maximum field strength in restrict band is  $94.80 - 37.72 = 57.08$ dBuV/m which is under 74dBuV/m limit.



The band edge emission plot on the next page shows 48.89dBc between carrier maximum power and local maximum emission in restrict band (2.39000GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 84.71dBuV/m (Peak), so the maximum field strength in restrict band is  $84.71 - 48.89 = 35.82$ dBuV/m which is under 54dBuV/m limit.

**NOTE 2:** The band edge emission plot on the next second page shows 38.07dBc between carrier maximum power and local maximum emission in restrict band (2.49280GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 94.69dBuV/m (Peak), so the maximum field strength in restrict band is  $94.69 - 38.07 = 56.62$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot on the next third page shows 48.62dBc between carrier maximum power and local maximum emission in restrict band (2.48350GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 84.43dBuV/m (Peak), so the maximum field strength in restrict band is  $84.43 - 48.62 = 35.81$ dBuV/m which is under 54dBuV/m limit.









## 4.7 ANTENNA REQUIREMENT

### 4.7.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### 4.7.2 ANTENNA CONNECTED CONSTRUCTION

The antenna used in this product is PIFA antenna with UFL antenna connector. The maximum gain of the antenna is 2.2dBi.



## 5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



## 6. INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

<b>USA</b>	FCC, UL, A2LA
<b>Germany</b>	TUV Rheinland
<b>Japan</b>	VCCI
<b>Norway</b>	NEMKO
<b>Canada</b>	INDUSTRY CANADA, CSA
<b>R.O.C.</b>	TAF, BSMI, NCC
<b>Netherlands</b>	Telefication
<b>Singapore</b>	GOST-ASIA(MOU)
<b>Russia</b>	CERTIS(MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

[www.adt.com.tw/index.5/phtml](http://www.adt.com.tw/index.5/phtml). If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab:**  
Tel: 886-2-26052180  
Fax: 886-2-26051924

**Hsin Chu EMC/RF Lab:**  
Tel: 886-3-5935343  
Fax: 886-3-5935342

**Hwa Ya EMC/RF/Safety Telecom Lab:**  
Tel: 886-3-3183232  
Fax: 886-3-3185050

**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The address and road map of all our labs can be found in our web site also.



## 7. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.