

# RF Exposure Evaluation declaration

Product Name : Bluetooth handsfree speaker

Model No. : BTHF260

FCC ID. : TQ6BTHF260

Applicant : Shanghai Flaircomm Inc

Address : No211 North Urumqi Road, Suite 616, Shanghai 200040 P.R.  
China

Date of Receipt : 2006/09/22

Issued Date : 2006/010/13

Report No. : 06AS001

The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of QuieTek Corporation.

## 1. RF Exposure Evaluation

### 1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

$P_d$  = power density in  $\text{mW/cm}^2$

$P_{out}$  = output power to antenna in mW

$G$  = gain of antenna in linear scale

$\pi$  = 3.1416

$R$  = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE,  $1 \text{ mW/cm}^2$ . If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance  $r$  where the MPE limit is reached.

### 1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity:  $18^\circ\text{C}$  and 78% RH.

### 1.3. Test Result of RF Exposure Evaluation

Product : Bluetooth handsfree speaker  
Test Item : RF Exposure Evaluation  
Test Site : AC-3  
Test Mode : Transmitter

#### Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is  $-3.5\text{dBi}$  or  $0.45$  in linear scale.

#### Output Power Into Antenna & RF Exposure Evaluation Distance:

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
00	2402.00	0.2138	0.00001900
39	2441.00	0.2094	0.00001861
78	2480.00	0.2118	0.00001882

The power density  $P_d$  (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of  $1\text{mW/cm}^2$ .