



Test Report

Product Name : Bluetooth Speaker

Model No. : BTHF304

FCC ID : TQ6BTHF304

Applicant : Shanghai Flaircomm Technologies Inc.

Address : No. 5, Bibo Road, Keyuan Building 4F, Zhangjiang
Hi-Tech Park, Shanghai 201203 P.R. China

Date of Receipt : 2008/05/27

Issued Date : 2008/08/05

Report No. : 086S026-RF-US-P06V01

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by CNLA, NVLAP or any agency of the Government.
The test report shall not be reproduced except in full without the written approval of QuieTek Corporation.

Test Report Certification

Issued Date : 2008/08/05

Report No. : 086S026-RF-US-P06V01



Product Name : Bluetooth Speaker

Applicant : Shanghai Flaircomm Technologies Inc.

Address : No. 5, Bibo Road, Keyuan Building 4F, Zhangjiang
Hi-Tech Park, Shanghai 201203 P.R. China

Manufacturer : Shanghai Flaircomm Technologies Inc.

Address : No. 5, Bibo Road, Keyuan Building 4F, Zhangjiang
Hi-Tech Park, Shanghai 201203 P.R. China

Model No. : BTHF304

FCC ID : TQ6BTHF304

EUT Voltage : DC 3.7V

Trade Name : Flaircomm

Applicable Standard : FCC CFR Title 47 Part 15 Subpart C: 2007
ANSI C63.4: 2003

Test Result : Complied

Performed Location : SuZhou EMC laboratory
No.99 Hongye Rd., Suzhou Industrial Park Loufeng
Hi-Tech Development Zone., SuZhou, China
TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098
FCC Registration Number: 800392

Documented By :

(Any Liu)

Reviewed By :

(Dream Cao)

Approved By :

(Gene Chang)

Laboratory Information

We , **Quietek Corporation**, are an independent EMC and safety consultancy that was established the whole facility in our laboratories. The test facility has been accredited by the following accreditation Bodies in compliance with ISO 17025, EN 45001 and Guide 25:

Taiwan R.O.C.	: BSMI, DGT, CNLA
Germany	: TUV Rheinland
Norway	: Nemko, DNV
USA	: FCC, NVLAP
Japan	: VCCI

The related certificate for our laboratories about the test site and management system can be downloaded from Quietek Corporation's Web Site : <http://tw.quietek.com/modules/myalbum/>
The address and introduction of Quietek Corporation's laboratories can be founded in our Web site : <http://www.quietek.com/>
If you have any comments, Please don't hesitate to contact us. Our contact information is as below:

HsinChu Testing Laboratory :

No.75-2, 3rd Lin, Wangye Keng, Yonghxing Tsuen, Qionglin Shiang, Hsinchu County 307, Taiwan, R.O.C.
TEL:+886-3-592-8858 / FAX:+886-3-592-8859 E-Mail : service@quietek.com



LinKou Testing Laboratory :

No. 5, Ruei-Shu Valley, Ruei-Ping Tsuen, Lin-Kou Shiang, Taipei, Taiwan, R.O.C.
TEL : +886-2-8601-3788 / FAX : 886-2-8601-3789 E-Mail : service@quietek.com



Suzhou Testing Laboratory :

No.99 Hongye Rd., Suzhou Industrial Park Loufeng Hi-Tech Development Zone., SuZhou, China
TEL : +86-512-6251-5088 / FAX : 86-512-6251-5098 E-Mail : service@quietek.com



TABLE OF CONTENTS

Description	Page
1. General Information.....	7
1.1. EUT Description.....	7
1.2. Mode of Operation	9
1.3. Tested System Details	10
1.4. Configuration of Tested System	11
1.5. EUT Exercise Software.....	12
2. Technical Test.....	13
2.1. Summary of Test Result.....	13
2.2. Test Environment	14
3. Conducted Emission	15
3.1. Test Equipment.....	15
3.2. Test Setup.....	15
3.3. Limit.....	16
3.4. Test Procedure	16
3.5. Uncertainty	16
3.6. Test Result.....	16
4. Radiated Emission	17
4.1. Test Equipment.....	17
4.2. Test Setup.....	18
4.3. Limit.....	19
4.4. Test Procedure	19
4.5. Uncertainty	19
4.6. Test Result.....	20
5. 20dB Bandwidth	38
5.1. Test Equipment.....	38
5.2. Test Setup.....	38
5.3. Limit.....	38
5.4. Test Procedure	39
5.5. Uncertainty	39
5.6. Test Result.....	40
6. Carrier Frequency Separation	42
6.1. Test Equipment.....	42
6.2. Test Setup.....	42
6.3. Limit.....	42
6.4. Test Procedure	43
6.5. Uncertainty	43
6.6. Test Result.....	44

7.	Number of Hopping Frequencies.....	46
7.1.	Test Equipment.....	46
7.2.	Test Setup.....	46
7.3.	Limit.....	46
7.4.	Test Procedure	47
7.5.	Uncertainty	47
7.6.	Test Result.....	48
8.	Time of Occupancy (Dwell Time).....	51
8.1.	Test Equipment.....	51
8.2.	Test Setup.....	51
8.3.	Limit.....	51
8.4.	Test Procedure	52
8.5.	Uncertainty	52
8.6.	Test Result.....	53
9.	Peak Output Power	57
9.1.	Test Equipment.....	57
9.2.	Test Setup.....	57
9.3.	Limit....	57
9.4.	Test Procedure	58
9.5.	Uncertainty	58
9.6.	Test Result.....	59
10.	Band-edge Compliance of RF Conducted Emissions.....	61
10.1.	Test Equipment.....	61
10.2.	Test Setup	61
10.3.	Limit.....	61
10.4.	Test Procedure	62
10.5.	Uncertainty	62
10.6.	Test Result.....	63
11.	Spurious RF Conducted Emissions	65
11.1.	Test Equipment.....	65
11.2.	Test Setup.....	65
11.3.	Limit.....	65
11.4.	Test Procedure.....	66
11.5.	Uncertainty.....	66
11.6.	Test Result.....	67
12.	Radiated Emission Band Edge.....	69
12.1.	Test Equipment.....	69
12.2.	Test Setup	70

12.3. Limit..... 70

12.4. Test Procedure 70

12.5. Uncertainty 71

12.6. Test Result..... 72

1. General Information

1.1. EUT Description

Product Name	Bluetooth Speaker
Trade Name	Flaircomm
Model No.	BTHF304
FCC ID	TQ6BTHF304
Working Voltage	DC 3.7V
Frequency Range	2402 - 2480 MHz
Channel Number	79
Type of Modulation	FHSS
Data Rate	723 kbps
Channel Control	Auto
Antenna Type	Trace Antenna
Antenna Gain	Refer to the "Antenna List"

Component	
Car Charger	Manufacturer: Shanghai Flaircomm Technologies Inc M/N: TTX-GC-196C Input: 12~24VDC Output: 5.0VDC, 500mA Cable Out: Non-Shielded, 1.8m
USB Cable	Manufacturer: MORETHANALL(CHANGZHOU)ELECTRONICS CO.,LTD M/N: YK-C008-USB002

Bluetooth Working Frequency of Each Channel:							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2402 MHz	01	2403 MHz	02	2404 MHz	03	2405 MHz
04	2406 MHz	05	2407 MHz	06	2408 MHz	07	2409 MHz
08	2410 MHz	09	2411 MHz	10	2412 MHz	11	2413 MHz
12	2414 MHz	13	2415 MHz	14	2416 MHz	15	2417 MHz
16	2418 MHz	17	2419 MHz	18	2420 MHz	19	2421 MHz
20	2422 MHz	21	2423 MHz	22	2424 MHz	23	2425 MHz
24	2426 MHz	25	2427 MHz	26	2428 MHz	27	2429 MHz
28	2430 MHz	29	2431 MHz	30	2432 MHz	31	2433 MHz
32	2434 MHz	33	2435 MHz	34	2436 MHz	35	2437 MHz
36	2438 MHz	37	2439 MHz	38	2440 MHz	39	2441 MHz
40	2442 MHz	41	2443 MHz	42	2444 MHz	43	2445 MHz
44	2446 MHz	45	2447 MHz	46	2448 MHz	47	2449 MHz
48	2450 MHz	49	2451 MHz	50	2452 MHz	51	2453 MHz
52	2454 MHz	53	2455 MHz	54	2456 MHz	55	2457 MHz
56	2458 MHz	57	2459 MHz	58	2460 MHz	59	2461 MHz
60	2462 MHz	61	2463 MHz	62	2464 MHz	63	2465 MHz
64	2466 MHz	65	2467 MHz	66	2468 MHz	67	2469 MHz
68	2470 MHz	69	2471 MHz	70	2472 MHz	71	2473 MHz
72	2474 MHz	73	2475 MHz	74	2476 MHz	75	2477 MHz
76	2478 MHz	77	2479 MHz	78	2480 MHz	N/A	N/A

Antenna List

Antenna	Manufacturer	Model No.	Peak Gain
Bluetooth Antenna	Flaircomm Technologies Inc	BTHF304	0.54dBi for 2.4GHz

1.2. Mode of Operation

QuieTek has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was shown in this test report and defined as:


Test Mode
Mode 1: Transmit

1.3. Tested System Details

The types for all equipments, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product		Manufacturer	Model No.	Serial No.	Power Cord
1	N/A	N/A	N/A	N/A	N/A

1.4. Configuration of Tested System



1.5. EUT Exercise Software

1	Setup the EUT and simulators as shown on above
2	Turn on the power of EUT.
3	Use RF test control software Bluetest to set EUT work on continuously transmission mode.

2. Technical Test

2.1. Summary of Test Result

- ☒ No deviations from the test standards
- ☐ Deviations from the test standards as below description:

Performed Test Item	Normative References	Test Performed	Deviation
Conducted Emission	FCC CFR Title 47 Part 15 Subpart C: 2007 Section 15.207	N/A	N/A
Radiated Emission	FCC CFR Title 47 Part 15 Subpart C: 2007 Section 15.209	Yes	No
20dB Bandwidth	FCC CFR Title 47 Part 15 Subpart C: 2007 Section 15.247(a)(1)	Yes	No
Carrier Frequency Separation	FCC CFR Title 47 Part 15 Subpart C: 2007 Section 15.247(a)(1)	Yes	No
Number of Hopping Frequencies	FCC CFR Title 47 Part 15 Subpart C: 2007 Section 15.247(a)(1)(iii)	Yes	No
Time of Occupancy (Dwell Time)	FCC CFR Title 47 Part 15 Subpart C: 2007 Section 15.247(a)(1)(iii)	Yes	No
Peak Output Power	FCC CFR Title 47 Part 15 Subpart C: 2007 Section 15.247(b)(1)	Yes	No
Band-edge Compliance of RF Conducted Emissions	FCC CFR Title 47 Part 15 Subpart C: 2007 Section 15.215(c), 15.247(d)	Yes	No
Spurious RF Conducted Emissions	FCC CFR Title 47 Part 15 Subpart C: 2007 15.247(d)	Yes	No
Radiated Emission Band Edge	FCC CFR Title 47 Part 15 Subpart C: 2007 15.247(d)	Yes	No

2.2. Test Environment

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	21
Humidity (%RH)	25-75	50
Barometric pressure (mbar)	860-1060	950-1000

3. Conducted Emission


3.1. Test Equipment

Conducted Emission / SR-1

Instrument	Manufacturer	Type No.	Serial No.	Cal. Date
EMI Test Receiver	R&S	ESCI	100726	2008/02/07
Two-Line V-Network	R&S	ENV216	100013	2007/11/15
Two-Line V-Network	R&S	ENV216	100014	2007/11/15
50ohm Coaxial Switch	Anritsu	MP59B	6200464462	2007/11/25
50ohm Termination	SHX	TF2	07081401	2007/10/19
Coaxial Cable	Luthi	RG214	519358	2007/11/25
Temperature/Humidity Meter	zhicheng	ZC1-2	QT-TH004	2008/03/31

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

3.2. Test Setup



3.3. Limit

FCC Part 15 Subpart C Paragraph 15.207 Limits		
Frequency (MHz)	QP (dBuV)	AV (dBuV)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.

Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

3.4. Test Procedure

According to FCC Public Notice DA 00-705, March 30, 2000.

The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface. The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)

Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.

The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.

Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

3.5. Uncertainty

The measurement uncertainty is defined as ± 2.02 dB

3.6. Test Result

This product is a DC device, so this test item needn't perform.

4. Radiated Emission

4.1. Test Equipment

☐ Radiated Emission / AC-2

Instrument	Manufacturer	Type No.	Serial No.	Cal. Date
Spectrum Analyzer	Agilent	E4408B	MY45102679	2007/11/12
EMI Test Receiver	R&S	ESCI	100573	2008/05/10
Preamplifier	Quietek	AP-025C	QT-AP003	2007/11/25
Preamplifier	Quietek	AP-180C	CHM-0602012	2007/11/25
Bilog Type Antenna	Schaffner	CBL6112B	2932	2007/11/22
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	496	2007/11/25
High-Pass Filter	Wainwright	WHKX2.8/18G-12SS	SN1	2008/03/03
Band Reject Filter	Wainwright	WRCG2400/2485-2375 /2510-60/11SS	SN9	2008/03/03
High-Pass Filter	Wainwright	WHKX7.0/18G-8SS	SN16	2008/03/03
Low-Pass Filter	Wainwright	WLKS4500-9SS	SN2	2008/03/03
50ohm Coaxial Switch	Anritsu	MP59B	6200447304	2007/11/25
Coaxial Cable	Huber+Suhner	AC2-C	04	2007/11/25
Temperature/Humidity Meter	zhicheng	ZC1-2	QT-TH002	2008/03/31

☒ Radiated Emission / AC-3

Instrument	Manufacturer	Type No.	Serial No.	Cal. Date
Spectrum Analyzer	Agilent	N9010A	MY48030494	2008/04/24
EMI Test Receiver	R&S	ESCI	100176	2007/11/15
Preamplifier	Quietek	AP-025C	QT-AP004	2007/11/25
Preamplifier	Quietek	AP-180C	CHM-0602012	2007/11/25
Bilog Type Antenna	Schaffner	CBL6112D	22254	2007/11/22
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	496	2007/11/25
High-Pass Filter	Wainwright	WHKX2.8/18G-12SS	SN1	2008/03/03
Band Reject Filter	Wainwright	WRCG2400/2485-2375 /2510-60/11SS	SN9	2008/03/03
High-Pass Filter	Wainwright	WHKX7.0/18G-8SS	SN16	2008/03/03
Low-Pass Filter	Wainwright	WLKS4500-9SS	SN2	2008/03/03
50ohm Coaxial Switch	Anritsu	MP59B	6200464463	2007/11/25
Coaxial Cable	Huber+Suhner	AC2-C	05	2007/11/25


Temperature/Humidity Meter	zhicheng	ZC1-2	QT-TH003	2008/03/31
----------------------------	----------	-------	----------	------------

Note 1: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.


Note 2: The test instruments marked with "X" are used to measure the final test results.

4.2. Test Setup

Under 1GHz Test Setup:



Above 1GHz Test Setup:



4.3. Limit

FCC Part 15 Subpart C Paragraph 15.209		
Frequency (MHz)	Distance (m)	Level (dBuV/m)
30 - 88	3	40
88 - 216	3	43.5
216 - 960	3	46
Above 960	3	54

Note 1: The lower limit shall apply at the transition frequency.

Note 2: Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

Note 3: E field strength (dBuV/m) = 20 log E field strength (uV/m)

4.4. Test Procedure

According to FCC Public Notice DA 00-705, March 30, 2000.

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.4:2003 on radiated measurement.

The resolution bandwidth below 1GHz setting on the field strength meter is 120 kHz and above 1GHz is 1MHz.

The frequency range from 30MHz to 10th harmonic is checked.


Note: When doing emission measurement above 1GHz, the horn antenna will be bended down a little (as horn antenna have the narrow beamwidth) in order to keeping the antenna in the "cone of radiation" of EUT. This horn 3dB's beamwidth is 60 degrees for H-plane and 90 degrees for E-plane.

4.5. Uncertainty

The measurement uncertainty above 1G is defined as ± 3.9 dB
below 1G is defined as ± 3.8 dB


4.6. Test Result

Engineer : Robin	
Site : AC3 (3m Semi-Anechoic Chamber)	Time : 2008/06/30 - 09:46
Limit : FCC_SpartC_15.209_03M_QP	Margin : 0
EUT : Bluetooth Speaker	Probe : CBL6112D_22254(30-2000MHz) - HORIZONTAL
Power : DC 12V	Note : Mode 1: Transmit at channel 2402MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type	Ant Pos (cm)	Table Pos (deg)
1		200.750	10.221	10.196	20.417	-23.103	43.520	QUASIPeAK	106.200	75.400
2		250.675	12.236	14.346	26.582	-19.438	46.020	QUASIPeAK	126.000	99.500
3		401.025	15.957	8.733	24.690	-21.330	46.020	QUASIPeAK	140.000	125.000
4		500.500	17.348	7.267	24.615	-21.405	46.020	QUASIPeAK	100.000	84.900
5		625.125	19.601	3.196	22.797	-23.223	46.020	QUASIPeAK	203.000	77.900
6	*	750.250	22.002	4.626	26.628	-19.392	46.020	QUASIPeAK	114.000	82.300

Engineer : Robin	
Site : AC3 (3m Semi-Anechoic Chamber)	Time : 2008/06/30 - 09:48
Limit : FCC_SpartC_15.209_03M_QP	Margin : 0
EUT : Bluetooth Speaker	Probe : CBL6112D_22254(30-2000MHz) - VERTICAL
Power : DC 12V	Note : Mode 1: Transmit at channel 2402MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type	Ant Pos (cm)	Table Pos (deg)
1	*	73.650	6.646	15.701	22.347	-17.653	40.000	QUASIPeAK	100.000	36.400
2		124.750	11.337	13.590	24.926	-18.594	43.520	QUASIPeAK	100.000	78.500
3		200.750	10.221	9.496	19.717	-23.803	43.520	QUASIPeAK	106.300	105.000
4		275.125	12.399	13.848	26.247	-19.773	46.020	QUASIPeAK	100.000	49.300
5		500.450	17.346	7.372	24.718	-21.302	46.020	QUASIPeAK	100.000	116.900
6		750.250	22.002	-2.374	19.628	-26.392	46.020	QUASIPeAK	100.000	244.500

Engineer : Robin	
Site : AC3 (3m Semi-Anechoic Chamber)	Time : 2008/06/30 - 09:50
Limit : FCC_SpartC_15.209_03M_QP	Margin : 0
EUT : Bluetooth Speaker	Probe : CBL6112D_22254(30-2000MHz) - HORIZONTAL
Power : DC 12V	Note : Mode 1: Transmit at channel 2441MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type	Ant Pos (cm)	Table Pos (deg)
1		125.750	11.404	6.208	17.613	-25.907	43.520	QUASIPeAK	201.000	74.600
2	*	185.200	9.449	10.754	20.203	-23.317	43.520	QUASIPeAK	312.600	95.400
3		275.250	12.395	7.455	19.850	-26.170	46.020	QUASIPeAK	135.700	65.800
4		374.750	14.996	6.518	21.514	-24.506	46.020	QUASIPeAK	100.000	93.800
5		525.750	17.502	1.567	19.069	-26.951	46.020	QUASIPeAK	185.000	49.000
6		875.650	22.663	-0.401	22.262	-23.758	46.020	QUASIPeAK	109.500	215.700

Engineer : Robin	
Site : AC3 (3m Semi-Anechoic Chamber)	Time : 2008/06/30 - 09:50
Limit : FCC_SpartC_15.209_03M_QP	Margin : 0
EUT : Bluetooth Speaker	Probe : CBL6112D_22254(30-2000MHz) - VERTICAL
Power : DC 12V	Note : Mode 1: Transmit at channel 2441MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type	Ant Pos (cm)	Table Pos (deg)
1		42.250	16.379	1.022	17.401	-22.599	40.000	QUASIPeAK	100.000	62.900
2	*	175.500	9.881	11.956	21.837	-21.683	43.520	QUASIPeAK	112.600	84.900
3		226.250	12.333	5.764	18.097	-27.923	46.020	QUASIPeAK	100.000	253.900
4		275.525	12.387	9.066	21.453	-24.567	46.020	QUASIPeAK	100.000	169.400
5		375.350	15.005	4.099	19.104	-26.916	46.020	QUASIPeAK	100.000	354.000
6		876.250	22.662	-2.314	20.347	-25.673	46.020	QUASIPeAK	100.000	115.900

Engineer : Robin	
Site : AC3 (3m Semi-Anechoic Chamber)	Time : 2008/06/30 - 09:50
Limit : FCC_SpartC_15.209_03M_QP	Margin : 0
EUT : Bluetooth Speaker	Probe : CBL6112D_22254(30-2000MHz) - HORIZONTAL
Power : DC 12V	Note : Mode 1: Transmit at channel 2480MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type	Ant Pos (cm)	Table Pos (deg)
1		175.500	9.881	7.556	17.437	-26.083	43.520	QUASIPeAK	133.400	76.900
2		300.175	13.040	3.281	16.321	-29.699	46.020	QUASIPeAK	206.000	146.000
3	*	325.585	14.113	6.985	21.098	-24.922	46.020	QUASIPeAK	175.600	49.000
4		476.250	17.031	-0.276	16.755	-29.265	46.020	QUASIPeAK	203.000	116.900
5		575.750	19.198	-0.181	19.017	-27.003	46.020	QUASIPeAK	100.000	94.600
6		675.500	20.713	-2.193	18.520	-27.500	46.020	QUASIPeAK	114.800	71.900

Engineer : Robin	
Site : AC3 (3m Semi-Anechoic Chamber)	Time : 2008/06/30 - 09:50
Limit : FCC_SpartC_15.209_03M_QP	Margin : 0
EUT : Bluetooth Speaker	Probe : CBL6112D_22254(30-2000MHz) - VERTICAL
Power : DC 12V	Note : Mode 1: Transmit at channel 2480MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type	Ant Pos (cm)	Table Pos (deg)
1	*	52.825	11.348	6.665	18.013	-21.987	40.000	QUASIPeAK	100.000	44.800
2		97.250	9.192	9.818	19.010	-24.510	43.520	QUASIPeAK	100.000	46.600
3		300.175	13.040	7.181	20.221	-25.799	46.020	QUASIPeAK	122.800	136.500
4		425.275	16.199	3.489	19.688	-26.332	46.020	QUASIPeAK	112.900	326.000
5		524.700	17.470	4.404	21.874	-24.146	46.020	QUASIPeAK	100.000	106.600
6		675.050	20.709	1.137	21.846	-24.174	46.020	QUASIPeAK	105.000	92.600

Engineer : Robin	
Site : AC3 (3m Semi-Anechoic Chamber)	Time : 2008/06/29 - 11:19
Limit : FCC_SpartC_15.209_03M_PK	Margin : 0
EUT : Bluetooth Speaker	Probe : BBHA9120D_496(1-18GHz) - HORIZONTAL
Power : DC 12V	Note : Mode 1: Transmit at channel 2402MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type	Ant Pos (cm)	Table Pos (deg)
1		1595.000	-7.060	50.357	43.297	-30.673	73.970	PEAK	120.500	65.800
2	*	4796.667	3.490	55.493	58.983	-14.987	73.970	PEAK	100.000	165.200
3		7261.667	12.250	39.563	51.813	-22.157	73.970	PEAK	114.200	144.800

Engineer : Robin	
Site : AC3 (3m Semi-Anechoic Chamber)	Time : 2008/06/29 - 11:19
Limit : FCC_SpartC_15.209_03M_AV	Margin : 0
EUT : Bluetooth Speaker	Probe : BBHA9120D_496(1-18GHz) - HORIZONTAL
Power : DC 12V	Note : Mode 1: Transmit at channel 2402MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type	Ant Pos (cm)	Table Pos (deg)
1		1595.000	-7.060	33.500	26.440	-27.530	53.970	AVERAGE	120.500	65.800
2		4796.667	3.490	34.900	38.390	-15.580	53.970	AVERAGE	100.000	165.200
3	*	7261.667	12.250	28.900	41.150	-12.820	53.970	AVERAGE	114.200	144.800

Engineer : Robin	
Site : AC3 (3m Semi-Anechoic Chamber)	Time : 2008/06/29 - 11:20
Limit : FCC_SpartC_15.209_03M_PK	Margin : 0
EUT : Bluetooth Speaker	Probe : BBHA9120D_496(1-18GHz) - VERTICAL
Power : DC 12V	Note : Mode 1: Transmit at channel 2402MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type	Ant Pos (cm)	Table Pos (deg)
1		1595.000	-7.060	52.076	45.016	-28.954	73.970	PEAK	100.000	187.000
2	*	4796.667	3.490	54.947	58.437	-15.533	73.970	PEAK	100.000	205.000
3		7176.667	12.693	38.644	51.337	-22.633	73.970	PEAK	106.000	328.000

Engineer : Robin	
Site : AC3 (3m Semi-Anechoic Chamber)	Time : 2008/06/29 - 11:20
Limit : FCC_SpartC_15.209_03M_AV	Margin : 0
EUT : Bluetooth Speaker	Probe : BBHA9120D_496(1-18GHz) - VERTICAL
Power : DC 12V	Note : Mode 1: Transmit at channel 2402MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type	Ant Pos (cm)	Table Pos (deg)
1		1595.000	-7.060	36.200	29.140	-24.830	53.970	AVERAGE	100.000	187.000
2		4796.667	3.490	37.900	41.390	-12.580	53.970	AVERAGE	100.000	205.000
3	*	7176.667	12.693	29.400	42.093	-11.877	53.970	AVERAGE	106.000	328.000

Engineer : Robin	
Site : AC3 (3m Semi-Anechoic Chamber)	Time : 2008/06/29 - 11:20
Limit : FCC_SpartC_15.209_03M_PK	Margin : 0
EUT : Bluetooth Speaker	Probe : BBHA9120D_496(1-18GHz) - HORIZONTAL
Power : DC 12V	Note : Mode 1: Transmit at channel 2441MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type	Ant Pos (cm)	Table Pos (deg)
1		1623.333	-7.067	51.309	44.242	-29.728	73.970	PEAK	105.000	113.600
2		4881.667	3.633	49.120	52.753	-21.217	73.970	PEAK	103.600	72.800
3	*	7318.333	12.017	42.662	54.679	-19.291	73.970	PEAK	100.000	165.000

Engineer : Robin	
Site : AC3 (3m Semi-Anechoic Chamber)	Time : 2008/06/29 - 11:20
Limit : FCC_SpartC_15.209_03M_AV	Margin : 0
EUT : Bluetooth Speaker	Probe : BBHA9120D_496(1-18GHz) - HORIZONTAL
Power : DC 12V	Note : Mode 1: Transmit at channel 2441MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type	Ant Pos (cm)	Table Pos (deg)
1		1623.333	-7.067	31.300	24.233	-29.737	53.970	AVERAGE	105.000	113.600
2		4881.667	3.633	30.200	33.833	-20.137	53.970	AVERAGE	103.600	72.800
3	*	7318.333	12.017	26.600	38.617	-15.353	53.970	AVERAGE	100.000	165.000

Engineer : Robin	
Site : AC3 (3m Semi-Anechoic Chamber)	Time : 2008/06/29 - 11:20
Limit : FCC_SpartC_15.209_03M_PK	Margin : 0
EUT : Bluetooth Speaker	Probe : BBHA9120D_496(1-18GHz) - VERTICAL
Power : DC 12V	Note : Mode 1: Transmit at channel 2441MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type	Ant Pos (cm)	Table Pos (deg)
1		1623.333	-7.067	51.028	43.961	-30.009	73.970	PEAK	100.000	166.800
2		4881.667	3.633	49.995	53.628	-20.342	73.970	PEAK	105.400	117.500
3	*	7318.333	12.017	46.084	58.101	-15.869	73.970	PEAK	100.000	93.400

Engineer : Robin	
Site : AC3 (3m Semi-Anechoic Chamber)	Time : 2008/06/29 - 11:20
Limit : FCC_SpartC_15.209_03M_AV	Margin : 0
EUT : Bluetooth Speaker	Probe : BBHA9120D_496(1-18GHz) - VERTICAL
Power : DC 12V	Note : Mode 1: Transmit at channel 2441MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type	Ant Pos (cm)	Table Pos (deg)
1		1623.333	-7.067	32.800	25.733	-28.237	53.970	AVERAGE	100.000	166.800
2		4881.667	3.633	30.600	34.233	-19.737	53.970	AVERAGE	105.400	117.500
3	*	7318.333	12.017	28.400	40.417	-13.553	53.970	AVERAGE	100.000	93.400

Engineer : Robin	
Site : AC3 (3m Semi-Anechoic Chamber)	Time : 2008/06/29 - 11:20
Limit : FCC_SpartC_15.209_03M_PK	Margin : 0
EUT : Bluetooth Speaker	Probe : BBHA9120D_496(1-18GHz) - HORIZONTAL
Power : DC 12V	Note : Mode 1: Transmit at channel 2480MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type	Ant Pos (cm)	Table Pos (deg)
1		1651.667	-7.080	54.499	47.419	-26.551	73.970	PEAK	108.000	65.900
2		4966.667	4.073	47.532	51.605	-22.365	73.970	PEAK	100.000	122.000
3	*	7431.667	11.500	41.896	53.396	-20.574	73.970	PEAK	100.000	245.000

Engineer : Robin	
Site : AC3 (3m Semi-Anechoic Chamber)	Time : 2008/06/29 - 11:20
Limit : FCC_SpartC_15.209_03M_AV	Margin : 0
EUT : Bluetooth Speaker	Probe : BBHA9120D_496(1-18GHz) - HORIZONTAL
Power : DC 12V	Note : Mode 1: Transmit at channel 2480MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type	Ant Pos (cm)	Table Pos (deg)
1		1651.667	-7.080	35.900	28.820	-25.150	53.970	AVERAGE	108.000	65.900
2		4966.667	4.073	30.200	34.273	-19.697	53.970	AVERAGE	100.000	122.000
3	*	7431.667	11.500	26.300	37.800	-16.170	53.970	AVERAGE	100.000	245.000

Engineer : Robin	
Site : AC3 (3m Semi-Anechoic Chamber)	Time : 2008/06/29 - 11:20
Limit : FCC_SpartC_15.209_03M_PK	Margin : 0
EUT : Bluetooth Speaker	Probe : BBHA9120D_496(1-18GHz) - VERTICAL
Power : DC 12V	Note : Mode 1: Transmit at channel 2480MHz



		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type	Ant Pos (cm)	Table Pos (deg)
1		1651.667	-7.080	55.070	47.990	-25.980	73.970	PEAK	100.000	114.500
2		4966.667	4.073	47.362	51.435	-22.535	73.970	PEAK	105.800	94.000
3	*	7431.667	11.500	45.613	57.113	-16.857	73.970	PEAK	100.000	168.400

Engineer : Robin	
Site : AC3 (3m Semi-Anechoic Chamber)	Time : 2008/06/29 - 11:20
Limit : FCC_SpartC_15.209_03M_AV	Margin : 0
EUT : Bluetooth Speaker	Probe : BBHA9120D_496(1-18GHz) - VERTICAL
Power : DC 12V	Note : Mode 1: Transmit at channel 2480MHz



		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type	Ant Pos (cm)	Table Pos (deg)
1		1651.667	-7.080	37.500	30.420	-23.550	53.970	AVERAGE	100.000	114.500
2		4966.667	4.073	30.600	34.673	-19.297	53.970	AVERAGE	105.800	94.000
3	*	7431.667	11.500	30.600	42.100	-11.870	53.970	AVERAGE	100.000	168.400

5. 20dB Bandwidth


5.1. Test Equipment

20dB Bandwidth / AC-4

Instrument	Manufacturer	Type No.	Serial No.	Cal. Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2008/06/11
Coaxial Cable	Huber+Suhner	AC4-RF	09	2007/11/25
Temperature/Humidity Meter	zhicheng	ZC1-2	QT-TH007	2008/03/09

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

5.2. Test Setup



5.3. Limit

- For frequency hopping systems operating in 2400-2483.5 MHz band, no limitation.
- For frequency hopping systems operating in 902-928 MHz band, the maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.
- For frequency hopping systems operating in 5725-5850 MHz band, the maximum 20 dB bandwidth of the hopping channel is 1 MHz.

5.4. Test Procedure

According to FCC Public Notice DA 00-705, March 30, 2000.

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20dB bandwidth, centered on a hopping channel

RBW $\geq$ 1% of the 20dB bandwidth

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize.

Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation.

5.5. Uncertainty


The measurement uncertainty is defined as ± 1 kHz

5.6. Test Result


Product	:	Bluetooth Speaker
Test Item	:	20dB Bandwidth
Test Site	:	AC-4
Test Mode	:	Mode 1: Transmit

Channel No.	Frequency (MHz)	20dB Bandwidth (kHz)	Limit (kHz)	Result
00	2402	915	N/A	Pass
39	2441	935	N/A	Pass
78	2480	938	N/A	Pass


Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)



6. Carrier Frequency Separation


6.1. Test Equipment

Carrier Frequency Separation / AC-4

Instrument	Manufacturer	Type No.	Serial No.	Cal. Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2008/06/11
Coaxial Cable	Huber+Suhner	AC4-RF	09	2007/11/25
Temperature/Humidity Meter	zhicheng	ZC1-2	QT-TH007	2008/03/09

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

6.2. Test Setup



6.3. Limit

- Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudorandomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each

transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

- For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; If the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.
- Frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75 hopping frequencies. The maximum 20 dB bandwidth of the hopping channel is 1 MHz. The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30 second period.

6.4. Test Procedure

According to FCC Public Notice DA 00-705, March 30, 2000.

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW) $\geq$ 1% of the span

Video (or Average) Bandwidth VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

6.5. Uncertainty


The measurement uncertainty is defined as ± 1 kHz

6.6. Test Result


Product	:	Bluetooth Speaker
Test Item	:	Carrier Frequency Separation
Test Site	:	AC-4
Test Mode	:	Mode 1: Transmit

Channel No.	Frequency (MHz)	Carrier Frequency Separation (kHz)	Limit (kHz)	Result
00	2402	1000	>25 kHz or 2/3 of 20 dB BW	Pass
39	2441	1000	>25 kHz or 2/3 of 20 dB BW	Pass
78	2480	1000	>25 kHz or 2/3 of 20 dB BW	Pass


Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)



7. Number of Hopping Frequencies


7.1. Test Equipment

Number of Hopping Frequencies / AC-4

Instrument	Manufacturer	Type No.	Serial No.	Cal. Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2008/06/11
Coaxial Cable	Huber+Suhner	AC4-RF	09	2007/11/25
Temperature/Humidity Meter	zhicheng	ZC1-2	QT-TH007	2008/03/09

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

7.2. Test Setup



7.3. Limit

- For frequency hopping systems operating in the 2400-2483.5 MHz band shall use at least 15 hopping frequencies.
- For frequency hopping systems operating in 902-928 MHz band shall use at least 50 hopping frequencies.
- For frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75 hopping frequencies.

7.4. Test Procedure

According to FCC Public Notice DA 00-705, March 30, 2000.

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW $\geq$ 1% of the span

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. It may prove necessary to bread the span up to sections, in order to clearly show all of the hopping frequencies.

7.5. Uncertainty


The measurement uncertainty is defined as ± 1 kHz

7.6. Test Result


Product	:	Bluetooth Speaker
Test Item	:	Number of Hopping Frequencies
Test Site	:	AC-4
Test Mode	:	Mode 1: Transmit

Frequency Band (MHz)	Number of Hopping Frequencies	Limit	Result
2400 - 2483.5	79	>15	Pass


2402 - 2421 MHz




2422 - 2441 MHz



2442 - 2461 MHz



2462 - 2480 MHz



8. Time of Occupancy (Dwell Time)


8.1. Test Equipment

Time of Occupancy (Dwell Time) / AC-4

Instrument	Manufacturer	Type No.	Serial No.	Cal. Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2008/06/11
Coaxial Cable	Huber+Suhner	AC4-RF	09	2007/11/25
Temperature/Humidity Meter	zhicheng	ZC1-2	QT-TH007	2008/03/09

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

8.2. Test Setup



8.3. Limit

- For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; If the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

- Frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75 hopping frequencies. The maximum 20 dB bandwidth of the hopping channel is 1 MHz. The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30 second period.
- Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

8.4. Test Procedure

According to FCC Public Notice DA 00-705, March 30, 2000.

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = zero span, centered on a hopping channel

RBW = 1MHz

VBW $\geq$ RBW

Sweep = as necessary to capture the entire dwell time per hopping channel

Detector function = peak

Trace = max hold

If possible, use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation.

8.5. Uncertainty

The measurement uncertainty is defined as ± 0.1 us

8.6. Test Result



Product	:	Bluetooth Speaker
Test Item	:	Time of Occupancy (Dwell Time)
Test Site	:	AC-4
Test Mode	:	Mode 1: Transmit

Channel No.	Frequency (MHz)	Time of Occupancy (ms)	Limit (ms)	Result
00	2402	125.344	< 400	Pass
39	2441	125.344	< 400	Pass
78	2480	125.344	< 400	Pass



Test Time Period: $0.4 \times 79 = 31.6\text{sec}$, Hopping Times Within 1sec: $40/50\text{msec} = 800\text{ hops/sec}$.

- 2402MHz, The Maximum Occupancy Time Within 31.6sec: $(391.7 \mu\text{s} \times 800) / 79 \times 31.6 = 125.344\text{msec}$
- 2441MHz, The Maximum Occupancy Time Within 31.6sec: $(391.7 \mu\text{s} \times 800) / 79 \times 31.6 = 125.344\text{msec}$
- 2480MHz, The Maximum Occupancy Time Within 31.6sec: $(391.7 \mu\text{s} \times 800) / 79 \times 31.6 = 125.344\text{msec}$



Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)



9. Peak Output Power


9.1. Test Equipment

Peak Output Power / AC-4

Instrument	Manufacturer	Type No.	Serial No.	Cal. Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2008/06/11
Coaxial Cable	Huber+Suhner	AC4-RF	09	2007/11/25
Temperature/Humidity Meter	zhicheng	ZC1-2	QT-TH007	2008/03/09

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

9.2. Test Setup



9.3. Limit

- For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.
- For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels.

Note: the conducted output power limit specified above is based on the use the antennas with directional gains that do not exceed 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values above, as appropriate, by the amount in dB that the directional gain of antenna exceeds 6 dBi.

9.4. Test Procedure

According to FCC Public Notice DA 00-705, March 30, 2000.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20dB bandwidth, centered on a hopping channel

RBW > the 20 dB bandwidth of the emission being measured.

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power (don't forget added the external attenuation and cable loss).

9.5. Uncertainty

The measurement uncertainty is defined as ± 1.0 dB


9.6. Test Result

Product	:	Bluetooth Speaker
Test Item	:	Peak Output Power
Test Site	:	AC-4
Test Mode	:	Mode 1: Transmit


Channel No.	Frequency (MHz)	Measurement Level (dBm)	External Attenuation (dBm)	Peak Output Power (dBm)	Limit (dBm)	Result
00	2402	5.15	0.32	5.47	30	Pass
39	2441	4.88	0.35	5.23	30	Pass
78	2480	3.64	0.40	4.04	30	Pass

Note: The antenna gain of transmitter is less than 6 dBi and other than fixed, point-to-point operation, therefore the limit is 30 dBm.


Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)



10. Band-edge Compliance of RF Conducted Emissions


10.1. Test Equipment

Band-edge Compliance of RF Conducted Emissions / AC-4

Instrument	Manufacturer	Type No.	Serial No.	Cal. Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2008/06/11
Coaxial Cable	Huber+Suhner	AC4-RF	09	2007/11/25
Temperature/Humidity Meter	zhicheng	ZC1-2	QT-TH007	2008/03/09

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

10.2. Test Setup



10.3. Limit

- Intentional radiators operating under the alternative provisions to the general emission limits as contained in 15.217 through 15.257 and in Subpart E of FCC part 15, must be designed to ensure that 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.
- In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is

produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) of FCC part 15 is not required.

10.4. Test Procedure

According to FCC Public Notice DA 00-705, March 30, 2000.

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation.

RBW $\geq$ 1% of the span

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge.

Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. The marker-delta value now displayed must comply with the limit specified in this Section.


Now, using the same instrument settings, enable the hopping function of the EUT. Allow the trace to stabilize. Follow the same procedure listed above to determine if any spurious emissions caused by the hopping function also comply with the specified limit.

10.5. Uncertainty


The measurement uncertainty is defined as ± 1.0 dB

10.6. Test Result

Product	:	Bluetooth Speaker
Test Item	:	Band-edge Compliance of RF Conducted Emissions
Test Site	:	AC-4
Test Mode	:	Mode 1: Transmit



Channel 78 (2480MHz)



11. Spurious RF Conducted Emissions


11.1. Test Equipment

Spurious RF Conducted Emissions / AC-4

Instrument	Manufacturer	Type No.	Serial No.	Cal. Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2008/06/11
Coaxial Cable	Huber+Suhner	AC4-RF	09	2007/11/25
Temperature/Humidity Meter	zhicheng	ZC1-2	QT-TH007	2008/03/09

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

11.2. Test Setup



11.3. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this

paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) of FCC part 15 is not required.

11.4. Test Procedure

According to FCC Public Notice DA 00-705, March 30, 2000.

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold


Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded. The level displayed must comply with the limit specified in this section.

11.5. Uncertainty


The measurement uncertainty is defined as ± 1.0 dB

11.6. Test Result


Product	:	Bluetooth Speaker
Test Item	:	Spurious RF Conducted Emissions
Test Site	:	AC-4
Test Mode	:	Mode 1: Transmit



Channel 39 (2441MHz)



Channel 78 (2480MHz)



12. Radiated Emission Band Edge

12.1. Test Equipment

☐ Radiated Emission Band Edge / AC-2

Instrument	Manufacturer	Type No.	Serial No.	Cal. Date
Spectrum Analyzer	Agilent	E4408B	MY45102679	2007/11/12
EMI Test Receiver	R&S	ESCI	100573	2008/05/10
Preamplifier	Quietek	AP-025C	QT-AP003	2007/11/25
Preamplifier	Quietek	AP-180C	CHM-0602012	2007/11/25
Bilog Type Antenna	Schaffner	CBL6112B	2932	2007/11/22
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	496	2007/11/25
50ohm Coaxial Switch	Anritsu	MP59B	6200447304	2007/11/25
Coaxial Cable	Huber+Suhner	AC2-C	04	2007/11/25
Temperature/Humidity Meter	zhicheng	ZC1-2	QT-TH002	2008/03/31


☒ Radiated Emission Band Edge / AC-3

Instrument	Manufacturer	Type No.	Serial No.	Cal. Date
Spectrum Analyzer	Agilent	N9010A	MY48030494	2008/04/24
EMI Test Receiver	R&S	ESCI	100176	2007/11/15
Preamplifier	Quietek	AP-025C	QT-AP004	2007/11/25
Preamplifier	Quietek	AP-180C	CHM-0602012	2007/11/25
Bilog Type Antenna	Schaffner	CBL6112D	22254	2007/11/22
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	496	2007/11/25
50ohm Coaxial Switch	Anritsu	MP59B	6200464463	2007/11/25
Coaxial Cable	Huber+Suhner	AC2-C	05	2007/11/25
Temperature/Humidity Meter	zhicheng	ZC1-2	QT-TH003	2008/03/31

Note 1: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

Note 2: The test instruments marked with "X" are used to measure the final test results.

12.2. Test Setup



12.3. Limit

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a) of FCC part 15.

12.4. Test Procedure

According to FCC Public Notice DA 00-705, March 30, 2000.

This test is required for any spurious emission or modulation product that falls in a Restricted Band, as defined in Section 15.205 of FCC part 15. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.4 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being

corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b) of FCC part 15.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209 of FCC Part 15. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a “duty cycle correction factor”, derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit of FCC part 15.


If the emission on which a radiated measurement must be made is located at the edge of the authorized band of operation, then the alternative “marker-delta” method may be employed.

12.5. Uncertainty

The measurement uncertainty above 1G is defined as $\pm 3.9 \text{ dB}$
below 1G is defined as $\pm 3.8 \text{ dB}$

12.6. Test Result

Engineer : Robin	
Site : AC3 (3m Semi-Anechoic Chamber)	Time : 2008/06/28 - 19:00
Limit : FCC_SpartC_15.209_03M_PK	Margin : 0
EUT : Bluetooth Speaker	Probe : BBHA9120D_496(1-18GHz) - HORIZONTAL
Power : DC 12V	Note : Mode 1: Transmit at channel 2402MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type
1		2386.500	-3.212	42.033	38.821	-35.149	73.970	PEAK
2		2390.000	-3.202	40.653	37.451	-36.519	73.970	PEAK
3	*	2402.167	-3.199	89.574	86.374	N/A	N/A	PEAK

Engineer : Robin	
Site : AC3 (3m Semi-Anechoic Chamber)	Time : 2008/06/28 - 19:03
Limit : FCC_SpartC_15.209_03M_AV	Margin : 0
EUT : Bluetooth Speaker	Probe : BBHA9120D_496(1-18GHz) - HORIZONTAL
Power : DC 12V	Note : Mode 1: Transmit at channel 2402MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type
1		2386.000	-3.213	28.724	25.510	-28.460	53.970	AVERAGE
2		2390.000	-3.202	27.327	24.125	-29.845	53.970	AVERAGE
3	*	2402.500	-3.200	50.106	46.906	N/A	N/A	AVERAGE

Engineer : Robin	
Site : AC3 (3m Semi-Anechoic Chamber)	Time : 2008/06/28 - 18:39
Limit : FCC_SpartC_15.209_03M_PK	Margin : 0
EUT : Bluetooth Speaker	Probe : BBHA9120D_496(1-18GHz) - VERTICAL
Power : DC 12V	Note : Mode 1: Transmit at channel 2402MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type
1		2385.667	-3.214	42.029	38.814	-35.156	73.970	PEAK
2		2390.000	-3.202	40.904	37.702	-36.268	73.970	PEAK
3	*	2402.167	-3.199	92.829	89.629	N/A	N/A	PEAK

Engineer : Robin	
Site : AC3 (3m Semi-Anechoic Chamber)	Time : 2008/06/28 - 18:53
Limit : FCC_SpartC_15.209_03M_AV	Margin : 0
EUT : Bluetooth Speaker	Probe : BBHA9120D_496(1-18GHz) - VERTICAL
Power : DC 12V	Note : Mode 1: Transmit at channel 2402MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type
1		2386.167	-3.213	28.378	25.165	-28.805	53.970	AVERAGE
2		2390.000	-3.202	27.339	24.137	-29.833	53.970	AVERAGE
3	*	2402.667	-3.200	50.245	47.045	N/A	N/A	AVERAGE

Engineer : Robin	
Site : AC3 (3m Semi-Anechoic Chamber)	Time : 2008/06/28 - 19:06
Limit : FCC_SpartC_15.209_03M_PK	Margin : 0
EUT : Bluetooth Speaker	Probe : BBHA9120D_496(1-18GHz) - HORIZONTAL
Power : DC 12V	Note : Mode 1: Transmit at channel 2480MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type
1	*	2479.850	-3.187	83.424	80.237	N/A	N/A	PEAK
2		2483.500	-3.177	41.987	38.810	-35.160	73.970	PEAK
3		2485.600	-3.171	42.391	39.220	-34.750	73.970	PEAK

Engineer : Robin	
Site : AC3 (3m Semi-Anechoic Chamber)	Time : 2008/06/28 - 19:07
Limit : FCC_SpartC_15.209_03M_AV	Margin : 0
EUT : Bluetooth Speaker	Probe : BBHA9120D_496(1-18GHz) - HORIZONTAL
Power : DC 12V	Note : Mode 1: Transmit at channel 2480MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type
1	*	2479.700	-3.188	47.281	44.093	N/A	N/A	AVERAGE
2		2483.500	-3.177	27.679	24.502	-29.468	53.970	AVERAGE
3		2495.900	-3.140	27.493	24.353	-29.617	53.970	AVERAGE

Engineer : Robin	
Site : AC3 (3m Semi-Anechoic Chamber)	Time : 2008/06/28 - 19:09
Limit : FCC_SpartC_15.209_03M_PK	Margin : 0
EUT : Bluetooth Speaker	Probe : BBHA9120D_496(1-18GHz) - VERTICAL
Power : DC 12V	Note : Mode 1: Transmit at channel 2480MHz



		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type
1	*	2479.850	-3.187	89.677	86.490	N/A	N/A	PEAK
2		2483.500	-3.177	44.158	40.981	-32.989	73.970	PEAK
3		2492.900	-3.149	41.922	38.773	-35.197	73.970	PEAK

Engineer : Robin	
Site : AC3 (3m Semi-Anechoic Chamber)	Time : 2008/06/28 - 19:11
Limit : FCC_SpartC_15.209_03M_AV	Margin : 0
EUT : Bluetooth Speaker	Probe : BBHA9120D_496(1-18GHz) - VERTICAL
Power : DC 12V	Note : Mode 1: Transmit at channel 2480MHz



		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type
1	*	2479.400	-3.189	52.055	48.866	N/A	N/A	AVERAGE
2		2483.500	-3.177	29.060	25.883	-28.087	53.970	AVERAGE
3		2496.000	-3.140	28.720	25.580	-28.390	53.970	AVERAGE