

Report Number: F690501/RF-RTL007988

Page: 1

of

6

MPE TEST REPORT

of

FCC CFR 47 part 1, 1.1307(b), 1.1310

FCC ID: TQ8-AC111DFEE

Equipment Under Test : DIGITAL CAR AUDIO SYSTEM

AC111DFEE (Alt.: AC101DFEE, AC101DFEG,

AC111DFEG, AC111DFDG, AC111DFGG, Model Name

AC111DFGN, AC111DFGE, AC111DFGL,

AC111DFUG)

Applicant : Hyundai MOBIS Co., Ltd.

: Hyundai MOBIS Co., Ltd. Manufacturer

Date of Test(s) : 2014.08.14 ~ 2014.08.29

Date of Issue : 2014.09.02

In the configuration tested, the EUT complied with the standards specified above.

Tested By: Date: 2014.09.02 Harim Lee Approved By: 2014.09.02 Date:

Hyunchae You

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.



Report Number: F690501/RF-RTL007988 Page: 2 of 6

INDEX

Table of Contents	Page
1. General Information	3
2. RF Exposure Evaluation	5



Report Number: F690501/RF-RTL007988 Page: 3 of 6

1. General Information

1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

-Wireless Div. 2FL, 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 435-837

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.

Telephone : +82 31 428 5700

FAX : +82 31 427 2370

1.2. Details of Applicant

Applicant : Hyundai MOBIS Co., Ltd.

Address : 69-23, Hansam-ro, Deoksan-myeon, Jincheong-gun, Chungcheongbuk-do

Contact Person: Choi, Seung-Hoon Phone No.: +82 31 260 0098

1.3. Description of EUT

Kind of Product	DIGITAL CAR AUDIO SYSTEM	
Model Name	AC111DFEE (Alt.: AC101DFEE, AC101DFEG, AC111DFEG, AC111DFDG, AC111DFGG, AC111DFGN, AC111DFGE, AC111DFGL, AC111DFUG)	
Power Supply	DC 14.4 V	
Frequency Range	2 402 MHz ~ 2 480 MHz	
Modulation Technique	GFSK, π/4DQPSK, 8DPSK	
Number of Channels	79	
Antenna Type	Internal type	
Antenna Gain	3.5 dBi	

1.4. Test report revision

Revision	Report number	Date of Issue	Description
0	F690501/RF-RTL007988	2014.09.02	Initial



Report Number: F690501/RF-RTL007988 Page: 4 of 6

1.5. Alternative models

Model name		Specification
Basic model AC111DFEE		R+CD+MP3+RDS+BT+VR
	AC101DFEE	R+CD+MP3+RDS
	AC101DFEG	R+CD+MP3
	AC111DFEG	R+CD+MP3+BT+VR, Different region
	AC111DFDG	R+CD+MP3+BT+VR, Different region
Alternative model	AC111DFGG	R+CD+MP3+BT, Different region
	AC111DFGN	R+CD+MP3+BT, Different region
	AC111DFGE	R+CD+MP3+BT, Different region
	AC111DFGL	R+CD+MP3+BT, Different region
	AC111DFUG	R+CD+MP3+BT, Different region



Report Number: F690501/RF-RTL007988 Page: 5 of 6

2. RF Exposure Evaluation

2.1. Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(b), 1.1310

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in §1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (썐)	Electric Field Strength(V/m)	Magnetic Field Strength (A/m)	Power Density (ﷺ)	Average Time
(A) Limits for Occupational /Control Exposures				
300 – 1 500			F/300	6
1 500 – 100 000			5	6
(B) Limits for General Population/Uncontrol Exposures				
300 – 1 500			F/1500	30
<u>1 500 – 100 000</u>			1	<u>30</u>

2.1.1. Friis transmission formula: Pd = (Pout*G)/(4*pi*R²)

Where Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.141 6

R = distance between observation point and center of the radiator in cm

Pd the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.



Report Number: F690501/RF-RTL007988 Page: 6 of 6

2.1.2. Test Result of RF Exposure Evaluation

Test Item : RF Exposure Evaluation Data

Test Mode : Normal Operation

2.1.3. Output Power into Antenna & RF Exposure Evaluation Distance

Channel	Output Average Power to Antenna (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (㎡/c㎡)	LIMITS (mW/cm²)
Maximum tune up tolerance	4.00	3.50	0.001 119	1

Note:

^{1.} The power density Pd (5th column) at a distance of 20 cm calculated from the friis transmission formula is far below the limit of 1 mW/cm².