FCC/IC TEST REPORT

Test report No.:

EMC-FCC-R0132

FCC ID:

TQ8-AC1B0C2AN

IC:

5074A-AC1B0C2KN

Type of equipment:

DIGITAL CAR AUDIO SYSTEM

Basic Model Name:

AC1B0C2AN

Variant Model Name:

AC1B0C2KN, AC1B0C2AX

Applicant:

Hyundai Mobis Co., Ltd.

Max.RF Output Power:

2.43 dBm

FCC Rule Part(s):

FCC Part 15 Subpart C 15.247

IC Rule:

RSS-210, RSS-GEN

Frequency Range:

2 402 MHz ~ 2 480 MHz

Test result:

Complied

The above equipment was tested by EMC compliance Testing Laboratory for compliance with the requirements of FCC Rules and Regulations.

The results of testing in this report apply to the product/system which was tested only. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Date of test: 2014. 01. 06 ~ 08

Issued date: 2014. 01. 16

Tested by:

Approved by

YU, SANG HOON



[Contents]

1. Client information	3
2. Laboratory information	4
3. Description of E.U.T.	5
3.1 Basic description	5
3.2 General description	5
3.3 Test frequency	6
3.4 Test Voltage	6
4. Summary of test results	7
4.1 Standards & results	7
4.2 Uncertainty	7
5. Test results	8
5.1 Antenna Requirement	8
5.2 Maximum Peak Output Power	9
5.3 Carrier Frequency Separation	14
5.4 20 dB Channel Bandwidth	19
5.5 Number of Hopping Channels	27
5.6 Time of Occupancy(Dwell Time)	30
5.7 Spurious Emission, Band edge, and Restricted bands	35
5.8 Receiver Spurious Emissions	55
5.9 RF Exposure	62
6. Test equipment used for test	63



1. Client information

Applicant: Hyundai Mobis Co., Ltd.

Address: 80-9, Mabook-dong, Giheung-gu, Yongin-shi, Gyunggi-do,

Korea (446-912)

Telephone number: +82-31-260-0092

Facsimile number: +82-31-899-1788

Contact person: Jong Tae Kim / dounu@mobis.co.kr

Manufacturer: Hyundai Mobis Co., Ltd.

Address: 69-23, Hansam-Ro, Ducksan-Myeon, Jinchun-Gun,

Chungcheongbuk-Do 365-843 Korea

Telephone number: +82-31-260-0092

Facsimile number: +82-31-899-1788

Contact person: Jong Tae Kim / dounu@mobis.co.kr

2. Laboratory information

Address

EMC compliance Ltd.

480-5 Sin-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do, 443-390, Korea Telephone Number: 82-31-336-9919 Facsimile Number: 82-505-299-8311

Certificate


CBTL Testing Laboratory, KOLAS NO.: 231

FCC Filing No.: 508785

VCCI Registration No.: R-3327, G-198, C-3706, T-1849

IC Recognition No.:8035A-2

SITE MAP





3. Description of E.U.T.

3.1 Basic description

Applicant:	Hyundai Mobis Co., Ltd.
Address of Applicant	80-9, Mabook-dong, Giheung-gu, Yongin-shi, Gyunggi-do, Korea (446-912)
Manufacturer	Hyundai Mobis Co., Ltd.
Address of Manufacturer	69-23, Hansam-Ro, Ducksan-Myeon, Jinchun-Gun, Chungcheongbuk-Do 365-843 Korea
Type of equipment	DIGITAL CAR AUDIO SYSTEM
Basic Model	AC1B0C2AN
Variant Model	AC1B0C2KN, AC1B0C2AX
Serial number	Proto Type

^{*} Variant model names are different only for the marketing area, and all model names are electrically identical in construction, radio characteristics, and features.

3.2 General description

Frequency Range	2 402 MHz ~ 2 480 MHz	
Type of Modulation	Modulation technologies: FHSS Modulation : GFSK, π/4DQPSK, 8DPSK	
Number of Channels	79 channels	
Type of Antenna	Integral type	
Antenna Gain	3.5 dBi	
Transmit Power	2.43 dBm	
Power supply	14.4 V DC	



3.3 Test frequency

	Frequency
Low frequency	2 402 MHz
Middle frequency	2 441 MHz
High frequency	2 480 MHz

3.4 Test Voltage

mode	Voltage
Norminal voltage	DC 14.4 V

*** 15.247 Requirements for Bluetooth transmitter**

- This Bluetooth module has been tested by a Bluetooth Qualification Lab, and we confirm the following:
 - 1) This system is hopping pseudo-randomly.
 - 2) Each frequency is used equally on the average by each transmitter.
 - 3) The receiver input bandwidths that match the hopping channel bandwidths of their corresponding transmitters
 - 4) The receiver shifts frequencies in synchronization with the transmitted signals.
- 15.247(g): The system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this Section 15.247 should the transmitter be presented with a continuous data (or information) stream.
- 15.247(h): The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

4. Summary of test results

4.1 Standards & results

FCC Rule	IC Rule	Parameter	Report Section	Test Result
15.203, 15.247(b)(4)	RSS-GEN, 7.1.2	Antenna Requirement	5.1	С
15.247(b)(1), (4)	RSS-210, A8.4(2)	Maximum Peak Output Power	5.2	C
15.247(a)(1)	RSS-210, A8.1(b)	Carrier Frequency Separation	5.3	С
15.247(a)(1)	RSS-210, A8.1(a)	20dB Channel Bandwidth	5.4	С
-	RSS-210, A1.1	Occupied Bandwidth	5.4	С
15.247(a)(iii) 15.247(b)(1)	RSS-210, A8.1(d)	Nunber of Hopping Channel	5.5	С
15.247(a) (iii)	RSS-210, A8.1(d)	Time of Occupancy(Dwell Time)	5.6	С
15.247(d), 15.205(a), 15.209(a)	RSS-210, A8.5 RSS-210, A2.9 RSS-GEN, 7.2.3	Spurious Emission, BandEdge, Restricted Band	5.7	С
-	RSS-GEN, 4.10	Receiver Spurious Emissions	5.8	С
15.247(i), 1.1307(b)(1)	-	RF Exposure	5.9	С

Note: C=complies

NC= Not complies NT=Not tested NA=Not Applicable

4.2 Uncertainty

Measurement Item	$ \begin{array}{c cccc} & & & & & & & & & & & & & & \\ \text{Combined Standard} & & & & & & & & \\ \text{Uncertainty} & & & & & & & & \\ & & & & & & & & & \\ & & & & & & & & \\ & & & & & & & & \\ & & & & & & & \\ & & & & & & & \\ & & & & & & & \\ & & & & & & \\ & & & & & & \\ & & & & & & \\ & & & & & & \\ & & & & & & \\ & & & & & & \\ & & & & & \\ & & & & & \\ & & & & & \\ & & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & \\ & & & \\ & & & \\ & & \\ & & & \\ & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & &$		
Conducted RF power	± 0.29 dB	± 0.58 dB	
Radiated disturbance	$\begin{array}{cccccccccccccccccccccccccccccccccccc$	$\begin{array}{cccccccccccccccccccccccccccccccccccc$	

^{*} The method of measurement used to test this DSS device is FCC Public Notice DA 00-705

^{*} The general test methods used to test this device is ANSI C63.4 2003 (or 2009, or ANSI C63.10 2009)



5. Test results

5.1 Antenna Requirement

5.1.1 Regulation

According to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

And according to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

5.1.2 Result

-Complied

The transmitter has an integral type of antenna. The directional gain of the antenna is 3.5 dBi.



5.2 Maximum Peak Output Power

5.2.1 Regulation

According to §15.247(b)(1), for frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

According to §15.247(b)(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

5.2.2 Measurement Procedure

The method of measurement used to test this DSS device is FCC Public Notice DA 00-705.

- 1. Check the calibration of the measuring instrument (spectrum analyzer) using either an internal calibrator or a known signal from an external generator.
- 2. Connect the antenna port of the EUT to RF input on the spectrum analyzer via a low loss cable.
- 3. Turn on the EUT and set it to any one measured frequency within its operating range by controlling it via UART interface and make sure the spectrum analyzer is operated in its linear range.
- 4. Set the spectrum analyzer as follows: Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel RBW > the 20 dB bandwidth of the emission being measured VBW ≥ RBW Sweep = auto Detector function = peak Trace = max hold
- 5. Measure the highest amplitude appearing on spectral display and record the level to calculate results.
- 6. Repeat above procedures until all frequencies measured were complete.



5.2.3 Test Result

- Complied

* GFSK

Channel	Frequency (MHz)	Result (dBm)	Limit (dBm)	Margin (dB)
Low	2 402	1.16	30.00	28.84
Middle	2 441	1.60	30.00	28.40
High	2 480	2.01	30.00	27.99

* $\pi/4$ DOPSK

Channel	Frequency (MHz)	Result (dBm)	Limit (dBm)	Margin (dB)
Low	2 402	2.08	30.00	27.92
Middle	2 441	2.35	30.00	27.65
High	2 480	2.35	30.00	27.65

* 8DPSK

Channel	Frequency (MHz)	Result (dBm)	Limit (dBm)	Margin (dB)
Low	2 402	2.39	30.00	27.61
Middle	2 441	2.39	30.00	27.61
High	2 480	2.43	30.00	27.57

NOTE:

- 1. Since the directional gain of the integral antenna declared by the manufacturer ($G_{ANT} = 3.5 \text{ dBi}$) does not exceed 6.0 dBi, there was no need to reduce the output power.
- 2. We took the insertion loss of the cable loss into consideration within the measuring instrument.




5.2.4 Test Plot


Figure 1. Plot of the Maximum Peak Output Power (Conducted)


* GFSK

Lowest Channel (2 402 MHz)



Middle Channel (2 441 MHz)










* π/4DQPSK

Lowest Channel (2 402 MHz)



Middle Channel (2 441 MHz)










* 8DPSK

Lowest Channel (2 402 MHz)



Middle Channel (2 441 MHz)







5.3 Carrier Frequency Separation

5.3.1 Regulation

According to §15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW

5.3.2 Measurement Procedure

The method of measurement used to test this DSS device is FCC Public Notice DA 00-705.

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Connect the antenna port of the EUT to RF input on the spectrum analyzer via a low loss cable and attenuator.
- 3. Turn on the EUT and set it to any one measured frequency within its operating range by controlling it via UART interface.
- 4. Set the spectrum analyzer as follows: Span = wide enough to capture the peaks of two adjacent channels Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span Video (or Average) Bandwidth (VBW) ≥ RBW Sweep = auto Detector function = peak Trace = max hold
- 5. Measure the separation between the peaks of the adjacent channels using the marker-delta function.
- 6. Repeat above procedures until all frequencies measured were complete.

Page: 14 of 63



5.3.3 Test Result

- Complied

* GFSK

Channel	Carrier frequency separation (MHz)	Limit
Low	1.003	≥25 kHz or two-thirds of the 20 dB bandwidth
Middle	1.003	≥25 kHz or two-thirds of the 20 dB bandwidth
High	0.999	≥25 kHz or two-thirds of the 20 dB bandwidth

* π/4DQPSK

W 12 Q1 511		
Channel	Carrier frequency separation (MHz)	Limit
Low	0.999	≥25 kHz or two-thirds of the 20 dB bandwidth
Middle	0.999	≥25 kHz or two-thirds of the 20 dB bandwidth
High	1.003	≥25 kHz or two-thirds of the 20 dB bandwidth

* 8DPSK

Channel	Carrier frequency separation (MHz)	Limit
Low	0.999	≥25 kHz or two-thirds of the 20 dB bandwidth
Middle	1.003	≥25 kHz or two-thirds of the 20 dB bandwidth
High	1.003	≥25 kHz or two-thirds of the 20 dB bandwidth

NOTE: We took the insertion loss of the cable loss into consideration within the measuring instrument.




5.3.4 Test Plot


Figure 2.Plot of the Carrier Frequency Separation (Conducted)

* GFSK

Lowest Channel (2 402 MHz)



Middle Channel (2 441 MHz)









* π/4DQPSK

Lowest Channel (2 402 MHz)



Middle Channel (2 441 MHz)









* 8DPSK

Lowest Channel (2 402 MHz)



Middle Channel (2 441 MHz)







5.4 20 dB Channel Bandwidth

5.4.1 Regulation

According to §15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW

5.4.2 Measurement Procedure

The method of measurement used to test this DSS device is FCC Public Notice DA 00-705.

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Connect the antenna port of the EUT to RF input on the spectrum analyzer via a low loss cable and attenuator.
- 3. Turn on the EUT and set it to any one measured frequency within its operating range by controlling it via UART interface and make sure the spectrum analyzer is operated in its linear range.
- 4. Set the spectrum analyzer as follows: Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel RBW ≥ 1% of the 20 dB bandwidth VBW ≥ RBW Sweep = auto Detector function = peak Trace = max hold
- 5. Set a reference level on it equal to the highest peak value.
- 6. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- 7. Repeat above procedures until all frequencies measured were complete..

Page: 19 of 63



5.4.3 Test Result

- Complied

* GFSK

Channel	20dB Channel Bandwidth(MHz)	Carrier frequency Separation(MHz)	Occupied Bandwidth (99% BW)(MHz)			
Low	0.821	1.003	0.877			
Middle	0.825	1.003	0.868			
High	0.821	0.999	0.868			

* π/4DQPSK

Channel	20dB Channel Bandwidth(MHz)	Carrier frequency Separation(MHz)	Occupied Bandwidth (99% BW)(MHz)
Low	1.250	0.999	1.216
Middle	1.246	0.999	1.203
High	1.246	1.003	1.181

* 8DPSK

Channel	20dB Channel Bandwidth(MHz)	Carrier frequency Separation(MHz)	Occupied Bandwidth (99% BW)(MHz)
Low	1.267	0.999	1.229
Middle	1.216	1.003	1.207
High	1.263	1.003	1.194


NOTE: We took the insertion loss of the cable loss into consideration within the measuring instrument.

5.4.4 Test Plot


Figure 3.Plot of the 20dB Channel Bandwidth/ Occupied Bandwidth (Conducted)

* GFSK (20dB Channel Bandwidth)

Lowest Channel (2 402 MHz)



Middle Channel (2 441 MHz)










* π/4DQPSK (20dB Channel Bandwidth)

Lowest Channel (2 402 MHz)



Middle Channel (2 441 MHz)










* 8DPSK (20dB Channel Bandwidth)

Lowest Channel (2 402 MHz)



Middle Channel (2 441 MHz)










* GFSK (Occupied Bandwidth)

Lowest Channel (2 402 MHz)



Middle Channel (2 441 MHz)








* π/4DQPSK (Occupied Bandwidth)

Lowest Channel (2 402 MHz)



Middle Channel (2 441 MHz)









* 8DPSK (Occupied Bandwidth)

Lowest Channel (2 402 MHz)



Middle Channel (2 441 MHz)







5.5 Number of Hopping Channels

5.5.1 Regulation

According to §15.247(a)(1)(iii), Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used. According to §15.247(b)(1), For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

5.5.2 Measurement Procedure

The method of measurement used to test this DSS device is FCC Public Notice DA 00-705.

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Connect the antenna port of the EUT to RF input on the spectrum analyzer via a low loss cable and
- 3. Turn on the EUT and set the hopping function enabled by controlling it via UART interface.
- 4. Set the spectrum analyzer as follows: Span = the frequency band of operation RBW $\geq 1\%$ of the span $VBW \ge RBW$ Sweep = auto Detector function = peak Trace = max hold
- 5. Record the number of hopping channels.

Page: 27 of 63



5.5.3 Test Result

- Complied

* GFSK

Frequency	Number of hopping channel	Limit
2 402 – 2 480 MHz	79	≥15

* $\pi/4$ DQPSK

Frequency	Number of hopping channel	Limit
2 402 – 2 480 MHz	79	≥15

* 8DPSK

Frequency	Number of hopping channel	Limit
2 402 – 2 480 MHz	79	≥15

NOTE: We took the insertion loss of the cable loss into consideration within the measuring instrument.



5.5.4 Test Plot Figure 4. Plot of the Number of Hopping Channels (Conducted) * GFSK * π/4DQPSK * 8DPSK



5.6 Time of Occupancy(Dwell Time)

5.6.1 Regulation

According to §15.247(a)(1)(iii), frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

5.6.2 Measurement Procedure

The method of measurement used to test this DSS device is FCC Public Notice DA 00-705.

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Connect the antenna port of the EUT to RF input on the spectrum analyzer via a low loss cable.
- 3. Turn on the EUT and set it to any one measured frequency within its operating range by controlling it via UART interface.
- 4. Set the spectrum analyzer as follows: Span = zero span, centered on a hopping channel RBW = 1 MHz VBW ≥ RBW Sweep = as necessary to capture the entire dwell time per hopping channel Detector function = peak Trace = max hold
- 5. Measure the dwell time using the marker-delta function.
- 6. Repeat above procedures until all frequencies measured were complete.
- 7. Repeat this test for different modes of operation (e.g., data rate, modulation format, etc.), if applicable.

Page: 30 of 63



5.6.3 Test Result

- Complied

* GFSK

Channel	Reading[ms]	Hopping rate[hop/s]	Number of Channels	Actual[s]	Limit[s]
Low	2.902	266.667	79	0.310	0.40
Middle	2.902	266.667	79	0.310	0.40
High	2.902	266.667	79	0.310	0.40

* π/4DQPSK

_	W 12 Q 1 2 1 2					
	Channel	Reading[ms]	Hopping rate[hop/s]	Number of Channels	Actual[s]	Limit[s]
	Low	2.902	266.667	79	0.310	0.40
	Middle	2.902	266.667	79	0.310	0.40
	High	2.902	266.667	79	0.310	0.40

* 8DPSK

Channel	Reading[ms]	Hopping rate[hop/s]	Number of Channels	Actual[s]	Limit[s]
Low	2.902	266.667	79	0.310	0.40
Middle	2.902	266.667	79	0.310	0.40
High	2.902	266.667	79	0.310	0.40

Actual = Reading \times (Hopping rate / Number of channels) \times Test period Test period = 0.4 [seconds / channel] \times 79 [channel] = 31.6 [seconds]

1. We took the insertion loss of the cable loss into consideration within the measuring instrument.




5.6.4 Test Plot


Figure 5. Plot of the Time of Occupancy (Conducted)


* GFSK

Lowest Channel (2 402 MHz)



Middle Channel (2 441 MHz)







* π/4DQPSK Lowest Channel (2 402 MHz) Middle Channel Ref Level 10.00 dBm Offset 7.00 dB ■ RBW 1 MHz Att 20 dB ■ SWT 4.5 ms ■ VBW 1 MHz (2 441 MHz) D1[1] MI[I] **Highest Channel** (2 480 MHz)



* 8DPSK Lowest Channel (2 402 MHz) Golfman Halle Commenter Middle Channel Ref Level 10.00 dBm Offset 7.00 dB RBW 1 MHz Att 20 dB SWT 4.5 ms VBW 1 MHz (2 441 MHz) D1[1] **Highest Channel** (2 480 MHz)



5.7 Spurious Emission, Band edge, and Restricted bands

5.7.1 Regulation

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

According to §15.209(a), for an intentional device, the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency (MHz)	Field strength ($\mu V/m @ 3m$)	Field strength (dBμV/m @ 3m)
30–88	100	40.0
88–216	150	43.5
216–960	200	46.0
Above 960	500	54.0

According to §15.109(a), for an unintentional device, except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the above table.

Page: 35 of 63

^{**} The emission limits shown in the above table are based on measurement instrumentation employing a CISPR quasi-peak detector and above 1000 MHz are based on the average value of measured emissions.



5.7.2 Measurement Procedure

The method of measurement used to test this DSS device is FCC Public Notice DA 00-705.

1) Band-edge Compliance of RF Conducted Emissions

1. Set the spectrum analyzer as follows:

Span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation

 $RBW \ge 1\%$ of the span

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

- 2. Allow the trace to stabilize. Set the marker on the emission at the band-edge, or on the highest modulation product outside of the band, if this level is greater than that at the band-edge. Enable the marker-delta function, and then use the marker-to-peak function to move the marker to the peak of the in-band emission.
- 3. Now, using the same instrument settings, enable the hopping function of the EUT. Allow the trace to stabilize. Follow the same procedure listed above to determine if any spurious emissions caused by the hopping function also comply with the specified limit.

2) Spurious RF Conducted Emissions:

1. Set the spectrum analyzer as follows:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

 $VBW \ge RBW$

Sweep = auto

Detector function = peak

Trace = max hold

- 2. Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded.
 - a 4×4 meter at the Open Area Test Site. The EUT was tested at a distance 3 meters.
- 3. Each frequency found during preliminary measurements was re-examined and investigated. The test-receiver system was set up to average, peak, and quasi-peak detector function with specified bandwidth.

Page: 36 of 63



3) Spurious Radiated Emissions:

- 1. The preliminary radiated measurements were performed to determine the frequency producing the maximum emissions in an anechoic chamber at a distance of 3 meters.
- 2. The EUT was placed on the top of the 0.8-meter height, 1×1.5 meter non-metallic table. To find the maximum emission levels, the height of a measuring antenna was changed and the turntable was rotated 360°.
- 3. The antenna polarization was also changed from vertical to horizontal. The spectrum was scanned from 9 kHz to 30 MHz using the loop antenna, and from 30 to 1000 MHz using the TRILOG broadband antenna, and from 1000 MHz to 26500 MHz using the horn antenna.
- 4. To obtain the final measurement data, the EUT was arranged on a turntable situated on a 4 × 4 meter at the Open Area Test Site. The EUT was tested at a distance 3 meters.
- 5. Each frequency found during preliminary measurements was re-examined and investigated. The test-receiver system was set up to average, peak, and quasi-peak detector function with specified bandwidth.

Page: 37 of 63



5.7.3 Test Result

- Complied

- 1. Band edge compliance of RF Conducted Emissions was shown in figure 6.
- 2. Band edge compliance of RF Radiated Emissions was shown in figure 7.
- 3. Spurious RF conducted Emissions were shown in the Figure 8.

Note: We took the insertion loss of the cable into consideration within the measuring instrument.

4. Measured value of the Field strength of spurious Emissions (Radiated)

* GFSK

Low channel (2 402 MHz)

Eow channer (2	102 11112)									
Frequency	Receiver Bandwidth	Pol.	Reading	Factor	Result	Limit	Margin			
[MHz]	[kHz]	[V/H]	[dB(µV)]	[dB]	$[dB(\mu V/m)]$	$[dB(\mu V/m)]$	[dB]			
Quasi-Peak DA	TA. Emissions b	elow 30 M	IHz							
Below 30.00	Not Detected	-	-	-	-	-	-			
Quasi-Peak DATA. Emissions below 1GHz										
35.82	120	V	52.3	-17.1	35.2	54.0	18.8			
45.52	120	V	44.3	-15.9	28.4	54.0	25.6			
Above 100.00	Not Detected	ı	-	1	-	-	-			
Peak DATA. En	nissions above 1	GHz								
2 809.50	1 000	V	52.4	-6.2	46.2	74.0	27.8			
Above 3 000.00	Not Detected	-	-	-	-	-	-			
Average DATA.	Average DATA. Emissions above 1GHz									
2 809.50	1 000	V	47.6	-6.2	41.4	54.0	12.6			
Above 3 000.00	Not Detected	-	-	-	-	-	-			



Middle	channel	()	441	MH ₂)	
Minaie	Chamber	12	441	IVILIZI	

viiduic channe	ei (2 441 Ninz)									
Frequency	Receiver Bandwidth	Pol.	Reading	Factor	Result	Limit	Margin			
[MHz]	[kHz]	[V/H]	$[dB(\mu V)]$	[dB]	$[dB(\mu V/m)]$	$[dB(\mu V/m)]$	[dB]			
Quasi-Peak DA	ATA. Emissions	below 30 M	IHz							
Below 30.00	Not Detected	-	-	-	-	-	-			
Quasi-Peak DATA. Emissions below 1GHz										
35.82	120	V	53.6	-17.1	36.5	54.0	17.5			
Above 100.00	Not Detected	-	1	-	-	-	-			
Peak DATA. E	missions above	1GHz								
2 809.50	1 000	V	52.4	-6.2	46.2	74.0	27.8			
Above 3 000.00	Not Detected	-	-	-	-	-	-			
Average DATA	Average DATA. Emissions above 1GHz									
2 809.50	1 000	V	42.1	-6.2	35.9	54.0	18.1			
Above 3 000.00	Not Detected	-	-	-	-	-	-			



righ channel (2 400 WIIIZ)									
Frequency	Receiver Bandwidth	Pol.	Reading	Factor	Result	Limit	Margin			
[MHz]	[kHz]	[V/H]	$[dB(\mu V)]$	[dB]	$[dB(\mu V/m)]$	$[dB(\mu V/m)]$	[dB]			
Quasi-Peak DATA. Emissions below 30 MHz										
Below 30.00	Not Detected	-	-	-	-	-	-			
Quasi-Peak DATA. Emissions below 1GHz										
35.82	120	V	52.2	-17.1	35.1	54.0	18.9			
Above 800.00	Not Detected	-	-	-	-	-	-			
Peak DATA. E	missions above 1	GHz								
2 809.50	1 000	V	52.9	-6.2	46.7	74.0	27.3			
Above	Not									
3 000.00	Detected	ı	-	ı	-	-	-			
Average DATA	Average DATA. Emissions above 1GHz									
2 809.50	1 000	V	43.7	-6.2	37.5	54.0	16.5			
Above 3 000.00	Not Detected	-	-	-	-	-	-			



* 8DPSK

Low channel (2 402 MHz)

Low Channel (2	102 MILL)										
Frequency [MHz]	Receiver Bandwidth [kHz]	Pol. [V/H]	Reading [dB(μV)]	Factor	Result [dB(μV/m)]	Limit [dB(µV/m)]	Margin [dB]				
Quasi-Peak DA	Quasi-Peak DATA. Emissions below 30 MHz										
Below 30.00	Not Detected	-	-	-	-	-	-				
Quasi-Peak DATA. Emissions below 1GHz											
35.82	120	V	51.6	-17.1	34.5	54.0	19.5				
Above 100.00	Not Detected	-	-	1	-	-	-				
Peak DATA. E	missions above 1	lGHz									
2 809.50	1 000	V	52.3	-6.2	46.1	74.0	27.9				
Above 3 000.00	Not Detected	-	-	-	-	-	-				
Average DATA	Average DATA. Emissions above 1GHz										
2 809.50	1 000	V	47.7	-6.2	41.5	54.0	12.5				
Above 3 000.00	Not Detected	-	-	-	-	-	-				



Middle channel (2 441 MHz)

Middle channe	(= ::::::::::::::::::::::::::::::::::::									
Frequency	Receiver Bandwidth	Pol.	Reading	Factor	Result	Limit	Margin			
[MHz]	[kHz]	[V/H]	$[dB(\mu V)]$	[dB]	$[dB(\mu V/m)]$	$[dB(\mu V/m)]$	[dB]			
Quasi-Peak DA	ATA. Emissions	below 30 M	ПНz							
Below 30.00	Not Detected	-	-	-	-	-	-			
Quasi-Peak DATA. Emissions below 1GHz										
35.82	120	V	52.2	-17.1	35.1	54.0	18.9			
359.80	120	V	42.2	-8.5	33.7	54.0	20.3			
Above 400.00	Not Detected	ı	-	1	-	-	-			
Peak DATA. E	missions above	lGHz								
2 809.50	1 000	V	52.4	-6.2	46.2	74.0	27.8			
4 877.50	1 000	Н	44.3	-1.0	43.3	74.0	30.7			
Above 5 000.00	Not Detected	-	-	-	-	-	-			
Average DATA	. Emissions abo	ve 1GHz								
2 809.50	1 000	V	44.3	-6.2	38.1	54.0	15.9			
4 877.50	1 000	Н	36.3	-1.0	35.3	54.0	18.7			
Above 5 000.00	Not Detected	ı	-	-	-	-	-			



High channel (2 480 MHz)

ingh channer (2 400 WIII2)									
Frequency [MHz]	Receiver Bandwidth [kHz]	Pol. [V/H]	Reading [dB(μV)]	Factor [dB]	Result	Limit [dB(μV/m)]	Margin [dB]			
	ATA. Emissions				TE (1 /3	L (1 /1)	. ,			
Below 30.00	Not Detected	-	-	-	-	-	-			
Quasi-Peak DATA. Emissions below 1GHz										
35.82	120	V	52.5	-17.1	35.4	54.0	18.6			
183.26	120	V	47.2	-14.6	32.6	54.0	21.4			
Above 200.00	Not Detected	-	-	-	-	-	-			
Peak DATA. E	missions above 1	1GHz								
2 809.50	1 000	V	52.3	-6.2	46.1	74.0	27.9			
Above 3 000.00	Not Detected	-	-	-	-	-	-			
Average DATA	Average DATA. Emissions above 1GHz									
2 809.50	1 000	V	47.1	-6.2	40.9	54.0	13.1			
Above 3 000.00	Not Detected	-	-	-	-	-	-			

Factor(dB) = ANT Factor+Amp Gain + Cable Loss

Margin (dB) = Limit - Result

[Result = Reading - Factor]

- 1. H = Horizontal, V = Vertical Polarization
- 2. ATT = Attenuation (10dB pad and/or Insertion Loss of HPF), AF/CL = Antenna Factor and Cable Loss
- * The spurious emission at the frequency does not fall in the restricted bands.
- ** The measured result is within the test standard limit by a margin less than the measurement uncertainty; it is therefore not possible to state compliance based on the 95 % level of confidence. However, the result indicates that compliance is more probable than non-compliance.

NOTE: All emissions not reported were more than 20 dB below the specified limit or in the noise floor.





5.7.4 Test Plot

Figure 6. Plot of the Band Edge (Conducted)

* GFSK (Without hopping)

Lowest Channel (2 402 MHz)










* GFSK (With hopping)

Lowest Channel (2 402 MHz)












Lowest Channel (2 402 MHz)













* 8DPSK (Without hopping)

Lowest Channel (2 402 MHz)









* 8DPSK (With hopping)

Lowest Channel (2 402 MHz)






5.7.4 Test Plot (Continue)


Figure 7. Plot of the Band Edge (Radiated)

* GFSK


Lowest Channel(2 402 MHz): PEAK




Lowest Channel(2 402 MHz): AVERAGE



Highest Channel(2480 MHz): PEAK




Highest Channel(2480 MHz): AVERAGE






* 8DPSK


Lowest Channel(2 402 MHz): PEAK




Lowest Channel(2 402 MHz): AVERAGE




Highest Channel(2480 MHz): PEAK



Highest Channel(2480 MHz): AVERAGE










* π/4DQPSK Lowest Channel(2 402 MHz):30 MHz ~ 13 GHz Lowest Channel(2 402 MHz):12 GHz ~ 25 GHz Spectrum 2 Spectrum 3 Spectrum 3 Middle Channel(2 441 MHz): 30 MHz ~ 13 GHz Middle Channel(2 441 MHz): 12 GHz ~ 25 GHz rum 2 X Spectrum 3 X Spectrum 4 X Highest Channel(2 480 MHz): 30 MHz ~ 13 GHz Highest Channel(2 480 MHz): 12 GHz ~ 25 GHz MILLI







5.8 Receiver Spurious Emissions

5.8.1 Regulation

The receiver shall be operated in the normal receive mode near the mid-point of the band in which the receiver is designed to operate.

Radiated emission measurements are to be performed on a test site registered with Industry Canada. As an alternative, the conducted measurement method may be used when the antenna is detachable. In such a case, the receiver spurious signal may be measured at the antenna port.

If the receiver is super-regenerative, stabilize it by coupling to it an unmodulated carrier on the receiver frequency (antenna conducted measurement) or by transmitting an unmodulated carrier on the receiver frequency from an antenna in the proximity of the receiver (radiated measurement). Taking care not to overload the receiver, vary the amplitude and frequency of the stabilizing signal to obtain the highest level of the spurious emissions from the receiver.

For either method, the search for spurious emissions shall be from the lowest frequency internally generated or used in the receiver (e.g. local oscillator, intermediate or carrier frequency), or 30 MHz, whichever is higher, to at least 3 times the highest tuneable or local oscillator frequency, whichever is higher, without exceeding 40 GHz.

For emissions below 1000 MHz, measurements shall be performed using a CISPR quasi-peak detector and the related measurement bandwidth. As an alternative to CISPR quasi-peak measurement, compliance with the emission limit can be demonstrated using measuring equipment employing a peak detector function properly adjusted for factors such as pulse desensitization as required, with an equal or greater measurement bandwidth relative to the applicable CISPR quasi-peak bandwidth.

Above 1000 MHz, measurements shall be performed using an average detector with a minimum resolution bandwidth of 1 MHz.

5.8.2 Measurement Procedure

Radiated spurious emission measurements shall be performed with the receiver antenna connected to the receiver antenna terminals.

Spurious emissions from receivers shall not exceed the radiated limits shown in the table below:

Frequency (MHz)	Field Strength (microvolts/m at 3 metres)*
30-88	100
88-216	150
216-960	200
Above 960	500

^{*}Measurements for compliance with limits in the above table may be performed at distances other than 3 metres, in accordance with Section 7.2.7.

Page: 55 of 63



5.8.3 Test Result

- Complied

* GFSK

Low channel (2 402 MHz)

Low channel (2	2 402 WIIIZ)									
Frequency	Receiver Bandwidth	Pol.	Reading	Factor	Result	Limit	Margin			
[MHz]	[kHz]	[V/H]	$[dB(\mu V)]$	[dB]	$[dB(\mu V/m)]$	$[dB(\mu V/m)]$	[dB]			
Quasi-Peak DATA. Emissions below 1GHz										
Below 1 000.00	Not Detected	-	-	-	-	-	-			
Peak DATA. E	Peak DATA. Emissions above 1GHz									
2 809.50	1 000	V	51.8	-6.2	45.6	74.0	28.4			
Above 3 000.00	Not Detected	-	-	-	-	-	-			
Average DATA	Average DATA. Emissions above 1GHz									
2 809.50	1 000	V	44.9	-6.2	38.7	54.0	15.3			
Above 3 000.00	Not Detected	-	-	-	-	-	-			



Middle channel (2 441 MHz)

THUMBE CHAIN	1 (2 441 WIIIZ)									
Frequency	Receiver Bandwidth	Pol.	Reading	Factor	Result	Limit	Margin			
[MHz]	[kHz]	[V/H]	$[dB(\mu V)]$	[dB]	$[dB(\mu V/m)]$	$[dB(\mu V/m)]$	[dB]			
Quasi-Peak DATA. Emissions below 1GHz										
Below 1 000.00	Not Detected	-	-	ı	-	-	-			
Peak DATA. E	Peak DATA. Emissions above 1GHz									
2 809.50	1 000	V	52.6	-6.2	46.4	74.0	27.6			
Above 3 000.00	Not Detected	-	-	-	-	-	-			
Average DATA	Average DATA. Emissions above 1GHz									
2 809.50	1 000	V	45.3	-6.2	39.1	54.0	14.9			
Above 3 000.00	Not Detected	-	-	-	-	-	-			



High channel (2 480 MHz)

Frequency	Receiver Bandwidth	Pol.	Reading	Factor	Result	Limit	Margin			
[MHz]	[kHz]	[V/H]	$[dB(\mu V)]$	[dB]	$[dB(\mu V/m)]$	$[dB(\mu V/m)]$	[dB]			
Quasi-Peak DATA. Emissions below 1GHz										
Below 1 000.00	Not Detected	-	-	-	-	-	-			
Peak DATA. Emissions above 1GHz										
2 809.50	1 000	V	52.9	-6.2	46.7	74.0	27.3			
Above 3 000.00	Not Detected	-	-	-	-	-	-			
Average DATA	Average DATA. Emissions above 1GHz									
2 809.50	1 000	V	45.1	-6.2	38.9	54.0	15.1			
Above 3 000.00	Not Detected	-	-	-	-	-	-			

Factor(dB) = ANT Factor+ Amp Gain + Cable Loss

Margin (dB) = Limit - Result

[Result = Reading - Factor]

- 1. H = Horizontal, V = Vertical Polarization
- 2. ATT = Attenuation (10dB pad and/or Insertion Loss of HPF), AF/CL = Antenna Factor and Cable Loss
- * The spurious emission at the frequency does not fall in the restricted bands.
- ** The measured result is within the test standard limit by a margin less than the measurement uncertainty; it is therefore not possible to state compliance based on the 95 % level of confidence. However, the result indicates that compliance is more probable than non-compliance.

NOTE: All emissions not reported were more than 20 dB below the specified limit or in the noise floor.

Page: 58 of 63



* 8DPSK

Low channel (2 402 MHz)

Frequency [MHz]	Receiver Bandwidth [kHz]	Pol. [V/H]	Reading [dB(µV)]	Factor [dB]	Result [dB(μV/m)]	Limit [dB(µV/m)]	Margin [dB]			
Quasi-Peak DATA. Emissions below 1GHz										
Below 1 000.00	Not Detected	-	-	-	-	-	-			
Peak DATA. E	Peak DATA. Emissions above 1GHz									
2 809.50	1 000	V	52.7	-6.2	46.5	74.0	27.5			
Above 3 000.00	Not Detected	-	-	-	-	-	-			
Average DATA	Average DATA. Emissions above 1GHz									
2 809.50	1 000	V	45.3	-6.2	39.1	54.0	14.9			
Above 3 000.00	Not Detected	-	-	- -	_	-	-			



Middle channel (2 441 MHz)

Frequency [MHz]	Receiver Bandwidth [kHz]	Pol. [V/H]	Reading [dB(µV)]	Factor [dB]	Result [dB(µV/m)]	Limit [dB(μV/m)]	Margin [dB]	
Quasi-Peak DATA. Emissions below 1GHz								
Below 1 000.00	Not Detected	-	-	-	-	-	-	
Peak DATA. E	Peak DATA. Emissions above 1GHz							
2 809.50	1 000	V	52.7	-6.2	46.5	74.0	27.5	
Above 3 000.00	Not Detected	-	-	-	-	-	-	
Average DATA. Emissions above 1GHz								
2 809.50	1 000	V	45.1	-6.2	38.9	54.0	15.1	
Above 3 000.00	Not Detected	-	-	-	_	-	-	



High channel (2 480 MHz)

Frequency [MHz]	Receiver Bandwidth [kHz]	Pol. [V/H]	Reading [dB(μV)]	Factor [dB]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	
Quasi-Peak DATA. Emissions below 1GHz								
Below 1 000.00	Not Detected	-	-	-	-	-	-	
Peak DATA. E	Peak DATA. Emissions above 1GHz							
2 809.50	1 000	V	52.7	-6.2	46.5	74.0	27.5	
Above 3 000.00	Not Detected	-	-	-	-	-	-	
Average DATA. Emissions above 1GHz								
2 809.50	1 000	V	44.8	-6.2	38.6	54.0	15.4	
Above 3 000.00	Not Detected	-	-	-	-	-	-	

Factor(dB) = ANT Factor+ Amp Gain + Cable Loss

Margin (dB) = Limit - Result

[Result = Reading – Factor]

- 1. H = Horizontal, V = Vertical Polarization
- 2. ATT = Attenuation (10dB pad and/or Insertion Loss of HPF), AF/CL = Antenna Factor and Cable Loss
- * The spurious emission at the frequency does not fall in the restricted bands.
- ** The measured result is within the test standard limit by a margin less than the measurement uncertainty; it is therefore not possible to state compliance based on the 95 % level of confidence. However, the result indicates that compliance is more probable than non-compliance.

NOTE: All emissions not reported were more than 20 dB below the specified limit or in the noise floor.

Page: 61 of 63

5.9 RF Exposure

5.9.1 Regulation

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this Chapter.

Limits for Maximum Permissive Exposure: RF exposure is calculated

Emilio for Maximum Formissive Exposure. It exposure is curculated.							
Eraguanay Danga	Electric Field	Magnetic Field	Power Density	Averaging Time			
Frequency Range	Strength [V/m]	Strength [A/m]	$[mW/cm^2]$	[minute]			
Limits for General Population / Uncontrolled Exposure							
0.3 ~ 1.34	614	1.63	*(100)	30			
$1.34 \sim 30$	824 /f	2.19/f	$*(180/f^2)$	30			
$30 \sim 300$	27.5	0.073	0.2	30			
300 ~ 1500	/	/	f/1500	30			
$1500 \sim 15000$	/	/	1.0	30			

f=frequency in MHz, *= plane-wave equivalent power density

MPE (Maximum Permissive Exposure) Prediction

Predication of MPE limit at a given distance: Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2 \quad (\Rightarrow R = \sqrt{PG/4\pi S})$$

S=power density [mW/cm²]

P=Power input to antenna [mW]

G=Power gain of the antenna in the direction of interest relative to an isotropic radiator

R= distance to the center of radiation of the antenna [cm]

EUT: Maximum peak output power = 1.75 [mW](= 2.43 dBm) Antenna gain= 2.24(= 3.5 [dBi])					
	$S = PG/4\pi R^2 = 100 \times 3.98 / (4 \times \pi \times 400)$				
100 mW, at 20 cm from an antenna 6[dBi]	$= 0.0792 \text{ [mW/cm}^2] < 1.0 \text{ [mW/cm}^2]$				
2.239 mW, at 20 cm from an antenna 3.5 [dBi]	$S = PG/4\pi R^2 = 0.000 78 [mW/cm^2] < 1.0 [mW/cm^2]$				
2.239 mW, at 2.5 cm from an antenna 3.5 [dBi]	$S = PG/4\pi R^2 = 0.049 88 [mW/cm^2] < 1.0 [mW/cm^2]$				

5.9.2 RF Exposure Compliance Issue

The information should be included in the user's manual:

This appliance and its antenna must not be co-located or operation in conjunction with any other antenna or transmitter. A minimum separation distance of 20 cm must be maintained between the antenna and the person for this appliance to satisfy the RF exposure requirements.

Page: 62 of 63



6. Test equipment used for test

Description	Manufacture	Model No.	Serial No.	Next Cal Date.
Spectrum Analyzer	R&S	FSV30	101437	14.12.31
DC Power Supply	Agilent	E3632A	MY51220373	14.12.24
Signal Generator	R&S	SMR40	100007	14.06.11
Test Receiver	R&S	ESCI7	100732	14.02.18
Spectrum Analyzer	R&S	FSP40	100209	14.10.21
Loop Antenna	R&S	HFH2-Z2	100355	15.06.19
Bi-Log Antenna	Schwarzbeck	VULB9163	552	14.07.18
Amplifier	Sonoma	310N	186280	14.02.15
Attenuator	HP	8491A	16861	14.07.08
Amplifier	Agilent	8449B	3008A02343	14.10.31
Horn Antenna	ETS-Lindgren	3115	86706	14.08.20
Antenna Mast	Innco Systems	MA4000-EP	303	-
Turn Table	Innco Systems	DT2000S-1t	79	-