

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA TEL: +82-31-645-6300 FAX: +82-31-645-6401

FCC MPE REPORT

FCC Certification

Applicant Name:

HYUNDAI MOBIS CO., LTD.

Address:

203, Teheran-ro, Gangnam-gu, Seoul, 135-977, South

Korea

Date of Issue:

October 17, 2017

Test Site/Location:

HCT CO., LTD., 74, Seoicheon-ro 578beon-gil, Majangmyeo, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA

Report No.: HCT-R-1710-E007

HCT FRN: 0005866421

FCC ID

: TQ8-ACB10S1GG

APPLICANT

: HYUNDAI MOBIS CO., LTD.

Model:

ACB10S1GG

Additional model(s):

ACB10S1RE, ACB11S1EG, ACB10S1EE, ACB10S1UG, ACB10S1MG

EUT Type:

Car Audio System

Frequency Range:

2402 MHz - 2480 MHz (Bluetooth)

The measurements shown in this report were made in accordance with the procedures specified in §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits

pursuant to section 5301 of the Anti-Drug Abuse Act of 1998,21 U.S. C.853(a)

Report prepared by: Soo Kyung Kang Engineer of Telecommunication testing center

Approved by: Yong Hyun Lee

Manager of Telecommunication testing center

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.



Report No: HCT-R-1710-E007 FCC ID : TQ8-ACB10S1GG

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-R-1710-E007	October 17, 2017	- First Approval Report

F-TP22-03 (Rev.00) 2 / 4 **HCT CO.,LTD.**



Report No: HCT-R-1710-E007 FCC ID: TQ8-ACB10S1GG

RF Exposure Statement

1. LIMITS

According to §1.1310 and §2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

Frequency range	Electric field	Magnetic field	Power density	Averaging time
(MHz)	Strength (V/m)	Strength (A/m)	(mW/cm²)	(minutes)
0.3 - 1.34	614 824/f 27.5	1.63 2.19/f 0.073	*(100) *(180/ f²) 0.2 f/1500 1.0	30 30 30 30 30

F = frequency in MHz

2. MAXIMUM PERMISSIBLE EXPOSURE Prediction

Prediction of MPE limit at a given distance

 $S = PG/4\pi R^2$

S = Power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

^{* =} Plane-wave equivalent power density



Report No: HCT-R-1710-E007 FCC ID : TQ8-ACB10S1GG

3. RESULTS

BT Only

Max Peak output Power at antenna input terminal	-3.129	dBm
Max Peak output Power at antenna input terminal	0.487	mW
Prediction distance	20.000	cm
Prediction frequency	2441.000	MHz
Antenna Gain(typical)	2.460	dBi
Antenna Gain(numeric)	1.762	-
Power density at prediction frequency(S)	0.000171	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm ²