

Report Number: F690501/RF-RTL009947

Page:

1

52

TEST REPORT

of

FCC Part 15 Subpart C §15.247

FCC ID: TQ8-ADBB0GSAN

Equipment Under Test

: DISPLAY CAR SYSTEM

Model Name

: ADBB0GSAN

Applicant

: Hyundai MOBIS Co., Ltd.

Manufacturer

: Hyundai MOBIS Co., Ltd.

Date of Test(s)

: 2016.05.13 ~ 2016.05.30

Date of Issue

: 2016.06.08

In the configuration tested, the EUT complied with the standards specified above.

Jun

Date:

2016.06.08

Approved By:

Tested By:

Date:

2016.06.08

Hyunchae You



Report Number: F690501/RF-RTL009947 Page: 2 of 52

INDEX

Table of contents

1. General information	3
2. Transmitter radiated spurious emissions and conducted spurious emission	7
3. 6 dB bandwidth	38
4. Maximum Peak Conducted Output Power	44
5. Power Spectral Density	46
6. Antenna Requirement	52



Report Number: F690501/RF-RTL009947 Page: 3 of 52

1. General Information

1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- Wireless Div. 2FL, 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.

Telephone : +82 31 688 0901 FAX : +82 31 688 0921

1.2. Details of Applicant

Applicant : Hyundai MOBIS Co., Ltd.

Address : 203, Teheran-ro, Gangnam-gu, Seoul, 06141, Korea

Contact Person : Kwon, Heung-Chul Phone No. : +82 31 260 2714

1.3. Description of EUT

Kind of Product	DISPLAY CAR SYSTEM
Model Name	ADBB0GSAN
Power Supply	DC 14.4 V
Frequency Range	2 402 Mb ~ 2 480 Mb (Bluetooth), 2 412 Mb ~ 2 462 Mb (11b/g/n_HT20), 5 745 Mb ~ 5 825 Mb (Band 3: 11a/n_HT20, 11ac_VHT20), 5 755 Mb ~ 5 795 Mb (Band 3: 11n_HT40, 11ac_VHT40), 5 775 Mb (Band 3: 11ac_VHT80), 5 180 Mb ~ 5 240 Mb (Band 1: 11a/n_HT20, 11ac_VHT20), 5 190 Mb ~ 5 230 Mb (Band 1: 11n_HT40, 11ac_VHT40), 5 210 Mb (Band 1: 11ac_VHT80), 5 210 Mb (Band 1: 11ac_VHT80), 5 260 Mb ~ 5 320 Mb (Band 2A: 11a/n_HT20, 11ac_VHT20), 5 270 Mb ~ 5 310 Mb (Band 2A: 11n_HT40, 11ac_VHT40), 5 290 Mb (Band 2A: 11ac_VHT80), 5 500 Mb ~ 5 720 Mb (Band 2C: 11a/n_HT20, 11ac_VHT20), 5 510 Mb ~ 5 710 Mb (Band 2C: 11n_HT40, 11ac_VHT40), 5 530 Mb ~ 5 690 Mb (Band 2C: 11ac_VHT80)
Modulation Technique	DSSS, OFDM, GFSK, π/4DQPSK, 8DPSK
Number of Channels	79 channel (Bluetooth), 11 channel (11b/g/n_HT20), 5 channel (Band 3: 11a/n_HT20, 11ac_VHT20), 2 channel (Band 3: 11n_HT40, 11ac_VHT40), 1 channel (Band 3: 11ac_VHT80), 4 channel (Band 1: 11a/n_HT20, 11ac_VHT20), 2 channel (Band 1: 11n_HT40, 11ac_VHT40), 1 channel (Band 1: 11ac_VHT80), 4 channel (Band 2A: 11a/n_HT20, 11ac_VHT20), 2 channel (Band 2A: 11n_HT40, 11ac_VHT40), 1 channel (Band 2A: 11ac_VHT80), 9 channel (Band 2C: 11a/n_HT20, 11ac_VHT20), 4 channel (Band 2C: 11n_HT40, 11ac_VHT40), 2 channel (Band 2C: 11ac_VHT80)
Antenna Type	Chip Antenna (Bluetooth), PCB Antenna (WLAN)
Antenna Gain	2 402 MHz ~ 2 480 MHz: 2.29 dB i, 2 412 MHz ~ 2 462 MHz: -0.50 dB i, 5 180 MHz ~ 5 320 MHz: 2.89 dB i, 5 500 MHz ~ 5 720 MHz: 2.51 dB i, 5 745 MHz ~ 5 825 MHz: 5.78 dB i

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 http://www.sgsgroup.kr



Report Number: F690501/RF-RTL009947 Page: 4 of 52

1.4. Test Equipment List

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Interval	Cal. Due
Signal Generator	Agilent	E8257D	MY51501169	Jul. 13, 2015	Annual	Jul. 13, 2016
Spectrum Analyzer	R&S	FSV30	103100	Jun. 22, 2015	Annual	Jun. 22, 2016
Spectrum Analyzer	Agilent	N9020A	MY53421758	Sep. 24, 2015	Annual	Sep. 24, 2016
Attenuator	MCLI	FAS-23-20	23834	Jun. 08, 2015	Annual	Jun. 08, 2016
High Pass Filter	Wainwright Instrument GmbH	WHK3.0/18G-6SS	4	Jun. 23, 2015	Annual	Jun. 23, 2016
High Pass Filter	Wainwright Instrument GmbH	WHNX7.5/26.5G-6SS	15	Jun. 23, 2015	Annual	Jun. 23, 2016
Low Pass Filter	Mini-Circuits	NLP-1200+	V8979400903-2	Feb. 29, 2016	Annual	Feb. 29, 2017
Power Sensor	R&S	NRP-Z81	100669	Feb. 29, 2016	Annual	Feb. 29, 2017
DC Power Supply	Agilent	U8002A	MY53150029	Jun. 22, 2015	Annual	Jun. 22, 2016
Preamplifier	H.P.	8447F	2944A03909	Aug. 27, 2015	Annual	Aug. 27, 2016
Preamplifier	R&S	SCU-18	10117	Apr. 07, 2016	Annual	Apr. 07, 2017
Preamplifier	MITEQ Inc.	JS44-18004000-35-8P	1546891	May 12, 2016	Annual	May 12, 2017
Loop Antenna	R&S	HFH2-Z2	100118	Jun. 04, 2015	Biennial	Jun. 04, 2017
Bilog Antenna	Schwarzbeck Mess-Elektronik	VULB9163	396	Jun. 18, 2015	Biennial	Jun. 18, 2017
Horn Antenna	R&S	HF906	100326	Feb. 01, 2016	Biennial	Feb. 01, 2018
Horn Antenna	Schwarzbeck Mess-Elektronik	BBHA9170	BBHA9170223	Sep. 01, 2014	Biennial	Sep. 01, 2016
Antenna Master	INN-CO	MM4000	N/A	N.C.R.	N/A	N.C.R.
Turn Table	INN-CO	DS 1200 S	N/A	N.C.R.	N/A	N.C.R.
Test Receiver	R&S	ESU26	100109	Mar. 07, 2016	Annual	Mar. 07, 2017
Anechoic Chamber	SY Corporation	L × W × H (9.6 m × 6.4 m × 6.6 m)	N/A	N.C.R.	N/A	N.C.R.



Report Number: F690501/RF-RTL009947 Page: 5 of 52

1.5. Summary of Test Results

The EUT has been tested according to the following specifications:

AP	APPLIED STANDARD: FCC Part15 Subpart C									
Standard section	Test Item(s)	Result								
15.205(a) 15.209 15.247(d)	Transmitter Radiated Spurious Emissions Conducted Spurious Emission	Complied								
15.247(a)(2)	6 dB Bandwidth	Complied								
15.247(b)(3)	Maximum Peak Conducted Output Power	Complied								
15.247(e)	Power Spectral Density	Complied								

1.6. Test Procedure(s)

The measurement procedures described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2009) and the guidance provided in KDB 558074_v03r05 were used in the measurement of the DUT.

1.7. Sample calculation

Where relevant, the following sample calculation is provided:

1.7.1. Conducted test

Offset value (dB) = Attenuator (dB) + Cable loss (dB)

1.7.2. Radiation test

Field strength level ($dB\mu V/m$) = Measured level ($dB\mu V$) + Antenna factor (dB) + Cable loss (dB) - Amplifier gain (dB)

1.8. Test report revision

Revision	Report number	Date of Issue	Description
0	F690501/RF-RTL009947	2016.06.08	Initial



Report Number: F690501/RF-RTL009947 Page: 6 of 52

1.9. Duty Cycle of EUT

Regarding to KDB558074 v03r05, 6.0, the maximum duty cycles of all modes were investigated and set the spectrum analyzer as below

Set RBW \geq OBW if possible; otherwise, set RBW to the largest available value, Set VBW \geq RBW. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are > 50/T and the number of sweep points across duration T exceeds 100.

Mode		Data Rate (Mbps)									
11b	1	2	5.5	11	-	-	-	-			
Duty Cycle (%)	99	97	94	90	-	-	-	-			
Correction factor (dB)	0.04	0.13	0.27	0.46	-	-	-	-			
11g	6	9	12	18	24	36	48	54			
Duty Cycle (%)	93	90	87	82	78	71	65	63			
Correction factor (dB)	0.32	0.46	0.60	0.86	1.08	1.49	1.87	2.01			
11n_HT20	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7			
Duty Cycle (%)	93	86	82	78	72	66	64	62			
Correction factor (dB)	0.32	0.66	0.86	1.08	1.43	1.80	1.94	2.08			

Remark:

- 1. As measured duty cycles of EUT, all of mode and data rate keep constant period and are converted to log scale (power averaging) to compensate correction factor to result of average test items.
- 2. Duty cycle (%) = $(Tx \text{ on time } / Tx \text{ on + off time}) \times 100$
- 3. Correction factor (dB) = $10 \log (1 / \text{Duty cycle})$



Report Number: F690501/RF-RTL009947 Page: 7 of 52


2. Transmitter Radiated Spurious Emissions and Conducted Spurious Emission

2.1. Test Setup


RTT5041-20(2015.10.01)(3)

2.1.1. Transmitter Radiated Spurious Emissions

The diagram below shows the test setup that is utilized to make the measurements for emission from 9 klb to 30 Mb Emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 $\,\text{Mz}$ to 1 $\,\text{GHz}$ Emissions.



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 http://www.sgsgroup.kr


Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210mm × 297mm)



F690501/RF-RTL009947 Page: Report Number: 8 of 52

The diagram below shows the test setup that is utilized to make the measurements for emission. The spurious emissions were investigated form 1 GHz to the 10th harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.





Report Number: F690501/RF-RTL009947 Page: 9 of 52

2.1.2. Conducted Spurious Emission



2.2. Limit

RTT5041-20(2015.10.01)(3)

According to §15.247(d), in any 100 klb bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 klb bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph(b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in section §15.209(a) is not required. In addition, radiated emission which in the restricted band, as define in section §15.205(a), must also comply the radiated emission limits specified in section §15.209(a) (see section §15.205(c))

According to § 15.209(a), Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (脈)	Distance (Meters)	Field Strength (μV/m)	
0.009 - 0.490	300	20 log (2 400/F(kl/z))	2 400/F(kHz)
0.490 - 1.705	30	20 log (24 000/F(kllz))	24 000/F(kllz)
1.705 - 30.0	30	29.54	30
30 - 88	3	40.0	100**
88 - 216	3	43.5	150**
216 - 960	3	46.0	200**
Above 960	3	54.0	500

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210mm × 297mm)



Report Number: F690501/RF-RTL009947 Page: 10 of 52

2.3. Test Procedures

Radiated emissions from the EUT were measured according to the dictates in section 11.0 & 12.0 of KDB 558074 v03r05 and ANSI C63.10-2009.

Remark:

2.3.1. Test Procedures for emission below 30 Mb

- 1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- 2. Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel and perpendicular of the antenna are set to make the measurement.
- 3. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
- 4. The test-receiver system was set to average or quasi peak detect function and Specified Bandwidth with Maximum Hold Mode.

2.3.2. Test Procedures for emission from above 30 Mb

- 1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site below 1 ¾ and 1.5 meter above the ground at a 3 meter anechoic chamber test site above 1 ¾ The table was rotated 360 degrees to determine the position of the highest radiation.
- 2. During performing radiated emission below 1 % the EUT was set 3 meters away from the interference receiving antenna, which was mounted on the top of a variable-height antenna tower. During performing radiated emission above 1 % the EUT was set 3 meter away from the interference-receiving antenna.
- 3. The antenna is a bi-log antenna, a horn antenna and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
- 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- 6. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.



Report Number: F690501/RF-RTL009947 Page: 11 of 52

NOTE;

All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

- 1. Unwanted Emissions into Non-Restricted Frequency Bands
- The Reference Level Measurement refer to section 11.2 Set analyzer center frequency to DTS channel center frequency, SPAN \geq 1.5 times the DTS bandwidth, the RBW = 100 kHz and VBW \geq 3 \times RBW, Detector = Peak, Sweep time = Auto couple, Trace = Max hold.
- Unwanted Emissions Level Measurement refer to section 11.3 Set the center frequency and span to encompass frequency range to be measured, the RBW = 100 $\,\mathrm{kHz}$ and $\,\mathrm{VBW} \ge 3 \times \mathrm{RBW}$, Detector = Peak, Sweep time = Auto couple, Trace = Max hold.
- 2. Unwanted Emissions into Restricted Frequency Bands
- Peak Power measurement procedure refer to section 12.2.4 Set RBW = as specified in Table 1, VBW ≥ 3 x RBW, Detector = Peak, Sweep time = auto, Trace = Max hold.

Table 1- RBW as a function of frequency

Frequency	RBW
9 – 150 kHz	200 – 300 Hz
0.15 − 30 MHz	9 – 10 kHz
30 – 1 000 MHz	100 – 120 kHz
>1 000 MHz	1 MHz

- Average Power measurements procedure refer to section 12.2.5.2

The EUT shall be configured to operate at the maximum achievable duty cycle.

Measure the duty cycle, x, of the transmitter output signal as described in section 6.0.

Set RBW = 1 Mb, VBW ≥ 3 x RBW, Detector = RMS, if span / (# of points in sweep) ≤ (RBW/2).

Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied then the detector mode shall be set to peak.

Averaging type = power (i.e., RMS).

As an alternative the detector and averaging type may be set for linear voltage averaging.

Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used. Sweep time = auto, Perform a trace average of at least 100 traces.

A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:

- 1) If power averaging (RMS) mode was used in step f), then the applicable correction factor is 10 log (1/x), where x is the duty cycle.
- 3) If a specific emission is demonstrated to be continuous (≥ 98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.
- 3. Definition of DUT Axis.

Definition of the test orthogonal plan for EUT was described in the test setup photo.

The test orthogonal plan of EUT is **X-axis** during radiation test.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.



Report Number: F690501/RF-RTL009947 Page: 12 of 52

2.3.3. Test Procedures for Conducted Spurious Emissions

All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

Per the guidance of KDB 558074 v03r05, section 11.1 & 11.2 & 11.3, the reference level for out of band emissions is established from the plots of this section since the band edge emissions are measured with a RBW of 100 $\,\mathrm{klz}$. This reference level is then used as the limit in subsequent plots for out of band spurious emissions shown in section 2.4.3. The limit for out of band spurious emission at the band edge is 20 $\,\mathrm{dB}$ or 30 $\,\mathrm{dB}$ below the fundamental emission level measured in a 100 $\,\mathrm{klz}$ bandwidth.

1. Conducted Emissions at Band Edge

2. Conducted Spurious Emissions

- The Measurement refer to section 11.3

Start frequency was set to 9 № and stop frequency was set to 25 № (separated into two plots per channel), RBW = 100 № VBW ≥ 3 x RBW, Detector = Peak, Sweep time = Auto couple, Trace = Max hold, The trace was allowed to stabilize.

3. TDF function

- For plots showing conducted spurious emissions from 16 Mb to 25 GHz, all path loss of wide frequency range was investigated and compensated to spectrum analyzer as TDF function. So, the reading values shown in plots were final result.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.



Report Number: F690501/RF-RTL009947 Page: 13 of 52

2.4. Test Results

Ambient temperature : **(23** ± **1)** ℃ % R.H. Relative humidity : 47

2.4.1. Radiated Spurious Emission below 1 000 Mb

The frequency spectrum from 16 Mb to 1 000 Mb was investigated. All reading values are peak values.

Radia	ated Emissio	sions		Ant Correction Factors		Total	Lim	it
Frequency (脏)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP + CL (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
53.97	46.80	Peak	V	13.87	-26.99	33.68	40.00	6.32
226.47	40.30	Peak	V	12.92	-25.58	27.64	46.00	18.36
266.64	42.90	Peak	Н	13.60	-25.34	31.16	46.00	14.84
350.99	47.60	Peak	V	16.42	-25.29	38.73	46.00	7.27
466.66	44.90	Peak	V	17.76	-25.85	36.81	46.00	9.19
621.01	43.40	Peak	V	19.94	-25.81	37.53	46.00	8.47
675.05	46.70	Peak	V	21.12	-25.63	42.19	46.00	3.81
Above 700.00	Not detected	-	-	-	-	-	-	-

Remark:

- Reported spurious emissions are in 11n_HT20 / MCS0 / high channel as worst case among other modes.
- Radiated spurious emission measurement as below. (Actual = Reading + Antenna Factor + Amp + CL)
- 4. According to §15.31(o), emission levels are not report much lower than the limits by over 20 dB.
- 5. The device has a reference clock operating at 16 Mb.



Report Number: F690501/RF-RTL009947 Page: 14 of 52

2.4.2. Radiated Spurious Emission above 1 000 Mb

The frequency spectrum above 1 000 Mb was investigated. All reading values are peak and average values.

DSSS: 802.11b(1 Mbps)

Low Channel (2 412 Mb)

Radi	ated Emissio	ns	Ant.	t. Correction Factors			Total	Limi	it
Frequency (脈)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Duty (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*2 310.00	24.79	Peak	Н	28.07	5.69	-	58.55	74.00	15.45
*2 310.00	14.66	Average	Н	28.07	5.69	-	48.42	54.00	5.58
*2 374.26	26.83	Peak	Н	28.13	5.82	ı	60.78	74.00	13.22
*2 389.71	15.43	Average	Н	28.15	5.79	-	49.37	54.00	4.63
*2 390.00	24.54	Peak	Н	28.15	5.79	-	58.48	74.00	15.52
*2 390.00	15.15	Average	Н	28.15	5.79	-	49.09	54.00	4.91

Radiated Emissions			Ant.	Correction Factors			Total Limit		it
Frequency (Mb)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dΒμV/m)	Limit (dBµV/m)	Margin (dB)
*4 823.98	45.09	Peak	Н	32.71	-29.38	-	48.42	74.00	25.58
*4 823.90	37.81	Average	Н	32.71	-29.38	-	41.14	54.00	12.86
Above 4 900.00	Not detected	-	-	-	-	-	-	-	-



Report Number: F690501/RF-RTL009947 Page: 15 of 52

Middle Channel (2 437 Mb)

Radiated Emissions			Ant.	Correction Factors			Total	Lim	it
Frequency (Mb)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dΒμV/m)	Limit (dBµV/m)	Margin (dB)
*4 873.72	46.53	Peak	Н	32.84	-29.16	-	50.21	74.00	23.79
*4 873.85	40.44	Average	Н	32.84	-29.16	-	44.12	54.00	9.88
Above 4 900.00	Not detected	-	-	-	-	-	-	-	-

High Channel (2 462 雕)

Radi	ated Emissio	ns	Ant.	Corre	ction Fa	ctors	Total	Limi	t
Frequency (账)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Duty (dB)	Actual (dBµN/m)	Limit (dBµV/m)	Margin (dB)
*2 483.50	26.51	Peak	Н	28.24	5.82	-	60.57	74.00	13.43
*2 483.50	15.72	Average	Н	28.24	5.82	-	49.78	54.00	4.22
*2 484.88	28.35	Peak	Н	28.24	5.82	-	62.41	74.00	11.59
*2 488.28	16.52	Average	Н	28.25	5.83	-	50.60	54.00	3.40
*2 500.00	26.12	Peak	Н	28.26	5.85	-	60.23	74.00	13.77
*2 500.00	15.56	Average	Н	28.26	5.85	-	49.67	54.00	4.33

Radi	ated Emissio	ons	Ant.	Corre	ection Fa	ctors	Total	Lim	it
Frequency (Mb)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*4 927.20	42.06	Peak	Н	32.98	-29.15	-	45.89	74.00	28.11
*4 921.10	32.77	Average	Н	32.97	-29.15	-	36.59	54.00	17.41
Above 5 000.00	Not detected	-	-	-	-	-	-	-	-



Report Number: F690501/RF-RTL009947 Page: 16 of 52

OFDM: 802.11g(6 Mbps)

Low Channel (2 412 Mb)

Radi	ated Emissio	ons	Ant.	Corre	ection Fa	ctors	Total	Limi	it
Frequency (쌘)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Duty (dB)	Actual (dBµN/m)	Limit (dBµV/m)	Margin (dB)
*2 310.00	24.94	Peak	Н	28.07	5.69	-	58.70	74.00	15.30
*2 310.00	14.64	Average	Н	28.07	5.69	0.32	48.72	54.00	5.28
*2 378.62	26.59	Peak	Н	28.14	5.81	-	60.54	74.00	13.46
*2 389.38	15.55	Average	Н	28.15	5.79	0.32	49.81	54.00	4.19
*2 390.00	24.90	Peak	Н	28.15	5.79	-	58.84	74.00	15.16
*2 390.00	14.86	Average	Н	28.15	5.79	0.32	49.12	54.00	4.88

Radi	ated Emissio	ns	Ant.	Corre	ection Fa	ctors	Total	Limi	it
Frequency (Mb)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dΒμV/m)	Limit (dBµV/m)	Margin (dB)
*4 822.44	41.59	Peak	Н	32.70	-29.40	-	44.89	74.00	29.11
*4 821.55	30.52	Average	Н	32.70	-29.40	0.32	34.14	54.00	19.86
Above 4 900.00	Not detected	-	-	-	-	-	-	-	-

Middle Channel (2 437 Mb)

Radi	ated Emissio	ns	Ant.	Corre	Correction Factors			Limi	it
Frequency (Mb)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dΒμV/m)	Limit (dBµV/m)	Margin (dB)
*4 875.38	41.52	Peak	Н	32.85	-29.14	-	45.23	74.00	28.77
*4 872.32	30.47	Average	Н	32.84	-29.19	0.32	34.44	54.00	19.56
Above 4 900.00	Not detected	-	-	-	-	-	-	-	-



Report Number: F690501/RF-RTL009947 Page: 17 of 52

High Channel (2 462 Mb)

Radi	ated Emissic	ns	Ant.	Corre	ction Fa	ctors	Total	Limi	it
Frequency (Mb)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Duty (dB)	Actual (dBµV/m)	Limit (dB <i>µ</i> V/m)	Margin (dB)
*2 483.50	25.87	Peak	Н	28.24	5.82	-	59.93	74.00	14.07
*2 483.50	15.65	Average	Н	28.24	5.82	0.32	50.03	54.00	3.97
*2 490.52	27.50	Peak	Н	28.25	5.83	1	61.58	74.00	12.42
*2 491.76	16.22	Average	Н	28.25	5.83	0.32	50.62	54.00	3.38
*2 500.00	25.66	Peak	Н	28.26	5.85	-	59.77	74.00	14.23
*2 500.00	15.30	Average	Н	28.26	5.85	0.32	49.73	54.00	4.27

Radi	ated Emissio	ns	Ant.	Corre	ection Fa	ctors	Total	Lim	it
Frequency (Mb)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dΒμV/m)	Limit (dBµV/m)	Margin (dB)
*4 922.71	41.79	Peak	Н	32.97	-29.15	-	45.61	74.00	28.39
*4 927.44	31.25	Average	Н	32.99	-29.15	0.32	35.41	54.00	18.59
Above 5 000.00	Not detected	-	-	-	-	-	-	-	-



Report Number: F690501/RF-RTL009947 Page: 18 of 52

OFDM: 802.11n_HT20(MCS0)

Low Channel (2 412 Mb)

Radi	ated Emissio	ns	Ant.	Corre	ection Fa	ctors	Total	Limi	it
Frequency (Mb)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Duty (dB)	Actual (dBµV/m)	Limit (dBµN/m)	Margin (dB)
*2 310.00	25.46	Peak	Н	28.07	5.69	-	59.22	74.00	14.78
*2 310.00	14.71	Average	Н	28.07	5.69	0.32	48.79	54.00	5.21
*2 330.58	27.52	Peak	Н	28.09	5.68	ı	61.29	74.00	12.71
*2 389.82	15.74	Average	Н	28.15	5.79	0.32	50.00	54.00	4.00
*2 390.00	26.39	Peak	Н	28.15	5.79	-	60.33	74.00	13.67
*2 390.00	15.39	Average	Н	28.15	5.79	0.32	49.65	54.00	4.35

Radi	ated Emissio	ns	Ant.	Corre	Correction Factors			Lim	it
Frequency (Mb)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dΒμV/m)	Limit (dBµV/m)	Margin (dB)
*4 822.72	41.47	Peak	Н	32.70	-29.39	-	44.78	74.00	29.22
*4 823.97	30.42	Average	Н	32.71	-29.38	0.32	34.07	54.00	19.93
Above 4 900.00	Not detected	-	-	-	-	-	-	-	-

Middle Channel (2 437 Mb)

Radi	ated Emissio	ns	Ant.	Corre	ection Fa	ctors	Total	Total Limit	
Frequency (Mb)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dΒμV/m)	Limit (dBµV/m)	Margin (dB)
*4 873.78	42.34	Peak	Н	32.84	-29.16	-	46.02	74.00	27.98
*4 874.98	30.67	Average	Н	32.84	-29.14	0.32	34.69	54.00	19.31
Above 4 900.00	Not detected	-	-	-	-	-	-	-	-



Report Number: F690501/RF-RTL009947 Page: 19 of 52

High Channel (2 462 账)

Radi	ated Emissio	ns	Ant.	Corre	ection Fa	ctors	Total	Limi	t
Frequency (Mb)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Duty (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*2 483.50	25.98	Peak	Н	28.24	5.82	-	60.04	74.00	13.96
*2 483.50	15.63	Average	Н	28.24	5.82	0.32	50.01	54.00	3.99
*2 485.16	26.71	Peak	Н	28.24	5.82	-	60.77	74.00	13.23
*2 483.64	16.13	Average	Н	28.24	5.82	0.32	50.51	54.00	3.49
*2 500.00	24.68	Peak	Н	28.26	5.85	-	58.79	74.00	15.21
*2 500.00	15.33	Average	Н	28.26	5.85	0.32	49.76	54.00	4.24

Radi	ated Emissio	ns	Ant.	Corre	ection Fa	ctors	Total	Lim	it
Frequency (畑)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+ CL (dB)	Duty (dB)	Actual (dΒμΝ/m)	Limit (dBµV/m)	Margin (dB)
*4 923.38	42.47	Peak	Н	32.97	-29.16	-	46.28	74.00	27.72
*4 924.13	31.03	Average	Н	32.98	-29.16	0.32	35.17	54.00	18.83
Above 5 000.00	Not detected	-	-	-	-	-	-	-	-

Remarks:

- 1. "*" means the restricted band.
- 3. Radiated emissions measured in frequency above 1 000 Mb were made with an instrument using peak/average detector mode.
- 4. Actual = Reading + AF + AMP + CL or Reading + AF + CL.
- 5. According to § 15.31(o), Emission levels are not reported much lower than the limits by over 20 dB.




Report Number: F690501/RF-RTL009947 Page: 20 of 52

2.4.3. Spurious RF Conducted Emissions: Plot of Spurious RF Conducted Emission

DSSS: 802.11b (1 Mbps)


Low Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.




Report Number: F690501/RF-RTL009947 Page: 21 52 of






Report Number: F690501/RF-RTL009947 Page: 22 of 52

Middle Channel






Report Number: F690501/RF-RTL009947 Page: 23 52 of





Report Number: F690501/RF-RTL009947 Page: 24 of 52


High Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.



Report Number: F690501/RF-RTL009947 Page: 25 52 of






Report Number: F690501/RF-RTL009947 Page: 26 of 52

OFDM: 802.11g (6 Mbps)


Low Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.




Report Number: F690501/RF-RTL009947 Page: 27 52 of






Report Number: F690501/RF-RTL009947 Page: 28 of 52

Middle Channel






Report Number: F690501/RF-RTL009947 Page: 29 52 of






Report Number: F690501/RF-RTL009947 Page: 30 of 52

High Channel





Report Number: F690501/RF-RTL009947 Page: 31 52 of






Report Number: F690501/RF-RTL009947 Page: 32 of 52

OFDM: 802.11n_HT20 (MCS0)


Low Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.




Report Number: F690501/RF-RTL009947 Page: 33 52 of






Report Number: F690501/RF-RTL009947 Page: 34 of 52

Middle Channel






Report Number: F690501/RF-RTL009947 Page: 35 52 of





Report Number: F690501/RF-RTL009947 Page: 36 of 52


High Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.



Report Number: F690501/RF-RTL009947 Page: 37 52 of





Report Number: F690501/RF-RTL009947 Page: 38 of 52

3. 6 dB Bandwidth

3.1. Test Setup



3.2. Limit

According to §15.247(a)(2), systems using digital modulation techniques may operate in the 902-928 Mb, 2 400-2 483.5 Mb, and 5 725-5 825 Mb bands. The minimum of 6 dB Bandwidth shall be at least 500 klb.

3.3. Test Procedure

3.3.1. 6 dB Bandwidth

All data rates and modes were investigated for this test. The full data for the worst case data rate are reported in this section.

The test follows section 8.0 DTS bandwidth of FCC KDB Publication 558074_v03r05. Tests performed using section 8.1 Option 1.

- Option 1:
- 1. Set RBW = 100 kHz.
- 2. Set the video bandwidth (VBW) \geq 3 x RBW.
- 3. Detector = Peak.
- 4. Trace mode = max hold.
- 5. Sweep = auto couple.
- 6. Allow the trace to stabilize.
- 7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Report Number: F690501/RF-RTL009947 Page: 39 of 52


3.4. Test Results

Ambient temperature : (23 \pm 1) $^{\circ}$ C Relative humidity : 47 $^{\circ}$ R.H.

Operation Mode	Data Rate (Mbps)	Channel	Frequency (썐)	6 dB Bandwidth (畑)	Minimum Bandwidth (朏)	
DSSS (802.11b)	1	Low	2 412	7.64		
		Middle	2 437	7.65		
		High	2 462	8.57		
OFDM (802.11g)	6	Low	2 412	16.44		
		Middle	2 437	16.45	500	
		High	2 462	16.44		
OFDM (802.11n_HT20)	MCS0	Low	2 412	17.66		
		Middle	2 437	17.72		
		High	2 462	17.71		

DSSS: 802.11b


Low Channel






Report Number: F690501/RF-RTL009947 Page: 40 of 52

Middle Channel



High Channel







Report Number: F690501/RF-RTL009947 Page: 41 of 52

OFDM: 802.11g

Low Channel




Middle Channel






Report Number: F690501/RF-RTL009947 Page: 42 of 52

High Channel



OFDM: 802.11n_HT20


Low Channel






Report Number: F690501/RF-RTL009947 Page: 43 of 52

Middle Channel



High Channel






Report Number: F690501/RF-RTL009947 Page: 44 of 52

4. Maximum Peak Conducted Output Power

4.1. Test Setup



4.2. Limit

According to §15.247(b)(3), for systems using digital modulation in the 902-928 Mb, 2 400-2 483.5 Mb, and 5 725-5 850 Mb band: 1 Watt. As an alternative to a peak power measurement, compliance with the one watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antenna elements. The average must not include any intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

According to §15.247(b)(4), the conducted output power limit specified in paragraph(b) of this section is based on the use of antenna with directional gains that do not exceed 6 dBi. Except as shown in paragraph(c) of this section, if transmitting antenna of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraph (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

4.3. Test Procedure

The test follows section 9.1.2 of FCC KDB Publication 558074 v03r05.

- Peak power meter method

-The maximum peak conducted output power can be measured using a broad band peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

Test program: (S/W name : R&S Power Viewer, Version : 3.2.0)

- 1. Initially overall offset for attenuator and cable loss is measured per frequency.
- 2. Measured offset is inserted in test program in advance of measurement for output power.
- 3. Power for each frequency (channel) and data rate of device is investigated as final result.
- 4. Final result reported on this section from R&S power viewer program includes with several factors and test program shows only final result.



Report Number: F690501/RF-RTL009947 Page: 45 of 52

4.4. Test Results

Ambient temperature : (23 \pm 1) $^{\circ}$ C Relative humidity : 47 $^{\circ}$ R.H.

Mode	Channel	Frequency (Mb)	Data Rate (Mbps)	Attenuator + Cable offset (dB)	Peak Power Result (dB m)	Peak Power Limit (dB m)
DSSS (802.11b)	Low	2 412	1	21.00	18.99	
	Middle	2 437	1	21.07	19.10	
	High	2 462	1	20.93	<u>19.28</u>	
OFDM (802.11g)	Low	2 412	6	21.00	19.44	
	Middle	2 437	6	21.07	19.34	30
	High	2 462	6	20.93	<u>19.77</u>	
OFDM (802.11n_HT20)	Low	2 412	MCS0	21.00	20.22	
	Middle	2 437	MCS0	21.07	20.22	
	High	2 462	MCS0	20.93	<u>20.25</u>	

Remark:

Attenuator and cable offset was compensated in test program (R&S Power Viewer) before measuring.



Report Number: F690501/RF-RTL009947 Page: 46 of 52

5. Power Spectral Density

5.1. Test Setup



5.2. Limit

§15.247(e) For digitally modulated system, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dB m in any 3 kHz band any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

5.3. Test Procedure

All data rates and modes were investigated for this test. The full data for the worst case data rate are reported in this section.

The measurements are recorded using the PKPSD measurement procedure in section 10.2 of KDB 558074 v03r05.

- This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance, and is optional if the maximum conducted (average) output power was used to demonstrate compliance.
- 1. Set analyzer center frequency to DTS channel center frequency.
- 2. Set the span to at least 1.5 times the DTS channel bandwidth.
- 3. Set the RBW to : 3 kHz \leq RBW \leq 100 kHz.
- 4. Set the VBW \geq 3 x RBW.
- 5. Detector = Peak.
- 6. Sweep time = auto couple.
- 7. Trace mode = max hold.
- 8. Allow trace to fully stabilize.
- 9. Use the peak marker function to determine the maximum amplitude level within the RBW.
- 10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Report Number: F690501/RF-RTL009947 Page: 47 of 52


5.4. Test Results

Ambient temperature : (23 \pm 1) $^{\circ}$ C Relative humidity : 47 $^{\circ}$ R.H.

Operation Mode	Data Rate (Mbps)	Channel	Frequency (Mb)	Measured PSD (dB m)	Maximum Limit (dB m)	
DSSS (802.11b)	1	Low	2 412	-4.01		
		Middle	2 437	-5.48		
		High	2 462	-5.64		
OFDM (802.11g)	6	Low	2 412	-12.27		
		Middle	2 437	-11.69	8	
		High	2 462	-12.67		
OFDM (802.11n_HT20)	MCS0	Low	2 412	-12.77		
		Middle	2 437	-12.77		
		High	2 462	-12.27		

DSSS: 802.11b


Low Channel






Report Number: F690501/RF-RTL009947 Page: 48 of 52

Middle Channel



High Channel







Report Number: F690501/RF-RTL009947 Page: 49 of 52

OFDM: 802.11g

Low Channel




Middle Channel






Report Number: F690501/RF-RTL009947 Page: 50 of 52

High Channel



OFDM: 802.11n_HT20


Low Channel






Report Number: F690501/RF-RTL009947 Page: 51 of 52

Middle Channel



High Channel





Report Number: F690501/RF-RTL009947 Page: 52 of 52

6. Antenna Requirement

6.1. Standard Applicable

For intentional device, according to FCC 47 CFR Section §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section §15.247 (b) if transmitting antennas of directional gain greater than 6 dB i are used, the power shall be reduced by the amount in dB that the gain of the antenna exceeds 6 dB i.

6.2. Antenna Connected Construction

Antenna used in this product is PCB type with gain of -0.50 dB i.