

Report Number: F690501/RF-RTL006395 Page: 1 of 5

MPE TEST REPORT

of

FCC CFR 47 part 1, 1.1307(b), 1.1310

FCC ID: TQ8-AM9B1MDAN

Equipment Under Test : DIGITAL CAR AUDIO SYSTEM

Model Name : FCC:AM9B1MDAN(Alt:AM9B0MDAN, AM9B0MDKN,

AM910MDMG, AM911MDMG, AM910MDMN,

AM910MDEE, AM911MDMN, AM910MDXN, AM910MDAN)

Serial No. : N/A

Applicant : Hyundai MOBIS Co., Ltd.

Manufacturer : Hyundai MOBIS Co., Ltd.

Date of Test(s) : 2013.03.30 ~ 2013.04.09

Date of Issue : 2013.04.09

In the configuration tested, the EUT complied with the standards specified above.

Tested By:	glate	Date:	2013.04.09	
-	Harim Lee			
Approved By:	Min	Date:	2013.04.09	
	Hyunchae You	~		

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.



Report Number: F690501/RF-RTL006395 Page: 2 of 5

INDEX

Table of Contents	Page
1. General Information	3
2. RF Exposure Evaluation	4



Report Number: F690501/RF-RTL006395 Page: 3 of 5

1. General Information

1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- Wireless Div. 3FL, 18-34, Sanbon-dong, Gunpo-si, Gyeonggi-do, Korea 435-040 (Lab)
- Wireless Div. 1FL, 18-34, Sanbon-dong, Gunpo-si, Gyeonggi-do, Korea 435-040 (Chamber)

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.

Telephone : +82 31 428 5700 FAX : +82 31 427 2371

1.2. Details of Applicant

Applicant : Hyundai MOBIS Co., Ltd.

Address : 80-9, Mabook-Dong, Giheung-Gu Yongin-Shi, Gyunggi-Do, 446-912, South Korea

Contact Person : Kim, Jong-Tae Phone No. : +82 31 260 0092

1.3. Description of EUT

Kind of Product	DIGITAL CAR AUDIO SYSTEM		
Model Name	FCC: AM9B1MDAN(Alt:AM9B0MDAN, AM9B0MDKN, AM910MDMG, AM911MDMG, AM910MDMN, AM910MDEE, AM911MDMN, AM910MDXN, AM910MDAN)		
Serial Number	N/A		
Power Supply	DC 12 V		
Frequency Range	2 402 Mb ~ 2 480 Mb		
Modulation Technique	GFSK, π/4DQPSK, 8DPSK		
Number of Channels	79		
Antenna Type	Chip antenna		
Antenna Gain	3.5 dBi		

1.4. Test report revision

Revision	Report number	Description		
0	F690501/RF-RTL006395	Initial		



Report Number: F690501/RF-RTL006395 Page: 4 of 5

2. RF Exposure Evaluation

2.1. Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(b), 1.1310

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in §1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (쌘)	Electric Field Strength(V/m)	Magnetic Field Strength (A/m)	Power Density (ﷺ)	Average Time			
(A) Limits for Occupational /Control Exposures							
300 – 1 500			F/300	6			
1 500 – 100 000			5	6			
(B) Limits for General Population/Uncontrol Exposures							
300 – 1 500			F/1500	6			
<u>1 500 – 100 000</u>			1	<u>30</u>			

2.1.1. Friis transmission formula: Pd = (Pout*G)/(4*pi*R²)

Where Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.



Report Number: F690501/RF-RTL006395 Page: 5 of 5

2.1.2. Test Result of RF Exposure Evaluation

Test Item : RF Exposure Evaluation Data

Test Mode : Normal Operation

2.1.3. Output Power into Antenna & RF Exposure Evaluation Distance

FHSS: GFSK

Channel	Channel Frequency (쌘)	Output Average Power to Antenna (dB m)	Antenna Gain (dB i)	Duty Cycle (%)	Power Density at 20 cm (mW/cm²)	Limits (nW/cm²)
Low	2 402	0.90	3.5	46	0.000 252	1
Middle	2 441	1.03	3.5	46	0.000 260	1
High	2 480	0.88	3.5	46	0.000 251	1

FHSS: 8DPSK

Channel	Channel Frequency (쌘)	Output Average Power to Antenna (dB m)	Antenna Gain (dB i)	Duty Cycle (%)	Power Density at 20 cm (ﷺ/ﷺ)	Limits (nW/cm²)
Low	2 402	0.10	3.5	42	0.000 191	1
Middle	2 441	0.21	3.5	42	0.000 196	1
High	2 480	-0.30	3.5	42	0.000 175	1

Note:

1. The power density Pd (5th column) at a distance of 20 cm calculated from the friis transmission formula is far below the limit of 1 mW/cm².