

# HCT CO., LTD.

# CERTIFICATE OF COMPLIANCE

# **FCC Certification**

**Applicant Name:** 

HYUNDAI MOBIS CO., LTD.

Address:

80-9, Mabook-Dong, Giheung-Gu Yongin-shi

Gyunggi-Do, 446-912 South Korea

Date of Issue:

April 05, 2012

Location:

HCT CO., LTD., 105-1, Jangam-ri, Majang-Myeon, Icheon-

si, Kyunggi-Do, Korea

Test Report No.: HCTR1204FR04

HCT FRN: 0005866421

IC Recognition No.: 5944A-3

FCC ID

:TQ8-AV2B0SDAN

IC

:5074A-AV2B0SDKN

**APPLICANT** 

:HYUNDAI MOBIS CO., LTD.

FCC Model(s):

AV2B0SDAN

IC Model(s):

AV2B0SDKN

**EUT Type:** 

CAR AVN

Max. RF Output Power:

4.10 dBm(2.57 mW)

Frequency Range:

2402 - 2480 MHz (Bluetooth)

Modulation type

GFSK(Normal), PSK(EDR)

FCC Classification:

FCC Part 15 Spread Spectrum Transceiver

FCC Rule Part(s):

Part 15 subpart C 15.247

IC Rule:

RSS-210, RSS-GEN

Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998,21 U.S. C.853(a)

Report prepared by : Jong Seok Lee

Test Engineer of RF Team

Approved by

: Chang Seok Choi Manager of RF Team

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

FCC PT.15.247 TEST REPORT		FCC & IC CERTIFICATION REPORT		www.hct.co.kr
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID :	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN



# **Version**

TEST REPORT NO.	DATE	DESCRIPTION
HCTR1204FR04	April 05, 2012	- First Approval Report



# **Table of Contents**

1.	GENERA	AL INFORMATION	4
2.	EUT DES	SCRIPTION	4
3.	TEST ME	ETHODOLOGY	5
	3.1	EUT CONFIGURATION	5
	3.2	EUT EXERCISE	5
	3.3	GENERAL TEST PROCEDURES	5
	3.4	DESCRIPTION OF TEST MODES	5
4.	INSTRU	MENT CALIBRATION	6
5.	FACILITI	ES AND ACCREDITATIONS	6
	5.1	FACILITIES	6
	5.2	EQUIPMENT	6
6.	ANTENN	IA REQUIREMENTS	6
7.	SUMMAI	RY OF TEST RESULTS	7
8.	FCC PAF	RT 15.247 REQUIREMENTS	8
	8.1	PEAK POWER	8
	8.2	BAND EDGES	13
	8.3	FREQUENCY SEPARATION / OCCUPIED BANDWIDTH (99% BW)	19
	8.4	NUMBER OF HOPPING FREQUENCY	24
	8.5	TIME OF OCCUPANCY (DWELL TIME)	27
	8.6	SPURIOUS EMISSIONS	32
	8.6.1	CONDUCTED SPURIOUS EMISSIONS	32
	8.6.2	RADIATED SPURIOUS EMISSIONS	39
	8.6.3	RECEIVER SPURIOUS EMISSIONS	47
	8.6.4	RADIATED RESTRICTED BAND EDGES	48
	8.7	POWERLINE CONDUCTED EMISSIONS	50
9.	LIST OF	TEST EQUIPMENT	51

FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID:	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN



# 1. GENERAL INFORMATION

**Applicant Name:** HYUNDAI MOBIS CO., LTD.

Address: 80-9, Mabook-Dong, Giheung-Gu Yongin-shi

Gyunggi-Do, 446-912 South Korea

FCC ID: TQ8-AV2B0SDAN IC 5074A-AV2B0SDKN

EUT: CAR AVN
FCC Model name(s): AV2B0SDAN
IC Model name(s): AV2B0SDKN

**Date(s) of Tests:** March 19, 2012 ~ March 26, 2012

Contact Person: Name: Jong Tae Kim

Phone #: +82-31-288-6081 Fax #: +82-31-899-1788

Place of Tests: HCT Co., Ltd.

Icheon-si, Kyunggi-Do, Korea(Lab) (IC Recognition No.: 5944A-3)

# 2. EUT DESCRIPTION

EUT Type	CAR AVN
FCC Model Name	AV2B0SDAN
IC Model Name	AV2B0SDKN
Power Supply	DC 12 V
Frequency Range	2402 - 2480 MHz (Bluetooth)
Transmit Power	4.10 dBm(2.57 mW)
BT Operating Mode	Nomal, EDR, AFH
Modulation Type	GFSK(Normal), PSK(EDR)
Modulation Technique	FHSS
Number of Channels	79Channels, Minimum 20 Channels(AFH)
Antenna Specification	Manufacturer: AMOTECH Co., Ltd.
	Antenna type: Chip Antenna
	Peak Gain: 3.5 dBi

#### **\* 15.247 Requirements for Bluetooth transmitter**

- This Bluetooth module has been tested by a Bluetooth Qualification Lab, and we confirm the following:
- 1) This system is hopping pseudo-randomly.
- 2) Each frequency is used equally on the average by each transmitter.
- 3) The receiver input bandwidths that match the hopping channel bandwidths of their corresponding transmitters
- 4) The receiver shifts frequencies in synchronization with the transmitted signals.
- 15.247(g): The system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this Section 15.247 should the transmitter be presented with a continuous data (or information) stream.
- 15.247(h): The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

FCC PT.15.247 TEST REPORT		FCC & IC CERTIFICATION REPORT		
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID:	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN



# 3. TEST METHODOLOGY

The measurement procedure described in the American National Standard for Testing Unlicensed Wireless Devices(ANSI C63.10-2009) and FCC Public Notice DA 00-705 dated March 30, 2000 entitled "Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems" were used in the measurement of the **HYUNDAI MOBIS CO., LTD.** 

**CAR AVN FCC ID: TQ8-AV2B0SDAN** 

# 3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

#### 3.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

#### 3.3 GENERAL TEST PROCEDURES

# **Conducted Emissions**

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2 of ANSI C63.10. (Version :2009) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

#### **Radiated Emissions**

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical according to the requirements in Section 6.3 of ANSI C63.10. (Version: 2009)

# 3.4 DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Channel low, mid and high with highest data rate (worst case) is chosen for full testing.

FCC PT.15.247 TEST REPORT		FCC & IC CERTIFICATION REPORT			
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID:	IC:	
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN	



# 4. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipments, which is traceable to recognized national standards.

# 5. FACILITIES AND ACCREDITATIONS

#### 5.1 FACILITIES

The SAC(Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at the 105-1, Jangam-ri, Majang-Myeon, Icheon-si, Kyunggi-Do, 467-811, Korea. The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2003) and CISPR Publication 22. Detailed description of test facility was submitted to the Commission and accepted dated March 02, 2011 (Registration Number: 90661)

# **5.2 EQUIPMENT**

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements. Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

# 6. ANTENNA REQUIREMENTS

#### According to FCC 47 CFR §15.203:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

FCC PT.15.247 TEST REPORT		FCC & IC CERTIFICATION REPORT			
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID :	IC:	
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN	

<sup>\*</sup> The antennas of this E.U.T are permanently attached.

<sup>\*</sup>The E.U.T Complies with the requirement of §15.203



# 7. SUMMARY OF TEST RESULTS

Test Description	IC Part Section(s)	FCC Part Section(s)	Test Limit	Test Condition	Test Result
20 dB Bandwidth	RSS-210, A8.1(a)	§15.247(a)(1)(ii) or (iii)	NA		PASS
Occupied Bandwidth	RSS-210, A1.1.3	NA	NA		PASS
Conducted Maximum Peak Output Power	RSS-210, A8.4(2)	§15.247(b)(1)	< 1 Watts		PASS
Carrier Frequency Separation	RSS-210, A8.1(b)	§15.247(a)(1)	>25 kHz or >2/3 of the 20dB BW		PASS
Number of Hopping Frequencies	RSS-210, A8.1(d)	§15.247(a)(1)(iii)	>15	CONDUCTED	PASS
Time of Occupancy	RSS-210, A8.1(d)	§15.247(a)(1)(iii)	<400 ms		PASS
Conducted Spurious Emissions	RSS-210, A 8.5 RSS- GEN, Section 7.2.3	§15.247(d)	< 20 dB for all out-of band emissions		PASS
Band Edge(Out of Band Emissions)	RSS-210, A 8.5	§15.247(d)	< 20 dB for all out-of band emissions		PASS
AC Power line Conducted Emissions	RSS-GEN, Section 7.2.2	§15.207(a)	cf. Section 8.7		PASS
Radiated Spurious Emissions	RSS-210, A2.9, A 8.5	§15.247(d), 15.205, 15.209	cf. Section 8.6.2		PASS
Radiated Restricted  Band Edge	RSS-210, A2.9, A 8.5	§15.247(d), 15.205, 15.209	cf. Section 8.6.4	RADIATED	PASS
Receiver Spurious Emissions	RSS-GEN, Section 7.2.3	§15.109	cf. Section 8.6.3		PASS

FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID:	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN



# 8. FCC PART 15.247 REQUIREMENTS


#### **8.1 PEAK POWER**

#### LIMIT

The maximum peak output power of the intentional radiator shall not exceed the following:

- 1. For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt.
- 2. The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi.

# **Test Configuration**



#### **TEST PROCEDURE**

The transmitter output is connected to the Spectrum Analyzer. The Spectrum Analyzer is set to the peak detector mode. This test is performed with hopping off.

- 1. Span = 2 MHz (GFSK) / 5 MHz (8DPSK)
- 2. RBW = 1 MHz (GFSK) / 3 MHz (8DPSK)
- 3. VBW = 1 MHz (GFSK) / 3 MHz (8DPSK)
- 4. Sweep = auto
- 5. Packet type= DH5 (GFSK) / 3-DH5 (8DPSK)

#### **SAMPLE CALCULATION**

Output Power = Spectrum Reading Power + Power Splitter loss + Cable loss(2 ea) = 10 dBm + 6 dB + 1.5 dB = 17.5 dBm

#### Note:

- 1. Spectrum reading values are not plot data. The power results in plot is already including the actual values of loss for the splitter and cable combination.
- 2. Spectrum offset = Power Splitter loss + Cable loss
- 3. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB. So, 7.6 dB is offset for peak power measurement.

FCC PT.15.247 TEST REPORT		FCC & IC CERTIFICATION REPORT			
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID :	IC:	
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN	



# **TEST RESULTS**

No non-compliance noted

# **Test Data**


Channel	Frequency	Output Po	wer(GFSK)	Output Pov	ver(8DPSK)	Limit	Booult
Channel	(MHz)	(dBm)	(mW)	(dBm)	(mW)	(W)	Result
Low	2402	2.01	1.59	4.03	2.53		PASS
Mid	2441	2.20	1.66	4.10	2.57	1	PASS
High	2480	2.25	1.68	3.85	2.43		PASS



Test Plots (GFSK) Peak Power (Low-CH)



Test Plots (GFSK)
Peak Power (Mid-CH)




FCC PT.15.247 TEST REPORT		FCC & IC CERTIFICATION REPORT			
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID :	IC:	
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN	



Test Plots (GFSK) Peak Power (High-CH)




Test Plots (8DPSK)
Peak Power (Low-CH)




FCC PT.15.247 TEST REPORT		FCC & IC CERTIFICATION REPORT			
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID :	IC:	
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN	



Test Plots (8DPSK)
Peak Power (Mid-CH)



Test Plots (8DPSK)



FCC PT.15.247 TEST REPORT		FCC & IC CERTIFICATION REPORT			
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID:	IC:	
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN	




#### **8.2 BAND EDGES**

#### **LIMIT**

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

Limit: 20 dBc

# **Test Configuration**



#### **TEST PROCEDURE**

This test is performed with hopping off and hopping on.

The spectrum analyzer is set to:

- 1. Span = 8 MHz / 10 MHz(with hopping)
- 2. RBW = 100 kHz
- 3. VBW = 300 kHz
- 4. Sweep = auto
- 5. Detector Mode = Peak

# **TEST RESULTS**

See attached.

#### Note:

- 1. The results in plot is already including the actual values of loss for the splitter and cable combination.
- 2. Spectrum offset = Power Splitter loss + Cable loss
- 3. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB. So, 7.6 dB is offset for band edge measurement.

FCC PT.15.247 TEST REPORT		FCC & IC CERTIFICATION REPORT			
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID:	IC:	
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN	



# **Test Data**

# - Without hopping

	Eroguenov	GFSK	8DPSK	Limit	Mai	rgin	
Channel	Frequency (MHz)	(dB)	(dB)	(dBc)	GFSK	8DPSK	Result
	(141112)	(45)	(dD)	(abo)	(dBc)	(dBc)	
Low	2402	38.45	40.04	20	18.45	20.04	PASS
High	2480	58.42	56.14	20	38.42	36.14	PASS

# - With hopping

	GFSK 8DPSK		8DPSK	Limit	Margin		
Channel	Frequency (MHz)	(dB)	(dB)	(dBc)	GFSK (dBc)	8DPSK (dBc)	Result
Low	2402	39.57	42.18	20	19.57	22.18	PASS
High	2480	58.50	56.73	20	38.50	36.73	PASS


FCC PT.15.247 TEST REPORT		FCC & IC CERTIFICATION REPORT			
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID:	IC:	
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN	



Test Plots without hopping (GFSK) Band Edges (Low-CH)




Test Plots without hopping (GFSK) Band Edges (High-CH)



FCC PT.15.247 TEST REPORT		FCC & IC CERTIFICATION REPORT			
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID:	IC:	
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN	



Test Plots without hopping (8DPSK) Band Edges (Low-CH)




Test Plots without hopping (8DPSK) Band Edges (High-CH)




FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID:	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN



Test Plots with hopping (GFSK) Band Edges (Low-CH)



Test Plots with hopping (GFSK) Band Edges (High-CH)




FCC PT.15.247 TEST REPORT		FCC & IC CERTIFICATION REPORT			
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID :	IC:	
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN	



Test Plots with hopping (8DPSK) Band Edges (Low-CH)



Test Plots with hopping (8DPSK) Band Edges (High-CH)



FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID:	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN




# 8.3 FREQUENCY SEPARATION / OCCUPIED BANDWIDTH (99% BW)

#### **LIMIT**

According to §15.247(a)(1), Frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

# **Test Configuration**



#### **TEST PROCEDURE**

The Channel Separation test is performed with hopping on. And the 20 dB Bandwidth test is performed with hopping off.

The spectrum analyzer is set to:

- 1. Span = 3 MHz
- 2. RBW = 30 kHz
- 3. VBW = 100 kHz
- 4. Sweep = auto

The trace was allowed to stabilize. The marker-delta function was used to determine the separation between the peaks of the adjacent channels.

#### **TEST RESULTS**

No non-compliance noted

#### **Test Data**

Channel Separation (kHz)		20d	20dB Bandwidth (kHz)			Result
GFSK	8DPSK	Channel	GFSK	8DPSK	(kHz)	
		Low CH	933.7	1291.0	>25 or	
820	990	Middle CH	935.3	1283.0	>2/3 of the	Pass
		High CH	936.3	1264.0	20dB BW	


# Occupied Bandwidth (99% BW)

99% BW (kHz)					
Channel GFSK 8DPSK					
Low CH	854.9	1212.7			
Middle CH	852.4	1197.3			
High CH	858.3	1183.6			


FCC PT.15.247 TEST REPORT		FCC & IC CERTIFICATION REPORT		
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID:	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN



# Test Plots (GFSK) Channel Separation



# Test Plots (8DPSK) Channel Separation




FCC PT.15.247 TEST REPORT		FCC & IC CERTIFICATION REPORT		
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID:	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN



#### Test Plots (GFSK)

20 dB Bandwidth & Occupied Bandwidth (Low-CH)



# Test Plots (GFSK)

20 dB Bandwidth & Occupied Bandwidth (Mid-CH)




FCC PT.15.247 TEST REPORT		FCC & IC CERTIFICATION REPORT		
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID :	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN




#### Test Plots (GFSK)

20 dB Bandwidth & Occupied Bandwidth (High-CH)



#### Test Plots (8DPSK)

20 dB Bandwidth & Occupied Bandwidth (Low-CH)




FCC PT.15.247 TEST REPORT		FCC & IC CERTIFICATION REPORT		
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID :	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN




#### Test Plots (8DPSK)

20 dB Bandwidth & Occupied Bandwidth (Mid-CH)



#### Test Plots (8DPSK)

20 dB Bandwidth & Occupied Bandwidth (High-CH)



FCC PT.15.247 TEST REPORT		FCC & IC CERTIFICATION REPORT		
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID:	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN




# 8.4 NUMBER OF HOPPING FREQUENCY

#### **LIMIT**

According to \$15.247(a)(1)(iii), Frequency hopping systems operating in the 2400 MHz ~ 2483.5 MHz bands shall use at least 15 hopping frequencies.

# **Test Configuration**



# **TEST PROCEDURE**

The Bluetooth frequency hopping function of the EUT was enabled. The spectrum analyzer was set to :

- 1. Span = the frequency band of operation (Start = 2400 MHz, Stop = 2483.5 MHz)
- 2. RBW = 300 kHz
- 3. VBW = 300 kHz
- 4. Sweep = auto

The trace was allowed to stabilize.

# **TEST RESULTS**

No non-compliance noted

# **Test Data**

Result (No. of CH)		1 ::4	Dooule	
GFSK	8DPSK	Limit	Result	
79	79	>15	Pass	


Note: In case of AFH mode, minimum number of hopping channels is 20.

FCC PT.15.247 TEST REPORT		FCC & IC CERTIFICATION REPORT		
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID:	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN




Test Plots (GFSK)

Number of Channels (2.4 GHz - 2.441 GHz)



# Test Plots (GFSK)

Number of Channels (2.441 GHz - 2.4835 GHz)




FCC PT.15.247 TEST REPORT		FCC & IC CERTIFICATION REPORT		
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID:	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN




# Test Plots (8DPSK)

Number of Channels (2.4 GHz - 2.441 GHz)



# Test Plots (8DPSK)

Number of Channels (2.441 GHz - 2.4835 GHz)



FCC PT.15.247 TEST REPORT		FCC & IC CERTIFICATION REPORT		
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID:	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN




# 8.5 TIME OF OCCUPANCY (DWELL TIME)

#### **LIMIT**

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400 MHz ~ 2483.5 MHz bands. The average time of occupancy on any channels shall not greater than 0.4 s within a period 0.4 s multiplied by the number of hopping channels employed.

# **Test Configuration**



#### **TEST PROCEDURE**

This test is performed with hopping off.

EUT was set to transmit the longest packet type (DH5)

- 1. Span = zero span
- 2. RBW = 1 MHz
- 3. VBW = 1 MHz
- 4. Sweep = as necessary to capture the entire dwell time per channel

The marker-delta function was used to determine the dwell time.

#### **TEST RESULTS**

See the table.

# Normal Mode / EDR Mode

**DH 5**(The longest packet type for GFSK)

CH Mid: 2.908 \* (1600/6)/79 \* 31.6 = 310.19 (ms)

**3-DH 5**(The longest packet type for 8DPSK)

CH Mid: 2.908 \* (1600/6)/79 \* 31.6 = 310.19 (ms)

#### **AFH Mode**

**DH 5**(The longest packet type for GFSK)

CH Mid: 2.908 \* (1600/6)/20 \* 8.0 = 310.19 (ms)

**3-DH 5**(The longest packet type for 8DPSK)

CH Mid: 2.908 \* (1600/6)/20 \* 8.0 = 310.19 (ms)

FCC PT.15.247 TEST REPORT		FCC & IC CERTIFICATION REPORT		
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID:	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN




Channel	Pulse Ti	me (ms)	Total of D	well (ms)	Period Time	Limit	Result
Citatille	GFSK	8DPSK	GFSK	8DPSK	(s)	(ms)	Nesuit
Low	2.908	2.917	310.19	311.15	31.6		PASS
Mid	2.908	2.908	310.19	310.19	31.6	400	PASS
High	2.900	2.908	309.33	310.19	31.6		PASS

FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT		www.hct.co.kr	
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID :	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN




Test Plots (GFSK)

Dwell Time (Low-CH)




Test Plots (GFSK)




FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT		www.hct.co.kr	
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID:	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN



Test Plots (GFSK)
Dwell Time (High-CH)




Test Plots (8DPSK)
Dwell Time (Low-CH)




FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID:	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN



Test Plots (8DPSK)
Dwell Time (Mid-CH)



Test Plots (8DPSK)
Dwell Time (High-CH)



FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT		www.hct.co.kr	
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID:	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN




#### 8.6 SPURIOUS EMISSIONS

# 8.6.1 CONDUCTED SPURIOUS EMISSIONS

LIMIT: §15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

# **Test Configuration**



#### **TEST PROCEDURE**

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.

Detector Mode is set to a peak detector Mode.

Measurements are made over the 30 MHz to 26 GHz range with the transmitter set to the lowest, middle, and highest channels.

This test is performed with hopping off.


#### **TEST RESULTS**

No non-compliance noted


FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT		www.hct.co.kr	
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID:	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN



Test Plots (GFSK) - 30 MHz - 1 GHz (RBW:100 kHz, VBW: 300 kHz) Spurious Emission (Low-CH)




Test Plots (GFSK) - 30 MHz - 1 GHz (RBW:100 kHz, VBW: 300 kHz) Spurious Emission (Mid-CH)




FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID:	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN



Test Plots (GFSK) - 30 MHz - 1 GHz (RBW:100 kHz, VBW: 300 kHz) Spurious Emission (High-CH)




Test Plots (8DPSK) - 30 MHz - 1 GHz (RBW:100 kHz, VBW: 300 kHz) Spurious Emission (Low-CH)




FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID:	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN



Test Plots (8DPSK) - 30 MHz - 1 GHz (RBW:100 kHz, VBW: 300 kHz) Spurious Emission (Mid-CH)




Test Plots (8DPSK) - 30 MHz - 1 GHz (RBW:100 kHz, VBW: 300 kHz) Spurious Emission (High-CH)




FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT		www.hct.co.kr	
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID:	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN



Test Plots (GFSK) - 1 GHz - 26 GHz (RBW:1 MHz, VBW: 1 MHz) Spurious Emission (Low-CH)




Test Plots (GFSK) - 1 GHz - 26 GHz (RBW:1 MHz, VBW: 1 MHz) Spurious Emission (Mid-CH)




FCC PT.15.247 TEST REPORT	FCC & IC CERTIFICATION REPORT		www.hct.co.kr	
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID:	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN



Test Plots (GFSK) - 1 GHz - 26 GHz (RBW:1 MHz, VBW: 1 MHz) Spurious Emission (High-CH)




Test Plots (8DPSK) - 1 GHz - 26 GHz (RBW:1 MHz, VBW: 1 MHz) Spurious Emission (Low-CH)




FCC PT.15.247 TEST REPORT		FCC & IC CERTIFICATION REPORT		
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID:	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN



Test Plots (8DPSK) - 1 GHz - 26 GHz (RBW:1 MHz, VBW: 1 MHz) Spurious Emission (Mid-CH)



Test Plots (8DPSK) - 1 GHz - 26 GHz (RBW:1 MHz, VBW: 1 MHz) Spurious Emission (High-CH)



FCC PT.15.247 TEST REPORT		FCC & IC CERTIFICATION REPORT		
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID :	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN



## **8.6.2 RADIATED SPURIOUS EMISSIONS**

# LIMIT: §15.247(d), §15.205, §15.209

1. 20dBc in any 100kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.


Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

FCC PT.15.247 TEST REPORT		FCC & IC CERTIFICATION REPORT		
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID:	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN




# **Test Configuration**

### Below 30 MHz




### 30 MHz - 1 GHz



FCC PT.15.247 TEST REPORT		FCC & IC CERTIFICATION REPORT		
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID:	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN



### **Above 1 GHz**



### **TEST PROCEDURE**

- 1. The EUT is placed on a turntable, which is 0.8 m above ground plane.
- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- 4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 6. Repeat above procedures until the measurements for all frequencies are complete.

TEST REPORT		FCC & IC CERTIFICATION REPORT		www.hct.co.kr		
Test Report No. HCTR1204FR04	Date of Issue: April 05, 2012	EUT Type: CAR AVN	FCC ID : TQ8-AV2B0SDAN	IC: 5074A-AV2B0SDKN		



### **TEST RESULTS**

### 9 kHz - 30MHz

**Operation Mode:** Normal Mode

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	$dB\mu \! V$	dB /m	dB	(H/V)	dB <i>μ</i> V/m	dB <i>μ</i> V/m	dB
No Critical peaks found							

- 1. Measuring frequencies from 9 kHz to the 30MHz.
- 2. The reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
- 3. Distance extrapolation factor = 40 log (specific distance / test distance) (dB)
- 4. Limit line = specific Limits (dBuV) + Distance extrapolation factor
- 5. This test is performed with hopping off.

FCC PT.15.247 TEST REPORT		FCC & IC CERTIFICATION REPORT		
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID:	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN



### **TEST RESULTS**

### Below 1 GHz

Operation Mode: EDR Mode (Channel: 2441)

Frequency	Reading	Ant. Factor	Cable Loss	ANT POL	Total	Limit	Margin
MHz	dBuV	dB/m	dB	(H/V)	dBuV/m	dBuV/m	dB
475.3	16.02	17.24	2.44	V	35.7	46.0	10.3
955.0	12.68	23.70	3.62	Н	40.0	46.0	6.0

- 1. Measuring frequencies from 30 MHz to the 1 GHz.
- 2. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.
- 3. This test is performed with hopping off.

FCC PT.15.247 TEST REPORT		FCC & IC CERTIFICATION REPORT		
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID:	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN



#### **Above 1 GHz**

**Operation Mode:** CH Low(GFSK)

Frequency	Reading	*A.F+CL-AMP GAIN	ANT. POL	Total	Limit	Margin	Detect
[MHz]	dBuV	[dB]	[H/V]	[dBuV/m]	[dBuV/m]	[dB]	Detect
4804	53.78	-0.20	V	53.58	74	20.42	PK
4804	47.19	-0.20	V	46.99	54	7.01	AV
7206	48.20	10.34	V	58.54	74	15.46	PK
7206	35.97	10.34	V	46.31	54	7.69	AV
4804	55.85	-0.20	Н	55.65	74	18.35	PK
4804	50.53	-0.20	Н	50.33	54	3.67	AV
7206	47.91	10.34	Н	58.25	74	15.75	PK
7206	36.14	10.34	Н	46.48	54	7.52	AV

**\*** A·F: ANTENNA FACTOR

C·L: CABLE LOSS

AMP GAIN: AMPLIFIER GAIN

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
- Radiated emissions measured in frequency above 1000 MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4. Total = Reading Value + Antenna Factor + Cable Loss Amp Gain
- 5. Spectrum setting:
  - a. Peak Setting 1 GHz 26 GHz, RBW = 1 MHz, VBW = 1 MHz.
  - b. AV Setting 1 GHz 26 GHz, RBW = 1 MHz, VBW = 1 kHz  $\geq$  1/T Hz, where T = pulse width in seconds.
- 6. We have done Normal Mode and EDR Mode test. Worst case of EUT is Normla Mode.
- 7. This test is performed with hopping off.

FCC PT.15.247 TEST REPORT		FCC & IC CERTIFICATION REPORT		
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID :	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN



**Operation Mode:** CH Mid(GFSK)

Frequency	Reading	※ A.F+CL-AMP GAIN	ANT. POL	Total	Limit	Margin	Detect
[MHz]	dBuV	[dB]	[H/V]	[dBuV/m]	[dBuV/m]	[dB]	Detect
4882	53.32	0.25	V	53.57	74	20.43	PK
4882	46.71	0.25	V	46.96	54	7.04	AV
7323	47.71	10.01	V	57.72	74	16.28	PK
7323	36.05	10.01	V	46.06	54	7.94	AV
4882	54.36	0.25	Н	54.61	74	19.39	PK
4882	49.41	0.25	Н	49.66	54	4.34	AV
7323	48.29	10.01	Н	58.30	74	15.70	PK
7323	35.90	10.01	Н	45.91	54	8.09	AV

\* A·F: ANTENNA FACTOR

C·L: CABLE LOSS

AMP GAIN: AMPLIFIER GAIN

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Radiated emissions measured in frequency above 1000 MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4. Total = Reading Value + Antenna Factor + Cable Loss Amp Gain
- 5. Spectrum setting:
  - a. Peak Setting 1 GHz 26 GHz, RBW = 1 MHz, VBW = 1 MHz.
  - b. AV Setting 1 GHz 26 GHz, RBW = 1 MHz, VBW = 1 kHz  $\geq$  1/T Hz, where T = pulse width in seconds.
- 6. We have done Normal Mode and EDR Mode test. Worst case of EUT is Normla Mode.
- 7. This test is performed with hopping off.

FCC PT.15.247 TEST REPORT		FCC & IC CERTIFICATION REPORT		
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID:	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN



Operation Mode: CH High(GFSK)

Frequency	Reading	※A.F+CL-AMP GAIN	ANT. POL	Total	Limit	Margin	Detect
[MHz]	dBuV	[dB]	[H/V]	[dBuV/m]	[dBuV/m]	[dB]	Detect
4960	52.80	0.75	V	53.55	74	20.45	PK
4960	45.55	0.75	V	46.30	54	7.70	AV
7440	48.35	10.11	V	58.46	74	15.54	PK
7440	35.59	10.11	V	45.70	54	8.30	AV
4960	51.66	0.75	Н	52.41	74	21.59	PK
4960	43.97	0.75	Н	44.72	54	9.28	AV
7440	48.35	10.11	Н	58.46	74	15.54	PK
7440	35.24	10.11	Н	45.35	54	8.65	AV

\* A·F: ANTENNA FACTOR

C-L: CABLE LOSS

AMP GAIN: AMPLIFIER GAIN

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Radiated emissions measured in frequency above 1000 MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4. Total = Reading Value + Antenna Factor + Cable Loss Amp Gain
- 5. Spectrum setting:
  - a. Peak Setting 1 GHz 26 GHz, RBW = 1 MHz, VBW = 1 MHz.
  - b. AV Setting 1 GHz 26 GHz, RBW = 1 MHz, VBW = 1 kHz  $\geq$  1/T Hz, where T = pulse width in seconds.
- 6. We have done Normal Mode and EDR Mode test. Worst case of EUT is Normla Mode.
- 7. This test is performed with hopping off.

FCC PT.15.247 TEST REPORT		FCC & IC CERTIFICATION REPORT		
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID:	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN



### **8.6.3 RECEIVER SPURIOUS EMISSIONS**

FCC Rule(s) §15.109 (see Table Below)

Test Requirements: Emission Level shall not exceed §15.109 limits

Operating conditions: Under normal test conditions

Method of testing: Radiated

F < 1 GHz: RBW: 120 kHz, VBW: 300 kHz (Quasi Peak)

S/A. Settings:

F > 1 GHz: RBW: 1 MHz, VBW: 1 MHz (Peak)

Mode of operation: Receive

Frequency (MHz)	Field Strength (mV/m)	Measurement Distance (m)
30 – 88	100 (40 dBuV)	3
88 - 216	150 (43.5 dBuV))	3
216 – 960	200 (46 dBuV)	3
Above 960	500 (54 dBuV)	3

### Operation Mode: Receive:

30 MHz  $\sim$  1 GHz

Frequency	Reading	Ant. Factor	Cable Loss	ANT POL	Total	Limit	Margin
MHz	dBuV	dB/m	dB	(H/V)	dBuV/m	dBuV/m	dB
437.0	18.26	16.41	2.33	V	37.0	46.0	9.0
935.0	14.03	23.59	3.58	Н	41.2	46.0	4.8

### Above 1 GHz

Frequency	Reading	Ant. Factor	Cable Loss	ANT POL	Total	Limit	Margin
MHz	dBuV	dB/m	dB	(H/V)	dBuV/m	dBuV/m	dB
No Critical peaks found							



#### **8.6.4 RADIATED RESTRICTED BAND EDGES**

## Test Requirements and limit, §15.247(d), §15.205, §15.209

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in section 15.209(a) (See section 15.205(c).

Operation Mode Normal(GFSK)
Operating Frequency 2402 MHz, 2480 MHz
Channel No CH 0, CH 78

Frequency	*Fund. Reading	፠ A.F.+CL	Ant. Pol.	*Fundamental	Delta Value	Duty Cycle Correction	Total	Limit	Margin	Detect
[MHz]	dBuV	[dB]	[H/V]	[dBuV/m]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	Detect
2390.0	59.43	33.86	Η	93.29	40.95	0	52.34	74	21.66	PK
2390.0	59.04	33.86	Н	92.90	40.95	-30.73	21.22	54	32.78	AV
2390.0	63.18	33.86	V	97.04	44.40	0	52.64	74	21.36	PK
2390.0	62.77	33.86	V	96.63	44.40	-30.73	21.50	54	32.50	AV
2483.5	59.08	34.02	Н	93.10	44.09	0	49.01	74	24.99	PK
2483.5	58.56	34.02	Н	92.58	44.09	-30.73	17.76	54	36.24	AV
2483.5	58.08	34.02	V	92.10	42.94	0	49.16	74	24.84	PK
2483.5	57.71	34.02	V	91.73	42.94	-30.73	18.06	54	35.94	AV

\* A·F: ANTENNA FACTOR

C·L: CABLE LOSS

AMP GAIN: AMPLIFIER GAIN

- Total = Fundamental Reading Value + Antenna Factor + Cable Loss Delta Value + Duty Cycle Correction Factor
- 2. Spectrum setting:
  - a. Peak Setting 1 GHz 26 GHz, RBW = 1 MHz, VBW = 1 MHz.
  - b. AV Setting 1 GHz 26 GHz, RBW = 1 MHz, VBW = 1 kHz  $\geq$  1/ $\tau$  Hz, where  $\tau$  = pulse width in seconds.
- 3. Duty Cycle Correction Factor = 20log (Worst Case Dwell Time/ 100ms) dB = -30.73 dB
- 4. Duty Cycle Correction Factor(AFH):
  - a. Time to cycle through all channels=  $\Delta$  t=  $\tau$  [ms] x 20 channels = 58.16 ms, where  $\tau$  = pulse width
  - b. 100 ms/  $\Delta t$  [ms] =  $H \rightarrow \text{Round up to next highest integer}$ , H = 1.719395

FCC PT.15.247 TEST REPORT		FCC & IC CERTIFICATION REPORT		
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID:	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN



- c. Worst Case Dwell Time =  $\tau$  [ms] x H '= 5.0 ms
- d. Duty Cycle Correction(AFH) = 20log (Worst Case Dwell Time/ 100ms) dB = -26.02 dB
- 5. Radiated Restricted Band Edge measures by marker-delta method according to ANSI C63.10(version : 2009)
- 6. We have done Normal Mode and EDR Mode test. Worst case of EUT is Normla Mode.
- 7. This test is performed with hopping off.
- 8. Marker-Delta Method

In making radiated band-edge measurements, there can be a problem obtaining meaningful data because a measurement instrument that is tuned to a band-edge frequency may also capture some in-band signals when using the resolution bandwidth (RBW). In an effort to compensate for this problem, the following technique for determining band-edge compliance shall be used.

- a) Perform an in-band field strength measurement of the fundamental emission using the RBW and detector function specified in 6.3 and 6.4, 6.5, or 6.6, as applicable, and the appropriate regulatory requirements for the frequency being measured. and our Rules for the frequency being measured. For example, for a device operating in the 902-928 MHz band under 47 CFR 15.249, use a 120 kHz RBW with a CISPR QP detector (a peak detector with 100 kHz RBW may alternatively be used). For unlicensed wireless devices operating above 1 GHz, use a 1 MHz RBW, a 1 MHz VBW, and a peak detector as required by 47 CFR 15.35. Repeat the measurement with an average detector (i.e., 1 MHz RBW with 10 Hz VBW). For pulsed emissions, other factors must be included. For example note that radiated measurements of the fundamental emission of a spread spectrum unlicensed wireless device operating under 47 CFR 15.247 are not normally required, but they are necessary in connection with this procedure.
- b) Choose a spectrum analyzer span that encompasses both the peak of the fundamental emission and the band-edge emission under investigation. Set the analyzer RBW to approximately 1% to 5 % of the total span, unless otherwise specified, with a video bandwidth equal to or greater than the RBW. Record the peak levels of the fundamental emission and the relevant band-edge emission (i.e., run several sweeps in peak hold mode). Observe the stored trace and measure the amplitude delta between the peak of the fundamental and the peak of the band-edge emission. This is not an abosolute field strength measurement; it is only a relative measurement to determine the amount by which the emission drops at the band-edge relative to the highest fundamental emission level.
- c) Subtract the delta measured in b) from the field strengths measured in a). The resultant field strengths (CISPR QP, average, or peak, as appropriate) are then used to determine band-edge compliance of the resricted bands, described in 5.9

FCC PT.15.247 TEST REPORT		FCC & IC CERTIFICATION REPORT		
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID:	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN



### 8.7 POWERLINE CONDUCTED EMISSIONS

### **LIMIT**

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolt (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Francisco Ponco (MILE)	Limits (dBμV)				
Frequency Range (MHz)	Quasi-peak	Average			
0.15 to 0.50	66 to 56	56 to 46			
0.50 to 5	56	46			
5 to 30	60	50			

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

### **Test Configuration**

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

### **TEST PROCEDURE**

- 1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
- 2. The EUT is connected via LISN to a test power supply.
- 3. The measurement results are obtained as described below:
- 4. Detectors Quasi Peak and Average Detector.

Note: We don't perform powerline conducted emission test. Because this EUT is used with vehicle.

FCC PT.15.247 TEST REPORT		FCC & IC CERTIFICATION REPORT		
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID:	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN



# 9. LIST OF TEST EQUIPMENT

Manufacturer	Model / Equipment	Calibration Interval	Calibration Due	Serial No.
Rohde & Schwarz	ESH2-Z5/ LISN	Annual	02/03/2013	861741/013
Schwarzbeck	VULB 9168/ TRILOG Antenna Biennial		02/09/2013	200
Rohde & Schwarz	ESI 40 / EMI TEST RECEIVER	Annual	05/26/2012	831564103
Agilent	E4440A/ Spectrum Analyzer	Annual	05/02/2012	US45303008
Agilent	N9020A/ SIGNAL ANALYZER Annual 09/23/2012		09/23/2012	MY51110020
HD	MA240/ Antenna Position Tower	N/A	N/A	556
EMCO	1050/ Turn Table	N/A	N/A	114
HD GmbH	HD 100/ Controller	N/A	N/A	13
HD GmbH	KMS 560/ SlideBar	N/A	N/A	12
Rohde & Schwarz	ESH3-Z2/ PULSE LIMITER	Annual	08/01/2012	375.8810.352
Rohde & Schwarz	SCU-18/ Signal Conditioning Unit	Annual	09/19/2012	10094
MITEQ	AFS44-00102650-42-10P-44-PS/ POWER AMP	Annual	09/23/2012	1532439
Schwarzbeck	BBHA 9120D/ Horn Antenna	Biennial	10/17/2013	937
Schwarzbeck	BBHA9170 / Horn Antenna(15 GHz ~ 40 GHz)	Biennial	10/26/2012	BBHA9170342
Rohde & Schwarz	FSP / Spectrum Analyzer	Annual	02/09/2013	839117/011
Agilent	E4440A / Spectrum Analyzer	Annual	05/02/2012	US45303008
Agilent	E4416A /Power Meter	Annual	11/07/2012	GB41291412
Agilent	E9327A /POWER SENSOR	Annual	05/02/2012	MY4442009
Wainwright Instrument	WHF3.3/18G-10EF / High Pass Filter	Annual	05/02/2012	1
Wainwright Instrument	WRCJ2400/2483.5-2370/2520-60/14SS / Band Reject Filter	Annual	05/02/2012	1
Hewlett Packard	11636B/Power Divider	Annual	11/07/2012	11377
Hewlett Packard	11667B / Power Splitter	Annual	11/04/2012	10126
DIGITAL	EP-3010 /DC POWER SUPPLY	Annual	11/07/2012	3110117
ITECH	IT6720 / DC POWER SUPPLY	Annual	11/07/2012	010002156287001199
TESCOM	TC-3000C / BLUETOOTH TESTER	Annual	11/14/2012	3000C000276
Rohde & Schwarz	CBT / BLUETOOTH TESTER	Annual	05/02/2012	100422
EMCO	6502.LOOP ANTENNA	Biennial	01/11/2014	9009-2536
MITEQ	AMF-6D-001180-35-20P/ POWER AMP	Annual	12/26/2012	990893

FCC PT.15.247 TEST REPORT		www.hct.co.kr		
Test Report No.	Date of Issue:	EUT Type: CAR AVN	FCC ID:	IC:
HCTR1204FR04	April 05, 2012		TQ8-AV2B0SDAN	5074A-AV2B0SDKN