Test of Tehama Wireless TW101

To: FCC 47 CFR Part15.247 & IC RSS-210

Test Report Serial No.: TEHA01-U2 Rev A





Test of Tehama Wireless TW101

To FCC 47 CFR Part15.247 & IC RSS-210

Test Report Serial No.: TEHA01-U2 Rev A

This report supersedes: None

**Manufacturer:** Tehama Wireless

423 Tehama Street

San Francisco California 94103, USA

Product Function: Repeater / Access Point

Copy No: pdf Issue Date: 11th January 2011

## This Test Report is Issued Under the Authority of;

#### MiCOM Labs, Inc.

440 Boulder Court, Suite 200 Pleasanton, CA 94566 USA Phone: +1 (925) 462-0304

Fax: +1 (925) 462-0306 www.micomlabs.com ACCREDITED

TESTING CERTIFICATE #2381.01

MiCOM Labs is an ISO 17025 Accredited Testing Laboratory



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

**Page:** 3 of 98

This page has been left intentionally blank



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

**Page:** 4 of 98

## **TABLE OF CONTENTS**

| AC | CCREDITATION, LISTINGS & RECOGNITION                       | 5  |
|----|--|----|
|    | RECOGNITION  | 6  |
|    | PRODUCT CERTIFICATION                                      | 7  |
| 1. | TEST RESULT CERTIFICATE                                    | 9  |
| 2. | REFERENCES AND MEASUREMENT UNCERTAINTY                     | 10 |
|    | 2.1. Normative References                                  | 10 |
|    | 2.2. Test and Uncertainty Procedures                       | 10 |
| 3. | PRODUCT DETAILS AND TEST CONFIGURATIONS                    | 11 |
|    | 3.1. Technical Details                                     |    |
|    | 3.2. Scope of Test Program                                 |    |
|    | 3.3. Equipment Model(s) and Serial Number(s)               |    |
|    | 3.4. Antenna Details                                       |    |
|    | 3.5. Cabling and I/O Ports                                 |    |
|    | 3.6. Test Configurations                                   |    |
|    | 3.7. Equipment Modifications                               |    |
|    | 3.8. Deviations from the Test Standard                     |    |
|    | 3.9. Subcontracted Testing or Third Party Data             |    |
| 4. | TEST SUMMARY   |    |
| 5. | TEST RESULTS   | 21 |
|    | 5.1. Device Characteristics                                | 21 |
|    | 5.1.1. 20 dB Bandwidth                                     |    |
|    | 5.1.2. Transmitter Channels - Channel Spacing              |    |
|    | 5.1.3. Transmitter Channels                                |    |
|    | 5.1.4. Output Power  |    |
|    | 5.1.5. Maximum Permissible Exposure                        |    |
|    | 5.1.6. Conducted Spurious Emissions Transmitter            |    |
|    | 5.1.8. Radiated Emissions - Transmitter and Receiver       |    |
|    | 5.1.9. Radiated Spurious Emissions – Digital Emissions     |    |
|    | 5.1.10. AC Wireline Conducted Emissions (150 kHz – 30 MHz) |    |
| 6. | PHOTOGRAPHS  |    |
|    | 6.1. General Measurement Test Set-Up                       |    |
|    | 6.2. Radiated Emissions >1 GHz                             |    |
|    | 6.3. Radiated Emissions <1 GHz                             |    |
|    | 6.4. AC Mains Conducted Emissions                          | 96 |
| 7  | TEST FOLLIPMENT DETAILS                                    | 07 |



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 5 of 98

## **ACCREDITATION, LISTINGS & RECOGNITION**

MiCOM Labs, Inc. an accredited laboratory complies with the international standard EN ISO/IEC 17025. The company is accredited by the American Association for Laboratory Accreditation (A2LA) <a href="www.a2la.org">www.a2la.org</a> test laboratory number 2381.01. MiCOM Labs test schedule is available at the following URL; <a href="http://www.a2la.org/scopepdf/2381-01.pdf">http://www.a2la.org/scopepdf/2381-01.pdf</a>



# Accredited Laboratory

A2LA has accredited

## **MICOM LABS**

Pleasanton, CA for technical competence in the field of

#### Electrical Testing

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated 8 January 2009).



Presented this 14th day of April 2010.

President & CEO For the Accreditation Council Certificate Number 2381.01 Valid to November 30, 2011

For the tests or types of tests to which this accreditation applies, please refer to the laboratory's Electrical Scope of Accreditation.



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

**Page:** 6 of 98

## **RECOGNITION**

MiCOM Labs, Inc has widely recognized Electrical testing capabilities. Our international recognition includes Conformity Assessment Body designation by APEC MRA\*\* countries. Our test reports are widely accepted for global type approvals.

| Country      | Recognition Body  | Status | Phase         | Identification<br>No. |
|--------------|---|--------|---------------|-----------------------|
| USA          | Federal Communications Commission (FCC)   | TCB    | -             | Listing #:<br>102167  |
| Canada       | Industry Canada (IC)  | FCB    | APEC<br>MRA 2 | Listing #:<br>4143A   |
| Japan        | VCCI  | -      | -             | No. 2959              |
| Australia    | Australian Communications and Media Authority (ACMA)  | CAB    | APEC<br>MRA 1 |                       |
| Hong<br>Kong | Office of the Telecommunication Authority (OFTA)  | CAB    | APEC<br>MRA 1 |                       |
| Korea        | Ministry of Information and<br>Communication Radio<br>Research Laboratory (RRL)               | CAB    | APEC<br>MRA 1 | US0159                |
| Singapore    | Infocomm Development<br>Authority (IDA)   | CAB    | APEC<br>MRA 1 | 050159                |
| Taiwan       | National Communications Commission (NCC) Bureau of Standards, Metrology and Inspection (BSMI) | CAB    | APEC<br>MRA 1 |                       |
| Vietnam      | Ministry of Communication (MIC)   | CAB    | APEC<br>MRA 1 |                       |

<sup>\*\*</sup>APEC MRA – Asia Pacific Economic Community Mutual Recognition Agreement.

Phase I - recognition for product testing

Phase II – recognition for both product testing and certification

N/A – Not Applicable

Is a recognition agreement under which test lab is accredited to regulatory standards of the APEC member countries.



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 7 of 98

#### **PRODUCT CERTIFICATION**

MiCOM Labs, Inc. is an accredited Product Certification Body per the international standard EN ISO/IEC Guide 65. The company is accredited by the American Association for Laboratory Accreditation (A2LA) <a href="https://www.a2la.org/scopepdf/2381-02.pdf">www.a2la.org/scopepdf/2381-02.pdf</a>



The American Association for Laboratory Accreditation

World Class Accreditation

## Accredited Product Certification Body

A2LA has accredited

## **MICOM LABS**

Pleasanton, CA for technical competence as a

## Product Certification Body

This product certification body is accredited in accordance with the recognized International Standard ISO/IEC Guide 65:1996

General requirements for bodies operating product certification systems. This accreditation demonstrates technical competence for a defined scope and the operation of a quality management system for a Telecommunications Certification Body (TCB) meeting

FCC (U.S.), and IC (Canada) requirements.



Presented this 24th day of June 2010.

President & CEO

President & CEO

Certificate Number 2381.02

Valid to November 30, 2011

For the product certification schemes to which this accreditation applies, please refer to the organization's Product Certification Scope of Accreditation.

#### **United States of America – Telecommunication Certification Body**

TCB Identifier - US0159

**Industry Canada – Certification Body** 

CAB Identifier - US0159



**To:** FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 8 of 98

## **DOCUMENT HISTORY**

|          | Document History              |                 |  |  |  |  |
|----------|-------------------------------|-----------------|--|--|--|--|
| Revision | Date                          | Comments        |  |  |  |  |
| Draft    |                               |                 |  |  |  |  |
| Rev A    | 11 <sup>th</sup> January 2011 | Initial release |  |  |  |  |
|          |                               |                 |  |  |  |  |
|          |                               |                 |  |  |  |  |
|          |                               |                 |  |  |  |  |



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Tested By:

**Page:** 9 of 98

## 1. TEST RESULT CERTIFICATE

Manufacturer: Tehama Wireless

440 Dayldan C

423 Tehama Street

MiCOM Labs, Inc. 440 Boulder Court

San Francisco

Suite 200

California 94103, USA

Pleasanton California, 94566, USA

EUT: Wireless Auto Metering

Telephone: +1 925 462

(WAM) System

+1 925 462 0304

Model: TW101

Fax:

+1 925 462 0306

S/N: E0000116

Test Date(s): 10th - 15th May 2010

Website:

www.micomlabs.com

STANDARD(S)

**TEST RESULTS** 

FCC 47 CFR Part15.247 & IC RSS-210

**EQUIPMENT COMPLIES** 

MiCOM Labs, Inc. tested the equipment mentioned in accordance with the requirements set forth in the above standards. Test results indicate that the equipment tested is capable of demonstrating compliance with the requirements as documented within this report.

#### Notes:

- 1. This document reports conditions under which testing was conducted and the results of testing performed.
- 2. Details of test methods used have been recorded and kept on file by the laboratory.
- 3. Test results apply only to the item(s) tested.

Approved & Released for MiCOM Labs, Inc. by:

ACCREDITED

TESTING CERTIFICATE #2381.01

Graeme Grieve/

Quality/Manager MiCOM Labs,

Gordon Hurst

President & CEO MiCOM Labs, Inc.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 10 of 98

## 2. <u>REFERENCES AND MEASUREMENT UNCERTAINTY</u>

#### 2.1. Normative References

| Ref.   | Publication                | Year                                  | Title  |
|--------|----------------------------|---------------------------------------|--|
| (i)    | FCC 47 CFR Part<br>15.247  | 2007                                  | Code of Federal Regulations  |
| (ii)   | Industry Canada<br>RSS-210 | Issue 7<br>June 2007                  | Low Power License-Exempt Radiocommunication Devices (All Frequency Bands)  |
| (iii)  | Industry Canada<br>RSS-Gen | Issue 2<br>June 2007                  | General Requirements and Information for the Certification of Radiocommunication Equipment.  |
| (iv)   | ANSI C63.4                 | 2003                                  | American National Standards for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz |
| (v)    | CISPR 22/<br>EN 55022      | 1997<br>1998                          | Limits and Methods of Measurements of Radio Disturbance Characteristics of Information Technology Equipment  |
| (vi)   | M 3003                     | Edition 1<br>Dec. 1997                | Expression of Uncertainty and Confidence in Measurements   |
| (vii)  | LAB34                      | Edition 1<br>Aug 2002                 | The expression of uncertainty in EMC Testing   |
| (viii) | ETSI TR 100 028            | 2001                                  | Parts 1 and 2 Electromagnetic compatibility and Radio Spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics             |
| (ix)   | A2LA                       | 14 <sup>th</sup><br>September<br>2005 | Reference to A2LA Accreditation Status – A2LA Advertising Policy   |

## 2.2. Test and Uncertainty Procedures

Conducted and radiated emission measurements were conducted in accordance with American National Standards Institute ANSI C63.4, listed in the Normative References section of this report.

Measurement uncertainty figures are calculated in accordance with ETSI TR 100 028 Parts 1 and 2.

Measurement uncertainties stated are based on a standard uncertainty multiplied by a coverage factor k = 2, providing a level of confidence of approximately 95 % in accordance with UKAS document M 3003 listed in the Normative References section of this report.



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 11 of 98

## 3. PRODUCT DETAILS AND TEST CONFIGURATIONS

#### 3.1. Technical Details

| Details                          | Description                                    |
|----------------------------------|--|
| Purpose:                         | Test of the Tehama Wireless TW101 to FCC Part  |
|                                  | 15.247 and Industry Canada RSS-210 regulations |
| Applicant:                       | As Manufacturer                                |
| Manufacturer:                    | Tehama Wireless                                |
|                                  | 423 Tehama Street                              |
|                                  | San Francisco                                  |
|                                  | California 94103, USA                          |
| Laboratory performing the tests: | MiCOM Labs, Inc.                               |
|                                  | 440 Boulder Court, Suite 200                   |
|                                  | Pleasanton, California 94566 USA               |
| Test report reference number:    | TEHA01-U2 Rev A                                |
| Standard(s) applied:             | FCC 47 CFR Part15.247 & IC RSS-210             |
| Date EUT received:               | 10 <sup>th</sup> May 2010                      |
| Dates of test (from - to):       | 10th - 15th May 2010                           |
| No of Units Tested:              | Two (2):                                       |
|                                  | 1 Unit – FCC Test Code                         |
|                                  | 1 Unit – With Hopping enabled                  |
| Type of Equipment:               | 915 MHz RFID Reader                            |
| Manufacturers Trade Name:        | Tehama Wireless                                |
| Model:                           | TW101  |
| Location for use:                |  |
| Declared Frequency Range(s):     | 902 - 928 MHz                                  |
| Type of Modulation:              | FSK  |
| Declared Nominal Output Power:   | 28dBm (+1dB /- 2dB)                            |
| EUT Modes of Operation:          | FHSS   |
| Transmit/Receive Operation:      | Transceiver, Simplex                           |
| Rated Input Voltage and Current: | 5 VDC w/ Battery                               |
| Operating Temperature Range:     | 0 to +50 C                                     |
| Microprocessor(s) Model:         | Atmel AVR Micro (8MHz internal LC oscillator)  |
| Clock/Oscillator(s):             | 8 MHz, 2 MHz, 12.8 MHz, 32.768 kHz             |
| Frequency Stability:             | ±20ppm   |
| EUT Dimensions:                  | 1.8" x 3.2" x 0.8"                             |
| EUT Weight :                     | 3 oz   |
| Primary function of equipment:   | Repeater / Access Point                        |



To: FCC 47 CFR Part15.247 & IC RSS-210


Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 12 of 98

## 3.2. Scope of Test Program

The scope of the test program was to test the Tehama Wireless TW101 in the frequency ranges 902 - 928 MHz against FCC 47 CFR Part 15.247 and Industry Canada RSS-210 specifications for radiated and conducted emissions for intentional radiators.

TW101 PCB Top






To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 13 of 98

#### **TW101 PCB Underside**





**To:** FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 14 of 98

**Power Supply** 





To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 15 of 98

**Power Supply Labeling** 





To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

**Page:** 16 of 98

## 3.3. Equipment Model(s) and Serial Number(s)

| Type<br>(EUT/<br>Support) | Equipment Description (Including Brand Name)                                     | Mfr                | Model No. | Serial No.                              |
|---------------------------|--|--------------------|-----------|---|
| EUT                       | TW101 with FCC test code   | Tehama<br>Wireless | TW101     | E0000116                                |
| EUT                       | 5V 1A Class II Power Supply  | CUI Inc            | EPS050100 | n/a                                     |
| Support                   | Laboratory DC Power Supply   | Hewlett<br>Packard | 6274B     | 2713A-09023                             |
| Support                   | Dell Inspiron 4150 Laptop –<br>Hyperterminal control over EUT<br>(FCC test code) | Dell               | PP01L     | CN-04P449-<br>48643-2CN-9629<br>Rev Ao2 |
| Support                   | USB to serial converter  | Tehama<br>Wireless | N/A       | N/A                                     |

#### 3.4. Antenna Details

Integral PCB Whip Antenna; Gain = 2.15 dBi



## 3.5. Cabling and I/O Ports

Number and type of I/O ports

- RF Port (915 MHz)
- Battery Terminals (1 x AA type)
- Serial Port (3 pin) Local Maintenance Terminal
- DC Power Port



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

**Page:** 17 of 98

## 3.6. Test Configurations

Test configurations:

EUT was set to 100% duty cycle by FCC Test Code for testing purposes.

## **Frequency Bands:**

| Start<br>Freq.<br>(MHz) | Stop<br>Freq.<br>(MHz) | Rated<br>Output<br>Power<br>(Watts) | Frequency<br>Tolerence<br>(p.p.m.) | 20dB<br>BW<br>(KHz) | Emission<br>Designator | Microprocessor |
|-------------------------|------------------------|-------------------------------------|------------------------------------|---------------------|------------------------|----------------|
| 903                     | 926                    | 0.689                               | 20                                 | 304K                | 304KF1D                | ATMega 644     |
| 903                     | 926                    | 0.723                               | 20                                 | 133K                | 127KF1D                | ATMega 644     |
| 903                     | 913.325                | 0.723                               | 20                                 | 133K                | 127KF1D                | ATMega 644     |
| 914.9                   | 926                    | 0.723                               | 20                                 | 133K                | 127KF1D                | ATMega 644     |

| Operating Channel | Frequencies<br>(MHz) | Data Rate   | Deviation | Channel<br>Spacing |
|-------------------|----------------------|-------------|-----------|--------------------|
| 0                 | 903.0                | 25 Kbits/S  | 33 kHz    | 350 kHz            |
| 31                | 914.9                | 25 Kbits/S  | 33 kHz    | 350 kHz            |
| 59                | 926.0                | 25 Kbits/S  | 33 kHz    | 350 kHz            |
| 0                 | 903.0                | 100 Kbits/S | 100 kHz   | 350 kHz            |
| 31                | 914.9                | 100 Kbits/S | 100 kHz   | 350 kHz            |
| 59                | 926.0                | 100 Kbits/S | 100 kHz   | 350 kHz            |
| 0                 | 903.0                | 25 Kbits/S  | 33 kHz    | 175 kHz            |
| 31                | 908.425              | 25 Kbits/S  | 33 kHz    | 175 kHz            |
| 59                | 913.325              | 25 Kbits/S  | 33 kHz    | 175 kHz            |
| 0                 | 914.775              | 25 Kbits/S  | 33 kHz    | 175 kHz            |
| 31                | 921.1                | 25 Kbits/S  | 33 kHz    | 175 kHz            |
| 59                | 926.0                | 25 Kbits/S  | 33 kHz    | 175 kHz            |

## 3.7. Equipment Modifications

The following modifications were required to bring the equipment into compliance:

1. NONE



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

**Page:** 18 of 98

#### 3.8. Deviations from the Test Standard

The following deviations from the test standard were required in order to complete the test program:

1. NONE

## 3.9. Subcontracted Testing or Third Party Data

The following tests were performed by a MiCOM Labs approved test facility;-

1. NONE



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 19 of 98

## 4. TEST SUMMARY

#### **List of Measurements**

The following table represents the list of measurements required under the FCC CFR47 Part 15.247, Industry Canada RSS-210 and Industry Canada RSS-Gen.

| Section(s)                  | Test Items                         | Description                               | Condition | Result   | Test<br>Report<br>Section |
|-----------------------------|------------------------------------|---|-----------|----------|---------------------------|
| <b>15.247(a)(1)</b><br>A8.1 | 20 dB BW                           | 20 dB BW                                  | Conducted | Complies | 5.1.1                     |
| 15.247(a)(1)<br>A8.1        | Transmitter<br>Channels            | Channel Spacing                           | Conducted | Complies | 5.1.2                     |
| 15.247(a)(1)<br>A8.1        | Transmitter<br>Channels            | Number of<br>Channels                     | Conducted | Complies | 5.1.3.1                   |
|                             |                                    | Channel Occupancy                         | Conducted | Complies | 5.1.3.2                   |
| 15.247(b)(2)<br>A8.4        | Output Power                       | Transmit Power                            | Conducted | Complies | 5.1.4                     |
| 15.247(i)<br>5.5            | Maximum<br>Permissible<br>Exposure | Exposure to radio frequency energy levels | Conducted | Complies | 5.1.5                     |
| 15.247(d)<br>A8.5           | Conducted<br>Spurious<br>Emissions | Band Edge                                 | Conducted | Complies | 5.1.6                     |
|                             |                                    | Spurious Emissions<br>Transmitter         | Conducted | Complies |                           |
| §7.2.3                      |                                    | (1 to 10 GHz) Standby                     | Conducted | Complies | 5.1.7                     |



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 20 of 98

#### **List of Measurements**

The following table represents the list of measurements required under the FCC CFR47 Part 15.247, Industry Canada RSS-210 and Industry Canada RSS-Gen.

| Section(s)   | Test Items                                    | Description  | Condition | Result   | Test<br>Report<br>Section     |
|--|---|--|-----------|----------|-------------------------------|
| 15.247(d)<br>15.205<br>15.209<br>A8.5<br>2.2<br>2.6<br>4.9 | Radiated Emissions - Transmitter and Receiver | Transmitter Peak Emissions Radiated Spurious Emissions Band Edge Emissions | Radiated  | Complies | 5.1.8.1<br>5.1.8.2<br>5.1.8.3 |
| 4.10   |   | Receiver   | Radiated  | Complies | 5.1.8.4                       |
| 15.247(d)<br>15.205<br>15.209<br>A8.5<br>2.2<br>2.6        | Radiated Emissions - Digital Emissions        |  | Radiated  | Complies | 5.1.9                         |
| 15.207<br>7.2.2  | Conducted                                     | AC Wireline<br>Conducted<br>Emissions                                      | Conducted | N/A      | 5.1.10                        |

Note 1: Test results reported in this document relate only to the items tested

Note 2: The required tests demonstrated compliance as per client declaration of test configuration, monitoring methodology and associated pass/fail criteria

Note 3: Section 3.7 - Equipment Modifications highlights the equipment modifications that were required to bring the product into compliance with the above test matrix



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 21 of 98

## 5. TEST RESULTS

#### 5.1. Device Characteristics


#### 5.1.1. 20 dB Bandwidth

FCC, Part 15 Subpart C §15.247(a)(1) Industry Canada RSS-210 §A8.1

#### **Test Procedure**

The 20 dB bandwidth is measured with a spectrum analyzer connected to the antenna terminal, while the EUT is operating in transmission mode at the appropriate center frequency and modulation.

#### **Test Measurement Set up**



Measurement set up for 20 dB bandwidth test



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 22 of 98

#### Test Results for 20 dB Bandwidth

Ambient conditions.

Temperature: 17 to 23 °C Relative humidity: 31 to 57 % Pressure: 999 to 1012 mbar

Testing was performed on all data rates available on the EUT.

#### TABLE OF RESULTS: 33kHz Deviation; 25 Kbits/S

| Channel<br># | Center Frequency<br>(MHz) | 20 dB Bandwidth<br>(kHz) | Specification (kHz) |
|--------------|---------------------------|--------------------------|---------------------|
| 0            | 903.00                    | 126.002                  |                     |
| 31           | 914.90                    | 126.253                  | <500                |
| 59           | 926.00                    | 126.503                  |                     |

TABLE OF RESULTS: 100kHz Deviation; 100 Kbits/S

| Channel<br># | Center Frequency<br>(MHz) | 20 dB Bandwidth<br>(kHz) | Specification (kHz) |
|--------------|---------------------------|--------------------------|---------------------|
| 0            | 903.00                    | 302.104                  |                     |
| 31           | 914.90                    | 301.353                  | <500                |
| 59           | 926.00                    | 303.607                  |                     |




To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 23 of 98

#### 5.1.1.1. 33kHz Deviation Test Results:

#### CH 0 903.00 MHz 20 dB Bandwidth



Date: 12.MAY.2010 15:10:08




To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 24 of 98

#### CH 31 914.90 MHz 20 dB Bandwidth






To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 25 of 98

#### CH 59 926.00 MHz 20 dB Bandwidth



Date: 12.MAY.2010 15:22:45




To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 26 of 98

#### 5.1.1.2. 100kHz Deviation Test Results:

#### CH 0 903.00 MHz 20 dB Bandwidth



Date: 12.MAY.2010 15:07:04




To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 27 of 98

#### CH 31 914.90 MHz 20 dB Bandwidth






To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 28 of 98

#### CH 59 926.00 MHz 20 dB Bandwidth



Date: 12.MAY.2010 15:20:26



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 29 of 98

#### **Specification**

#### Limits

## FCC §15.247 (a)(1) Industry Canada RSS-210 §8.1

For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

#### **Laboratory Measurement Uncertainty for Spectrum Measurement**

| Measurement uncertainty | ±2.81 dB |
|-------------------------|----------|
|-------------------------|----------|

#### **Traceability**

| Method                               | Test Equipment Used                            |
|--------------------------------------|--|
| Measurements were made per work      | 0158, 0193, 0252, 0313, 0314, 0070, 0116, 0117 |
| instruction WI-03 'Measurement of RF |  |
| Spectrum Mask'                       |  |



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 30 of 98


#### 5.1.2. <u>Transmitter Channels - Channel Spacing</u>

FCC, Part 15 Subpart C §15.247(a)(1) Industry Canada RSS-210 §8.1(2)

#### **Test Procedure**

The channel spacing is measured with a spectrum analyzer connected to the antenna terminal, while the EUT is operating in transmission mode at the appropriate center frequency and modulation.

#### **Test Measurement Set up**



Measurement set up for Channel Spacing Test



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 31 of 98

Ambient conditions.

Temperature: 17 to 23 °C Relative humidity: 31 to 57 % Pressure: 999 to 1012 mbar

#### TABLE OF RESULTS

| Channel(s)          | Channel Spacing<br>(KHz) | Specification                        |
|---------------------|--------------------------|--------------------------------------|
| 36-37 (33kHz Dev.)  | 350.2004                 | Greater than maximum 20 dB Bandwidth |
| 36-37 (100kHz Dev.) | 350.2004                 | Greater than maximum 20 dB Bandwidth |
| 36-37 (33kHz Dev.)  | 175.51                   | Greater than maximum 20 dB Bandwidth |

Maximum 20 dB bandwidth (100kHz) = 303.607 kHz

Maximum 20 dB bandwidth (33kHz) = 126.503 kHz




To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 32 of 98

## Channel Spacing for CH 36 - CH 37; 30 kHz Deviation



Date: 12.MAY.2010 15:36:52




To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 33 of 98

## Channel Spacing for CH 36 - CH 37; 100 kHz Deviation



Date: 12.MAY.2010 15:40:04




To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 34 of 98

## Channel Spacing for CH 36 - CH 37; 30 kHz Deviation; 175kHz Channel Separation



Date: 1.JAN.1997 00:38:32



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 35 of 98

## **Specification for Channel Spacing**

#### Limits

FCC §15.247 (a)(1)

Industry Canada RSS-210 §A8.1(2)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

#### **Laboratory Uncertainty for Frequency Measurements**

| Measurement uncertainty | ±0.86ppm |
|-------------------------|----------|

#### **Traceability**

| Method                                    | Test Equipment Used                 |
|---|-------------------------------------|
| Measurements were made per work           | 0078, 0134, 0158, 0184, 0193, 0250, |
| instruction WI-02 'Frequency Measurement" | 0252 0310, 0312.                    |



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

**Page:** 36 of 98

## 5.1.3. <u>Transmitter Channels</u>


#### 5.1.3.1. Number of Channels

FCC, Part 15 Subpart C §15.247(a)(1) Industry Canada RSS-210 §A8.1

#### **Test Procedure**

The number of channels and channel occupancy is measured with a spectrum analyzer connected to the antenna terminal, while the EUT is operating in transmission mode at the appropriate center frequency and modulation.

#### **Test Measurement Set up**



Test set up to measure the number of channels and channel occupancy



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 37 of 98


Ambient conditions.

Temperature: 17 to 23 °C Relative humidity: 31 to 57 % Pressure: 999 to 1012 mbar

#### TABLE OF RESULTS

| Number of Channels | 20 dB Bandwidth | Specification                  |
|--------------------|-----------------|--------------------------------|
| 60                 | < 250 kHz       | Minimum of 50 hopping channels |
| 60                 | > 250 kHz       | Minimum of 25 hopping channels |

#### NUMBER OF TRANSMISSION CHANNELS



Date: 12.MAY.2010 10:09:16



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 38 of 98

# 5.1.3.2. Channel Occupancy

FCC, Part 15 Subpart C §15.247(a)(1) Industry Canada RSS-210 §A8.1

Ambient conditions.

Temperature: 17 to 23 °C Relative humidity: 31 to 57 % Pressure: 999 to 1012 mbar

#### **Channel Dwell Time**

# TABLE OF RESULTS

| Channel # | Center Frequency<br>(MHz) | Channel Dwell Time (single channel) (mSecs) |
|-----------|---------------------------|---|
| 39        | 919.0                     | 254.91                                      |




To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 39 of 98

### **CHANNEL DWELL TIME CH 39 919MHZ**



Date: 15.MAY.2010 00:54:16



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 40 of 98

### **Channel Occupancy**

#### TABLE OF RESULTS

| Channel<br># | Center<br>Frequency<br>(MHz) | 20dB<br>Bandwidth<br>(kHz) | Channel<br>Occupancy<br>Limit<br>(mSeconds) | Channel<br>Occupancy<br>Period<br>(Seconds) | Channel<br>Occupancy<br>Limit<br>(mSeconds) |
|--------------|------------------------------|----------------------------|---|---|---|
| 39           | 919                          | 303.607                    | 400   | 10  | 254.91                                      |
| 39           | 919                          | 126.503                    | 400   | 20  | 254.91                                      |

Note: Channel repeats after minimum 27.05 seconds

Note: Device test code was set-up to provide the maximum dwell time supported by the EUT hardware. This mode was chosen since EUT only transmits on each channel a maximum of one (1) time during each 10s or 20s period specified in FCC Part 15.247(a)(1)(i). Maximum dwell times will vary by data rate and channel spacing, but all are within compliance based on hardware limitation of the device.




To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 41 of 98

# **Channel Occupancy 919 MHz**



Date: 31.DEC.1996 23:40:12



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 42 of 98

# Specification for Number of Channels and Channel Occupancy Limits

# FCC, Part 15 Subpart C §15.247(a)(1) Industry Canada RSS-210 §A8.1

For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

### **Laboratory Uncertainty for Frequency Measurements**

| Measurement uncertainty | ±0.86ppm |
|-------------------------|----------|
|-------------------------|----------|

#### **Traceability**

| Method                                    | Test Equipment Used                 |
|---|-------------------------------------|
| Measurements were made per work           | 0078, 0134, 0158, 0184, 0193, 0250, |
| instruction WI-02 'Frequency Measurement" | 0252 0310, 0312.                    |



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 43 of 98


# 5.1.4. Output Power

FCC, Part 15 Subpart C §15.247(b)(2) Industry Canada RSS-210 §A8.4

#### **Test Procedure**

The transmitter terminal of EUT was set for CW (continuous wave) operation and connected to the input of the power meter which was calibrated to measure power. The value of measured power including antenna cable loss was reported.

### **Test Measurement Set up**



Measurement set up for Transmitter Output Power



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 44 of 98

# **Measurement Results for Output Power**

Ambient conditions.

Temperature: 17 to 23 °C Relative humidity: 31 to 57 % Pressure: 999 to 1012 mbar

#### TABLE OF RESULTS: 33 kHz Deviation

| Channel # | Center Frequency (MHz) | Power<br>(dBm) |
|-----------|------------------------|----------------|
| 0         | 903.00                 | +28.40         |
| 31        | 914.90                 | +28.55         |
| 59        | 926.00                 | +28.59         |

### TABLE OF RESULTS: 100 kHz Deviation

| Channel # | Center Frequency (MHz) | Power<br>(dBm) |
|-----------|------------------------|----------------|
| 0         | 903.00                 | +28.12         |
| 31        | 914.90                 | +28.32         |
| 59        | 926.00                 | +28.38         |



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 45 of 98

### **Specification**

#### Limits

FCC, Part 15 Subpart C §15.247 (b)(2) The maximum output power of the intentional radiator shall not exceed the following:

(2) For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels, as permitted under paragraph (a)(1)(i) of this section.

#### Industry Canada RSS-210 §A8.4

For frequency hopping systems operating in the 902 - 928 MHz band, the maximum peak conducted power output power is not to succeed 1.0 W if the hopset uses 50 or more hopping channels and 0.25 W if the hopset uses less than 50 hopping channels.

### **Laboratory Measurement Uncertainty for Power Measurements**

| Measurement uncertainty | ±1.33 dB |
|-------------------------|----------|
|-------------------------|----------|

#### **Traceability**

| Method  | Test Equipment Used                            |
|---|--|
| Measurements were made per work instruction WI-01 'Measuring RF Output Power' | 0158, 0193, 0252, 0313, 0314, 0070, 0116, 0117 |



**To:** FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

**Page:** 46 of 98

### 5.1.5. <u>Maximum Permissible Exposure</u>

FCC, Part 15 Subpart C §15.247(i) Industry Canada RSS-Gen §5.5

### **Calculations for Maximum Permissible Exposure Levels**

Power Density = Pd (mW/cm<sup>2</sup>) = EIRP/ $(4\pi d^2)$ 

EIRP = P \* G

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

Numeric Gain =  $10 ^ (G (dBi)/10)$ 

Because the EUT belongs to the General Population/Uncontrolled Exposure the limit of power density is 1.0 mW/cm²

| Freq. Band       | Antenna Gain | Peak Output<br>Power | Antenna Gain | EIRP    | Distance @<br>1mW/cm2 | Minimum<br>Separation<br>Distance |
|------------------|--------------|----------------------|--------------|---------|-----------------------|-----------------------------------|
| (MHz)            | (dBi)        | (dBm)                | (numeric)    | (mW)    | Limit(cm)             | (cm)                              |
| 2400 -<br>2483.5 | 2.15         | 28.59                | 1.6405898    | 1185.77 | 9.72                  | 20                                |

\*Note: for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

#### **Specification**

#### **Maximum Permissible Exposure Limits**

§15.247(i) Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency levels in excess of the Commission's guidelines.

FCC §1.1310 Limit = 1mW / cm<sup>2</sup> from 1.310 Table 1

RSS-Gen §5.5 Before equipment certification is granted, the applicable requirements of RSS-102 shall be met.

#### **Laboratory Measurement Uncertainty for Power Measurements**

| , | Measurement uncertainty | ±1.33 dB |
|---|-------------------------|----------|
|---|-------------------------|----------|



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 47 of 98

# 5.1.6. Conducted Spurious Emissions Transmitter

FCC, Part 15 Subpart C §15.247(d) Industry Canada RSS-210 §A8.5

#### **Test Procedure**

Conducted emissions were measured at a limit of 20 dB below the highest in-band spectral density measured with a spectrum analyzer connected to the antenna terminal. Emissions at the band edge were measured and recorded. Measurements were made while EUT was operating in transmit mode of operation at the appropriate center frequency.

### **Test Measurement Set up**



Band-edge measurement test configuration

#### **Measurement Results of Conducted Spurious Emissions**

Ambient conditions.

Temperature: 17 to 23 °C Relative humidity: 31 to 57 % Pressure: 999 to 1012 mbar



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011


Page: 48 of 98

#### **Conducted Band-Edge Results**

### TABLE OF RESULTS

| Channel<br># | Center<br>Frequency<br>(MHz) | Band-edge<br>Frequency<br>(MHz) | Limit<br>(dBm) | Amplitude @<br>Band-edge<br>(dBm) | Margin<br>(dB) |
|--------------|------------------------------|---------------------------------|----------------|-----------------------------------|----------------|
| 0            | 903.00                       | 902.0                           | 6.42           | -32.81                            | -39.23         |
| 59           | 926.00                       | 928.0                           | 5.96           | -35.15                            | -41.11         |

#### 902 MHZ LOWER BAND EDGE - HOPPING OFF



Date: 12.MAY.2010 15:45:44




To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 49 of 98

#### 902 MHZ LOWER BAND EDGE - HOPPING ON



Date: 12.MAY.2010 15:49:31




To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

**Page:** 50 of 98

### 928 MHZ UPPER BAND EDGE - HOPPING OFF



Date: 12.MAY.2010 15:52:57




To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

**Page:** 51 of 98

### 928 MHZ UPPER BAND EDGE - HOPPING ON



Date: 12.MAY.2010 15:57:19



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

**Page:** 52 of 98

# **Spurious Emissions (1-10 GHz)**

Conducted spurious emissions (30MHz - 10 GHz) are provided below. The maximum emissions observed are indicated in the results table before each plot.

< Plots available beginning next page>



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011


Page: 53 of 98

### TABLE OF RESULTS

| Channel<br>Centre<br>Frequency<br>(MHz) | Start<br>Frequency<br>(MHz) | Stop<br>Frequency<br>(MHz) | Maximum<br>Emission<br>Observed<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) |
|---|-----------------------------|----------------------------|--|----------------|----------------|
| 903.00                                  | 30                          | 10,000                     | -21.23                                   | 7.92           | -29.15         |

The emission breaking the limit line is the carrier.

### CHANNEL 903.00 MHZ - 30 MHZ TO 10,000 MHZ



Date: 12.MAY.2010 09:36:36



To: FCC 47 CFR Part15.247 & IC RSS-210


Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 54 of 98

| Channel<br>Centre<br>Frequency<br>(MHz) | Start<br>Frequency<br>(MHz) | Stop<br>Frequency<br>(MHz) | Maximum<br>Emission<br>Observed<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) |
|---|-----------------------------|----------------------------|--|----------------|----------------|
| 914.90                                  | 30                          | 10,000                     | -22.77                                   | 8.07           | 30.84          |

The emission breaking the limit line is the carrier.

### CHANNEL 914.90 MHZ - 30 MHZ TO 10,000 MHZ



Date: 12.MAY.2010 09:49:38



To: FCC 47 CFR Part15.247 & IC RSS-210


Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 55 of 98

| Channel<br>Centre<br>Frequency<br>(MHz) | Start<br>Frequency<br>(MHz) | Stop<br>Frequency<br>(MHz) | Maximum<br>Emission<br>Observed<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) |
|---|-----------------------------|----------------------------|--|----------------|----------------|
| 926.00                                  | 30                          | 10,000                     | -24.71                                   | 7.76           | -32.47         |

The emission breaking the limit line is the carrier.

### CHANNEL 926.00 MHZ - 30 MHZ TO 10,000 MHZ



Date: 12.MAY.2010 09:51:45



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

**Page:** 56 of 98

### **Specification**

#### **Limits Band-Edge**

| Lower Limit<br>Band-edge | Upper Limit<br>Band-edge | Limit below highest level of desired power |
|--------------------------|--------------------------|--|
| 902 MHz                  | 928 MHz                  | ≥ 20 dB                                    |

# FCC, Part 15 Subpart C §15.247(d)

### Industry Canada RSS-210 §A.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

### **Laboratory Measurement Uncertainty for Conducted Spurious Emissions**

| Measurement uncertainty | ±2.37 dB |
|-------------------------|----------|
| Measurement uncertainty | 12.31 UD |

### **Traceability**

| Method  | Test Equipment Used                                   |
|---|---|
| Measurements were made per work instruction WI-05 'Measurement of Spurious Emissions' | 0287, 0158, 0193, 0252, 0313, 0314, 0070, 0116, 0117. |



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 57 of 98


### 5.1.7. Conducted Spurious Emissions Stand-By

# Industry Canada RSS-Gen §7.2.3

#### **Test Procedure**

Conducted Stand-By emissions were measured on the device on the mid channel. The EUT was placed in Stand-By mode and emissions were measured 30 MHz – 7 GHz.

### **Test Measurement Set up**



Stand-By spurious emissions test configuration

### Measurement Results of Stand -By Spurious Emissions

Ambient conditions.

Temperature: 17 to 23 °C Relative humidity: 31 to 57 % Pressure: 999 to 1012 mbar




To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

**Page:** 58 of 98

### 5.1.7.1. Conducted Stand-By Spurious Emissions 30M - 10 GHz

No emissions were observed breaking the limit.



12.MAI.2010 12.12.21



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

**Page:** 59 of 98

# **Specification**

Antenna Conducted Measurement Industry Canada RSS-Gen §7.2.3

If the device has a detachable antenna of known antenna impedance, then the antenna conducted method is permitted in lieu of a radiated measurement.

Receiver spurious emissions at any discrete frequency shall not exceed 2 nanowatts (-57 dBm) in the band 30-1000 MHz, or 5 nanowatts (-53 dBm) above 1 GHz.

# **Laboratory Measurement Uncertainty for Conducted Spurious Emissions**

| Measurement uncertainty | ±2.37 dB |
|-------------------------|----------|
|-------------------------|----------|

### **Traceability**

| Method  | Test Equipment Used                                   |
|---|---|
| Measurements were made per work instruction WI-05 'Measurement of Spurious Emissions' | 0287, 0158, 0193, 0252, 0313, 0314, 0070, 0116, 0117. |



**To:** FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

**Page:** 60 of 98

# 5.1.8. Radiated Emissions - Transmitter and Receiver

FCC, Part 15 Subpart C §15.247(d) Industry Canada RSS-210 §A8.5

#### **Test Procedure**

Testing was performed in a 3-meter anechoic chamber. Preliminary radiated emissions were measured on every azimuth and with the receiving antenna in both horizontal and vertical polarizations. Preliminary emissions were recorded with in Spectrum Analyzer mode, using a maximum peak detector while in peak hold mode.

Emissions nearest the limits were chosen for maximization and formal measurement using a CISPR Compliant receiver. Emissions above 1000 MHz are measured utilizing a CISPR compliant average detector with a tuned receiver, using a bandwidth of 1 MHz. Emissions from 30 MHz – 1000 MHz are measured utilizing a CISPR compliant quasi-peak detector with a tuned receiver, using a bandwidth of 120 kHz. Only the highest emissions relative to the limit are listed.




To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 61 of 98

### **Test Measurement Set Up**




Radiated Emission Measurement Setup - Above 1 GHz



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 62 of 98



Radiated Emission Measurement Setup - Below 1 GHz



**To:** FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 63 of 98

### **Field Strength Calculation**

The field strength is calculated by adding the Antenna Factor and Cable Loss, and subtracting Amplifier Gain from the measured reading. All factors are included in the reported data.

FS = R + AF + CORR - FO

FS = Field Strength

R = Measured Spectrum analyzer Input Amplitude

AF = Antenna Factor

CORR = Correction Factor = CL - AG + NFL

CL = Cable Loss

AG = Amplifier Gain

FO = Distance Falloff Factor

NFL = Notch Filter Loss or Waveguide Loss

Field Strength Calculation Example:

Given receiver input reading of 51.5 dB $\mu$ V; Antenna Factor of 8.5 dB; Cable Loss of 1.3 dB; Falloff Factor of 0 dB, an Amplifier Gain of 26 dB and Notch Filter Loss of 1 dB. The Field Strength of the measured emission is:

 $FS = 51.5 + 8.5 + 1.3 - 26.0 + 1 = 36.3 dB\mu V/m$ 

Conversion between  $dB\mu V/m$  (or  $dB\mu V$ ) and  $\mu V/m$  (or  $\mu V$ ) are done as:

Level (dB $\mu$ V/m) = 20 \* Log (level ( $\mu$ V/m))

40 dB $\mu$ V/m = 100  $\mu$ V/m 48 dB $\mu$ V/m = 250  $\mu$ V/m



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 64 of 98

### **Specification**

#### **Radiated Spurious Emissions**

**FCC §15.247(d)** In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section §15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(a)).

FCC §15.205 (a) Except as shown in paragraph (d) of 15.205 (a), only spurious emissions are permitted in any of the frequency bands listed.

FCC §15.205 (a) Except as shown in paragraphs (d) and (e) of this section, the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

FCC §15.209 (a) Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table.

**Table 1: FCC 15.209 Spurious Emissions Limits** 

| Frequency (MHz) | Field Strength<br>(µV/m) | Field Strength<br>(dBµV/m) | Measurement Distance (meters) |  |  |
|-----------------|--------------------------|----------------------------|-------------------------------|--|--|
| 30-88           | 100                      | 40.0                       | 3                             |  |  |
| 88-216          | 150                      | 43.5                       | 3                             |  |  |
| 216-960         | 200                      | 46.0                       | 3                             |  |  |
| Above 960       | 500                      | 54.0                       | 3                             |  |  |



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 65 of 98

# **Laboratory Measurement Uncertainty for Spectrum Measurement**

Measurement Uncertainty +5.6/ -4.5 dB

# Traceability:

| Method                 | Test Equipment Used                            |
|------------------------|--|
| Work instruction WI-03 | 0088, 0158, 0134, 0304, 0311, 0315, 0310, 0312 |




To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 66 of 98

#### 5.1.8.1. Transmitter Peak Emissions

#### Radiated Emissions - Peak Fundamental Emissions





Legend:

PK = Peak Emission of Fundamental

**Title:** Tehama Wireless TW101

To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

**Page:** 67 of 98

| Test      | Freq.  | 915.00   | MHz      |             |             |     |                       | E      | ngineer                   | CSB          |                                       |          |
|-----------|--------|--|----------|-------------|-------------|-----|-----------------------|--------|---------------------------|--------------|---------------------------------------|----------|
| V         | ariant | FSK  |          |             |             |     | <b>Temp (°C)</b> 21.5 |        |                           |              |                                       |          |
| Freq. F   | Range  | 902 - 928 MHz  |          |             |             |     |                       | Rel.   | Hum .(%)                  | 37           |                                       |          |
| Power S   | etting | Maximum  |          |             |             |     | Pı                    | ress.  | (mBars)                   | 1009         |                                       |          |
| An        | tenna  | Integra  | l Whip   |             |             |     |                       | Duty ( | Cycle (%)                 | 100          |                                       |          |
| Test No   | otes 1 | Peak E   | mission  | s           |             |     |                       |        |                           |              |                                       |          |
| Test No   | otes 2 | 10dB a   | ttenuate | or, no prea | amp         |     |                       |        |                           |              |                                       |          |
| MiC@ML    |        | 100B attenuator, no preamp  dBu\sim Vasona by E  120C  100C  100C  Radiated Emissions Filename: k:vorogram\tehama\tehama\tenama\tehamama\tehama\tehama\tehama\tehama\tehama\tehama\tehama\tehama\tehama |          |             |             |     | <del>pil</del> est.   | CC 15  | 209 RE 30-<br>st program\ | Meas<br>Spec | úasi Lt<br>ebug<br>Dist 3m<br>Dist 3m | ţt.      |
| Frequency | Raw    | Cable  | AF       | Level       | Measurement | Pol | Hgt                   | Azt    | Limit                     | Margin       | Pass                                  | Comments |
| MHz       | dBuV   | Loss   | dB       | dBuV/m      | Туре        |     | cm                    | Deg    | dBuV/m                    | dB           | /Fail                                 |          |
| 914.922   | 85.5   | 17.4   | 22.9     | 125.8       | Peak [Scan] | Н   |                       |        |                           |              |                                       | PK       |

TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 68 of 98

| Test Freq          | 926.00  | MHz                     |                 |                     |        |                       | E          | ngineer         | CSB          |               |          |
|--------------------|---|-------------------------|-----------------|---------------------|--------|-----------------------|------------|-----------------|--------------|---------------|----------|
| Varian             | t FSK   |                         |                 |                     |        | <b>Temp (°C)</b> 21.5 |            |                 |              |               |          |
| Freq. Range        | 902 - 9   | 28 MHz                  |                 |                     |        |                       | Rel. I     | Hum .(%)        | 37           |               |          |
| Power Setting      | Maximu  | ım                      |                 |                     |        | Pi                    | ress.      | (mBars)         | 1009         |               |          |
| Antenna            | a Integra   | l Whip                  |                 |                     |        |                       | Duty (     | Cycle (%)       | 100          |               |          |
| Test Notes         | Peak E  | mission                 | s               |                     |        |                       |            |                 |              |               |          |
| Test Notes 2       | 2 10dB a  | ttenuat                 | or, no prea     | amp                 |        |                       |            |                 |              |               |          |
| MiC MLabs          | dBu√/m<br>130.p<br>120.p<br>110.p<br>100.p<br>90.p<br>Rac<br>File | TOTAL STATE BY EMISSING |                 |                     |        |                       |            |                 |              |               |          |
| Formally me        | asured  | emiss                   | sion pea        | ıks                 |        |                       |            |                 |              |               |          |
| Frequency Raw dBu\ |   | AF<br>dB                | Level<br>dBuV/m | Measurement<br>Type | Pol    | Hgt<br>cm             | Azt<br>Deg | Limit<br>dBuV/m | Margin<br>dB | Pass<br>/Fail | Comments |
|                    | 17.4  | 22.9                    | 123.2           | Peak [Scan]         | V      |                       |            |                 |              |               | PK       |
| 926.072 82.9       |   |                         |                 |                     |        |                       |            |                 |              |               |          |
|                    |   |                         | sions; DIC      | 6 = Digital Emissi  | ons; F | UND =                 | Funda      | ımental; W      | B = Wide     | band En       | nission  |




To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 69 of 98

#### 5.1.8.2. Transmitter Radiated Spurious Emissions

### Radiated Spurious Emissions - [30-1000MHz]



Note: Fundamental is visible in plot. Please see Radiated Digital Emissions for emissions results not categorized as radio emissions (TX, NRB = Non Restricted Band, FUND)



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

**Page:** 70 of 98

|                                  |   |  |                 |                      |                 |                                   |            |                 | I            |               |          |  |  |
|----------------------------------|---|--|-----------------|----------------------|-----------------|-----------------------------------|------------|-----------------|--------------|---------------|----------|--|--|
|                                  |   | 915 MHz                                    |                 |                      |                 | Engineer CSB                      |            |                 |              |               |          |  |  |
| Varian                           | t FSK   |  |                 |                      |                 | <b>Temp (°C)</b> 21.5             |            |                 |              |               |          |  |  |
| Freq. Rang                       | 30 MHz  | MHz  |                 |                      | Rel. Hum.(%) 37 |                                   |            |                 |              |               |          |  |  |
| Power Settin                     | Maxim   | ım   |                 |                      |                 | Press. (mBars) 1009               |            |                 |              |               |          |  |  |
| Antenn                           | Integra   | l Whip                                     |                 |                      |                 |                                   | Duty (     | Cycle (%)       | 100          |               |          |  |  |
| Test Notes                       | 1 EUT V   | EUT Vertical on Test Table                 |                 |                      |                 |                                   |            |                 |              |               |          |  |  |
| Test Notes                       | 2 Fundar  | Fundamental attenuated by Band Stop Filter |                 |                      |                 |                                   |            |                 |              |               |          |  |  |
| MiceMLabs                        | BMLabs  dBuV/m  Vasona by EMiSoft  10 May 10 10:25  [1] Horizonta  Qp Ouasi Lt  Debug  Meas Dist 3m  Spec Dist 3m  Spec Dist 3m  Spec Dist 3m  Frequency: MHz  Radiated Emissions  Radiated Emissions  Template: FCC 15.209 RE 30-1000MHz  Filename: k:\program\tehama wireless\teha01- remote sensor\test program\north america\15.247 |  |                 |                      |                 |                                   |            |                 |              |               |          |  |  |
| Formally measured emission peaks |   |  |                 |                      |                 |                                   |            |                 |              |               |          |  |  |
| Frequency Ray                    |   | AF<br>dB                                   | Level<br>dBuV/m | M easurement<br>Type | Pol             | Hgt<br>cm                         | Azt<br>Deg | Limit<br>dBuV/m | Margin<br>dB | Pass<br>/Fail | Comments |  |  |
| 811.984 51.                      | 7.2   | -8.1                                       | 50.5            | Peak                 | Н               | > 20dB below Fundamental Pass NRB |            |                 |              |               | NRB      |  |  |
| Legend: TX =                     | TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission   |  |                 |                      |                 |                                   |            |                 |              |               |          |  |  |

Note: Fundamental is visible in plot. Please see Radiated Digital Emissions for emissions results not categorized as radio emissions (TX, NRB = Non Restricted Band, FUND)



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

**Page:** 71 of 98

| Test Freq   | 926 MH   | z  |                 |                      |     |                                   | E          | ngineer         | CSB          |               |          |  |
|---|--|--|-----------------|----------------------|-----|-----------------------------------|------------|-----------------|--------------|---------------|----------|--|
| Varian  | FSK  |  |                 |                      |     | Temp (°C) 2                       |            |                 |              | 21.5          |          |  |
| Freq. Range   | 30 MHz - 1000 MHz  |  |                 |                      |     | Rel. Hum.(%) 37                   |            |                 |              | 7             |          |  |
| Power Setting   | Maximu   | m  |                 |                      |     | Press. (mBars) 1009               |            |                 |              |               |          |  |
| Antenna   | Integral   | Whip                                       |                 |                      |     | Duty Cycle (%) 100                |            |                 |              |               |          |  |
| Test Notes 1  | EUT Ve   | EUT Vertical on Test Table                 |                 |                      |     |                                   |            |                 |              |               |          |  |
| Test Notes 2  | Fundam   | Fundamental attenuated by Band Stop Filter |                 |                      |     |                                   |            |                 |              |               |          |  |
| MiCoMLabs  Vasona by EMiSoft  10 May 10 10:35  (1) Horizonts (2) Vertical Operation |  |  |                 |                      |     |                                   |            |                 |              |               |          |  |
| Formally measured emission peaks  |  |  |                 |                      |     |                                   |            |                 |              |               |          |  |
| Frequency Raw   | Cable<br>Loss  | AF<br>dB                                   | Level<br>dBuV/m | M easurement<br>Type | Pol | Hgt<br>cm                         | Azt<br>Deg | Limit<br>dBuV/m | Margin<br>dB | Pass<br>/Fail | Comments |  |
| 823.092 47.7  | 7.2  | -8.0                                       | 46.8            | Peak [Scan]          | Н   | > 20dB below Fundamental Pass NRB |            |                 |              |               | NRB      |  |
| Legend: TX =  | Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission |  |                 |                      |     |                                   |            |                 |              |               |          |  |

Note: Fundamental is visible in plot. Please see Radiated Digital Emissions for emissions results not categorized as radio emissions (TX, NRB = Non Restricted Band, FUND)



**To:** FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 72 of 98

# Radiated Spurious Emissions – [1000MHz – 10,000MHz]

EUT was tested at 100% duty cycle. Typical packet lengths are below 15ms, and channel does not repeat over a period of approximately 27 seconds. The slowest baud rate (highest spectral density) and longest operational packet length was used to calculate the duty cycle correction factor displayed below.

Slowest baud rate = 25Kbit/sec. At 25Kbit/sec, the longest packet will be 23.68mS, and our typical packet under 15mS.

### **Duty Cycle Correction Factor:**

Duty cycle correction factor was applied to spurious emissions in the restricted bands closest to the fundamental transmission.

EUT Operational Duty Cycle: 23.68mS per 100mS window Correction Factor = 20 \* LOG (23.68 / 100)

Correction Factor = -12.51dB

Corrected Value = Measured Value (dB) - 12.51 (dB)




To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 73 of 98

| Test Freq.    | 903.00 MHz                                | Engineer   | CSB  |  |  |  |  |  |  |
|---------------|---|--|------|--|--|--|--|--|--|
| Variant       | FSK                                       | Temp (°C)  | 21.5 |  |  |  |  |  |  |
| Freq. Range   | 1000 - 10000 MHz                          | Rel. Hum.(%)                                       | 37   |  |  |  |  |  |  |
| Power Setting | Maximum                                   | Press. (m Bars)                                    | 1009 |  |  |  |  |  |  |
| Antenna       | Integral Whip                             | Duty Cycle (%)                                     | 100  |  |  |  |  |  |  |
| Test Notes 1  | Duty Cycle correction factor applied as a | ty Cycle correction factor applied as appropriate. |      |  |  |  |  |  |  |
| Test Notes 2  |   |  |      |  |  |  |  |  |  |





Duty Cycle Correction Factor (dB): 12.51

### Formally measured emission peaks

| Frequency<br>M Hz | Raw<br>dBuV | Cable<br>Loss | AF<br>dB | Level<br>dBuV | M easurement<br>Type | Pol | Hgt<br>cm | Azt<br>Deg | Limit<br>dBuV | Margin<br>dB | Pass<br>/Fail | Comments |
|-------------------|-------------|---------------|----------|---------------|----------------------|-----|-----------|------------|---------------|--------------|---------------|----------|
| 1805.969          | 72.1        | 2.6           | -12.7    | 62.0          | Peak [Scan]          | V   | > 20      | OdB be     | low funda     | amental      | Pass          | NRB      |
| 2608.642          | 56.5        | 3.1           | -11.4    | 48.2          | Peak [Scan]          | Н   | > 20      | OdB be     | low funda     | amental      | Pass          | NRB      |
| 2708.978          | 78.2        | 3.2           | -11.2    | 70.2          | Peak [Scan]          | Н   | 100       | 0          | 74            | -3.8         | Pass          | RB       |
| 2709.028          | 67.4        | 3.2           | -11.2    | 59.4          | 10Hz VBW             | Н   | 101       | 220        | 54            | -7.1         | Pass          | RB       |
| 3611.943          | 68.4        | 3.7           | -10.7    | 61.3          | Peak [Scan]          | V   | 100       | 0          | 54            | -5.2         | Pass          | RB       |
| 4514.976          | 61.5        | 4.2           | -9.7     | 56.1          | Peak [Scan]          | Н   | 100       | 0          | 54            | -10.5        | Pass          | RB       |
| 5418.006          | 55.0        | 4.6           | -9.2     | 50.5          | Peak [Scan]          | ٧   | 100       | 0          | 54            | -16.1        | Pass          | RB       |
| 6320.892          | 56.1        | 5.1           | -6.7     | 54.4          | Peak [Scan]          | Н   | > 20      | odB be     | low funda     | mental       | Pass          | NRB      |
| 7223.908          | 49.6        | 5.4           | -5.5     | 49.5          | Peak [Scan]          | ٧   | > 20      | OdB be     | low funda     | mental       | Pass          | NRB      |
| 8126.854          | 51.6        | 5.7           | -4.0     | 53.3          | Peak [Scan]          | Н   | 100       | 0          | 54            | -13.2        | Pass          | RB       |
| 9029.881          | 58.4        | 6.2           | -3.7     | 61.0          | Peak [Scan]          | Η   | 100       | 0          | 54            | -5.6         | Pass          | RB       |
| 9932.881          | 46.6        | 6.4           | -2.7     | 50.4          | Peak [Scan]          | Н   | > 20      | OdB be     | low funda     | mental       | Pass          | NRB      |

Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission

DCCF = Duty Cycle Correction Factor Applied




To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 74 of 98

|               | <u> </u>                                  |   |      |  |  |  |  |  |  |
|---------------|---|---|------|--|--|--|--|--|--|
| Test Freq.    | 914.9 MHz                                 | Engineer  | CSB  |  |  |  |  |  |  |
| Variant       | FSK                                       | Temp (ºC)   | 21.5 |  |  |  |  |  |  |
| Freq. Range   | 1000 - 10000 MHz                          | Rel. Hum.(%)                                      | 37   |  |  |  |  |  |  |
| Power Setting | Maximum                                   | Press. (m Bars)                                   | 1009 |  |  |  |  |  |  |
| Antenna       | Integral Whip                             | Duty Cycle (%)                                    | 100  |  |  |  |  |  |  |
| Test Notes 1  | Duty Cycle correction factor applied as a | y Cycle correction factor applied as appropriate. |      |  |  |  |  |  |  |
| Test Notes 2  |   |   |      |  |  |  |  |  |  |





Duty Cycle Correction Factor (dB): 12.51

#### Formally measured emission peaks

| Frequency<br>MHz | Raw<br>dBuV | Cable<br>Loss | AF<br>dB | Level<br>dBuV | M easurement<br>Type | Pol | Hgt<br>cm | Azt<br>Deg | Limit<br>dBuV | Margin<br>dB | Pass<br>/Fail | Comments |
|------------------|-------------|---------------|----------|---------------|----------------------|-----|-----------|------------|---------------|--------------|---------------|----------|
| 1829.762         | 68.5        | 2.6           | -12.8    | 58.4          | Peak [Scan]          | V   | > 20      | 0dB be     | low funda     | amental      | Pass          | NRB      |
| 2744.689         | 77.0        | 3.2           | -11.6    | 68.7          | Peak [Scan]          | Н   | 100       | 0          | 74.0          | -5.3         | Pass          | RB       |
| 2744.689         | 71.3        | 3.2           | -11.6    | 63.0          | 10Hz VBW             | Н   | 100       | 0          | 54            | -3.6         | Pass          | RB       |
| 3659.587         | 70.6        | 3.7           | -10.7    | 63.6          | Peak [Scan]          | Н   | 100       | 0          | 54            | -2.9         | Pass          | RB       |
| 4574.459         | 62.7        | 4.2           | -10.1    | 56.9          | Peak [Scan]          | V   | 100       | 0          | 54            | -9.7         | Pass          | RB       |
| 5489.352         | 60.1        | 4.6           | -8.8     | 56.0          | Peak [Scan]          | Н   | > 20      | 0dB be     | low funda     | amental      | Pass          | NRB      |
| 6404.289         | 60.2        | 5.1           | -6.6     | 58.7          | Peak [Scan]          | Н   | > 20      | 0dB be     | low funda     | amental      | Pass          | NRB      |
| 7319.238         | 49.2        | 5.4           | -5.0     | 49.6          | Peak [Scan]          | Η   | 100       | 0          | 54            | -16.9        | Pass          | RB       |
| 8233.955         | 53.3        | 5.7           | -3.6     | 55.5          | Peak [Scan]          | Н   | 100       | 0          | 54            | -11.0        | Pass          | RB       |
| 9148.957         | 58.4        | 6.2           | -3.3     | 61.3          | Peak [Scan]          | Η   | 100       | 0          | 54            | -5.3         | Pass          | RB       |

Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission




To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 75 of 98

| Test Freq.    | 926 MHz  | Engineer       | CSB  |  |  |  |  |  |
|---------------|--|----------------|------|--|--|--|--|--|
| Variant       | FSK  | Temp (°C)      | 21.5 |  |  |  |  |  |
| Freq. Range   | 1000 - 10000 MHz                                   | Rel. Hum.(%)   | 37   |  |  |  |  |  |
| Power Setting | Maximum  | Press. (mBars) | 1009 |  |  |  |  |  |
| Antenna       | Integral Whip                                      | Duty Cycle (%) | 100  |  |  |  |  |  |
| Test Notes 1  | ty Cycle correction factor applied as appropriate. |                |      |  |  |  |  |  |
| Test Notes 2  |  |                |      |  |  |  |  |  |





Duty Cycle Correction Factor (dB): 12.51

#### Formally measured emission peaks

| Frequency<br>MHz | Raw<br>dBuV | Cable<br>Loss | AF<br>dB | Level<br>dBuV | M easurement<br>Type | Pol | Hgt<br>cm | Azt<br>Deg | Limit<br>dBuV | Margin<br>dB | Pass<br>/Fail | Comments |
|------------------|-------------|---------------|----------|---------------|----------------------|-----|-----------|------------|---------------|--------------|---------------|----------|
| 1851.973         | 70.1        | 2.7           | -12.5    | 60.2          | Peak [Scan]          | Н   | > 20      | OdB be     | low funda     | mental       | Pass          | NRB      |
| 2777.957         | 76.3        | 3.2           | -11.6    | 67.9          | Peak [Scan]          | Н   | 100       | 0          | 74.0          | -6.1         | Pass          | RB       |
| 2777.957         | 73.2        | 3.2           | -11.6    | 64.8          | 10Hz VBW             | Н   | 100       | 0          | 54            | -1.7         | Pass          | RB       |
| 3703.937         | 71.4        | 3.7           | -10.5    | 64.7          | Peak [Scan]          | Н   | 100       | 0          | 54            | -1.8         | Pass          | RB       |
| 4629.961         | 62.6        | 4.3           | -9.8     | 57.1          | Peak [Scan]          | V   | 100       | 0          | 54            | -9.4         | Pass          | RB       |
| 5555.932         | 62.2        | 4.7           | -8.5     | 58.4          | Peak [Scan]          | Н   | > 20      | OdB be     | low funda     | mental       | Pass          | NRB      |
| 6481.941         | 59.4        | 5.1           | -6.6     | 58.0          | Peak [Scan]          | Н   | > 20      | OdB be     | low funda     | mental       | Pass          | NRB      |
| 8333.968         | 56.4        | 5.8           | -3.6     | 58.5          | Peak [Scan]          | Н   | 100       | 0          | 54            | -8.0         | Pass          | RB       |
| 9259.915         | 53.0        | 6.2           | -2.8     | 56.5          | Peak [Scan]          | Н   | > 20      | OdB be     | low funda     | mental       | Pass          | NRB      |

Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 76 of 98

# 5.1.8.3. Band Edge Emissions

| Test              | Freq.       | 903 MH  | lz   |            |          |  |    | E      | ngineer   | CSB  |  |  |
|-------------------|-------------|---|--|------------|----------|--|----|--------|-----------|------|--|--|
| Va                | ariant      | FSK   | SK <b>Temp (°C)</b> 21.5                   |            |          |  |    |        |           |      |  |  |
| Freq. F           | Range       | Band E  | dge  |            |          |  |    | Rel. I | Hum .(%)  | 37   |  |  |
| Power Se          | etting      | Maximu  | ım   |            |          |  | Pı | ress.  | (mBars)   | 1009 |  |  |
| Ant               | tenna       | Integra   | Whip                                       |            |          |  |    | Duty ( | Cycle (%) | 100  |  |  |
| Test No           | otes 1      | AC Pov  | v ered                                     |            |          |  |    |        |           |      |  |  |
| Test No           | otes 2      |   |  |            |          |  |    |        |           |      |  |  |
| MiCeM             | abs         | dBuVim<br>50.0<br>50.0<br>40.0<br>70.0<br>10.0<br>10.0<br>Rade<br>File                          | Meas Dist 3m  Spec Dist 3m  Frequency: MHz |            |          |  |    |        |           |      |  |  |
| Formally          | mea         | sure  | sured emission peaks                       |            |          |  |    |        |           |      |  |  |
| Frequency<br>M Hz | Raw<br>dBuV | Cable<br>Loss   | Polling                                    |            |          |  |    |        |           |      |  |  |
| Emissions cov     | ered u      | nder rad  | diated s                                   | purious er | nissions |  |    |        |           |      |  |  |
| Legend:           | TX = T      | TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission |  |            |          |  |    |        |           |      |  |  |
|                   |             |   |  |            |          |  |    |        |           |      |  |  |



**To:** FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 77 of 98

| Test             | Freq.       | 926 MH   | łz  |      |  |           |    | E      | ngineer   | CSB  |  |  |
|------------------|-------------|--|---|------|--|-----------|----|--------|-----------|------|--|--|
| V                | ariant      | FSK  |   |      |  | Temp (°C) |    |        | 21.5      |      |  |  |
| Freq. F          | Range       | Band E   | dge                                       |      |  |           |    | Rel. I | Hum.(%)   | 37   |  |  |
| Power Se         | etting      | Maximu   | ım  |      |  |           | Pr | ress.  | (m Bars)  | 1009 |  |  |
| Ant              | tenna       | Integra  |   |      |  |           |    | Duty ( | Cycle (%) | 100  |  |  |
| Test No          | tes 1       | AC Pov   | v ered                                    |      |  |           |    |        |           |      |  |  |
| Test No          | tes 2       |  |   |      |  |           |    |        |           |      |  |  |
| MiCOM            | abs         | 40.0<br>40.0<br>30.0<br>20.0<br>10.0<br>980.0<br>Rade<br>File                                | Meas Dist 3m Spec Dist 3m  Frequency: MHz |      |  |           |    |        |           |      |  |  |
| Formally         | mea         | sured  | red emission peaks                        |      |  |           |    |        |           |      |  |  |
| Frequency<br>MHz | Raw<br>dBuV | Cable<br>Loss  | Comments                                  |      |  |           |    |        |           |      |  |  |
| No radio emis    | sions v     | v ithin 6  | dB of lin                                 | nit. |  |           |    |        |           |      |  |  |
| Legend:          | TX = T      | = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission |   |      |  |           |    |        |           |      |  |  |




To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 78 of 98

### 5.1.8.4. Receiver Radiated Spurious Emissions



Note: Fundamental is visible in plot. Please see Radiated Digital Emissions for emissions results not categorized as radio emissions (TX, NRB. FUND)




To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

**Page:** 79 of 98

| Test Freq.         | 2437 MHz          | Engineer       | CSB   |
|--------------------|-------------------|----------------|---|
| Variant            | FSK               | Temp (°C)      | 21.5  |
| Freq. Range        | 30 MHz - 1000 MHz | Rel. Hum.(%)   | 37  |
| Power Setting      | Maximum           | Press. (mBars) | 1009  |
| Antenna            | Integral Whip     | Duty Cycle (%) | 100   |
| Test Notes 1       | AC Pow ered       |                |   |
| Test Notes 2       |                   |                |   |
| <b>MiC®iM</b> Labs | dBu√ Vasona by E  | MiSoft         | 10 May 10 14:29  [1] Horizontz Pk [2] Vertical Peak Limit Average It Debug Meas Dist 3m |



### Formally measured emission peaks

| Frequency | Raw  | Cable | AF | Level  | Measurement<br>Type | Pol | Hgt | Azt | Limit  | Margin | Pass  | Comments |
|-----------|------|-------|----|--------|---------------------|-----|-----|-----|--------|--------|-------|----------|
| MHz       | dBuV | Loss  | dB | dBuV/m | Type                |     | cm  | Deg | dBuV/m | dB     | /Fail | Commonto |

No radio emissions within 6dB of limit.

Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 80 of 98

FCC, Part 15 Subpart C §15.247(d) Industry Canada RSS-210 §A8.5

### **Specification**

**FCC Part 15 Subpart C §15.247(d)** 

**Industry Canada §A8.5** 

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

## **Laboratory Measurement Uncertainty for Radiated Emissions**

| Measurement uncertainty | +5.6/ -4.5 dB |
|-------------------------|---------------|
|-------------------------|---------------|

### **Traceability**

| Method  | Test Equipment Used  |
|---|--|
| Measurements were made per work instruction WI-03 'Measurement of | 0287, 0335, 0338, 0158, 0134, 0304, 0311, 0315, 0310, 0312 |
| Radiated Emissions'   |  |



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 81 of 98

## 5.1.9. Radiated Spurious Emissions – Digital Emissions

FCC, Part 15 Subpart C §15.247(d), §15.205, 15.109

#### **Test Procedure**

Testing was performed in a 3-meter anechoic chamber. Preliminary radiated emissions were measured on every azimuth and with the receiving antenna in both horizontal and vertical polarizations. Preliminary emissions were recorded with in Spectrum Analyzer mode, using a maximum peak detector while in peak hold mode.

Emissions nearest the limits were chosen for maximization and formal measurement using a CISPR Compliant receiver. Emissions above 1000 MHz are measured utilizing a CISPR compliant average detector with a tuned receiver, using a bandwidth of 1 MHz. Emissions from 30 MHz – 1000 MHz are measured utilizing a CISPR compliant quasi-peak detector with a tuned receiver, using a bandwidth of 120 kHz. Only the highest emissions relative to the limit are listed.




To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 82 of 98

### **Test Measurement Set Up**




Radiated Emission Measurement Setup - Above 1 GHz



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 83 of 98



Radiated Emission Measurement Setup - Below 1 GHz



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 84 of 98

## **Test Measurement Set Up**

# **Field Strength Calculation**

The field strength is calculated by adding the Antenna Factor and Cable Loss, and subtracting Amplifier Gain from the measured reading. All factors are included in the reported data.

FS = R + AF + CORR - FO

FS = Field Strength

R = Measured Spectrum analyzer Input Amplitude

AF = Antenna Factor

CORR = Correction Factor = CL - AG + NFL

CL = Cable Loss

AG = Amplifier Gain

FO = Distance Falloff Factor

NFL = Notch Filter Loss or Waveguide Loss

#### Field Strength Calculation Example:

Given receiver input reading of 51.5 dB $\mu$ V; Antenna Factor of 8.5 dB; Cable Loss of 1.3 dB; Falloff Factor of 0 dB, an Amplifier Gain of 26 dB and Notch Filter Loss of 1 dB. The Field Strength of the measured emission is:

$$FS = 51.5 + 8.5 + 1.3 - 26.0 + 1 = 36.3 dB\mu V/m$$

Conversion between  $dB\mu V/m$  (or  $dB\mu V$ ) and  $\mu V/m$  (or  $\mu V$ ) are done as:

Level  $(dB\mu V/m) = 20 * Log (level (\mu V/m))$ 

 $40 \text{ dB}\mu\text{V/m} = 100 \mu\text{V/m}$  $48 \text{ dB}\mu\text{V/m} = 250 \mu\text{V/m}$ 



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 85 of 98

## **Specification**

### **Radiated Spurious Emissions**

FCC §15.247(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section §15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(a)).

FCC §15.205 (a) Except as shown in paragraph (d) of 15.205 (a), only spurious emissions are permitted in any of the frequency bands listed.

FCC §15.205 (a) Except as shown in paragraphs (d) and (e) of this section, the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

FCC §15.209 (a) Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table.

**Table 1: FCC 15.209 Spurious Emissions Limits** 

| Frequency (MHz) | Field Strength<br>(µV/m) | Field Strength<br>(dBµV/m) | Measurement Distance (meters) |
|-----------------|--------------------------|----------------------------|-------------------------------|
| 30-88           | 100                      | 40.0                       | 3                             |
| 88-216          | 150                      | 43.5                       | 3                             |
| 216-960         | 200                      | 46.0                       | 3                             |
| Above 960       | 500                      | 54.0                       | 3                             |



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 86 of 98

# **Laboratory Measurement Uncertainty for Spectrum Measurement**

Measurement Uncertainty +5.6/ -4.5 dB

# Traceability:

| Method                 | Test Equipment Used                            |
|------------------------|--|
| Work instruction WI-03 | 0088, 0158, 0134, 0304, 0311, 0315, 0310, 0312 |



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 87 of 98

### 5.1.9.1. Radiated Digital Emissions

| Test Freq.    | Rx Mode - 914.9 MHz                               | Engineer        | CSB  |  |  |  |
|---------------|---|-----------------|------|--|--|--|
| Variant       | Digital Emissions                                 | Temp (°C)       | 25   |  |  |  |
| Freq. Range   | 30 MHz - 1000 MHz                                 | Rel. Hum.(%)    | 38   |  |  |  |
| Power Setting | Receive Mode                                      | Press. (m Bars) | 1005 |  |  |  |
| Antenna       | Integral  |                 |      |  |  |  |
| Test Notes 1  | AC Pow er supply on table. EUT vertical on table. |                 |      |  |  |  |
| Test Notes 2  |   |                 |      |  |  |  |

1031 10103 2





## Formally measured emission peaks

| Frequency<br>MHz | Raw<br>dBuV | Cable<br>Loss | AF<br>dB | Level<br>dBuV/m | Measurement<br>Type | Pol | Hgt<br>cm | Azt<br>Deg | Limit<br>dBuV/m | Margin<br>dB | Pass<br>/Fail | Comments |
|------------------|-------------|---------------|----------|-----------------|---------------------|-----|-----------|------------|-----------------|--------------|---------------|----------|
| 71.566           | 49.1        | 3.9           | -23.1    | 29.9            | Quasi Max           | V   | 158       | 104        | 40              | -10.1        | Pass          | DIG      |
| 134.483          | 54.4        | 4.4           | -17.3    | 41.5            | Quasi Max           | V   | 99        | 118        | 43.5            | -2.0         | Pass          | DIG      |
| 140.979          | 55.2        | 4.4           | -18.1    | 41.5            | Quasi Max           | V   | 105       | 100        | 43.5            | -2.0         | Pass          | DIG      |
| 208.240          | 52.3        | 4.8           | -19.6    | 37.5            | Quasi Max           | V   | 98        | 249        | 43.5            | -6.0         | Pass          | DIG      |
| 212.572          | 53.4        | 4.8           | -19.7    | 38.5            | Quasi Max           | V   | 98        | 27         | 43.5            | -5.0         | Pass          | DIG      |
| 277.628          | 51.0        | 5.1           | -17.1    | 39.1            | Quasi Max           | Н   | 120       | 53         | 46              | -6.9         | Pass          | DIG      |

Legend: DIG = Digital Device Emission; TX = Transmitter Emission; FUND = Fundamental Frequency

NRB = Non-Restricted Band, Limit is 20 dB below Fundamental; RB = Restricted Band



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 88 of 98

| Test Freq.    | Rx Mode - 914.9 MHz  | Engineer       | CSB  |
|---------------|--|----------------|--|
| Variant       | Digital Emissions  | Temp (°C)      | 25   |
| Freq. Range   | 1000 MHz - 6000 MHz  | Rel. Hum.(%)   | 38   |
| Power Setting | Receive Mode   | Press. (mBars) | 1005   |
| Antenna       | Integral   |                |  |
| Test Notes 1  | AC Pow er supply on table. EUT vertical  | on table.      |  |
| Test Notes 2  |  |                |  |
| MiC@MLabs     | dBuVim Vasona by El 200 200 200 200 100 Radiated Emissions Filename: K:'program'tehama wireless'teha |                | 12 May 10 17:44  [1] Horizonta [2] Vertical Peak Limit Pk Average to Debug Meas Dist 3m Spec Dist 3m Au  Frequency: MHz 50000 2 - 6 GHz] Inorth america\15.247 |

# Formally measured emission peaks

| Frequency |      |      | AF | Level  | Measurement<br>Type | Pol  | Hgt | Azt | Limit  | Margin | Pass  | Comments |
|-----------|------|------|----|--------|---------------------|------|-----|-----|--------|--------|-------|----------|
| MHz       | dBuV | Loss | dB | dBuV/m | Type                | F 01 | cm  | Deg | dBuV/m | dB     | /Fail | Comments |

No emissions w ithing 6dB of the limit.

.egend: DIG = Digital Device Emission; TX = Transmitter Emission; FUND = Fundamental Frequency

NRB = Non-Restricted Band, Limit is 20 dB below Fundamental; RB = Restricted Band



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 89 of 98

### **Specification**

#### Limits

**§15.205 (a)** Except as shown in paragraph (d) of 15.205 (a), only spurious emissions are permitted in any of the frequency bands listed.

§15.205 (a) Except as shown in paragraphs (d) and (e) of this section, the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

§15.109 (b) The field strength of radiated emissions from a Class A digital device, as determined at a distance of 3 meters, shall not exceed the following:

§15.109 (b) Limit Matrix Class A digital device

| Frequency(MHz) | Field Strength<br>(μV/m) | Field Strength<br>(dBμV/m) | Measurement Distance (meters) |  |  |
|----------------|--------------------------|----------------------------|-------------------------------|--|--|
| 30-88          | 100                      | 49.5                       | 3                             |  |  |
| 88-216         | 150                      | 54.0                       | 3                             |  |  |
| 216-960        | 200                      | 57.0                       | 3                             |  |  |
| Above 960      | 500                      | 60.0                       | 3                             |  |  |

### **Laboratory Measurement Uncertainty for Radiated Emissions**

| Measurement uncertainty | +5.6/ -4.5 dB |
|-------------------------|---------------|
|                         |               |

### **Traceability**

| Method  | Test Equipment Used  |
|---|--|
| Measurements were made per work instruction WI-03 'Measurement of Radiated Emissions' | 0287, 0335, 0338, 0158, 0134, 0304, 0311, 0315, 0310, 0312, 0341 |



**To:** FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

**Page:** 90 of 98


## 5.1.10. AC Wireline Conducted Emissions (150 kHz - 30 MHz)

FCC, Part 15 Subpart C §15.207 Industry Canada RSS-Gen §7.2.2

#### **Test Procedure**

The measurement frequency range extends from 150 kHz to 30 MHz. The conducted emissions are measured in a shielded room with a spectrum analyzer in peak hold in the first instance. Emissions closest to the limit are measured in the quasi-peak mode (QP) with the tuned receiver using a bandwidth of 9 kHz. The emissions are maximized further by cable manipulation. The highest emissions relative to the limit are listed.

### **Test Measurement Setup**



Measurement set up for Conducted Emissions Test

### **Specification**

§15.207 (a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50  $\mu\Omega$  line impedance stabilization network (LISN), see §15.207 (a) matrix below. Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal.



To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 91 of 98

### Limits

| Frequency of Emission (MHz) | Conducted Limit (dBµV) |           |
|-----------------------------|------------------------|-----------|
|                             | Quasi-peak             | Average   |
| 0.15-0.5                    | 66 to 56*              | 56 to 46* |
| 0.5-5                       | 56                     | 46        |
| 5-30                        | 60                     | 50        |

<sup>\*</sup> Decreases with the logarithm of the frequency

# **Traceability**

All conducted emission measurements are traceable to national standards. The uncertainty of measurement at a confidence level of not less than 95 %, with a coverage factor of k=2, in the range 9 kHz - 30 MHz (Average & Quasi-peak) is  $\pm 2.64$  dB.

| Laboratory Measurement Uncertainty |          |  |
|------------------------------------|----------|--|
| Measurement uncertainty            | ±2.64 dB |  |

| Method  | Test Equipment Used                               |
|---|---|
| Measurements were made per work instruction WI-EMC-01 'Measurement of | 0158, 0184, 0193, 0190, 0293, 0307, 156, 193, 190 |
| Conducted Emissions'  | 130, 130  |




To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 92 of 98

| Test Freq.    | N/A                       | Engineer        | CSB  |
|---------------|---------------------------|-----------------|------|
| Variant       | AC Line Emissions         | Temp (°C)       | 25   |
| Freq. Range   | 0.150 MHz - 30 MHz        | Rel. Hum.(%)    | 38   |
| Power Setting | Transmitting at Max Power | Press. (m Bars) | 1005 |
| Antenna       | Integral                  |                 |      |
| Test Notes 1  |                           |                 |      |
| Test Notes 2  |                           |                 |      |





### Formally measured emission peaks

| Frequency<br>MHz | Raw<br>dBuV | Cable<br>Loss | Factors<br>dB | Level<br>dBuV | M easurement<br>Type | Line    | Limit<br>dBuV | Margin<br>dB | Pass<br>/Fail | Comments |
|------------------|-------------|---------------|---------------|---------------|----------------------|---------|---------------|--------------|---------------|----------|
| 0.629            | 15.4        | 10.0          | 0.1           | 25.5          | Average              | Live    | 46            | -20.6        | Pass          |          |
| 0.629            | 33.5        | 10.0          | 0.1           | 43.5          | Quasi Peak           | Live    | 56            | -12.5        | Pass          |          |
| 0.685            | 11.7        | 10.0          | 0.1           | 21.7          | Average              | Live    | 46            | -24.3        | Pass          |          |
| 0.685            | 32.2        | 10.0          | 0.1           | 42.2          | Quasi Peak           | Live    | 56            | -13.8        | Pass          |          |
| 0.788            | 34.2        | 10.0          | 0.1           | 44.2          | Quasi Peak           | Neutral | 56            | -11.8        | Pass          |          |
| 0.788            | 18.8        | 10.0          | 0.1           | 28.8          | Average              | Neutral | 46            | -17.2        | Pass          |          |
| 0.948            | 17.5        | 9.9           | 0.1           | 27.6          | Average              | Neutral | 46            | -18.5        | Pass          |          |
| 0.948            | 36.1        | 9.9           | 0.1           | 46.1          | Quasi Peak           | Neutral | 56            | -9.9         | Pass          |          |
| 1.740            | 34.7        | 10.0          | 0.1           | 44.8          | Quasi Peak           | Live    | 56            | -11.2        | Pass          |          |
| 1.740            | 18.9        | 10.0          | 0.1           | 29.1          | Average              | Live    | 46            | -16.9        | Pass          |          |
| 9.736            | 18.1        | 10.3          | 0.4           | 28.7          | Average              | Live    | 50            | -21.3        | Pass          |          |
| 9.736            | 31.9        | 10.3          | 0.4           | 42.5          | Quasi Peak           | Live    | 60            | -17.5        | Pass          |          |

Legend: DIG = Digital Device Emission; TX = Transmitter Emission; FUND = Fundamental Frequency

NRB = Non-Restricted Band, Limit is 20 dB below Fundamental; RB = Restricted Band




To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 93 of 98

# 6. PHOTOGRAPHS

# 6.1. General Measurement Test Set-Up






**To:** FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 94 of 98

# 6.2. Radiated Emissions >1 GHz





**To:** FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 95 of 98

# 6.3. Radiated Emissions <1 GHz





**To:** FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

Page: 96 of 98

# 6.4. AC Mains Conducted Emissions





To: FCC 47 CFR Part15.247 & IC RSS-210

Serial #: TEHA01-U2 Rev A Issue Date: 11th January 2011

**Page:** 97 of 98

# 7. TEST EQUIPMENT DETAILS

| Asset # | Instrument                  | Manufacturer                  | Part #                    | Serial #    |  |
|---------|-----------------------------|-------------------------------|---------------------------|-------------|--|
| 0070    | Power Meter                 | Hewlett Packard               | 437B                      | 3125U11552  |  |
| 0116    | Power Sensor                | Hewlett Packard               | 8485A                     | 3318A19694  |  |
| 0117    | Power Sensor                | Hewlett Packard               | 8487D                     | 3318A00371  |  |
| 0158    | Barometer<br>/Thermometer   | Control Co.                   | 4196                      | E2844       |  |
| 0184    | Pulse Limiter               | Rhode & Schwarz               | ESH3Z2                    | 357.8810.52 |  |
| 0190    | LISN                        | Rhode & Schwarz               | ESH3Z5                    | 836679/006  |  |
| 0223    | Power Meter                 | Hewlett Packard               | HP EPM-442A               | US37480256  |  |
| 0251    | K-Cable                     | Megaphase                     | Sucoflex 104              | Unknown     |  |
| 0252    | K-Cable                     | Megaphase                     | Sucoflex 104              | Unknown     |  |
| 0253    | K-Cable                     | Megaphase                     | Sucoflex 104              | Unknown     |  |
| 0256    | K-Cable                     | Megaphase                     | Sucoflex 104              | Unknown     |  |
| 0271    | Amplifier                   | 1 to 26.5 GHz                 | MiCOM                     |             |  |
| 0287    | EMI Receiver                | Rhode & Schwarz               | ESIB 40                   | 100201      |  |
| 0293    | BNC Cable                   | Megaphase                     | 1689 1GVT4                | 15F50B001   |  |
| 0307    | BNC Cable                   | Megaphase                     | 1689 1GVT4                | 15F50B002   |  |
| 0310    | 2m SMA Cable                | Micro-Coax                    | UFA210A-0-0787-<br>3G03G0 | 209089-001  |  |
| 0312    | 3m SMA Cable                | Micro-Coax                    | UFA210A-1-1181-<br>3G0300 | 209092-001  |  |
| 0313    | Coupler                     | Hewlett Packard               | 86205A                    | 3140A01285  |  |
| 0314    | 30 dB N-Type<br>Attenuator  | ARRA                          | N944-30                   | 1623        |  |
| 0335    | Horn Antenna                | The Electro-Mechanics Company | 3117                      | 00066580    |  |
| 0337    | Amplifier                   | 30 MHz – 3 GHz                | MiCOM                     |             |  |
| 0338    | Antenna (30M-3GHz)          | Sunol Sciences                | JB3                       | A052907     |  |
| 0341    | 902-928 MHz Notch<br>Filter | EWT                           | EWT-14-0199               | H1          |  |
| 0363    | Switch                      | MiCOM Labs                    |                           |             |  |



440 Boulder Court, Suite 200 Pleasanton, CA 94566, USA Tel: 1.925.462.0304

Fax: 1.925.462.0306 www.micomlabs.com