## **MPE Prediction**

FCC Rule: 15.247(b)(5)

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See §1.1307(b)(1) of this Chapter.

## LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency	Electric Field	Magnetic Field	Power Density	Average time
Range	Strength (V/m)	Strength (A/m)	(mW/cm2)	(minutes)
(MHz)				
(A)Limits For Occupational / Control Exposures				
30-300	61.4	0.613	1.0	6
300-1500			F/300	6
1500-100,000			5	6
(B)Limits For General Population / Uncontrolled Exposure				
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

F = Frequency in MHz

## Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4 \pi R^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Maximum peak output power at antenna input terminal: 12.43 (dBm)

Maximum peak output power at antenna input terminal: 17.498 (mW)

Antenna gain(maximal): 3.0 (dBi)

Prediction distance: 20 (cm)

Prediction frequency: 2480 (MHz)

MPE limit for uncontrolled exposure at prediction frequency: 1.0 (mW/cm²)

Power density at prediction frequency: 0.0069 (mW/cm²)

The manual instruct the user to install and operate the device in a minimum distance of 20 cm between antenna and the user's body.