

## RF exposure

According to FCC part 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in § 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength(V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Average time				
(A) Limits for Occupational / Control Exposures								
300 – 1 500			f/300 6					
1 500 - 100000			5	6				
(B) Limits for General Population / Uncontrol Exposures								
300 – 1 500			f/1500	6				
1 500 – 100 000			<u>1</u>	<u>30</u>				

f= frequency in Mb

Friis transmission formula:  $Pd = (Pout \times G)/(4 \times pi \times R^2)$ 

Where,

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd the limit of MPE, f/1500 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

## **Results**

Operation mode / Data Rate	Frequency (Mb)	Output power (dBm)	Antenna gain (dBi)	Power density at 20 cm (mW/cm²)	Limit (mW/cm²)
LE / 1Mbps	2 402	8.5	1.0	0.001 77	1
LE / 1Mbps	2 442	8.5	1.0	0.001 77	1
LE / 1Mbps	2 480	8.5	1.0	0.001 77	1

FCC ID.: TSW-BTLEM Page 1 of 1