

FCC-TEST REPORT

Report Number	68.930.16.015	. 01 Da	te of Issue:	July 12, 2016
			•	
Model	: COM-DEX Rei	note MIC		
Product Type	: COM-DEX Rer	note MIC		
Applicant	: Widex A/S			_
Address	: Nymoellevej 6,	DK-3540 Lyng	e, Denmark	_
Production Facility	: Widex A/S			
Address	: Nymoellevej 6,	DK-3540 Lyng	e, Denmark	
Test Result :	■ Positive	□ Negative		
Total pages including	24			
Appendices :	24			

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval.



1 Table of Contents

1	Т	able of Contents	. 2
2	D	etails about the Test Laboratory	. 3
3	D	escription of the Equipment under Test	. 4
4	S	ummary of Test Standards	. 5
5	S	ummary of Test Results	. 6
6	G	eneral Remarks	. 7
7	Т	est Setups	. 8
8	S	ystems test configuration	. 9
9	Т	echnical Requirement	10
,	9.1	Conducted peak output power	10
,	9.2	6dB bandwidth	11
,	9.3	Power spectral density	13
,	9.4	Spurious RF conducted emissions	14
,	9.5	Band edge	18
,	9.6	Spurious radiated emissions for transmitter	20
10)	Test Equipment List	23
11		System Measurement Uncertainty	24



2 Details about the Test Laboratory

Details about the Test Laboratory

Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen

Branch

Building 12&13, Zhiheng Wisdomland Business Park,

Nantou Checkpoint Road 2, Nanshan District,

Shenzhen City, 518052,

P. R. China

FCC Registration No.: 502708

IC Registration No: 10320A-1

Telephone: 86 755 8828 6998 Fax: 86 755 8828 5299



3 Description of the Equipment under Test

Description of the Equipment Under Test

Product: COM-DEX Remote MIC

Model no.: COM-DEX Remote MIC

Brand Name: Widex

FCC ID: TTY-CDRM

Options and accessories: NIL

Rating: DC 3.7V by Li-ion Battery

RF Transmission

Frequency:

2402-2480MHz

No. of Operated Channel: 40

Modulation: GFSK

Antenna Type: Integral Antenna

Antenna Gain: -0.15dBi

Description of the EUT: The Equipment Under Test (EUT) is a Bluetooth Low Energy Module

operated at 2.4GHz



4 Summary of Test Standards

	Test Standards
FCC Part 15 Subpart C	PART 15 - RADIO FREQUENCY DEVICES
10-1-2015 Edition	Subpart C - Intentional Radiators

All the test methods were according to KDB558074 D01 DTS Meas Guidance v03r02 and ANSI C63.10 (2014).



5 Summary of Test Results

Technical Requirements						
FCC Part 15 Subpar	t C		1	1		
Test Condition		Pages	Test Site	Te Pass	st Res	ult N/A
§15.207	Conducted emission AC power port					\boxtimes
§15.247 (b) (1)	Conducted peak output power	10	Site 1	\boxtimes		
§15.247(a)(1)	20dB bandwidth					\boxtimes
§15.247(a)(1)	Carrier frequency separation					\boxtimes
§15.247(a)(1)(iii)	Number of hopping frequencies					\boxtimes
§15.247(a)(1)(iii)	Dwell Time					\boxtimes
§15.247(a)(2)	6dB bandwidth	11	Site 1	\boxtimes		
§15.247(e)	Power spectral density	13	Site 1	\boxtimes		
§15.247(d)	Spurious RF conducted emissions	14	Site 1	\boxtimes		
§15.247(d)	Band edge	18	Site 1	\boxtimes		
§15.247(d) & §15.209	Spurious radiated emissions for transmitter	20	Site 1			
§15.203	Antenna requirement	See note 1		\boxtimes		

Remark 1: N/A – Not Applicable.

Note 1: The EUT uses an integral antenna, which gain is -0.15dBi. According to §15.203 and RSSGEN 8.3, it is considered sufficiently to comply with the provisions of this section.



6 General Remarks

Remarks

This submittal(s) (test report) is intended for FCC ID: TTY-CDRM complies with Section 15.207, 15.209, 15.247 of the FCC Part 15, Subpart C Rules.

SUMMARY:

All tests according to the regulations cited on page 5 were

- Performed
- ☐ Not Performed

The Equipment under Test

- **Fulfills** the general approval requirements.
- ☐ **Does not** fulfill the general approval requirements.

Sample Received Date: June 24, 2016

Testing Start Date: June 26, 2016

Testing End Date: July 4, 2016

- TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch-

Reviewed by: Prepared by:

John Zhi EMC Project Manager

Johnshi


Alan Xiong EMC Project Engineer

Alem X300



7 Test Setups

7.1 Radiated test setups



7.2 Conducted RF test setups





8 Systems test configuration

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.(SHIELD)	S/N(LENGTH)
Notebook	Lenovo	X240	

Test software: Bluetest 3, which used to control the EUT in continues transmitting mode

The system was configured to channel 0, 19, and 39 for the test.

Channel	Frequency (MHz)
0	2402
19	2440
39	2480



9 Technical Requirement

9.1 Conducted peak output power

Test Method

- Use the following spectrum analyzer settings:
 RBW > the 6 dB bandwidth of the emission being measured, VBW≥3RBW, Span≥3RBW
 Sweep = auto, Detector function = peak, Trace = max hold.
- 2. Add a correction factor to the display.
- 3. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power.

Limits

According to §15.247 (b) (1), conducted peak output power limit as below:

Frequency Range	Limit	Limit
MHz	W	dBm
2400-2483.5	≤1	≤30

Test result as below table

	Conducted Peak	
Frequency	Output Power	Result
 MHz	dBm	
 Low channel 2402MHz	-1.00	Pass
Middle channel 2440MHz	1.87	Pass
High channel 2480MHz	1 57	Pass



9.2 6dB bandwidth

Test Method

- Use the following spectrum analyzer settings:
 RBW=100K, VBW≥3RBW, Sweep = auto, Detector function = peak, Trace = max hold
- 2. Use the automatic bandwidth measurement capability of an instrument, may be employed using the X dB bandwidth mode with X set to 6 dB, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.
- 3. Allow the trace to stabilize, record the X dB Bandwidth value.


Limit

According to §15.247 (a) (2), 6dB bandwidth limit as below:

Limit [kHz]	
≥500	

Test result

Frequency MHz	6dB bandwidth kHz	Result
Low channel 2402MHz	707.7	Pass
Middle channel 2440MHz	699.0	Pass
High channel 2480MHz	699.0	Pass



Owie: 27.JUN 2016 14:46:38

Span 3.0 MHz







Date: 27 JUN 2016 14:49:31

2480MHz



Date: 27 JUN 2016 14:48:44



9.3 Power spectral density

Test Method

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance:

- Set analyzer center frequency to DTS channel center frequency.
 RBW=3kHz,VBW≥3RBW,Span=1.5 times DTS bandwidth, Detector=Peak, Sweep=auto, Trace= max hold.
- 2. Allow trace to fully stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.
- 3. Repeat above procedures until other frequencies measured were completed.

Limit

According to §15.247 (e) (2), power spectral density limit as below:

Limit [dBm]	
≤8	

Test result

	Power spectral	
Frequency	density	Result
MHz	dBm	
Low channel 2402MHz	-17.00	Pass
Middle channel 2440MHz	-13.93	Pass
High channel 2480MHz	-13.60	Pass



9.4 Spurious RF conducted emissions

Test Method

- 1. Establish a reference level by using the following procedure:
 - a. Set RBW=100 kHz. VBW≥3RBW. Detector =peak, Sweep time = auto couple, Trace mode = max hold.
 - b. Allow trace to fully stabilize, use the peak marker function to determine the maximum PSD level.
- 2. Use the maximum PSD level to establish the reference level.
 - a. Set the center frequency and span to encompass frequency range to be measured.
 - b. Use the peak marker function to determine the maximum amplitude level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements, report the three highest emissions relative to the limit.
- 3. Repeat above procedures until other frequencies measured were completed.


Limit

According to §15.247 (d), spurious RF conducted emissions limit as below:


Frequency Range MHz	Limit (dBc)
30-25000	-20



Spurious RF conducted emissions




Date: 27.JUN.2016 14:53:02




Date: 27.JUN.2016 14:52:40



2440MHz




Date: 27.JUN.2016 14:54:06




Date: 27.JUN.2016 14:53:50



2480MHz



Date: 27.JUN.2016 14:55:01



Date: 27.JUN.2016 14:54:40



9.5 Band edge

Test Method


- 1 Use the following spectrum analyzer settings: Span = wide enough to capture the peak level of the in-band emission and all spurious RBW = 100 kHz, VBW ≥ RBW, Sweep = auto, Detector function = peak, Trace = max hold.
- 2 Allow the trace to stabilize, use the peak and delta measurement to record the result.
- 3 The level displayed must comply with the limit specified in this Section.

Limit

According to §15.247 (d), band edge limit as below:


Frequency Range MHz	Limit (dBc)
30-25000	-20

Test result



Date: 27 JUN 2016 14:51:58





Date: 27 JUN 2016 14:55:49



9.6 Spurious radiated emissions for transmitter

Test Method

- 1. The EUT was place on a turn table which is 1.5m above ground plane for above 1GHz and 0.8m above ground for below 1GHz at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- 2. The EUT was set 3 meters away from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
- 3. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned
- 5. Use the following spectrum analyzer settings According to C63.10:

For Above 1GHz

Span = wide enough to capture the peak level of the in-band emission and all spurious RBW = 1MHz, VBW≥RBW for peak measurement and VBW = 10Hz for average measurement, Sweep = auto, Detector function = peak, Trace = max hold.

For Below 1GHz

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious RBW = 100 KHz, VBW≥RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

Note:

- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 KHz for Quasi-peak detection (QP) at frequency below 1GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for peak detection (PK) at frequency above 1GHz.
- 3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average ((duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor (20log(1/duty cycle)).
- 4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.



Limit

According to part 15.247(d), the radio emission outside the operating frequency band shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Radiated emissions which fall in the restricted bands, as defined in section15.205, must comply with the radiated emission limits specified in section 15.209.

Frequency MHz	Field Strength uV/m	Field Strength dBµV/m	Detector
30-88	100	40	QP
88-216	150	43.5	QP
216-960	200	46	QP
960-1000	500	54	QP
Above 1000	500	54	AV
Above 1000	5000	74	PK



Spurious radiated emissions for transmitter

According to C63.10, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in below table if the peak value complies with average limit.

Transmitting spurious emission test result as below:

2402MHz

Frequency	Emission Level	Polarization	Limit	Detector	Margin	Result
MHz	dBuV/m		dBμV/m		dΒμV/m	
33.72	19.47	Horizontal	40.00	QP	20.53	Pass
44.93	25.18	Horizontal	40.00	QP	14.82	Pass
275.79	21.81	Horizontal	46.00	QP	24.19	Pass
887.48	33.30	Horizontal	46.00	QP	12.70	Pass
33.72	21.14	Vertical	40.00	QP	18.86	Pass
43.80	23.45	Vertical	40.00	QP	16.55	Pass
871.10	29.99	Vertical	46.00	QP	16.01	Pass
1000-12750		Horizontal	74	PK		Pass
1000-12750		Vertical	74	PK		Pass

2440MHz

Frequency	Emission Level	Polarization	Limit	Detector	Margin	Result
MHz	dBuV/m		dBμV/m		dΒμV/m	
1000-12750		Horizontal	74	PK		Pass
1000-12750		Vertical	74	PK		Pass

2480MHz

Frequency	Emission Level	Polarization	Limit	Detector	Margin	Result
MHz	dBuV/m		dBμV/m		dΒμV/m	
1000-12750		Horizontal	74	PK		Pass
1000-12750		Vertical	74	PK		Pass

Remark:

(1) Data of measurement within 30-1000MHz frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20db below the permissible limits or the field strength is too small to be measured.



10 Test Equipment List

List of Test Instruments

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESR 26	101269	2016-7-24
Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9163	707	2016-8-14
Horn Antenna	Rohde & Schwarz	HF907	102294	2016-7-24
Pre-amplifier	Rohde & Schwarz	SCU 18	102230	2016-7-24
3m Semi-anechoic chamber	TDK	9X6X6		2019-5-29



11 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

System Measurement Uncertainty

Cyclom Modeurement Shoottamty			
System Measurement Uncertainty			
Test Items	Extended Uncertainty		
Uncertainty for Radiated Emission in 3m	Horizontal: 4.83dB;		
chamber 30MHz-1000MHz	Vertical: 4.91dB;		
Uncertainty for Radiated Emission in 3m	Horizontal: 4.89dB;		
chamber 1000MHz-26000MHz	Vertical: 4.88dB;		
Conducted RF test	Power level test involved: 2.04dB		
	Frequency test involved:1.1×10 ⁻⁷		