

TRaC Wireless Test Report : 0F3137WUS3

**Applicant**: Widex A/S

**Apparatus**: TV DEX, TV CONTROLLER

**Specification(s)**: CFR47 Part 15 October 2008

Purpose of Test : Certification

FCCID : TTY-TVC

IC ID : 5676B-TVC

Authorised by

:Radio Product Manager

John Charters

Issue Date : 17<sup>th</sup> March 2011

**Authorised Copy Number** : PDF

## **Contents**

Section	า 1:	Introduction	3
1.1	Gen	eral	3
		s Requested By	4
		ufacturer	4
		aratus Assessed	4
		: Result Summary	5
		es Relating To The Assessment	6
1.7	Devi	iations from Test Standards	6
Section	ո 2։	Measurement Uncertainty	7
2.1	Mea	surement Uncertainty Values	7
Section	1 3·	Modifications	9
3.1		ifications Performed During Assessment	9
Annone	div A:	Formal Emission Test Results	10
		nsmitter Intentional Emission Radiated	10
		iated Electric Field Emissions	12
		ntentional Radiated Emissions	15
		er Line Conducted Emissions	17
Annan	div D	Supporting Craphical Data	19
Append	JIX B.	Supporting Graphical Data	19
Append	dix C:	Additional Test and Sample Details	23
Append	dix D:	Additional Information	29
Append	dix E:	Photographs and Figures	30
Append	dix G:	MPE Calculation	34
Annon	div ∐.	Cross Reference FCC Part 15c to IC RSS 210	35
Thhelic	JIX II.	Closs Releighed FCC Fall 130 to IC RSS 210	33

Section 1:			Introduction
1.1 General			
		paratus against Electromagnetic Co amples submitted to the Laboratory.	
Test performed by:	TRaC Telecoms Unit E South Orbital Tra Hedon Road Hull, HU9 1NJ. United Kingdom	ading Park	[]
	Telephone: Fax:	+44 (0) 1482 801801 +44 (0) 1482 801806	
	TRaC Telecoms Moss View Nipe Lane Up Holland West Lancashire United Kingdom	e, WN8 9PY	[X]
	Telephone: Fax:	+44 (0) 1695 556666 +44 (0) 1695 577077	
	Email: Web site:	test@tracglobal.com http://www.tracglobal.com	
Tests performed by:	D Winstanley		
Report author:	D Winstanley		

This report must not be reproduced except in full without prior written permission from TRaC Telecoms & Radio.

## 1.2 Tests Requested By

This testing in this report was requested by :

Widex A/S Nymoellevej 6 DK-3540 Lynge Denmark

## 1.3 Manufacturer

Widex A/S Nymoellevej 6 DK-3540 Lynge Denmark

## 1.4 Apparatus Assessed

The following apparatus was assessed between: 18<sup>th</sup> February to 11<sup>th</sup> March 2011.

## TV DEX, TV CONTROLLER

The above equipment was an audio level control device passing audio form the 2.4 GHz link to a hearing aid via a 10.6 MHz link. This report covers the 10.6MHz frequency of operation, the 2.4GHz results can be found in TRaC test report 0F3137WUS4.

## 1.5 Test Result Summary

Full details of test results are contained within Appendix A. The following table summarises the results of the assessment.

The statements relating to compliance with the standards below apply ONLY as qualified in the notes and deviations stated in sections 1.6 to 1.7 of this test report.

Full details of test results are contained within Appendix A. The following table summarises the results of the assessment.

Test Type	Regulation	Measurement standard	Result
Spurious Emissions Radiated <1000MHz	Title 47 of the CFR: Part 15 Subpart (c) 15.209	ANSI C63.10	Pass
Spurious Emissions Radiated >1000MHz	Title 47 of the CFR: Part 15 Subpart (c)	ANSI C63.10	N/A
AC Power conducted emissions	Title 47 of the CFR: Part 15 Subpart (c) 15.207	ANSI C63.10	Pass
Intentional Emission Frequency	Title 47 of the CFR: Part 15 Subpart (c) 15.209	ANSI C63.10	Pass
Intentional Emission Field Strength:	Title 47 of the CFR: Part 15 Subpart (c) 15. 209	ANSI C63.10	Pass
Intentional Emission Band Occupancy	Title 47 of the CFR: Part 15 Subpart (c) 15.215	ANSI C63.10	Pass
Intentional Emission ERP (mW)	Title 47 of the CFR: Part 15 Subpart (c)	ANSI C63.10	N/A
Unintentional Radiated Spurious Emissions	Title 47 of the CFR: Part 15 Subpart (b) 15.109	ANSI C63.10	Pass
Antenna Arrangements Integral:	Title 47 of the CFR: Part 15 Subpart (c) 15.203	-	Pass
Antenna Arrangements External Connector	Title 47 of the CFR: Part 15 Subpart (c) 15.204	-	-
Restricted Bands	Title 47 of the CFR: Part 15 Subpart (c) 15.205	-	-
Maximum Frequency Of Search	Title 47 of the CFR: Part 15 Subpart (c) 15.33	-	-
Extrapolation Factor	Title 47 of the CFR: Part 15 Subpart (c) 15.31(f)	-	-

Abbreviations used in the above table:

CFR : Code of Federal Regulations ANSI : American National Standards Institution REFE : Radiated Electric Field Emissions PLCE : Power Line Conducted Emissions

## 1.6 Notes Relating To The Assessment

With regard to this assessment, the following points should be noted:

The results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

The apparatus was set up and exercised using the configurations, modes of operation and arrangements defined in this report only.

Particular operating modes, apparatus monitoring methods and performance criteria required by the standards tested to have been performed except where identified in Section 1.7 of this test report (Deviations from Test Standards).

For emissions testing, throughout this test report, "Pass" indicates that the results for the sample as tested were below the specified limit (refer also to Section 2, Measurement Uncertainty).

Where relevant, the apparatus was only assessed using the monitoring methods and susceptibility criteria defined in this report.

All testing with the exception of testing at the Open Area Test Site was performed under the following environmental conditions:

Temperature : 17 to 23 °C Humidity : 45 to 75 % Barometric Pressure : 86 to 106 kPa

All dates used in this report are in the format dd/mm/yy.

This assessment has been performed in accordance with the requirements of ISO/IEC 17025.

#### 1.7 Deviations from Test Standards

There were no deviations from the standards tested to.

#### Section 2:

## **Measurement Uncertainty**

### 2.1 Measurement Uncertainty Values

For test data recorded in accordance with note (iii) of Section 2.1 the following measurement uncertainty was calculated:

#### Radio Testing - General Uncertainty Schedule

All statements of uncertainty are expanded standard uncertainty using a coverage factor of 1.96 to give a 95% confidence where no required test level exists.

#### [1] Adjacent Channel Power

Uncertainty in test result = 1.86dB

#### [2] Carrier Power

```
Uncertainty in test result (Equipment - TRLUH120) = 2.18dB
Uncertainty in test result (Equipment – TRL05) = 1.08dB
Uncertainty in test result (Equipment – TRL479) = 2.48dB
```

#### [3] Effective Radiated Power

Uncertainty in test result = 4.71dB

#### [4] Spurious Emissions

Uncertainty in test result = 4.75dB

#### [5] Maximum frequency error

```
Uncertainty in test result (Equipment - TRLUH120) = 119ppm Uncertainty in test result (Equipment – TRL05) = 0.113ppm Uncertainty in test result (Equipment – TRL479) = 0.265ppm
```

## [6] Radiated Emissions, field strength OATS 14kHz-18GHz Electric Field

Uncertainty in test result (14kHz - 30MHz) = **4.8dB**, Uncertainty in test result (30MHz - 1GHz) = **4.6dB**, Uncertainty in test result (16Hz - 18GHz) = **4.7dB** 

#### [7] Frequency deviation

Uncertainty in test result = 3.2%

#### [8] Magnetic Field Emissions

Uncertainty in test result = 2.3dB

## [9] Conducted Spurious

```
Uncertainty in test result (Equipment TRL479) Up to 8.1GHz = 3.31dB
Uncertainty in test result (Equipment TRL479) 8.1GHz – 15.3GHz = 4.43dB
Uncertainty in test result (Equipment TRL479) 15.3GHz – 21GHz = 5.34dB
Uncertainty in test result (Equipment TRLUH120) Up to 26GHz = 3.14dB
```

#### [10] Channel Bandwidth

Uncertainty in test result = 15.5%

#### [11] Amplitude and Time Measurement – Oscilloscope

Uncertainty in overall test level = 2.1dB, Uncertainty in time measurement = 0.59%, Uncertainty in Amplitude measurement = 0.82%

#### [11] Power Line Conduction

Uncertainty in test result = 3.4dB

#### [12] Spectrum Mask Measurements

Uncertainty in test result = 2.59% (frequency)
Uncertainty in test result = 1.32dB (amplitude)

#### [13] Adjacent Sub Band Selectivity

Uncertainty in test result = 1.24dB

#### [14] Receiver Blocking - Listen Mode, Radiated

Uncertainty in test result = 3.42dB

#### [15] Receiver Blocking - Talk Mode, Radiated

Uncertainty in test result = 3.36dB

#### [16] Receiver Blocking - Talk Mode, Conducted

Uncertainty in test result = 1.24dB

## [17] Receiver Threshold

Uncertainty in test result = 3.23dB

#### [18] Transmission Time Measurement

Uncertainty in test result = 7.98%

Section 3:	Modifications

# 3.1 Modifications Performed During Assessment

No modifications were performed during the assessment

## **Appendix A:**

## **Formal Emission Test Results**

## Abbreviations used in the tables in this appendix:

Spec : Specification ALSR : Absorber Lined Screened Room

Mod : Modification OATS : Open Area Test Site ATS : Alternative Test Site

EUT : Equipment Under Test

SE : Support Equipment Ref : Reference

Freq : Frequency

Freq : Frequency
L : Live Power Line

N : Neutral Power Line MD : Measurement Distance
E : Earth Power Line SD : Spec Distance

Pk : Peak Detector Pol : Polarisation

QP : Quasi-Peak Detector H : Horizontal Polarisation Av : Average Detector V : Vertical Polarisation

CDN : Coupling & decoupling network

#### A1 Transmitter Intentional Emission Radiated

Carrier power was verified with the EUT transmitting Test Details:				
Regulation	Title 47 of the CFR: Part15 Subpart (c) 15.209(b)(1)			
Measurement standard	ANSI C63.10:2009			
EUT sample number	S07			
Modification state	0			
SE in test environment	None			
SE isolated from EUT	None			
EUT set up	Refer to Appendix C			
Photographs (Appendix F)	Photograph 1			

FREQ. (MHz)	MEASUREMENT DISTANCE Meters	MEASUREMENT Rx. READING (dBµV/m)	FAC	RAP. TOR B)	FIELD STRENGTH (µV/m)
10.606	1	91.1	63.1		25.2
10.606	3	68.0	40	0.0	25.2
Limit va	lue @ fc	30 μV/m			
	f lower f higher			f higher	
Band occupar	10.338782 10.926923			0.926923	
			588.14	1kHz	

Notes:

- 1 Results quoted are extrapolated as indicated
- 2 Receiver detector @ fc = Quasi Peak 10 kHz
- 3 When battery powered the EUT was powered with new batteries
- 4 Extrapolation 3 30 Meters 40 dB as per 15.31(f)
- 5 Extrapolation 1 3 Meters 23.1dB as Measured
- 6 Extrapolation 1 30 Meters 40+23.1 = 63.1 dB

**Test Method**:

- 1 As per Radio Noise Emissions, ANSI C63.10
- 2 Measuring distances 3m
- 3 EUT 0.8 metre above ground plane
- 4 Emissions maximised by rotation of EUT, on an automatic turntable. Raising and lowering the receiver antenna between 1m & 4m. Horizontal and vertical polarisations, of the receive antenna.

EUT orientation in three orthagonal planes.

Maximum results recorded

## A2 Radiated Electric Field Emissions

Preliminary scans were performed using a peak detector with the RBW = 100 kHz. The radiated electric filed emission test applies to all spurious emissions and harmonics emissions. The maximum permitted field strength is listed in Section 15.209. The EUT was set to transmit as required.

The following test site was used for fir	nal measur	ements as specified by the stan	dard tested to:
3m open area test site :		3m alternative test site :	X

The effect of the EUT set-up on the measurements is summarised in note (c) below.

Test Details:			
Regulation	Title 47 of the CFR, Part 15 Subpart (c) Clause 15.209		
Measurement standard	ANSI C63.10:2009		
Frequency range	9kHz – 1000MHz		
EUT sample number	S07		
Modification state	0		
SE in test environment	S27		
SE isolated from EUT	None		
EUT set up	Refer to Appendix C		
Photographs (Appendix F)	Photograph 2		

The worst case radiated emission measurements for spurious emissions are listed overleaf:

## **Radiated Electric Field Emissions Continued**

Ref No.	FREQ. (MHz)	MEAS Rx (dBμV)	CABLE LOSS (dB)	ANT FACT. (dB/m)	PRE AMP (dB)	FIELD ST'GH (dBµV/m)	EXTRAP FACT (dB)	FIELD ST'GH (μV/m)	LIMIT (μV/m)
1	31.80	39.5	1.1	16.9	27.5	30.4	-	33.11	100
2	34.50	31.1	1.1	15.5	27.5	20.2	-	10.23	100
3	37.10	40.0	1.1	14.1	27.5	27.7	-	24.27	100
4	74.25	44.8	1.1	5.8	27.7	24.0	-	15.85	100
5	95.45	41.2	1.1	9.6	27.7	24.2	-	16.22	150
6	106.05	51.4	1.1	11.0	27.7	37.2	-	72.44	150
7	148.50	50.4	1.3	10.0	27.7	36.9	-	69.98	150
8	159.15	42.5	1.4	9.6	27.8	30.5	-	33.50	150
9	180.30	51.8	1.5	8.3	27.8	34.9	-	55.59	150
10	190.90	51.2	1.6	8.5	27.8	34.8	-	54.95	150
11	201.52	48.1	1.6	8.8	27.8	31.7	-	38.46	150
12	212.10	33.3	1.7	8.4	27.7	22.5	-	13.34	150
13	222.75	44.6	1.7	8.8	27.7	34.6	-	53.70	200
14	243.94	39.0	1.8	11.4	27.7	27.7	-	24.27	200
15	265.25	40.2	1.9	13.0	27.7	33.2	-	45.71	200
16	296.95	33.6	2.0	13.0	27.6	23.7	-	15.31	200
17	318.18	36.3	2.1	13.6	27.6	26.7	-	21.63	200
18	328.75	28.4	2.1	13.7	27.6	25.0	-	17.78	200
19	339.45	38.8	2.1	14.0	27.6	36.0	-	63.10	200
20	350.00	40.0	2.2	14.3	27.6	30.0	-	31.62	200
21	360.60	42.2	2.2	14.6	27.5	34.3	-	51.88	200
22	371.30	34.1	2.2	14.8	27.6	26.2	-	20.42	200
23	381.80	37.2	2.3	15.1	27.6	27.0	-	22.39	200
24	392.45	36.2	2.3	15.4	27.5	27.6	-	23.99	200
25	402.95	38.1	2.3	16.0	27.5	30.2	-	32.36	200
26	413.70	33.4	2.3	16.4	27.5	26.2	-	20.42	200
27	456.05	32.5	2.5	16.3	27.5	25.8	-	19.50	200
28	466.65	30.0	2.5	16.6	27.5	25.4	-	18.62	200

#### Notes:

- Any testing performed below 30 MHz was performed using a magnetic loop antenna in accordance with ANSI C63.10: section 4.5, Table 1. For emissions below 30MHz the cable losses are assumed to be negligible.
- In accordance with 15.35(b), above 1 GHz, emissions measured using a peak detector shall not exceed a level 20 dB above the average limit.
- Testing was performed with the EUT orientated in three orthogonal planes and the maximum emissions level recorded. In addition, the EUT antenna was varied within its range of motion in order to maximise emissions.
- 4 For Frequencies below 1 GHz, RBW= 120 kHz, testing was performed with CISPR16 compliant test receiver with QP detector.

The upper and lower frequency of the measurement range was decided according to 47 CFR Part 15:2008 Clause 15.33(a) and 15.33(a)(1).

Radiated emission limits 47 CFR Part 15: Clause 15.209 for all emissions:

Frequency of emission (MHz)	Field strength μV/m	Measurement Distance m	Field strength dBμV/m
0.009-0.490	2400/F(kHz)	300	67.6/F (kHz)
0.490-1.705	24000/F(kHz)	30	87.6/F (kHz
1.705-30	30	30	29.5
30-88	100	3	40.0
88-216	150	3	43.5
216-960	200	3	46.0
Above 960	500	3	54.0

(a) Where results have been measured at one distance, and a signal level displayed at another, the results have been extrapolated using the following formula:

Extrapolation (dB) = 
$$20 \log_{10} \left( \frac{\text{measurement distance}}{\text{specification distance}} \right)$$

- (b) The levels may have been rounded for display purposes.
- (c) The following table summarises the effect of the EUT operating mode, internal configuration and arrangement of cables / samples on the measured emission levels :

	See (i)	See (ii)	See (iii)	See (iv)
Effect of EUT operating mode on emission levels		<b>√</b>		
Effect of EUT internal configuration on emission levels		✓		
Effect of Position of EUT cables & samples on emission levels	✓			

- (i) Parameter defined by standard and / or single possible, refer to Appendix D
- (ii) Parameter defined by client and / or single possible, refer to Appendix D
- (iii) Parameter had a negligible effect on emission levels, refer to Appendix D
- (iv) Worst case determined by initial measurement, refer to Appendix D

## A3 Unintentional Radiated Emissions

Preliminary scans were performed using a peak detector with the RBW = 100kHz. The radiated electric filed emission test applies to all spurious emissions on directly related to the transmitter. The maximum permitted field strength is listed in Section 15.109. The EUT was set to operate in a transmit standby / receive mode.

The following test site was used for fi	al measurements as specified by the standard tested to:
3m open area test site :	3m alternative test site : X
The effect of the EUT set-up on the m	easurements is summarised in note (c) below.

Test Details:				
Regulation	Title 47 of the CFR, Part 15 Subpart (c) Clause 15.109			
Measurement standard	ANSI C63.10:2009			
Frequency range	9kHz – 1000MHz			
EUT sample number	S07			
Modification state	0			
SE in test environment	S27			
SE isolated from EUT	None			
EUT set up	Refer to Appendix C			
Photographs (Appendix F)	Photograph 2			

The worst case radiated emission measurements for spurious emissions are listed below:

Ref No.	FREQ. (MHz)	MEAS Rx (dBμV)	CABLE LOSS (dB)	ANT FACT. (dB/m)	PRE AMP (dB)	FIELD ST'GH (dBµV/m)	EXTRAP FACT (dB)	FIELD ST'GH (μV/m)	LIMIT (µV/m)
1.				No Significant	Emissions Withi	in 20 dB of the	limit		

#### Notes:

- 1 Any testing performed below 30 MHz was performed using a magnetic loop antenna in accordance with ANSI C63.10: section 4.5, Table 1. For emissions below 30MHz the cable losses are assumed to be negligible.
- 2 In accordance with 15.35(b), above 1 GHz, emissions measured using a peak detector shall not exceed a level 20 dB above the average limit.
- 3 Testing was performed with the EUT orientated in three orthogonal planes and the maximum emissions level recorded. In addition, the EUT antenna was varied within its range of motion in order to maximise emissions.
- 4 For Frequencies below 1 GHz, RBW = 120 kHz, testing was performed with CISPR16 compliant test receiver with QP detector. Above 1 GHz tests were performed using a spectrum analyser using the following settings:

Peak RBW=VBW= 1MHz Average RBW=VBW= 1MHz

The upper and lower frequency of the measurement range was decided according to 47 CFR Part 15:2008 Clause 15.33(a) and 15.33(a)(1).

Radiated emission limits 47 CFR Part 15: Clause 15.109 for all emissions:

Frequency of emission (MHz)	Field strength μV/m	Measurement Distance m	Field strength dBμV/m
30-88	100	3	40.0
88-216	150	3	43.5
216-960	200	3	46.0
Above 960	500	3	54.0

(a) Where results have been measured at one distance, and a signal level displayed at another, the results have been extrapolated using the following formula:

Extrapolation (dB) = 
$$20 \log_{10} \left( \frac{\text{measurement distance}}{\text{specification distance}} \right)$$

- (b) The levels may have been rounded for display purposes.
- (c) The following table summarises the effect of the EUT operating mode, internal configuration and arrangement of cables / samples on the measured emission levels :

	See (i)	See (ii)	See (iii)	See (iv)
Effect of EUT operating mode on emission levels		✓		
Effect of EUT internal configuration on emission levels		✓		
Effect of Position of EUT cables & samples on emission levels	✓			

- (i) Parameter defined by standard and / or single possible, refer to Appendix D
- (ii) Parameter defined by client and / or single possible, refer to Appendix D
- (iii) Parameter had a negligible effect on emission levels, refer to Appendix D
- (iv) Worst case determined by initial measurement, refer to Appendix D

#### A3 Power Line Conducted Emissions

Preview power line conducted emission measurements were performed with a peak detector in a screened room. The effect of the EUT set-up on the measurements is summarised in note (b). Where applicable formal measurements of the emissions were performed with a peak, average and/or quasi peak detector.

Test Details:		
Regulation	Title 47 of the CFR: Part 15 Subpart (c) Clause 15.207	
Measurement standard	ANSI C63.10:2003	
Frequency range	150kHz to 30MHz	
EUT sample number	S07	
Modification state	0	
SE in test environment	S27	
SE isolated from EUT	None	
EUT set up	Refer to Appendix C	

The worst-case power line conducted emission measurements are listed below:

## Results measured using the average detector compared to the average limit

Ref No.	Freq (MHz)	Conductor	Result (dBuV)	Spec Limit (dBuV)	Margin (dB)	Result Summary
1	10.605	Live	46.75	50.00	-3.25	Pass

## Results measured using the quasi-peak detector compared to the quasi-peak limit

Ref No.	Freq (MHz)	Conductor	Result (dBuV)	Spec Limit (dBuV)	Margin (dB)	Result Summary
1	4.97	Live	36.77	56.00	-19.23	Pass
2	10.605	Live	50.54	60.00	-9.46	Pass

## **Specification limits:**

Conducted emission limits (47 CFR Part 15: Clause 15.207):

Conducted disturbance at the mains ports.

Frequency range MHz	Limits	dΒμV
1 Toquettoy fullgo Will2	Quasi-peak	Average
0.15 to 0.5	66 to 56 <sup>2</sup>	56 to 46 <sup>2</sup>
0.5 to 5	56	46
5 to 30	60	50

#### Notes:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.

## Notes:

- (a) The levels may have been rounded for display purposes.
- (b) The following table summarises the effect of the EUT operating mode and internal configuration on the measured emission levels :

	See (i)	See (ii)	See (iii)	See (iv)
Effect of EUT operating mode on emission levels		✓		
Effect of EUT internal configuration on emission levels		✓		

- (i) Parameter defined by standard and / or single possible, refer to Appendix C
- (ii) Parameter defined by client and / or single possible, refer to Appendix C
- (iii) Parameter had a negligible effect on emission levels, refer to Appendix C
- (iv) Worst case determined by initial measurement, refer to Appendix C


## Appendix B:

## **Supporting Graphical Data**


This appendix contains graphical data obtained during testing.

#### Notes:


- (a) The radiated electric field emissions and conducted emissions graphical data in this appendix is preview data. For details of formal results, refer to Appendix A and Appendix B.
- (b) The time and date on the plots do not necessarily equate to the time of the test.
- (c) Where relevant, on power line conducted emission plots, the limit displayed is the average limit, which is stricter than the quasi peak limit.
- (d) Appendix C details the numbering system used to identify the sample and its modification state.
- (e) The plots presented in this appendix may not be a complete record of the measurements performed, but are a representative sample, relative to the final assessment.




## 20dB Bandwidth




**AC Powerline Conduction** 




Radiated spurious emissions 9kHz to 30MHz



Radiated spurious emissions 30MHz 1GHz



Unintentional Radiated spurious emissions 9kHz to 30MHz



Unintentional Radiated spurious emissions 30MHz to 1GHz

## **Appendix C: Additional Test and Sample Details**

This appendix contains details of:

- 1. The samples submitted for testing.
- Details of EUT operating mode(s)
- 3. Details of EUT configuration(s) (see below).
- 4. EUT arrangement (see below).

Throughout testing, the following numbering system is used to identify the sample and it's modification state:

Sample No: Sxx Mod w

where:

xx = sample number eg. S01 w = modification number eg. Mod 2

The following terminology is used throughout the test report:

**Support Equipment (SE)** is any additional equipment required to exercise the EUT in the applicable operating mode. Where relevant SE is divided into two categories:

SE in test environment: The SE is positioned in the test environment and is not isolated from the EUT (e.g. on the table top during REFE testing).

SE isolated from the EUT: The SE is isolated via filtering from the EUT. (e.g. equipment placed externally to the ALSR during REFE testing).

**EUT configuration** refers to the internal set-up of the EUT. It may include for example:

Positioning of cards in a chassis. Setting of any internal switches. Circuit board jumper settings. Alternative internal power supplies.

Where no change in EUT configuration is **possible**, the configuration is described as "single possible configuration".

**EUT arrangement** refers to the termination of EUT ports / connection of support equipment, and where relevant, the relative positioning of samples (EUT and SE) in the test environment.

For further details of the test procedures and general test set ups used during testing please refer to the related document "EMC Test Methods - An Overview", which can be supplied by TRaC Telecoms & Radio upon request.

## C1) Test samples

The following samples of the apparatus were submitted by the client for testing:

Sample No.	Description	Identification
S07	TV-Dex, TV-Controller	None
S27	Friwo FW7662M-05	None

The following samples of apparatus were submitted by the client as host, support or drive equipment (auxiliary equipment):

Sample No.	Description	Identification
NONE		

The following samples of apparatus were supplied by TRaC Telecoms & Radio as support or drive equipment (auxiliary equipment):

Identification	Description
NONE	

# C2) EUT Operating Mode During Testing.

During testing, the EUT was exercised as described in the following tables:

Test	Description of Operating Mode: Transmit
REFE: Radiated E-Field (Transmitter carrier output levels dBuV/m)	
REFE: Radiated Spurious emissions E- Field at frequencies below 30MHz (dBuV/m) (15.209)	The EUT was transmitting continuously on maximum power using FSK (center frequency
Radiated Spurious emissions (E-Field) at frequencies ≥ 30MHz (15.209)	10.6MHz / Deviation ±200kHz) modulation and powered by a new battery.
20dB Bandwidth of Emissions	

Test	Description of Operating Mode: Receive mode
REFE: 15.109 Radiated Spurious emissions E-field below 30MHz (Receive)	The EUT was placed in receive mode (non-transmitting) Mode during the test. Powered by a
REFE: 15.109 Radiated Spurious emissions (E-Field) frequencies ≥ 30MHz (Receive)	new battery.

# C3) EUT Configuration Information.

The EUT was submitted for testing in one single possible configuration.

# C4) List of EUT Ports

The tables below describe the termination of EUT ports:

Sample : S07 Tests : All

Port	Description of Cable Attached	Cable length	Equipment Connected
dc power port	2 Wire Cable	1	Friwo FW7662M_05 (S27)
Antenna port	None	N/A	Integral

.

# C5 Details of Equipment Used

TRAC Ref	Type	Description	Manufacturer	Date Calibrated.
TRLUH281	FSU46	Spectrum Analyser	Rhode & Schwarz	29/01/2010
TRLUH04	ESHS10	Receiver	Rhode & Schwarz	14/12/2010
TRLUH187	ESVS10	Receiver	Rhode & Schwarz	14/12/2010
TRLUH93	CBL6112	BiLog Periodic Antenna	Chase	03/06/2009
TRL07	HFH2	Loop Antenna	Rhode & Schwarz	26/08/2009
TRLUH372	6201-69	30MHz – 1 GHz Pre Amplifier	Watkins Johnson	14/04/2010

Appendix D:	Additional Information
No additional information is included within this test report.	

## Appendix E:

## **Photographs and Figures**

The following photographs were taken of the test samples:

- 1. Radiated emissions: TV DEX, TV CONTROLLER H Field
- 2. Radiated emissions: TV DEX, TV CONTROLLER E Filed
- 3. Radiated emissions: TV DEX, TV CONTROLLER close Up



Photograph 1



Photograph 2



Photograph 3

Appendix G: MPE Calculation

OET Bulletin No. 65, Supplement C 01-01

## 47 CFR §§1.1307 and 2.1091

2.1091 Radio frequency radiation exposure evaluation: mobile devices.

For purposes of these requirements mobile devices are defined by the FCC as transmitters designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimetres is normally maintained between radiating structures and the body of the user or nearby persons. These devices are normally evaluated for exposure potential with relation to the MPE limits. As the 20cm separation specified under FCC rules may not be achievable under normal operation of the EUT, an RF exposure calculation is needed to show the minimum distance required to be less than 1mW/cm² power density limit, as required under FCC rules.

## Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{EIRP}{4 \pi R^2}$$
 re - arranged  $R = \sqrt{\frac{EIRP}{S 4 \pi}}$ 

where:

S = power density R = distance to the centre of radiation of the antenna EIRP = EUT Maximum power

Note:

The EIRP value was determined using the peak E Field measurement.

#### Result

Prediction Frequency (MHz)	Maximum EIRP (mW)	Power density limit (S) (mW/cm <sup>2</sup> )	Distance (R) cm required to be less than 1mW/cm <sup>2</sup>
10.6	0.11 x10 <sup>-4</sup>	1	1.1x10 <sup>-4</sup>

## **Appendix H:**

#### Cross Reference FCC Part 15c to IC RSS 210

The testing of the C4-PA was carried out to FCC 47CFR Part 15c and the results for this testing can be found in Appendix A of this report.

All measurements were carried out in accordance with ANSI C63.4, 'Methods of Measurements of RF Emissions from low voltage Electrical and Electronic Equipment in the Range 9kHz to 40GHz.

The table below shows the applicable RSS-210 parts and the corresponding FCC 47CFR Part 15 rules:

RSS-210	FCC 47CFR Part 15
2.6	Part 15.109
2.6	Part 15.209

In addition below is a plot of the 99% emissions bandwidth, as stipulated in Section 4.4.1 of RSS-Gen.

