

## Evoluent VerticalMouse 3 Wireless – Right Hand User Manual

### Operation procedure

- 1 Insert two AA batteries to the RF mouse, and close the battery door.
- 2 Plug in the Receiver to the USB port of PC.
- 3 Press the Connect button of Receiver.
- 4 Press the Connect button of RF mouse for pairing with the Receiver within 15 seconds.
- 5 Access LED will go off and RF mouse is ready. If Access LED is still blinking, please repeat the above procedure 1 to 4 again.

### Note:

When batteries are out of power, RF mouse can still work. Just simply connect PC and mouse with retractable cable, but the Receiver must stay on the USB port of PC.

### Notice:

Changes or modifications are not expressly approved by the manufacturer could void the user's authority to operate the equipment. Changes or modifications to the device may void FCC and CE compliance. In frequently used radio links should be tested regularly to protect against undetected interference or fault.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.