

No.198 Kezhu Road, Science Town Economic& Technology Development District Guangzhou, China 510663 Telephone: +86 (0) 20 8215 5555 Fax: +86 (0) 20 8207 5059 Email: sgs_internet_operations@sgs.com

FEDERAL COMMUNICATIONS COMMISSION

Registration number: 282399

Report No.: SZEMO051201503RFF

Page: 1 of 9

FCC ID: TUUXGWRC4126

TEST REPORT

Application No.: SZEMO051201503RF(SGS SZ NO. SZTYR051201435/EL)

Applicant: Xin Guang Wei Toys Trading CO., Ltd.

FCC ID: TUUXGWRC4126

Fundamental Frequency: 27.145MHz

Equipment Under Test (EUT):

Name: WHO Cut the cheese

Model No.: 4126
Labelled Age Grading: 3AND UP
Country of Origin: CHIINA

Standards: FCC PART 15, SUBPART C : 2004

Section 15.227

Date of Receipt:06 December 2005Date of Test:07 December 2005Date of Issue:08 December 2005

Test Result : PASS *

Authorized Signature:

Dedoo(

Robinson Lo Laboratory Manager

This report refers to the General Conditions for Inspection and Testing Services, printed overleaf

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

All test results in this report can be traceable to National or International Standards.

^{*} In the configuration tested, the EUT complied with the standards specified above.



Report No.: SZEMO051201503RFF

Page: 2 of 9

2 Test Summary

Test	Test Requirement	Stanadard Paragraph	Result
Radiated Emission (30MHz to 1000MHz)	FCC PART 15 :2004	Section 15.227 and	PASS
Occupied Bandwidth	FCC PART 15 :2004	Section 15.215 and	PASS

Tx: In this whole report Tx (or tx) means Transmitter.

Rx: In this whole report Rx (or rx) means Receiver.

RF: In this whole report RF means Radiated Frequency.



Report No.: SZEMO051201503RFF Page: 3 of 9

3 Contents

			Page
1	CO/	VER PAGE	1
2	TES	ST SUMMARY	2
3	CON	NTENTS	3
4	GEN	NERAL INFORMATION	4
	4.1	CLIENT INFORMATION	4
	4.2	DETAILS OF E.U.T.	
	4.3	DESCRIPTION OF SUPPORT UNITS	
	4.4	TEST LOCATION	4
	4.5	OTHER INFORMATION REQUESTED BY THE CUSTOMER	4
	4.6	TEST FACILITY	5
5	TES	T RESULTS	6
	5.1	TEST INSTRUMENTS	6
	5.2	E.U.T. OPERATION	
	5.3	TEST PROCEDURE & MEASUREMENT DATA	6
	5.3.		
	5.3.2	2 Occupied Bandwidth	8



Report No.: SZEMO051201503RFF

Page: 4 of 9

4 General Information

4.1 Client Information

Applicant Name: Xin Guang Wei Toys Trading CO., Ltd

Applicant Address: 3th Floor, Ninhong Bld, Hongfa Plaza, Chenghai Guangdong China

4.2 Details of E.U.T.

EUT Name: WHO Cut the cheese

Item No.: 4126

Power Supply: 3.0V DC (2*1.5V 'AG3' Size Batteries) for Tx.

Power Cord: N/A-

4.3 Description of Support Units

The EUT was tested as an independent unit: 27MHz radio transmitter.

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory, No.198 Kezhu Road, Science Town Economic & Technology Development District Guangzhou, China 510663

Tel: +86 20 82155555 Fax: +86 20 8207 5059

4.5 Other Information Requested by the Customer

None.



Report No.: SZEMO051201503RFF

Page: 5 of 9

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

NVLAP – Lab Code: 200611-0

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is recognized under the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 200611-0. Effective through December 31, 2005.

ACA

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our NVLAP accreditation.

VCCI

The 3m Semi-anechoic chamber and Shielded Room (11.5m x 4m x 4m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-1599 and C-1706 respectively.

Date of Registration: June 01, 2005. Valid until February 22, 2008.

SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

CNAL – LAB Code: L0141

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAL/AC01:2002 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:1999 General Requirements) for the Competence of Testing Laboratories.

FCC – Registration No.: 282399

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 282399, May 31, 2002. With the above and NVLAP's accreditation, SGS-CSTC is an authorised test laboratory for the DoC process.

Industry Canada (IC)

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 5169.



Report No.: SZEMO051201503RFF

Page: 6 of 9

5 Test Results

5.1 Test Instruments

RE in Chamber						
Item	Test Equipment	Manufacturer	Serial No.	Cal.Date (dd-mm-yy)	Cal.Due date (dd-mm-yy)	
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	SEL0017	28-04-2005	27-04-2006	
2	EMI Test Receiver	Rohde & Schwarz	100249	20-09-2005	19-09-2006	
3	EMI Test software	AUDIX	E3	N/A	N/A	
4	Coaxial cable	SGS	SEL0028	30-05-2005	29-05-2006	
5	Coaxial cable	SGS	SEL0027	30-05-2005	29-05-2006	
6	BiConiLog Antenna	ETS-LINDGREN	00042673	11-01-2005	10-01-2006	
7	BiConiLog Antenna	ETS-LINDGREN	00042670	11-01-2005	10-01-2006	

5.2 E.U.T. Operation

Input voltage: 3.0V DC (2 x 1.5v 'AG3' Size Batteries)

Operating Environment:

Temperature: 20.0 °C
Humidity: 55% RH
Atmospheric Pressure: 1002mbar

EUT Operation: Test the EUT in transmitting mode.

5.3 Test Procedure & Measurement Data

5.3.1 Radiated Emissions

Test Requirement: FCC Part15 C Section 15.227

Test Method: ANSI C63.4

Test Date: 06 December 2005

Measurement Distance: 3m (Semi-Anechoic Chamber)

Requirements: Carrier frequency will not exceed 80dBuV/m AT 3m.

Out of band emissions shall not exceed: $40.0~dB\mu V/m~between~30MHz~\&~88MHz$ $43.5~dB\mu V/m~between~88MHz~\&~216MHz$ $46.0~dB\mu V/m~between~216MHz~\&~960MHz$

 $54.0 \text{ dB}\mu\text{V/m}$ above 960MHz

Detector: Peak Scan (120kHz resolution bandwidth)



Report No.: SZEMO051201503RFF

Page: 7 of 9

Test Procedure: The procedure used was ANSI Standard C63.4-2003. The receive was scanned from 30MHz to 1000MHz. When an emission was found, the table was rotated to produce the maximum signal strength. An initial pre-scan was performed for in peak detection mode using the receiver. The EUT was measured for both the Horizontal and Vertical polarities and performed a pre-test three orthogonal planes. The worst case emissions were reported.

An initial pre-scan was performed in the 3m chamber using the spectrum analyser in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by Bilog antenna with 2 orthogonal polarities

The following measurements were performed on the EUT on 06 December 2005: Test the EUT in transmitting mode.

27.145MHz Mode.

Intentional emission

Test Frequency	Peak (dBµV/m)		Limits	Margin (dB)	
(MHz)	Vertical	Horizontal	(dBµV/m)	Vertical	Horizontal
27.145	20.61	21.43	100.0	79.39	78.57

Test Frequency	Average (dBµV/m)		Limits	Marg	in (dB)
(MHz)	Vertical	Horizontal	(dBµV/m)	Vertical	Horizontal
27.145	17.63	19.84	80.0	62.37	60.16

Other emissions

Test Frequency	Quasi-Pea	Quasi-Peak (dBµV/m)		Margin (dB)	
(MHz)	Vertical	Horizontal	(dBµV/m)	Vertical	Horizontal
54.290	20.57	19.84	40.0	19.43	20.16
81.435	24.75	20.53	40.0	15.25	19.47
108.590	26.96	29.20	43.5	16.54	14.30
138.500	24.34	26.42	43.5	19.16	17.08
165.345	28.63	29.19	43.5	14.87	14.31
192.625	32.31	34.65	43.5	11.19	8.85
217.160	29.64	42.11	46.0	13.86	1.39
244.305	14.44	35.48	46.0	31.56	10.52

Remark:

According to 15.35 (b) When average radiated emission measurements are specified in the regulations, including emission measurements below 1000 MHz, there is also a imit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules, e.g., see Section 15.255.

Test Results: The unit does meet the FCC Part 15 C Section 15.227 requirements.



Report No.: SZEMO051201503RFF

Page: 8 of 9

5.3.2 Occupied Bandwidth

Test Requirement: FCC Part 15 C Section 15.215 (C) and Section 15.235.

Test Method: ANSI C63.4

Operation within the band 26.960 – 27.280 MHz.

Test Date: 06 December 2005

26.960 - 27.280 MHz Mode.

Requirements:

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the 20 dB bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-

band operation.

Method of measurement: The useful radiated emission from the EUT was detected by the


spectrum analyser with peak detector. The vertical Scale is set to 10dB per division. The horizontal scale is set to 32KHz per

division.



Report No.: SZEMO051201503RFF

Page: 9 of 9



Date: 6.DEC.2005 09:09:42

The results: The unit does meet the FCC Part 15 C Section 15.215 requirements