

Company: MikroTik

Test of: RBLHG-5HPnD Wireless Module

To: FCC CFR 47 Part 1.1310

Report No.: MIKO62-U2_MPE Rev A

MPE/RF EXPOSURE TEST REPORT



MPE/RF EXPOSURE TEST REPORT

FROM



Test of: MikroTik RBLHG-5HPnD Wireless Module

To: FCC CFR 47 Part 1.1310

Test Report Serial No.: MIKO62-U2_MPE Rev A

This report supersedes: NONE

Applicant: MikroTik
Pernavas 46
Riga LV 1009
Latvia

Product Function: WLAN Access Point

Issue Date: 26th October 2017

This Test Report is Issued Under the Authority of:

MiCOM Labs, Inc.
575 Boulder Court
Pleasanton California 94566
USA
Phone: +1 (925) 462-0304
Fax: +1 (925) 462-0306
www.micomlabs.com



MiCOM Labs is an ISO 17025 Accredited Testing Laboratory

1. MAXIMUM PERMISSABLE EXPOSURE

Calculations for Maximum Permissible Exposure Levels

Power Density = P_d (mW/cm²) = EIRP/(4*π*d²)

EIRP = P * G

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

Numeric Gain = 10 ^ (G (dBi)/10)

The calculations in the following table use the highest conducted power values together with the lowest antenna gain specified for the EUT. These calculations represent worst case in terms of the exposure levels.

The transmitters cannot operate simultaneously

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Power Density (mW/cm ²) @ 20cm	Power Density Limit (mW/cm ²)	Min Calculated safe distance for Limit (cm)	Calculated Power Density (mW/cm ²) @ Safe Distance
5725.0 - 5850.0	9.00	7.94	22.60	181.97	0.29	1.00	10.72	1.00
5150.0 - 5250.0	9.00	7.94	20.76	119.11	0.19	1.00	8.68	1.00
5725.0 - 5850.0	27.00	501.19	8.60	7.24	0.72	1.00	17.00	1.00
5150.0 - 5250.0	27.00	501.19	8.76	7.52	0.75	1.00	17.31	1.00

Note: for mobile or fixed location transmitters, the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

Specification - Maximum Permissible Exposure Limits

The Limit is defined in Table 1 of FCC §1.1310.



575 Boulder Court
Pleasanton, California 94566, USA
Tel: +1 (925) 462 0304
Fax: +1 (925) 462 0306
www.micomlabs.com