

# APPLICATION SUBMITTAL TEST REPORT

# FOR GRANT OF CERTIFICATION

**FOR** 

Model: RouterBOARD SXT 5nD r2
5745-5825 MHz
Broadband Digital Transmission System
FCC ID: TV7SXT-5ND

**FOR** 

# MIKROTIKLS SIA

Pernavas 46 Riga, Latvia LV-1009

Test Report Number: 120917

Authorized Signatory: Sot DRogers

Scot D. Rogers

Rogers Labs, Inc. 4405 W. 259th Terrace Louisburg, KS 66053

Phone/Fax: (913) 837-3214

Revision 1

Mikrotikls SIA

Model: RouterBOAR

Model: RouterBOARD SXT 5nD r2

Test #: 120917

Test to: CFR47 (15.247) File: Mikrotikls RBSXT5nDr2 TstRpt 120911 SN: 3B5501DDAF1/236 FCC ID#: TV7SXT-5ND Date: January 29, 2013

Page 1 of 32





# ROGERS LABS, INC.

4405 West 259th Terrace Louisburg, KS 66053 Phone / Fax (913) 837-3214

# **Engineering Test Report** For Grant of Certification Application

**FOR** CFR 47, PART 15C - Intentional Radiators CFR 47 Paragraph 15.247 License Exempt Intentional Radiator

For

# MIKROTIKLS SIA

Pernavas 46 Riga, Latvia LV-1009

**Broadband Digital Transmission System** Model: RouterBOARD SXT 5nD r2 Frequency Range 5745-5825 MHz FCC ID#: TV7SXT-5ND

Test Date: September 17, 2012

Scot D Rogers Certifying Engineer:

> Scot D. Rogers Rogers Labs, Inc.

4405 West 259<sup>th</sup> Terrace Louisburg, KS 66053

Telephone/Facsimile: (913) 837-3214

This report shall not be reproduced except in full, without the written approval of the laboratory. This report must not be used by the client to claim product endorsement by NVLAP, NIST, or any agency of the U.S. Government.

Rogers Labs, Inc. 4405 W. 259th Terrace Louisburg, KS 66053

Phone/Fax: (913) 837-3214

Revision 1

Mikrotikls SIA Model: RouterBOARD SXT 5nD r2

Test #: 120917

Test to: CFR47 (15.247)

File: Mikrotikls RBSXT5nDr2 TstRpt 120911

SN: 3B5501DDAF1/236 FCC ID#: TV7SXT-5ND Date: January 29, 2013

Page 2 of 32



# **Table Of Contents**

TABLE OF CONTENTS	3
REVISIONS	4
FORWARD	5
OPINION / INTERPRETATION OF RESULTS	5
ENVIRONMENTAL CONDITIONS	5
EQUIPMENT TESTED	5
APPLICATION FOR CERTIFICATION	6
APPLICABLE STANDARDS & TEST PROCEDURES	7
EQUIPMENT FUNCTION AND CONFIGURATION	7
Equipment Configuration	8
TEST SITE LOCATIONS	8
UNITS OF MEASUREMENTS	8
TEST PROCEDURES	9
AC Line Conducted Emission Test Procedure	9
Diagram 1 Test arrangement for Conducted emissions	9
RADIATED EMISSION TEST PROCEDURE	10
Diagram 2 Test arrangement for radiated emissions of tabletop equipment	11
Diagram 3 Test arrangement for radiated emissions tested on Open Area Test Site (OATS)	12
LIST OF TEST EQUIPMENT	13
INTENTIONAL RADIATORS	14
Antenna Requirements	14
Restricted Bands of Operation	14

Rogers Labs, Inc. 4405 W. 259th Terrace Louisburg, KS 66053 Phone/Fax: (913) 837-3214

Revision 1

Mikrotikls SIA Model: RouterBOARD SXT 5nD r2 Test #: 120917

Test to: CFR47 (15.247)

File: Mikrotikls RBSXT5nDr2 TstRpt 120911

SN: 3B5501DDAF1/236 FCC ID#: TV7SXT-5ND Date: January 29, 2013

Page 3 of 32



Restricted Bands Data (General Radiated Emissions)	14
Summary of Results for Radiated Emissions in Restricted Bands	15
AC Line Conducted Emissions Procedure	15
Figure One AC Line Conducted Emissions Line 1	16
Figure Two AC Line Conducted Emissions Line 2	16
AC Line Conducted Emissions Data (Highest Emissions)	17
Summary of Results for AC Line Conducted Emissions	18
General Radiated Emissions Procedure	19
General Radiated Emissions from EUT Data (Highest Emissions)	20
Summary of Results for General Radiated Emissions	20
Operation in the Band 5725 – 5850 MHz	21
Figure Three Plot of Transmitter Emissions (Across Operational Band, 20MHz Mode)	22
Figure Four Plot of Transmitter Emissions (Across Operational Band, 40 MHz Mode)	22
Figure Five Plot of Low Band Edge	23
Figure Six Plot of High Band Edge	23
Transmitter Emissions Data	24
Calculated Transmitter Antenna Port Power	24
Transmitter Radiated Emission	25
Summary of Results for Transmitter Radiated Emissions of Intentional Radiator	26
STATEMENT OF MODIFICATIONS AND DEVIATIONS	26
ANNEX	27
Annex A Measurement Uncertainty Calculations	28
Annex B Rogers Labs Test Equipment List	29
Annex C Rogers Qualifications	30
Annex D FCC Site Registration Letter	31
Annex E Industry Canada Site Registration Letter	32

# **Revisions**

Revision 1 Issued January 29, 2013

Rogers Labs, Inc. 4405 W. 259th Terrace Louisburg, KS 66053 Phone/Fax: (913) 837-3214

Revision 1

Mikrotikls SIA

Model: RouterBOARD SXT 5nD r2

Test #: 120917

Test to: CFR47 (15.247)

File: Mikrotikls RBSXT5nDr2 TstRpt 120911

SN: 3B5501DDAF1/236 FCC ID#: TV7SXT-5ND Date: January 29, 2013

Page 4 of 32



#### **Forward**

The following information is submitted for consideration in obtaining Grant of Certification for License Exempt Digital Transmission System Intentional Radiator operating under CFR 47 Paragraph 15.247.

Name of Applicant: Mikrotikls SIA

Pernavas 46

Riga, Latvia LV-1009

Model: RouterBOARD SXT 5nD r2 (abbreviated as RBSXT5nDr2)

FCC I.D.: TV7SXT-5ND FRN: 0014 43 1100

Frequency Range: 5745-5825 MHz (20 MHz channel operation), 5755-5815 MHz (40 MHz

channel operation)

Operating Power: 0.25 Watt (24-dBm) transmitter design incorporating integral 15-dBi gain

antenna system

# **Opinion / Interpretation of Results**

Tests Performed	Margin (dB)	Results
Emissions as per CFR 47 paragraphs 2 and 15.205	-7.6	Complies
Emissions as per CFR 47 paragraphs 2 and 15.207	-7.4	Complies
Emissions as per CFR 47 paragraphs 2 and 15.209	-1.5	Complies
Harmonic Emissions per CFR 47 15.247	-12.4	Complies
Peak Power Spectral Density per CFR 47 15.247	-8.9	Complies

### **Environmental Conditions**

Ambient Temperature 24.0° C Relative Humidity 53%

Atmospheric Pressure 1010.5 mb

# **Equipment Tested**

Equipment Model FCC I.D.

EUT RBSXT5nDr2 TV7SXT-5ND

 AC Adapter
 KSAS015240003
 9551

 Dell Studio XPS
 921LBN1
 N/A

Rogers Labs, Inc. Mikrotikls SIA

 4405 W. 259th Terrace
 Model: RouterBOARD SXT 5nD r2
 SN: 3B5501DDAF1/236

 Louisburg, KS 66053
 Test #: 120917
 FCC ID#: TV7SXT-5ND

 Phone/Fax: (913) 837-3214
 Test to: CFR47 (15.247)
 Date: January 29, 2013

Revision 1 File: Mikrotikls RBSXT5nDr2 TstRpt 120911 Page 5 of 32



# **Application for Certification**

(1) Manufacturer: Mikrotikls SIA

Pernavas 46

Riga, Latvia LV-1009

(2) Identification: Model: RouterBOARD SXT 5nD r2

FCC ID: TV7SXT-5ND

(3) Instruction Book:

Refer to Exhibit for Instruction Manual.

(4) Description of Circuit Functions:

Refer to Exhibit of Operational Description.

(5) Block Diagram with Frequencies:

Refer to Exhibit of Operational Description.

(6) Report of Measurements:

Report of measurements follows in this Report.

(7) Photographs: Construction, Component Placement, etc.:

Refer to Exhibit for photographs of equipment.

- (8) List of Peripheral Equipment Necessary for operation. The equipment operates from power received from authorized AC/DC power adapter and Power Over Ethernet (POE) adapter. The EUT offers single network connection port only. During testing, the EUT was connected to Power Over Ethernet (POE) and CPU through network cable. The EUT received power supplied from external POE and AC/DC adapter.
- (9) Transition Provisions of CFR47 15.37 are not requested.
- (10) Not Applicable. The unit is not a scanning receiver.
- (11) Not Applicable. The EUT does not operate in the 59 64 GHz frequency band.
- (12) The equipment is not software defined and this section is not applicable.

Rogers Labs, Inc. 4405 W. 259th Terrace Louisburg, KS 66053 Phone/Fax: (913) 837-3214

Revision 1

Mikrotikls SIA Model: RouterBOARD SXT 5nD r2 Test #: 120917

Test to: CFR47 (15.247)

File: Mikrotikls RBSXT5nDr2 TstRpt 120911

SN: 3B5501DDAF1/236 FCC ID#: TV7SXT-5ND Date: January 29, 2013

Page 6 of 32



# **Applicable Standards & Test Procedures**

In accordance with the Federal Communications Code of Federal Regulations, dated October 1, 2011, Part 2, Subpart J, Paragraphs 2.907, 2.911, 2.913, 2.925, 2.926, 2.1031 through 2.1057, and applicable parts of paragraph 15, Part 15C Paragraph 15.247 the following information is submitted. Test procedures used are the established Methods of Measurement of Radio-Noise Emissions as described in the ANSI C63.4-2009 Document, FCC document KDB 558074. Testing for the AC line-conducted emissions were performed as defined in sections 7 and 13.1.3, testing of the radiated emissions was performed as defined in sections 8 and 13.1.4 of ANSI C63.4-2009. Testing of the intentional radiated emissions was performed as defined in section 13 of ANSI C63.4-2009.

# **Equipment Function and Configuration**

The EUT is a 5745-5825 MHz Digital Transmission System used to transmit data in applications offering broadband wireless connectivity. The equipment is marketed for use to incorporate a wireless link to exchange data information from one point to another. For testing purposes, the RouterBOARD SXT 5nD r2 transceiver was connected to the manufacturer supplied POE and AC/DC adapter and communicating to the laptop computer through Ethernet network interface. This configuration offered operational control of the transmitter and communications over the network interface between the EUT and supporting computer system. The RouterBOARD SXT 5nD r2 receives power from the supplied POE and AC/DC adapter connected to utility power system. The EUT offers a single Ethernet network interface port for connection to the network and powering the device. No other interfacing options are provided. For testing purposes, the RouterBOARD SXT 5nD r2 received powered from the POE and AC/DC adapter and configured to transmit in available data modes. The transmitter design offers 250 mW output power and incorporates 15-dBi integral antenna system only. There are no provisions for connection with alternative antenna configurations. The antenna system complies with requirements for unique antenna connection port.

Rogers Labs, Inc. 4405 W. 259th Terrace Louisburg, KS 66053 Phone/Fax: (913) 837-3214

Revision 1

Mikrotikls SIA Model: RouterBOARD SXT 5nD r2 Test #: 120917

Test to: CFR47 (15.247)


File: Mikrotikls RBSXT5nDr2 TstRpt 120911

SN: 3B5501DDAF1/236 FCC ID#: TV7SXT-5ND Date: January 29, 2013

Page 7 of 32



## **Equipment Configuration**



#### **Test Site Locations**

Conducted EMI The AC power line conducted emissions testing performed in a shielded

screen room located at Rogers Labs, Inc., 4405 W. 259<sup>th</sup> Terrace,

Louisburg, KS

Radiated EMI The radiated emissions tests were performed at the 3 meters, Open Area

Test Site (OATS) located at Rogers Labs, Inc., 4405 W. 259th Terrace,

Louisburg, KS

Site Registration Refer to Annex for Site Registration Letters

NVLAP Accreditation Lab code 200087-0

#### **Units of Measurements**

Conducted EMI Data is in dBµV; dB referenced to one microvolt

Radiated EMI Data is in dBµV/m; dB/m referenced to one microvolt per meter

Sample Calculation:

RFS = Radiated Field Strength, FSM = Field Strength Measured

A.F. = Receive antenna factor, Gain = amplification gains and/or cable losses

SN: 3B5501DDAF1/236

RFS  $(dB\mu V/m @ 3m) = FSM (dB\mu V) + A.F. (dB) - Gain (dB)$ 

Rogers Labs, Inc. Mikrotikls SIA

4405 W. 259th Terrace Model: RouterBOARD SXT 5nD r2

Louisburg, KS 66053 Test #: 120917 FCC ID#: TV7SXT-5ND

Phone/Fax: (913) 837-3214 Test to: CFR47 (15.247) Date: January 29, 2013

Revision 1 File: Mikrotikls RBSXT5nDr2 TstRpt 120911 Page 8 of 32



#### **Test Procedures**

#### AC Line Conducted Emission Test Procedure

The EUT operates from DC power only and must be connected to an approved AC/DC adapter for operation. For testing purposes, the manufacturer supplied POE and AC/DC power adapter was used to power the EUT. Testing for the AC line-conducted emissions testing was performed as defined in sections 7 and 13.1.3 of ANSI C63.4-2009. The test setup including the EUT was arranged in typical equipment configurations and placed on a 1 x 1.5-meter wooden bench, 0.8 meters high located in a screen room. The power lines of the system were isolated from the power source using a standard LISN with a 50- $\mu$ Hy choke. EMI was coupled to the spectrum analyzer through a 0.1  $\mu$ F capacitor internal to the LISN. The LISN was positioned on the floor beneath the wooden bench supporting the EUT. The power lines and cables were draped over the back edge of the table. Refer to diagram 1 showing typical test arrangement and photographs in the test setup exhibits for specific EUT placement during testing.




Diagram 1 Test arrangement for Conducted emissions

Rogers Labs, Inc. 4405 W. 259th Terrace Louisburg, KS 66053 Phone/Fax: (913) 837-3214

Revision 1

Mikrotikls SIA Model: RouterBC

Model: RouterBOARD SXT 5nD r2

Test #: 120917 Test to: CFR47 (15.247)

File: Mikrotikls RBSXT5nDr2 TstRpt 120911

SN: 3B5501DDAF1/236 FCC ID#: TV7SXT-5ND Date: January 29, 2013

Page 9 of 32

NVLAP Lab Code 200087-0

- 1. Interconnecting cables that hung closer than 40 cm to the ground plane were folded back and forth in the center forming a bundle 30 cm to 40 cm long.
- 2. Input/output (I/O) cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- 3. EUT connected to one LISN. Unused LISN measuring port connectors are terminated into 50  $\Omega$  loads. LISN is placed on top of and bonded to reference ground plane.
- 3.1 All other equipment powered from additional LISN(s).
- 3.2 Multiple outlet strips can be used for multiple power cords of non-EUT equipment.
- 3.3 LISN is positioned at least 80 cm from nearest part of EUT chassis.
- 4. Cables of hand-operated devices, such as keyboards, mice, and so on, shall be placed as for normal use.
- 5. Non-EUT components of EUT system being tested
- 6. Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- 7. Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane (see 5.2.2 for options).

#### **Radiated Emission Test Procedure**

The EUT was placed on a rotating 1 x 1.5-meter wooden platform, 0.8 meters above the ground plane at a distance of 3 meters from the FSM antenna. Testing for the radiated emissions was performed as required by CFR47 15 and specified in sections 8 and 13.1.4 of ANSI C63.4-2009. EMI energy was maximized by equipment placement, raising and lowering the FSM antenna, changing the antenna polarization, and by rotating the turntable. Each emission was maximized before data was taken using a spectrum analyzer. Refer to photographs in the test setup exhibits for EUT placement during testing. Refer to diagrams two and three showing typical test arrangement and photographs in the test setup exhibits for specific EUT placement during testing

Rogers Labs, Inc. 4405 W. 259th Terrace Louisburg, KS 66053 Phone/Fax: (913) 837-3214

Revision 1

Mikrotikls SIA Model: RouterBOARD SXT 5nD r2 Test #: 120917

Test to: CFR47 (15.247)


File: Mikrotikls RBSXT5nDr2 TstRpt 120911

SN: 3B5501DDAF1/236 FCC ID#: TV7SXT-5ND Date: January 29, 2013

Page 10 of 32



## Diagram 2 Test arrangement for radiated emissions of tabletop equipment



- 1. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center, forming a bundle 30 cm to 40 cm long.
- 2. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated if required using the correct terminating impedance. The total length shall not exceed 1 m.
- 3. If LISNs are kept in the test setup for radiated emissions, it is preferred that they be installed under the ground plane with the receptacle flush with the ground plane.
- 4. Cables of hand-operated devices, such as keyboards, mice, and so on, shall be placed as for normal use.
- 5. Non-EUT components of EUT system being tested
- 6. Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop (possibly center of table for transmitter equipment).
- 7. No vertical conducting plane used.
- 8. Power cords drape to the floor and are routed over to receptacle.

Rogers Labs, Inc. 4405 W. 259th Terrace Louisburg, KS 66053

Phone/Fax: (913) 837-3214

Revision 1

Mikrotikls SIA Model: RouterBOARD SXT 5nD r2

Test #: 120917 Test to: CFR47 (15.247)


File: Mikrotikls RBSXT5nDr2 TstRpt 120911

SN: 3B5501DDAF1/236 FCC ID#: TV7SXT-5ND Date: January 29, 2013

Page 11 of 32



# Diagram 3 Test arrangement for radiated emissions tested on Open Area Test Site (OATS)



Rogers Labs, Inc. 4405 W. 259th Terrace Louisburg, KS 66053 Phone/Fax: (913) 837-3214

Revision 1

Mikrotikls SIA

Model: RouterBOARD SXT 5nD r2

Test #: 120917

Test to: CFR47 (15.247) File: Mikrotikls RBSXT5nDr2 TstRpt 120911 SN: 3B5501DDAF1/236 FCC ID#: TV7SXT-5ND Date: January 29, 2013

Page 12 of 32



# **List of Test Equipment**

A Rohde and Schwarz ESU40 and/or Hewlett Packard 8591EM was used as the measuring device for the emissions testing of frequencies below 1 GHz. A Rohde and Schwarz ESU40 and/or Hewlett Packard 8562A Spectrum Analyzer was used as the measuring device for testing the emissions at frequencies above 1 GHz. The analyzer settings used are described in the following table. Refer to the appendix for a complete list of test equipment.

AC Line Conducted Emissions (0.150 -30 MHz)				
RBW	AVG. BW Detector Function			
9 kHz	30 kHz	Peak / Quasi Peak		
	Emissions (30-1000 MHz)			
RBW	AVG. BW	Detector Function		
120 kHz	300 kHz	Peak / Quasi Peak		
	Emissions (Above 1000 MHz)			
RBW	Video BW	Detector Function		
100 kHz	100 kHz	Peak		
1 MHz	1 MHz	Peak / Average		

<b>Equipment</b>	<u>Manufacturer</u>	<u>Model</u>	<b>Band</b>	Cal Date	<u>Due</u>
LISN	Comp. Design I	FCC-LISN-2-MOD.CD	.15-30MHz	10/11	10/12
Antenna	ARA	BCD-235-B	20-350MHz	10/11	10/12
Antenna	EMCO	3147	200-1000MHz	10/11	10/12
Antenna 🔀	Com Power	AH-118	1-18 GHz	10/11	10/12
Antenna	Com Power	AH-840	18-40 GHz	10/11	10/12
Antenna	Standard	FXRY638A	10-18 GHz	3/12	5/13
Antenna	EMCO	6509	.001-30  MHz	2/12	2/13
Antenna	EMCO	3143	20-1200 MHz	5/12	5/13
Antenna	Sunol	JB-6	30-1000 MHz	5/12	5/13
Analyzer	HP	8591EM	9kHz-1.8GHz	5/12	5/13
Analyzer	HP	8562A	9kHz-110GHz	5/12	5/13
Analyzer X	Rohde & Schwarz	z ESU40	20Hz-40GHz	5/12	5/13
Margar Amplifier	Com-Power	PA-010	100Hz-30MHz	10/11	10/12
Margar Amplifier	Com-Power	CPPA-102	1-1000 MHz	10/11	10/12
Margar Amplifier	Com-Power	PA-22	0.5-22 GHz	10/11	10/12

Rogers Labs, Inc. 4405 W. 259th Terrace Louisburg, KS 66053 Phone/Fax: (913) 837-3214

Revision 1

Mikrotikls SIA Model: RouterF Test #: 120917

Model: RouterBOARD SXT 5nD r2

Test to: CFR47 (15.247)

File: Mikrotikls RBSXT5nDr2 TstRpt 120911

SN: 3B5501DDAF1/236 FCC ID#: TV7SXT-5ND Date: January 29, 2013

Page 13 of 32



#### **Intentional Radiators**

As per CFR47, Subpart C, paragraph 15.247 the following information is submitted.

#### Antenna Requirements

The EUT incorporates integral 15-dBi gain antenna system and offers no provision for connection to alternate antenna system. The antenna connection point complies with the unique antenna connection requirements. The requirements are fulfilled there are no deviations or exceptions to the specification.

### Restricted Bands of Operation

Spurious emissions falling in the restricted frequency bands of operation were measured at the OATS. The EUT utilizes frequency, determining circuitry, which generates harmonics falling in the restricted bands. Emissions were investigated at the OATS, using appropriate antennas or pyramidal horns, amplification stages, and a spectrum analyzer. Peak and average amplitudes of frequencies above 1000 MHz were compared to the required limits with worst-case data presented below. Test procedures of ANSI C63.4-2009 paragraphs 13.1 and 8.3.1.2 were used during testing. No other significant emission was observed which fell into the restricted bands of operation. Computed emission values take into account the received radiated field strength, receive antenna correction factor, amplifier gain stage, and test system cable losses.

#### **Restricted Bands Data (General Radiated Emissions)**

Frequency in MHz	Horizontal Peak (dBµV/m)	Horizontal Quasi-Peak (dBµV/m)	Horizontal Average (dBµV/m)	Vertical Peak (dBµV/m)	Vertical Quasi-Peak (dBµV/m)	Vertical Average (dBµV/m)	Limit @ 3m (dBµV/m)
108.8	39.4	35.3	N/A	39.8	35.9	N/A	43.5
137.0	31.7	27.1	N/A	37.6	28.3	N/A	43.5
11490.0	51.8	N/A	38.0	49.1	N/A	36.0	54.0
11570.0	52.2	N/A	38.3	49.2	N/A	36.2	54.0
11650.0	49.9	N/A	36.7	49.6	N/A	36.2	54.0
22980.0	38.0	N/A	24.9	38.3	N/A	25.4	54.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded above for frequency range of 30-1000 MHz. Peak and Average amplitude emissions are recorded above for frequency range above 1000 MHz.

Rogers Labs, Inc. Mikrotikls SIA

4405 W. 259th Terrace Model: RouterBOARD SXT 5nD r2

Louisburg, KS 66053 Test #: 120917 FCC ID#: TV7SXT-5ND Phone/Fax: (913) 837-3214 Test to: CFR47 (15.247) Date: January 29, 2013

SN: 3B5501DDAF1/236

Revision 1 File: Mikrotikls RBSXT5nDr2 TstRpt 120911 Page 14 of 32



## Summary of Results for Radiated Emissions in Restricted Bands

The EUT demonstrated compliance with the radiated emissions requirements of CFR 47 Part 15C Intentional Radiators. The EUT demonstrated a minimum margin of -7.6 dB below the radiated emissions requirements in restricted frequency bands. Peak, Quasi-peak, and average amplitudes were checked for compliance with the regulations. Worst-case emissions are reported with other emissions found in the restricted frequency bands at least 20 dB below the requirements.

#### **AC Line Conducted Emissions Procedure**

The EUT was arranged in a typical equipment configuration and placed on a 1 x 1.5-meter wooden bench 80 cm above the conducting ground plane, floor of a screen room. The bench was positioned 40 cm away from the wall of the screen room. The LISN was positioned on the floor of the screen room 80-cm from the rear of the EUT. The manufacturer supplied AC power adapter for the EUT was connected to the LISN. A second LISN was positioned on the floor of the screen room 80-cm from the rear of the supporting equipment of the EUT. All power cords except the EUT were then powered from the second LISN. EMI was coupled to the spectrum analyzer through a 0.1 µF capacitor, internal to the LISN. Power line conducted emissions testing were carried out individually for each current carrying conductor of the EUT. The excess length of lead between the system and the LISN receptacle was folded back and forth to form a bundle not exceeding 40 cm in length. The screen room, conducting ground plane, analyzer, and LISN were bonded together to the protective earth ground. Preliminary testing was performed to identify the frequency of each radio frequency emission displaying the highest amplitude. The cables were repositioned to obtain maximum amplitude of measured EMI level. Once the worstcase configuration was identified, plots were made of the EMI from 0.15 MHz to 30 MHz then the data was recorded with maximum conducted emissions levels. Refer to figures one and two for plots of the AC Power Line conducted emissions of EUT while powered from the manufacturer supplied POE and AC/DC adapter.

Rogers Labs, Inc. 4405 W. 259th Terrace Louisburg, KS 66053 Phone/Fax: (913) 837-3214

Revision 1

Mikrotikls SIA Model: RouterBOARD SXT 5nD r2 Test #: 120917

Test to: CFR47 (15.247)

File: Mikrotikls RBSXT5nDr2 TstRpt 120911

SN: 3B5501DDAF1/236 FCC ID#: TV7SXT-5ND Date: January 29, 2013

Page 15 of 32






Figure One AC Line Conducted Emissions Line 1




Figure Two AC Line Conducted Emissions Line 2

Rogers Labs, Inc. 4405 W. 259th Terrace Louisburg, KS 66053 Phone/Fax: (913) 837-3214

Phone/Fax: (913) 837-32 Revision 1 Mikrotikls SIA

Model: RouterBOARD SXT 5nD r2

Test #: 120917 Test to: CFR47 (15.247)

File: Mikrotikls RBSXT5nDr2 TstRpt 120911

SN: 3B5501DDAF1/236 FCC ID#: TV7SXT-5ND Date: January 29, 2013

Page 16 of 32



# **AC Line Conducted Emissions Data (Highest Emissions)**

Line 1

Trace	Frequenc	у	Level (dBµV)	Detector	Delta Limit/dB
1	430.000000000	kHz	41.09	Quasi Peak	-16.16
2	470.000000000	kHz	35.76	Average	-10.75
1	558.000000000	kHz	44.68	Quasi Peak	-11.32
2	570.000000000	kHz	35.15	Average	-10.85
1	578.000000000	kHz	45.37	Quasi Peak	-10.63
1	958.000000000	kHz	41.96	Quasi Peak	-14.04
1	974.000000000	kHz	40.02	Quasi Peak	-15.98
1	1.442000000	MHz	39.32	Quasi Peak	-16.68
1	2.618000000	MHz	38.37	Quasi Peak	-17.63
1	4.978000000	MHz	39.48	Quasi Peak	-16.52
1	8.568000000	MHz	42.36	Quasi Peak	-17.64
2	12.752000000	MHz	40.25	Average	-9.75
2	13.376000000	MHz	42.60	Average	-7.40
1	13.444000000	MHz	52.00	Quasi Peak	-8.00
2	13.568000000	MHz	42.69	Average	-7.31
1	13.596000000	MHz	51.80	Quasi Peak	-8.20
2	13.808000000	MHz	42.09	Average	-7.91

Other emissions present had amplitudes at least 20 dB below the limit.

Rogers Labs, Inc. 4405 W. 259th Terrace Louisburg, KS 66053 Phone/Fax: (913) 837-3214

Revision 1

Mikrotikls SIA Model: RouterBOARD SXT 5nD r2

Test #: 120917 Test to: CFR47 (15.247)

File: Mikrotikls RBSXT5nDr2 TstRpt 120911

SN: 3B5501DDAF1/236 FCC ID#: TV7SXT-5ND Date: January 29, 2013

Page 17 of 32



Line 2

Trace	Frequenc	y	Level (dBµV)	Detector	Delta Limit/dB
2	378.000000000	kHz	36.52	Average	-11.80
1	430.000000000	kHz	42.86	Quasi Peak	-14.39
2	466.000000000	kHz	37.97	Average	-8.61
1	554.000000000	kHz	45.44	Quasi Peak	-10.56
2	562.000000000	kHz	36.92	Average	-9.08
2	566.000000000	kHz	37.26	Average	-8.74
1	578.000000000	kHz	46.42	Quasi Peak	-9.58
1	958.000000000	kHz	42.65	Quasi Peak	-13.35
1	966.000000000	kHz	41.73	Quasi Peak	-14.27
1	1.450000000	MHz	39.74	Quasi Peak	-16.26
2	12.324000000	MHz	37.00	Average	-13.00
2	12.976000000	MHz	39.47	Average	-10.53
2	13.120000000	MHz	40.00	Average	-10.00
1	13.288000000	MHz	49.93	Quasi Peak	-10.07
2	13.384000000	MHz	40.50	Average	-9.50
2	13.476000000	MHz	40.69	Average	-9.31
1	13.636000000	MHz	50.12	Quasi Peak	-9.88
2	13.736000000	MHz	40.00	Average	-10.00
2	13.920000000	MHz	39.35	Average	-10.65

Other emissions present had amplitudes at least 20 dB below the limit.

# Summary of Results for AC Line Conducted Emissions

The EUT demonstrated compliance to the conducted emissions requirements of CFR47 Part 15C equipment. The EUT demonstrated minimum margin of -7.4 dB below the limit. Measurements were taken using the peak, quasi peak, and average, measurement function for each emissions amplitude and were below the limits stated in the specification. Other emissions were present with recorded data representing worst-case amplitudes.

Rogers Labs, Inc. 4405 W. 259th Terrace Louisburg, KS 66053 Phone/Fax: (913) 837-321

Phone/Fax: (913) 837-3214 Revision 1 Mikrotikls SIA Model: RouterBOARD SXT 5nD r2 Test #: 120917

Test to: CFR47 (15.247)

File: Mikrotikls RBSXT5nDr2 TstRpt 120911

SN: 3B5501DDAF1/236 FCC ID#: TV7SXT-5ND Date: January 29, 2013

Page 18 of 32

NVLAP Lab Code 200087-0

#### General Radiated Emissions Procedure

The EUT was arranged in a typical equipment configuration and operated through all available modes with worst-case data recorded. Preliminary testing was performed in a screen room with the EUT positioned 1 meter from the FSM. Radiated emissions measurements were performed to identify the frequencies, which produced the highest emissions. Plots were made of the radiated frequency spectrum from 30 MHz to 25,000 MHz during the preliminary investigation. Each radiated emission was then maximized at the OATS location before final radiated emissions measurements were performed. Final data was taken with the EUT located at the OATS at a distance of 3 meters between the EUT and the receiving antenna. The frequency spectrum from 9 kHz to 25,000 MHz was searched for general radiated emissions. Measured emission levels were maximized by EUT placement on the table, rotating the turntable through 360 degrees, varying the antenna height between 1 and 4 meters above the ground plane and changing antenna position between horizontal and vertical polarization. Antennas used were Loop from 9 kHz to 30 MHz, Broadband Biconical from 30 to 200 MHz, Biconilog from 30 to 1000 MHz, Log Periodic from 200 MHz to 1 GHz and or double Ridge or pyramidal horns and mixers from 1 GHz to 40 GHz, notch filters and appropriate amplifiers and external mixers were utilized.

Rogers Labs, Inc. 4405 W. 259th Terrace Louisburg, KS 66053 Phone/Fax: (913) 837-3214

Revision 1

Mikrotikls SIA Model: RouterBOARD SXT 5nD r2

Test #: 120917 Test to: CFR47 (15.247)

File: Mikrotikls RBSXT5nDr2 TstRpt 120911

SN: 3B5501DDAF1/236 FCC ID#: TV7SXT-5ND Date: January 29, 2013

Page 19 of 32



### **General Radiated Emissions from EUT Data (Highest Emissions)**

Frequency in MHz	Horizontal Peak (dBµV/m)	Horizontal Quasi-Peak (dBµV/m)	Horizontal Average (dBµV/m)	Vertical Peak (dBµV/m)	Vertical Quasi-Peak (dBµV/m)	Vertical Average (dBµV/m)	Limit @ 3m (dBµV/m)
62.0	35.5	29.4	N/A	37.5	35.0	N/A	40.0
62.7	33.2	30.0	N/A	38.3	36.3	N/A	40.0
77.1	35.1	32.8	N/A	38.7	36.4	N/A	40.0
81.2	32.2	26.1	N/A	39.3	34.8	N/A	40.0
87.3	36.6	31.9	N/A	33.3	29.7	N/A	40.0
90.0	38.7	33.2	N/A	38.3	33.1	N/A	43.5
94.4	42.6	38.3	N/A	43.0	39.5	N/A	43.5
98.2	45.1	40.1	N/A	46.4	41.1	N/A	43.5
99.2	44.4	38.3	N/A	40.4	35.8	N/A	43.5
100.5	45.3	42.0	N/A	43.0	40.5	N/A	43.5
101.8	45.1	40.9	N/A	45.6	41.6	N/A	43.5
103.4	43.8	38.0	N/A	44.6	39.5	N/A	43.5
104.0	43.8	40.9	N/A	45.4	40.1	N/A	43.5
104.7	43.6	41.6	N/A	45.0	40.9	N/A	43.5
108.8	39.4	35.3	N/A	39.8	35.9	N/A	43.5
137.0	31.7	27.1	N/A	37.6	28.3	N/A	43.5
156.0	37.0	32.2	N/A	32.3	28.4	N/A	43.5
157.0	35.9	31.7	N/A	29.7	24.5	N/A	43.5
161.1	37.4	31.7	N/A	27.9	23.2	N/A	43.5
230.0	39.1	34.7	N/A	30.4	24.1	N/A	46.0
233.0	41.1	36.7	N/A	31.7	26.1	N/A	46.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded above for frequency range of 30-1000 MHz. Peak and Average amplitude emissions are recorded above for frequency range above 1000 MHz.

## Summary of Results for General Radiated Emissions

The EUT demonstrated compliance with the radiated emissions requirements of CFR47 Part 15C paragraph 15.209 Intentional Radiators. The EUT demonstrated a minimum margin of -1.5 dB below the requirements. Other emissions were present with amplitudes at least 20 dB below the Limits.

Rogers Labs, Inc. 4405 W. 259th Terrace Louisburg, KS 66053 Phone/Fax: (913) 837-3214

Revision 1

Mikrotikls SIA

Model: RouterBOARD SXT 5nD r2

Test to: CFR47 (15.247)

SN: 3B5501DDAF1/236 Test #: 120917 FCC ID#: TV7SXT-5ND Date: January 29, 2013 File: Mikrotikls RBSXT5nDr2 TstRpt 120911

Page 20 of 32



## Operation in the Band 5725 - 5850 MHz

The power output was measured at the open area test site at a three-meter distance. The EUT was placed on a wooden turntable 0.8 meters above the ground plane at a distance of 3 meters from the FSM antenna. The peak and quasi-peak amplitude of the frequencies below 1000 MHz were measured using a spectrum analyzer. The peak and average amplitude of emissions above 1000 MHz including were measured using a spectrum analyzer. Emissions data was recorded from the measurement results. Plots were made of transmitter performance for reference purposes. Refer to figures three through six showing plots taken of the EUT performance displaying compliance with the specifications. As this product utilizes permanently attached antenna and offers no provision for antenna port measurements. Test procedures as defined in publications KDB 558074 and ANSI C63.10-2009 were utilized for compliance testing. These procedures utilize measurement of maximum field strength and conversion calculation for comparison with requirements.

1. Calculate the transmitter's peak power using the following equation:

$$P = (E * d)^2 / (30 * G)$$

Where: E = the measured maximum field strength in V/m.

G = the numeric gain of the transmitting antenna over an isotropic radiator.

d = the distance in meters from which the field strength was measured.

P =the power in watts

Setting the RBW > 6dB bandwidth of the emission or using a peak power meter

- 2. Emission Bandwidth was measured in compliance with KDB 558074 paragraph 5.1.1.
- 3. Maximum Peak Output Power was measured in compliance with KDB 558074 paragraph 5.2.1.2.
- 4. Maximum Power Spectral Density was measured in compliance with KDB 558074 paragraph 5.3.1.
- 5. Maximum Unwanted Emissions Levels were measured in compliance with KDB 558074 and CFR47 paragraph 15C at 3-meters distance located on the OATS.

Rogers Labs, Inc. 4405 W. 259th Terrace Louisburg, KS 66053

Phone/Fax: (913) 837-3214 Revision 1 Mikrotikls SIA Model: RouterBOARD SXT 5nD r2 Test #: 120917

Test to: CFR47 (15.247) File: Mikrotikls RBSXT5nDr2 TstRpt 120911 SN: 3B5501DDAF1/236 FCC ID#: TV7SXT-5ND Date: January 29, 2013

Page 21 of 32






Figure Three Plot of Transmitter Emissions (Across Operational Band, 20MHz Mode)




Figure Four Plot of Transmitter Emissions (Across Operational Band, 40 MHz Mode)

Rogers Labs, Inc. 4405 W. 259th Terrace Louisburg, KS 66053 Phone/Fax: (913) 837-3214

Revision 1

Mikrotikls SIA

Model: RouterBOARD SXT 5nD r2

Test #: 120917 Test to: CFR47 (15.247)

SN: 3B5501DDAF1/236 FCC ID#: TV7SXT-5ND Date: January 29, 2013 File: Mikrotikls RBSXT5nDr2 TstRpt 120911

Page 22 of 32






Figure Five Plot of Low Band Edge




Figure Six Plot of High Band Edge

Rogers Labs, Inc. 4405 W. 259th Terrace Louisburg, KS 66053

Phone/Fax: (913) 837-3214

Revision 1

Mikrotikls SIA

Model: RouterBOARD SXT 5nD r2

Test #: 120917

Test to: CFR47 (15.247)

File: Mikrotikls RBSXT5nDr2 TstRpt 120911

SN: 3B5501DDAF1/236 FCC ID#: TV7SXT-5ND Date: January 29, 2013

Page 23 of 32



### Transmitter Emissions Data

#### **Calculated Transmitter Antenna Port Power**

Frequency MHz	Calculated Conducted Antenna Port Output Power (Watts)	Occupied Bandwidth (kHz)	Calculated Power Spectral Density (dBm)				
	20 MHz Channel						
5745	0.25	16,466	-1.3				
5785	0.23	16,627	-2.3				
5825	0.21	16,627	-0.9				
	40 M	Hz Channel					
5755	0.24	37,107	-5.7				
5795	0.22	37,107	-4.1				
5815	0.21	37,107	-4.4				

Rogers Labs, Inc. 4405 W. 259th Terrace Louisburg, KS 66053 Phone/Fax: (913) 837-3214

Revision 1

Mikrotikls SIA
Model: RouterB

Model: RouterBOARD SXT 5nD r2

Test #: 120917 Test to: CFR47 (15.247) File: Mikrotikls RBSXT5nDr2 TstRpt 120911 SN: 3B5501DDAF1/236 FCC ID#: TV7SXT-5ND Date: January 29, 2013

Page 24 of 32



#### **Transmitter Radiated Emission**

Frequency in MHz	Horizontal Peak (dBµV/m)	Horizontal Average (dBµV/m)	Vertical Peak (dBµV/m)	Vertical Average (dBµV/m)	Limit @ 3m (dBµV/m)
5745.0	116.4	102.7	131.0	118.6	
11490.0	51.8	38.0	49.1	36.0	54.0
17235.0	54.2	41.4	54.6	41.5	54.0
22980.0	38.0	24.9	38.3	25.4	54.0
28725.0	39.9	26.9	39.7	27.0	54.0
5785.0	114.7	102.5	130.6	118.0	
11570.0	52.2	38.3	49.2	36.2	54.0
17355.0	53.7	41.0	53.7	41.0	54.0
23140.0	38.1	24.1	36.8	24.2	54.0
28925.0	39.8	27.1	40.2	27.3	54.0
5825.0	115.7	103.1	130.1	117.6	
11650.0	49.9	36.7	49.6	36.2	54.0
17475.0	54.3	41.5	54.9	41.6	54.0
23300.0	43.7	40.5	43.3	40.5	54.0
29125.0	48.5	36.0	48.2	36.0	54.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded above for frequency range of 30-1000 MHz. Peak and Average amplitude emissions are recorded above for frequency range above 1000 MHz.

Rogers Labs, Inc. 4405 W. 259th Terrace Louisburg, KS 66053 Phone/Fax: (913) 837-3214

Revision 1

Mikrotikls SIA Model: RouterBOARD SXT 5nD r2

Test #: 120917 Test to: CFR47 (15.247)

File: Mikrotikls RBSXT5nDr2 TstRpt 120911

SN: 3B5501DDAF1/236 FCC ID#: TV7SXT-5ND Date: January 29, 2013

Page 25 of 32

NVLAP Lab Code 200087-0

**Summary of Results for Transmitter Radiated Emissions of Intentional Radiator** 

The EUT demonstrated compliance with the radiated emissions requirements of CFR47 Part 15.247. Calculated Antenna port conducted power of 250 mW (0.25 watts or 24 dBm). The peak power spectral density presented a minimum margin of -8.9 dB below the requirements.

The EUT demonstrated a minimum margin of -12.4 dB below the harmonic emissions requirements. There were no other significantly measurable emissions in the restricted bands other than those recorded in this report. Other emissions were present with amplitudes at least

20 dB below the requirements. There were no other deviations or exceptions to the

requirements.

Statement of Modifications and Deviations

No modifications to the EUT were required for the unit to demonstrate compliance with the CFR47 Part 15C emissions standards. There were no deviations to the specifications.

Rogers Labs, Inc. 4405 W. 259th Terrace Louisburg, KS 66053 Phone/Fax: (913) 837-3214

Revision 1

Mikrotikls SIA Model: RouterBOARD SXT 5nD r2

Test #: 120917 Test to: CFR47 (15.247)

File: Mikrotikls RBSXT5nDr2 TstRpt 120911

SN: 3B5501DDAF1/236 FCC ID#: TV7SXT-5ND Date: January 29, 2013

Page 26 of 32



## **Annex**

- Annex A Measurement Uncertainty Calculations
- Annex B Rogers Labs Test Equipment List
- Annex C Rogers Qualifications
- Annex D FCC Site Registration Letter
- Annex E Industry Canada Site Registration Letter

Rogers Labs, Inc. 4405 W. 259th Terrace Louisburg, KS 66053 Phone/Fax: (913) 837-3214

Revision 1

Mikrotikls SIA Model: RouterBOARD SXT 5nD r2

Test #: 120917

Test to: CFR47 (15.247) File: Mikrotikls RBSXT5nDr2 TstRpt 120911 SN: 3B5501DDAF1/236 FCC ID#: TV7SXT-5ND Date: January 29, 2013

Page 27 of 32



## Annex A Measurement Uncertainty Calculations

Measurement uncertainty calculations were made for the laboratory. Result of measurement uncertainty calculations are recorded below for AC line conducted and radiated emission measurements.

Measurement Uncertainty	U <sub>(E)</sub>	U <sub>(lab)</sub>
3 Meter Horizontal 30-200 MHz Measurements	2.08	4.16
3 Meter Vertical 30-200 MHz Measurements	2.16	4.33
3 Meter Vertical Measurements 200-1000 MHz	2.99	5.97
10 Meter Horizontal Measurements 30-200 MHz	2.07	4.15
10 Meter Vertical Measurements 30-200 MHz	2.06	4.13
10 Meter Horizontal Measurements 200-1000 MHz	2.32	4.64
10 Meter Vertical Measurements 200-1000 MHz	2.33	4.66
3 Meter Measurements 1-6 GHz	2.57	5.14
3 Meter Measurements 6-18 GHz	2.58	5.16
AC Line Conducted	1.72	3.43

Rogers Labs, Inc. 4405 W. 259th Terrace Louisburg, KS 66053 Phone/Fax: (913) 837-3214

Revision 1

Mikrotikls SIA

Model: RouterBOARD SXT 5nD r2 Test #: 120917

Test to: CFR47 (15.247)

File: Mikrotikls RBSXT5nDr2 TstRpt 120911

SN: 3B5501DDAF1/236 FCC ID#: TV7SXT-5ND Date: January 29, 2013

Page 28 of 32



# Annex B Rogers Labs Test Equipment List

The test equipment is maintained in calibration and good operating condition. Use of this calibrated equipment ensures measurements are traceable to national standards.

<b>4 4</b>	s measurements are traceable to national stand	
List of Test Equipment		Calibration Date
Spectrum Analyzer: Rohde		5/12
= -	2A, HP Adapters: 11518, 11519, and 11520	5/12
	970A, 11970K, 11970U, 11970V, 11970W	
Spectrum Analyzer: HP 859	1EM	5/12
Antenna: EMCO Biconilog	Model: 3143	5/12
Antenna: Sunol Biconilog Model: JB6		10/11
Antenna: EMCO Log Periodic Model: 3147		10/11
Antenna: Antenna Research Biconical Model: BCD 235		10/11
LISN: Compliance Design Model: FCC-LISN-2.Mod.cd, 50 µHy/50 ohm/0.		$1/0.1  \mu f  10/11$
R.F. Preamp CPPA-102		10/11
Attenuator: HP Model: HP11509A		10/11
Attenuator: Mini Circuits Model: CAT-3		10/11
Attenuator: Mini Circuits Model: CAT-3		10/11
Cable: Belden RG-58 (L1)		10/11
Cable: Belden RG-58 (L2)		10/11
Cable: Belden 8268 (L3)		10/11
Cable: Time Microwave: 4M-750HF290-750		10/11
Cable: Time Microwave: 4M-750HF290-750		10/11
		2/12
Frequency Counter: Leader LDC825		
Oscilloscope Scope: Tektronix 2230		2/12
Wattmeter: Bird 43 with Load Bird 8085		2/12
Power Supplies: Sorensen SRL 20-25, SRL 40-25, DCR 150, DCR 140		2/12
R.F. Generators: HP 606A, HP 8614A, HP 8640B		2/12
R.F. Power Amp 65W Model: 470-A-1010		2/12
R.F. Power Amp 50W M185- 10-501		2/12
R.F. Power Amp A.R. Model: 10W 1010M7		2/12
R.F. Power Amp EIN Model: A301		2/12
LISN: Compliance Eng. Model 240/20		2/12
LISN: Fischer Custom Communications Model: FCC-LISN-50-16-2-08		2/12
Antenna: EMCO Dipole Set 3121C		2/12
Antenna: C.D. B-101		2/12
Antenna: Solar 9229-1 & 9230-1		2/12
Antenna: EMCO 6509		2/12
Audio Oscillator: H.P. 201CD		2/12
Peavey Power Amp Model: IPS 801		2/12
ELGAR Model: 1751		2/12
ELGAR Model: TG 704A-3D		2/12
ESD Test Set 2010i		2/12
Fast Transient Burst Generator Model: EFT/B-101		2/12
Field Intensity Meter: EFM-018		2/12
KEYTEK Ecat Surge Generator		2/12
Shielded Room 5 M x 3 M x 3.0 M		
Rogers Labs, Inc.	Mikrotikls SIA	
4405 W. 259th Terrace	Model: RouterBOARD SXT 5nD r2	SN: 3B5501DDAF1/236
Louisburg, KS 66053	Test #: 120917	FCC ID#: TV7SXT-5ND
Phone/Fax: (913) 837-3214	Test to: CFR47 (15.247)	Date: January 29, 2013
Revision 1	File: Mikrotikls RBSXT5nDr2 TstRpt 120911	Page 29 of 32

NVLAP Lab Code 200087-0

## Annex C Rogers Qualifications

Scot D. Rogers, Engineer

## Rogers Labs, Inc.

Mr. Rogers has approximately 17 years experience in the field of electronics. Engineering experience includes six years in the automated controls industry and remaining years working with the design, development and testing of radio communications and electronic equipment.

#### Positions Held

Systems Engineer: A/C Controls Mfg. Co., Inc. 6 Years

Electrical Engineer: Rogers Consulting Labs, Inc. 5 Years

Electrical Engineer: Rogers Labs, Inc. Current

## **Educational Background**

- 1) Bachelor of Science Degree in Electrical Engineering from Kansas State University.
- 2) Bachelor of Science Degree in Business Administration Kansas State University.
- 3) Several Specialized Training courses and seminars pertaining to Microprocessors and Software programming.

Scot D. Rogers

Scot DRogers

Revision 1

Page 30 of 32

NVLAP Lab Code 200087-0

## Annex D FCC Site Registration Letter

### FEDERAL COMMUNICATIONS COMMISSION

**Laboratory Division** 7435 Oakland Mills Road Columbia, MD 21046

November 01, 2011

Registration Number: 90910

Rogers Labs, Inc. 4405 West 259th Terrace, Louisburg, KS 66053

Attention:

Scot Rogers,

Re:

Measurement facility located at Louisburg

3 & 10 meter site

Date of Renewal: November 01, 2011

#### Dear Sir or Madam:

Your request for renewal of the registration of the subject measurement facility has been received. The information submitted has been placed in your file and the registration has been renewed. The name of your organization will remain on the list of facilities whose measurement data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Please note that the file must be updated for any changes made to the facility and the registration must be renewed at least every three years.

Measurement facilities that have indicated that they are available to the public to perform measurement services on a fee basis may be found on the FCC website www.fcc.gov under E-Filing, OET Equipment Authorization Electronic Filing, Test Firms.

**Industry Analyst** 

Rogers Labs, Inc. 4405 W. 259th Terrace Louisburg, KS 66053

Phone/Fax: (913) 837-3214

Revision 1

Mikrotikls SIA

Model: RouterBOARD SXT 5nD r2

Test #: 120917

Test to: CFR47 (15.247)

File: Mikrotikls RBSXT5nDr2 TstRpt 120911

SN: 3B5501DDAF1/236 FCC ID#: TV7SXT-5ND

Date: January 29, 2013

Page 31 of 32



## Annex E Industry Canada Site Registration Letter



Industry Canada Industrie Canada

December 28, 2011

OUR FILE: 46405-3041 Submission No: 152685

Rogers Labs Inc. 4405 West 259th Terrance Louisburg, KS, 66053 USA

Attention: Mr. Scot D. Rogers

Dear Sir/Madame:

The Bureau has received your application for the renewal of 3/10m OATS. Be advised that the information received was satisfactory to Industry Canada. The following number(s) is now associated to the site(s) for which registration / renewal was sought ( Site# 3041A-1 ). Please reference the appropriate site number in the body of test reports containing measurements performed on the site. In addition, please keep for your records the following information;

- The company address code associated to the site(s) located at the above address is: 3041A

Furthermore, to obtain or renew a unique site number, the applicant shall demonstrate that the site has been accredited to ANSI C63.4-2003 or later. A scope of accreditation indicating the accreditation by a recognized accreditation body to ANSI C63.4-2003 or later shall be accepted. Please indicate in a letter the previous assigned site number if applicable and the type of site (example: 3 metre OATS or 3 metre chamber). If the test facility is not accredited to ANSI C63.4-2003 or later, the test facility shall submit test data demonstrating full compliance with the ANSI standard. The Bureau will evaluate the filing to determine if recognition shall be granted.

The frequency for re-validation of the test site and the information that is required to be filed or retained by the testing party shall comply with the requirements established by the accrediting organization. However, in all cases, test site re-validation shall occur on an interval not to **exceed three years**. There is no fee or form associated with an OATS filing. OATS submissions are encouraged to be submitted electronically to the Bureau using the following URL;

http://strategis.ic.gc.ca/epic/internet/inceb-bhst.nsf/en/h\_tt00052e.html.

If you have any questions, you may contact the Bureau by e-mail at <a href="mailto:certification.bureau@ic.gc.ca">certification.bureau@ic.gc.ca</a> Please reference our file and submission number above for all correspondence.

Yours sincerely,

Dalwinder Gill

Revision 1

For: Wireless Laboratory Manager Certification and Engineering Bureau 3701 Carling Ave., Building 94 P.O. Box 11490, Station "H" Ottawa, Ontario K2H 8S2 Email: dalwinder.gill@ic.gc.ca Tel. No. (613) 998-8363

Rogers Labs, Inc. 4405 W. 259th Terrace Louisburg, KS 66053 Phone/Fax: (913) 837-3214

Fax. No. (613) 990-4752

Mikrotikls SIA

Model: RouterBOARD SXT 5nD r2

Test #: 120917 Test to: CFR47 (15.247)

File: Mikrotikls RBSXT5nDr2 TstRpt 120911

SN: 3B5501DDAF1/236 FCC ID#: TV7SXT-5ND Date: January 29, 2013

Page 32 of 32