




Test Report

Report No	EF0764-2
Client	LS Starrett 121 Crescent Street Athol, MA 01331
Phone	978-249-3551
FRN	0014116503
	<u>RSS-210 Issue 6; FCC Part 15.249</u>
Model	1500-2
FCC ID	TV81500-2
IC	6164A-15002
Equipment Type	Low Power Communications Device Transmitter
Equipment Code	DXX
Emission Designator	K1D
Results	As detailed within this report
Prepared by	 David Harris – Test Engineer
Authorized by	 Michael Buchholz – EMC Manager
Issue Date	1/17/06
Conditions of issue	This Test Report is issued subject to the conditions stated in 'terms and conditions' section of this report.

Curtis-Straus LLC is accredited by the American Association for Laboratory Accreditation for the specific scope of accreditation under Certificate Number 1627-01. This report may contain data which is not covered by the A2LA accreditation.

Curtis-Straus LLC • 527 Great Road • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



Table of Contents

<i>Summary</i>	3
<i>Test Methodology</i>	3
<i>Statement of Conformity</i>	4
<i>EUT Configuration</i>	5
<i>Fundamental Measurement</i>	6
<i>Band Edge Measurements</i>	6
<i>Radiated Spurious Emissions</i>	7
<i>AC Line Conducted Emissions</i>	9
<i>Voltage Variations</i>	10
<i>Test Equipment Used</i>	11
<i>Terms And Conditions</i>	13
<i>A2LA Accreditation</i>	15

Summary

This test report supports an application for certification of a transmitter operating pursuant to 47 CFR 15.249 and RSS-210(A2.9). The product is the Router, MN 1500-2. It is a transmitter that operates at 916.5 MHz.

Test Methodology

Radiated emissions testing are performed according to the procedures specified in ANSI C63.4 (2003) and RSS-GEN. Emissions were maximized by rotating the device around three orthogonal axes as well as varying the test antenna's height and polarity. The environmental conditions are shown below.

Date	Temperature (°c)	Humidity (%)
10/13/05	23.4	43
10/19/05	24.7	34
10/28/05	23.4	25
10/31/05	24.9	27

Frequency range investigated: 0.15MHz – 10GHz

Measurement distance:	0.15 – 30MHz	Conducted
	30MHz – 3GHz	3m
	3 – 10GHz	1m

EUT antenna was varied and maximized during testing.



Statement of Conformity

The Router, MN 1500-2 has been found to conform to the following parts:

RSS-GEN	RSS 210	Part 15	Comments
5.3		15.15(b)	There are no controls accessible to the user that vary the output power.
5.2		15.19	The label is shown in the label exhibit.
7.1.5		15.21	Information to the user is shown in the instruction manual exhibit.
		15.27	No special accessories are required for compliance.
7.1.4		15.203	The antenna connector for this device is inaccessible to the user, see below.
	2.6	15.205 15.209	The fundamental is not in a Restricted band and the spurious and harmonic emissions in the Restricted bands comply with the general emission limits of 15.209.
7.2.2		15.207	EUT meets the AC Line conducted emissions requirements of 15.207.
	A2.9	15.249	The unit complies with the requirements of 15.249

The antenna is not hard wired to the PCB, but the connection is inside the box. See picture below.



EUT Configuration**EUT Configuration****Work Order:** F0764**Company:** LS Starrett**Company Address:** 121 Crescent Street

Athol, MA 01331

Contact: John Belliveau**MN SN****EUT:**

Powered by 5Vdc Adapter 1500-2-N Sample 1

Unifive power supply UL310-0515 -

Powered by 24VAC 1500-2-HN Sample 1

Small Unit, Powered by Battery 1500-2-SN Sample 1

EUT Description: Router**EUT Max Frequency:** 916.6MHz**Support Equipment:** **MN SN**

None

EUT Cables:	Qty	Shielded?	Length	Ferrites
DC	1	No	2 m	None
24Vac Power Cable	1	No	3m	None

Unpopulated EUT Ports: **Qty Reason**

None

Software / Operating Mode Description:

EUT was running in the transmit mode specified by the test. The modes available are: sleep, ASK transmit, OOK transmit, and receive. Unless otherwise stated the EUT was operating in ASK transmit mode which is the maximum transmitted power level mode.

The differences for the Router models are the way that it is powered. For all models of the Router the transmitter portion of the unit is the same, therefore only spurious emissions testing was done on the 1500-2-HN, and SN. All Radio related testing and spurious emissions testing was done on the 1500-2-N.

Fundamental Measurement**LIMIT**QuasiPeak: 93.9dB μ V/m @ 3m [15.35(b)]**MEASUREMENTS**

Fundamental								Curtis-Straus LLC							
Date: 13-Oct-05			Company: LS Starrett					Work Order: F0764							
Engineer: Mairaj Hussain															
EUT Desc: Router MN 1500-2-N															
Measurement Distance: 3 m															
Notes: RBW: 120KHz; VBW: 1MHz								EUT Max Freq: 916.6MHz							
Antenna Polarization (H / V)	Frequency (MHz)	Reading (dB μ V)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Reading (dB μ V/m)				FCC Class B					
Vpk	916.6	63.2	0.0	21.7	4.6	89.5				Limit (dB μ V/m)					
										Margin (dB)					
										Result (Pass/Fail)					
								94.0	-4.5	Pass					
Table Result: Pass by -4.5 dB								Worst Freq: 916.6 MHz							
Test Site: "F"			Pre-Amp: none			Cable: EMIR-04			Analyzer: Black						
									Antenna: Green						

Band Edge Measurements**LIMITS**QuasiPeak limit: FCC Class B limits 46dB μ V/m @ 3m [15.35(b)]**MEASUREMENTS**

Band Edges								Curtis-Straus LLC							
Date: 13-Oct-05			Company: LS Starrett					Work Order: F0764							
Engineer: Mairaj Hussain															
EUT Desc: Router MN 1500-2-N															
Measurement Distance: 3 m															
Notes: EUT Max Freq: 916.6MHz															
Antenna Polarization (H / V)	Frequency (MHz)	Reading (dB μ V)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Reading (dB μ V/m)				FCC Class B					
Vpk	902.0	18.8	20.7	21.6	4.5	24.2				Limit (dB μ V/m)					
Vpk	928.0	17.9	20.6	21.8	4.7	23.8				Margin (dB)					
								46.0	-21.8	Pass					
								46.0	-22.2	Pass					
Table Result: Pass by -21.8 dB								Worst Freq: 902.0 MHz							
Test Site: "F"			Pre-Amp: Green			Cable: EMIR-04			Analyzer: Black						
									Antenna: Green						

Radiated Spurious Emissions

LIMITS

Average (above 1000MHz): $500\mu\text{V}/\text{m} = 53.9\text{dB}\mu\text{V}/\text{m}$ @ 3m [15.249(a), (b), and (d)]

QuasiPeak limit (30-1000MHz): FCC Class B limits @ 3m [15.35(b)]

Note: If Peak measurements meet Average limits, then Average measurements are not required.

MEASUREMENTS

Radiated Emissions Table										Curtis-Straus LLC									
Date: 19-Oct-05			Company: LS Starret				Work Order: F0764												
Engineer: David Harris			EUT Desc: Router MN 1500-2-SN																
Frequency Range: 30-1000MHz							Measurement Distance: 3 m												
Notes: Tested with Gateway MN 1500-1-M							EUT Max Freq: 916.6MHz												
Antenna Polarization (H / V)	Frequency (MHz)	Reading (dB μ V)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Reading (dB μ V/m)				FCC Class B									
H	65.3	29.1	21.5	8.3	1.0	16.9				40.0	-23.1	Pass							
	113.7	33.6	21.5	12.9	1.3	26.3				43.5	-17.2	Pass							
	117.88	38.5	21.5	13.5	1.4	31.9				43.5	-11.6	Pass							
	136.68	35.8	21.5	14.2	1.5	30.0				43.5	-13.5	Pass							
	332.151	26.5	21.3	14.7	2.4	22.3				46.0	-23.7	Pass							
	364.75	28.2	21.2	15.6	2.6	25.2				46.0	-20.8	Pass							
	562.8	28.2	21.0	18.9	3.4	29.5				46.0	-16.5	Pass							
	586.37	30.2	20.9	19.3	3.5	32.1				46.0	-13.9	Pass							
	846.97	29.7	20.6	22.3	4.4	35.8				46.0	-10.2	Pass							
	960.0	31.7	20.6	23.4	4.7	39.2				46.0	-6.8	Pass							
	1009.0	27.6	20.5	24.3	4.9	36.3				54.0	-17.7	Pass							
Table Result: Pass by -6.8 dB							Worst Freq: 960.0 MHz												
Test Site: "F"	Pre-Amp: Green	Cable: EMIR-04	Analyzer: Green				Antenna: Red-White												

Radiated Emissions Table										Curtis-Straus LLC									
Date: 19-Oct-05			Company: LS Starret				Work Order: F0764												
Engineer: David Harris			EUT Desc: Router MN 1500-2-N																
Frequency Range: 1-10GHz							Measurement Distance: 3 m												
Notes: Tested with Gateway MN 1500-1-M							EUT Max Freq: 916.6MHz												
Antenna Polarization (H / V)	Frequency (MHz)	Reading (dB μ V)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Reading (dB μ V/m)				FCC Class B									
H	1065.0	42.5	38.3	25.6	1.3	31.1				54.0	-22.9	Pass							
	1260.0	40.0	38.2	26.1	1.5	29.4				54.0	-24.6	Pass							
	1597.0	39.7	39.1	27.1	1.8	29.5				54.0	-24.5	Pass							
	2064.0	50.1	39.4	28.9	2.0	41.6				54.0	-12.4	Pass							
Table Result: Pass by -12.4 dB							Worst Freq: 2064.0 MHz												
Test Site: "F"	Pre-Amp: Brown	Cable: EMIR-HIGH 3	Analyzer: Green				Antenna: Orange Horn												

Radiated Emissions Table

Curtis-Straus LLC

Date: 31-Oct-05 Company: LS Starrett
 Engineer: David Harris EUT Desc: Router MN 1500-2-N

Work Order: F0764

Frequency Range: 30-10000MHz

Measurement Distance: 3 m

Notes: Tested in TX and RX mode. There was no change in emissions

EUT Max Freq: 916.3MHz

Antenna Polarization (H / V)	Frequency (MHz)	Reading (dB μ V)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Reading (dB μ V/m)				FCC Class B		
										Limit (dB μ V/m)	Margin (dB)	Result (Pass/Fail)
H	42.1	42.1	22.2	13.3	0.9	34.1				40.0	-5.9	Pass
H	57.0	41.9	22.2	7.6	1.0	28.3				40.0	-11.7	Pass
H	107.6	40.7	22.2	11.9	1.4	31.8				43.5	-11.7	Pass
V	110.0	34.6	22.2	12.1	1.4	25.9				43.5	-17.6	Pass
H	199.8	33.5	22.2	10.6	1.9	23.8				43.5	-19.7	Pass
V	202.2	29.0	22.2	10.7	1.9	19.4				43.5	-24.1	Pass

Table Result: Pass by -5.9 dB

Worst Freq: 42.1 MHz

Test Site: "M"

Pre-Amp: Blue

Cable: EMIR-02

Analyzer: White

Antenna: Green

AC Line Conducted Emissions**LIMITS**

Frequency of emission (MHz)	Quasi-peak limit (dB μ V)	Average limit (dB μ V)
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

[47 CFR 15.207(a)]

MEASUREMENTS**AC Mains Conducted Emissions****Curtis-Straus LLC**

Date: 28-Oct-05		Company: LS Starrett		Work Order: F0764								
Engineer: David Harris		EUT Desc: Router MN 1500-2-N		Test Site: EMI 1								
Notes:												
LISN(s): Brown												
Range: 0.15-30MHz	Other Equipment: ---	Spectrum Analyzer: Red										
Frequency (MHz)	Q.P. Readings QP1 (dB μ V)	QP2 (dB μ V)	Ave. Readings AV1 (dB μ V)	AV2 (dB μ V)	Impedance Factor (dB)			FCC/CISPR B qp Limit (dB μ V)	qp Margin dB	FCC/CISPR B AVE Limit (dB μ V)	AVE Margin dB	Overall Result (Pass/Fail)
0.19	36.9	34.8	25.8	29.0	20.0			64.0	-7.1	54.0	-5.0	Pass
0.71	16.7	22.4	14.3	17.5	20.0			56.0	-13.6	46.0	-8.5	Pass
3.44	21.5	20.5	7.9	7.7	20.0			56.0	-14.6	46.0	-18.1	Pass
10.00	10.5	9.3			20.0			60.0	-29.6	50.0	-19.6	Pass
15.00	6.7	7.7			20.0			60.0	-32.3	50.0	-22.3	Pass
25.00	10.5	7.5			20.0			60.0	-29.5	50.0	-19.5	Pass

Table Result: Pass by -5.04 dB

Worst Freq: 0.19 MHz

Measurements were made using a 50 ohm, 50uH LISN.

Voltage Variations

Voltage Variations			Curtis-Straus LLC			
Date: 31-Oct-05			Company: LS Starret			
Engineer: David Harris			EUT Desc: Router 1500-2-N			
Work Order: F0764						
Notes:						
Variation from Nominal (%)	Frequency (MHz)	Reading (dB μ V)	Voltage (Vdc)	Difference (%)		Result
0	916.3	65.2	5.000			Pass
+15	916.3	65.2	5.750	0.0		Pass
-15	916.3	65.0	4.250	0.3		Pass
Test Site: "EMC 1"		Analyzer: Blue	Antenna: Black Horn			

Voltage Variations			Curtis-Straus LLC			
Date: 31-Oct-05			Company: LS Starret			
Engineer: David Harris			EUT Desc: Router 1500-2-HN			
Work Order: F0764						
Notes:						
Variation from Nominal (%)	Frequency (MHz)	Reading (dB μ V)	Voltage (Vdc)	Difference (%)		Result
0	916.3	65.5	24.000			Pass
+15	916.3	65.8	27.600	0.5		Pass
-15	916.3	65.8	20.400	0.5		Pass
Test Site: "EMC 1"		Analyzer: Blue	Antenna: Black Horn			

Test Equipment Used

REV. 05-OCT-2005

SPECTRUM ANALYZERS / RECEIVERS	RANGE	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
RED	9kHz-1.8GHz	8591E	HP	3441A03559	00024	I	13-JAN-2006
WHITE	9kHz-22GHz	8593E	HP	3547U01252	00022	I	08-MAR-2006
BLUE	9kHz-1.8GHz	8591E	HP	3223A00227	00070	I	03-NOV-2005
YELLOW	9kHz-2.9GHz	8594E	HP	3523A01958	00100	I	20-APR-2006
GREEN	9kHz-26.5GHz	8593E	HP	3829A03618	00143	I	02-AUG-2006
BLACK	9kHz-12.8GHz	8596E	HP	3710A00944	00337	I	27-DEC-2005
YELLOW-BLACK	20Hz-40.0MHz	3585A	HP	2504A05219	00030	I	Out of Service
TELECOM 3585A	20Hz-40.0MHz	3585A	HP	1750A02762	01067	I	04-FEB-2006
ORANGE	9kHz-26.5GHz	E4407B	HP	US39440975	00394	I	22-JUN-2006
EMI TEST RECEIVER	20-1000MHz	ESVS30	R&S	827957/001	01098	I	27-OCT-2005
LISNs/MEASUREMENT PROBES	RANGE	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
RED	10kHz-30MHz	8012-50-R-24-BNC	SOLAR	956348	00753	II	15-APR-2006
BLUE (DC)	10kHz-30MHz	8012-50-R-24-BNC	SOLAR	956349	00752	II	02-MAY-2006
YELLOW-BLACK	10kHz-30MHz	8012-50-R-24-BNC	SOLAR	984735	00248	II	15-APR-2006
ORANGE	10kHz-30MHz	8012-50-R-24-BNC	SOLAR	903707	00754	II	02-MAY-2006
GOLD (DC)	10kHz-30MHz	8012-50-R-24-BNC	SOLAR	984734	00247	II	02-MAY-2006
BROWN	10kHz-30MHz	8012-50-R-24-BNC	SOLAR	0411656	00986	II	04-MAY-2006
GREEN	10kHz-30MHz	8012-50-R-24-BNC	SOLAR	0411657	00987	II	04-MAY-2006
YELLOW	10kHz-30MHz	8012-50-R-24-BNC	SOLAR	0411658	1080	II	04-MAY-2006
WHITE-BLACK	10kHz-30MHz	8610-50-TS-100-N	SOLAR	972019	00678	II	15-APR-2006
BLACK	10kHz-30MHz	8610-50-TS-100-N	SOLAR	972017	00675	II	15-APR-2006
RED-BLACK	10kHz-30MHz	8610-50-TS-100-N	SOLAR	972016	00677	II	15-APR-2006
BLUE-BLACK	10kHz-30MHz	8610-50-TS-100-N	SOLAR	972018	00676	II	15-APR-2006
BLUE MONITORING PROBE	0.01-150MHz	91550-2	TEGAM	12350	00807	I	26-MAY-2007
YELLOW MONITORING PROBE	0.01-150MHz	91550-2	ETS	50972	00493	I	24-NOV-2005
GREEN CURRENT TRANSFORMER	40Hz-20MHz	150	PEARSON	10226	00793	I	07-APR-2007
BLUE CISPR LINE PROBE	150kHz-30MHz	N/A	C-S	N/A	00805	II	08-JUN-2007
BLACK CISPR LINE PROBE	150kHz-30MHz	N/A	C-S	N/A	NONE	II	08-JUN-2007
CISPR TELCO VOLTAGE PROBE	10kHz-30MHz	CS A/C-10	C-S	CS01	00296	II	30-SEP-2006
CISPR 22 TELCO ISN	9kHz-30MHz	FCC-TLISN-T4	FISCHER	20115	00746	I	26-OCT-2006
OPEN AREA TEST SITE (OATS)	FCC CODE	IC CODE	VCCI CODE	CAT	CALIBRATION DUE		
SITE F	93448	IC 2762-F	R-1688	II	04-APR-2007		
SITE T	93448	IC 2762-T	R-905	II	14-AUG-2007		
SITE A	93448	IC 2762-A	R-903	II	13-AUG-2007		
SITE M	93448	IC 2762-M	R-904	II	19-MAR-2007		
LINE CONDUCTED TEST SITES	FCC CODE	IC CODE	VCCI CODE	CAT	CALIBRATION DUE		
EMI 1	93448	N/A	C-1801	II	01-MAY-2006		
EMI 2	93448	N/A	C-1802	II	01-MAY-2006		
EMI 3	93448	N/A	C-1803	II	01-MAY-2006		
MIXERS/DIPLEXERS	RANGE	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
MIXER / HORN	26.5-40 GHz	11970A/28-442-6	HP/ATM	2332A01695/A046903-01	1087	I	23-AUG-2006
MIXER / HORN	26.5-40 GHz	11970A/28-442-6	HP/ATM	3003A07825/A046903-01	1086	I	23-AUG-2006
MIXER / HORN	40-60 GHz	M19HW/A	OML	U30110-1	00821	I	02-MAR-2007
MIXER / HORN	60-90 GHz	M12HW/A	OML	E30110-1	00822	I	03-MAR-2007
MIXER / HORN	90-140 GHz	MO8HW/A	OML	F21206-1	00811	I	03-MAR-2007
MIXER / HORN	140-220 GHz	MO5HW/A	OML	G21206-1	00812	II	OUT OF CALIBRATION
DIPLEXER	40-220 GHz	DPL.26	OML	N/A	00813	I	03-MAR-2007
PREAMPS / ATTENUATORS / FILTERS	RANGE	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
RED	0.10-2000MHz	ZFL-1000-LN	C-S	N/A	00798	II	08-APR-2006
BLUE	0.01-2000MHz	ZFL-1000-LN	C-S	N/A	00759	II	03-AUG-2006
BLUE-BLACK	0.01-2000MHz	ZFL-1000-LN	C-S	N/A	00800	II	10-FEB-2006
GREEN	0.01-2000MHz	ZFL-1000-LN	C-S	N/A	00802	II	21-JUL-2006
BLACK	0.01-2000MHz	ZFL-1000-LN	C-S	N/A	00799	II	25-AUG-2006

ORANGE	0.01-2000MHz	ZFL-1000-LN	C-S	N/A	00765	II	10-FEB-2006
WHITE	1-20GHz	SMC-12A	C-S	426643	00760	II	04-AUG-2006
BROWN	1-20GHz	PM2-38-218-4R5-17-15-SFF	C-S	PL1655	1132	II	27-JUN-2006
YELLOW-BLACK	1-20GHz	SMC-12A	C-S	535055	00801	II	25-AUG-2006
HF (YELLOW)	18-26.5GHz	AFS4-18002650-60-8P-4	C-S	467559	00758	II	23-AUG-2007
HIGH PASS FILTER	1-18 GHz	SPA-F-55204	K&L	36	00817	II	06-JAN-2006
LOW PASS FILTER	1-9 GHz	11SL10-4100/X4400-O/O	K&L	4	00816	II	06-JAN-2006
HF 20dB 50W ATTENUATOR	0.03-20 GHz	PE 7019-20	PASTERNAK	01	00791	II	10-MAY-2007
HF 30dB 50W ATTENUATOR	0.03-20 GHz	PE 7019-30	PASTERNAK	02	1168	II	10-MAY-2007
LOW FREQ LPF	10-100kHz	L200K1G1	MICROWAVE CIRCUITS	4460-01 DC0432	1019	II	OUT OF SERVICE
LOW FREQ LPF	10-100kHz	L200K1G1	MICROWAVE CIRCUITS	4777-01 DC0434	1088	II	30-AUG-2006

ANTENNAS	RANGE	MN	MFR	SN	ASSET	CA T	CALIBRATION DUE
GREEN BILOG	30-2000MHz	CBL6112B	CHASE	2742	00620	II	06-APR-2006
GREEN-BLACK BILOG	30-2000MHz	CBL6112B	CHASE	2412	00127	II	06-JAN-2006
GREEN-RED BILOG	30-2000MHz	CBL6112B	CHASE	2435	00990	II	OUT OF SERVICE
BLUE BILOG	30-1000MHz	3143	EMCO	1271	00803	II	06-MAY-2007
GRAY BILOG	20-2000MHz	3141	EMCO	9703-1038	00066	II	06-MAY-2007(EMI) / 05-AUG-2006(RFI)
YELLOW-BLACK BILOG	20-2000MHz	CBL6140A	CHASE	1112	00126	II	06-MAY-2007(EMI) / 12-AUG-2006(RFI)
RED-WHITE BILOG	30-2000MHz	JB1	SUNOL	A091604-1	01105	II	28-SEP-2006
RED-BLACK BILOG	30-2000MHz	JB1	SUNOL	A091604-2	01106	II	28-SEP-2006
YELLOW HORN	1-18GHz	3115	EMCO	9608-4898	00037	I	27-MAY-2007(EMI) / 05-JUN-2006 (RFI)
BLACK HORN	1-18GHz	3115	EMCO	9703-5148	00056	I	17-JUN-2007
ORANGE HORN	1-18GHz	3115	EMCO	0004-6123	00390	I	09-JUN-2007
HF (WHITE) HORN	18-26.5GHz	801-WLM	WAVELINE	00758	00758	I	26-AUG-2007
SMALL LOOP	9kHz-30MHz	PLA-130/A	ARA	1024	00755	I	23-FEB-2006
LARGE LOOP	20Hz-5MHz	6511	EMCO	9704-1154	00067	I	12-NOV-2005
ACTIVE MONPOLE	30Hz-30MHz	3301B	EMCO	3824	00068	II	04-MAY-2006
INDUCTION COIL	50-60Hz	1000-4-8	C-S	N/A	00778	II	26-SEP-2007
ADJUSTABLE DIPOLE	30-1000MHz	3121C	EMCO	1370	00757	II	18-MAR-2007
ADJUSTABLE DIPOLE	30-1000MHz	3121C	EMCO	1371	00756	II	18-MAR-2007
RE101 LOOP SENSOR	30Hz-100kHz	RE101-13.3CM	C-S	N/A	00818	II	13-MAR-2007
RS101 RADIATING LOOP	30Hz-100kHz	RS101-12CM	C-S	N/A	00819	II	13-MAR-2007
RS101 LOOP SENSOR	30Hz-100kHz	RS101-4CM	C-S	N/A	00820	II	13-MAR-2007

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.

Terms And Conditions

Paragraph 1. SERVICES. LABORATORY will:

- 1.1 Use the degree of care and skill ordinarily exercised by and consistent with the standards of the profession.
- 1.2 Perform all technical services in substantial accordance with the generally accepted laboratory principles and practices.
- 1.3 Retain all pertinent records relating to the services performed for a period of three (3) years following submission of the report describing such services, during which period the records will be made available to CLIENT upon reasonable request.

Paragraph 2. CLIENT'S RESPONSIBILITIES. CLIENT or his authorized representative will:

- 2.1 Provide LABORATORY with all plans, schematics, specifications, addenda, change orders, drawings and other information for the proper performance of technical services.
- 2.2 Designate a person to act as CLIENT's representative with respect to LABORATORY's services to be performed on behalf of the CLIENT; such person or firm to have complete authority to transmit instructions, receive information and data, interpret and define CLIENT's policies and decisions with respect to the LABORATORY's work on behalf of the CLIENT and to order, at CLIENT's expense, such technical services as may be required.
- 2.3 Designate a person who is authorized to receive copies of LABORATORY's reports.
- 2.4 Undertake the following:
 - (a) Secure and deliver to LABORATORY, without cost to LABORATORY, preliminary representative samples of the equipment proposed to require technical services, together with any relevant data.
 - (b) Furnish such labor and equipment needed by LABORATORY to handle samples at the LABORATORY and to facilitate the specified technical services.

Paragraph 3. GENERAL CONDITIONS:

- 3.1 LABORATORY, by the performance of services covered hereunder, does not in any way assume any of those duties or responsibilities customarily vested in the CLIENT, its employees, or any other party, agency or authority.
- 3.2 LABORATORY shall not be responsible for acts of omissions of any other party or parties involved in the design, manufacture or maintenance of the equipment or the failure of any employee, contractor or subcontractor to undertake any aspect of equipment's design, manufacture or maintenance.
- 3.3 LABORATORY is not authorized to revoke, alter, release, enlarge or release any requirement of the equipment's design, manufacture or maintenance unless specifically authorized by CLIENT or his authorized representative.
- 3.4 **THE ONLY WARRANTY MADE BY LABORATORY IN CONNECTION WITH ITS SERVICE PERFORMED HEREUNDER IS THAT IT WILL USE THAT DEGREE OF CARE AND SKILL AS SET FORTH IN PARAGRAPH 1 ABOVE. NO OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE OR INTENDED FOR SERVICES PROVIDED HEREUNDER.**
- 3.5 Where the LABORATORY indicates that additional testing is advisable to obtain more valid or useful data, and where such testing has not been authorized, CLIENT agrees to view such test reports as inconclusive and preliminary.
- 3.6 The LABORATORY will supply technical service and prepare a report based solely on the sample submitted to the LABORATORY by the CLIENT. The CLIENT understands that application of the data to other devices is highly speculative and should be applied with extreme caution.
- 3.7 The LABORATORY agrees to exercise ordinary care in receiving, preserving and shipping (F.O.B. Littleton, MA) any sample to be tested, but assumes no responsibility for damages, either direct or consequential, which arise from loss, damage or destruction of the samples due to the act of examination, modification or testing, or technical services or circumstances beyond LABORATORY's control.
- 3.8 The LABORATORY will hold samples for thirty (30) days after tests are completed, or until the CLIENT's outstanding debts to the LABORATORY are satisfied, whichever is later.
- 3.9 The CLIENT recognizes that generally accepted error variances apply and agrees to consider such error variances in its use of test data.
- 3.10 It is agreed between LABORATORY and CLIENT that no distribution of any tests, reports or analysis other than that described below shall be made to any third party without the prior written consent of both parties unless such distribution is mandated by operation of law. It is agreed that tests, reports, or analysis results may be disclosed to third party auditors of the laboratory at the laboratory facility in the course of accreditation maintenance audits. No reference to reports or technical services of the LABORATORY shall be made in any advertising or promotional literature without the express written permission of the LABORATORY.
- 3.11 The CLIENT acknowledges that all employees of LABORATORY operate under employment contracts with the LABORATORY and CLIENT agrees not to solicit employment of such employees or to solicit information related to other clients from said employees.
- 3.12 In recognition of the relative risks and benefits of the project to both CLIENT and LABORATORY, the risks have been allocated such that the CLIENT agrees, to the fullest extent permitted by law, to limit the liability of the LABORATORY to the CLIENT for any and all claims, losses, costs, damages of any nature whatsoever or claims expenses from any cause or causes, including attorneys' fees and costs and expert witness fees and costs, so that the total aggregate liability of the LABORATORY to the CLIENT shall not exceed \$100,000, or the LABORATORY'S total fee for services rendered on this project, whichever is greater. It is intended that this limitation apply to any and all liability or cause of action however alleged or arising, unless otherwise prohibited by law.

Paragraph 4. INSURANCE:

- 4.1 LABORATORY shall secure and maintain throughout the full period of the services provided to the CLIENT adequate insurance to protect it from claims under applicable Workmen's Compensation Acts and also shall maintain one million dollars of general liability coverage to cover claims for bodily injury, death or property damage as may arise from the performance of its services.
- 4.2 The CLIENT hereby warrants that it has sufficient insurance to protect its employees adequately under applicable Workmen's Compensation Acts and for bodily injury, death, or property damage.
- 4.3 No insurance of whatever kind or type, which may be carried by either party is to be considered as in any way limiting any other party's responsibility for damages resulting from their operations or for furnishing work and materials.

Paragraph 5. PAYMENT:

- 5.1 CLIENT shall pay to LABORATORY such fees for services as previously agreed, orally or in writing, within 30 days of presentment of a bill for such services performed. In the event CLIENT ordered, orally or in writing, services but such services were not assigned a rate for billing, such services shall be billed at the LABORATORY's reasonable and customary rate.
- 5.2 CLIENT shall be responsible for all shipping, customs and other expenses related to services provided by LABORATORY to the CLIENT, and shall fully insure any test sample or other equipment provided to LABORATORY by the CLIENT.
- 5.3 Amounts overdue from CLIENT to LABORATORY shall be charged interest at a rate of 1½% per month.

Paragraph 6. ISO/IEC GUIDE 17025 ADDITIONS:

- 6.1 CLIENT agrees that this test report will not be reproduced except in full, without written approval from the LABORATORY.
- 6.2 CLIENT agrees that this test report shall not be used to claim product endorsement by A2LA or ANSI or any agency of the U.S. Government.
- 6.3 CLIENT agrees that test results presented herein relate only to the sample tested by the LABORATORY.

A2LA Accreditation

SCOPE OF ACCREDITATION TO ISO/IEC 17025-1999 CURTIS-STRAUS¹ 527 Great Road Littleton, MA 01460 Barry Quindan Phone: 978-486-8880 ELECTRICAL Valid until: January 31, 2006 Certificate Number: 1627.01		EN 55011 1991, 1998 SABS CISPR 11:1997 Canada ICES-001 1998 CNS13803 AS/NZS 2064: 1997 CSA C108.8 – M1983 CISPR 13:1996, 1998, 2001 EN 55013: 1990, 2001 EN 55013 Amend 12 1994 SABS CISPR 13: 1996 CNS 13439 AS/NZS 1053: 1999 CISPR 14 1993 (except discontinuous disturbances) EN 55014 1993, 1997 discontinuous disturbances AS/NZS 1044: 1995 discontinuous disturbances Immunity CNS13783-1 SABS CISPR 14-1 1993 SABS CISPR 14-2 1997 + A1:2001 EN 61000-6-1: 1997, 2001 EN 61000-6-2: 1998, 2001 EN 50091-2 1996 EN 55024 1998 EN 55103-1 1997 EN 55103-2 1997 (excluding Annex A3) EN 61326 1998 EN 61547 1996 EN 50130-4 1996 EN 55104 1995 EN 50083-2 1995 EN 60601-1-2: 1993, 2002 IEC 1800-3 1995 EN 60555 Part 2 1987 EN 60555 Part 3 1987 EN 61000-3-2: 1995, 2000 AS/NZS 61000.3.2 1998 EN 61000-3-3 1995 AS/NZS 61000.3.3 1999 ETS 300 386-1 1994	Limits and methods of measurement of radio disturbance characteristics of industrial, scientific and medical (ISM) radio-frequency equipment. Industrial, scientific and medical (ISM) radio-frequency equipment – Electromagnetic disturbance characteristics Limits and methods of measurement Industrial, scientific and medical radio frequency generators Industrial, Scientific and Medical Instrument Limits and methods of measurement of electromagnetic disturbance characteristics of industrial, scientific and medical (ISM) radio-frequency equipment. Electromagnetic Emission from Data Processing Equipment and Electronic Office Machines Limits and methods of measurement of radio interference characteristics of sound and television broadcast receivers and associated equipment. Sound and television broadcast receivers and associated equipment: Electromagnetic compatibility. Part 1: Specification for limits and methods of measurement of radio disturbance characteristics of broadcast receivers and associated equipment. Limits and methods of measurement of radio disturbance characteristics of broadcast receivers and associated equipment. Amendment 12 Limits and methods of measurement of radio interference characteristics of sound and television broadcast receivers and associated equipment. Broadcast receiver and associated equipment Limits and methods of measurement of radio interference characteristics of sound and television broadcast receivers and associated equipment. Limits and methods of measurement of radio disturbance characteristics of electrical motor- operated and thermal appliances for household and similar purposes, electric tools and electric apparatus. Limits and methods of measurement of radio disturbance (except characteristics of electrical motor- operated and thermal appliances for household and similar purposes, electric tools and similar electric apparatus. Limits and methods of measurement of radio disturbance (except characteristics of electrical motor- operated and thermal appliances for household and similar purposes, electric tools and similar electric apparatus. Household Electrical Appliances Electromagnetic compatibility – Requirements for household appliances, electric tools and similar apparatus Part 1: Emission – Product family standard Electromagnetic compatibility – Requirements for household appliances, electric tools and similar apparatus Part 2: Immunity – Product family standard
¹ Note: This accreditation covers testing performed at the laboratory listed above and the satellite facility located at 168 Ayer Rd, Littleton, MA 01460		Page 1 of 11	
(A2LA Cert. No. 1627-01) 11/28/05		(A2LA Cert. No. 1627-01) 11/28/05	
Page 2 of 11			
CISPR 14-2 1996, 1997 + A1:2001 CISPR 20: 1995, 2002 with amendment 3 (associated group only) EN 55020: 1995, 2002 (associated group only) CISPR 24 SABS CISPR 24 1997 AS/NZS 3200.1.2: 1995 European Union Basic EMC Standards EN 61000-4-2: 1995, 1999, 2001 EN 61000-4-3:1997, 1998, 2002 AS/NZS 61000.4.3 1999 EN 61000-4-4 1995 EN 61000-4-5 1995 AS/NZS 61000.4.5 1999 EN 61000-4-6 1996 AS/NZS 61000.4.6 1999 EN 61000-4-8 1994 EN 61000-4-11 1994 ENV 61000-2-2 1993 EU Product Family Standards EN 50081-1 1992 EN 50081-2 1993 EN 50082-1 1992, 1998 EN 50082-2 1995		EN 61000-6-1: 1997, 2001 EN 61000-6-2: 1998, 2001 EN 50091-2 1996 EN 55024 1998 EN 55103-1 1997 EN 55103-2 1997 (excluding Annex A3) EN 61326 1998 EN 61547 1996 EN 50130-4 1996 EN 55104 1995 EN 50083-2 1995 EN 60601-1-2: 1993, 2002 IEC 1800-3 1995 EN 60555 Part 2 1987 EN 60555 Part 3 1987 EN 61000-3-2: 1995, 2000 AS/NZS 61000.3.2 1998 EN 61000-3-3 1995 AS/NZS 61000.3.3 1999 ETS 300 386-1 1994	Electromagnetic Compatibility (EMC) – Part 6: Generic standards-Section 1: Immunity for residential, commercial and light-industrial environments Electromagnetic Compatibility (EMC) – Part 6: Generic standards-Section 2: Immunity for industrial environments Specification for Uninterruptible Power Systems (UPS). Part 2: EMC requirements Information technology equipment – Immunity Characteristics – Limits and methods of measurement. Electromagnetic Compatibility – Product family standard for audio, video, audio-visual and entertainment lighting control apparatus for professional use. Part 1: Emission Electromagnetic Compatibility – Product family standard for audio, video, audio-visual and entertainment lighting control professional use. Part 2: Immunity Electrical equipment for measurement, control and laboratory use – EMC requirements Equipment for general lighting purposes – EMC immunity requirements Alarm Systems. Part 4: Electromagnetic compatibility. Product family standard: Immunity requirements for components of fire, intruder and social alarm systems. Electromagnetic compatibility immunity – requirements for household appliances, tools and similar apparatus. Product family standard. Cabled distribution systems for television and sound signals. Part 2: Electromagnetic compatibility for equipment. Medical electrical equipment Part 1: general requirements for safety Section 2: Collateral standard: Electromagnetic compatibility – requirements and tests Adjustable speed electrical power drive systems. Part 3: EMC product standard including specific test methods. Disturbances in supply systems caused by household appliances and similar electrical equipment. Part 2: Harmonics Disturbances in supply systems caused by household appliances and similar electrical equipment. Part 3: Voltage fluctuations. Electromagnetic compatibility (EMC). Part 3: Limits Section 2: Limits for harmonic current emissions Electromagnetic compatibility (EMC). Part 3: Limits Section 2: Limitation of voltage fluctuations and flicker in low-voltage supply systems. Equipment Engineering (EE): Public telecommunication network equipment electro-magnetic compatibility (EMC) requirements Part 1: Product family overview, compliance criteria and test levels
(A2LA Cert. No. 1627-01) 11/28/05		Page 3 of 11	
(A2LA Cert. No. 1627-01) 11/28/05		(A2LA Cert. No. 1627-01) 11/28/05	
Page 4 of 11			



ETS EN 300 386-2 1997, 1998, ETS EN 300 386 2000 v1.2.1, 2001 v1.3.1	Electromagnetic compatibility and radio spectrum matters (ERM); Telecommunication network equipment; Electromagnetic compatibility (EMC) requirements; Part 2: Product family standard.	EN 300 328-2:2001 v1.2.1	Electromagnetic compatibility and Radio spectrum Matters (ERM); Wideband Transmission systems; Data transmission equipment operating in the 2.4 GHz ISM band and using spread spectrum modulation techniques; Part 2: Harmonized EN covering essential requirements under article 3.2 of the R&TTE Directive
ETS 300 132-1 1996	Equipment Engineering (EE); Power supply interface at the input to telecommunications equipment; Part 1: Operated by alternating current (ac) derived from direct current (dc) sources	EN 301 489-1:2002	Electromagnetic compatibility and Radio spectrum Matters (ERM); Electromagnetic Compatibility (EMC) standard for radio equipment and services; Part 1: Common technical requirements
ETS 300 132-2 1996	Equipment Engineering (EE); Power supply interface at the input to telecommunications equipment; Part 2: Operated by direct current (dc)	EN 60669-2-1:2002	Switches for household and similar fixed electrical installations -- Part 2-1: Particular requirements - Electronic switches
ETR 283 1997	Equipment Engineering (EE); Transient voltages at Interface A on telecommunications direct current (DC) power distributions.	<i>Canada Radio Standards</i> Canadian GL-36 1995	
<i>EU radio standards</i> (ETSI) EN 300 385 v1.2.1: 1998, 1999	Electromagnetic compatibility and Radio spectrum matters (ERM); Electromagnetic Compatibility (EMC) standard for fixed radio links and ancillary equipment (ETSI)	Canadian RSS-119 1999, 2000 Issue 6	Industry Canada - technical requirements for low power Devices in the 2400 - 2483.5 MHz band.
EN 300 330 v1.2.1: 1998, 1999	Electromagnetic compatibility and Radio spectrum matters (ERM); Short range devices (SRD); Technical characteristics and test methods for radio equipment in the range 9 kHz to 25 MHz and inductive loop systems in the frequency range 9 kHz to 30 MHz	Canadian RSS-134 1996 & 2000, Issue Rev 1	Industry Canada - Land mobile and fixed radio Transmitters and receivers, 27.41 to 960.0 MHz
ETS 300 328 1996	Radio Equipment and Systems (RES); Wideband transmission systems; Technical characteristics and test conditions for data transmission equipment operating in the 2.4 GHz ISM band and using spread spectrum modulation techniques	Canadian RSS-210 2000 Issue 3, RFS29 1998	Industry Canada - Low power license-exempt radio 2001 Issue 5 communication devices Specification for Restricted Radiation Radio Apparatus (New Zealand)
ETS EN 300 440 v1.2.1 1999	Electromagnetic compatibility and Radio spectrum matters (ERM); Short range devices; Technical characteristics and test methods for radio equipment to be used in the 1 GHz to 40 GHz frequency range	<i>FCC Standards</i>	
EN 301 893:2002 v1.2.1	Broadband Radio Access Networks (BRAN); 5 GHz (draft) high performance RLAN; Harmonized EN covering Essential requirements of article 3.2 of the R&TTE Directive	47 CFR FCC low power transmitters operating on frequencies below 1 GHz, emergency alert systems, unintentional radiators and ISM devices.	Scope A1
ETS 300 836-1:1998	Broadband Radio Access Networks (BRAN); High Performance Radio Local Area Network (HIPERLAN) Type 1; Conformance testing specification; Part 1: Radio Type approval and Radio Frequency (RF) conformance test specification	47 CFR FCC low power transmitters operating on frequencies above 1 GHz, with the exception of spread spectrum devices.	Scope A2
EN 301 489-17:2002 v1.2.1	Electromagnetic compatibility and Radio spectrum Matters (ERM); Electromagnetic Compatibility (EMC) standard for radio equipment and services; Part 17: Specific conditions for 2.4 GHz wideband transmission systems and 5 GHz high performance RLAN equipment	47 CFR FCC Unlicensed Personal Scope Communications System (PCS) devices	A3
		47 CFR FCC Unlicensed National Scope	A4
		Information Infrastructure devices and low power transmitters using spread spectrum techniques.	
		47 CFR FCC Personal mobile Scope Radio Services in the following FCC Rule Parts 22, 24, 25, 27.	B1
		47 CFR FCC General Mobile Radio Scope Services in the following FCC Rule Parts 22, 74, 90, 95, 97.	B2
		47 CFR FCC Maritime and Aviation Scope RadioServices in 47 CFR Parts 80 and 87	B3
		47 CFR FCC Microwave Radio Services Scope in 47 CFR Parts 21, 74 and 101.	B4
(A2LA Cert. No. 1627-01) 11/28/05	Page 5 of 11	(A2LA Cert. No. 1627-01) 11/28/05	Page 6 of 11
FCC/OST MP-5 1986	FCC (Federal Communications Commission) methods Of measurement of radio noise emissions from industrial, scientific and medical equipment.	TIA/EIA-IS-968	Telecommunications Telephone Terminal Equipment Technical Requirements for Connection of Terminal Equipment to the Telephone Network
GR-1089-CORE: 1997, 1999 issue 2/ 2002 Issue 3	Bellcore electromagnetic compatibility and electrical safety - Generic criteria for network telecommunications equipment.	TIA/EIA-IS-883	Telecommunications Telephone Terminal Equipment Supplemental Technical Requirements for Connection of Stutter Dial Tone Detection Devices and ADSL Modems to the Telephone Network
<i>ANSI EMC Standards</i> ANSI C63.4: 1992, 1999, 2001, 2003	American National Standard for methods of measurement of radio-noise emissions for low-voltage electrical and electronic equipment in the range of 9 kHz to 40GHz.	TIA-968-A	Telecommunications Telephone Terminal Equipment Technical Requirements for Connection of Terminal Equipment to the Telephone Network
ANSI C63.5 1988	American National Standard for electromagnetic compatibility - radiated emissions measurements in electromagnetic interference (EMI) control - calibration of antennas.	T1.TRQ.6-2001	Technical Requirements for SHDSL, HDSL2, HDSL4 Digital Subscriber Line Terminal Equipment to Prevent Harm to the Telephone Network
<i>IEEE EMC Standards</i> IEEE C62.41: 1980, 1991	IEEE recommended practice on surge voltages in low-voltage AC power circuits	Canada VDSL Issue 1 January 2003	Terminal Attachment Program Requirements and Test Methods for Very-High-Bit-Rate Digital Subscriber Line (VDSL) Terminal Equipment
<i>Swedish EMC Standards</i> BAKOM 3336.3 1995	Electromagnetic compatibility and electrical safety (EMC & S) for wired terminal equipment. Harmonization document information over the OFCOM requirements.	AS/ACIF S002-2001	Analogue interworking and non-interference requirements for Customer Equipment for connection to the Public Switched Telephone Network
<i>South African EMC standards other than CISPR equivalents</i> SABS 1718-1: 1996	South African Bureau of Standards: Specification for Gaming equipment. Part 1: Casino equipment.	AS/ACIF S016-2001	Requirements for Customer Equipment for connection to hierarchical digital interfaces
<i>Japanese VCCI Standards</i> VCCI V-3/99.05 1999 VCCI V-4/99.05 1999	Technical Requirements Instruction for Test Conditions for Requirement under Test	AS/ACIF S031-2001 AS/ACIF S038-2001 AS/ACIF S043-2001	Requirements for ISDN Basic Access Interface Requirements for ISDN Primary Rate Access Interface Requirements for Customer Equipment for Connection to a Metallic Local Loop Interface of a Telecommunications Network — Part 1: General Part 2: Broadband Part 3: DC, Low Frequency AC and Voiceband
<i>Telecommunications</i>	Telecommunications Registration; General test methods; Lightning surge; Drop testing; Balance testing; Signal power (metallic and longitudinal); Frequency measurements; Pulse templates; Leakage testing; Impedance testing; Hearing Aid Compatibility testing (<i>excluding volume control</i>); Protocol analysis and Jitter testing.	ITU-T G.703 HKTA 2028 HKTA 2029 TBR 1 : 1995	Physical/electrical characteristics of hierarchical Digital interfaces Network connection specification for connection of CPE to the PTNs in Hong Kong using digital leased circuits at data rate of 1544 kbit/s Network connection specification for connection of CPE to the PTNs in Hong Kong using digital leased circuits at data rate of 2048 kbit/s Attachment requirements for terminal equipment to be connected to circuit switched data networks and leased circuits using a CCITT Recommendation X.21 interface, or at an interface physically, functionally and electrically compatible with CCITT Recommendation X.21 but operating at any data signaling rate up to, and including, 1 984 kbit/s
<i>Telecom Standards</i>	<i>Title</i>	TBR 2 : 1997	Attachment requirements for Data Terminal Equipment (DTE) to connect to Packet Switched Public Data Networks (PSPDNs) for CCITT Recommendation X.25 interfaces at data signaling rates up to 1 920 kbit/s utilizing interfaces derived from CCITT Recommendations X.21 and X.21 bit
FCC 47 CFR Part 68 Telephone	Connection of terminal equipment to the telephone Terminal Equipment network. Analog and Digital Equipment. TCB Scope C1.		
CS-03 Issue 8 1996 through amendment 5	Specification for terminal equipment, terminal systems, Network protection devices, connection arrangements and hearing aids compatibility.		
TIA/EIA TSB31-B 1998	Bulletin Part 68 Rationale and Measurement Guidelines (Feb 1998)		
(A2LA Cert. No. 1627-01) 11/28/05	Page 7 of 11	(A2LA Cert. No. 1627-01) 11/28/05	Page 8 of 11

TBR 3 : 1995 + Amdt : 1997	Integrated Services Digital Network (ISDN); Attachment requirements for terminal equipment to connect to an ISDN using ISDN basic access	IEC 60950 2000 EN 60950 1997, 1998, 2000 IEC 60950-1 2001 UL 60950-1 2003 CSA C22.2 No. 60950-00 CSA C22.2 No. 60950-1 03 AS/NZS 3260 1993 AS/NZS 3260 Supp 1 1996	Safety of information technology equipment Safety of information technology equipment, including Electrical business equipment.
TBR 4 : 1995 + Amdt : 1997	Integrated Services Digital Network (ISDN); Attachment requirements for terminal equipment to connect to an ISDN using ISDN primary rate access		
TBR 012 : 1993 + Amdt : 1996	Business Telecommunications (BT); Open Network Provision (ONP) technical requirements; 2 048 kbit/s digital unstructured leased line (D2048U) Attachment requirements for terminal equipment		Approval and test specification – Safety of information technology equipment including electrical business Equipment.
TBR 013 : 1996	Business TeleCommunications (BTC); 2 048 kbit/s digital structured leased lines (D2048S); Attachment requirements for terminal equipment interface	ACA TS 001 1997	Approval and test specification – Safety of information technology equipment including electrical business equipment – Alphabetical reference index to IEC 950 (Supplement to AS/NZS 3260:1993)
TBR 21 : 1998	Terminal Equipment (TE); Attachment requirements for pan-European approval for connection to the analogue Public Switched Telephone Networks (PSTNs) of TE (excluding TE supporting the voice telephony service) in which network addressing, if provided, is by means of Dual Tone Multi Frequency (DTMF) signaling	UL 1459 1995 IEC 1010-1 1990 IEC 61010-1 1993 EN 61010-1 1993, 2001 IEC 61010-1 2001 UL 61010B-1 2003 UL 3101-1 1993 CAN/CSA 1010-1 1999 (<i>Including AM 2</i>) UL 3111-1 1996 UL 3121-1 1995 IEC 60601-1 1995 EN 60601-1 1995 (<i>Including AM 2</i>) UL 2601-1 1997 IEC 60065 1998, 2000 ANSI/UL 6500: 1998 CAN/CSA 60065-00 AS/NZS 3250 1995 AS/NZS 60065 2000	Australian Communications Authority – Safety requirements for customer equipment. Telephone Equipment Safety requirements for electrical equipment for measurement, control and laboratory use, Part 1: General requirements. Safety requirements for electrical equipment for measurement, control and laboratory use, Part 1: General requirements.
TBR 24 : 1997	Business TeleCommunications (BTC); 34 Mbit/s digital Unstructured and structured leased lines (D34U and D34S); Attachment requirements for terminal equipment interface		Electrical equipment for laboratory use Part 1: General requirements.
<i>Australia</i> TS 002 : 1997	Analogue Interworking and Non interference Requirements for Customer Equipment Connected to the Public Switched Telephone Network		Electrical measuring and test equipment. Part 1: General requirements.
TS 016 : 1997	General Requirements for Customer Equipment Connected to Hierarchical Digital Interfaces		Medical electrical equipment. Part 1: General requirements for safety.
TS 031 : 1997	Requirements for ISDN Basic Access Interface		Medical electrical equipment
TS 038 : 1997	Requirements for ISDN Primary Rate Access Interface		Medical electrical equipment. Part 1: General Requirements for safety.
AS/ACIF S043.2:2001	Requirements for Customer Equipment for connection to a metallic loop interface of a Telecommunications Network – Part 2 Broadband		Audio, video and similar electronic apparatus – Safety requirements for Household, commercial and similar general use
Product Safety			Australian/New Zealand Standard – Approval and test Specification – Mains operated electronic and related Equipment for household and similar general use
General test methods; Input tests; Electric strength tests; Impulse tests; Permanency of marking tests; Accessibility tests; Energy Hazard measurements; Capacitor discharge tests; Humidity conditioning; Earthing tests; Limited power source measurements; Stability tests; Steel ball tests; Lithium Battery Reverse Current measurements; Leakage current tests; Transformer abnormal tests; Telecom leakage tests; Over voltage/power cross tests (<i>excluding x-ray tests</i>).			Audio, video and similar electronic equipment. Consumer and 1994, commercial products
Product Safety Standards	Title		Safety requirements for main operated electronic and related apparatus for household and similar general use.
Specific Product Safety Standards			Radiation safety of laser products, equipment Classification, requirements and user's guide
IEC 950 1991	Safety of information technology equipment including Includes Amendments 1, 2, 3, and 4 electrical business equipment.		Safety of laser products Part 1: equipment Classification, requirements and user's guide.
UL 1950 1998	Safety of information technology equipment, including electrical business equipment.		Safety of laser products – Part 2: Safety of optical communication systems
CSA C22.2 No.950-95	Safety of Information Technology Equipment (UL 1950)		Safety of laser products – Part 4: Laser guards
UL 60950 2000	Safety of information technology equipment		Safety of household and similar electrical appliances
(A2LA Cert. No. 1627.01) 11/28/05	Page 9 of 11	(A2LA Cert. No. 1627.01) 11/28/05	Page 10 of 11
UL 61010A-1 : 2002	Electrical equipment for laboratory use; part 1: General requirements		
EN 61010-1 : 2001	Safety requirements for electrical equipment for measurement, control, and laboratory use - Part 1: General requirements		
AS/NZS 60950 : 2000	Safety information technology equipment		
Environmental²			
Environmental Standards	Title		
GR-63-CORE	NEBS Requirements: Physical Protection		
ETS 300 019	Environmental conditions and environmental tests For telecommunications equipment		
(A2LA Cert. No. 1627.01) 11/28/05	Page 11 of 11		

² Environmental testing is performed at the satellite facility located at 168 Ayer Rd, Littleton, MA 01460