

RF Exposure Report

Report No.: SA170505C01A

FCC ID: TVE-141703

Test Model: FortiAP 222E

Series Model: FortiAP 222Exxxxxx, FAP-222Exxxxxx, FORTIAP-222Exxxxxx (where "x"

can be used as "A-Z" or "0-9" or "-" or blank for software changes or

marketing purposes only)

Received Date: May 05, 2017

Test Date: May 19 ~ Jul. 24, 2017

Issued Date: Jul. 25, 2017

Applicant: Fortinet Inc.

Address: 899 Kifer Road Sunnyvale, CA 94086 USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan,

R.O.C.

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City

33383, TAIWAN (R.O.C.)





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Report No.: SA170505C01A Page No. 1 / 6 Report Format Version: 6.1.1 Reference No.: 170505C05



Classification ______5

2.3

3



Release Control Record

Issue No.	Description	Date Issued
SA170505C01	Original release	Jul. 25, 2017

Page No. 3 / 6 Report Format Version: 6.1.1

Report No.: SA170505C01A Reference No.: 170505C05



1 Certificate of Conformity

Product: Secured Wireless Access Point

Brand: Fortinet Inc.

Test Model: FortiAP 222E

Series Model: FortiAP 222Exxxxxx, FAP-222Exxxxxx, FORTIAP-222Exxxxxx (where "x" can be

used as "A-Z" or "0-9" or "-" or blank for software changes or marketing purposes

only)

Sample Status: Engineering sample

Applicant: Fortinet Inc.

Test Date: May 19 ~ Jul. 24, 2017

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D03 (January 17, 2014)

IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : , Date: Jul. 25, 2017

Pettie Chen / Senior Specialist

Approved by: Jul. 25, 2017

Ken Liu / Senior Manager



2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)		
Limits For General Population / Uncontrolled Exposure						
300-1500			F/1500	30		
1500-100,000			1.0	30		

F = Frequency in MHz

2.2 MPE Calculation Formula

 $Pd = (Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 28cm away from the body of the user. So, this device is classified as **Mobile Device**.

Report No.: SA170505C01A Reference No.: 170505C05 Page No. 5 / 6

Report Format Version: 6.1.1



3 Calculation Result of Maximum Conducted Power

Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm ²)	
WLAN						
CDD Mode						
2412-2462	26.94	8.01	28	0.317	1	
5180-5240	23.67	10.01	28	0.237	1	
5260-5320	21.38	10.01	28	0.140	1	
5500-5700	20.41	10.01	28	0.112	1	
5745-5825	25.72	10.01	28	0.380	1	
Beamforming Mod	le					
2412-2462	23.55	8.01	28	0.145	1	
5180-5240	20.54	10.01	28	0.115	1	
5260-5320	18.37	10.01	28	0.070	1	
5500-5700	19.09	10.01	28	0.083	1	
5745-5825	22.71	10.01	28	0.190	1	
BT LE						
2402-2480	4.95	2	28	0.001	1	

NOTE:

WLAN 2.4GHz: Directional gain = 5dBi + 10log(2) = 8.01dBi WLAN 5GHz: Directional gain = 7dBi +10log (2) = 10.01dBi

Frequency Band	Max. Power (dBm)		Total Power	Power Limit
	WLAN	BT LE	(dBm)	(dBm)
2.4GHz	26.94	4.95	26.97	30

CONCULSION:

The WLAN & BT LE can transmit simultaneously, the formula of calculated the MPE is:

CPD1 / LPD1 + CPD2 / LPD2 +etc. < 1

CPD = Calculation power density

LPD = Limit of power density

WLAN 2.4G + WLAN 5.0G + BT LE = 0.317 + 0.380 + 0.001 = 0.698

Therefore, the maximum calculation of this situation is 0.698, which is less than the "1" limit.

---END---