

Sample acceptance

Name of the supplier Shenzhen Feiyuxin Electronics Co., LTD

Grid type number IPEX-2.4G FPC Ant.-1.13 Gray-L140MM

SAP Material coding _____

ERP Material coding _____

Acceptance stamp

Supplier acceptance (Supplier field)			Customer acceptance		
Engineering	Quality	approval	R&d recognition	R&d approval	Quality confirmation
Li Yongjie	Chen Yan	Li HE			
Seal and sign			Seal and sign		
Date		2024-08-14	Date		
Instructions: ☐ acceptance ☐ Conditional acceptance					

Document correction record

Version	Modify location	modify content	modifier	approver	Time in Force
A0	/	New drawing			

Specification For Approval

Customer: _____ 10295 _____

Part name: _____ IPEX-2.4G FPC Ant.-1.13 Gray-L140MM _____

Part No: _____ 3.03.0101003983 _____

Customer Part No: _____

Customer confirmation		
Confirmation	check	Approver

Manufacturer recognition			
Sales	Drafters	check	Approver
Luo Yi	Li Yongjie	Zhou Xihua	Li He
Thank you for giving us the chance to approve samples. If you agree to pass it, please kindly send it back to us.			

Shenzhen Feiyuxin Electronics Co., LTD

Add: No. 76, Baotong South Road, Xikeng Community, Yuanshan Street, Longgang District, Shenzhen 518115, China

Phone: 0755-89737230 Fax: 0755-89737181

<http://www.fyxdz.com>

Catalog

1.Product dimension drawing.....	3
2.Product appearance.....	4
3.Antenna performance parameters	4
4.Cable specification.....	4-5
5.Environmental experiment	5-8
6.Product pictures.....	9
7.Standing wave ratio of antenna	9-10

Modification record

Versions	Date	Engineer	Content modification
A0	2024.08.14	Li Yongjie	New Drawing

1.Product size drawing

A		B		C		D		E		F		END PRODUCT DRAWING	
REV		DATE		DESCRIPTION		ECN NO.		NAME					
A0		2024.05.10		New Drawing				Li Yongjie					

RoHS Compliant

Requirements:

1.No damage to wire;

2.The finished product must be 100% mesh testing OK;

3.The finished product must be 100% inspected OK;

4.Adopt environmental protection process;

5.Mark @ part as the key control size.

4

Frequency Range

2400-2500MHz

Gain

2dBi

VSWR

Compare the waveform

Polarization

Linear Vertical

Impedance

50 ohm

⑥

⑤

④

③

②

①

No.

Apply UV glue

33.00±1

20.00±1

140±5

④downward

PRODUCT NAME

IPEX-2.4G FPC Ant.-1.13 Gray-L140MM

PRODUCT NO

3.03.0101003983

UNIT

N M

SIZE

FREE

D S

Li Yongjie

PAGE

1 OF 1

FORMAT

A4

CHK

Zhou Xinhua

APPD

Li He

SHENZHEN FYX ELECTRONIC CO.,LTD

CUSTOMER NO

Form Number: FYX/E-QR-14A

Version: 3rd edition

2. Product appearance

Size	L33*20mm	Fixed mode	Paste type
Weight	0.82g	Connector	IPEX
colour	FPC black	Cable	1.13

3. Antenna performance parameters

Items	Specifications	unit
Center Frequency	2400~2500	MHz
Output impedance	50	Ω
V.S.W.R	Compare the waveform	-
Average Gain	1.87	dBi
Maximum Peak Gain	2.0 @2470MHz	dBi
Maximum Efficiency	67.33%@2490MHz	
Polarization mode	Linear polarization	
Radiation direction	omnidirectional	
Maximum input power	5	W
working temperature	-40~+70	°C
Storage temperature	-45~+75	°C

4. Cable specification

1.13 Structure chart		
		
Structure parameter		
	Material Science	Diameter(mm)
1.Inner conductor	Tinned copper wire	7/0.08±0.02
2.Insulator	(PE)	0.66±0.02
3.Outer conductor	Tinned copper wire	0.88±0.05
4.Sheath	FEP	1.13±0.05
Electric performance parameters		

Capacitance (pF/m)	96±3
Impedance(ohm)	50
Rate (%)	66
Bending radius (mm)	≤7
Maximum working voltage	1000
Maximum operating frequency (MHz)	6000
Operating temperature range (°C)	-40~ +80
Attenuation	
(MHz)	(≥dB/m)
100	0.42
400	0.58
1000	2.20
2000	3.40
3000	4.20
4000	4.50
5000	5.20
6000	5.60

5.Environmental experiment

Environmental test report

5.1High low temperature and constant humidity test

No	3.03.0101003983	Specifications	IPEX-2.4G FPC Ant.-1.13 Gray-L140MM	
Items	High temperature, low temperature and constant humidity test			
Testing equipment	Alternating constant temperature and humidity test chamber	number	3	
Inspection standard	1. The coating on the metal surface shall be free of peeling, cracking, wrinkling and other defects; the non-metal part shall not have discoloration, cracking, deformation, degumming and other phenomena.			
Test name	Test items	requirement	test method	Result judgment
High temperature	Temperature (°C) Test sample temperature	75±3 1	Test procedure: a) Put the test piece into the test	OK

e test	time (H) Test duration (H) Recovery time (H)	2 1	chamber, and then adjust the temperature of the high temperature chamber to 75 °C± 3 °C, and monitor the time. b) After the test, it was placed at room temperature for 1 hour for routine inspection.	
Low temperature test	Temperature (°C) Test sample temperature time (H) Test duration (H) Recovery time (H)	-40±3 1 2 1	Test procedure: a) Put the test piece into the test chamber, and then adjust the temperature of the high temperature chamber to 75 °C± 3 °C, and monitor the time. b) After the test, it was placed at room temperature for 1 hour for routine inspection	OK
Constant damp heat test	Temperature (°C) Test sample temperature time (H) Test duration (H) Recovery time (H)	+40±3 90-95 21 1	a) Put the tested object into the test chamber, then adjust the temperature of the test chamber to + 40 °C± 3 °C, the humidity to 90-95%, and monitor the time. b) After the test, it was placed at room temperature for 1 hour for routine inspection.	OK
inspector: Guo Guangfeng ratify: Xie Zhoujun				

5.2 Free fall test

No	3.03.0101003983		Specifications	IPEX-2.4G FPC Ant.-1.13 Gray-L140MM	
Items	Free fall test				
Testing equipment	1m high desktop		number	3	
Inspection standard	1. The product has no defects such as falling off, cracking, etc. and no deformation in appearance when it falls 1 meter high.				
Test name	Items	requirement	test method		Result

				judgment
Free fall test	1000mm Drop height 1000mm	Drop both sides twice	Test procedure: a) Drop the test piece at a height of 1000mm, and carry out routine inspection after the test.	OK
inspector: Guo Guangfeng				ratify: Xie Zhoujun


5.3 Salt spray test


NO	3.03.0101003983	Specifications	IPEX-2.4G FPC Ant.-1.13 Gray-L140MM	
Items	Salt spray test			
Testing equipment	Salt spray tester	number	3	
Inspection standard	1. The coating on the metal surface shall not fall off; the appearance shall be free of rust, corrosion, oxidation and other adverse phenomena.			
Test name	Items	requirement	test method	Result judgment
Salt spray test	1. NaCl concentration: 2. Air pressure: 3. PH value: 4. spray volume: 5. Salt water test temperature setting a. Laboratory temperature: b. Pressure tank temperature: 6. Test time:	40-60g/1kg 1.0±0.01kgf m² 6.5-7.2 1.0-2.0ml/80c/h。 35±1℃ 47±1℃ 24H	Test procedure: a) Adjust the salt spray tester to relevant test conditions. b) Put the test piece into the salt spray testing machine for 24 hours. After the test, rinse with clean water, visually inspect the appearance of the tested parts, and carry out routine inspection.	OK
inspector: Guo Guangfeng				

6.Product pictures



7.Antenna performance test





Frequency(MHz)	Gain(dBi)	Efficiency(%)
2400	1.78	63.45
2410	1.53	62.25
2420	1.62	60.75
2430	1.62	60.58
2440	2.04	62.32
2450	1.92	61.58
2460	1.74	60.51
2470	2.07	64.91
2480	1.93	62.42
2490	2.4	67.33
2500	1.95	61.78

