

RF Exposure Report

Report No.: SA191111C01

FCC ID: TVE-4617T06785

Test Model: FAP-431F, FAP-433F

Series Model: FortiAP 431Fxxxxxx, FAP-431Fxxxxxx, FORTIAP-431Fxxxxxx, FortiAP 433Fxxxxxx, FAP-433Fxxxxxx, FORTIAP-433Fxxxxxx (where "x" can be used as "A-Z", or "0-9", or "-", or blank for software changes or marketing purposes only)

Received Date: Nov. 11, 2019

Test Date: Jan. 04 ~ Mar. 02, 2020

Issued Date: Mar. 20, 2020

Applicant: Fortinet Inc.

Address: 899 Kifer Road Sunnyvale, CA 94086 USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, Taiwan

FCC Registration / 788550 / TW0003
Designation Number:



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
3 Calculation Result of Maximum Conducted Power	6

Release Control Record

Issue No.	Description	Date Issued
SA191111C01	Original release	Mar. 20, 2020

1 Certificate of Conformity

Product: Secured Wireless Access Point

Brand: Fortinet

Test Model: FAP-431F, FAP-433F

Series Model: FortiAP 431Fxxxxxx, FAP-431Fxxxxxx, FORTIAP-431Fxxxxxx, FortiAP 433Fxxxxxx, FAP-433Fxxxxxx, FORTIAP-433Fxxxxxx (where "x" can be used as "A-Z", or "0-9", or "-", or blank for software changes or marketing purposes only)

Sample Status: Engineering sample

Applicant: Fortinet Inc.

Test Date: Jan. 04 ~ Mar. 02, 2020

Standards: FCC Part 2 (Section 2.1091)

References Test KDB 447498 D01 General RF Exposure Guidance v06

Guidance: IEEE C95.3 -2002

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Pettie Chen, **Date:** Mar. 20, 2020
Pettie Chen / Senior Specialist

Approved by : Bruce Chen, **Date:** Mar. 20, 2020
Bruce Chen / Senior Project Engineer

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 44cm away from the body of the user. So, this device is classified as **Mobile Device**.

3 Calculation Result of Maximum Conducted Power

Model: FAP-431F

Frequency Band (MHz)	Max Average Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN					
traffic radio: CDD Mode					
2412-2462	29.92	11.27	44	0.541	1
5180-5240	28.56	11.51	44	0.418	1
5745-5825	29.02	11.35	44	0.448	1
traffic radio: Beamforming Mode					
2412-2462	24.71	11.27	44	0.163	1
5180-5240	24.38	11.51	44	0.160	1
5745-5825	24.64	11.35	44	0.163	1
Scanning radio: CDD Mode					
2412-2462	12.35	5.22	44	0.002	1
5180-5240	12.28	5.06	44	0.002	1
5745-5825	12.28	5.14	44	0.002	1
BT LE					
2412-2462	3.89	4.71	44	0.0003	1

*Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

Note:

1. Directional gain:

Model: FAP-431F

2G traffic radio

2.4GHz Band: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/4] = 11.27\text{dBi}$

5180 ~ 5240MHz: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/4] = 11.51\text{dBi}$

5745 ~ 5825MHz: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/4] = 11.35\text{dBi}$

2. The above Max Power is Tune-up Power which client declared.

Model: FAP-433F

Frequency Band (MHz)	Max Average Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN					
traffic radio: CDD Mode					
2412-2462	29.09	10.02	44	0.335	1
5180-5240	27.29	12.03	44	0.351	1
5745-5825	29.37	12.22	44	0.593	1
traffic radio: Beamforming Mode					
2412-2462	25.90	10.02	44	0.161	1
5180-5240	23.72	12.03	44	0.154	1
5745-5825	23.08	12.22	44	0.139	1
Scanning radio: CDD Mode					
2412-2462	12.21	5.22	44	0.002	1
5180-5240	12.23	6.01	44	0.003	1
5745-5825	12.08	6.20	44	0.003	1
BT LE					
2412-2462	3.89	4.71	44	0.0003	1

*Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

Note:

1. Directional gain:

Model: FAP-433F

2G traffic radio

2.4GHz Band: Directional gain = 4dBi + 10log(4) = 10.02dBi

5180 ~ 5240MHz: Directional gain = 6.01dBi + 10log(4) = 12.03dBi

5745 ~ 5825MHz: Directional gain = 6.20dBi + 10log(4) = 12.22dBi

2. The above Max Power is Tune-up Power which client declared.

Conclusion:

The formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

Model: FAP-431F

2G traffic radio + 5GHz traffic radio + Scanning radio (5G) + BT
 $= 0.541 / 1 + 0.448 / 1 + 0.002 / 1 + 0.0003 / 1 = 0.9913 < 1$

Model: FAP-433F

2G traffic radio + 5GHz traffic radio + Scanning radio (5G) + BT
 $= 0.335 / 1 + 0.593 / 1 + 0.003 / 1 + 0.0003 / 1 = 0.9313 < 1$

Therefore the maximum calculations of above situations are less than the "1" limit.

---END---