

**TRaC Wireless Test Report : TTR-000557WUS2**

**Applicant** : COMARK Ltd

**Apparatus** : RF500LITE

**Specification(s)** : CFR47 Part 15.247 July 2008

**FCCID** : TVHFR500LITE

**Purpose of Test** : Class II Permissive Change



**Authorised by** : John Charles  
: Radio Product Manager

**Issue Date** : 17<sup>th</sup> December 2010

**Authorised Copy Number** : PDF

## Contents

|   |    |
|---|----|
| Section 1: Introduction                                     | 3  |
| 1.1 General   | 3  |
| 1.2 Tests Requested By                                      | 4  |
| 1.3 Manufacturer  | 4  |
| 1.4 Apparatus Assessed                                      | 4  |
| 1.5 Test Result Summary                                     | 5  |
| 1.6 Notes Relating To The Assessment                        | 6  |
| 1.7 Deviations from Test Standards                          | 6  |
| Section 2: Measurement Uncertainty                          | 7  |
| 2.1 Measurement Uncertainty Values                          | 7  |
| Section 3: Modifications                                    | 9  |
| 3.1 Modifications Performed During Assessment               | 9  |
| Appendix A: Formal Emission Test Results                    | 10 |
| A1 Transmitter Peak Output Power                            | 11 |
| A2 Radiated Electric Field Emissions                        | 12 |
| A3 Power Line Conducted Emissions                           | 15 |
| A4 Antenna Gain   | 17 |
| Appendix B: Supporting Graphical Data                       | 18 |
| Appendix C: Additional Test and Sample Details              | 28 |
| Appendix D: Additional Information                          | 34 |
| Appendix E: Calculation of the duty cycle correction factor | 35 |
| Appendix F: Photographs and Figures                         | 36 |

**Section 1:**

**Introduction**

**1.1 General**

This report contains an assessment of an apparatus against Electromagnetic Compatibility Standards based upon tests carried out on samples submitted to the Laboratory.

Test performed at: TRaC Telecoms & Radio [ ]

Unit E  
South Orbital Trading Park  
Hedon Road  
Hull, HU9 1NJ.  
United Kingdom.

Telephone: +44 (0) 1482 801801  
Fax: +44 (0) 1482 801806

TRaC Telecoms & Radio [X]

Moss View  
Nipe Lane  
Up Holland  
West Lancashire, WN8 9PY  
United Kingdom

Telephone: +44 (0) 1695 556666  
Fax: +44 (0) 1695 577077

Email: [test@tracglobal.com](mailto:test@tracglobal.com)  
Web site: <http://www.tracglobal.com>

Tests performed by: D. Winstanley

Report author: D. Winstanley

**This report must not be reproduced except in full without prior written permission from  
TRaC Telecoms & Radio.**

## **1.2 Tests Requested By**

This testing in this report was requested by :

Comark Ltd  
Gunnels Wood Park  
Gunnelswood Road  
Stevenage  
Hertfordshire  
SG1 2TS  
United Kingdom

## **1.3 Manufacturer**

As Above

## **1.4 Apparatus Assessed**

The following apparatus was assessed between 2<sup>nd</sup> – 7<sup>th</sup> December 2010:

Comark RF500LITE Gateway

The Class II Permissive change covered in this report concerns the change of External power supply as Follows

The original external PSU Stontronics LAD6019AB5 has been made obsolete, and is now replaced by a Friwo DT60 Power supply.

Results contained in this report were all obtained during testing with the Friwo DT60 Power Supply.

## 1.5 Test Result Summary

Full details of test results are contained within Appendix A. The following table summarises the results of the assessment.

The statements relating to compliance with the standards below apply ONLY as qualified in the notes and deviations stated in sections 1.6 to 1.7 of this test report.

Full details of test results are contained within Appendix A. The following table summarises the results of the assessment.

| Test Type                    | Regulation   | Measurement standard | Result |
|------------------------------|--|----------------------|--------|
| Conducted Carrier Power      | Title 47 of the CFR :<br>Part 15 Subpart C; 15.247(b)      | ANSI C63.10          | Pass   |
| Radiated spurious emissions  | Title 47 of the CFR:<br>Part 15 Subpart C; 15.247 & 15.109 | ANSI C63.10          | Pass   |
| AC Power conducted emissions | Title 47 of the CFR:<br>Part 15 Subpart C; 15.207          | ANSI C63.10          | Pass   |

Abbreviations used in the above table:

|      |                                     |      |   |
|------|-------------------------------------|------|---|
| Mod  | : Modification                      |      |   |
| CFR  | : Code of Federal Regulations       | ANSI | : American National Standards Institution |
| REFE | : Radiated Electric Field Emissions | PLCE | : Power Line Conducted Emissions          |

## **1.6 Notes Relating To The Assessment**

With regard to this assessment, the following points should be noted:

The results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

The apparatus was set up and exercised using the configurations, modes of operation and arrangements defined in this report only.

Particular operating modes, apparatus monitoring methods and performance criteria required by the standards tested to have been performed except where identified in Section 1.7 of this test report (Deviations from Test Standards).

For emissions testing, throughout this test report, "Pass" indicates that the results for the sample as tested were below the specified limit (refer also to Section 2, Measurement Uncertainty).

Where relevant, the apparatus was only assessed using the monitoring methods and susceptibility criteria defined in this report.

All testing with the exception of testing at the Open Area Test Site was performed under the following environmental conditions:

|                     |                 |
|---------------------|-----------------|
| Temperature         | : 17 to 23 °C   |
| Humidity            | : 45 to 75 %    |
| Barometric Pressure | : 86 to 106 kPa |

All dates used in this report are in the format dd/mm/yy.

This assessment has been performed in accordance with the requirements of ISO/IEC 17025.

## **1.7 Deviations from Test Standards**

There were no deviations from the standards tested to.

**Section 2:****Measurement Uncertainty****2.1 Measurement Uncertainty Values**

For the test data recorded in accordance with note (iii) of Section 2.1 the following measurement uncertainty was calculated:

**Radio Testing – General Uncertainty Schedule**

*All statements of uncertainty are expanded standard uncertainty using a coverage factor of 1.96 to give a 95% confidence where no required test level exists.*

**[1] Adjacent Channel Power**

Uncertainty in test result = **1.86dB**

**[2] Carrier Power**

Uncertainty in test result (Equipment - TRLUH120) = **2.18dB**

Uncertainty in test result (Equipment – TRL05) = **1.08dB**

Uncertainty in test result (Equipment – TRL479) = **2.48dB**

**[3] Effective Radiated Power**

Uncertainty in test result = **4.71dB**

**[4] Spurious Emissions**

Uncertainty in test result = **4.75dB**

**[5] Maximum frequency error**

Uncertainty in test result (Equipment - TRLUH120) = **119ppm**

Uncertainty in test result (Equipment – TRL05) = **0.113ppm**

Uncertainty in test result (Equipment – TRL479) = **0.265ppm**

**[6] Radiated Emissions, field strength OATS 14kHz-18GHz Electric Field**

Uncertainty in test result (14kHz – 30MHz) = **4.8dB**, Uncertainty in test result (30MHz – 1GHz) = **4.6dB**, Uncertainty in test result (1GHz-18GHz) = **4.7dB**

**[7] Frequency deviation**

Uncertainty in test result = **3.2%**

**[8] Magnetic Field Emissions**

Uncertainty in test result = **2.3dB**

**[9] Conducted Spurious**

Uncertainty in test result (Equipment TRL479) Up to 8.1GHz = **3.31dB**

Uncertainty in test result (Equipment TRL479) 8.1GHz – 15.3GHz = **4.43dB**

Uncertainty in test result (Equipment TRL479) 15.3GHz – 21GHz = **5.34dB**

Uncertainty in test result (Equipment TRLUH120) Up to 26GHz = **3.14dB**

**[10] Channel Bandwidth**

Uncertainty in test result = **15.5%**

**[11] Amplitude and Time Measurement – Oscilloscope**

Uncertainty in overall test level = **2.1dB**, Uncertainty in time measurement = **0.59%**, Uncertainty in Amplitude measurement = **0.82%**

**[11] Power Line Conduction**

Uncertainty in test result = **3.4dB**

**[12] Spectrum Mask Measurements**

Uncertainty in test result = **2.59% (frequency)**  
Uncertainty in test result = **1.32dB (amplitude)**

**[13] Adjacent Sub Band Selectivity**

Uncertainty in test result = **1.24dB**

**[14] Receiver Blocking – Listen Mode, Radiated**

Uncertainty in test result = **3.42dB**

**[15] Receiver Blocking – Talk Mode, Radiated**

Uncertainty in test result = **3.36dB**

**[16] Receiver Blocking – Talk Mode, Conducted**

Uncertainty in test result = **1.24dB**

**[17] Receiver Threshold**

Uncertainty in test result = **3.23dB**

**[18] Transmission Time Measurement**

Uncertainty in test result = **7.98%**

**Section 3:**

**Modifications**

**3.1 Modifications Performed During Assessment**

None

**Appendix A:****Formal Emission Test Results**

Abbreviations used in the tables in this appendix:

|      |                                 |      |                                |
|------|---------------------------------|------|--------------------------------|
| Spec | : Specification                 | ALSR | : Absorber Lined Screened Room |
| Mod  | : Modification                  | OATS | : Open Area Test Site          |
|      |                                 | ATS  | : Alternative Test Site        |
| EUT  | : Equipment Under Test          |      |                                |
| SE   | : Support Equipment             | Ref  | : Reference                    |
| L    | : Live Power Line               | Freq | : Frequency                    |
| N    | : Neutral Power Line            | MD   | : Measurement Distance         |
| E    | : Earth Power Line              | SD   | : Spec Distance                |
| Pk   | : Peak Detector                 | Pol  | : Polarisation                 |
| QP   | : Quasi-Peak Detector           | H    | : Horizontal Polarisation      |
| Av   | : Average Detector              | V    | : Vertical Polarisation        |
| CDN  | : Coupling & decoupling network |      |                                |

## A1 Transmitter Peak Output Power

Carrier power was verified with the EUT transmitting on its lowest, centre and highest carrier frequency in turn.

| Test Details:          |  |
|------------------------|--|
| Regulation             | Title 47 of the CFR: Part15 Subpart (c) 15.247(b)(3) |
| Measurement standard   | ANSI C63.10  |
| EUT sample number      | S03  |
| Modification state     | 01   |
| SE in test environment | None   |
| SE isolated from EUT   | None   |
| EUT set up             | Refer to Appendix C                                  |
| Temperature            | 20°C   |

| Channel Frequency (MHz) | Peak Carrier Power (W) | Antenna Gain dBi | Average Power (W) | Limit (W) | Result |
|-------------------------|------------------------|------------------|-------------------|-----------|--------|
| 2405.0                  | 0.0017                 | 7                | 0.0089            | 1         | Pass   |

Notes:

Conducted Measurement

Highest Gain of any antenna to be used = 7 dBi

Conducted measurements were performed on unique antenna connector provided by the client.

See Appendix B for plot.

Losses between EUT and Measurement device not taken into account on plot.

## A2 Radiated Electric Field Emissions

Preliminary scans were performed using a peak detector with the RBW = 100kHz. The radiated electric field emission in this report related only to emissions that were affected by the class II change. All other emissions, found to be unaffected by the change, are contained in report RU1538/8938. All emissions contained in this report were found to be unrelated to the radio section of the device.

The following test site was used for final measurements as specified by the standard tested to:

3m open area test site :

3m alternative test site :

The effect of the EUT set-up on the measurements is summarised in note (c) below.

| Test Details: 2405.0 MHz |  |
|--------------------------|--|
| Regulation               | Title 47 of the CFR: Part 15 Subpart (b) Clause 15.109 |
| Measurement standard     | ANSI C63.10  |
| Frequency range          | 30MHz to 25 GHz  |
| EUT sample number        | S02 & S03  |
| Modification state       | 01   |
| SE in test environment   | None   |
| SE isolated from EUT     | None   |
| EUT set up               | Refer to Appendix C                                    |
| Photographs (Appendix F) | 1 & 2  |

| Ref No. | FREQ.<br>(MHz) | MEAS<br>Rx<br>(dB $\mu$ V) | CABLE<br>LOSS<br>(dB) | ANT FACT.<br>(dB/m) | PRE AMP<br>(dB) | FIELD<br>ST'GH<br>(dB $\mu$ V/m) | EXTRAP<br>FACT<br>(dB) | FIELD ST'GH<br>( $\mu$ V/m) | LIMIT<br>( $\mu$ V/m) |
|---------|----------------|----------------------------|-----------------------|---------------------|-----------------|----------------------------------|------------------------|-----------------------------|-----------------------|
| 1.      | 31.10          | 8.6                        | 1.1                   | 17.3                | -               | 27.0                             | -                      | 22.39                       | 100                   |
| 2.      | 32.50          | 17.6                       | 1.1                   | 16.6                | -               | 35.3                             | -                      | 58.21                       | 100                   |
| 3.      | 33.50          | 15.2                       | 1.1                   | 16.1                | -               | 32.4                             | -                      | 41.69                       | 100                   |
| 4.      | 49.15          | 18.0                       | 1.1                   | 8.1                 | -               | 27.2                             | -                      | 22.91                       | 100                   |
| 5.      | 80.60          | 27.1                       | 1.1                   | 6.7                 | -               | 34.9                             | -                      | 55.59                       | 100                   |
| 6.      | 81.45          | 25.8                       | 1.1                   | 6.9                 | -               | 33.8                             | -                      | 48.98                       | 100                   |
| 7.      | 83.90          | 24.1                       | 1.1                   | 7.4                 | -               | 32.6                             | -                      | 42.66                       | 150                   |
| 8.      | 87.45          | 25.2                       | 1.1                   | 8.1                 | -               | 34.4                             | -                      | 52.48                       | 150                   |
| 9.      | 90.05          | 21.8                       | 1.1                   | 8.6                 | -               | 31.5                             | -                      | 37.58                       | 150                   |
| 10      | 93.70          | 21.9                       | 1.1                   | 9.3                 | -               | 32.3                             | -                      | 41.21                       | 150                   |
| 11      | 120.70         | 23.3                       | 1.2                   | 11.5                | -               | 36.0                             | -                      | 63.10                       | 150                   |
| 12      | 122.90         | 22.9                       | 1.2                   | 11.5                | -               | 35.6                             | -                      | 60.26                       | 150                   |
| 13      | 144.05         | 19.8                       | 1.3                   | 10.4                | -               | 31.5                             | -                      | 37.58                       | 150                   |
| 14      | 147.45         | 20.3                       | 1.3                   | 10.1                | -               | 31.7                             | -                      | 38.46                       | 150                   |
| 15      | 166.80         | 21.7                       | 1.4                   | 9.2                 | -               | 32.3                             | -                      | 41.21                       | 150                   |
| 16      | 172.00         | 21.3                       | 1.5                   | 9.0                 | -               | 31.8                             | -                      | 38.90                       | 150                   |
| 17      | 173.30         | 20.1                       | 1.5                   | 8.9                 | -               | 30.5                             | -                      | 33.50                       | 150                   |
| 18      | 192.85         | 20.2                       | 1.6                   | 8.6                 | -               | 30.4                             | -                      | 33.11                       | 150                   |
| 19      | 266.30         | 27.2                       | 1.9                   | 12.9                | -               | 42.0                             | -                      | 125.89                      | 200                   |
| 20      | 272.00         | 17.8                       | 1.9                   | 12.5                | -               | 32.2                             | -                      | 40.74                       | 200                   |
| 21      | 304.00         | 18.2                       | 2.0                   | 13.2                | -               | 33.4                             | -                      | 46.77                       | 200                   |

| Ref No. | FREQ.<br>(MHz) | MEAS<br>Rx<br>(dB $\mu$ V) | CABLE<br>LOSS<br>(dB) | ANT FACT.<br>(dB/m) | PRE AMP<br>(dB) | FIELD<br>ST'GH<br>(dB $\mu$ V/m) | EXTRAP<br>FACT<br>(dB) | FIELD ST'GH<br>( $\mu$ V/m) | LIMIT<br>( $\mu$ V/m) |
|---------|----------------|----------------------------|-----------------------|---------------------|-----------------|----------------------------------|------------------------|-----------------------------|-----------------------|
| 22      | 336.10         | 19.8                       | 2.1                   | 13.9                | -               | 35.8                             | -                      | 61.66                       | 200                   |
| 23      | 432.10         | 15.4                       | 2.4                   | 16.2                | -               | 34.0                             | -                      | 50.12                       | 200                   |
| 24      | 528.10         | 23.4                       | 2.7                   | 17.5                | -               | 43.6                             | -                      | 151.36                      | 200                   |
| 25      | 533.95         | 19.1                       | 2.7                   | 17.6                | -               | 39.4                             | -                      | 93.33                       | 200                   |
| 26      | 576.15         | 16.8                       | 2.8                   | 18.5                | -               | 38.1                             | -                      | 80.35                       | 200                   |
| 27      | 672.15         | 18.8                       | 2.9                   | 18.9                | -               | 40.6                             | -                      | 107.15                      | 200                   |
| 28      | 816.20         | 8.8                        | 3.2                   | 20.2                | -               | 32.2                             | -                      | 40.74                       | 200                   |
| 29      | 864.20         | 9.1                        | 3.3                   | 20.4                | -               | 32.8                             | -                      | 43.65                       | 200                   |

**Notes:**

- 1 Any testing performed below 30 MHz was performed using a magnetic loop antenna in accordance with ANSI C63.10: section 4.5, Table 1
- 2 In accordance with 15.35(b), above 1 GHz, emissions measured using a peak detector shall not exceed a level 20 dB above the average limit.
- 3 Measurements at 2400 & 2483.5 MHz were made to ensure band edge compliance.
- 4 Testing was performed with the EUT orientated in three orthogonal planes and the maximum emissions level recorded. In addition, the EUT antenna was varied within its range of motion in order to maximise emissions.
- 5 For Frequencies below 1 GHz, RBW= 100 kHz, testing was performed with CISPR16 compliant test receiver with QP detector. Above 1 GHz tests were performed using a spectrum analyser using the following settings:

Peak            RBW=VBW= 1MHz  
 Average        RBW=VBW= 1MHz

These settings as per ANSI C63.10

The upper and lower frequency of the measurement range was decided according to 47 CFR 15:2008 Clause 15.33(a) and 15.33(a)(1).

Radiated emission limits (47 CFR 15: Clause 15.209) for emissions falling within the restricted bands defined in 15.205(a):

| Frequency of emission (MHz) | Field strength $\mu$ V/m | Measurement Distance m | Field strength dB $\mu$ V/m |
|-----------------------------|--------------------------|------------------------|-----------------------------|
| 0.009-0.490                 | 2400/F(kHz)              | 300                    | 67.6/F (kHz)                |
| 0.490-1.705                 | 24000/F(kHz)             | 30                     | 87.6/F (kHz)                |
| 1.705-30                    | 30                       | 30                     | 29.5                        |
| 30-88                       | 100                      | 3                      | 40.0                        |
| 88-216                      | 150                      | 3                      | 43.5                        |
| 216-960                     | 200                      | 3                      | 46.0                        |
| Above 960                   | 500                      | 3                      | 54.0                        |

**Notes:**

(a) Where results have been measured at one distance, and a signal level displayed at another, the results have been extrapolated using the following formula:

$$\text{Extrapolation (dB)} = 20 \log_{10} \left( \frac{\text{measurement distance}}{\text{specification distance}} \right)$$

The results displayed take into account applicable antenna factors and cable losses.

(b) The levels may have been rounded for display purposes.

(c) The following table summarises the effect of the EUT operating mode, internal configuration and arrangement of cables / samples on the measured emission levels :

|  | See (i) | See (ii) | See (iii) | See (iv) |
|--|---------|----------|-----------|----------|
| Effect of EUT operating mode on emission levels  |         | ✓        |           |          |
| Effect of EUT internal configuration on emission levels  |         | ✓        |           |          |
| Effect of Position of EUT cables & samples on emission levels  |         |          |           | ✓        |
| (i) Parameter defined by standard and / or single possible, refer to Appendix D<br>(ii) Parameter defined by client and / or single possible, refer to Appendix D<br>(iii) Parameter had a negligible effect on emission levels, refer to Appendix D<br>(iv) Worst case determined by initial measurement, refer to Appendix D |         |          |           |          |

### A3 Power Line Conducted Emissions

Previous power line conducted emission measurements were performed with a peak detector in a screened room. The effect of the EUT set-up on the measurements is summarised in note (b). Where applicable formal measurements of the emissions were performed with a peak, average and/or quasi peak detector. The EUT was set to transmit on its lowest, centre and highest carrier frequency in turn. The formal measurements are detailed below:

| Test Details:            |  |
|--------------------------|--|
| Regulation               | Title 47 of the CFR: Part 15 Subpart (c) Clause 15.207 |
| Measurement standard     | ANSI C63.10  |
| Frequency range          | 150kHz to 30MHz  |
| EUT sample number        | S02 & S03  |
| Modification state       | 01   |
| SE in test environment   | Laptop   |
| SE isolated from EUT     | None   |
| EUT set up               | Refer to Appendix C                                    |
| Photographs (Appendix F) | Photograph 3   |

The worst-case power line conducted emission measurements are listed below:

#### Results measured using the average detector compared to the average limit

| Ref No. | Freq (MHz) | Conductor | Result (dBuV) | Spec Limit (dBuV) | Margin (dB) | Result Summary |
|---------|------------|-----------|---------------|-------------------|-------------|----------------|
| 1       | 0.185      | Neutral   | 38.65         | 54.26             | 15.61       | Pass           |
| 2       | 0.19       | Neutral   | 37.62         | 54.04             | 16.42       | Pass           |
| 3       | 0.375      | Live      | 33.32         | 48.39             | 15.07       | Pass           |
| 4       | 0.5        | Neutral   | 31.22         | 46                | 14.78       | Pass           |
| 5       | 0.565      | Neutral   | 32.56         | 46                | 13.44       | Pass           |

#### Results measured using the quasi-peak detector compared to the quasi-peak limit

| Ref No. | Freq (MHz) | Conductor | Result (dBuV) | Spec Limit (dBuV) | Margin (dB) | Result Summary |
|---------|------------|-----------|---------------|-------------------|-------------|----------------|
| 1       | 0.15       | Live      | 46.53         | 66                | 19.47       | Pass           |
| 2       | 0.185      | Neutral   | 50.78         | 64.26             | 13.48       | Pass           |
| 3       | 0.375      | Neutral   | 39.64         | 58.39             | 18.75       | Pass           |
| 4       | 0.44       | Live      | 38.82         | 57.06             | 18.24       | Pass           |
| 5       | 0.53       | Neutral   | 40.74         | 56                | 15.26       | Pass           |
| 6       | 0.565      | Neutral   | 38.38         | 56                | 17.62       | Pass           |

**Specification limits :**

Conducted emission limits (47 CFR 15: Clause 15.207):

Conducted disturbance at the mains ports.

| Frequency range MHz | Limits dB $\mu$ V     |                       |
|---------------------|-----------------------|-----------------------|
|                     | Quasi-peak            | Average               |
| 0.15 to 0.5         | 66 to 56 <sup>2</sup> | 56 to 46 <sup>2</sup> |
| 0.5 to 5            | 56                    | 46                    |
| 5 to 30             | 60                    | 50                    |

Notes:

1. The lower limit shall apply at the transition frequency.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.

Notes:

- (a) The levels may have been rounded for display purposes.
- (b) The following table summarises the effect of the EUT operating mode and internal configuration on the measured emission levels :

|   | See (i) | See (ii) | See (iii) | See (iv) |
|---|---------|----------|-----------|----------|
| Effect of EUT operating mode on emission levels                                 | ✓       |          |           |          |
| Effect of EUT internal configuration on emission levels                         |         | ✓        |           |          |
| (i) Parameter defined by standard and / or single possible, refer to Appendix C |         |          |           |          |
| (ii) Parameter defined by client and / or single possible, refer to Appendix C  |         |          |           |          |
| (iii) Parameter had a negligible effect on emission levels, refer to Appendix C |         |          |           |          |
| (iv) Worst case determined by initial measurement, refer to Appendix C          |         |          |           |          |

#### **A4      Antenna Gain**

The maximum antenna gain for the antenna types to be used with the EUT, as declared by the client, is 7 dBi.


**Appendix B:**

**Supporting Graphical Data**


This appendix contains graphical data obtained during testing.

Notes:


- (a) The radiated electric field emissions and conducted emissions graphical data in this appendix is preview data. For details of formal results, refer to Appendix A and Appendix B.
- (b) The time and date on the plots do not necessarily equate to the time of the test.
- (c) Where relevant, on power line conducted emission plots, the limit displayed is the average limit, which is stricter than the quasi peak limit.
- (d) Appendix C details the numbering system used to identify the sample and its modification state.
- (e) The plots presented in this appendix may not be a complete record of the measurements performed, but are a representative sample, relative to the final assessment.




Conducted carrier power 2405.0MHz




Transmitter Radiated Spurious Emissions 30 MHz to 1 GHz – 2405.0MHz




Transmitter Radiated Spurious Emissions 1 GHz to 2 GHz – 2405.0MHz



Transmitter Radiated Spurious Emissions 2 GHz to 5 GHz – 2405.0MHz




Transmitter Radiated Spurious Emissions 5 GHz to 9 GHz – 2405.0MHz




Transmitter Radiated Spurious Emissions 9 GHz to 13 GHz – 2405.0MHz




Transmitter Radiated Spurious Emissions 13 GHz to 18GHz – 2405.0MHz




Transmitter Radiated Spurious Emissions 18 GHz to 25 GHz – 2405.0MHz




Receiver Radiated Spurious Emissions 30 MHz to 1 GHz – 2405.0MHz



Receiver Radiated Spurious Emissions 1 GHz to 2 GHz – 2405.0MHz




### Receiver Radiated Spurious Emissions 2 GHz to 5 GHz – 2405.0MHz



Date: 6.DEC.2010 11:02:20


### Receiver Radiated Spurious Emissions 5 GHz to 9 GHz – 2405.0MHz



Receiver Radiated Spurious Emissions 9 GHz to 13 GHz – 2405.0MHz



Receiver Radiated Spurious Emissions 13 GHz to 18GHz – 2405.0MHz



Receiver Radiated Spurious Emissions 18 GHz to 25 GHz – 2405.0MHz

## Appendix C: Additional Test and Sample Details

This appendix contains details of:

1. The samples submitted for testing.
2. Details of EUT operating mode(s)
3. Details of EUT configuration(s) (see below).
4. EUT arrangement (see below).

Throughout testing, the following numbering system is used to identify the sample and its modification state:

**Sample No:** Sxx Mod w

where:

|    |                       |           |
|----|-----------------------|-----------|
| xx | = sample number       | eg. S02   |
| w  | = modification number | eg. Mod 2 |

The following terminology is used throughout the test report:

**Support Equipment (SE)** is any additional equipment required to exercise the EUT in the applicable operating mode. Where relevant SE is divided into two categories:

SE in test environment: The SE is positioned in the test environment and is not isolated from the EUT (e.g. on the table top during REFE testing).

SE isolated from the EUT: The SE is isolated via filtering from the EUT. (e.g. equipment placed externally to the ALSR during REFE testing).

**EUT configuration** refers to the internal set-up of the EUT. It may include for example:

- Positioning of cards in a chassis.
- Setting of any internal switches.
- Circuit board jumper settings.
- Alternative internal power supplies.

Where no change in EUT configuration is **possible**, the configuration is described as "single possible configuration".

**EUT arrangement** refers to the termination of EUT ports / connection of support equipment, and where relevant, the relative positioning of samples (EUT and SE) in the test environment.

For further details of the test procedures and general test set ups used during testing please refer to the related document "EMC Test Methods - An Overview", which can be supplied by TRaC Telecoms & Radio upon request.

**C1) Test samples**

The following samples of the apparatus were submitted by the client for testing :

| Sample No. | Description  | Identification |
|------------|--------------|----------------|
| 02         | RF500LITE    | 7147602        |
| 03         | Power Supply | DT6012         |
|            |              |                |

The following samples of apparatus were submitted by the client as host, support or drive equipment (auxiliary equipment):

| Sample No. | Description | Identification |
|------------|-------------|----------------|
| None       | None        |                |
|            |             |                |
|            |             |                |

The following samples of apparatus were supplied by TRaC Telecoms & Radio as support or drive equipment (auxiliary equipment):

| Identification | Description             |
|----------------|-------------------------|
| None           | Network Port Connection |
|                |                         |
|                |                         |

**C2) EUT Operating Mode During Testing.**

During testing, the EUT was exercised as described in the following tables :

| Test                                    | Description of Operating Mode: |
|---|--------------------------------|
| Transmitter radiated spurious emissions | EUT active & transmitting.     |

| Test                                 | Description of Operating Mode:   |
|--------------------------------------|----------------------------------|
| Receiver radiated spurious emissions | EUT active but non-transmitting. |

| Test | Description of Operating Mode:                                 |
|------|--|
| PLCE | EUT active & transmitting.<br>EUT active but non-transmitting. |

**C3) EUT Configuration Information.**

The EUT was submitted for testing in one single possible configuration.

**C4) List of EUT Ports**

The tables below describe the termination of EUT ports:

Sample : 02  
Tests : Radiated Emissions

| Port    | Description of Cable Attached | Cable length | Equipment Connected |
|---------|-------------------------------|--------------|---------------------|
| Antenna | No Cable                      | -            | 7dBi Antenna        |
| Power   | 2 Core                        | 2m           | AC Adaptor DT6012   |
| Network | CAT-5 Cable                   | 2m           | Network port        |

## C5 Details of Equipment Used

For Radiated Measurements:

| TRAC Ref | Type     | Description                 | Manufacturer    | Date Calibrated. |
|----------|----------|-----------------------------|-----------------|------------------|
| TRLUH281 | FSU46    | Spectrum Analyser           | Rhode & Schwarz | 29/01/2009       |
| TRL138   | 3115     | 1-18GHz Horn Antenna        | EMCO            | 10/09/2009       |
| TRL139   | 3115     | 1-18GHz Horn Antenna        | EMCO            | 17/08/2009       |
| TRL572   | 8499B    | 1 – 26.5 GHz Pre Amplifier  | Agilent         | 04/07/2008       |
| TRLUH186 | ESHS10   | Receiver                    | Rhode & Schwarz | 10/12/2009       |
| TRLUH191 | CBL611/A | BiLog Periodic Antenna      | York            | 27/01/2010       |
| TRLUH372 | 6201-69  | 30MHz – 1 GHz Pre Amplifier | Watkins Johnson | 14/04/2010       |

For Conducted Measurements

| TRAC Ref | Type  | Description       | Manufacturer    | Date Calibrated. |
|----------|-------|-------------------|-----------------|------------------|
| TRLUH281 | FSU46 | Spectrum Analyser | Rhode & Schwarz | 29/01/2009       |

For Power Line Conducted Emissions

| TRAC Ref | Type    | Description       | Manufacturer    | Date Calibrated |
|----------|---------|-------------------|-----------------|-----------------|
| TRLUH195 | ESH3-Z5 | Single-phase LISN | Rhode & Schwarz | 10/12/2009      |
| TRLUH187 | ESVS10  | Receiver          | Rhode & Schwarz | 10/12/2009      |

**Appendix D:**

**Additional Information**

No additional information is included within this test report.

**Appendix E:****Calculation of the duty cycle correction factor**

Using a spectrum analyser in zero span mode, centred on the fundamental carrier frequency with a RBW of 1MHz and a video Bandwidth of 1MHz the sweep time was set accordingly to capture the pulse train. The transmit pulsewidths and period was measured. A plots of the pulse train is contained in Appendix B of this test report.

If the pulse train was less than 100 ms, including blanking intervals, the duty cycle was calculated by averaging the sum of the pulsewidths over one complete pulse train. However if the pulse train exceeds 100ms then the duty cycle was calculated by averaging the sum of the pulsewidths over the 100ms width with the highest average value. (The duty cycle is the value of the sum of the pulse widths in one period (or 100ms), divided by the length of the period (or 100ms). The duty cycle correction factor was then expressed in dB and the peak emissions adjusted accordingly to give an average value of the emission.

Correction factor dB =  $20 \times (\log_{10} \text{Calculated Duty Cycle})$

Therefore the calculated duty cycle was determined:

The pulse train period was greater than >100ms and in as shown from the plots in contained in appendix B of this test report.

Duty cycle =  $\frac{\text{the sum of the highest average value pulsewidths over 100ms}}{100ms}$

e.g

$$= \frac{7.459ms}{100ms} = 0.07459$$

0.07459 or 7.459%

Correction factor (dB) =  $20 \times (\log_{10} 0.07459) = -22.54\text{dB}$

## **Appendix F:**


## **Photographs and Figures**

The following photographs were taken of the test samples:

1. Radiated electric field emissions arrangement: RF500LITE front view.
2. Radiated electric field emissions arrangement: RF500LITE close up.



Photograph 1



Photograph 2

