



**REPORT ON THE CERTIFICATION TESTING OF A  
COMARK Ltd  
RF505  
WITH RESPECT TO  
THE FCC RULES CFR 47, PART 15.247 July 2008  
INTENTIONAL RADIATOR SPECIFICATION**



TEST REPORT NO: RU1523/8854

COPY NO: 2 .....

ISSUE NO: 1

FCC ID: TVHFR505

**REPORT ON THE CERTIFICATION TESTING OF A  
COMARK Ltd  
RF505  
WITH RESPECT TO  
THE FCC RULES CFR 47, PART 15.247 July 2008  
INTENTIONAL RADIATOR SPECIFICATION**

TEST DATE: 14<sup>th</sup> – 16<sup>th</sup> October 2008

TESTED BY: \_\_\_\_\_ D WINSTANLEY

APPROVED BY: \_\_\_\_\_ J CHARTERS  
RADIO SECTION  
LEADER

DATE: 23<sup>rd</sup> October 2008

Distribution:

Copy Nos:

1. Comark Ltd
2. TCB: TRL COMPLIANCE Ltd
3. TRL Compliance Ltd

THIS DOCUMENT MAY BE REPRODUCED ONLY IN ITS ENTIRETY AND WITHOUT CHANGE



0728

- Moss View, Nipe Lane, Up Holland, West Lancashire, WN8 9PY, UK.
- T +44 (0)1695 556666
- F +44 (0)1695 557077
- E test@trlcompliance.com



## CONTENTS

	PAGE
CERTIFICATE OF CONFORMITY & COMPLIANCE	4
APPLICANT'S SUMMARY	5
EQUIPMENT TEST CONDITIONS	5
TESTS REQUIRED	6
TEST RESULTS	7 -18
<b>ANNEX</b>	
PHOTOGRAPHS	A
PHOTOGRAPH No. 1: Test setup	
PHOTOGRAPH No. 2: Transmitter front view	
PHOTOGRAPH No. 3: Transmitter rear view	
PHOTOGRAPH No. 4: Transmitter PCB track side	
PHOTOGRAPH No. 5: Transmitter PCB component side	
APPLICANT'S SUBMISSION OF DOCUMENTATION LIST	B
TEST EQUIPMENT CALIBRATION	C
MEASUREMENT UNCERTAINTY	D
POWERLINE CONDUCTIONS GRAPH(s)	E
RADIATED SPURIOUS EMISSIONS	F
RADIATED BANDEDGE COMPLIANCE	G
6dB BANDWIDTH	H
PEAK POWER CONDUCTED	I
POWER SPECTRAL DENSITY	J

## Notes:

Notes:

1. Component failure during test YES  NO  [X]
2. If Yes, details of failure:
3. The facilities used for the testing of the product contain in this report are FCC Listed.
4. The contents of the attached applicants declarations and other supplied information are not covered by the scope of this laboratory's UKAS or FCC accreditations' and is provided in good faith.



**TRL Compliance**  
part of TRAC global

**CERTIFICATE OF CONFORMITY & COMPLIANCE**

FCC IDENTITY: TVHRF505  
PURPOSE OF TEST: Certification  
TEST SPECIFICATION: FCC RULES CFR 47, Part 15.247 July 2008  
TEST RESULT: Compliant to Specification  
EQUIPMENT UNDER TEST: RF505  
ITU: EMISSION CODE: 1M61F1D  
EQUIPMENT TYPE: Temperature Monitor  
CARRIER EMISSION: 0.00303 W  
ANTENNA TYPE: Unique Antenna Connector  
GAIN ANTENNA: 2.1 dBi Maximum Gain antenna  
FREQUENCY OF OPERATION: 2405MHz  
CHANNEL SPACING: N/A Wideband channel  
NUMBER OF CHANNELS: 1  
FREQUENCY GENERATION: SAW Resonator  Crystal  Synthesiser   
MODULATION METHOD: FHSS  DSSS  Other   
POWER SOURCE(s): +4.5Vdc (Via USB)  
TEST DATE(s): 14<sup>th</sup> -16<sup>th</sup> October 2008  
ORDER No(s): S06574  
APPLICANT: Comark Ltd.  
ADDRESS: Comark House  
Gunnels Wood Park  
Gunnelswood Road  
Stevenage  
Hertfordshire  
SG1 2TS  
United Kingdom

TESTED BY:

D WINSTANLEY

APPROVED BY:

J CHARTERS  
RADIO SECTION  
LEADER

## APPLICANT'S SUMMARY

EQUIPMENT UNDER TEST (EUT): RF505

EQUIPMENT TYPE: Wireless monitoring system (Survey Tool)

PURPOSE OF TEST: Certification

TEST SPECIFICATION(s): FCC RULES CFR 47, Part 15.247 July 2008

TEST RESULT: COMPLIANT Yes  [X]  
No  [ ]

APPLICANT'S CATEGORY: MANUFACTURER  [X]  
IMPORTER  [ ]  
DISTRIBUTOR  [ ]  
TEST HOUSE  [ ]  
AGENT  [ ]

APPLICANT'S ORDER No(s): S06574

APPLICANT'S CONTACT PERSON(s): Mr P Morrison

E-mail address: [paulmorrison@comarkltd.com](mailto:paulmorrison@comarkltd.com)

APPLICANT: Comark Ltd

ADDRESS: Comark House  
Gunnels Wood Park  
Gunnelswood Road  
Stevenage  
Hertfordshire  
SG1 2TS  
United Kingdom

TEL: +44 1483 367367

FAX: +44 1483 367400

EUT(s) COUNTRY OF ORIGIN: United Kingdom

TEST LABORATORY: TRL Compliance Ltd

UKAS ACCREDITATION No: 0728

TEST DATE(s): 14<sup>th</sup> -16<sup>th</sup> October 2008

TEST REPORT No: RU1523/8854

## EQUIPMENT TEST / EXAMINATIONS REQUIRED

1. TEST/EXAMINATION	RULE PART	DETECTOR	APPLICABILITY
Intentional Emission Frequency:	15.247	Peak	Yes
Intentional Emission Field Strength:	-	-	No
Intentional Emission Band Occupancy:	15.247(a)1	Peak	Yes
Intentional Emission EIRP (mW):	15.247(b)1	Peak	Yes
Spurious Emissions – Conducted:	15.207	Quasi Peak Average	Yes
Spurious Emissions – Conducted:	15.247	Peak	Yes
Spurious Emissions – Radiated <1000MHz:	15.209 ,15.247	Quasi Peak	Yes
Spurious Emissions – Radiated >1000MHz:	15.247 15.209	Peak average	Yes
Transmitter Carrier Frequency Separation:	15.247(a)(1)	Peak	Yes
Transmitter Maximum Peak Power Output Power:	15.247(b)(1)	Peak	Yes
Transmitter Band Edge Conducted Emissions:	15.247(c)	Peak	Yes
Transmitter Band Edge Radiated Emission:	15.247(c)	Peak	Yes
Extrapolation Factor:	15.31(f)	-	Yes
Maximum Frequency of Search:	15.33	-	Yes
Antenna Arrangements Integral:	15.203	-	Yes
Antenna Arrangements External Connector:	15.204	-	Yes
Restricted Bands:	15.205	-	Yes

2. Product Description :

1M6F1D

3. Temperatures:

Ambient (T<sub>nom</sub>) 16°C

4. Supply Voltages:

V<sub>nom</sub> +4.5Vdc

Note: V<sub>nom</sub> voltages are as stated above unless otherwise shown on the test report page

5. Equipment Category:

Single channel

Multi-channel

6. Channel spacing:

Narrowband


Wideband

## TRANSMITTER TESTS

### TRANSMITTER 6dB BANDWIDTH – CONDUCTED - PART 15.247(A)(2)

Ambient temperature = 20°C  
 Relative humidity = 60%  
 Conditions = Semi Anechoic Chamber  
 Supply voltage = +4.5Vdc

#### Diagram



Frequency	Channel	$F_{lower}$	$F_{Higher}$	Measured Bandwidth	Limit
2.405MHz	1	2404.153846 MHz	2405.764423 MHz	1610.577 MHz	>500kHz

**Notes:** 1 For analyser plots see annex G.

**Test Method:** 1 The EUT was had the highest gain antenna (2.1dBi) to be used with the equipment fitted.  
 2 The 6dB bandwidth was recorded with the EUT activity transmitting data.  
 3 Measurement distance of 3m


TYPE OF EQUIPMENT	MAKER/ SUPPLIER	MODEL No	SERIAL No	TRL No	ACTUAL EQUIPMENT USED
SPECTRUM ANALYSER	RHODE & SCHWARZ	FSU46	200034	UH281	X
HORN ANTENNA	EMCO	3115	9010-3580	138	X
PRE AMPLIFIER	AGILENT	8449B	3008A01610	572	X

## TRANSMITTER TESTS

### TRANSMITTER - MAXIMUM PEAK POWER - CONDUCTED - PART 15.247(B)(3)

Ambient temperature = 16°C  
 Relative humidity = 54%  
 Conditions = Radio Lab  
 Supply voltage = +4.5Vdc

#### Diagram



Frequency MHz	Channel	Peak Power dBm	Peak Power Watts	Antenna Gain dBi	Average Power Watts	Limit Watts
2.405	1	2.71	0.00186	2.1	0.00303	1

#### Notes:

- 1 Gain of antenna 2.1dBi, maximum gain antenna supplied by manufacturer.
- 2 For analyser plots see annex H.

#### Test Method:

- 1 The EUT was connected to the spectrum analyser via the unique antenna connector a cable and attenuator - if applicable.
- 2 The EUT was operated in transmit mode with modulation.
- 3 The level on the analyser was recorded.
- 4 The resolution bandwidth of the analyser was set to > than the 6dB bandwidth

Test equipment used for Peak Power measurement:


TYPE OF EQUIPMENT	MAKER/ SUPPLIER	MODEL No	SERIAL No	TRL No	ACTUAL EQUIPMENT USED
SPECTRUM ANALYSER	RHODE & SCHWARZ	FSU46	200034	UH281	X

## TRANSMITTER TESTS

### TRANSMITTER POWER SPECTRAL DENSITY – CONDUCTED - PART 15.247(E)

Ambient temperature = 20°C  
Relative humidity = 60%  
Conditions = Radio Lab  
Supply voltage = +4.5Vdc

#### Diagram



Frequency	Channel	Measured Power Spectral Density	Limit
2.405MHz	1	-9.37 dBm	+8 dBm

**Notes:** 1 For analyser plots see annex E.


**Test Method:** 1 The EUT was connected to the analyser via the unique antenna connector & a cable  
2 The resolution bandwidth on the analyser was set to 3kHz and trace set to max hold.  
3 The span is set to 3MHz  
4 The sweep time is 1000 seconds (Span/3kHz).  
5 The analyser level is offset to take the antenna gain (2.1dBi) into account.

TYPE OF EQUIPMENT	MAKER/ SUPPLIER	MODEL No	SERIAL No	TRL No	ACTUAL EQUIPMENT USED
SPECTRUM ANALYSER	RHODE & SCHWARZ	FSU46	200034	UH281	X

## TRANSMITTER TESTS

### TRANSMITTER SPURIOUS EMISSIONS – RADIATED – Part 15.247(c) and 15.209

Ambient temperature	= 21°C	3m measurements <1GHz	[X]
Relative humidity	= 30%	3m measurements >1GHz	[X]
Conditions	= Open Area Test Site (OATS)		
Supply voltage	= +4.5Vdc		



	Emission Frequency (MHz)	Meas. Rx. (dBuV)	Cable loss & Pre Amp Gain (dB)	Ant. Factor (dB/m)	Field Strength (dB $\mu$ V/m)	Extrap. Factor (dB)	Result ( $\mu$ V/m)	Limit ( $\mu$ V/m)
30MHz – 88MHz Restricted bands	50.00	23.85	1.11	7.74	32.7	-	43.15	100
	60.00	25.08	1.13	5.09	31.3	-	36.73	100
	70.00	16.75	1.21	5.24	23.2	-	14.45	100
	80.00	29.41	1.31	6.68	37.4	-	74.13	100
88MHz – 216MHz Restricted bands	Note 5/6							150
216MHz – 960MHz Restricted bands	Note 5/6							200
960MHz – 1GHz Restricted bands	Note 5/6							500
1GHz – 26GHz Restricted bands	4810.682	37.00	-33.14	32.8	36.66	-	68.07	500
30MHz -26GHz	Note 5/6							-20dBc

See annex E for initial pre scan results.

#### Notes:

- 1 Initial pre scans were performed see Annex E for plots.
- 2 See annex F for radiated bandedge compliance plots.
- 3 Emissions above 1GHz were measured with both a peak and average detectors.
- 4 Measurements were performed at 3 meters.
- 5 Only emissions within 20dB of limit are recorded.
- 6 Emissions not directly related to the transmitter are reported under receiver tests.

#### Test Method:

- 1 As per section 15.247.
- 2 Measuring distances as Note 4 above.
- 3 EUT 0.8 metre above ground plane.
- 4 Emissions maximised by rotation of EUT, on an automatic turntable.  
Raising and lowering the receiver antenna between 1m & 4m >30MHz.  
Horizontal and vertical polarisations, of the receive antenna.  
EUT orientation in three orthogonal planes. Maximum results recorded.

The test equipment used for the tests is shown overleaf:

TYPE OF EQUIPMENT	MAKER/ SUPPLIER	MODEL No	SERIAL No	TRL No	ACTUAL EQUIPMENT USED
AE, LOOP, Z2, 9kHz - 30MHz	ROHDE & SCHWARZ	HFH2	881058 - 53	07	
HORN ANTENNA	EMCO	3115	9010-3580	138	<b>X</b>
HORN ANTENNA	EMCO	3115	9010-3581	139	
RECEIVER	ROHDE & SCHWARZ	ESHS 10	830051/001	UH03	
RECEIVER	ROHDE & SCHWARZ	ESVS 10	844594/003	352	<b>X</b>
RANGE 1	TRL	3 METRE	N/A	UH06	<b>X</b>
AE, LOOP, Z2, 9kHz - 30MHz	ROHDE & SCHWARZ	HFH2	881058 - 53	07	
BILOG ANTENNA	CHASE	CBL6112	2129	UH93	<b>X</b>
SPECTRUM ANALYSER	ROHDE & SCHWARZ	FSU	200034	UH281	<b>X</b>
PRE AMPLIFIER	AGILENT	8449B	3008A01610	572	<b>X</b>

**TRANSMITTER and RECEIVER TESTS****TRANSMITTER CONDUCTED EMISSIONS – AC POWER LINE Parts 15.207 & 15.107****SIGNIFICANT EMISSIONS**

FREQUENCY (MHz)	MEASUREMENT RECEIVER READING (dB $\mu$ V)	DETECTOR	CONDUCTOR (L or N)	LIMIT (dB $\mu$ V)
0.15	55.65	Quasi Peak	Neutral	66.00
0.19	49.02	Quasi Peak	Neutral	64.04
0.225	53.66	Quasi Peak	Live	62.63
0.23	46.88	Quasi Peak	Neutral	15.57
0.245	38.83	Average	Live	51.92
0.25	55.65	Quasi Peak	Live	61.76
0.375	41.79	Quasi Peak	Live	58.39
0.455	47.20	Quasi Peak	Live	56.78
0.495	26.13	Average	Live	46.08
0.740	36.36	Quasi Peak	Live	56.00

**Notes:**


- 1 See attached plot annex D
- 2 EUT in normal operation mode connected to PC.
- 3 Worst case result recorded.

**Test Method:** 1 As per Radio – Noise Emissions, ANSI C63.4: 2003

The test equipment used for the Transmitter Conducted Emissions – AC Power Line Part 15.207 test was:

TYPE OF EQUIPMENT	MAKER/ SUPPLIER	MODEL No	SERIAL No	TRL No	ACTUAL EQUIPMENT USED
RECEIVER	ROHDE & SCHWARZ	ESHS 10	830051/001	UH03	
LISN/AMN	ROHDE & SCHWARZ	ESH3-Z5	863906/018	UH05	
RECEIVER	ROHDE & SCHWARZ	ESHS 10	841429/012	UH187	X
LISN/AMN	ROHDE & SCHWARZ	ESH3-Z5	8407 31/015	UH195	X


## POWER LINE CONDUCTION EMISSIONS



## RECEIVER TESTS

### RECEIVER SPURIOUS EMISSIONS – RADIATED – PART 15.109

Ambient temperature	= 14°C	3m measurements <1GHz	[X]
Relative humidity	= 43%	3m measurements >1GHz	[X]
Conditions	= Open Area Test Site (OATS)		
Supply voltage	= +4.5Vdc		



	FREQ. (MHz)	MEAS. Rx. (dB $\mu$ V)	CABLE LOSS (dB)	ANT FACT. (dB/m)	PRE AMP (dB)	FIELD ST'GH (dB $\mu$ V/m)	FIELD ST'GH ( $\mu$ V/m)	LIMIT ( $\mu$ V/m)	
30MHz – 88MHz	33.05	13.95	0.95	16.4	-	31.3	36.73	100	
	64.75	22.05	1.23	4.92	-	28.2	25.70	100	
	64.90	21.04	1.23	4.93	-	27.2	22.91	100	
	66.30	21.27	1.23	5.00	-	27.5	23.71	100	
88MHz – 216MHz	130.35	17.57	1.55	11.48	-	30.6	33.88	150	
	132.65	13.43	1.57	11.30	-	26.3	20.65	150	
	144.00	18.80	1.70	10.40	-	30.9	35.07	150	
	176.80	18.88	1.82	8.60	-	29.3	29.17	150	
	187.80	13.67	1.88	8.35	-	23.9	15.67	150	
	199.85	12.41	1.92	8.67	-	23.0	14.12	150	
216MHz – 960MHz	327.70	13.35	2.35	13.80	-	29.5	29.85	200	
	352.00	20.50	2.50	14.40	-	37.4	74.13	200	
	357.95	18.88	2.52	14.60	-	36.0	63.09	200	
	366.05	11.87	2.55	14.78	-	29.2	28.84	200	
	432.05	11.30	2.80	16.40	-	30.5	33.49	200	
960MHz – 1.0GHz									
1GHz – 25.0GHz									
Limits	30MHz to 88MHz			100 $\mu$ V/m @ 3m					
	88MHz to 216MHz			150 $\mu$ V/m @ 3m					
	216MHz to 960MHz			200 $\mu$ V/m @ 3m					
	960MHz to 1GHz			500 $\mu$ V/m @ 3m					
	1GHz to 5GHz			500 $\mu$ V/m @ 3m					

#### Notes:

- Initial pre scans were performed see Annex E for plots <1GHz.
- Emissions above 1GHz were measured with both a peak and average detectors.
- Measurements <1GHz were performed at 3 meters.
- Measurements >1GHz were performed at 3 meters
- Only emissions with in 20dB of limit are recorded.

#### Test Method:

- As per Radio – Noise Emissions, ANSI C63.4: 2003.
- Measuring distances as Notes 1 to 4 above.
- EUT 0.8 metre above ground plane.
- Emissions maximised by rotation of EUT, on an automatic turntable.  
Raising and lowering the receiver antenna between 1m & 4m.  
Horizontal and vertical polarisations, of the receive antenna.  
EUT orientation in three orthogonal planes.  
Maximum results recorded.


The test equipment used for the Transmitter Spurious Emissions – Radiated – Part 15.209 tests is shown below:

TYPE OF EQUIPMENT	MAKER/ SUPPLIER	MODEL No	SERIAL No	TRL No	ACTUAL EQUIPMENT USED
AE, LOOP, Z2, 9kHz - 30MHz	ROHDE & SCHWARZ	HFH2	881058 - 53	07	
HORN ANTENNA	EMCO	3115	9010-3580	138	X
HORN ANTENNA	EMCO	3115	9010-3581	139	
RECEIVER	ROHDE & SCHWARZ	ESHS 10	830051/001	UH03	
RECEIVER	ROHDE & SCHWARZ	ESVS 10	844594/003	352	X
RANGE 1	TRL	3 METRE	N/A	UH06	X
AE, LOOP, Z2, 9kHz - 30MHz	ROHDE & SCHWARZ	HFH2	881058 - 53	07	
BILOG ANTENNA	CHASE	CBL6112	2129	UH93	X
SPECTRUM ANALYSER	ROHDE & SCHWARZ	FSU	200034	UH281	X
PRE AMPLIFIER	AGILENT	8449B	3008A01610	572	X

**ANNEX A**  
**PHOTOGRAPHS**

PHOTOGRAPH No. 1

**TEST SETUP**



PHOTOGRAPH No. 2

**POWERLINE TEST SETUP**




PHOTOGRAPH No. 3

**OVERVIEW**




PHOTOGRAPH No. 4

**CONNECTOR OVERVIEW**




PHOTOGRAPH No. 5

**INTERFACE PCB COMPONENT SIDE**




PHOTOGRAPH No. 6

**INTERFACE PCB TRACK SIDE**




PHOTOGRAPH No. 7

**RF PCB TOP**



PHOTOGRAPH No. 7

**RF PCB BOTTOM**



**ANNEX B**  
**APPLICANT'S SUBMISSION OF DOCUMENTATION LIST**

## APPLICANT'S SUBMISSION OF DOCUMENTATION LIST

a.	TCB	-	APPLICATION	[X]
		-	FEE	[X]
b.	AGENT'S LETTER OF AUTHORISATION	-		[X]
c.	MODEL(s) vs IDENTITY	-		[ ]
d.	ALTERNATIVE TRADE NAME DECLARATION(s)	-		[X]
e.	LABELLING	-	PHOTOGRAPHS	[X]
		-	DECLARATION	[ ]
		-	DRAWINGS	[X]
f.	TECHNICAL DESCRIPTION	-		[X]
g.	BLOCK DIAGRAMS	-	Tx	[X]
		-	Rx	[ ]
		-	PSU	[ ]
		-	AUX	[ ]
h.	CIRCUIT DIAGRAMS	-	Tx	[X]
		-	Rx	[ ]
		-	PSU	[ ]
		-	AUX	[ ]
i.	COMPONENT LOCATION	-	Tx	[X]
		-	Rx	[ ]
		-	PSU	[ ]
		-	AUX	[ ]
j.	PCB TRACK LAYOUT	-	Tx	[X]
		-	Rx	[ ]
		-	PSU	[ ]
		-	AUX	[ ]
k.	BILL OF MATERIALS	-	Tx	[X]
		-	Rx	[ ]
		-	PSU	[ ]
		-	AUX	[ ]
l.	USER INSTALLATION / OPERATING INSTRUCTIONS	-		[X]

**ANNEX C**  
**EQUIPMENT CALIBRATION DETAILS**

## EQUIPMENT CALIBRATION

TRL Number	Equipment Type	Manufacturer	Last Cal Calibration	Calibration Period	Due For Calibration
UH06/07	IC OATS Submission	TRL	01/06/2007	24	01/06/2009
UH06/07	NSA Calibration	TRL	17/12/2007	12	17/12/2008
UH006	3m Range ERP CAL	TRL	08/12/2006	12	08/12/2007
UH028	Log Periodic Ant	Schwarbeck	30/05/2007	24	30/05/2009
UH029	Bicone Antenna	Schwarbeck	06/05/2007	24	06/05/2009
UH041	Multimeter	AVometer	15/01/2008	12	15/01/2009
UH093	Bilog Antenna	Chase	21/05/2007	24	21/05/2009
UH122	Oscilloscope	Tektronix	10/12/2007	24	10/12/2009
UH132	Power meter	Marconi	15/01/2008	12	15/01/2009
UH162	ERP Cable Cal	TRL	21/12/2007	12	21/12/2008
UH187	Receiver	R&S	12/12/2007	12	12/12/2008
UH195	LISN	R&S	04/01/2008	12	04/01/2009
UH228	Power Sensor	Marconi	16/01/2008	12	16/01/2009
UH253	1m Cable N type	TRL	30/01/2008	12	30/01/2009
UH254	1m Cable N type	TRL	30/01/2008	12	30/01/2009
UH269	1m Cable N type	TRL	30/01/2008	12	30/01/2009
UH270	1m Cable N type	TRL	30/01/2008	12	30/01/2009
UH271	1.5m Cable N type	TRL	30/01/2008	12	30/01/2009
UH272	1.5m Cable N type	TRL	30/01/2008	12	30/01/2009
UH273	2m Cable N type	TRL	30/01/2008	12	30/01/2009
UH274	2m Cable N type	TRL	30/01/2008	12	30/01/2009
UH281	Spectrum Analyser	R&S	24/10/2007	12	24/10/2008
UH330	K type transition	Maury M'wave	13/06/2008	24	13/06/2010
UH340	Signal Generator		06/05/2008	12	06/05/2009
UH365	Harmonic Mixer		16/07/2008	24	16/07/2010
UH366	Harmonic Mixer		21/07/2008	24	21/07/2010
UH367	Harmonic Mixer		02/07/2008	24	02/07/2010
L005	CMTA	R&S	30/10/2007	12	30/10/2008
L007	Loop Antenna	R&S	22/05/2007	24	22/05/2009
L138	1-18GHz Horn	EMCO	23/05/2007	24	23/05/2009
L139	1-18GHz Horn	EMCO	23/05/2007	24	23/05/2009
L176	Signal Generator	Marconi	06/05/2008	12	06/05/2009
L193	Bicone Antenna	Chase	06/05/2008	24	06/05/2010
L203	Log Periodic Ant	Chase	06/05/2008	24	06/05/2010
L263/A	Horn 18-26GHz	Flann	13/06/2008	24	13/06/2010
L300	Horn 18-26GHz	Flann	12/06/2008	24	12/06/2010
L309	SMA Transition		13/06/2008	24	13/06/2010
L352	Receiver	R&S	05/12/2007	12	05/12/2008
L426	Temperature Indicator	Fluke	22/01/2008	12	22/01/2009
L479	Analysyer	Anritsu	22/09/2008	12	22/09/2009
L572	Pre Amp	Agilent	04/07/2008	12	04/07/2009

**ANNEX D**  
**MEASUREMENT UNCERTAINTY**

## Radio Testing – General Uncertainty Schedule

All statements of uncertainty are expanded standard uncertainty using a coverage factor of 1.96 to give a 95% confidence where no required test level exists.

### **[1] Adjacent Channel Power**

Uncertainty in test result = **1.86dB**

### **[2] Carrier Power**

Uncertainty in test result (Equipment - TRLUH120) = **2.18dB**

Uncertainty in test result (Equipment – TRL05) = **1.08dB**

Uncertainty in test result (Equipment – TRL479) = **2.48dB**

### **[3] Effective Radiated Power**

Uncertainty in test result = **4.71dB**

### **[4] Spurious Emissions**

Uncertainty in test result = **4.75dB**

### **[5] Maximum frequency error**

Uncertainty in test result (Equipment - TRLUH120) = **119ppm**

Uncertainty in test result (Equipment – TRL05) = **0.113ppm**

Uncertainty in test result (Equipment – TRL479) = **0.265ppm**

### **[6] Radiated Emissions, field strength OATS 14kHz-18GHz Electric Field**

Uncertainty in test result (14kHz – 30MHz) = **4.8dB**, Uncertainty in test result (30MHz – 1GHz) = **4.6dB**,  
Uncertainty in test result (1GHz-18GHz) = **4.7dB**

### **[7] Frequency deviation**

Uncertainty in test result = **3.2%**

### **[8] Magnetic Field Emissions**

Uncertainty in test result = **2.3dB**

### **[9] Conducted Spurious**

Uncertainty in test result (Equipment TRL479) Up to 8.1GHz = **3.31dB**

Uncertainty in test result (Equipment TRL479) 8.1GHz – 15.3GHz = **4.43dB**

Uncertainty in test result (Equipment TRL479) 15.3GHz – 21GHz = **5.34dB**

Uncertainty in test result (Equipment TRLUH120) Up to 26GHz = **3.14dB**

### **[10] Channel Bandwidth**

Uncertainty in test result = **15.5%**

### **[11] Amplitude and Time Measurement – Oscilloscope**

Uncertainty in overall test level = **2.1dB**, Uncertainty in time measurement = **0.59%**, Uncertainty in Amplitude measurement = **0.82%**

### **[11] Power Line Conduction**

Uncertainty in test result = **3.4dB**

**[12] Spectrum Mask Measurements**

Uncertainty in test result = **2.59% (frequency)**  
Uncertainty in test result = **1.32dB (amplitude)**

**[13] Adjacent Sub Band Selectivity**

Uncertainty in test result = **1.24dB**

**[14] Receiver Blocking – Listen Mode, Radiated**

Uncertainty in test result = **3.42dB**

**[15] Receiver Blocking – Talk Mode, Radiated**

Uncertainty in test result = **3.36dB**

**[16] Receiver Blocking – Talk Mode, Conducted**

Uncertainty in test result = **1.24dB**


**[17] Receiver Threshold**

Uncertainty in test result = **3.23dB**

**[18] Transmission Time Measurement**


Uncertainty in test result = **7.98%**

**ANNEX E**  
**POWER LINE CONDUCTION**




**ANNEX F**  
**RADIATED EMISSIONS**

## RADIATED EMISSIONS 30MHz – 1 GHz




## RADIATED EMISSIONS 1GHz –5GHz




Date: 14.OCT.2008 15:25:14

## RADIATED EMISSIONS 5GHz –9GHz




Date: 14.OCT.2008 15:28:32

## RADIATED EMISSIONS 9GHz – 13GHz




Date: 14.OCT.2008 15:28:32

## RADIATED EMISSIONS 13GHz – 18GHz




Date: 14.OCT.2008 15:30:20

## RADIATED EMISSIONS 18GHz – 22GHz



Date: 14.OCT.2008 16:38:57


## RADIATED EMISSIONS 22GHz – 25GHz



Date: 14.OCT.2008 16:40:13


**ANNEX G**  
**RADIATED BANDEdge COMPLIANCE**

## RADIATED LOWER BAND EDGE



Date: 14.OCT.2008 15:47:14


## RADIATED UPPER BAND EDGE



Date: 14.OCT.2008 15:51:10

**ANNEX H**  
**6dB BANDWIDTH**

## 6dB BANDWIDTH




Date: 14.OCT.2008 15:58:46

$$\begin{aligned}
 f_{\text{lower}} &= 2404.153846 \text{ MHz} \\
 f_{\text{higher}} &= 2405.764423 \text{ MHz} \\
 \text{6dB Bandwidth} &= 1610.577 \text{ MHz}
 \end{aligned}$$

**ANNEX I**  
**PEAK OUTPUT POWER**


## OUTPUT POWER



Date: 15.OCT.2008 16:12:01

**ANNEX J**  
**POWER SPECTRAL DENSITY**

## POWER SPECTRAL DENSITY



Date: 15.OCT.2008 17:22:27