

Electromagnetic Emissions Test Report Application for Grant of Equipment Authorization Class II Permissive Change pursuant to FCC Part 15 Subpart C on the J-Link Co., Ltd Transmitter Model: iTrip Universal - P1141

> FCC ID: TVT1141

GRANTEE: J-Link Co., Ltd

No. 28-12 Gangkou, Gangnan Village,

Anding Township

Tainan County 745 Taiwan, R.O.C.

TEST SITE(S): **Elliott Laboratories**

41039 Boyce Road.

Fremont, CA. 94538-2435

IC Site Registration #: IC 4549-3

REPORT DATE: February 5, 2009

FINAL TEST DATE: January 20, 2009

AUTHORIZED SIGNATORY:

Mark E. Hill Staff Engineer



Testing Cert #2016-01

Elliott Laboratories is accredited by the A2LA, certificate number 2016-01, to perform the test(s) listed in this report. This report shall not be reproduced, except in its entirety, without the written approval of Elliott Laboratories

REVISION HISTORY

Rev#	Date	Comments	Modified By
1	February 10, 2009	Initial Release	-

File: R74496 Rev 1 Page 2 of 17

TABLE OF CONTENTS

COVER PAGE	1
REVISION HISTORY	2
TABLE OF CONTENTS	3
SCOPE	5
OBJECTIVE	
STATEMENT OF COMPLIANCE	6
TEST RESULTS SUMMARY	6
DEVICES OPERATING IN THE 88-108 MHZ FM BANDGENERAL REQUIREMENTS APPLICABLE TO ALL BANDS	
MEASUREMENT UNCERTAINTIES	7
EQUIPMENT UNDER TEST (EUT) DETAILS	7
GENERAL	
ANTENNA SYSTEM	7
ENCLOSURE	
MODIFICATIONSSUPPORT EQUIPMENT	
EUT INTERFACE PORTS	8
EUT OPERATION	
PROPOSED MODIFICATION DETAILS	8
GENERAL	8
TEST SITE	9
GENERAL INFORMATION	
CONDUCTED EMISSIONS CONSIDERATIONS	
RADIATED EMISSIONS CONSIDERATIONS	
MEASUREMENT INSTRUMENTATION	
RECEIVER SYSTEM	
INSTRUMENT CONTROL COMPUTERLINE IMPEDANCE STABILIZATION NETWORK (LISN)	
FILTERS/ATTENUATORS	11
ANTENNAS	11
ANTENNA MAST AND EQUIPMENT TURNTABLE INSTRUMENT CALIBRATION	
TEST PROCEDURES	
EUT AND CABLE PLACEMENT	
RADIATED EMISSIONS	
BANDWIDTH MEASUREMENTS	15
SPECIFICATION LIMITS AND SAMPLE CALCULATIONS	
GENERAL TRANSMITTER RADIATED EMISSIONS SPECIFICATION LIMITSRADIATEDFUNDAMENTAL & SPURIOUS EMISSIONS SPECIFICATION LIMITS – 15.239 AND RS	
A2.9	16
SAMPLE CALCULATIONS - RADIATED EMISSIONS	16
SAMPLE CALCULATIONS - FIELD STRENGTH TO EIRP CONVERSION	17

TABLE OF CONTENTS (Continued)

EXHIBIT 1: Test Equipment Calibration Data	1
EXHIBIT 2: Test Measurement Data	
EXHIBIT 3: Photographs of Test Configurations	
EXHIBIT 4: Proposed FCC ID Label & Label Location	
EXHIBIT 5: Detailed Photographs	
EXHIBIT 6: Schematic Diagrams	
EXHIBIT 7: RF Exposure Information	
Zillizii / Til Zilposwo ilgomicilo	••••

Page 4 of 17 File: R74496 Rev 1

SCOPE

An electromagnetic emissions test has been performed on the J-Link Co., Ltd model iTrip Universal - P1141 pursuant to the following rules:

FCC Part 15 Subpart C

Conducted and radiated emissions data has been collected, reduced, and analyzed within this report in accordance with measurement guidelines set forth in the following reference standards and as outlined in Elliott Laboratories test procedures:

ANSI C63.4:2003

The intentional radiator above has been tested in a simulated typical installation to demonstrate compliance with the relevant Industry Canada performance and procedural standards.

Final system data was gathered in a mode that tended to maximize emissions by varying orientation of EUT, orientation of power and I/O cabling, antenna search height, and antenna polarization.

Every practical effort was made to perform an impartial test using appropriate test equipment of known calibration. All pertinent factors have been applied to reach the determination of compliance.

The test results recorded herein are based on a single type test of the J-Link Co., Ltd model iTrip Universal - P1141 and therefore apply only to the tested sample. The sample was selected and prepared by Jeff Altheide of Griffin Technology.

OBJECTIVE

The primary objective of the manufacturer is compliance with the regulations outlined in the previous section.

Prior to marketing in the USA, all unlicensed transmitters and transceivers require certification. Receive-only devices operating between 30 MHz and 960 MHz are subject to either certification or a manufacturer's declaration of conformity, with all other receive-only devices exempt from the technical requirements.

Certification is a procedure where the manufacturer submits test data and technical information to a certification body and receives a certificate or grant of equipment authorization upon successful completion of the certification body's review of the submitted documents. Once the equipment authorization has been obtained, the label indicating compliance must be attached to all identical units, which are subsequently manufactured.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product which may result in increased emissions should be checked to ensure compliance has been maintained (i.e., printed circuit board layout changes, different line filter, different power supply, harnessing or I/O cable changes, etc.).

File: R74496 Rev 1 Page 5 of 17

STATEMENT OF COMPLIANCE

The tested sample of J-Link Co., Ltd model iTrip Universal - P1141 complied with the requirements of the following regulations:

FCC Part 15 Subpart C

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product which may result in increased emissions should be checked to ensure compliance has been maintained (i.e., printed circuit board layout changes, different line filter, different power supply, harnessing or I/O cable changes, etc.).

TEST RESULTS SUMMARY

DEVICES OPERATING IN THE 88-108 MHz FM BAND

FCC Rule Part	Description	Measured Value / Comments	Limit / Requirement	Result
15.239 (a)	Bandwidth and operating range	170kHz	Bandwidth less than 200kHz contained in the 88 – 108 MHz band	
15.239 (b)	Fundamental Field Strength	47.8dBuV/m @ 88.1MHz (-0.2dB)	250uV/m at 3m	Complies
15.239 (c) / 15.209	Radiated Spurious Emissions, 30 – 540 MHz	41.8dBμV/m @ 176.200MHz (-1.7dB)	Refer to table in limits section	Complies

GENERAL REQUIREMENTS APPLICABLE TO ALL BANDS

FCC Rule Part	Description	Measured Value / Comments	Limit / Requirement	Result (margin)
15.203	RF Connector	Antenna integral to the EUT	Refer to standard	Complies
15.109	Receiver spurious emissions	-	-	N/A - Note
15.207	AC Conducted Emissions		-	N/A – Note 1
15.247 (b) (5) 15.407 (f)	RF Exposure Requirements	RSS 102 declaration	Refer to OET 65, FCC Part 1 and RSS 102	Complies

Note 1 – The EUT is powered from the iPod and does not allow for charging of the iPod while connected.

Note 2 - The EUT does not have a receive function..

File: R74496 Rev 1 Page 6 of 17

MEASUREMENT UNCERTAINTIES

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level and were calculated in accordance with UKAS document LAB 34.

Measurement Type	Frequency Range (MHz)	Calculated Uncertainty (dB)
Conducted Emissions	0.15 to 30	± 2.4
Radiated Emissions	0.015 to 30	± 3.0
Radiated Emissions	30 to 1000	± 3.6
Radiated Emissions	1000 to 40000	± 6.0

EQUIPMENT UNDER TEST (EUT) DETAILS

GENERAL

The J-Link Co., Ltd model iTrip Universal - P1141 is a portable FM transmitter that is designed to transmit audio information from an iPod or a computer. For this testing, the EUT was placed on a table-top. The EUT is powered via the USB port of a computer, or via the 12V automobile power outlet.

The sample was received on January 20, 2009 and tested on January 20, 2009. The EUT consisted of the following component(s):

Manufacturer	Model	Description	Serial Number	FCC ID
Griffin	iTrip Universal -	FM Transmitter	N/A	TVT1141
	P1141			

ANTENNA SYSTEM

The antenna system used with the J-Link Co., Ltd model iTrip Universal - P1141 is integral to the device.

ENCLOSURE

The EUT enclosure is primarily constructed of plastic. It measures approximately 3 cm wide by 7 cm deep by 1.3 cm high.

MODIFICATIONS

The EUT did not require modifications during testing in order to comply with emissions specifications.

File: R74496 Rev 1 Page 7 of 17

Report Date: February 5, 2009

SUPPORT EQUIPMENT

The following equipment was used as local support equipment for emissions testing:

	Manufacturer	Model	Description	Serial Number	FCC ID
Ī	Apple	iPod NANO	MP3 Player	-	N/A

No remote support equipment was used during emissions testing.

EUT INTERFACE PORTS

The I/O cabling configuration during emissions testing was as follows:

Port Connected To		Cable(s)		
Port	Connected 10	Description	Shielded or Unshielded	Length(m)
Audio	IPod Audio	Audio Cable	Shielded	0.4

Note: The audio cable used was consistent with the cable provided with the device at the time of sale.

EUT OPERATION

During emissions testing the EUT was configured to play a typical music file in a continuous loop.

PROPOSED MODIFICATION DETAILS

GENERAL

Changes were made to the battery charge circuitry that resulted in a layout change and the need to revise the power settings in order to comply with the requirements.

File: R74496 Rev 1 Page 8 of 17

TEST SITE

GENERAL INFORMATION

Final test measurements were taken on January 20, 2009 at the test sites listed below. Pursuant to section 2.948 of the FCC's Rules and section 3.3 of RSP-100, construction, calibration, and equipment data has been filed with the Commission and with industry Canada.

Site	Registration Numbers		Location
Site	FCC	Canada	
Chamber 3	769238	IC 4549-3	41039 Boyce Road Fremont, CA 94538-2435

ANSI C63.4:2003 recommends that ambient noise at the test site be at least 6 dB below the allowable limits. Ambient levels are below this requirement. The test site(s) contain separate areas for radiated and conducted emissions testing. Considerable engineering effort has been expended to ensure that the facilities conform to all pertinent requirements of ANSI C63.4:2003.

CONDUCTED EMISSIONS CONSIDERATIONS

Conducted emissions testing is performed in conformance with ANSI C63.4:2003. Measurements are made with the EUT connected to the public power network through a nominal, standardized RF impedance, which is provided by a line impedance stabilization network, known as a LISN. A LISN is inserted in series with each current-carrying conductor in the EUT power cord.

RADIATED EMISSIONS CONSIDERATIONS

The FCC has determined that radiation measurements made in a shielded enclosure are not suitable for determining levels of radiated emissions. Radiated measurements are performed in an open field environment or in a semi-anechoic chamber. The test sites are maintained free of conductive objects within the CISPR defined elliptical area incorporated in ANSI C63.4:2003 guidelines and meet the Normalized Site Attenuation (NSA) requirements of ANSI C63.4:2003.

File: R74496 Rev 1 Page 9 of 17

MEASUREMENT INSTRUMENTATION

RECEIVER SYSTEM

An EMI receiver as specified in CISPR 16-1 is used for emissions measurements. The receivers used can measure over the frequency range of 9 kHz up to 2000 MHz. These receivers allow both ease of measurement and high accuracy to be achieved. The receivers have Peak, Average, and CISPR (Quasi-peak) detectors built into their design so no external adapters are necessary. The receiver automatically sets the required bandwidth for the CISPR detector used during measurements. If the repetition frequency of the signal being measured is below 20Hz, peak measurements are made in lieu of Quasi-Peak measurements.

For measurements above the frequency range of the receivers, a spectrum analyzer is utilized because it provides visibility of the entire spectrum along with the precision and versatility required to support engineering analysis. Average measurements above 1000MHz are performed on the spectrum analyzer using the linear-average method with a resolution bandwidth of 1 MHz and a video bandwidth of 10 Hz, unless the signal is pulsed in which case the average (or video) bandwidth of the measuring instrument is reduced to onset of pulse desensitization and then increased.

INSTRUMENT CONTROL COMPUTER

The receivers utilize either a Rohde & Schwarz EZM Spectrum Monitor/Controller or contain an internal Spectrum Monitor/Controller to view and convert the receiver measurements to the field strength at an antenna or voltage developed at the LISN measurement port, which is then compared directly with the appropriate specification limit. This provides faster, more accurate readings by performing the conversions described under Sample Calculations within the Test Procedures section of this report. Results are printed in a graphic and/or tabular format, as appropriate. A personal computer is used to record all measurements made with the receivers.

The Spectrum Monitor provides a visual display of the signal being measured. In addition, the controller or a personal computer run automated data collection programs which control the receivers. This provides added accuracy since all site correction factors, such as cable loss and antenna factors are added automatically.

LINE IMPEDANCE STABILIZATION NETWORK (LISN)

Line conducted measurements utilize a fifty microhenry Line Impedance Stabilization Network as the monitoring point. The LISN used also contains a 250 uH CISPR adapter. This network provides for calibrated radio frequency noise measurements by the design of the internal low pass and high pass filters on the EUT and measurement ports, respectively.

File: R74496 Rev 1 Page 10 of 17

Report Date: February 5, 2009

FILTERS/ATTENUATORS

External filters and precision attenuators are often connected between the receiving antenna or LISN and the receiver. This eliminates saturation effects and non-linear operation due to high amplitude transient events.

ANTENNAS

A loop antenna is used below 30 MHz. For the measurement range 30 MHz to 1000 MHz either a combination of a biconical antenna and a log periodic or a bi-log antenna is used. Above 1000 MHz, horn antennas are used. The antenna calibration factors to convert the received voltage to an electric field strength are included with appropriate cable loss and amplifier gain factors to determine an overall site factor, which is then programmed into the test receivers or incorporated into the test software.

ANTENNA MAST AND EQUIPMENT TURNTABLE

The antennas used to measure the radiated electric field strength are mounted on a non-conductive antenna mast equipped with a motor-drive to vary the antenna height. Measurements below 30 MHz are made with the loop antenna at a fixed height of 1m above the ground plane.

ANSI C63.4:2003 specifies that the test height above ground for table mounted devices shall be 80 centimeters. Floor mounted equipment shall be placed on the ground plane if the device is normally used on a conductive floor or separated from the ground plane by insulating material from 3 to 12 mm if the device is normally used on a non-conductive floor. During radiated measurements, the EUT is positioned on a motorized turntable in conformance with this requirement.

INSTRUMENT CALIBRATION

All test equipment is regularly checked to ensure that performance is maintained in accordance with the manufacturer's specifications. All antennas are calibrated at regular intervals with respect to tuned half-wave dipoles. An exhibit of this report contains the list of test equipment used and calibration information.

TEST PROCEDURES

EUT AND CABLE PLACEMENT

The regulations require that interconnecting cables be connected to the available ports of the unit and that the placement of the unit and the attached cables simulate the worst case orientation that can be expected from a typical installation, so far as practicable. To this end, the position of the unit and associated cabling is varied within the guidelines of ANSI C63.4:2003, and the worst-case orientation is used for final measurements.

File: R74496 Rev 1 Page 11 of 17


RADIATED EMISSIONS

A preliminary scan of the radiated emissions is performed in which all significant EUT frequencies are identified with the system in a nominal configuration. At least two scans are performed, one scan for each antenna polarization (horizontal and vertical; loop parallel and perpendicular to the EUT). During the preliminary scans, the EUT is rotated through 360°, the antenna height is varied (for measurements above 30 MHz) and cable positions are varied to determine the highest emission relative to the limit. Preliminary scans may be performed in a fully anechoic chamber for the purposes of identifying the frequencies of the highest emissions from the EUT.

A speaker is provided in the receiver to aid in discriminating between EUT and ambient emissions. Other methods used during the preliminary scan for EUT emissions involve scanning with near field magnetic loops, monitoring I/O cables with RF current clamps, and cycling power to the EUT.


Final maximization is a phase in which the highest amplitude emissions identified in the spectral search are viewed while the EUT azimuth angle is varied from 0 to 360 degrees relative to the receiving antenna. The azimuth, which results in the highest emission is then maintained while varying the antenna height from one to four meters (for measurements above 30 MHz, measurements below 30 MHz are made with the loop antenna at a fixed height of 1m). The result is the identification of the highest amplitude for each of the highest peaks. Each recorded level is corrected in the receiver using appropriate factors for cables, connectors, antennas, and preamplifier gain.

When testing above 18 GHz, the receive antenna is located at 1meter from the EUT and the antenna height is restricted to a maximum of 2.5 meters.




Typical Test Configuration for Radiated Field Strength Measurements

File: R74496 Rev 1 Page 12 of 17




The ground plane extends beyond the ellipse defined in CISPR 16 / CISPR 22 / ANSI C63.4 and is large enough to accommodate test distances (d) of 3m and 10m. Refer to the test data tables for the actual measurement distance.




<u>Test Configuration for Radiated Field Strength Measurements</u>
<u>OATS- Plan and Side Views</u>

File: R74496 Rev 1 Page 13 of 17



The anechoic materials on the walls and ceiling ensure compliance with the normalized site attenuation requirements of CISPR 16 / CISPR 22 / ANSI C63.4 for an alternate test site at the measurement distances used.

Floor-standing equipment is placed on the floor with insulating supports between the unit and the ground plane.



<u>Test Configuration for Radiated Field Strength Measurements</u> Semi-Anechoic Chamber, Plan and Side Views

File: R74496 Rev 1 Page 14 of 17

BANDWIDTH MEASUREMENTS

The 6dB, 20dB and/or 26dB signal bandwidth is measured in using the bandwidths recommended by ANSI C63.4. When required, the 99% bandwidth is measured using the methods detailed in RSS GEN.

SPECIFICATION LIMITS AND SAMPLE CALCULATIONS

The limits for conducted emissions are given in units of microvolts, and the limits for radiated emissions are given in units of microvolts per meter at a specified test distance. Data is measured in the logarithmic form of decibels relative to one microvolt, or dB microvolts (dBuV). For radiated emissions, the measured data is converted to the field strength at the antenna in dB microvolts per meter (dBuV/m). The results are then converted to the linear forms of uV and uV/m for comparison to published specifications.

For reference, converting the specification limits from linear to decibel form is accomplished by taking the base ten logarithm, then multiplying by 20. These limits in both linear and logarithmic form are as follows:

GENERAL TRANSMITTER RADIATED EMISSIONS SPECIFICATION LIMITS

The table below shows the limits for the spurious emissions from transmitters that fall in restricted bands¹ (with the exception of transmitters operating under FCC Part 15 Subpart D and RSS 210 Annex 9), the limits for all emissions from a low power device operating under the general rules of RSS 310 (tables 3 and 4), RSS 210 (table 2) and FCC Part 15 Subpart C section 15.209.

Frequency Range (MHz)	Limit (uV/m)	Limit (dBuV/m @ 3m)
0.009-0.490	2400/F _{KHz} @ 300m	67.6-20*log ₁₀ (F _{KHz}) @ 300m
0.490-1.705	24000/F _{KHz} @ 30m	87.6-20*log ₁₀ (F _{KHz}) @ 30m
1.705 to 30	30 @ 30m	29.5 @ 30m
30 to 88	100 @ 3m	40 @ 3m
88 to 216	150 @ 3m	43.5 @ 3m
216 to 960	200 @ 3m	46.0 @ 3m
Above 960	500 @ 3m	54.0 @ 3m

File: R74496 Rev 1 Page 15 of 17

-

¹ The restricted bands are detailed in FCC 15.203, RSS 210 Table 1 and RSS 310 Table 2

RADIATEDFUNDAMENTAL & SPURIOUS EMISSIONS SPECIFICATION LIMITS - 15.239 and RSS 210 A2.9

Frequency Range (MHz)	Limit for Fundamental @ 3m	Limit for all signals outside of the occupied bandwidth @ 3m
88 - 108	250 uV/m 48 dBuV/m	General limits apply

The occupied bandwidth is limited to 200kHz.

RSS 210 allows the fundamental field strength to be 1000uV/m at 30m at these specific frequencies 88.1; 88.3; 88.5; 107.7; 107.9 MHz is1000uV/m at 30m for FM devices.

SAMPLE CALCULATIONS - RADIATED EMISSIONS

Receiver readings are compared directly to the specification limit (decibel form). The receiver internally corrects for cable loss, preamplifier gain, and antenna factor. The calculations are in the reverse direction of the actual signal flow, thus cable loss is added and the amplifier gain is subtracted. The Antenna Factor converts the voltage at the antenna coaxial connector to the field strength at the antenna elements.

A distance factor, when used for electric field measurements above 30MHz, is calculated by using the following formula:

 $F_d = 20*LOG_{10} (D_m/D_s)$

where:

 F_d = Distance Factor in dB

 $D_m = Measurement Distance in meters$

 D_S = Specification Distance in meters

File: R74496 Rev 1 Page 16 of 17

For electric field measurements below 30MHz the extrapolation factor is either determined by making measurements at multiple distances or a theoretical value is calculated using the formula:

$$F_d = 40*LOG_{10} (D_m/D_s)$$

Measurement Distance is the distance at which the measurements were taken and Specification Distance is the distance at which the specification limits are based. The antenna factor converts the voltage at the antenna coaxial connector to the field strength at the antenna elements.

The margin of a given emission peak relative to the limit is calculated as follows:

$$R_c = R_r + F_d$$

and

$$M = R_c - L_s$$

where:

 R_r = Receiver Reading in dBuV/m

 F_d = Distance Factor in dB

 R_C = Corrected Reading in dBuV/m

 L_S = Specification Limit in dBuV/m

M = Margin in dB Relative to Spec

SAMPLE CALCULATIONS - FIELD STRENGTH TO EIRP CONVERSION

Where the radiated electric field strength is expressed in terms of the equivalent isotropic radiated power (eirp), or where a field strength measurement of output power is made in lieu of a direct measurement, the following formula is used to convert between eirp and field strength at a distance of 3m from the equipment under test:

E =
$$\frac{1000000 \sqrt{30 P}}{3}$$
 microvolts per meter
3
where P is the eirp (Watts)

File: R74496 Rev 1 Page 17 of 17

EXHIBIT 1: Test Equipment Calibration Data

1 Page

File: R74496 Rev 1 Exhibit Page 1 of 7

Radiated Emissions, 30 - 1,000 MHz, 07-Jan-09 **Engineer: rvarelas Manufacturer Description** Model # Asset # Cal Due Power Meter, Single Channel Rohde & Schwarz NRVS 05-Mar-09 1534 **Sunol Sciences** Biconilog, 30-3000 MHz JB3 1548 13-Jun-10 Hewlett Packard Preamplifier, 100 kHz - 1.3 GHz 1606 8447E 29-May-09

Radiated Emissions, 30 - 1,000 MHz, 21-Jan-09

Engineer: rvarelas

<u>Manufacturer</u>	<u>Description</u>	Model #	Asset #	Cal Due
Com-Power Corp.	Preamplifier, 30-1000 MHz	PA-103	1543	14-Nov-09
Sunol Sciences	Biconilog, 30-3000 MHz	JB3	1657	23-May-10
Rohde & Schwarz	EMI Test Receiver, 20 Hz-7 GHz	ESIB7	1756	04-Feb-09

EXHIBIT 2: Test Measurement Data

10 Pages

File: R74496 Rev 1 Exhibit Page 2 of 7

Elliot	t	EM	C Test Data
Client:	J-Link	Job Number:	J74189
Model:	iTrip Universal - P1141	Test-Log Number:	T74216
		Project Manager:	Sheareen
Contact:	Jeff Altheide		
Emissions Spec:	FCC 15.239/RSS 210, Issue 7	Class:	В
Immunity Spec:	-	Environment:	-

EMC Test Data

For The

J-Link

Model

iTrip Universal - P1141

Date of Last Test: 1/20/2009



EMC Test Data

Client:	J-Link	Job Number:	J74189
Model:	iTrip Universal - P1141	Test-Log Number: T74216	
		Project Manager:	Sheareen
Contact:	Jeff Altheide		
Emissions Spec:	FCC 15.239/RSS 210, Issue 7	Class:	В
Immunity Spec:		Environment:	-

EUT INFORMATION

The following information was collected during the test sessions(s).

General Description

The EUT is a portable FM transmitter that is designed to transmit audio information from an iPod or a computer. For this testing, the EUT was placed on a table-top. The EUT is powered via the USB port of a computer, or via the 12V automobile power outlet.

Equipment Under Test

Manufacturer	Model	Description	Serial Number	FCC ID
J-Link	iTrip Universal - P1141	FM Transmitter	N/A	TVT1141

EUT Antenna (Intentional Radiators Only)

The antenna is integral to the device.

EUT Enclosure

The EUT enclosure is primarily constructed of plastic. It measures approximately 3 cm wide by 7 cm deep by 1.3 cm high.

Modification History

Mod. #	Test	Date	Modification
1			
2			
3			

Modifications applied are assumed to be used on subsequent tests unless otherwise stated as a further modification.

Elliott EMC Test Data				
Client:	J-Link	Job Number:	J74189	
Model:	iTrip Universal - P1141	T-Log Number:	T74216	
		Project Manager:	Sheareen	
Contact:	Jeff Altheide			
Emissions Spec:	FCC 15.239/RSS 210, Issue 7	Class:	В	
Immunity Spec:	-	Environment:	-	

Test Configuration #1
The following information was collected during the test sessions(s).

Local Support Equipment

Manufacturer	Model	Description	Serial Number	FCC ID
Apple	iPod Nano	MP3 Player	N/A	N/A

Remote Support Equipment

	11 11						
Manufacturer	Model	Description	Serial Number	FCC ID			
-	-	-	-	-			

Cabling and Ports

Port	Connected To	Cable(s)		
		Description Shielded or Unshielded Length(m)		
iPod Audio Output	EUT	Audio Cable	Shielded	0.4

EUT Operation During Emissions Tests

During emissions testing the EUT was configured to play an typical music file in a continuous loop.

EMC Test Data

V			
Client:	J-Link	Job Number:	J74189
Model:	iTrip Universal - P1141	T-Log Number:	T74216
	Trip Offiversal - P1141	Account Manager:	Sheareen
Contact:	Jeff Altheide		
Standard:	FCC 15.239/RSS 210, Issue 7	Class:	В

Radiated Emissions

(Elliott Laboratories Fremont Facility, Semi-Anechoic Chamber)

Test Specific Details

Objective: The objective of this test session is to perform final qualification testing of the EUT with respect to the

specification listed above.

Date of Test: 1/20/2009 Config. Used: 1
Test Engineer: Rafael Varelas Config Change: None

Test Location: Fremont Chamber #3 EUT Voltage: Internal Battery

General Test Configuration

The EUT and any local support equipment were located on the turntable for radiated emissions testing.

The test distance and extrapolation factor (if applicable) are detailed under each run description.

Note, **preliminary** testing indicates that the emissions were maximized by orientation of the EUT and elevation of the measurement antenna. **Maximized** testing indicated that the emissions were maximized by orientation of the EUT, elevation of the measurement antenna, and manipulation of the EUT's interface cables.

Ambient Conditions: Temperature: 19.2 °C

Rel. Humidity: 39 %

Summary of Results

Run #	Test Performed	Limit	Result	Margin
1	RE, Fundamental Measurements	FCC 15.239	Pass	47.8dBµV/m @ 88.100MHz (-0.2dB)
2	RE, 30 - 1000 MHz	FCC 15.239	Pass	41.8dBµV/m @ 176.200MHz (-1.7dB)
3	Bandwidth Measurements	FCC 15.239	Pass	170 kHz

Modifications Made During Testing

No modifications were made to the EUT during testing

Deviations From The Standard

No deviations were made from the requirements of the standard.

Frequency Range	Test Distance	Limit Distance	Extrapolation Factor
30 - 1000 MHz	3	3	0.0

EMC Test Data

_			
Client:	J-Link	Job Number:	J74189
Model:	iTrip Universal - P1141	T-Log Number:	T74216
	TTTP OTIIVEISAI - PTT4T	Account Manager:	Sheareen
Contact:	Jeff Altheide		
Standard:	FCC 15.239/RSS 210, Issue 7	Class:	В

Run #1a: Fundamental

EUT and Test Configuration Details:

EUT configured to transmit a song and volume was set to maximum.

FCC Sample, Elliott tag 2009-2042

Fundamental Measurements

Frequency	Level	Pol	FCC 1	5.239	Detector	Azimuth	Height	Comments
MHz	dBμV/m	v/h	Limit	Margin	Pk/QP/Avg	degrees	meters	
EUT Flat								
88.100	42.1	Н	48.0	-5.9	AVG	189	2.2	Setting = L6
88.100	35.3	V	48.0	-12.7	AVG	296	3.6	Setting = L6
98.100	43.3	Н	48.0	-4.7	AVG	195	3.1	Setting = L2
98.100	37.0	V	48.0	-11.0	AVG	302	1.0	Setting = L2
107.900	42.5	Н	48.0	-5.5	AVG	194	2.8	Setting = L2
107.900	35.5	V	48.0	-12.5	AVG	291	1.0	Setting = L2
EUT Side								
88.100	47.8	Н	48.0	-0.2	AVG	228	2.1	Setting = L6
88.100	41.3	V	48.0	-6.7	AVG	335	3.5	Setting = L6
98.100	47.0	Н	48.0	-1.0	AVG	50	3.1	Setting = L2
98.100	40.2	V	48.0	-7.8	AVG	625	3.9	Setting = L2
107.900	46.5	Н	48.0	-1.5	AVG	51	2.9	Setting = L2
107.900	39.0	V	48.0	-9.0	AVG	333	1.0	Setting = L2
EUT Uprigh	t							
88.100	41.8	V	48.0	-6.2	AVG	294	1.0	Setting = L6
88.100	42.2	Н	48.0	-5.8	AVG	188	3.5	Setting = L6
98.100	42.9	V	48.0	-5.1	AVG	296	1.0	Setting = L2
98.100	43.7	Н	48.0	-4.3	AVG	23	3.2	Setting = L2
107.900	41.4	V	48.0	-6.6	AVG	283	1.0	Setting = L2
107.900	42.6	Н	48.0	-5.4	AVG	26	3.0	Setting = L2

Summary of Worse Case Results - EUT Side

Frequency	Level	Pol	FCC 1	15.239	Detector	Azimuth	Height	Comments	
MHz	dBμV/m	v/h	Limit	Margin	Pk/QP/Avg	degrees	meters		
88.100	47.8	Н	48.0	-0.2	AVG	228	2.1	Setting = L6	
88.095	49.1	Н	68.0	-18.9	Peak	47	2.0	Setting = L6	

EMC Test Data

_			
Client:	J-Link	Job Number:	J74189
Madal	iTrip Universal - P1141	T-Log Number:	T74216
Model.	Timp Oniversal - P1141	Account Manager:	Sheareen
Contact:	Jeff Altheide		
Standard:	FCC 15.239/RSS 210, Issue 7	Class:	В

Run #2a: Radiated Emissions, 30 - 1000 MHz, EUT Side


Low Channel at 88.1 MHz

EUT and Test Configuration Details:

EUT configured to transmit a song and volume was set to maximum.

FCC Sample, Elliott tag 2009-2042

Setting = L6



Frequency	Level	Pol	FCC 1	15.239	Detector	Azimuth	Height	Comments
MHz	dBμV/m	v/h	Limit	Margin	Pk/QP/Avg	degrees	meters	
176.200	41.8	Н	43.5	-1.7	QP	216	1.5	QP (1.00s)
88.095	49.1	Н	-	-	Peak	47	2.0	Fundamental
352.685	27.2	Н	46.0	-18.8	Peak	13	1.0	

EMC Test Data

_			
Client:	J-Link	Job Number:	J74189
Model:	iTrip Universal - P1141	T-Log Number:	T74216
	TTTP OTIIVEISAI - PTT4T	Account Manager:	Sheareen
Contact:	Jeff Altheide		
Standard:	FCC 15.239/RSS 210, Issue 7	Class:	В

Run #2b: Radiated Emissions, 30 - 1000 MHz, EUT Side


Middle Channel at 98.1 MHz

EUT and Test Configuration Details:

EUT configured to transmit a song and volume was set to maximum.

FCC Sample, Elliott tag 2009-2042

Setting = L2



Frequency	Level	Pol	FCC 1	5.239	Detector	Azimuth	Height	Comments
MHz	dBμV/m	v/h	Limit	Margin	Pk/QP/Avg	degrees	meters	
196.198	34.1	Н	43.5	-9.4	QP	212	1.5	QP (1.00s)
98.094	47.0	Н	-	•	Peak	50	3.0	Fundamental
294.311	28.3	Н	46.0	-17.7	Peak	46	1.0	
392.399	26.0	Н	46.0	-20.0	Peak	10	1.0	

EMC Test Data

_			
Client:	J-Link	Job Number:	J74189
Model:	iTrip Universal - P1141	T-Log Number:	T74216
	TTTP OTIIVEISAI - PTT4T	Account Manager:	Sheareen
Contact:	Jeff Altheide		
Standard:	FCC 15.239/RSS 210, Issue 7	Class:	В

Run #2c: Radiated Emissions, 30 - 1000 MHz, EUT Side


High Channel at 107.9 MHz

EUT and Test Configuration Details:


EUT configured to transmit a song and volume was set to maximum.

FCC Sample, Elliott tag 2009-2042

Setting = L2



Frequency	Level	Pol	FCC 1	15.239	Detector	Azimuth	Height	Comments
MHz	dBμV/m	v/h	Limit	Margin	Pk/QP/Avg	degrees	meters	
215.800	36.6	Н	43.5	-6.9	QP	44	1.5	QP (1.00s)
107.908	46.0	Н	1	-	Peak	223	3.0	Fundamental
323.725	29.1	Н	46.0	-16.9	Peak	43	1.0	
431.580	27.6	Н	46.0	-18.4	Peak	3	1.0	






EXHIBIT 3: Photographs of Test Configurations

Exhibit Page 3 of 7 File: R74496 Rev 1

EXHIBIT 4: Proposed FCC ID Label & Label Location

File: R74496 Rev 1 Exhibit Page 4 of 7

EXHIBIT 5: Detailed Photographs of Griffin Technology Model iTrip Universal - P1141Construction

Pages

File: R74496 Rev 1 Exhibit Page 5 of 7

EXHIBIT 6: Schematic Diagrams for Griffin Technology Model iTrip Universal - P1141

Pages

File: R74496 Rev 1 Exhibit Page 6 of 7

EXHIBIT 7: RF Exposure Information

Pages

File: R74496 Rev 1 Exhibit Page 7 of 7