

cetecom  
advanced



Bundesnetzagentur

BNetzA-CAB-02/21-102

## TEST REPORT

Test Report No.: 1-8286/24-01-02\_TR1-R01



**DAkkS**  
Deutsche  
Akkreditierungsstelle  
D-PL-12047-01-00

### Testing Laboratory

**cetecom advanced GmbH**  
Untertürkheimer Straße 6 – 10  
66117 Saarbrücken/Germany  
Phone: + 49 681 5 98 - 0  
Fax: + 49 681 5 98 - 9075  
Internet: <http://www.cetecomadvanced.com>  
e-mail: [mail@cetecomadvanced.com](mailto:mail@cetecomadvanced.com)

#### Accredited Test Laboratory:

The testing laboratory (area of testing) is accredited according to DIN EN ISO/IEC 17025 (2018-03) by the Deutsche Akkreditierungsstelle GmbH (DAkkS).  
The accreditation is valid for the scope of testing procedures as stated in the accreditation certificate with the registration number: D-PL-12047-01-00.  
ISED Testing Laboratory Recognized Listing Number: DE0001  
FCC designation number: DE0002

### Applicant

**Gigaset Technologies GmbH**  
Frankenstraße 2  
46395 Bocholt  
Germany  
Contact: Timo Saturna  
e-mail: [timo.saturna@gigaset.com](mailto:timo.saturna@gigaset.com)

### Manufacturer

**Gigaset Technologies GmbH**  
Frankenstraße 2  
46395 Bocholt  
Germany

FCC Part 15, subpart D: 2016

Isochronous UPCS Device 1920 – 1930 MHz

Industry Canada RSS-213, Issue 3: 2015

2 GHz Licence-exempt Personal Communication Service Devices (LE-PCS)

### Test Standard/s

### Test Item

Kind of product: **DECT Device (PP)**  
Product name: **Gigaset S700H PRO US**  
HVIN: **Gigaset S700H**  
PMN: **Gigaset S700H PRO US**  
FVIN: /  
HMN: /  
FCC ID: **TVU-S700H**  
IC: **8023A-S700H**  
S/N serial number: Radiated: /  
Conducted: /  
HW hardware status: 2964-R302  
SW software status: 130.012.02  
Frequency [MHz]: 1920 -1930  
Type of Modulation: Digital (Gaussian Frequency Shift Keying)  
Number of channels: 5 RF Channels, 5x12 = 60 TDMA Duplex Channels  
Antenna: 1 internal antenna  
Power Supply: 2 x AAA NiMH batteries  
Temperature Range: -20°C to 50°C

**Test Report authorised:**

**Test performed:**

2025-01-27

Luckenbill, Andreas  
Head of Radio and SAR Services

2025-01-27

Wolf, Joachim  
Head of New Services

## 1 Table of contents

1	Table of contents.....	2
2	General information .....	3
2.1	Notes and disclaimer .....	3
2.2	Application details .....	3
3	Test standard/s:.....	3
4	Test Environment .....	4
5	Reporting statements of conformity – decision rule.....	4
6	Measurement uncertainty.....	5
7	Summary of Measurement Results .....	6
8	Test Set-up.....	7
8.1	Frequency Measurements .....	7
8.2	Timing Measurements .....	7
8.3	Conducted Emission Test .....	7
8.4	Radiated Emission Test.....	8
8.5	Power Line Conducted Emissions Test.....	10
8.6	Monitoring Tests.....	11
8.7	Radiated Output Power Test .....	11
9	Detailed Test Results .....	12
9.1	Power Line Conducted Emissions .....	12
9.2	Digital Modulation Techniques .....	15
9.3	Labeling Requirements.....	15
9.4	Antenna Requirements .....	16
9.5	Channel Frequencies .....	16
9.6	Automatic Discontinuation of Transmission.....	17
9.7	Peak Power Output .....	18
9.8	Emission Bandwidth B .....	23
9.9	Power Spectral Density .....	26
9.10	In-Band Unwanted Emissions, Conducted .....	29
9.11	Out-of-Band Emissions, Conducted.....	32
9.12	Carrier Frequency Stability.....	36
9.13	Frame Repetition Stability .....	37
9.14	Frame Period and Jitter.....	37
9.15	Monitoring Threshold, Least Interfered Channel .....	39
9.16	Threshold Monitoring Bandwidth .....	41
9.17	Reaction Time and Monitoring Interval .....	42
9.18	Time and Spectrum Window Access Procedure .....	44
9.19	Acknowledgments and Transmission duration.....	45
9.20	Dual Access Criteria Check .....	47
9.21	Alternative monitoring interval.....	50
9.22	Spurious Emissions (Radiated).....	50
9.23	Receiver Spurious Emissions .....	53
10	Test equipment and ancillaries used for tests.....	56
11	Observations .....	57
	Annex A: Photographs of the Test Set-up .....	57
	Annex B: External Photographs of the EUT .....	57
	Annex C: Internal Photographs of the EUT .....	57
	Annex D: Document History .....	58
	Annex E: Further Information .....	59

## 2 General information

### 2.1 Notes and disclaimer

The test results of this test report relate exclusively to the test item specified in this test report. cetecom advanced GmbH does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item.

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of cetecom advanced GmbH.

The testing service provided by cetecom advanced GmbH has been rendered under the current "General Terms and Conditions for cetecom advanced GmbH".

cetecom advanced GmbH will not be liable for any loss or damage resulting from false, inaccurate, inappropriate or incomplete product information provided by the customer.

Under no circumstances does the cetecom advanced GmbH test report include any endorsement or warranty regarding the functionality, quality or performance of any other product or service provided.

Under no circumstances does the cetecom advanced GmbH test report include or imply any product or service warranties from cetecom advanced GmbH, including, without limitation, any implied warranties of merchantability, fitness for purpose, or non-infringement, all of which are expressly disclaimed by cetecom advanced GmbH.

All rights and remedies regarding vendor's products and services for which cetecom advanced GmbH has prepared this test report shall be provided by the party offering such products or services and not by cetecom advanced GmbH.

In no case this test report can be considered as a Letter of Approval.

**Note: According to customer declaration RF part of Gigaset S700H PRO, R700H PRO, R700H PRO PROTECT, and SL800H PRO are identical.**

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

### 2.2 Application details

Date of receipt of order: 2024-12-10  
Date of receipt of test item: 2025-01-02  
Start of test: 2025-01-06  
End of test: 2025-01-24  
Person(s) present during the test:

## 3 Test standard/s:

Test Standard	Version	Test Standard Description
FCC Part 15, subpart D	2016-06	Isochronous UPCS Device 1920 – 1930 MHz
Industry Canada RSS-213, Issue 3	2015-03	2 GHz Licence-exempt Personal Communication Service Devices (LE-PCS)
ANSI C63.17	2013-08	American National Standard for Methods of Measurement of the Electromagnetic and Operational Compatibility of Unlicensed Personal Communication Services (UPCS) Devices
ANSI C63.4	2014-06	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

## 4 Test Environment


Temperature:	+ 22 °C during room temperature tests + 50 °C during high temperature test - 20 °C during low temperature test
Relative humidity content:	38 %
Air pressure:	not relevant for this kind of testing

## 5 Reporting statements of conformity – decision rule

Only the measured values related to their corresponding limits will be used to decide whether the equipment under test meets the requirements of the test standards listed in chapter 3.

The measurement uncertainty is mentioned in this test report, see chapter 9, but is not taken into account - neither to the limits nor to the measurement results. Measurement results with a smaller margin to the corresponding limits than the measurement uncertainty have a potential risk of more than 5% that the decision might be wrong."

measured value, measurement uncertainty, verdict



## 6 Measurement uncertainty

Measurement uncertainty		
Test case	Uncertainty	
Frequency and Timing	$\pm 1 \times 10^{-7}$	
Antenna Gain	$\pm 3$ dB	
Conducted Level Measurement	> 10 MHz	$\pm 0.28$ dB
	> 3.6 GHz	$\pm 0.39$ dB
	> 7.0 GHz	$\pm 1.00$ dB
	> 13.6 GHz	$\pm 1.32$ dB
Spurious emissions radiated below 30 MHz	$\pm 3$ dB	
Spurious emissions radiated 30 MHz to 1 GHz	$\pm 3$ dB	
Spurious emissions radiated 1 GHz to 12.75 GHz	$\pm 3.7$ dB	
Spurious emissions radiated above 12.75 GHz	$\pm 4.5$ dB	
Spurious emissions conducted below 30 MHz (AC conducted)	$\pm 2.6$ dB	

## 7 Summary of Measurement Results

<input checked="" type="checkbox"/>	<b>No deviations from the technical specifications were ascertained</b>
<input type="checkbox"/>	There were deviations from the technical specifications ascertained

## CFR 47 Part 15 UPCS

Name of test	FCC CFR 47 Paragraph	IC RSS-213 Paragraph	Verdict
Digital Modulation Techniques	15.319(b)	6.1	Complies
Labeling requirements	15.19(a)(3)	RSS-GEN 5.2	Complies
Antenna requirements	15.317, 15.203	4.1(e)	Complies
Power Line Conducted Emission	15.107(a), 15.207(a)	6.3 RSS_GEN 7.2.2	Complies
Emission Bandwidth	15.323(a)	6.4	Complies
In-band Emission	15.323(d)	6.7.2	Complies
Out-of-band Emissions	15.323(d)	6.7.1	Complies
Peak Transmit Power	15.319(c)(e), 15.31(e)	6.5	Complies
Power Spectral Density	15.319(d)	4.3.2.1	Complies
Automatic discontinuation of transmission	15.319(f)	4.3.4(a)	Complies
Carrier frequency stability	15.323(f)	6.2	Complies
Frame repetition stability	15.323(e)	4.3.4(c)	Complies
Frame period and jitter	15.323(e)	4.3.4(c)	Complies
Monitoring threshold, Least interfered channel	15.323(c)(2);(5); (9)	4.3.4(b)	Complies
Monitoring of intended transmit window and maximum reaction time	15.323(c)(1)	4.3.4	Complies
Threshold monitoring bandwidth	15.323(c)(7)	4.3.4	N/A
Reaction time and monitoring interval	15.323(c)(1);(5); (7)	4.3.4	Complies
Access criteria test interval	15.323(c)(4);(6)	4.3.4	Complies
Access criteria functional test	15.323(c)(4);(6)	4.3.4	Complies
Acknowledgments	15.323(c)(4)	4.3.4	Complies
Transmission duration	15.323(c)(3)	4.3.4	Complies
Dual access criteria	15.323(c)(10)	4.3.4	Complies
Alternative monitoring interval	15.323(c)(10);(11)	4.3.4	N/A <sup>2</sup>
Spurious Emissions (Antenna Conducted)	15.323(d)	6.7.1	Complies <sup>3</sup>
Spurious Emissions (Radiated)	15.319(g), 15.109(a), 15.209(a)	4.3.3 RSS-GEN 7.2.3	Complies <sup>4</sup>
Receiver Spurious Emissions	N/A	6.8	Complies

<sup>1</sup> Only applicable for EUT that can initiate a communication link

<sup>2</sup> The client declares that the tested equipment does not implement this provision


<sup>3</sup> The tested equipment has integrated antennas only

<sup>4</sup> Only requirement FCC 15.109 for unintentional radiators was tested radiated

## 8 Test Set-up

### 8.1 Frequency Measurements

**Test Set-up 1:**



This setup is used for measuring Carrier Frequency Stability at nominal and extreme temperatures.

For long term Frequency Stability, the EUT was in loopback-mode and was controlled with the CMD65, the modulation pattern was set to 01010101....

### 8.2 Timing Measurements


**Test Set-up 2:**



This setup is used for measuring Frame Repetition Stability, Frame Period and Jitter.

### 8.3 Conducted Emission Test

**Test Set-up 3:**



This setup is used for all conducted emission tests.

The EUT was in loopback-mode and was controlled with the CMD65, the modulation pattern was set to Pseudo-Random bit sequence to simulate normal speech.

## 8.4 Radiated Emission Test

### 30 MHz – 1GHz:

#### Test Set-up 4:


- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a no conducting table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 10 m or 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

#### Premereasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 m to 3 m.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

#### Final measurement

- The final measurement is performed for at least six highest peaks according to the requirements of the ANSI C63.4.
- Based on antenna and turntable positions at which the peak values are measured the software maximize the peaks by changing turntable position  $\pm 45^\circ$  and antenna height between 1 and 4 m.
- The final measurement is done with quasi-peak detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement with marked maximum final results and the limit is stored.



## 1GHz – 10 GHz:

### Test Set-up 5:


- The Equipment was setup to simulate a typical usage like described in the user manual / or described by manufacturer.
- If the EUT is a tabletop system, a no conducting table with 0,8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is: (see ANSI C 63.4)
  - < 18 GHz = 3 m
  - 18-26 GHz = 1,5 m
  - 26-40 GHz = 0,75 m
- The EUT was set into operation.

### Premeasurement

- The turntable rotates continuous from 0° to 360°
- The antenna is polarized vertical and horizontal.
- In accordance to the antenna beam and the size of the EUT the antenna height changes in 30 cm steps, start at 1 meter. If it is not possible to tilt the emissions will be checked with a manually tilted antenna from top side.
- The analyzer scans quickly to find the maximum emissions of the EUT

### Final measurement



- The final measurement will be performed with minimum the six highest peaks (depends on emissions and number of measured points below 1 GHz)
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ( $\pm 45^\circ$ ) and antenna movement between 1 and 4 meter.
- The final measurement will be done with AV (Average / see ANSI C 63.4) detector
- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit, and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.



## 8.5 Power Line Conducted Emissions Test


### Test Set-up 6:

According to EMC basic standard **ANSI C 63.4**



## 8.6 Monitoring Tests

### Test Set-up 6:




This test setup is used for all Monitoring and Time and Spectrum Access Procedure tests. The path loss from the signal generator to the EUT is measured with a power meter before the testing is started.

A clock signal is used to synchronize the Interference Generator to the start of the DECT frame, this signal always comes from the base station. If the EUT is a DECT Portable Part (i.e. a handset) the clock signal will come from the Companion Device.

## 8.7 Radiated Output Power Test

### Test Set-up 7:



This setup is used for measuring the radiated output power in a fully anechoic chamber with a measurement distance of 1m.

## 9 Detailed Test Results

### 9.1 Power Line Conducted Emissions

**Measurement Procedure:**


ANSI C63.4-2014 using 50µH/50 ohms LISN.

**Test Result:** Pass

**Measurement Data:** See attached plots and tables

**Requirement:** FCC 15.207 (a)

## Phase Line




Phase line tbl  
Project ID: 1-8286/24-01-03

Frequency MHz	Quasi peak level dBµV	Margin quasi peak dB	Limit QP dBµV	Average level dBµV	Margin average dB	Limit AV dBµV
0.172387	53.31	11.53	64.845	29.78	25.58	55.360
0.220894	52.11	10.67	62.785	29.12	24.85	53.974
0.362681	43.91	14.75	58.667	23.99	25.93	49.923
1.026844	27.00	29.00	56.000	17.13	28.87	46.000
2.023087	29.70	26.30	56.000	20.50	25.50	46.000
5.411062	24.26	35.74	60.000	14.95	35.05	50.000

Project ID - 1-8286/24-01-03  
EUT - S700H pro

Operating mode - Idle charging

## Neutral Line



Neutral line tbl  
Project ID: 1-8286/24-01-03

Frequenc y	Quasi peak level	Margin quasi peak	Limit QP	Average level	Margin Average	Limit AV
MHz	dBµV	dB	dBµV	dBµV	dB	dBµV
0.153731	50.83	14.97	65.796	27.35	28.54	55.893
0.172387	53.55	11.29	64.845	30.10	25.26	55.360
0.217163	51.80	11.13	62.927	29.77	24.31	54.081
1.788019	33.91	22.09	56.000	20.84	25.16	46.000
2.116369	39.22	16.78	56.000	23.50	22.50	46.000
5.175994	30.60	29.40	60.000	17.31	32.69	50.000

Project ID - 1-8286/24-01-03  
EUT - S700H pro

Operating mode - Idle charging

## 9.2 Digital Modulation Techniques

The tested equipment is based on DECT technology, the only difference is that the channel allocation is modified to operate in the 1920-1930 MHz band.

The EUT use Multi Carrier / Time Division Multiple Access / Time division duplex and Digital GFSK modulation.

For further details see the operational description provided by the applicant.

### Requirement: FCC 15.319(b)

All transmissions must use only digital modulation techniques.

## 9.3 Labeling Requirements

See separate documents showing the label design and the placement of the label on the EUT.

### Requirement: FCC 15.19

The FCC identifier shall be displayed on the label, and the device(s) shall bear the following statement in a conspicuous location on the device or in the user manual if the device is to small:

*This device complies with Part 15 of the FCC rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.*

The label itself shall be of a permanent type, not a paper label, and shall last the lifetime of the equipment.

## 9.4 Antenna Requirements

Does the EUT have detachable antenna(s)?  Yes  No

If detachable, is the antenna connector(s) non-standard?  Yes  No

The tested equipment has only integral antennas. The conducted tests were performed on a sample with a temporary antenna connector.

**Requirements: FCC 15.203, 14.204. 15.317**

## 9.5 Channel Frequencies

UPCS CHANNEL	FREQUENCY (MHz)
<b>Upper Band Edge</b>	1930.000
<b>0 (Highest)</b>	1928.448
<b>1</b>	1926.720
<b>2</b>	1924.992
<b>3</b>	1923.264
<b>4 (Lowest)</b>	1921.536
<b>Lower Band Edge</b>	1920.000

**Requirement: FCC 15.301**

Within 1920-1930 MHz band for isochronous devices.

## 9.6 Automatic Discontinuation of Transmission

Does the EUT transmit control and Signaling Information?	<input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No
Type of EUT:	<input checked="" type="checkbox"/> Initiating device	<input type="checkbox"/> Responding device

The following tests simulate the reaction of the EUT in case of either absence of information to transmit or operational failure after a connection with the companion device is established.

Number	Test	EUT Reaction	Verdict
1	Power removed from EUT	C	<b>Pass</b>
2	EUT switched Off	C	<b>Pass</b>
3	Hook-On by companion device	N/A	<b>N/A</b>
4	Hook-On by EUT	C	<b>Pass</b>
5	Power removed from companion device	A	<b>Pass</b>
6	Companion device switched Off	N/A	<b>N/A</b>

- A – Connection breakdown, Cease of all transmissions
- B – Connection breakdown, EUT transmits control and signaling information
- C – Connection breakdown, companion device transmits control and signaling information
- N/A – Not applicable (the EUT does not have an on/off switch and can not perform Hook-On)

### Requirement: FCC 15.319(f)

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. This provision is not intended to preclude transmission of control and signaling information or use or repetitive code used by certain digital modulation technologies to complete frame or burst intervals.

## 9.7 Peak Power Output

### Measurement Procedure:

ANSI C63.17, clause 6.1.2.

**Test Results: Pass**

### Measurement Data:

#### Maximum Conducted Output Power

Channel No.	Frequency (MHz)	Maximum Conducted Output Power (dBm)	Maximum Radiated Output Power (dBm)	Maximum Antenna Gain (dBi)
4	1921.536	17.6	17.7	0.1
2	1924.992	17.5	17.1	-0.4
0	1928.448	17.3	17.4	0.1

For this test it was also checked that the input voltage variation of 85 and 115% of nominal value did not have any effect on the measured output power, neither radiated nor conducted.

### Limit:

Conducted:  $100 \mu\text{W} \times \text{SQRT}(B)$  where B is the measured Emission Bandwidth in Hz

FCC 15.319(c)(e): 21.8 dBm (121 mW)

RSS-213, Issue 2: 20.5 dBm (117 mW)


The antenna gain is below 3 dBi.

### Requirements: FCC 15.319(c)(e). RSS-213, Issue 2


Peak transmit power shall not exceed 100 microwatts multiplied by the square root of the emission bandwidth in Hertz.

The peak transmit power shall be reduced by the amount in decibels that the maximum directional gain of the antenna exceeds 3 dBi.


## Conducted Peak Output Power



## Lower Channel




## Upper Channel




### Middle Channel


## Radiated Peak Output Power



## Lower Channel



## Upper Channel



### Middle Channel

## 9.8 Emission Bandwidth B

### Measurement Procedure:

ANSI C63.17, clause 6.1.3.

**Test Results: Pass**

### Measurement Data:

Channel No.	Frequency (MHz)	26 dB Bandwidth B (kHz)
4	1921.536	2132
0	1928.448	2319

Channel No.	Frequency (MHz)	99 % Bandwidth B (kHz)
2	1924.992	1252

Channel No.	Frequency (MHz)	6 dB Bandwidth B (kHz)
4	1921.536	N/A
0	1928.448	N/A
Channel No.	Frequency (MHz)	12 dB Bandwidth B (kHz)
4	1921.536	N/A
0	1928.448	N/A


### Requirement: FCC 15.323(a)

The 26 dB Bandwidth B shall be larger than 50 kHz and less than 2.5 MHz.


### Requirement: RSS-213 Issue 2, clause 6.4

The 20 dB Bandwidth B shall be larger than 50 kHz and less than 2.5 MHz.


No requirement for 6 dB and 12 dB Bandwidth. These values are only used for testing Monitoring Bandwidth if the Simple Compliance test fails (ANSI C63.17, clause 7.4).



### Emission Bandwidth B, Lower Channel



### Emission Bandwidth B, Upper Channel



**99 % Bandwidth B, Middle Channel**

## 9.9 Power Spectral Density

### Measurement Procedure:

ANSI C63.17, clause 6.1.5.

**Test Results: Pass**

### Measurement Data:

Channel No.	Frequency (MHz)	Power Spectral Density (dBm/3kHz)
4	1921.541120	-2.16
0	1928.453120	-3.06

Averaged over 100 sweeps.


### Requirement: FCC 15.319(d)

The Power Spectral Density shall be less than 3 mW/3kHz (4.77 dBm) when averaged over at least 100 sweeps.

## Power Spectral Density

Lower Channel:

Frequency of the maximum level was recorded under chapter 5.9.




Averaged, 100 Sweeps

Pulse power [dBm]	-2.16
Pulse power [mW]	0.61

## Power Spectral Density

Upper Channel:

Frequency of the maximum level was recorded under chapter 5.9.



Averaged, 100 Sweeps

Pulse power [dBm]	-3.06
Pulse power [mW]	0.49

## 9.10 In-Band Unwanted Emissions, Conducted

### Measurement Procedure:

ANSI C63.17, clause 6.1.6.1.

### Test Results: Pass


### Measurement Data:

See plots.


### Requirement: FCC 15.323(d)

$B < f2 \leq 2B$ :	less than or equal to 30 dB below max. permitted peak power level
$2B < f2 \leq 3B$ :	less than or equal to 50 dB below max. permitted peak power level
$3B < f2 \leq \text{UPCS Band Edge}$ :	less than or equal to 60 dB below max. permitted peak power level


## In-Band Unwanted Emissions, Conducted



## Lower Channel



## Upper Channel



### Middle Channel

The BS spurious in-band transmission level is below the indicated limit.

## 9.11 Out-of-Band Emissions, Conducted

### Measurement Procedure:

ANSI C63.17, clause 6.1.6.2.

### Test Results: Pass

### Measurement Data:



See plots.

### Requirement: FCC 15.323(d)



$f \leq 1.25$ MHz outside UPSCS band:	$\leq -9.5$ dBm
$1.25$ MHz $\leq f \leq 2.5$ MHz outside UPSCS band:	$\leq -29.5$ dBm
$f \geq 2.5$ MHz outside UPSCS band:	$\leq -39.5$ dBm

## Out-of-Band Unwanted Emissions, Conducted


### Upper and Lower Channel:



## Out-of-Band Unwanted Emissions, Conducted



## Out-of-Band Unwanted Emissions, Conducted



The BS spurious out-of-band transmission level is below the indicated limit.

## 9.12 Carrier Frequency Stability

### Measurement Procedure:

ANSI C63.17, clause 6.2.1.

Requirement: FCC 15.323(f)

Test Results: Pass

### Measurement Data:

The Frequency Stability is measured with the CMD65. The CMD65 was logged by a computer programmed to get the new readings as fast as possible (about 3 readings per second) over the noted time period or number of readings. The peak-to-peak difference was recorded and the mean value and deviation in ppm was calculated.

The Carrier Frequency Stability over power Supply Voltage and over Temperature is measured also with the CMD65.

### Carrier Frequency Stability over Time at Nominal Temperature

Average Mean Carrier Frequency (MHz)	Max. Diff. (kHz)	Min. Diff. (kHz)	Max Dev. (ppm)	Limit (ppm)
1924.987439	-2.51	-5.59	1.067	±10

Deviation ppm = ((Max.Diff. – Mean.Diff.) / Mean Carrier Freq.) x 10<sup>6</sup>

Deviation (ppm) is calculated from 3000 readings with the CMD65.

### Carrier Frequency Stability over Power Supply at Nominal Temperature

Voltage	Measured Carrier Frequency (MHz)	Difference (kHz)	Deviation (ppm)	Limit (ppm)
5.00 V DC	/	/	/	±10
5.75V DC	/	/	/	
4.25 V DC	/	/	/	

Deviation ppm = ((Mean – Measured frequency) / Mean) x 10<sup>6</sup>

### Carrier Frequency Stability over Temperature

Temperature	Measured Carrier Frequency (MHz)	Difference (kHz)	Deviation (ppm)	Limit (ppm)
T = +20°C	1924.991	Ref.	Ref.	±10
T = -20°C	1924.991	0.0	0.0	
T = +50°C	1924.991	0.0	0.0	

Deviation ppm = ((Mean – Measured frequency) / Mean) x 10<sup>6</sup>

## 9.13 Frame Repetition Stability

### Measurement Procedure:

ANSI C63.17, clause 6.2.2.

### Test Results: Pass

#### Measurement Data:

The Frame Repetition Stability is measured with the CMD65. The Frame Repetition Stability is 3 times the standard deviation.

Carrier Frequency (MHz)	Mean (Hz)	Standard Deviation (ppm)	Frame Repetition Stability (ppm)
1924.992	99.9999999917	0.575	1.725

#### Limit:

Frame Repetition Stability	±10 ppm (TDMA)
----------------------------	----------------

Ref. FCC 15.323(e). ANSI C63.17, clause 6.2.2.

## 9.14 Frame Period and Jitter

### Measurement Procedure:

ANSI C63.17, clause 6.2.3.

### Test Results: Pass

#### Measurement Data:

The Frame Repetition Stability is measured with the CMD65


Carrier Frequency (MHz)	Frame Period (ms)	Max Jitter (μs)	3xStandard Deviation of Jitter (μs)
1924.992	10.000	0.812	0.148

Max Jitter =  $(1/(\text{Frame Period} + \text{Pk-Pk})/2) - (1/\text{Frame Period})$ , when Pk-Pk and Frame Period are in Hz.  
 $3 \times \text{St.Dev.Jitter} = 3 \times (1/(\text{Frame Period} + \text{St.Dev})) - (1/\text{St.Dev}) \times 10^6$


#### Limit:

Frame Period	20 or 10 ms
Max Jitter	25 μs
3 times St.Dev. of Jitter	12.5 μs


Ref. FCC 15.323(e). ANSI C63.17, clause 6.2.3.



**Histogram of Carrier Frequency Stability**



**Histogram of Frame Repetition Stability**



**Histogram of Frame Period and Jitter**

## 9.15 Monitoring Threshold, Least Interfered Channel

### Measurement Procedure:

ANSI C63.17, clause 7.3.2

### Monitoring Threshold limits:

Lower Threshold:

$$T_L = 15 \log B - 184 + 30 - P_{EUT} \text{ (dBm)}$$

B is measured Emission Bandwidth in Hz

$P_{EUT}$  is measured Transmitter Power in dBm

### Calculated value:

Lower Threshold	-76.1 dBm
-----------------	-----------

### Least Interfered Channel (LIC) Procedure Test, FCC 15.323(c)(2) and (c)(5)

ANSI C63.17 clause 7.3.2 ref.	Observation	Verdict
b) $f_1 T_L + 13 \text{ dB}$ , $f_2 T_L + 6 \text{ dB}$	Transmission always on $f_2$	Pass
c) $f_1 T_L + 6 \text{ dB}$ , $f_2 T_L + 13 \text{ dB}$	Transmission always on $f_1$	Pass
d) $f_1 T_L + 7 \text{ dB}$ , $f_2 T_L$	Transmission always on $f_2$	Pass
e) $f_1 T_L$ , $f_2$ at $T_L + 7 \text{ dB}$	Transmission always on $f_1$	Pass


**Measurement Procedure:**

ANSI C63.17, clause 7.3.3

**Selected Channel Confirmation, FCC 15.323(c)(1) and (5)**

ANSI C63.17 clause 7.3.3	Observation	Verdict
b) Shall <b>not</b> transmit on $f_1$	EUT transmits on $f_2$	<b>Pass</b>
d) Shall <b>not</b> transmit on $f_2$	EUT transmits on $f_1$	<b>Pass</b>

Comment: This test is only applicable for EUTs that can be an initiating device.

**7.3.3 Selected Channel Confirmation, connection 0.8 s after interferer removed**

## 9.16 Threshold Monitoring Bandwidth

This test is only required if a dedicated monitoring receiver is used. If the test is not carried out the manufacturer shall declare and provide evidence that the monitoring is made through the radio receiver used for communication.

### Measurement Procedure:

Simple Compliance Test, ANSI C63.17, clause 7.4.1

More Detailed Test, ANSI C63.17, clause 7.4.2

The test is passed if **either** the Simple Compliance Test or the More Detailed Test is passed.

During this test the spectrum analyzer is observed visually to see if the EUT transmits or not.

### Test Results:

Test performed	Observation	Verdict
Simple Compliance Test, at $\pm 30\%$ of B	N/A	N/A
More Detailed Test, at -6 dB points	N/A	N/A
More Detailed Test, at -12 dB points	N/A	N/A

The More Detailed Test must be pass at both the -6dB and -12 dB points if the Simple Compliance Test fails.

**Comment:** The tested EUT uses the same receiver for monitoring and communication, this test is therefore not required.

### Limits: FCC 15.323(c)(7):

The monitoring system bandwidth must be equal to or greater than the emission bandwidth of the intended transmission.

## 9.17 Reaction Time and Monitoring Interval

### Measurement Procedure:

ANSI C63.17, clause 7.5

### Test Results:

By administrative commands and out-of-operating region interference, the EUT is restricted to operate on carrier frequencies  $f_1$  and  $f_2$ .

Time-synchronized pulsed interference was then applied on  $f_1$  at pulsed levels  $TL + UM$  to check that the EUT does not transmit. The level was raised 6 dB for part d) with 35  $\mu$ s pulses. Additionally a CW signal was applied on  $f_2$  with a level of  $TL$ .

The pulses are synchronized with the EUT timeslots and applied centered within all timeslots.

Pulse Width, ref. to ANSI C63.17 clause 7.5	Observation	Verdict
c) > largest of 50 $\mu$ s and $50 * \text{SQRT}(1.25/B)$	Transmission on $f_2$	<b>Pass</b>
d) > largest of 35 $\mu$ s and $35 * \text{SQRT}(1.25/B)$ and with interference level raised 6 dB	Transmission on $f_2$	<b>Pass</b>


**Comment:** Since B is larger than 1.25 MHz, the test was performed with pulse lengths of 50  $\mu$ s and 35  $\mu$ s.

### Limits: FCC 15.323(c)(1), (5) and (7)


The maximum reaction time must be less than  $50 * \text{SQRT}(1.25/\text{emission bandwidth in MHz})$  microseconds for signals at the applicable threshold level but shall not be required to be less than 50 microseconds.

If a signal is detected that is 6 dB or more above the applicable threshold level, the maximum reaction time shall be  $35 * \text{SQRT}(1.25/\text{emission bandwidth in MHz})$  microseconds but shall not be required to be less than 35 microseconds.

Comment: This test is only applicable for EUTs that can be an initiating device.



### 50 $\mu$ s Pulses



### 35 $\mu$ s Pulses

## 9.18 Time and Spectrum Window Access Procedure

This requirement is only for EUTs which transmit unacknowledged control and signaling information

### Measurement Procedure:

Timing for EUTs using control and signaling channel type transmissions: ANSI C63.17, clause 8.1

Test results:

Access Criteria, ref. to ANSI C63.17 clause 8.1.1	Observation	Verdict
b) Check that the EUT transmits on the interference free time slot	N/A	<b>N/A</b>
b) The EUT must terminate or pause in its repetitive transmission of the control and signaling channel on the open channel to repeat the access criteria not less frequently than every 30 s	N/A	<b>N/A</b>

If FCC 15.323(c)(6) option Random Waiting Interval is NOT implemented

Access Criteria, ref. to ANSI C63.17 clause 8.1.2	Observation	Verdict
b) Check that the EUT changes to interference free time slot when interference is introduced on the time slot in use	N/A	<b>N/A</b>

If FCC 15.323(c)(6) option Random Waiting Interval is implemented

Access Criteria, ref. to ANSI C63.17 clause 8.1.3	Observation	Verdict
b-d) Check that the EUT uses random waiting interval before continuing transmission on an interfered time slot	N/A	<b>N/A</b>

Comment: The tested EUT does not support the Random Waiting Interval option.

### Limits:

#### FCC 15.323(c)(4):

Once access to specific combined time and spectrum windows is obtained an acknowledgement from a system participant must be received by the initiating transmitter within one second or transmission must cease. Periodic acknowledgments must be received at least every 30 seconds or transmission must cease. Channels used exclusively for control and signaling information may transmit continuously for 30 seconds without receiving an acknowledgement, at which the time access criteria must be repeated.

#### FCC 15.323(c)(6):

If the selected combined time and spectrum windows are unavailable, the device may either monitor and select different windows or seek to use the same windows after waiting an amount of time, randomly chosen from a uniform random distribution between 10 and 150 milliseconds, commencing when the channel becomes available.

## 9.19 Acknowledgments and Transmission duration

### Measurement Procedure:

Acknowledgments: ANSI C63.17, clause 8.2.1

Transmission Duration: ANSI C63.17, clause 8.2.2

During the test **Initial transmission without acknowledgments** the signal from the EUT to the companion device is blocked by circulators in addition to the tunable attenuator.

The test **Transmission time after loss of acknowledgments** is performed by cutting-off the signal from the companion device by a RF switch the time until the EUT stops transmitting.

The **Transmission Duration** test is performed by monitoring the slot in use and measuring the time until the EUT changes to a different slot.

### Test Results:

#### Acknowledgments

Test ref. to ANSI C63.17 clause 8.2.1	Observation	Verdict
a) Initial transmission without acknowledgments	0.4 ms	Pass
c) Transmission time after loss of acknowledgments	7.4 s	Pass


#### Transmission Duration

Test ref. to ANSI C63.17 clause 8.2.2	Observation	Verdict
b) Transmission duration on same time and frequency window	<1 h	Pass


Comment: /

#### Limits: FCC 15.323(c)(3) and (4)

Occupation of the same combined time and spectrum windows by a device or group of cooperating devices continuously over a period of time longer than 8 hours is not permitted without repeating the access criteria. Once access to specific combined time and spectrum windows is obtained an acknowledgment from a system participant must be received by the initiating transmitter within one second or transmission must cease. Periodic acknowledgments must be received at least every 30 seconds or transmission must cease. Channels used exclusively for control and signaling information may transmit continuously for 30 seconds without receiving an acknowledgement, at which the time access criteria must be repeated.



### 8.2.1a) Initial Transmission Time without Acknowledgments



### 8.2.1c) Transmission Time after Loss of Acknowledgments

## 9.20 Dual Access Criteria Check

### Measurement Procedure:

EUTs that do not implement the Upper Threshold: ANSI C62.17, clause 8.3.1

EUTs that implement the Upper Threshold: ANSI C62.17, clause 8.3.2

This test is required for equipment that uses the access criteria in FCC 15.323(c)(10).

### Test Results:

#### EUTs that do NOT implement the LIC algorithm:

Test ref. to ANSI C63.17 clause 8.3.1	Observation	Verdict
b) EUT is restricted to a single carrier $f_1$ for TDMA systems. The test is pass if the EUT can set up a communication link.	N/A	N/A
c) d) No transmission on interference-free <b>receive</b> time/spectrum window. All transmit slots blocked	N/A	N/A
e) f) No transmission on interference-free <b>transmit</b> time/spectrum window. All transmit slots blocked	N/A	N/A


#### EUTs that implement the LIC algorithm:

Test ref. to ANSI C63.17 clause 8.3.2	Observation	Verdict
b) EUT is restricted to a single carrier $f_1$ for TDMA systems. The test is pass if the EUT can set up a communication link.	N/A	N/A
c) d) Transmission on interference-free <b>receive</b> time/spectrum window.	Transmission on interference-free <b>receive</b> time window	Pass
e) f) Transmission on interference-free <b>transmit</b> time/spectrum window.	Transmission on interference-free <b>transmit</b> time window	Pass


Comment: This test is only applicable for EUTs that can be an initiating device of a duplex connection.

### Limits: FCC 15.323(c)(10)


An initiating device may attempt to establish a duplex connection by monitoring both, its intended transmit and receive time and spectrum windows. If both the intended transmit and receive time and spectrum windows meet the access criteria, then the initiating device can initiate a transmission in the intended transmit time and spectrum window. If the power detected by the responding device can be decoded as a duplex connection signal from the initiating device, then the responding device may immediately begin transmitting on the receive time and spectrum window monitored by the initiating device.




### 8.3.2 c) Transmission on interference-free receive time window before



### 8.3.2 d) Transmission on interference-free receive time window after



### 8.3.2 e) Transmission on interference-free transmit time window before



### 8.3.2 f) Transmission on interference-free transmit time window after

## 9.21 Alternative monitoring interval

Test procedure described in ANSI C63.17, clause 8.4.

This test is required if the EUT implements the provision of FCC 15.323(c)(11).

### Test Result:

Not tested. The tested EUT does not implement this provision. See manufacturer's declaration.

## 9.22 Spurious Emissions (Radiated)

### Measurement Procedure:

FCC 15.209, FCC 15.109

### Test Result: Pass


### Measurement Data: See plots.

### Requirement: FCC 15.109(b)

30 – 88 MHz:	90 $\mu$ V/m
88 – 216 MHz:	150 $\mu$ V/m
216 – 960 MHz:	210 $\mu$ V/m
960 – 1000 MHz:	300 $\mu$ V/m

## Common Information

EUT: S700H pro  
 Serial number:  
 Test description: FCC Part 15 B Class B  
 Operating condition: BT active  
 Operator name: MED  
 Comment:




## Final\_Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
145.023	15.41	33.5	18.1	1000	120.0	126.0	V	90	10
518.097	23.31	36.0	12.7	1000	120.0	311.0	V	55	20
559.526	26.67	36.0	9.3	1000	120.0	295.0	V	5	20
601.017	31.74	36.0	4.3	1000	120.0	281.0	V	-33	22
601.350	33.28	36.0	2.7	1000	120.0	271.0	V	-30	22
642.835	31.93	36.0	4.1	1000	120.0	264.0	V	-40	22
683.890	26.15	36.0	9.9	1000	120.0	234.0	V	51	22
897.860	15.79	36.0	20.2	1000	120.0	279.0	H	340	25

## Common Information

EUT: S700H pro  
 Serial number:  
 Test description: FCC Part 15 B Class B  
 Operating condition: DECT idle  
 Operator name: MED  
 Comment: AC 120V /60 Hz



## Final\_Result

Frequency (MHz)	Average (dBμV/m)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Pol	Azimuth (deg)	Corr. (dB/m)	Comment
2460.179	35.76	---	54.0	18.2	1000	1000.0	V	33	-5	
3514.130	30.48	---	54.0	23.5	1000	1000.0	V	68	-3	
9970.539	38.79	---	54.0	15.2	1000	1000.0	H	13	9	
13396.540	40.32	---	54.0	13.7	1000	1000.0	H	5	11	
14054.789	41.05	---	54.0	13.0	1000	1000.0	V	18	12	
14458.372	39.87	---	54.0	14.1	1000	1000.0	H	11	12	

The radiated spurious emission of the unintentional radiator is below the indicated limit.

## 9.23 Receiver Spurious Emissions

### Measurement Procedure:

Industry Canada RSS-213 paragraph 6.8 and RSS-GEN paragraphs 4.8 and 6.

### Test results:


Frequency MHz	Carrier No.	Measured Value Conducted dBm	Conducted Limit dBm	Margin dB
30 - 1000	all	-74.6	-57	17.6
> 1000	all	-70.7	-53	17.7

### Requirements: RSS-GEN Issue 2, clause 6


The measurement can be performed either radiated or conducted.

**When measured conducted:** No spurious signals appearing at the antenna terminals shall exceed 2 nW per any 4 kHz spurious frequency in the band 30-1000 MHz, or 5 nW above 1 GHz.


**When measured radiated:** See table 1 in RSS-GEN Issue2, clause 6.



### Receiver Spurious Emissions, Conducted, 100 kHz – 1 GHz



### Receiver Spurious Emissions, Conducted, 1 GHz – 12 GHz



## Receiver Spurious Emissions, Conducted, 12 GHz – 20 GHz

## 10 Test equipment and ancillaries used for tests

To simplify the identification of the test equipment and/or ancillaries which were used, the reporting of the relevant test cases only refer to the test item number as specified in the table below.

No.	Equipment	Manufacturer	Type	Serial No.	Inv. No.	Kind of Calib.	Last Calib.	Next Calib.
<b>Conducted</b>								
L-1	Spectrum Analyzer	R&S	FSV30	100763	300003950	k	12/2024	12/2025
L-2	Signal Generator	R&S	SMBV100A	257858	300004529	vlkl!	12/2023	12/2026
L-3	Signaling Unit	R&S	CMD 65	825486	300003611	vlkl!	12/2023	12/2025
L-4	Power Sensor	R&S	NRP-Z22	100031	400000188	vlkl!	01/2024	01/2026

No.	Equipment	Manufacturer	Type	Serial No.	Inv. No.	Kind of Calib.	Last Calib.	Next Calib.
<b>Power Line Conducted Emission</b>								
G-1	EMI Receiver	R&S	ESR3	102981	3000006318	k	12/2024	12/2025
G-2	VISN	R&S	ESH 3-Z5	893045/004	300000584	k	12/2024	12/2025

No.	Equipment	Manufacturer	Type	Serial No.	Inv. No.	Kind of Calib.	Last Calib.	Next Calib.
<b>Radiated Emission</b>								
F-1	EMI Receiver	R&S	ESR3	102587	300005771	k	12/2024	12/2025
F-2	Spectrum Analyzer	R&S	FSU26	200809	300003874	k	12/2024	12/2025
F-3	Trilog Antenna	Schwarzbeck	VULB9163	371	300003854	vlkl!	07/2024	07/2026
F-4	Horn antenna	EMCO	3115	9107-3697	300001605	vlkl!	03/2023	03/2025

### Agenda: Kind of Calibration

k	calibration / calibrated	EK	limited calibration
ne	not required (k, ev, izw, zw not required)	zw	cyclical maintenance (external cyclical maintenance)
ev	periodic self verification	izw	internal cyclical maintenance
Ve	long-term stability recognized	g	blocked for accredited testing
vlkl!	Attention: extended calibration interval	*	next calibration ordered / currently in progress
NK!	Attention: not calibrated		

## 11 Observations

No observations exceeding those reported with the single test cases have been made.

## Annex A: Photographs of the Test Set-up

See additional PDF document Annex A-C.

## Annex B: External Photographs of the EUT

See additional PDF document Annex A-C.

## Annex C: Internal Photographs of the EUT

See additional PDF document Annex A-C.

## Annex D: Document History

Version	Applied Changes	Date of Release
R01	Initial release	2025-01-27

## Annex E: Further Information

### Glossary

DUT	-	Device under Test
EMC	-	Electromagnetic Compatibility
EUT	-	Equipment under Test
FCC	-	Federal Communication Commission
FCC ID	-	Company Identifier at FCC
HW	-	Hardware
IC	-	Industry Canada
Inv. No.	-	Inventory number
N/A	-	not applicable
S/N	-	Serial Number
SW	-	Software