



FCC PART 15.247 TEST REPORT

For

Shenzhen Gospell Smarthome Electronic Co., Ltd

5 Floor/Block 2, Vision (SZ) Park, Hi-Tech, Industrial Park, Shenzhen, 518057 China

FCC ID: TW5GD7610

Product Type: Report Type:

Digital Wireless Backup Camera Original Report System with 3.5" TFT-LCD Monitor

Gardon Zhang **Test Engineer:** Gardon Zhang

Report Number: RSZ130104003-00

Report Date: 2013-01-23

Sula Huang

Reviewed By: RF Engineer

Bay Area Compliance Laboratories Corp. (Shenzhen) Prepared By:

6/F, the 3rd Phase of WanLi Industrial Building

Soma Hugof

ShiHua Road, FuTian Free Trade Zone

Shenzhen, Guangdong, China Tel: +86-755-33320018

Fax: +86-755-33320008 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP* or any agency of the Federal Government.

^{*} This report may contain data that are not covered by the NVLAP accreditation and shall be marked with an asterisk "★"

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
Objective	
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY TEST FACILITY	
SYSTEM TEST CONFIGURATION	
DESCRIPTION OF TEST CONFIGURATION	
EUT Exercise Software	
SUPPORT EQUIPMENT LIST AND DETAILS	6
External I/O Cable	
BLOCK DIAGRAM OF TEST SETUP	
SUMMARY OF TEST RESULTS	8
FCC §15.247 (i) & §1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)	
STANDARD APPLICABLE	
FCC §15.203 – ANTENNA REQUIREMENT	
APPLICABLE STANDARD	10
Antenna Connector Construction	10
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS	11
APPLICABLE STANDARD	
MEASUREMENT UNCERTAINTY	
EUT SETUP	11
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	
TEST PROCEDURE TEST EQUIPMENT LIST AND DETAILS	
CORRECTED AMPLITUDE & MARGIN CALCULATION	12
TEST RESULTS SUMMARY	
TEST DATA	
FCC §15.247(a) (1)-CHANNEL SEPARATION	17
APPLICABLE STANDARD	
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS.	
Test Data	17
FCC §15.247(a) (1) – 20 dB BANDWIDTH	20
APPLICABLE STANDARD	20
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS.	
TEST DATA	20
FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL	23
APPLICABLE STANDARD	23
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS	
Test Data	23

Report No.: RSZ130104003-00

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The Shenzhen Gospell Smarthome Electronic Co., Ltd's product, model number: GD7610 (FCC ID: TW5GD7610) (the "EUT") in this report was a Digital Wireless Backup Camera System with 3.5" TFT-LCD Monitor, which was measured approximately: 10.8 cm (L) x 7.5 cm (W) x 3.8 cm (H), rated with input voltage: DC12V/24V from cigarette lighter adapter which was connected to car battery.

Report No.: RSZ130104003-00

* All measurement and test data in this report was gathered from production sample serial number: 1201057 (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2013-01-14.

Objective

This report is prepared on behalf of *Shenzhen Gospell Smarthome Electronic Co., Ltd* in accordance with Part 2-Subpart J, Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

No related submittal(s).

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

FCC Part15.247 Page 4 of 33

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Report No.: RSZ130104003-00

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is an ISO/IEC 17025 accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at http://ts.nist.gov/Standards/scopes/2007070.htm.

FCC Part15.247 Page 5 of 33

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The EUT was configured for testing in an engineering mode which can transmit continuously at lowest, middle and highest channel frequencies individually.

Report No.: RSZ130104003-00

EUT Exercise Software

No exercise software was used.

Equipment Modifications

Modification was made to the EUT tested by the supplier as follows:

The display cable was shielded with copper foil. (As in the picture below)



Support Equipment List and Details


Manufacturer	Description	Model	Serial Number		
Long Wei	AC/DC Power Supply	TPR-6420D	-		

External I/O Cable

Cable Description	Length (m)	From/Port	To	
Un-shielding Detachable DC Power Cable	1.2	EUT	cigarette lighter adapter	

FCC Part15.247 Page 6 of 33

Block Diagram of Test Setup



FCC Part15.247 Page 7 of 33

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
\$15.247 (i), \$1.1307 (b)(1), \$2.1091	Maximum Permissible Exposure (MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	Conducted Emissions	Not Applicable
\$15.205, \$15.209, \$15.247(d)	Radiated Emissions	Compliance
§15.247 (a)(1)	20 dB Bandwidth	Compliance
§15.247(a)(1)	Channel Separation	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band Edges	Compliance

Report No.: RSZ130104003-00

Note: The EUT was powered by cigarette lighter adapter which was connected to car battery.

FCC Part15.247 Page 8 of 33

FCC §15.247 (i) & §1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Standard Applicable

According to subpart 15.247 (i) and subpart 1.1307 (b)(1), 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Report No.: RSZ130104003-00

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure									
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (Minutes)					
0.3-1.34	614	1.63	*(100)	30					
1.34-30	824/f	2.19/f	$*(180/f^2)$	30					
30-300	27.5	0.073	0.2	30					
300-1500	/	/	f/1500	30					
1500-100,000	/	/	1.0	30					

f = frequency in MHz

MPE Calculation

Predication of MPE limit at a given distance

 $S = PG/4\pi R^2$

Where:

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally *numeric* gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Frequency	Antei	nna Gain	Conduct	ted Power	Evaluation Distance	Power	MPE Limit
(MHz)	(dBi)	(numeric)	(dBm)	(mW)	(cm)	Density (mW/cm ²)	(mW/cm ²)
2403	2	1.58	17.04	50.58	20	0.015907	1.0
2442	2	1.58	17.86	61.09	20	0.019212	1.0
2478	2	1.58	17.86	61.09	20	0.019212	1.0

Note: To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliance

FCC Part15.247 Page 9 of 33

^{* =} Plane-wave equivalent power density

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Report No.: RSZ130104003-00

Antenna Connector Construction

The EUT use an external omni-directional dipole antenna which has a unique type of reverse connector and the maximum gain is 2.0 dBi, full fill the requirement of this section. Please refer to the internal photos.

Result: Compliance.

FCC Part15.247 Page 10 of 33

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;


Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Report No.: RSZ130104003-00

Based on CISPR 16-4-2, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of radiation emissions measurement at Bay Area Compliance Laboratories Corp. (Shenzhen) is 4.0 dB (k=2, 95% level of confidence), and the uncertainty will not be taken into consideration for the test data recorded in the report.

EUT Setup



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209 and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

FCC Part15.247 Page 11 of 33

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Report No.: RSZ130104003-00

Frequency Range	RBW	Video B/W	IF B/W	Detector	
30MHz – 1000 MHz	100 kHz	300 kHz	120kHz	QP	
Above 1 GHz	1MHz	3 MHz	/	PK	
Above I GHZ	1MHz	10 Hz	/	Ave.	

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz to 1GHz and peak and Average detection modes for frequencies above 1GHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
НР	Amplifier	8447E	1937A01046	2012-11-24	2013-11-23
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2012-08-08	2013-08-07
Sunol Sciences	Broadband Antenna	JB1	A040904-2	2011-11-28	2014-11-27
SUPER ULTRA	Amplifier	ZVA-213+	N/A	2012-11-24	2013-11-23
Sunol Sciences	Horn Antenna	DRH-118	A052304	2011-12-01	2014-11-30
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2012-11-24	2013-11-23
the electro- Mechanics Co.	Horn Antenna	3116	9510-2270	2010-10-14	2013-10-13

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements that traceable to National Primary Standards and International System of Units (SI).

FCC Part15.247 Page 12 of 33

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Report No.: RSZ130104003-00

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Results Summary

According to the recorded data in following table, the EUT complied with the <u>FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247</u>, with the worst margin reading of:

5.2 dB at 108.001700 MHz in the Vertical polarization

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

The testing was performed by Gardon Zhang on 2013-01-20.


FCC Part15.247 Page 13 of 33


Note: As the monitor unit has two power supply mode (DC12V/24V), both have been checked. The data in this report represented the worst-case.

Report No.: RSZ130104003-00

1) 30MHz ~ 1000 MHz

Test Mode: Comunicating (Hopping mode)





Frequency (MHz)	Corrected Amplitude (dBµV/m)	Antenna Height (cm)	Antenna Polarity	Turntable Position (Degree)	Correction Factor (dB)	Limit (dBµV/m)	Margin (dB)
108.001700	38.3	106.0	V	289.0	-15.4	43.5	5.2
71.590100	30.5	104.0	Н	100.0	-20.6	40.0	9.5
162.004300	33.8	105.0	V	78.0	-15.4	43.5	9.7
240.011450	32.6	136.0	Н	65.0	-15.9	46.0	13.4
175.508700	28.8	104.0	V	0.0	-16.0	43.5	14.7
30.533956	18.3	131.0	V	43.0	-7.1	40.0	21.7

FCC Part15.247 Page 14 of 33

2) 1 GHz ~ 25 GHz

Test Mode: Transmitting (CTX)

Frequency	Re	eceiver	Turntable	Rx An	itenna		Corrected		C Part /205/209			
(MHz)	Reading (dBµV)	Detector (PK/QP/Ave.)	Degree	Height (m)	Polar (H/V)	Factor (dB)	Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)			
	Low Channel (2403 MHz)											
2403.0	100.25	PK	23	1.6	Н	6.13	106.38	/	/			
2403.0	64.39	Ave.	23	1.6	Н	6.13	70.52	/	/			
2403.0	110.25	PK	11	1.5	V	6.13	116.38	/	/			
2403.0	74.75	Ave.	11	1.5	V	6.13	80.88	/	/			
4806.0	54.07	PK	81	1.4	V	12.40	66.47	74	7.53			
2489.1	55.91	PK	23	1.3	V	6.81	62.72	74	11.28			
2489.1	34.83	Ave.	23	1.3	V	6.81	41.64	54	12.36			
2360.5	54.65	PK	91	1.2	V	5.48	60.13	74	13.87			
2339.8	53.89	PK	111	1.1	Н	5.48	59.37	74	14.63			
9612.0	19.91	Ave.	103	1.2	Н	19.28	39.19	54	14.81			
2360.5	33.10	Ave.	91	1.2	V	5.48	38.58	54	15.42			
9612.0	39.22	PK	103	1.2	Н	19.28	58.50	74	15.50			
2339.8	32.63	Ave.	111	1.1	Н	5.48	38.11	54	15.89			
4806.0	25.52	Ave.	81	1.4	V	12.40	37.92	54	16.08			
7209.0	18.73	Ave.	60	1.3	V	17.06	35.79	54	18.21			
7209.0	36.89	PK	60	1.3	V	17.06	53.95	74	20.05			
	•		Middle C	hannel	(2442 N	(Hz)						
2442.0	100.93	PK	25	1.5	Н	7.21	108.14	/	/			
2442.0	65.07	Ave.	25	1.5	Н	7.21	72.28	/	/			
2442.0	111.29	PK	19	1.2	V	6.81	118.10	/	/			
2442.0	75.33	Ave.	19	1.2	V	6.81	82.14	/	/			
4884.0	53.93	PK	33	1.1	V	12.46	66.39	74	7.61			
2489.1	55.91	PK	91	1.6	V	6.81	62.72	74	11.28			
2489.1	35.03	Ave.	91	1.6	V	6.81	41.84	54	12.16			
2366.5	54.91	PK	15	1.3	V	5.48	60.39	74	13.61			
9768.0	20.15	Ave.	28	1.4	Н	19.40	39.55	54	14.45			
2337.8	53.91	PK	99	1.4	Н	5.48	59.39	74	14.61			
2366.5	33.81	Ave.	15	1.3	V	5.48	39.29	54	14.71			
9768.0	38.77	PK	28	1.4	Н	19.40	58.17	74	15.83			
2337.8	32.06	Ave.	99	1.4	Н	5.48	37.54	54	16.46			
7326.0	20.06	Ave.	60	1.3	V	16.49	36.55	54	17.45			
4884.0	24.04	Ave.	33	1.1	V	12.46	36.50	54	17.50			
7326.0	38.91	PK	60	1.3	V	16.49	55.40	74	18.60			

Report No.: RSZ130104003-00

FCC Part15.247 Page 15 of 33

Frequency	Re	eceiver	Turntable	Rx An	tenna		Corrected	15.247	C Part /205/209			
(MHz)	Pactor Amplitude	Amplitude (dBµV/m)		Margin (dB)								
			High Cl	nannel (2	2478 M	Hz)						
2478.0												
2478.0	65.25	Ave.	28	1.3	Н	7.21	72.46	/	/			
2478.0	110.81	PK	33	1.5	V	6.81	117.62	/	/			
2478.0	74.91	Ave.	33	1.5	V	6.81	81.72	/	/			
4956.0	55.73	PK	92	1.2	V	12.50	68.23	74	5.77			
2485.2	55.91	PK	6	1.3	V	6.81	62.72	74	11.28			
2485.2	34.66	Ave.	6	1.3	V	6.81	41.47	54	12.53			
2368.7	54.96	PK	91	1.2	V	5.48	60.44	74	13.56			
9912.0	20.07	Ave.	236	1.3	Н	19.38	39.45	54	14.55			
2330.8	53.91	PK	87	1.2	Н	5.48	59.39	74	14.61			
2368.7	33.71	Ave.	91	1.2	V	5.48	39.19	54	14.81			
4956.0	26.07	Ave.	92	1.2	V	12.50	38.57	54	15.43			
9912.0	38.93	PK	236	1.3	Н	19.38	58.31	74	15.69			
2330.8	32.81	Ave.	87	1.2	Н	5.48	38.29	54	15.71			
7434.0	20.11	Ave.	101	1.2	V	15.90	36.01	54	17.99			
7434.0	38.96	PK	101	1.2	V	15.90	54.86	74	19.14			

Report No.: RSZ130104003-00

FCC Part15.247 Page 16 of 33

FCC §15.247(a) (1)-CHANNEL SEPARATION

Applicable Standard

Frequency hopping systems shall have hoping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Report No.: RSZ130104003-00

Test Procedure

- 1. Set the EUT in operating mode, RBW was set at 100 kHz,VBW ≥ 3RBW maxhold the channel.
- 2. Set the adjacent channel of the EUT maxhold another trace
- 3. Measure the channel separation.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2012-11-24	2013-11-23

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25 ℃	
Relative Humidity:	56 %	
ATM Pressure:	100.0 kPa	

^{*} The testing was performed by Gardon Zhang on 2013-01-18.

Test Result: Compliance.

Please refer to following tables and plots

FCC Part15.247 Page 17 of 33

Test Mode: Transmitting


Channel	Channel Frequency (MHz)	Channel Separation (MHz)	>Limit (MHz)	Result
Low	2403	3.000	2.979	
Adjacent	2406	3.000	2.919	
Middle	2442	3.000	2.979	Pass
Adjacent	2439	3.000	2.919	1 455
High	2478	3.000	2.979	
Adjacent	2475	3.000	2.919	

Report No.: RSZ130104003-00

Note: limit =2/3 of 20 dB bandwidth

Please refer to the following plots.


Low Channel




FCC Part15.247 Page 18 of 33

Middle Channel

Report No.: RSZ130104003-00



High Channel



FCC Part15.247 Page 19 of 33

FCC $\S15.247(a)$ (1) – 20 dB BANDWIDTH

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW.

Report No.: RSZ130104003-00

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- 3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
- 4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2012-11-24	2013-11-23

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25 ℃	
Relative Humidity:	56 %	
ATM Pressure:	100.0 kPa	

^{*} The testing was performed by Gardon Zhang on 2013-01-18.

Test Result: Compliance.

Please refer to following tables and plots

FCC Part15.247 Page 20 of 33


Test Mode: Transmitting

Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
Low	2403	4.469
Middle	2442	4.469
High	2478	4.469

Report No.: RSZ130104003-00

Please refer to the following plots.


Low Channel




FCC Part15.247 Page 21 of 33

Middle Channel

Report No.: RSZ130104003-00



High Channel



FCC Part15.247 Page 22 of 33

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Report No.: RSZ130104003-00

Test Procedure

- 1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- 2. Set the EUT in hopping mode from first channel to last.
- 3. By using the max-hold function record the quantity of the channel.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2012-11-24	2013-11-23

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25℃	
Relative Humidity:	56 %	
ATM Pressure:	100.0 kPa	

The testing was performed by Gardon Zhang on 2013-01-18.

Test Result: Compliance.

Please refer to following tables and plots


FCC Part15.247 Page 23 of 33

Test Mode: Transmitting

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.50	26	≥ 15

Report No.: RSZ130104003-00

Number of Hopping Channels



FCC Part15.247 Page 24 of 33

FCC §15.247(a) (1) (iii) -TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Report No.: RSZ130104003-00

Test Procedure

The EUT was worked in channel hopping; spectrum span was set as 0. Sweep was set as 0.4 X channel no. (s), the quantity of pulse was get from single sweep. In addition, the time of single pulses was tested.

Dwell Time= Pulse time (ms) * hope rate/2/ number of hopping channels * hopping No.*0.4 s

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2012-11-24	2013-11-23

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25℃	
Relative Humidity:	56 %	
ATM Pressure:	100.0kPa	

The testing was performed by Gardon Zhang on 2013-01-18.

Test Result: Compliance.

Please refer to following tables and plots

FCC Part15.247 Page 25 of 33


Test Mode: Transmitting

Channel	Pulse Width (ms)	Dwell Time (S)	Limit (S)	Result	
Low	0.202	0.0485	0.4	Pass	
Middle	0.202	0.0485	0.4	Pass	
High	0.202	0.0485	0.4	Pass	
Note: Dwell time=Pulse time (ms) \times (1200/2/26) \times 26*0.4 S					

Report No.: RSZ130104003-00

Please refer to the following plots.


Low Channel




FCC Part15.247 Page 26 of 33

Middle Channel

Report No.: RSZ130104003-00



High Channel



FCC Part15.247 Page 27 of 33

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt, for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Report No.: RSZ130104003-00

Test Procedure

- 1. Place the EUT on a bench and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to an EMI Test Receiver.
- 3. Add a correction factor to the display.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2012-11-24	2013-11-23

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25 ℃	
Relative Humidity:	56 %	
ATM Pressure:	100.0kPa	

^{*} The testing was performed by Gardon Zhang on 2013-01-18.

Test Result: Compliance.

FCC Part15.247 Page 28 of 33


Note: As the monitor unit has two power supply mode (DC12V/24V), both have been checked. The data in this report represented the worst-case.

Test Mode: Transmitting

Channel	Channel frequency (MHz)	Peak output power (dBm)	Power output (mW)	Limit (mW)
Low channel	2403	17.04	50.58	125
Middle channel	2442	17.86	61.09	125
High channel	2478	17.86	61.09	125

Note: The data above was tested in conducted mode.


Low Channel




FCC Part15.247 Page 29 of 33

Middle Channel

Report No.: RSZ130104003-00



High Channel



FCC Part15.247 Page 30 of 33

FCC §15.247(d) - BAND EDGES

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Report No.: RSZ130104003-00

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in Operating mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
- 3. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- 4. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2012-11-24	2013-11-23

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements that traceable to National Primary Standards and International System of Units (SI).

FCC Part15.247 Page 31 of 33

Test Data

Environmental Conditions

Temperature:	25 °C	
Relative Humidity:	56 %	
ATM Pressure:	100.0kPa	

^{*}The testing was performed by Gardon Zhang on 2013-01-18.

Test Result: Compliance.


Test Mode: Transmitting

Band Side	Delta Peak to Band Emission (dBc)	Limit (dBc)	
Left Side	33.01	20	
Right Side	43.08	20	

Report No.: RSZ130104003-00

Please refer to follow plots:


Band Edge: Left Side



FCC Part15.247 Page 32 of 33

Band Edge: Right Side

Report No.: RSZ130104003-00



***** END OF REPORT *****

FCC Part15.247 Page 33 of 33