

198 Kezhu Road, Scientech Park, Guangzhou Economic & Technological Development District, Guangzhou, China 510663
Telephone: +86 (0) 20 82155555
Fax: +86 (0) 20 82075059
Email: ee.guangzhou@sgs.com

Report No.: GZEM140600271101
Page: 1 of 69
FCC ID: TWF-BT-EPSER01

TEST REPORT

Application No.:	GZEM1406002711RF
Applicant:	Cobalt Industrial Co., Ltd.
FCC ID:	TWF-BT-EPSER01
Product Name:	BLUETOOTH STEREO EARPHONES
Product Description:	Bluetooth earphone with 2.4 GHz as carrier.
Model No.:	BT SERIES
Standards:	CFR 47 FCC PART 15 Subpart C: 2013 section 15.247
Date of Receipt:	2014-05-19
Date of Test:	2014-05-27 to 2014-05-29
Date of Issue:	2014-07-28
Test Result:	Pass*

* In the configuration tested, the EUT detailed in this report complied with the standards specified above. Please refer to section 3 of this report for further detail.




The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
00		2014-07-28		Original

Authorized for issue by:			
Tested By		 (Jack Liang) /Project Engineer	2014-05-27 to 2014-05-29
Prepared By		 (June Chen) /Clerk	2014-07-28
Checked By		 (Fred Zhu)/Reviewer	2014-07-28

3 Test Summary

Test	Test Requirement	Test method	Result
Antenna Requirement	FCC PART 15 C section 15.247 (c) and Section 15.203	FCC PART 15 C section 15.247 (c) and Section 15.203	PASS
Occupied Bandwidth	FCC PART 15 C section 15.247 (a)(1)	ANSI C63.10: Clause 6.9.1	PASS
Carrier Frequencies Separated	FCC PART 15 C section 15.247(a)(1)	ANSI C63.10: Clause 7.7.2	PASS
Hopping Channel Number	FCC PART 15 C section 15.247(a)(1)(iii)	ANSI C63.10: Clause 7.7.3	PASS
Dwell Time	FCC PART 15 C section 15.247(a)(1)(iii)	ANSI C63.10: Clause 7.7.4	PASS
Pseudorandom Frequency Hopping Sequence	FCC PART 15 C section 15.247(a)(1)	ANSI C63.10: Clause 7.7.5	PASS
Maximum Peak Output Power	FCC PART 15 C section 15.247(b)(1)	ANSI C63.10: Clause 6.10.1	PASS
Conducted Spurious Emission	FCC PART 15 C section 15.247(d)	ANSI C63.10: Clause 6.7	PASS
Radiated Spurious Emission	FCC PART 15 C section 15.247(d)	ANSI C63.10: Clause 6.4, 6.5 and 6.6	PASS
Band Edges Measurement	FCC PART 15 C section 15.247 (d) &15.205	KDB 00-705	PASS
Remark:			
N/A: not applicable. Refer to the relative section for the details.			
EUT: In this whole report EUT means Equipment Under Test.			
Tx: In this whole report Tx (or tx) means Transmitter.			
Rx: In this whole report Rx (or rx) means Receiver.			
RF: In this whole report RF means Radio Frequency.			
ANSI C63.10: the detail version is ANSI C63.10:2009 in the whole report.			
DA 00-705 was used as a guideline in preparing this Test Report.			
According to the declaration of the applicant, Bluetooth function is not available when the EUT is charging.			

4 Contents

1 COVER PAGE	1
2 VERSION.....	2
3 TEST SUMMARY	3
4 CONTENTS.....	4
5 GENERAL INFORMATION	5
5.1 Client Information	5
5.2 General Description of E.U.T	5
5.3 Details of E.U.T	5
5.4 Modulation configure	6
5.5 Description of Support Units	7
5.6 Deviation from Standards	7
5.7 Abnormalities from Standard Conditions	7
5.8 Other Information Requested by the Customer	7
5.9 Test Location	7
5.10 Test Facility	8
6 EQUIPMENT USED DURING TEST.....	9
7 TEST RESULTS	10
7.1 E.U.T. test conditions.....	10
7.2 Antenna Requirement	13
7.3 Occupied Bandwidth	14
7.4 Carrier Frequencies Separated.....	19
7.5 Hopping Channel Number.....	23
7.6 Dwell Time	25
7.7 Pseudorandom Frequency Hopping Sequence	36
7.8 Maximum Peak Output Power.....	39
7.9 Conducted Spurious Emissions	44
7.10 Radiated Spurious Emissions	50
7.11 Band Edges Requirement	67

5 General Information

5.1 Client Information

Applicant: Cobalt Industrial Co., Ltd.

Address of Applicant: Flat M, 7/F., Yue Cheung Centre, 1-3 Wong Chuk Yeung Street, Fo Tan, Shatin, N.T., Hong Kong.

5.2 General Description of E.U.T.

Product Name: BLUETOOTH STEREO EARPHONES

Model No.: BT SERIES

5.3 Details of E.U.T.

Operating Frequency: 2402 MHz to 2480 MHz

Type of Modulation: GFSK, $(\pi/4)$ DQPSK, 8DPSK

Number of Channels: 79 Channels

Channel Separation: 1 MHz

Antenna Type: Integral antennas

Antenna gain: 2 dBi

Speciality: Bluetooth specification version 3.0 with EDR

Function: Earphone with BT function to transmit and receive audio signal.

Power Supply: DC 3.7V 50mA

Normal Test Voltage: DC 3.7V 50mA

Model: YJS010A-0800600B(Supplied by SGS)

Adapter: Input: AC 100-240V 50/60Hz 350mA

Output: DC 5.0V 600mA

Power cord: 1.0m x 2 wires unscreened USB cable

Remark: The device meets the requirements stated within Parts 15.247(g) & (h) in that they were developed under the Bluetooth protocol and operate as a true frequency hopping system.


The device does not have the ability to be coordinated with other FHSS systems in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitters.

5.4 Modulation configure

Modulation	Packet	Packet Type	Packet Size
GFSK	DH1	4	24
	DH3	11	183
	DH5	15	339
($\pi/4$)DQPSK	2DH1	20	54
	2DH3	26	367
	2DH5	30	379
8DPSK	3DH1	24	83
	3DH3	27	552
	3DH5	31	1021

Remark:**Modulation 8-DPSK**

The modulation 8 PSK works with 8 phases between 0 and 2π (0 and 360 degrees), it can be seen below in the circle.



Normal mode: the Bluetooth has been tested on the Modulation of GFSK;

EDR mode: the Bluetooth has been tested on the Modulation of ($\pi/4$)DQPSK and 8DPSK, compliance test and record the worst case on 8DPSK.

5.5 Description of Support Units

The EUT has been tested with corresponding accessories as below:

Supplied by SGS:

Description	Manufacturer	Model No.	SN/Certificate NO
NoteBook	IBM	T30	S/N78-3VMLX 06/01
BT test board	SGS EMC	RF 07	RF 07

5.6 Deviation from Standards

Biconical and log periodic antennas were used instead of dipole antennas.

5.7 Abnormalities from Standard Conditions

None.

5.8 Other Information Requested by the Customer

None.

5.9 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory,
198 Kezhu Road, Scientech Park, Guangzhou Economic & Technology Development District,
Guangzhou, China 510663
Tel: +86 20 82155555 Fax: +86 20 82075059

No tests were sub-contracted.

5.10 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **NVLAP (Lab Code: 200611-0)**

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is accredited under the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 200611-0.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

- **ACMA**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our NVLAP accreditation.

- **SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO**

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

- **CNAS (Lab Code: L0167)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAS-CL01:2006 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of Testing Laboratories.

- **FCC (Registration No.: 282399)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 282399, May 31, 2002.

- **Industry Canada (Registration No.: 4620B-1)**

The 3m/10m Alternate Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd., has been registered by Certification and Engineering of Industry Canada for radio equipment testing with Registration No. 4620B-1.

- **VCCI (Registration No.: R-2460, C-2584, G-449 and T-1179)**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co. Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2460, C-2584, G-449 and T-1179 respectively.

- **CBTL (Lab Code: TL129)**

SGS-CSTC Standards Technical Services Co., Ltd., E&E Laboratory has been assessed and fully comply with the requirements of ISO/IEC 17025:2005, the Basic Rules, IEC6006-10 and Rules of procedure IEC6006-10, and the relevant IEC600 CB-Scheme Operational documents.

6 Equipment Used during Test

RE in Chamber						
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Due date	Calibration Interval
					(YYYY-MM-DD)	
EMC0525	Compact Semi-Anechoic Chamber	ChangZhou ZhongYu	N/A	N/A	2014-08-30	2Y
EMC0522	EMI Test Receiver	Rohde & Schwarz	ESIB26	100283	2015-04-19	1Y
EMC0056	EMI Test Receiver	Rohde & Schwarz	ESCI	100236	2015-03-03	1Y
EMC0528	RI High frequency Cable	SGS	20 m	N/A	2015-05-09	1Y
EMC2025	Trilog Broadband Antenna 30-3000MHz	SCHWARZBECK MESS-ELEKTRONIK	VULB 9163	9163-450	2016-08-31	3Y
EMC0524	Bi-log Type Antenna	Schaffner -Chase	CBL6112B	2966	2016-08-31	3Y
EMC0519	Bilog Type Antenna	Schaffner -Chase	CBL6143	5070	2016-05-04	2Y
EMC2026	Horn Antenna 1-18GHz	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120D	9120D-841	2016-08-31	3Y
EMC0518	Horn Antenna	Rohde & Schwarz	HF906	100096	2014-07-01	2Y
EMC0521	1-26.5 GHz Pre-Amplifier	Agilent	8449B	3008A01649	2015-03-03	1Y
EMC2065	Amplifier	HP	8447F	N/A	2014-08-31	1Y
EMC2063	1-26GHz Pre Amplifier	Compliance Direction System Inc.	PAP-1G26-48	6279.628	2014-07-29	1Y
EMC0075	310N Amplifier	Sonama	310N	272683	2015-03-03	1Y
EMC0523	Active Loop Antenna	EMCO	6502	42963	2016-03-03	2Y
EMC2041	Broad-Band Horn Antenna (14)15-26.5(40)GHz	SCHWARZBECK MESS-ELEKTRONI	BBHA 9170	9170-375	2017-06-01	3Y
EMC2069	2.4GHz filter	Micro-Tronics	BRM 50702	149	2015-04-19	1Y
EMC0530	10m Semi-Anechoic Chamber	ETS	N/A	N/A	2016-05-03	2Y

General used equipment						
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Due date	Calibration Interval
					(YYYY-MM-DD)	
EMC0006	DMM	Fluke	73	70681569	2014-09-13	1Y
EMC0007	DMM	Fluke	73	70671122	2014-09-13	1Y

7 Test Results

7.1 E.U.T. test conditions

Test Voltage:	DC 3.7V 50mA
Temperature:	20.0 -25.0 °C
Humidity:	38-50 % RH
Atmospheric Pressure:	1000 -1010 mbar
Requirements:	<p>15.31(e): For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. For battery operated equipment, the equipment tests shall be performed using a new battery.</p> <p>15.32: Power supplies and CPU boards used with personal computers and for which separate authorizations are required to be obtained shall be tested as follows: Testing shall be in accordance with the procedures specified in Section 15.31 of this part.</p>
Test frequencies and frequency range:	<p>According to the 15.31(m) Measurements on intentional radiators or receivers, other than TV broadcast receivers, shall be performed and, if required, reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table.</p> <p>According to the 15.33 (a) For an intentional radiator, the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to at least the frequency shown in the following table:</p>

Table 1 Number of fundamental frequencies to be tested in EUT transmit band

Frequency range in which device operates	Number of frequencies	Location in frequency range of operation
1 MHz or less	1	Middle
1 MHz to 10 MHz	2	1 near top and 1 near bottom
More than 10 MHz	3	1 near top, 1 near middle and 1 near bottom

Table 2 Frequency range of radiated emission measurements

Lowest frequency generated in the device	Upper frequency range of measurement
9 kHz to below 10 GHz	10th harmonic of highest fundamental frequency or to 40 GHz, whichever is lower
At or above 10 GHz to below 30 GHz	5th harmonic of highest fundamental frequency or to 100 GHz, whichever is lower
At or above 30 GHz	5th harmonic of highest fundamental frequency or to 200 GHz, whichever is lower, unless otherwise specified

EUT channels and frequencies list:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	27	2429	54	2456
1	2403	28	2430	55	2457
2	2404	29	2431	56	2458
3	2405	30	2432	57	2459
4	2406	31	2433	58	2460
5	2407	32	2434	59	2461
6	2408	33	2435	60	2462
7	2409	34	2436	61	2463
8	2410	35	2437	62	2464
9	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454	/	/
26	2428	53	2455	/	/

Test frequencies are the lowest channel: 0 channel(2402 MHz), middle channel: 39 channel(2441 MHz) and highest channel: 78 channel(2480 MHz)

7.2 Antenna Requirement

Standard requirement

15.203 requirement:

For intentional device. According to 15.203. an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.


15.247(c) (1)(i) requirement:

(i) Systems operating in the 2400-2483.5 MHz bands that are used exclusively for fixed.

Point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna

The antenna is integrated on the main PCB and no consideration of replacement. The maximum gain of the antenna is 2 dBi .



Test result: The unit does meet the FCC requirements.

7.3 Occupied Bandwidth


Test Requirement: FCC Part 15 C section 15.247

(a)(1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Method: ANSI C63.10: Clause 6.9.1

Test Status: Pre-test the EUT in continuous transmitting mode at the lowest (2402 MHz), middle (2441 MHz) and highest (2480 MHz) channel with different data package. Compliance test in normal mode (DH5) and EDR mode (3DH5) as the worst case was found.

Test Configuration:



Test Procedure:



1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: Span = approximately 2 to 3 times the 20Db bandwidth, centring on a hopping channel;
3. Set the spectrum analyzer: RBW \geq 1% of the 20dB bandwidth VBW \geq RBW. Sweep = auto; Detector Function = Peak. Trace = Max Hold.
4. Mark the peak frequency and -20 dB points bandwidth.



Test result:**Normal mode:**



Test Channel	Bandwidth(MHz)	2/3 bandwidth (MHz)
Lowest	0.799	0.533
Middle	0.806	0.537
Highest	0.806	0.537

EDR mode:

Test Channel	Bandwidth (MHz)	2/3 bandwidth (MHz)
Lowest	1.220	0.813
Middle	1.275	0.850
Highest	1.166	0.777

Result plot as follows:
Normal mode (DH5):
Lowest Channel(2.402 GHz):

Middle Channel(2.441 GHz):


Highest Channel(2.480 GHz):

EDR mode (3DH5):
Lowest channel(2.402 GHz):


Middle channel(2.441 GHz):

Highest channel(2.480 GHz):


7.4 Carrier Frequencies Separated


Test Requirement: FCC Part 15 C section 15.247

(a),(1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Method: ANSI C63.10: Clause 7.7.2

Test Status: Pre-test the EUT in hopping mode with different data packet. Compliance test in hopping with EDR mode (3DH5) as the worst case was found.

Test Configuration:



Test Procedure:



1. Remove the antenna from the EUT and then connect a low attenuation RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW \geq 1% of the span, VBW \geq RBW, Sweep = auto; Detector Function = Peak. Trace = Max, hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.


Test result:

Test Channel	Carrier Frequencies Separated	Limit①	Pass/Fail
Lower Channels (channel 0 and channel 1)	0.982MHz	0.813	Pass
Middle Channels (channel 39 and channel 40)	1.002MHz	0.850	Pass
Upper Channels (channel 77 and channel 78)	1.022MHz	0.777	Pass

Remark:

① The limit is two-thirds of the 20dB bandwidth.EDR(3DH5) mode due to the transmission power is less than 0.125 W shown on section 7.8 of this report.

Result plot as follows:
Lowest Channels: Carrier Frequencies Separated

Middle Channels: Carrier Frequencies Separated


Highest Channels: Carrier Frequencies Separated

Test result: The unit does meet the FCC requirements.

7.5 Hopping Channel Number


Test Requirement: FCC Part15 C section 15.247

(a)(1)(iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

Test Method: ANSI C63.10: Clause 7.7.3

Test Status: Pre-test the EUT in hopping mode with different data packet. Compliance test in hopping with EDR mode (3DH5) as the worst case was found.


Test Configuration:



Test Procedure:

1. Remove the antenna from the EUT and then connect a low attenuation RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 100 kHz. VBW = 100 kHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. It may prove necessary to break the span up to sections. in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section.
4. Set the spectrum analyzer: start frequency = 2400 MHz. stop frequency = 2483.5 MHz. Submit the test result graph.

Test result: Total channels are 79 channels.



Test result: The unit does meet the FCC requirements.

7.6 Dwell Time


Test Requirement: FCC Part 15 C section 15.247

(a)(1)(iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Method: ANSI C63.10: Clause 7.7.4

Test Status: Test the EUT in hopping mode at the lowest (2402 MHz), middle (2441 MHz) and highest (2480 MHz) channel with different data packet. Compliance test in hopping mode with EDR mode (3DH1, 3DH3 and 3DH5) as the worst case was found.

Test Configuration:



Test Procedure:

1. Remove the antenna from the EUT and then connect a low attenuation RF cable from the antenna port to the spectrum.
2. Set spectrum analyzer span = 0. centered on a hopping channel;
3. Set RBW = 1 MHz and VBW = 1 MHz. Sweep = as necessary to capture the entire dwell time per hopping channel. Detector Function = Peak. Trace = Max hold;
4. Use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g.. data rate. modulation format. etc.). Repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s). An oscilloscope may be used instead of a spectrum analyzer.

Test Result:



The test period: T= 0.4 Second/Channel x 79 Channel = 31.6 s

1. Channel 0: 2.402GHz							
3DH1 time slot	=	0.400	(ms)	*	33	*	(31.6/3.16) = 132.000 ms
3DH3 time slot	=	1.645	(ms)	*	16	*	(31.6/3.16) = 263.200 ms
3DH5 time slot	=	2.898	(ms)	*	15	*	(31.6/3.16) = 434.700 ms
2. Channel 39: 2.441GHz							
3DH1 time slot	=	0.393	(ms)	*	33	*	(31.6/3.16) = 129.690 ms
3DH3 time slot	=	1.645	(ms)	*	16	*	(31.6/3.16) = 263.200 ms
3DH5 time slot	=	2.898	(ms)	*	11	*	(31.6/3.16) = 318.780 ms
3. Channel 78: 2.480GHz							
3DH1 time slot	=	0.403	(ms)	*	33	*	(31.6/3.16) = 132.990 ms
3DH3 time slot	=	1.645	(ms)	*	16	*	(31.6/3.16) = 263.200 ms
3DH5 time slot	=	2.888	(ms)	*	11	*	(31.6/3.16) = 317.680 ms

The average time of occupancy in the specified 31.6 second period is equal to pulse width*(# of pulse in observation period)*(test period / observation period)


The results are not greater than 0.4 seconds.

The unit does meet the FCC requirements.


Result plot as follows:
1. Lowest channel (2.402 GHz):
(1). 3DH1
Pulse Width:

Number of Pulses in 3.16 S observation period:




(2) 3DH3

Pulse Width:



Number of Pulses in 3.16 S observation period:




(3) 3DH5
Pulse Width:

Number of Pulses in 3.16 S observation period:



2. Middle Channel (2.441 GHz):

(1). 3DH1

Pulse Width:




Number of Pulses in 3.16 S observation period:






(2) 3DH3

Pulse Width:



Number of Pulses in 3.16 S observation period:




(3) 3DH5
Pulse Width:

Number of Pulses in 3.16 S observation period:



3. Highest Channel (2.480 GHz):



(1). 3DH1



Pulse Width:



Number of Pulses in 3.16 S observation period:



(2) 3DH3
Pulse Width:

Number of Pulses in 3.16 S observation period:


(3) 3DH5
Pulse Width:

Number of Pulses in 3.16 S observation period:


7.7 Pseudorandom Frequency Hopping Sequence

7.7.1 Standard requirement

15.247(a)(1) requirement:

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Alternatively. Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.


7.7.2 Other requirements Frequency Hopping Spread Spectrum System

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1), (h) requirement:
	<p>The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.</p>
	<p>Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.</p>
	<p>The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.</p>

Compliance for section 15.247(a)(1)


According to Bluetooth Core Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: $2^9 - 1 = 511$ bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

According to Bluetooth Core Specification, Bluetooth receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any Bluetooth transmitters and shift frequencies in synchronization with the transmitted signals.

Compliance for section 15.247(g)

According to Bluetooth Core Specification, the Bluetooth system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

Compliance for section 15.247(h)

According to Bluetooth Core specification, the Bluetooth system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

According to the Bluetooth Core specification, the Bluetooth system is designed not have the ability to coordinate with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.

7.8 Maximum Peak Output Power

Test Requirement: FCC Part 15 C section 15.247

(b)(1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.


Refer to the result "Hopping channel number" of this document. The 1 watt (30.0 dBm) limit applies.

Test Method: ANSI C63.10: Clause 6.10.1

Test Limit:

Test mode: Pre-test the EUT in continuous transmitting mode at the lowest (2402 MHz), middle (2441 MHz) and highest (2480 MHz) channel with different data packet. Compliance test in continuous transmitting mode with normal (DH5) and EDR mode (3DH5) as the worst case was found.



Test Configuration:







Test Procedure:

1. Remove the antenna from the EUT and then connect a low attenuation RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 2 MHz. VBW = 2 MHz. Sweep = auto; Detector Function = Peak.
3. Keep the EUT in transmitting at lowest, medium and highest channel individually. Record the max value.

Test Result:				
Normal mode:				
Test Channel	Fundamental Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Result
Lowest	2402	-0.75	30.0	Pass
Middle	2441	2.17	30.0	Pass
Highest	2480	2.97	30.0	Pass
EDR mode:				
Test Channel	Fundamental Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Result
Lowest	2402	-2.87	30.0	Pass
Middle	2441	0.69	30.0	Pass
Highest	2480	1.83	30.0	Pass
Remark: cable lose=1.5 dB				
Test result: The unit does meet the FCC requirements.				

Result plot as follows:
Normal mode:
Lowest Channel(2.402 MHz):

Middle Channel(2.441 GHz):


Highest Channel(2.480 GHz):

EDR mode:
Lowest channel(2.402 GHz):


Middle channel(2.441 GHz):

Highest channel(2.480 GHz):


7.9 Conducted Spurious Emissions


Test Requirement: FCC Part15 C section 15.247

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating. The radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Based on either an RF conducted or a radiated measurement. Provided the transmitter demonstrates compliance with the peak conducted power limits.

Test Method: ANSI C63.10: Clause 6.7



Test Status: Pre-test the EUT in continuous transmitting mode at the lowest (2402 MHz), middle (2441 MHz) and highest (2480 MHz) channel with different data packet. Compliance test in continuous transmitting mode with normal mode (DH5) as the worst case was found.



Test Configuration:







Test Procedure:


1. Remove the antenna from the EUT and then connect a low attenuation RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 100 kHz. VBW \geq RBW. Sweep = auto; Detector Function = Peak (Max. hold).

Result plot as follows:
Lowest Channel: 30 MHz to 1 GHz

Lowest Channel: 1 GHz to 5 GHz


Lowest Channel: 5 GHz to 25 GHz

Middle Channel: 30 MHz to 1 GHz


Middle Channel: 1 GHz to 5 GHz

Middle Channel: 5 GHz to 25 GHz


Highest Channel: 30 MHz to 1 GHz

Highest Channel: 1 GHz to 5 GHz


Highest Channel: 5 GHz to 25 GHz

7.10 Radiated Spurious Emissions

Test Requirement: FCC Part15 C section 15.247

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating. The radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, and provided the transmitter demonstrates compliance with the peak conducted power limits.

Test Method: ANSI C63.10: Clause 6.4, 6.5 and 6.6

Test Status: Pre-test the EUT in continuous transmitting mode at the lowest (2402 MHz), middle (2441 MHz) and highest (2480 MHz) channel with different data packet. Compliance test in continuous transmitting mode with normal mode (DH5) as the worst case was found.

Detector: For PK value:

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

For AV value:

RBW = 1 MHz for $f \geq 1$ GHz,

VBW = 10 Hz

Sweep = auto

Detector function = peak



Trace = max hold

15.209 Limit: 40.0 dB μ V/m between 30MHz & 88MHz


43.5 dB μ V/m between 88MHz & 216MHz

46.0 dB μ V/m between 216MHz & 960MHz

54.0 dB μ V/m above 960MHz

Test Configuration:1) 9 kHz to 30 MHz emissions:2) 30 MHz to 1 GHz emissions:

3) 1 GHz to 40 GHz emissions:

**Test Procedure:**

Test site with RF absorbing material covering the ground plane that met the site validation criterion called out in CISPR 16-1-4:2007 was used to perform radiated emission test above 1 GHz.

The receiver scanned from the lowest frequency generated within the EUT to 25GHz. When an emission was found, the table was rotated to produce the maximum signal strength. An initial pre-scan was performed for in peak detection mode using the receiver. The EUT was measured for both the Horizontal and Vertical polarities and performed a pre-test three orthogonal planes. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. The worst case emissions were reported.

For hand-held or body-worn devices rotated through three orthogonal axes(X,Y,Z) to determine which attitude (orientation) and equipment arrangement produces the highest emission relative to the limit; the attitude and equipment arrangement that produces the highest emission relative to the limit was used in making final radiated emission measurements.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit.

Submit this data.

7.10.1 Harmonic and other spurious emissions

7.10.1.1 Test the lowest Channel in transmitting status

9 kHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement


The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.

30 MHz~1 GHz Spurious Emissions .Quasi-Peak Measurement

Vertical:

Peak scan

Level (dB μ V/m)




Quasi-peak measurement

Freq MHz	Read Antenna		Cable Preamp		Limit Line dB	Over Limit dB	Remark
	Freq MHz	Level dB μ V	Antenna Factor	Cable Loss dB	Preamp Factor		
54.835	23.83	13.02	1.10	31.00	6.95	40.00	-33.05 QP
98.142	20.38	13.03	1.38	31.00	3.79	43.50	-39.71 QP
146.888	33.67	8.24	1.61	31.06	12.46	43.50	-31.04 QP
205.675	22.34	10.74	1.91	31.09	3.90	43.50	-39.60 QP
379.914	23.24	14.59	2.76	30.91	9.68	46.00	-36.32 QP
670.489	23.83	18.71	3.44	30.90	15.08	46.00	-30.92 QP

Horizontal:

Peak scan

Level (dB μ V/m)

Quasi-peak measurement

Freq MHz	ReadAntenna		Cable		Preamp Level dB	Limit Line dB μ V/m	Over Limit dB	Over Limit Remark
	Level dB μ V	Factor dB/m	Loss Factor dB	Level dB μ V/m				
49.014	23.02	13.31	1.09	31.00	6.42	40.00	-33.58	QP
96.436	21.48	12.94	1.36	31.00	4.78	43.50	-38.72	QP
145.861	28.89	8.23	1.59	31.06	7.65	43.50	-35.85	QP
239.987	22.79	12.09	2.05	31.05	5.88	46.00	-40.12	QP
499.425	24.15	16.58	3.10	31.00	12.83	46.00	-33.17	QP
815.968	24.57	20.24	3.82	30.90	17.73	46.00	-28.27	QP

1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

Peak Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
4804.00	31.53	11.11	38.57	49.65	53.72	74.00	V
7206.00	36.47	12.90	38.84	42.23	52.76	74.00	V
9608.00	38.08	15.16	39.70	42.54	56.08	74.00	V
4804.00	31.53	11.11	38.57	48.16	52.23	74.00	H
7206.00	36.47	12.90	38.84	41.68	52.21	74.00	H
9608.00	38.08	15.16	39.70	42.25	55.79	74.00	H

Average Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
4804.00	31.53	11.11	38.57	38.25	42.32	54.00	V
7206.00	36.47	12.90	38.84	37.23	47.76	54.00	V
9608.00	38.08	15.16	39.70	36.16	49.70	54.00	V
4804.00	31.53	11.11	38.57	35.98	42.16	54.00	H
7206.00	36.47	12.90	38.84	35.51	46.04	54.00	H
9608.00	38.08	15.16	39.70	37.14	48.57	54.00	H

7.10.1.2 Test the middle Channel in transmitting status

9 kHz~30 MHz Field Strength of Unwanted Emissions.Quasi-Peak Measurement


The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.

30 MHz~1 GHz Spurious Emissions .Quasi-Peak Measurement

Vertical:

Peak scan

Level (dB μ V/m)




Quasi-peak measurement

Freq MHz	Read Level dB μ V	Antenna Factor	Cable Loss dB	Preamp Factor	Line Level dB	Line Limit dB μ V/m	Over Limit dB μ V/m	Over Limit Remark
	MHz	dB μ V	dB/m	dB	dB μ V/m	dB μ V/m	dB	
53.318	26.56	13.10	1.10	31.00	9.76	40.00	-30.24	QP
102.719	23.15	12.92	1.41	31.00	6.48	43.50	-37.02	QP
193.095	22.85	10.56	1.88	31.10	4.19	43.50	-39.31	QP
306.754	24.25	13.15	2.41	30.99	8.82	46.00	-37.18	QP
633.907	24.02	18.58	3.27	30.90	14.97	46.00	-31.03	QP
938.833	24.26	21.34	4.06	30.82	18.84	46.00	-27.16	QP

Horizontal:

Peak scan

Level (dB μ V/m)

Quasi-peak measurement

Freq MHz	Read	Antenna Level	Cable Loss	Preamp Factor	Limit Line dBuV/m	Over Line dBuV/m	Over Limit dB	Remark
	dBuV	dB/m	dB	dB				
41.422	21.54	13.57	1.01	31.01	5.11	40.00	-34.89	QP
59.649	21.37	12.73	1.10	31.00	4.20	40.00	-35.80	QP
104.170	21.66	12.78	1.41	31.00	4.85	43.50	-38.65	QP
236.645	24.29	11.93	2.03	31.06	7.19	46.00	-38.81	QP
350.477	23.08	14.27	2.60	30.94	9.01	46.00	-36.99	QP
699.305	24.62	18.80	3.50	30.90	16.02	46.00	-29.98	QP

1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

Peak Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
4882.00	31.58	11.26	38.56	48.21	52.49	74.00	V
7323.00	36.50	13.28	38.88	42.65	53.55	74.00	V
9764.00	38.53	15.03	39.75	43.04	56.85	74.00	V
4882.00	31.58	11.26	38.56	48.26	52.54	74.00	H
7323.00	36.50	13.28	38.88	42.97	53.87	74.00	H
9764.00	38.53	15.03	39.75	41.16	54.97	74.00	H

Average Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
4882.00	31.58	11.26	38.56	38.65	42.93	54.00	V
7323.00	36.50	13.28	38.88	37.16	48.06	54.00	V
9764.00	38.53	15.03	39.75	35.79	49.60	54.00	V
4882.00	31.58	11.26	38.56	38.12	42.40	54.00	H
7323.00	36.50	13.28	38.88	37.23	48.13	54.00	H
9764.00	38.53	15.03	39.75	35.15	48.96	54.00	H

7.10.1.3 Test the highest Channel in transmitting status

9 kHz~30 MHz Field Strength of Unwanted Emissions.Quasi-Peak Measurement


The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.

30 MHz~1 GHz Spurious Emissions .Quasi-Peak Measurement

Vertical:

Peak scan

Level (dB μ V/m)




Quasi-peak measurement

Freq	Read	Antenna	Cable	Preamp	Limit	Over	Over	Remark
	Level	Factor	Loss	Factor				
MHz	dB μ V	dB/m	dB	dB	dB μ V/m	dB μ V/m	dB	
41.132	21.15	13.57	1.01	31.01	4.72	40.00	-35.28	QP
54.071	19.90	13.06	1.10	31.00	3.06	40.00	-36.94	QP
97.115	21.91	12.97	1.37	31.00	5.25	43.50	-38.25	QP
195.822	19.91	10.57	1.89	31.10	1.27	43.50	-42.23	QP
333.687	22.41	13.92	2.49	30.96	7.86	46.00	-38.14	QP
620.710	23.53	18.53	3.23	30.90	14.39	46.00	-31.61	QP

Horizontal:

Peak scan

Level (dB μ V/m)

Quasi-peak measurement

Freq	Read		Antenna		Cable		Preamp		Limit	Over	Line	Limit	Remark
	Level	Factor	Loss	Factor	Level	dB	dB	dB μ V/m	dB μ V/m	dB			
MHz	dB μ V	dB/m											
42.007	23.59	13.57		1.01	31.01	7.16	40.00	40.00	40.00	-32.84	QP		
56.991	22.06	12.89		1.10	31.00	5.05	40.00	40.00	40.00	-34.95	QP		
92.462	25.99	12.41		1.32	31.00	8.72	43.50	43.50	43.50	-34.78	QP		
238.310	22.61	11.99		2.05	31.05	5.60	46.00	46.00	46.00	-40.40	QP		
431.032	23.62	15.52		2.86	30.94	11.06	46.00	46.00	46.00	-34.94	QP		
851.035	25.80	20.60		3.90	30.90	19.40	46.00	46.00	46.00	-26.60	QP		

1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

Peak Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
4960.00	31.70	11.39	38.56	50.65	55.18	74.00	V
7440.00	36.60	13.60	38.91	44.12	55.41	74.00	V
9920.00	38.65	14.92	39.78	43.36	57.15	74.00	V
4960.00	31.70	11.39	38.56	50.46	54.99	74.00	H
7440.00	36.60	13.60	38.91	41.76	53.05	74.00	H
9920.00	38.65	14.92	39.78	43.36	57.15	74.00	H

Average Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
4960.00	31.70	11.39	38.56	39.63	44.16	54.00	V
7440.00	36.60	13.60	38.91	37.35	48.64	54.00	V
9920.00	38.65	14.92	39.78	36.42	50.21	54.00	V
4960.00	31.70	11.39	38.56	37.96	42.49	54.00	H
7440.00	36.60	13.60	38.91	35.35	46.64	54.00	H
9920.00	38.65	14.92	39.78	33.46	47.25	54.00	H

Remark:

- 1). The field strength is calculated by adding the Antenna Factor. Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Loss –Preamplifier Factor.

- 2). As shown in Section, for frequencies above 1000 MHz. the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.
- 3). The test only perform the EUT in transmitting status since the test frequencies were over 1GHz only required transmitting status.

Test result: The unit does meet the FCC requirements.

7.10.2 Radiated Emissions which fall in the restricted bands

Test Requirement: FCC Part15 C Section 15.247

(d) In addition, radiated emissions which fall in the restricted bands. as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

Test Method: ANSI C63.10: Clause 6.4, 6.5 and 6.6

Test Status: Pre-test the EUT in continuous transmitting mode at the lowest (2402 MHz), middle (2441 MHz) and highest (2480 MHz) channel with different data packet. Compliance test in continuous transmitting mode with normal mode (DH5) as the worst case was found.

Measurement Distance: 3m (Semi-Anechoic Chamber)

Limit:

Section 15.209(a)
40.0 dB μ V/m between 30MHz & 88MHz;
43.5 dB μ V/m between 88MHz & 216MHz;
46.0 dB μ V/m between 216MHz & 960MHz;
54.0 dB μ V/m above 960MHz.

Detector: For PK value:

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

For AV value:

RBW = 1 MHz for $f \geq 1$ GHz,

VBW = 10 Hz

Sweep = auto

Detector function = peak

Trace = max hold

Test Result:**1. Lowest Channel****Peak Measurement:**

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
2310.000	27.93	6.52	38.23	47.14	43.36	74.00	V
2390.000	27.63	6.55	38.25	46.72	42.65	74.00	V
2483.500	27.55	6.99	38.26	46.42	42.70	74.00	V
2500.000	27.55	7.02	38.26	47.65	43.96	74.00	V
2310.000	27.93	6.52	38.23	46.15	42.37	74.00	H
2390.000	27.63	6.55	38.25	45.69	41.62	74.00	H
2483.500	27.55	6.99	38.26	46.79	43.07	74.00	H
2500.000	27.55	7.02	38.26	46.53	42.84	74.00	H

Average Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
2310.000	27.93	6.52	38.23	39.23	35.45	54.00	V
2390.000	27.63	6.55	38.25	38.65	34.58	54.00	V
2483.500	27.55	6.99	38.26	38.28	34.56	54.00	V
2500.000	27.55	7.02	38.26	37.14	33.45	54.00	V
2310.000	27.93	6.52	38.23	40.69	36.91	54.00	H
2390.000	27.63	6.55	38.25	38.19	34.12	54.00	H
2483.500	27.55	6.99	38.26	40.69	36.97	54.00	H
2500.000	27.55	7.02	38.26	39.13	35.44	54.00	H

2. Middle Channel

Peak Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
2310.000	27.93	6.52	38.23	46.65	42.87	74.00	V
2390.000	27.63	6.55	38.25	46.12	42.05	74.00	V
2483.500	27.55	6.99	38.26	46.45	42.73	74.00	V
2500.000	27.55	7.02	38.26	46.53	42.84	74.00	V
2310.000	27.93	6.52	38.23	46.65	42.87	74.00	H
2390.000	27.63	6.55	38.25	45.15	41.08	74.00	H
2483.500	27.55	6.99	38.26	46.95	43.23	74.00	H
2500.000	27.55	7.02	38.26	46.32	42.63	74.00	H

Average Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
2310.000	27.93	6.52	38.23	38.23	34.45	54.00	V
2390.000	27.63	6.55	38.25	35.45	31.38	54.00	V
2483.500	27.55	6.99	38.26	38.12	34.40	54.00	V
2500.000	27.55	7.02	38.26	38.65	34.96	54.00	V
2310.000	27.93	6.52	38.23	36.87	33.09	54.00	H
2390.000	27.63	6.55	38.25	37.54	33.47	54.00	H
2483.500	27.55	6.99	38.26	37.46	33.74	54.00	H
2500.000	27.55	7.02	38.26	37.69	34.00	54.00	H

**3. Highest Channel
Peak Measurement:**

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
2310.000	27.93	6.52	38.23	45.61	41.83	74.00	V
2390.000	27.63	6.55	38.25	46.11	42.04	74.00	V
2483.500	27.55	6.99	38.26	46.65	42.93	74.00	V
2500.000	27.55	7.02	38.26	47.15	43.46	74.00	V
2310.000	27.93	6.52	38.23	45.12	41.34	74.00	H
2390.000	27.63	6.55	38.25	45.65	41.58	74.00	H
2483.500	27.55	6.99	38.26	46.48	42.76	74.00	H
2500.000	27.55	7.02	38.26	46.82	43.13	74.00	H

Average Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
2310.000	27.93	6.52	38.23	40.28	36.50	54.00	V
2390.000	27.63	6.55	38.25	39.22	35.15	54.00	V
2483.500	27.55	6.99	38.26	41.57	37.85	54.00	V
2500.000	27.55	7.02	38.26	40.76	37.07	54.00	V
2310.000	27.93	6.52	38.23	37.65	33.87	54.00	H
2390.000	27.63	6.55	38.25	37.18	33.11	54.00	H
2483.500	27.55	6.99	38.26	39.12	35.40	54.00	H
2500.000	27.55	7.02	38.26	40.69	37.00	54.00	H

Remark: No any other emission which falls in restricted bands can be detected and be reported.

Test result: The unit does meet the FCC requirements.

Section 15.205 Restricted bands of operation.

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	
13.36 - 13.41			

7.11 Band Edges Requirement

Test Requirement: FCC Part15 C section 15.247


(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

Frequency Band: 2400 MHz to 2483.5 MHz

Test Method: KDB 00-705 item "Band-edge Compliance of RF Conducted Emissions"

Test Status: Pre-test the EUT in continuous transmitting mode at the lowest (2402 MHz), and highest (2480 MHz) channel and hopping mode with different data packet. Compliance test in continuous transmitting mode with normal (DH5) and EDR mode (3DH5) as the worst case was found.

Test Configuration:



Test Procedure:

Use the following spectrum analyzer settings:

Span = 10MHz (wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation.)

RBW = 100 kHz (1% of the span) and VBW = 300 kHz

Sweep = auto

Detector function = peak


Trace = max hold

Test Result:


Compare with the output power of the lowest frequency, the Lower Edges attenuated more than 20dB
Compare with the output power of the highest frequency, the Upper Edges attenuated more than 20dB.



Normal mode: DH5

Lowest channel(2.402 GHz):



Highest Channel(2.480 GHz):



EDR mode: 3DH5
Lowest channel(2.402 GHz):

Highest Channel(2.480 GHz):

Test result: The unit does meet the FCC requirements.
--End of Report--