



1600 Parkwood Circle
Suite 500
Atlanta, GA 30339
(770) 693-5950

Numerex

MPE Calculation for DigiCell® ANYNET

The FCC requires that the calculated MPE be equal to or less than a given limit dependent on frequency at a distance of 20 cm from a device to the body of a user.

The transmitter operation for the DigiCell® ANYNET covers GSM850 and PCS1900 operating bands.

The unit can operate with a choice of two external antennae for a) direct connection (+3dBi max. gain) and b) magnetic mount with 3 meter connecting lead (+3.5dBi max. gain with 2.8dB cable loss).

The equation for the MPE calculation is given in OET Bulletin 65, page 19 as:

$$S = EIRP/4 \pi R^2$$

Where S = Power density

$EIRP$ = Effective Isotropically Radiated Power ($EIRP = P \times G$)

R = distance to the centre of radiation of the antenna

For the DigiCell® ANYNET @ GSM 850

Transmitter frequency range = 824MHz to 849MHz

Values	Output power: +32.8dBm measured ERP max with standard antenna ie: ERP = 1905mW $EIRP = 1.64 \times ERP$ For a GPRS transmit duty cycle of 25% $EIRP = 1.64 \times 1905 \times 0.25 = 781mW$ $R = 20cm$
--------	---

Calculation

$$S = EIRP/4 \pi R^2$$

$$S = 781 / (12.56 \times 20^2)$$

$$S = 0.155 \text{ mW/cm}^2$$

Requirement

From table 1 (b) - Limits for General Population/ Uncontrolled Exposure of FCC Rule Part 1.1310 for GSM850

$$S = f/1500 \text{ mW/cm}^2 \text{ (} f = \text{operating frequency)}$$

$$S = 824/1500 = 0.549 \text{ mW/cm}^2 \text{ (DigiCell® ANYNET @ GSM 850 worst case)}$$



1600 Parkwood Circle
Suite 500
Atlanta, GA 30339
(770) 693-5950

Numerex

For the DigiCell® ANYNET @ PCS 1900

Transmitter frequency range = 1850MHz to 1910MHz

Values Output power: +28.4dBm measured EIRP max with standard antenna
 ie: EIRP = 691.8mW
 For a GPRS transmit duty cycle of 25%
 EIRP = $691.8 \times 0.25 = 172.95\text{mW}$
 R = 20cm

Calculation

$$\begin{aligned} S &= \text{EIRP}/4 \pi R^2 \\ S &= 172.95/(12.56 \times 20^2) \\ S &= 0.034 \text{ mW/cm}^2 \end{aligned}$$

Requirement

From table 1 (b) - Limits for General Population/ Uncontrolled Exposure of FCC Rule Part 1.1310 for PCS1900

S = 1.0 mW/cm² (DigiCell® ANYNET @ GSM 1900)

Alternative magnetic mount antenna considerations

The alternative antenna has a specified maximum gain of +3.5dBi with 2.8db connecting cable loss.

Considering a 0dB cable loss worst case (ie: +3.5dBi antenna gain), the 25% duty cycle EIRP for the DigiCell® ANYNET @ GSM 850 is 874mW.

For this higher power level the MPE is then calculated as 0.174 mW/cm².

This remains within the 0.549 mW/cm² requirement as calculated above from table 1 (b) - Limits for General Population/ Uncontrolled Exposure of FCC Rule Part 1.1310 for GSM850 worst case.

Conclusion

The MPE value of the DigiCell® ANYNET at 20 cm meets the RF exposure limits.