

FCC PART 15.247

EMI MEASUREMENT AND TEST REPORT

For

Cheung Hung Electronics Ltd.

Unit 4, 15/F, North Point Asia-pac Centre, No.28 A Java Road, North Point, Hong Kong

FCC ID: TWXCH-W808

This Report Concerns: <input checked="" type="checkbox"/> Original Report	Equipment Type: 2.4GHz Cordless phone
Test Engineer: Oscar Au 	
Report No.: R0511174	
Report Date: 2006-1-6	
Reviewed By: Snell Leong 	
Prepared By: Bay Area Compliance Laboratory Corporation (BACL) 230 Commercial Street Sunnyvale, CA 94085 Tel: (408) 732-9162 Fax: (408) 732 9164	

Note: The test report is specially limited to the above company and this particular sample only. It may not be duplicated without prior written consent of Bay Area Compliance Laboratory Corporation. This report **must not** be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST or any agency of the US Government.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	6
JUSTIFICATION	6
EUT EXERCISE SOFTWARE	6
SPECIAL ACCESSORIES.....	6
SCHEMATICS / BLOCK DIAGRAM.....	6
EQUIPMENT MODIFICATIONS	6
LOCAL SUPPORT EQUIPMENT.....	6
HOST PC POWER SUPPLY AND LINE FILTERS.....	6
CONFIGURATION OF TEST SYSTEM	7
TEST SETUP BLOCK DIAGRAM	7
SUMMARY OF TEST RESULTS.....	8
§15.203 - ANTENNA REQUIREMENT.....	9
STANDARD APPLICABLE	9
§15.207 (a)- CONDUCTED EMISSION.....	10
MEASUREMENT UNCERTAINTY	10
TEST SETUP.....	10
RECEIVER SETUP.....	10
TEST EQUIPMENT LIST AND DETAILS.....	10
TEST PROCEDURE	10
ENVIRONMENTAL CONDITIONS	10
SUMMARY OF TEST RESULTS	11
CONDUCTED EMISSIONS TEST DATA	11
PLOT OF CONDUCTED EMISSIONS TEST DATA	11
§15.205 & §15.209 - RADIATED EMISSION.....	14
MEASUREMENT UNCERTAINTY	14
TEST SETUP.....	14
SPECTRUM ANALYZER SETUP	14
TEST EQUIPMENT LIST AND DETAILS.....	14
TEST PROCEDURE	15
CORRECTED AMPLITUDE & MARGIN CALCULATION	15
ENVIRONMENTAL CONDITIONS	15
SUMMARY OF TEST RESULTS	15
TX RADIATED EMISSION TEST RESULT	16
§15.247 (a) (1) - HOPPING CHANNEL SEPARATION	22
STANDARD APPLICABLE	22
MEASUREMENT PROCEDURE.....	22
TEST EQUIPMENT	22
ENVIRONMENTAL CONDITIONS	22
MEASUREMENT RESULTS.....	23
PLOTS OF HOPPING CHANNEL SEPARATION	23
§15.247(a)(1) – 20 dB BANDWIDTH.....	27
STANDARD APPLICABLE	27
MEASUREMENT PROCEDURE.....	27
EQUIPMENT LISTS	27
MEASUREMENT RESULT	27

§15.247 (a) (1) (iii) - NUMBER OF HOPPING FREQUENCY USED	33
STANDARD APPLICABLE	33
MEASUREMENT PROCEDURE.....	33
TEST EQUIPMENT	33
ENVIRONMENTAL CONDITIONS	33
MEASUREMENT RESULTS.....	33
PLOTS OF NUMBER OF HOPPING FREQUENCY	34
§15.247 (a) (1) (iii) - DWELL TIME	36
STANDARD APPLICABLE	36
MEASUREMENT PROCEDURE.....	36
TEST EQUIPMENT	36
ENVIRONMENTAL CONDITIONS	36
MEASUREMENT RESULTS.....	36
PLOTS OF DWELL TIME	37
§15.247(b)(1) - PEAK OUTPUT POWER MEASUREMENT	44
STANDARD APPLICABLE	44
MEASUREMENT PROCEDURE.....	44
EQUIPMENT LISTS	44
MEASUREMENT RESULT	44
§15.247 (e)(i) - RF EXPOSURE.....	50
§15.247(d) - 100 KHZ BANDWIDTH OF BAND EDGES.....	53
STANDARD APPLICABLE	53
MEASUREMENT PROCEDURE.....	53
EQUIPMENT LISTS	53
MEASUREMENT RESULT	53
§2.1051 - SPURIOUS EMISSION AT ANTENNA PORT.....	56
STANDARD APPLICABLE	56
MEASUREMENT PROCEDURE.....	56
EQUIPMENT LISTS	56
MEASUREMENT RESULT	56

GENERAL INFORMATION

Product Description for Equipment Under Test (EUT)

The *Cheung Hung Electronics Ltd.*'s product, *FCC ID: TWXCH-W808*, Model: *CH-W808* or the "EUT" as referred to this report is a 2.4GHz Cordless phone. The base part of the EUT measures approximately 170mmL x 90mmW x 90mmH and the handset part of the EUT measures approximately 170mmL x 45mmW x 30mmH.

* *The test data gathered are from typical production sample, serial number: 001 provided by the manufacturer.*

Objective

This type approval report is prepared on behalf of *Cheung Hung Electronics Ltd.* in accordance with Part 2, Subpart J, Part 15, Subparts A , B and C of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC rules for Output Power, Antenna Requirements, Dwell Time, Number of Hopping number, Channel Separation , 100 kHz Bandwidth of Band Edges Measurement, Spurious Emission, Conducted and Spurious Radiated Emission.

Related Submittal(s)/Grant(s)

No Related Submittals.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratory, Corp. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Open Area Test site used by BACL to collect radiated and conducted emission measurement data is located in the back parking lot of the building at 230 Commercial Street, Sunnyvale, California, USA with registration number: 90464.

Test site at BACL has been fully described in reports submitted to the Federal Communication Commission (FCC) and Voluntary Control Council for Interference (VCCI). The details of these reports has been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 11 and December 10, 1997 and Article 8 of the VCCI regulations on December 25, 1997. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission and Voluntary Control Council for Interference has the reports on file and is listed under FCC file 31040/SIT 1300F2 and VCCI Registration No.: C-1298 and R-1234. The test site has been approved by the FCC and VCCI for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, BACL is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (Lab Code 200167-0). The current scope of accreditations can be found at <http://ts.nist.gov/ts/htdocs/210/214/scopes/2001670.htm>

SYSTEM TEST CONFIGURATION

Justification

The host system was configured for testing according to ANSI C63.4-2003.

The EUT was tested in the normal (native) operating mode to represent *worst-case* results during the final qualification test.

EUT Exercise Software

Engineering software for RF testing

Special Accessories

As shown in following test block diagram, all interface cables used for compliance testing are shielded.

Schematics / Block Diagram

Please refer to Appendix A.

Equipment Modifications

No modifications were made to the EUT.

Local Support Equipment


Manufacturer	Description	Model	Serial Number	FCC ID
Southern Telecom	Telephone	None	None	None
Teltone Corp	Phone Simulator	TLS-3B-01	80071	None

Host PC Power Supply and Line Filters


Manufacturer	Description	Model	Serial Number	FCC ID
Cheung Hung Electronics	AC Adaptor	N/A	N/A	None

Configuration of Test System

Conducted Emission




Radiated Emission




Test Setup Block Diagram

Conducted Emission



Radiated Emission



SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.203	Antenna Requirement	Compliant
§ 15.205	Restricted Bands	Compliant
§15.207 (a)	Conducted Emission	Compliant
§15.209	Radiated Emission	Compliant*
§15.247 (a) (1)	Hopping Channel Separation	Compliant
§15.247 (a) (1)	Channel Bandwidth	Compliant
§15.247 (a) (1) (iii)	Number of Hopping Frequencies Used	Compliant
§15.247 (a) (1) (iii)	Dwell Time of Each Frequency within 37.2 Second Period of time (0.4 x Number of Channel)	Compliant
§15.247 (b) (1)	Maximum Peak Output Power	Compliant
§ 15.247 (e)(i) § 2.1093	RF Safety Requirements	Compliant
§ 15.247 (d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§ 2.1051	Spurious Emission at Antenna Port	Compliant

* test data are within the measurement uncertainty

§15.203 - ANTENNA REQUIREMENT

Standard Applicable

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to § 15.247 (b) (4), if transmitting antennas of directional gain greater than 6 dBi are used the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

The antenna for this device is an integral antenna with gain of 0 dBi.

§15.207 (a)- CONDUCTED EMISSION

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are receiver, cable loss, and LISN.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement at BACL is ± 2.4 dB.

Test Setup

The measurement was performed at shield room, using the same setup per ANSI C63.4 – 2003 measurement procedure. The specification used was FCC Class B limits.

External I/O cables were draped along the edge of the test table and bundle when necessary.

The EUT was connected with LISN-1.

Receiver Setup

The EMI receiver was set to investigate the spectrum from 150 kHz to 30MHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Cal. Date
Rohde & Schewarz	Artificial-Mains Network	ESH2-Z5	871884/039	8/16/2005
Rohde & Schewarz	EMI Test Receiver	ESCS30	100176	9/15/2005
Fluke	Calibrated Voltmeter	189	18485-38	12/29/2005

* **Statement of Traceability:** BACL Corp. attests that all calibrations have been performed per the NVLAP requirements, traceable to the NIST.

Test Procedure

During the conducted emission test, the power cord of the EUT was connected to the mains outlet of the LISN-1.

Maximizing procedures were performed on the six (6) highest emissions of the EUT.

All data was recorded in the peak detection mode, quasi-peak and average. Quasi-Peak readings are distinguished with an “QP”. Average readings are distinguished with an “Ave”.

Environmental Conditions

Temperature:	15° C
Relative Humidity:	45%
ATM Pressure:	1009 mbar

*The testing was performed by Oscar Au on 2005-12-09.

Summary of Test Results

According to the recorded data in following table, the EUT complied with the FCC Conducted limit for a Class B device, with the *worst* margin reading of:

-11.7 dB at 0.325 MHz in the **Neutral** conductor

Conducted Emissions Test Data

LINE CONDUCTED EMISSIONS				FCC CLASS B	
Frequency MHz	Amplitude dB μ V	Detector Qp/Ave/Peak	Phase Line/Neutral	Limit dB μ V	Margin dB
0.325	37.9	Ave	Neutral	49.58	-11.7
0.240	39.4	Ave	Neutral	52.10	-12.7
0.160	40.4	Ave	Neutral	55.46	-15.1
0.240	44.4	QP	Neutral	62.10	-17.7
0.325	38.8	QP	Neutral	59.58	-20.8
1.130	23.1	Ave	Line	46.00	-22.9
0.160	42.3	QP	Neutral	65.46	-23.2
24.000	20.3	Ave	Line	50.00	-29.7
0.160	25.2	Ave	Line	55.46	-30.3
1.130	24.4	QP	Line	56.00	-31.6
24.000	23.4	QP	Line	60.00	-36.6
0.160	27.4	QP	Line	65.46	-38.1


Plot of Conducted Emissions Test Data

Plot(s) of Conducted Emissions Test Data is presented in the following page as reference.


Bay Area Compliance Laboratory Corp
Class B

08. Dec 05 16:39

BUT: 2.4GHz digital cordless phone (CH-W808)
Manuf: Cheung Hung Electronics
Op Cond: Normal
Operator: Oscar
Comment: L
120VAC


12/09/05

Scan Settings (3 Ranges)			Receiver Settings				
Frequencies			IF BW	Detector	M-Time	Atten	Preamp
Start	Stop	Step	8K	QP+AV	20ms	15dBBLN	OFF
150k	1M	5K	9K	QP+AV	1ms	15dBBLN	OFF
1M	5M	10K	9K	QP+AV	1ms	15dBBLN	OFF
5M	30M	100K	9K	QP+AV	1ms	15dBBLN	OFF



Bay Area Compliance Laboratory Corp
Class B


09. Dec 05 17:13

BUT: 2.4GHz digital cordless phone (CH-W808)
Manuf: Cheung Hung Electronics
Op Cond: Normal
Operator: Oscar
Comment: N
120VAC

WA
12/09/05

Scan Settings (3 Ranges)

Frequencies			Receiver Settings					
Start	Stop	Step	IF BW	Detector	W-Times	Atten	Preamp	
150k	1M	5k	9k	QP+AV	20ms	15dBBLN	OFF	
1M	8M	10k	9k	QP+AV	1ms	15dBBLN	OFF	
8M	30M	100k	9k	QP+AV	1ms	15dBBLN	OFF	



§15.205 & §15.209 - RADIATED EMISSION

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at BACL is ± 4.0 dB.

Test Setup

The radiated emission tests were performed in the open area 3-meter test site, using the setup in accordance with ANSI C63.4-2003. The specification used was the FCC 15 Subpart C limits.

Spectrum Analyzer Setup

According to FCC Rules, 47 CFR §15.33 (a) (1), the system was tested to 25GHz.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

Frequency Range	RBW	Video B/W
Below 30MHz	10kHz	10kHz
30 – 1000MHz	100kHz	100kHz
Above 1000MHz	1MHz	1MHz

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Cal. Date
Agilent	Amplifier, Pre	8447D	2944A10198	8/17/2005
Agilent	Amplifier, Pre	8449B	3147A00400	10/05/2005
Sunol Science Corp	Combination Antenna	JB1 Antenna	A013105	2/11/2005
Rohde & Schewarz	EMI Test Receiver	ESCI 1166.595 0K03	100044	11/29/2005
Sunol Science Corp	System Controller	SC99V	122303-1	N/R
Agilent	Amplifier, Pre	8449B	3008A01988	8/10/2005
Sunol Science Corp	Horn Antenna	SAS-200/571	261	4/20/2005

* **Statement of Traceability:** BACL attests that all calibrations have been performed per the NVLAP requirements, traceable to NIST.

Test Procedure

For the radiated emissions test, the EUT, and all support equipment power cords was connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the peak detection mode. Quasi-peak readings performed only when an emission was found to be marginal (within -4 dB μ V of specification limits), and are distinguished with a "Qp" in the data table.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC 15.247 Limit}$$

Environmental Conditions

Temperature:	15° C
Relative Humidity:	45%
ATM Pressure:	1009 mbar

The testing was performed by Oscar Au on 2005-12-18.

Summary of Test Results

According to the data hereinafter, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247, and had the worst margin of:

For Handset of EUT (TX Spurious Emission):

-11.5 dB at 7203.0000 MHz in the **Vertical** polarization, Low Channel

-10.7 dB at 7323.0000 MHz in the **Horizontal** polarization, Middle Channel

-8.2 dB at 7446.0000MHz in the **Vertical** polarization, High Channel

For Base of EUT:

-7.7 dB at 7203.0000MHz in the **Vertical** polarization, Low Channel

-5.4 dB at 7323.0000MHz in the **Vertical** polarization, Middle Channel

-4.2 dB at 7446.0000 MHz in the **Vertical** polarization, High Channel

For Handset of EUT(RX Spurious Emission):**-7.5 dB at 538.30 MHz** in the **Horizontal** polarization, Unintentional Emission

For Base of EUT:

-14.2dB at 113.40MHz in the **Horizontal** polarization, Unintentional Emission**TX Radiated Emission Test Result**

For Handset of EUT (TX Spurious Emission)

Low Channel, 1-25GHz

INDICATED		TABLE	ANTENNA		CORRECTION FACTOR			CORRECTED AMPLITUDE	FCC 15 SUBPART C			
Frequency	Meter Reading		Angle	Height	Polar	Antenna Loss	Cable Loss	Amp.	Corr. Ampl.	Limit	Margin	PK/AV/QP
MHz	dB μ V	Degree	Meter	H/ V	dB	dB	dB	dB μ V/m	dB μ V/m	dB		
2401.0000	117.8	90	2.5	v	28.7	2.0	35.8	112.6				Fund/Peak
2401.0000	122.6	0	2.0	h	28.7	2.0	35.8	117.4				Fund/Peak
2401.0000	65.5	90	2.5	v	28.7	2.0	35.8	60.3				Ave
2401.0000	66.8	0	2.0	h	28.7	2.0	35.8	61.6				Ave
7203.0000	36.2	270	1.5	v	36.7	4.3	34.7	42.5	54	-11.5		Ave
7203.0000	36.0	60	2.0	h	36.7	4.3	34.7	42.3	54	-11.7		Ave
7203.0000	54.6	270	1.5	v	36.7	4.3	34.7	60.9	74	-13.1		Peak
7203.0000	53.3	60	2.0	h	36.7	4.3	34.7	59.6	74	-14.4		Peak
4802.0000	58.0	90	1.5	v	32.5	3.1	34.8	58.8	74	-15.2		Peak
4802.0000	57.4	340	1.8	h	32.5	3.1	34.8	58.2	74	-15.8		Peak
4802.0000	34.7	90	1.5	v	32.5	3.1	34.8	35.5	54	-18.5		Ave
4802.0000	34.5	340	1.8	h	32.5	3.1	34.8	35.3	54	-18.7		Ave

Middle Channel, 1-25GHz

INDICATED		TABLE	ANTENNA		CORRECTION FACTOR			CORRECTED AMPLITUDE	FCC 15 SUBPART C			
Frequency MHz	Meter Reading dB μ V		Angle Degree	Height Meter	Polar H/V	Antenna Loss dB	Cable Loss dB	Amp. dB	Corr. Ampl. dB μ V/m	Limit dB μ V/m	Margin dB	PK/AV/QP
2441.0000	119.3	270	1.0	v	28.7	2.0	35.8	114.1				Fund/Peak
2441.0000	121.6	180	3.0	h	28.7	2.0	35.8	116.4				Fund/Peak
2441.0000	64.8	270	1.0	v	28.7	2.0	35.8	59.6				Ave
2441.0000	67.1	180	3.0	h	28.7	2.0	35.8	61.9				Ave
7323.0000	37.0	90	1.8	h	36.7	4.3	34.7	43.3	54	-10.7		Ave
7323.0000	36.9	180	2.0	v	36.7	4.3	34.7	43.2	54	-10.8		Ave
7323.0000	55.5	90	1.8	h	36.7	4.3	34.7	61.8	74	-12.2		Peak
7323.0000	52.6	180	2.0	v	36.7	4.3	34.7	58.9	74	-15.1		Peak
4882.0000	57.3	270	2.0	h	32.5	3.1	34.8	58.1	74	-15.9		Peak
4882.0000	35.3	270	2.0	h	32.5	3.1	34.8	36.1	54	-17.9		Ave
4882.0000	34.8	90	2.0	v	32.5	3.1	34.8	35.6	54	-18.4		Ave
4882.0000	53.8	90	2.0	v	32.5	3.1	34.8	54.6	74	-19.4		Peak

High Channel, 1-25GHz

INDICATED		TABLE	ANTENNA		CORRECTION FACTOR			CORRECTED AMPLITUDE	FCC 15 SUBPART C			
Frequency MHz	Meter Reading dB μ V		Angle Degree	Height Meter	Polar H/V	Antenna Loss dB	Cable Loss dB	Amp. dB	Corr. Ampl. dB μ V/m	Limit dB μ V/m	Margin dB	PK/AV/QP
2482.0000	115.3	300	1.5	v	28.7	2.0	35.8	110.1				Fund/Peak
2482.0000	121.3	180	1.5	h	28.7	2.0	35.8	116.1				Fund/Peak
2482.0000	67.1	300	1.5	v	28.7	2.0	35.8	61.9				Ave
2482.0000	67.6	180	1.5	h	28.7	2.0	35.8	62.4				Ave
7446.0000	59.5	90	2.0	v	36.7	4.3	34.7	65.8	74	-8.2		Peak
7446.0000	38.0	90	2.0	v	36.7	4.3	34.7	44.3	54	-9.7		Ave
7446.0000	37.3	200	1.5	h	36.7	4.3	34.7	43.6	54	-10.4		Ave
7446.0000	57.0	200	1.5	h	36.7	4.3	34.7	63.3	74	-10.7		Peak
4964.0000	59.8	0	1.5	h	32.5	3.1	34.8	60.6	74	-13.4		Peak
4964.0000	56.2	270	1.8	v	32.5	3.1	34.8	57.0	74	-17.0		Peak
4964.0000	36.0	0	1.5	h	32.5	3.1	34.8	36.8	54	-17.2		Ave
4964.0000	35.5	270	1.8	v	32.5	3.1	34.8	36.3	54	-17.7		Ave

For Base of EUT (TX Spurious Emission)

Low Channel, 1-25GHz

INDICATED		TABLE	ANTENNA		CORRECTION FACTOR			CORRECTED AMPLITUDE	FCC 15 SUBPART C			
Frequency MHz	Meter Reading dB μ V		Angle Degree	Height Meter	Polar H/ V	Antenna Loss dB	Cable Loss dB	Amp. dB	Corr. Ampl. dB μ V/m	Limit dB μ V/m	Margin dB	PK/AV/QP
2401.0000	124.3	90	2.0	v	28.7	2.0	35.8	119.1				Fund/Peak
2401.0000	114.7	180	1.5	h	28.7	2.0	35.8	109.5				Fund/Peak
2401.0000	68.8	90	2.0	v	28.7	2.0	35.8	63.6				Ave
2401.0000	57.4	180	1.5	h	28.7	2.0	35.8	52.2				Ave
7203.0000	60.0	90	1.5	v	36.7	4.3	34.7	66.3	74	-7.7		Peak
3102.0000	69.0	180	1.8	v	29.8	2.5	35.2	66.2	74	-7.8		Peak
7203.0000	58.2	180	2.0	h	36.7	4.3	34.7	64.5	74	-9.5		Peak
3102.0000	66.5	90	1.5	h	29.8	2.5	35.2	63.7	74	-10.3		Peak
3601.0000	65.3	180	1.8	v	30.0	2.7	34.8	63.2	74	-10.8		Peak
7203.0000	36.8	90	1.5	v	36.7	4.3	34.7	43.1	54	-10.9		Ave
7203.0000	36.5	180	2.0	h	36.7	4.3	34.7	42.8	54	-11.2		Ave
4802.0000	35.8	270	2.4	v	32.5	3.1	34.8	36.6	54	-17.4		Ave
4802.0000	54.4	180	1.5	v	32.5	3.1	34.8	55.2	74	-18.8		Peak
4802.0000	34.2	180	2.3	h	32.5	3.1	34.8	35.0	54	-19.0		Ave
3291.0000	56.8	160	2.0	v	29.8	2.5	35.2	54.0	74	-20.0		Peak
3601.0000	36.0	180	1.8	v	30.0	2.7	34.8	33.9	54	-20.1		Ave
3601.0000	55.6	30	2.2	h	30.0	2.7	34.8	53.5	74	-20.5		Peak
3102.0000	36.2	180	1.8	v	29.8	2.5	35.2	33.4	54	-20.6		Ave
3291.0000	35.5	160	2.0	v	29.8	2.5	35.2	32.7	54	-21.3		Ave
3102.0000	35.5	90	1.5	h	29.8	2.5	35.2	32.7	54	-21.3		Ave
3291.0000	55.2	180	2.5	h	29.8	2.5	35.2	52.4	74	-21.6		Peak
3291.0000	35.2	180	2.5	h	29.8	2.5	35.2	32.4	54	-21.6		Ave
4802.0000	50.3	180	2.3	h	32.5	3.1	34.8	51.1	74	-22.9		Peak
3601.0000	33.1	30	2.2	h	30.0	2.7	34.8	31.0	54	-23.0		Ave

Middle Channel, 1-25GHz

INDICATED		TABLE	ANTENNA		CORRECTION FACTOR			CORRECTED AMPLITUDE	FCC 15 SUBPART C			
Frequency MHz	Meter Reading dB μ V		Angle Degree	Height Meter	Polar H/V	Antenna Loss dB	Cable Loss dB	Amp. dB	Corr. Ampl. dB μ V/m	Limit dB μ V/m	Margin dB	PK/AV/QP
2441.0000	119.1	90	1.0	v	28.7	2.0	35.8	113.9				Fund/Peak
2441.0000	124.8	180	1.2	h	28.7	2.0	35.8	119.6				Fund/Peak
2441.0000	66.7	90	1.2	v	28.7	2.0	35.8	61.5				Ave
2441.0000	67.3	180	1.2	h	28.7	2.0	35.8	62.1				Ave
7323.0000	62.3	90	1.5	v	36.7	4.3	34.7	68.6	74	-5.4		Peak
3142.0000	69.0	180	1.8	v	29.8	2.5	35.2	66.2	74	-7.8		Peak
7323.0000	59.7	180	2.0	h	36.7	4.3	34.7	66.0	74	-8.0		Peak
3318.0000	68.0	180	2.5	v	29.8	2.5	35.2	65.2	74	-8.8		Peak
7323.0000	37.3	90	1.5	v	36.7	4.3	34.7	43.6	54	-10.4		Ave
7323.0000	37.1	180	2.0	h	36.7	4.3	34.7	43.4	54	-10.6		Ave
3318.0000	62.7	60	1.8	h	29.8	2.5	35.2	59.9	74	-14.1		Peak
3142.0000	59.9	90	1.5	h	29.8	2.5	35.2	57.1	74	-16.9		Peak
4882.0000	34.8	270	1.8	v	32.5	3.1	34.8	35.6	54	-18.4		Ave
4882.0000	34.3	180	1.5	h	32.5	3.1	34.8	35.1	54	-18.9		Ave
3318.0000	37.3	180	2.5	v	29.8	2.5	35.2	34.5	54	-19.5		Ave
4882.0000	53.1	270	1.8	v	32.5	3.1	34.8	53.9	74	-20.1		Peak
3142.0000	36.2	180	1.8	v	29.8	2.5	35.2	33.4	54	-20.6		Ave
3318.0000	35.5	60	1.8	h	29.8	2.5	35.2	32.7	54	-21.3		Ave
3142.0000	34.5	90	1.5	h	29.8	2.5	35.2	31.7	54	-22.3		Ave
4882.0000	50.1	180	1.5	h	32.5	3.1	34.8	50.9	74	-23.1		Peak

High Channel, 1-25GHz

INDICATED		TABLE	ANTENNA		CORRECTION FACTOR			CORRECTED AMPLITUDE	FCC 15 SUBPART C			
Frequency MHz	Meter Reading dB μ V		Angle Degree	Height Meter	Polar H/V	Antenna Loss dB	Cable Loss dB		Corr. Ampl. dB μ V/m	Limit dB μ V/m	Margin dB	PK/AV/QP
2482.0000	122.9	160	2.0	v	28.7	2.0	35.8	117.7				Fund/Peak
2482.0000	117.1	200	1.2	h	28.7	2.0	35.8	111.9				Fund/Peak
2482.0000	67.2	160	2.0	v	28.7	2.0	35.8	62.0				Ave
2482.0000	66.8	200	1.2	h	28.7	2.0	35.8	61.6				Ave
7446.0000	63.5	300	2.0	v	36.7	4.3	34.7	69.8	74	-4.2		Peak
3724.0000	70.7	160	2.0	v	30.0	2.7	34.8	68.6	74	-5.4		Peak
7446.0000	60.8	180	2.0	h	36.7	4.3	34.7	67.1	74	-6.9		Peak
3359.0000	68.8	180	2.0	v	29.8	2.5	35.2	66.0	74	-8.0		Peak
7446.0000	38.5	300	2.0	v	36.7	4.3	34.7	44.8	54	-9.2		Ave
7446.0000	37.9	180	2.0	h	36.7	4.3	34.7	44.2	54	-9.8		Ave
3182.0000	65.6	180	1.8	v	29.8	2.5	35.2	62.8	74	-11.2		Peak
3182.0000	62.4	160	2.0	h	29.8	2.5	35.2	59.6	74	-14.4		Peak
3724.0000	61.5	180	2.0	h	30.0	2.7	34.8	59.4	74	-14.6		Peak
4964.0000	55.8	200	1.8	v	32.5	3.1	34.8	56.6	74	-17.4		Peak
4964.0000	35.2	200	2.0	v	32.5	3.1	34.8	36.0	54	-18.0		Ave
4964.0000	34.7	30	2.1	h	32.5	3.1	34.8	35.5	54	-18.5		Ave
3724.0000	37.2	160	2.0	v	30.0	2.7	34.8	35.1	54	-18.9		Ave
3359.0000	57.6	180	2.0	h	29.8	2.5	35.2	54.8	74	-19.2		Peak
3724.0000	36.2	180	2.0	h	30.0	2.7	34.8	34.1	54	-19.9		Ave
3182.0000	36.3	180	1.8	v	29.8	2.5	35.2	33.5	54	-20.5		Ave
3359.0000	35.8	180	2.0	v	29.8	2.5	35.2	33.0	54	-21.0		Ave
3182.0000	35.8	160	2.0	h	29.8	2.5	35.2	33.0	54	-21.0		Ave
3359.0000	34.2	180	2.0	h	29.8	2.5	35.2	31.4	54	-22.6		Ave
4964.0000	49.9	30	2.0	h	32.5	3.1	34.8	50.7	74	-23.3		Peak

30MHz - 1GHz (RX Spurious Emission)

For Handset of EUT

Frequency MHz	Indicated		Table Height Meter	Antenna		Cable Loss dB	Correction Factor		FCC 15 Subpart B	
	Ampl. dB μ V/m	Direction Degree		Polar	Antenna dB		Amp. dB	Corr. Ampl. dB μ V/m	Limit dB μ V/m	Margin dB
538.30	46.5	200	2.5	H	18.6	1.7	28.3	38.5	46	-7.5
496.60	45.9	180	1.5	H	17.9	1.6	28.5	36.9	46	-9.1
538.30	43.4	160	1.0	V	18.6	1.7	28.3	35.4	46	-10.6
496.60	44.3	200	1.5	V	17.9	1.6	28.5	35.3	46	-10.7
516.90	43.5	260	2.0	H	18.5	1.7	28.5	35.2	46	-10.8
516.90	41.2	180	1.5	V	18.5	1.7	28.5	32.9	46	-13.1
340.40	40.2	180	2.5	H	15.4	1.3	27.3	29.6	46	-16.4
351.10	40.6	180	3.0	H	14.9	1.3	27.3	29.5	46	-16.5
330.70	38.7	60	2.5	H	15.4	1.3	27.4	28.0	46	-18.0
58.90	39.0	30	1.5	V	10.3	0.6	28.4	21.5	40	-18.5
352.30	38.5	200	1.0	V	14.9	1.3	27.3	27.4	46	-18.6

For Base of EUT

Frequency MHz	Indicated		Table Height Meter	Antenna		Cable Loss dB	Correction Factor		FCC 15 Subpart B	
	Ampl. dB μ V/m	Direction Degree		Polar	Antenna dB		Amp. dB	Corr. Ampl. dB μ V/m	Limit dB μ V/m	Margin dB
113.40	45.1	180	3.0	H	11.7	0.8	28.3	29.3	43.5	-14.2
175.50	41.5	180	2.5	H	13.4	1.0	27.7	28.2	43.5	-15.3
466.63	39.7	180	1.5	H	17.1	1.6	28.3	30.1	46	-15.9
82.80	41.3	200	2.0	H	9.6	0.7	28.5	23.1	40	-16.9
113.40	42.2	100	1.5	V	11.7	0.8	28.3	26.4	43.5	-17.1
82.80	40.5	300	1.0	V	9.6	0.7	28.5	22.3	40	-17.7
175.50	38.9	200	1.0	V	13.4	1.0	27.7	25.6	43.5	-17.9
466.63	36.8	240	1.0	V	17.1	1.6	28.3	27.2	46	-18.8
134.40	38.4	60	1.5	V	12.6	0.8	28.1	23.8	43.5	-19.8

AVG = average

§15.247 (a) (1) - HOPPING CHANNEL SEPARATION

Standard Applicable

According to §15.247(a)(1), frequency hopping system shall have, hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies.

Measurement Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on a bench without connection to measurement instrument Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the Max-Hold function record the separation of two adjacent channels.
4. Measure the frequency difference of these two adjacent channels by SA MARK function, and then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

Test Equipment

Manufacturer	Description	Model No.	Serial No.	Calibration Date
Agilent	Analyzer, Spectrum	E4446A	US44300386	11/10/2005

* **Statement of Traceability:** BACL Corp. attests that all calibrations have been performed per the NVLAP requirements, traceable to the NIST.

Environmental Conditions

Temperature:	15° C
Relative Humidity:	46%
ATM Pressure:	1009 mbar

*The testing was performed by Oscar Au on 2005-12-18.

Measurement Results

For Handset of EUT

Channel	Frequency MHz	Channel Separation (MHz)
Low	2401	0.865
Mid	2441	0.865
High	2482	0.865


For Base of EUT

Channel	Frequency MHz	Channel Separation (MHz)
Low	2401	0.862
Mid	2441	0.88
High	2482	0.88


Plots of Hopping Channel Separation

Please refer to the following plots.


Handset of EUT, Low Channel




Handset of EUT, Middle Channel




Handset of EUT, High Channel




Base of EUT, Low Channel



Base of EUT, Middle Channel



Base of EUT, High Channel



§15.247(a)(1) – 20 dB BANDWIDTH

Standard Applicable

According to §15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Equipment Lists

Manufacturer	Description	Model	Serial Number	Cal. Date
Agilent	Analyzer, Spectrum	E4446A	US44300386	11/10/2005

* **Statement of Traceability:** **BACL Corp.** attests that all calibrations have been performed per the NVLAP requirements, traceable to the NIST.

Measurement Result

Environmental Conditions

Temperature:	15° C
Relative Humidity:	46%
ATM Pressure:	1009 mbar

The testing was performed by Oscar Au on 2005-12-18.

Test Result


For Handset of EUT

Channel	Frequency MHz	Channel Bandwidth (KHz)	Limit (KHz)	Result
Low	2401	705.02	<865	Pass
Mid	2441	690.05	<865	Pass
High	2482	697.6	<865	Pass

For Base of EUT

Channel	Frequency MHz	Channel Bandwidth (KHz)	Limit (KHz)	Result
Low	2401	682.75	<862	Pass
Mid	2441	679.22	<880	Pass
High	2482	693.14	<880	Pass

Handset of EUT, Low Channel



Handset of EUT, Mid. Channel




Handset of EUT, High Channel




Base of EUT, Low Channel



Base of EUT, Mid. Channel



Base of EUT, High Channel



§15.247 (a) (1) (iii) - NUMBER OF HOPPING FREQUENCY USED

Standard Applicable

According to §15.247(a)(1)(iii), frequency-hopping systems operating in the 2400-2483.5Mhz band shall use at least 15 hopping frequencies.

Measurement Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the bench without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set the SA on Max-Hold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
4. Set the SA on View mode and then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

Test Equipment

Manufacturer	Description	Model No.	Serial No.	Calibration Date
Agilent	Analyzer, Spectrum	E4446A	US44300386	11/10/2005

* **Statement of Traceability:** **BACL Corp.** attests that all calibrations have been performed per the NVLAP requirements, traceable to the NIST.

Environmental Conditions

Temperature:	15° C
Relative Humidity:	46%
ATM Pressure:	1009 mbar

*The testing was performed by Oscar Au on 2005-12-18.

Measurement Results

For Handset of EUT

Measurement	Standard	Result
93	>15	Compliant



For Base of EUT

Measurement	Standard	Result
93	>15	Compliant



Plots of Number of Hopping Frequency

Please refer to the attached plots.

Handset of EUT



Base of EUT



§15.247 (a) (1) (iii) - DWELL TIME

Standard Applicable

According to §15.247 (a)(1)(iii), the average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
4. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
5. Repeat above procedures until all frequencies measured were complete.

Test Equipment

Manufacturer	Description	Model No.	Serial No.	Calibration Date
Agilent	Analyzer, Spectrum	E4446A	US44300386	11/10/2005

* **Statement of Traceability:** **BACL Corp.** attests that all calibrations have been performed per the NVLAP requirements, traceable to the NIST.

Environmental Conditions

Temperature:	15° C
Relative Humidity:	46%
ATM Pressure:	1009 mbar

*The testing was performed by Oscar Au on 2005-12-18.

Measurement Results

For Handset of EUT

Channel	Frequency MHz	Pulse Wide uSec	Occupied time per 1 Sec	Dwell Time Sec	Limit Sec
Low	2401	788.7	38	0.030	0.4
Mid	2441	788.7	38	0.030	0.4
High	2482	788.7	38	0.030	0.4



For Base of EUT

Channel	Frequency MHz	Pulse Wide uSec	Occupied time per 1 Sec	Dwell Time Sec	Limit Sec
Low	2401	213	44.64	0.009	0.4
Mid	2441	214	44.64	0.009	0.4
High	2482	213	44.64	0.009	0.4



Plots of Dwell Time

Please refer the following plots.



Handset of EUT, Low Channel





Handset of EUT, Middle Channel





Handset of EUT, High Channel





Base of EUT, Low Channel



Base of EUT, Middle Channel



Base of EUT, High Channel




§15.247(b)(1) - PEAK OUTPUT POWER MEASUREMENT

Standard Applicable

According to §15.247(b) (1), For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Measurement Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to a spectrum analyzer.
3. Add a correction factor to the display.



Equipment Lists

Manufacturer	Description	Model	Serial Number	Cal. Date
Agilent	Analyzer, Spectrum	E4446A	US44300386	11/10/2005

* **Statement of Traceability:** BACL Corp. attests that all calibrations have been performed per the NVLAP requirements, traceable to the NIST.

Measurement Result

Environmental Conditions

Temperature:	15° C
Relative Humidity:	46%
ATM Pressure:	1009 mbar

The testing was performed by Oscar Au on 2005-12-18.

Output Power


For Handset of EUT

Channel	Frequency MHz	Max Peak Output Power		Limit (mW)	Result
		(dBm)	(mW)		
Low	2401	12.11	16.26	1000	Pass
Mid	2441	13.42	21.98	1000	Pass
High	2482	14.42	27.67	1000	Pass


For Base of EUT

Channel	Frequency MHz	Max Peak Output Power		Limit (mW)	Result
		(dBm)	(mW)		
Low	2401	15.12	32.51	1000	Pass
Mid	2441	15.31	33.96	1000	Pass
High	2482	15.36	34.36	1000	Pass


Handset of EUT, Low Channel




Handset of EUT, Mid. Channel




Handset of EUT, High Channel




Base of EUT, Low Channel



Base of EUT, Middle Channel



Base of EUT, High Channel



§15.247 (e)(i) - RF EXPOSURE

According to §15.247(b)(5) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

Limits for Maximum Permissive Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-15000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

MPE Prediction

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Base:

Maximum peak output power at antenna input terminal: 15.36 (dBm)

Maximum peak output power at antenna input terminal: 34.36 (mW)

Prediction distance: 20 (cm)

Predication frequency: 2400 (MHz)

Antenna Gain (typical): 0 (dBi)

Maximum antenna gain: 1 (numeric)

Power density at predication frequency at 20 cm: 0.0068(mW/cm²)

MPE limit for uncontrolled exposure at prediction frequency: 1.0 (mW/cm²)

Test Result

The predicted power density level at 20 cm is 0.006 mW/cm². This is below the uncontrolled exposure limit of 1mW/cm² at 2400 MHz. The EUT is used at least 20cm away from user's body. It is determined as mobile equipment.

TCB Exclusions List For Portable Device

According to §1.1310 and §2.1093 RF exposure is calculated.

Exposure category	<u>low threshold</u>	<u>high threshold</u>
general population	$(60/f_{GHz})$ mW, $d < 2.5$ cm $(120/f_{GHz})$ mW, $d \geq 2.5$ cm	$(900/f_{GHz})$ mW, $d < 20$ cm
occupational	$(375/f_{GHz})$ mW, $d < 2.5$ cm $(900/f_{GHz})$ mW, $d \geq 2.5$ cm	$(2250/f_{GHz})$ mW, $d < 20$ cm

For 2.4Ghz device, Low Threshold = 25 mW, High Threshold = 375mW


Duty cycle = On time / period

$$= 785.4 \mu\text{s} / 210 \text{ mS}$$


$$= 0.00374 \text{ sec}$$

EUT Average output power = Peak power * Duty Cycle = $27.67 * 0.00374 = 0.1035 \text{ mW}$.

Therefore, EUT is not subject to any SAR evaluation.



Plot showing period between each On time



Plot showing On time duration

§15.247(d) - 100 KHZ BANDWIDTH OF BAND EDGES

Standard Applicable

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Equipment Lists

Manufacturer	Description	Model	Serial Number	Cal. Date
Agilent	Analyzer, Spectrum	E4446A	US44300386	11/10/2005

* **Statement of Traceability:** BACL Corp. attests that all calibrations have been performed per the NVLAP requirements, traceable to the NIST.

Measurement Result


Environmental Conditions

Temperature:	15° C
Relative Humidity:	46%
ATM Pressure:	1009 mbar


The testing was performed by Oscar Au on 2005-12-18.

Please refer to following pages for plots of band edge.


Handset of EUT, Low Channel




Handset of EUT, High Channel



Base of EUT, Low Channel



Base of EUT, High Channel



§2.1051 - SPURIOUS EMISSION AT ANTENNA PORT

Standard Applicable

According to §15.209 (f) and §15.33(a), in some cases the emissions from an intentional radiator must be measured to beyond the tenth harmonic of the highest fundamental frequency designed to be emitted by the intentional radiator because of the incorporation of a digital device. If measurements above the tenth harmonic are so required, the radiated emissions above the tenth harmonic shall comply with the general radiated emission limits applicable to the incorporated digital device, as shown in §15.109 and as based on the frequency of the emission being measured, or, except for emissions contained in the restricted frequency bands shown in §15.205, the limit on spurious emissions specified for the intentional radiator, whichever is the higher limit.

Measurement Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on a bench without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set the SA on Max-Hold Mode, and then keep the EUT in transmitting mode. Record all the signals from each channel until each one has been recorded.
4. Set the SA on View mode and then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

Equipment Lists

Manufacturer	Description	Model	Serial Number	Cal. Date
Agilent	Analyzer, Spectrum	E4446A	US44300386	11/10/2005

* **Statement of Traceability:** BACL Corp. attests that all calibrations have been performed per the NVLAP requirements, traceable to the NIST.



Measurement Result

Please refer to following pages for plots of spurious emission.


Environmental Conditions

Temperature:	15° C
Relative Humidity:	45%
ATM Pressure:	1009 mbar


The testing was performed by Oscar Au on 2005-12-18.

*For Handset of EUT**30 MHz-1000MHz, Low Channel**30 MHz- 1000MHz, Middle Channel*


30 MHz- 1000MHz, High Channel




1GHz-3GHz, Low Channel





1GHz-3GHz, Middle Channel




1GHz-3GHz, High Channel




3GHz-5GHz, Low Channel*3GHz-5GHz, Middle Channel*


3GHz-5GHz, High Channel




5GHz-10GHz, Low Channel




5GHz-10GHz, Middle Channel




5GHz-10GHz, High Channel




10 GHz -15GHz, Low Channel




10 GHz -15GHz, Middle Channel




10 GHz -15GHz, High Channel




15 GHz -20GHz, Low Channel




15 GHz -20GHz, Middle Channel




15 GHz -20GHz,High Channel




20 GHz -25GHz,Low Channel



20 GHz -25GHz,Middle Channel




20 GHz -25GHz,High Channel




For Base of EUT


30 MHz- 1000MHz, Low Channel




30 MHz- 1000MHz, Middle Channel




30 MHz- 1000MHz, High Channel




1 GHz- 3GHz, Low Channel




1 GHz- 3GHz, Middle Channel




1 GHz- 3GHz, High Channel





3 GHz- 5GHz, Low Channel




3 GHz- 5GHz, Middle Channel




3 GHz- 5GHz, High Channel*5 GHz- 10 GHz, Low Channel*


5 GHz- 10 GHz, Middle Channel




5 GHz- 10 GHz, High Channel




10 GHz- 15 GHz, Low Channel




10 GHz- 15 GHz, Middle Channel




10 GHz- 15 GHz, High Channel




15 GHz- 20 GHz, Low Channel



15 GHz- 20 GHz, Middle Channel




15 GHz- 20 GHz, High Channel



20 GHz- 25 GHz, Low Channel



20 GHz- 25 GHz, Middle Channel



20 GHz- 25 GHz, High Channel

