


Appendix C. Co-location

1. Results of Radiated Emissions for Co-located


Temperature	24.5°C	Humidity	60%
Test Engineer	David Tseng	Test Mode	Mode 1
Configurations	HMC + Diversity + PIFA		

Horizontal



Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
		Line	Limit	Level	Loss	Factor	Factor	dB	cm		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1 pk	1596.00	54.58	74.00	-19.42	62.85	2.97	25.66	36.90	102	289	HORIZONTAL Peak
2 pp	1598.00	41.58	54.00	-12.42	49.85	2.97	25.66	36.90	102	289	HORIZONTAL Average


Vertical




Freq	Level	Limit		Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
		MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1 pp	1594.00	40.11	54.00	-13.89	48.39	2.97	25.66	36.91	100	298	VERTICAL	Average
2 pk	1594.00	54.11	74.00	-19.89	62.39	2.97	25.66	36.91	100	298	VERTICAL	Peak

Temperature	23°C	Humidity	62%
Test Engineer	David Tseng	Test Mode	Mode 5
Configurations	HMC + Diversity + Dipole		

Horizontal



Freq	Level	Limit		Over Line Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
		MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1 pp	1616.00	41.07	54.00	-12.93	49.27	3.00	25.65	36.85	101	145	HORIZONTAL	Average
2 pk	1616.00	51.88	74.00	-22.12	60.08	3.00	25.65	36.85	102	145	HORIZONTAL	Peak

Vertical


Freq	Level	Limit		Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
		MHz	dBuV/m	Line	dB	dBuV	dB	dB/m	dB	cm	deg	
1 pp	1616.00	40.80	54.00	-13.20	49.00	3.00	25.65	36.85	100	223	VERTICAL	Average
2 pk	1616.00	53.68	74.00	-20.32	61.88	3.00	25.65	36.85	100	223	VERTICAL	Peak