

Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

In accordance with the requirements of SAR Report and Order: FCC 47 CFR Part 2 (2.1093) RSS102 issue 5

SAR TEST REPORT

For

Product Name: 802.11a/b/g/n/ac RTL8821CE Combo module

Brand Name: REALTEK Model No.: RTL8821CE Series Model: N/A

FCCID: TX2-RTL8821CE
IC: 6317A-RTL8821CE
Test Report Number:
C170412R01-B-SF

Issued for

Realtek Semiconductor Corp.

No.2,Innovation Road II, Hsinchu Science Park, Hsinchu 300, Taiwan

Issued by

Compliance Certification Services Inc.

Kun shan Laboratory No.10 Weiye Rd., Innovation park, Eco&Tec,

Development Zone, Kunshan City, Jiangsu, China

TEL: 86-512-57355888 FAX: 86-512-57370818





Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by A2LA or any government agencies. The test results in the report only apply to the tested sample.



Compliance Certification Services (KunShan) Inc. Date of Issue: June 19, 2017 Report No .: C170412R

Report No .: C170412R01-B-SF

Revision History

Revision	REPORT NO.	Date	Page Revised	Contents
Original	C170412R01-B-SF	June 19, 2017	N/A	N/A



Compliance Certification Services (KunShan) Inc. Date of Issue: June 19, 2017 Report No .: C170412R

Report No .: C170412R01-B-SF

TABLE OF CONTENTS

1.	CERTIFICATE OF COMPLIANCE (SAR EVALUATION)4					
2.	EUT DESCRIPTION	5				
	2.1 TARGET RF OUTPUT POWER WITH TEST CHANNEL	7				
	2.2 STATEMENT OF COMPLIANCE	8				
3.	REQUIREMENTS FOR COMPLIANCE TESTING DEFINED BY THE FCC	9				
4.	TEST METHODOLOGY	9				
5.	TEST CONFIGURATION	9				
6.	DOSIMETRIC ASSESSMENT SETUP	10				
	6.1 MEASUREMENT SYSTEM DIAGRAM	11				
	6.2 SYSTEM COMPONENTS	12				
7.	EVALUATION PROCEDURES	15				
8.	MEASUREMENT UNCERTAINTY	19				
9.	EXPOSURE LIMIT	20				
10.	MEASUREMENT RESULTS	21				
	10.1 TEST LIQUIDS CONFIRMATION	21				
	10.2 LIQUID MEASUREMENT RESULTS	22				
	10.3 SYSTEM PERFORMANCE CHECK	23				
	10.4 EUT TUNE-UP PROCEDURES AND TEST MODE	25				
	10.5 SAR TEST CONFIGURATIONS	29				
	10.6 STANDALONE SAR TEST EXCLUSION	30				
	10.7 ANTENNA LOCATION	31				
	10.8 SAR MEASUREMENT RESULTS	32				
	10.9 REPEATED SAR MEASUREMENT	34				
	10.10 SAR MULTI XMITER ASSESSMENT	35				
11.	EQUIPMENT LIST & CALIBRATION STATUS	36				
12.	FACILITIES	37				
13.	REFERENCES	37				
App	pendix A: DUT AND SAR SETUP Photo	38				
App	Appendix B: Plots of Performance Check					
App	pendix C: DASY Calibration Certificate	45				
Apr	pendix D: Plots of SAR Test Result	45				



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

1. CERTIFICATE OF COMPLIANCE (SAR EVALUATION)

Product Name:	802.11a/b/g/n/ac RTL88210	CE Combo module			
Brand name:	REALTEK				
Model Name.:	RTL8821CE				
Series Model:	N/A				
Device Category:	PORTABLE DEVICES				
Exposure Category:	GENERAL POPULATION/UNCONTROLLED EXPOSURE				
Date of Test:	June 16, 2017 & June 18, 2017				
Applicant:	Realtek Semiconductor Corp. No.2,Innovation Road II, Hsinchu Science Park, Hsinchu 300, Taiwan				
Manufacturer:	Realtek Semiconductor Corp. No.2,Innovation Road II, Hsinchu Science Park, Hsinchu 300, Taiwan				
Application Type:	Certification				
AP	PLICABLE STANDARDS A	ND TEST PROCEDURES			
STANDARDS AND	TEST PROCEDURES	TEST RESULT			
IEEE 1 KDB KDB KDB KDB	Part 2 (2.1093) 528-2013 248227 865664 447498 616217 02 issue 5	No non-compliance noted			
Deviation from Applicable Standard					
None					

The device was tested by Compliance Certification Services Inc. in accordance with the measurement

methods and procedures specified in KDB 865664; RSS102 issue 5.The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Approved by:

Jeff fang

Tested by:

Jeff.fang RF Manager

Compliance Certification Services Inc.

Sam.ye Test Engineer

Compliance Certification Services Inc.

Sam. ye.



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

2. EUT DESCRIPTION

Product Name:	802.11a/b/g/n/ac RTL8821CE Combo module						
Brand name:	REALTEK						
Model Name.:	RTL8821C	E					
Series Model:	N/A						
FCC ID:	TX2-RTL88	B21CE					
IC:	6317A-RTL	_8821CE					
Power reduction:	Yes						
DTM Description:	N/A						
Device Category:	Production unit						
Frequency Range:	WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz WLAN 5.3GHz Band: 5260 MHz ~ 5320 MHz WLAN 5.5GHz Band: 5500 MHz ~ 5700 MHz WLAN 5.8GHz Band: 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz						
Modulation Technique:	802.11a/b/g/n HT20/HT40/VHT20/VHT40/VHT80						
Operating Mode:	Maximum continuous output						
	Gain(dBi)						
A . (0 !!! !	Brand		GHz	5GI	1		
Antenna Specification:	0 11 01	TX1	TX2	TX1	TX2		
	South Star INPAQ	3.56 0.87	2.90 1.42	3.56 0.87	2.90 1.42		
	INPAQ	0.87	1.42	0.87	1.42		



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

Tested System Details

Product	Manufacturer	Model No.
Notebook Computer	Lenovo	Lenovo ideapad 120S-11IAP; 81A4

Note:

1. The above EUT information is declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or User's Manual.



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

2.1 TARGET RF OUTPUT POWER WITH TEST CHANNEL

Band / Mode	Target Power(dBm)						
Bariu / Mode	V3.0 + EDR, GFSK	V3.0 + EDR, π/4-DQPSK	V3.0 + EDR, 8-DPSK				
Bluetooth	6	5	5				

Band / Mode	Target Power(dBm)
Bariu / Woue	BLE4.0, GFSK
Bluetooth	5

Band / Mode	Channel	SISO Target Power (dBm)
802.11b	1 -11	18
802.11g	1-11	18
	1	17
802.11n 20MHz	6	17
	11	17
	3	17
802.11n 40MHz	6	17
	9	17
802.11 a U-NII-1	36-48	17
802.11 a U-NII-2A	52-64	17
802.11 a U-NII-2C	100-140	16
802.11 a U-NII-3	149-165	15
802.11 n20 U-NII-1	36-48	16
802.11 n20 U-NII-2A	52-64	16
802.11 n20 U-NII-2C	100-140	15
802.11 n20 U-NII-3	149-165	14
802.11 n40 U-NII-1	38-46	16
802.11 n40 U-NII-2A	54-62	16
802.11 n40 U-NII-2C	102-134	15
802.11 n40 U-NII-3	151-159	14
802.11 ac80 U-NII-1	42	16
802.11 ac80 U-NII-2A	58	16
802.11 ac80 U-NII-2C	106-138	15
802.11 ac80 U-NII-3	155	14



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

2.2 STATEMENT OF COMPLIANCE

The maximum results of Specific Absorption Rate (SAR) found during testing for **802.11a/b/g/n/ac RTL8821CE Combo module**, **RTL8821CE**, are as follows.

	·	Highest SAR Summary				
Equipment Class	Frequency Band	Body 1g SAR (W/kg)	Simultaneous Transmission 1g SAR (W/kg)			
DTS	2.4GHz WLAN	0.752	0.902			
	5.2GHz WLAN	1				
NII	5.3GHz WLAN	1.154	1.322			
INII	5.5GHz WLAN	1.172	1.322			
	5.8GHz WLAN	1.054				
DSSS(BT)	2.4GHz	0.150	1.322			

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and RSS 102 issue5 2015, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013.



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

3. REQUIREMENTS FOR COMPLIANCE TESTING DEFINED BY THE FCC

The order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 W/Kg for an uncontrolled environment and 8.0 W/Kg for an occupational/controlled environment as recommended by the FCC 47 CFR part 2 (2.1093); RSS-102 issue 5: 2015.

4. TEST METHODOLOGY

The Specific Absorption Rate (SAR) testing specification, method and procedure for this device is in accordance with the following standards:

- ∇ FCC 47 CFR Part 2 (2.1093)
- RSS-102 issue 5: 2015

5. TEST CONFIGURATION

During WLAN SAR testing EUT is configured with the WLAN continuous TX tool, and the transmission duty factor was monitored on the spectrum analyzer with zero-span setting For WLAN SAR testing, WLAN engineering test software installed on the EUT can provide continuous transmitting RF signal.

Duty cycle Form

Band	Mode	Duty cycle(100%)
	Bluetooth	100
	802.11b	100
2.4GHz	802.11g	100
	802.11n 20MHz	100
	802.11n 40MHz	100
	802.11a	100
5GHz	802.11 20MHz	100
JUIZ	802.11 40MHz	100
	802.11 ac80	100



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

6. DOSIMETRIC ASSESSMENT SETUP

These measurements were performed with the automated near-field scanning system DASY 5 from SPEAG. The system is based on a high precision robot (working range greater than 0.9 m), which positions the probes with a positional repeatability of better than ± 0.02 mm. Special E- and H-field probes have been developed for measurements close to material discontinuity, the sensors of which are directly loaded with a Schottky diode and connected via highly resistive lines to the data acquisition unit. The SAR measurements were conducted with the E-field PROBE EX3DV4 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe has been calibrated according to the procedure described in [7] with accuracy of better than ±10%. The spherical isotropy was evaluated with the procedure described in [8] and found to be better than ±0.25 dB. The phantom used was the SAM Twin Phantom as described in FCC supplement C, IEE P1528 and CENELEC IEC 62209.

The following table gives the recipes for tissue simulating liquids.

Ingredients	Frequency (MHz)									
(% by weight)	450		835		915		1900		2450	
Tissue Type	Head	Body	Head	Body	Head	Body	Head	Body	Head	Body
Water	38.56	51.16	41.45	52.4	41.05	56.0	54.9	40.4	62.7	73.2
Salt (NaCl)	3.95	1.49	1.45	1.4	1.35	0.76	0.18	0.5	0.5	0.04
Sugar	56.32	46.78	56.0	45.0	56.5	41.76	0.0	58.0	0.0	0.0
HEC	0.98	0.52	1.0	1.0	1.0	1.21	0.0	1.0	0.0	0.0
Bactericide	0.19	0.05	0.1	0.1	0.1	0.27	0.0	0.1	0.0	0.0
Triton X-100	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	36.8	0.0
DGBE	0.0	0.0	0.0	0.0	0.0	0.0	44.92	0.0	0.0	26.7
Dielectric Constant	43.42	58.0	42.54	56.1	42.0	56.8	39.9	54.0	39.8	52.5
Conductivity (S/m)	0.85	0.83	0.91	0.95	1.0	1.07	1.42	1.45	1.88	1.78


Simulating Liquids for 5 GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	78
Mineral oil	11
Emulsifiers	9
Additives and Salt	2



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

6.1 MEASUREMENT SYSTEM DIAGRAM



The DASY5 system for performing compliance tests consists of the following items:

- A standard high precision 6-axis robot (St"aubli RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
- A data acquisition electronics (DAE) which performs the signal amplification, signal
 multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision
 detection, etc. The unit is battery powered with standard or rechargeable batteries. The
 signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion between optical and electrical
 of the signals for the digital communication to the DAE and for the analog signal from the
 optical surface detection. The EOC is connected to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- A computer operating Windows 7.
- DASY5 software.
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom enabling testing left-hand and right-hand usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- Validation dipole kits allowing validating the proper functioning of the system.



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

6.2 SYSTEM COMPONENTS



The DASY5 measurement server is based on a PC/104 CPU board with a 400MHz intel ULV celeron, 128MB chip-disk and 128 MB RAM. The necessary circuits for communication with either the DAE4(or DAE3) electronic box as well as the 16-bit AD-converter system for optical detection and digital I/O interface are contained on the DASY5 I/O-board, which is directly connected to the PC/104 bus of the CPU board.

The measurement server performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation.



The PC-operating system cannot interfere with these time critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with two expansion slots which are reserved for future applications. Please note that the expansion slots do not have a standardized pinout and therefore only the expansion cards provided by SPEAG can be inserted. Expansion cards from any other supplier could seriously damage the measurement server. Calibration: No calibration required.

Data Acquisition Electronics (DAE)



The data acquisition electronics (DAE4) consists of a highly sensitive electrometer grade preamplifier with auto-zeroing, a channel and gainswitching multiplexer, a fast 16 bit AD converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock. The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection. The input impedance of the DAE4 box is 200MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.

EX3DV4 Isotropic E-Field Probe for Dosimetric Measurements



Construction: Symmetrical design with triangular core

Built-in shielding against static charges

PEEK enclosure material (resistant to organic solvents,

e.g., DGBE)

Calibration: Basic Broad Band Calibration in air: 10-3000 MHz.

Conversion Factors (CF) for HSL 900 and HSL 1800 CF-Calibration for other liquids and frequencies upon

request.

Frequency: 10 MHz to > 6 GHz; Linearity: ± 0.2 dB (30 MHz to 3

GHz)

Directivity: ± 0.3 dB in HSL (rotation around probe axis)

± 0.5 dB in HSL (rotation normal to probe axis)

Dynamic Range: 10 μW/g to > 100 mW/g; Linearity: ± 0.2 dB

(noise: typically < 1 μW/g)



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

Dimensions: Overall length: 337 mm (Tip: 9 mm)

Tip diameter: 2.5 mm (Body: 10 mm) Distance from probe tip to dipole centers:

1 mm

Application: High precision dosimetric measurements

in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6

GHz with precision of better 30%.




Interior of probe

SAM Twin Phantom

Construction:

The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528-200X, CENELEC 50360 and IEC 62209. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points with the robot.



Dimensions: Height: 850mm; Length: 1000mm; Width:

750mm



Description Construction:

Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with the latest draft of the standard IEC 62209 Part II and all known tissue simulating liquids. ELI4 has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is supported by software version DASY4/DASY5.5 and higher and is compatible with all SPEAG dosimetric probes and dipoles

Shell Thickness: $2.0 \pm 0.2 \text{ mm (sagging: } <1\%)$

Filling Volume: Approx. 25 liters

Dimensions: Major ellipse axis: 600 mm

Minor axis: 400 mm 500mm





Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

Device Holder for SAM Twin Phantom

Construction: In combination with the Twin SAM Phantom, the

Mounting Device (made from POM) enables the rotation of the mounted transmitter in spherical coordinates, whereby the rotation point is the ear opening. The devices can be easily and accurately positioned according to IEC, IEEE, CENELEC, FCC or other specifications. The device holder can be locked at different phantom locations (left head, right head, and flat phantom).



System Validation Kits for SAM Twin Phantom

Construction: Symmetrical dipole with I/4 balun Enables

measurement of feedpoint impedance with NWA Matched for use near flat phantoms filled with brain simulating solutions Includes distance

holder and tripod adaptor.

Frequency: 900,1800,2450,5800 MHz

ReTune loss: > 20 dB at specified validation position **Power capability:** > 100 W (f < 1GHz); > 40 W (f > 1GHz)

Dimensions:

D835V2: dipole length: 161 mm; overall height: 340 mm D1800V2: dipole length: 72.5 mm; overall height: 300 mm D1900V2: dipole length: 67.7 mm; overall height: 300 mm D2450V2: dipole length: 51.5 mm; overall height: 290 mm D5GHzV2: dipole length: 20.6 mm; overall height: 300mm



System Validation Kits for ELI4 phantom

Construction: Symmetrical dipole with I/4 balun Enables

measurement of feedpoint impedance with NWA Matched for use near flat phantoms filled with brain simulating solutions Includes distance

holder and tripod adaptor.

Frequency: 900, 1800, 2450, 5800 MHz

ReTune loss: > 20 dB at specified validation position **Power capability:** > 100 W (f < 1GHz); > 40 W (f > 1GHz)

Dimensions:

D835V2: dipole length: 161 mm; overall height: 340 mm D1800V2: dipole length: 72.5 mm; overall height: 300 mm D1900V2: dipole length: 67.7 mm; overall height: 300 mm D2450V2: dipole length: 51.5 mm; overall height: 290 mm D5GHzV2: dipole length: 20.6 mm; overall height: 300 mm





Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

7. EVALUATION PROCEDURES

DATA EVALUATION

The DASY 5 post processing software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

> Probe parameters: - Sensitivity Normi, aio, ai1, ai2

> > - Conversion factor ConvF_i - Diode compression point dcpi

Device parameters: - Frequency

- Crest factor cf

Media parameters: - Conductivity σ

- Density

These parameters must be set correctly in the software. They can be found in the component documents or be imported into the software from the configuration files issued for the DASY 5 components. In the direct measuring mode of the multi-meter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

with V_i = Compensated signal of channel i(i = x, y, z)

U_i = Input signal of channel i (i = x, y, z)

cf = Crest factor of exciting field (DASY 5 parameter) dcp_i = Diode compression point (DASY 5 parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

E-field probes:

$$E_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}$$

H-field probes:

$$H_i = \sqrt{Vi} \cdot \frac{a_{i10} + a_{i11}f + a_{i12}f^2}{f}$$

= Compensated signal of channel i(i = x, y, z) with

 $Norm_i$ = Sensor sensitivity of channel i (i = x, y, z)

 $\mu V/(V/m)^2$ for E0field Probes

ConvF = Sensitivity enhancement in solution

= Sensor sensitivity factors for H-field probes

f = Carrier frequency (GHz)

= Electric field strength of channel i in V/m Εi

= Magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

with SAR = local specific absorption rate in mW/g

 E_{tot} = total field strength in V/m

 σ = conductivity in [mho/m] or [Siemens/m]

 ρ = equivalent tissue density in g/cm³

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid.

The power flow density is calculated assuming the excitation field as a free space field.

$$P_{pwe} = \frac{E_{tot}^2}{3770}$$
 or $P_{pwe} = H_{tot}^2 \cdot 37.7$

with P_{pwe} = Equivalent power density of a plane wave in mW/cm²

 E_{tot} = total electric field strength in V/m

 H_{tot} = total magnetic field strength in A/m



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

SAR EVALUATION PROCEDURES

The procedure for assessing the peak spatial-average SAR value consists of the following steps:

Power Reference Measurement

The reference and drift jobs are useful jobs for monitoring the power drift of the device under test in the batch process. Both jobs measure the field at a specified reference position, at a selectable distance from the phantom surface. The reference position can be either the selected section's grid reference point or a user point in this section. The reference job projects the selected point onto the phantom surface, orients the probe perpendicularly to the surface, and approaches the surface using the selected detection method.

Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a finer measurement around the hot spot. The sophisticated interpolation routines implemented in DASY 5 software can find the maximum locations even in relatively coarse grids. The scan area is defined by an editable grid. This grid is anchored at the grid reference point of the selected section in the phantom. When the area scan's property sheet is brought-up, grid was at to 15 mm by 15 mm and can be edited by a user.

Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The default zoom scan measures $5 \times 5 \times 7$ points within a cube whose base faces are centered around the maximum found in a preceding area scan job within the same procedure. If the preceding Area Scan job indicates more then one maximum, the number of Zoom Scans has to be enlarged accordingly (The default number inserted is 1).

Power Drift measurement

The drift job measures the field at the same location as the most recent reference job within the same procedure, and with the same settings. The drift measurement gives the field difference in dB from the reading conducted within the last reference measurement. Several drift measurements are possible for one reference measurement. This allows a user to monitor the power drift of the device under test within a batch process. In the properties of the Drift job, the user can specify a limit for the drift and have DASY 5 software stop the measurements if this limit is exceeded.

Z-Scan

The Z Scan job measures points along a vertical straight line. The line runs along the Z-axis of a one-dimensional grid. A user can anchor the grid to the current probe location. As with any other grids, the local Z-axis of the anchor location establishes the Z-axis of the grid.



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

SPATIAL PEAK SAR EVALUATION

The procedure for spatial peak SAR evaluation has been implemented according to the IEEE1529 standard. It can be conducted for 1 g and 10 g.

The DASY 5 system allows evaluations that combine measured data and robot positions, such as:

- · maximum search
- extrapolation
- · boundary correction
- peak search for averaged SAR

During a maximum search, global and local maximum searches are automatically performed in 2-D after each Area Scan measurement with at least 6 measurement points. It is based on the evaluation of the local SAR gradient calculated by the Quadratic Shepard's method. The algorithm will find the global maximum and all local maxima within -2 dB of the global maxima for all SAR distributions.

Extrapolation

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. Several measurements at different distances are necessary for the extrapolation.

Extrapolation routines require at least 10 measurement points in 3-D space. They are used in the Cube Scan to obtain SAR values between the lowest measurement points and the inner phantom surface. The routine uses the modified Quadratic Shepard's method for extrapolation. For a grid using 5x5x7 measurement points with 5mm resolution amounting to 343 measurement points, the uncertainty of the extrapolation routines is less than 1% for 1 g and 10 g cubes.

Boundary effect

For measurements in the immediate vicinity of a phantom surface, the field coupling effects between the probe and the boundary influence the probe characteristics. Boundary effect errors of different dosimetric probe types have been analyzed by measurements and using a numerical probe model. As expected, both methods showed an enhanced sensitivity in the immediate vicinity of the boundary. The effect strongly depends on the probe dimensions and disappears with increasing distance from the boundary. The sensitivity can be approximately given as:

$$S \approx S_o + S_b exp(-\frac{z}{a})cos(\pi \frac{z}{\lambda})$$

Since the decay of the boundary effect dominates for small probes ($a << \lambda$), the cos-term can be omitted. Factors Sb (parameter Alpha in the DASY 5 software) and a (parameter Delta in the DASY 5 software) are assessed during probe calibration and used for numerical compensation of the boundary effect. Several simulations and measurements have confirmed that the compensation is valid for different field and boundary configurations.

This simple compensation procedure can largely reduce the probe uncertainty near boundaries. It works well as long as:

- the boundary curvature is small
- the probe axis is angled less than 30 to the boundary normal
- the distance between probe and boundary is larger than 25% of the probe diameter
- the probe is symmetric (all sensors have the same offset from the probe tip)

Since all of these requirements are fulfilled in a DASY 5 system, the correction of the probe boundary effect in the vicinity of the phantom surface is performed in a fully automated manner via the measurement data extraction during post processing.



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

8. MEASUREMENT UNCERTAINTY

Per KDB865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04,when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. The equivalent ratio (1.5/1.6) is applied to extremity and occupational exposure conditions.



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

9. EXPOSURE LIMIT

(A). Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

(B). Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

Note: Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

<u>Population/Uncontrolled Environments</u> are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

<u>Occupational/Controlled Environments</u> are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

NOTE
GENERAL POPULATION/UNCONTROLLED EXPOSURE
PARTIAL BODY LIMIT
1.6 W/kg



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

10. MEASUREMENT RESULTS

10.1 TEST LIQUIDS CONFIRMATION

SIMULATED TISSUE LIQUID PARAMETER CONFIRMATION

The dielectric parameters were checked prior to assessment using the SPEAG DAK3.5 dielectric probe kit. The dielectric parameters measured are reported in each correspondent section.

IEEE SCC-34/SC-2 P1528 RECOMMENDED TISSUE DIELECTRIC PARAMETERS

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in P1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations and extrapolated according to the head parameters specified in P1528

Target Frequency	He		Body		
(MHz)	$\epsilon_{\rm r}$	σ (S/m)	ϵ_{r}	σ (S/m)	
150	52.3	0.76	61.9	0.80	
300	45.3	0.87	58.2	0.92	
450	43.5	0.87	56.7	0.94	
835	41.5	0.90	55.2	0.97	
900	41.5	0.97	55.0	1.05	
915	41.5	0.98	55.0	1.06	
1450	40.5	1.20	54.0	1.30	
1610	40.3	1.29	53.8	1.40	
1800-2000	40.0	1.40	53.3	1.52	
2450	39.2	1.80	52.7	1.95	
3000	38.5	2.40	52.0	2.73	
5800	35.3	5.27	48.2	6.00	

 $(\varepsilon_r = \text{relative permittivity}, \sigma = \text{conductivity and } \rho = 1000 \text{ kg/m}^3)$



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

10.2 LIQUID MEASUREMENT RESULTS

The following table show the measuring results for simulating liquid:

Liquid Type	Liquid Temp. (°C)	Parameters	Target	Measured	Deviation (%)	Limited (%)	Measured Date	
Body2402	21.5	Permitivity(ε)	52.76	51.74	-1.94	± 5	2017-6-16	
B00y2402	21.5	Conductivity(σ)	1.89	1.92	1.79	± 5	2017-0-10	
Body2412	12 21.5	Permitivity(ε)	52.75	51.74	-1.91	± 5	2017-6-16	
D00y2412	21.5	Conductivity(σ)	1.90	1.93	1.48	± 5	2017-0-10	
Body2437	21.5	Permitivity(ε)	52.72	51.97	-1.41	± 5	2017-6-16	
Dody2401	21.0	Conductivity(σ)	1.93	1.95	0.68	± 5	2017-0-10	
Body2441	21.5	Permitivity(ε)	52.71	51.98	-1.39	± 5	2017-6-16	
body2441	21.5	Conductivity(σ)	1.94	1.95	0.35	± 5	2017-0-10	
Body2462	21.5	Permitivity(ε)	52.68	51.80	-1.68	± 5	2017-6-16	
B00y2402	21.5	Conductivity(σ)	1.97	1.96	-0.56	± 5	2017-0-10	
Body2480	21.5	Permitivity(ε)	52.66	51.50	-2.20	± 5	2017-6-16	
B00y2400	21.5	Conductivity(σ)	1.99	1.99	-0.16	± 5		
Body5260	21.5	Permitivity(ε)	48.95	47.89	-2.17	± 5	2017-6-18	
B00y5200	21.5	Conductivity(σ)	5.42	5.31	-2.12	± 5	2017-0-10	
Body5280	21.5	Permitivity(ε)	48.92	48.00	-1.88	± 5	2017-6-18	
B00y3200	21.5	Conductivity(σ)	5.44	5.38	-1.08	± 5	2017-0-18	
Body5320	21.5	Permitivity(ε)	48.87	48.02	-1.73	± 5	2017-6-18	
B00y3320	21.5	Conductivity(σ)	5.49	5.44	-0.94	± 5	2017-0-10	
Body5500	21.5	Permitivity(ε)	48.62	47.84	-1.60	± 5	2017-6-18	
Бойуззоо	21.5	Conductivity(σ)	5.68	5.53	-2.66	± 5	2017-0-18	
Body5580	21.5	Permitivity(ε)	48.51	47.58	-1.91	± 5	2017-6-18	
Бойуээво	21.5	Conductivity(σ)	5.77	5.85	1.35	± 5	2017-0-18	
Body5640	21.5	Permitivity(ε)	48.42	47.31	-2.31	± 5	2017-6-18	
B00y3040	21.5	Conductivity(σ)	5.83	5.69	-2.38	± 5	2017-0-18	
Body5745	21.5	Permitivity(ε)	48.28	47.04	-2.57	± 5	2017-6-18	
Бойу5745	21.5	Conductivity(σ)	5.94	5.78	-2.70	± 5	2017-0-18	
Body5785	21.5	Permitivity(ε)	48.22	47.19	-2.14	± 5	2017-6-18	
1000y3703	21.0	Conductivity(σ)	5.98	6.09	1.78	± 5	2017-0-10	
Body5825	21.5	Permitivity(ε)	47.99	47.72	-0.56	± 5	2017-6-18	
D00y3023	21.0	Conductivity(σ)	6.03	6.03	0.10	± 5	2017-0-10	




Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF


10.3 SYSTEM PERFORMANCE CHECK

The system performance check is performed prior to any usage of the system in order to guarantee reproducible results. The system performance check verifies that the system operates within its specifications of $\pm 10\%$. The system performance check results are tabulated below. And also the corresponding SAR plot is attached as well in the SAR plots files.

SYSTEM PERFORMANCE CHECK MEASUREMENT CONDITIONS

- The measurements were performed in the flat section of the SAM twin phantom filled with head and body simulating liquid of the following parameters.
- The DASY5 system withan E-fileld probe EX3DV4 SN: 3798 was used for the measurements.
- The dipole was mounted on the small tripod so that the dipole feed point was positioned below
 the center marking of the flat phantom section and the dipole was oriented parallel to the body
 axis (the long side of the phantom). The standard measuring distance was
 15 mm (below 1 GHz) and 10 mm (above 1 GHz) from dipole center to the simulating liquid
 surface.
- The coarse grid with a grid spacing of 10mm was aligned with the dipole.
- Special 7x7x7 fine cube was chosen for cube integration (dx= 5 mm, dy= 5 mm, dz= 5 mm).
- Distance between probe sensors and phantom surface was set to 2 mm.
- The dipole less than 3G input power was 250mW±3%.
- The dipole above than 3G input power was 100mW±3%.
- The results are normalized to 1 W input power.





- Note: For SAR testing, less than 3G the liquid depth is 15cm shown above
- Note: For SAR testing, above than 3G the liquid depth is 10cm shown above



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

SYSTEM PERFORMANCE CHECK RESULTS

Liquid Type	Ambient Temp. (° C)	Liquid Temp. (°C)	Input Power (W)	Measured SAR _{1g} (W/Kg)	1W Target SAR _{1g} (W/Kg)	Normanzea	Deviatio n (%)	Limited (%)	Date
Body2450	22	21.5	0.25	13.00	51.50	52.00	0.97	± 10	2017-6-16
Body5200	22	21.5	0.1	7.66	74.50	76.6	2.82	± 10	2017-6-18
Body5300	22	21.5	0.1	7.72	77.20	77.2	0.00	± 10	2017-6-18
Body5500	22	21.5	0.1	7.82	81.10	78.2	-3.58	± 10	2017-6-18
Body5600	22	21.5	0.1	7.89	79.80	78.9	-1.13	± 10	2017-6-18
Body5800	22	21.5	0.1	7.59	77.20	75.9	-1.68	± 10	2017-6-18



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

10.4 EUT TUNE-UP PROCEDURES AND TEST MODE

Conducted output power(dBm):

General Note:

- 1 Power must be measured at each transmit antenna port according to the DSSS and OFDM transmission configurations in each standalone and aggregated frequency band.
- 2 Power measurement is required for the transmission mode configuration with the highest maximum output power specified for production units.
 - 1) When the same highest maximum output power specification applies to multiple transmission modes, the largest channel bandwidth configuration with the lowest order modulation and lowest data rate is measured.
 - 2) When the same highest maximum output power is specified for multiple largest channel bandwidth configurations with the same lowest order modulation or lowest order modulation and lowest data rate, power measurement is required for all equivalent 802.11 configurations with the same maximum output power.
- 3 For each transmission mode configuration, power must be measured for the highest and lowest channels; and at the mid-band channel(s) when there are at least 3 channels. For configurations with multiple mid-band channels, due to an even number of channels, both channels should be measured.
- 4 Apply the default power measurement procedures to measure maximum output power for each standalone and aggregated frequency band.
 - a) When band gap channels between U-NII-2C band and U-NII-3 band or §15.247 5.8 GHz band are supported and the bands are aggregated for SAR testing according to KDB 248227D01 sections 2.3 and 3.3, apply the following to determine high, middle and low channels for power measurement and SAR test reduction.
 - i) channels in U-NII-2C band below 5.65 GHz are considered as one band
 - ii) channels above 5.65 GHz, together with channels in 5.8 GHz U-NII-3 or §15.247 band, are considered as a separate band
 - b) The maximum output power of band gap channels is limited to the lowest maximum output power certified for the adjacent bands regardless of whether band aggregation is applied for SAR testing.
 - c) The measured maximum output power results are used to reduce the number of channels that need testing.

WLAN 2.4G Chain0

Mode	Channel	Frequency (MHZ)	Chain0 Target power(dBm)	Turn up tolerance (dBm)	Maximum Turn up power (dBm)	Average power (dBm)
	1	2412	17	±1	18	17.81
802.11 b	6	2437	17	±1	18	17.92
	11	2462	17	±1	18	17.72
	1	2412	17	±1	18	
802.11 g	6	2437	17	±1	18	
	11	2462	17	±1	18	
000.44	1	2412	16	±1	17	NIst
802.11 n 20MHz	6	2437	16	±1	17	Not required
2011112	11	2462	16	±1	17	roquirou
802.11 n 40MHz	3	2422	16	±1	17	
	6	2437	16	±1	17	
	9	2452	16	±1	17	



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

WLAN Conducted output power(dBm):

U-NII-1 Chain0

Mode	Channel	Frequency (MHZ)	Chain0 Target power(dBm)	Turn up tolerance (dBm)	Maximum Turn up power (dBm)	Average Power (dBm)
	36	5180	16	±1	17	16.96
802.11 a	40	5200	16	±1	17	16.87
002.11 a	44	5220	16	±1	17	16.83
	48	5240	16	±1	17	16.66
	36	5180	15	±1	16	
802.11 n 20MHz	40	5200	15	±1	16	
OUZ. I I II ZUIVII IZ	44	5220	15	±1	16	
	48	5240	15	±1	16	Not required
802.11 n 40MHz	38	5180	15	±1	16	
	46	5230	15	±1	16	
802.11 ac80	42	5210	15	±1	16	

U-NII-2A Chain0

Mode	Channel	Frequency (MHZ)	Chain0 Target power(dBm)	Turn up tolerance (dBm)	Maximum Turn up power (dBm)	Average Power (dBm)
	52	5260	16	±1	17	16.69
802.11 a	56	5280	16	±1	17	17.00
002.11 a	60	5300	16	±1	17	16.92
	64	5320	16	±1	17	16.83
	52	5260	15	±1	16	
802.11 n 20MHz	56	5280	15	±1	16	
002.11 11 20W112	60	5300	15	±1	16	
	64	5320	15	±1	16	Not required
802.11 n 40MHz	54	5270	15	±1	16	
	62	5310	15	±1	16	
802.11 ac80	58	5290	15	±1	16	



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

U-NII-2C Chain0

Mode	Channel	Frequency (MHZ)	Chain0 Target power(dBm)	Turn up tolerance (dBm)	Maximum Turn up power (dBm)	Average Power (dBm)
	100	5500	15	±1	16	15.85
802.11 a	112	5560	15	±1	16	15.63
002.11 a	116	5580	15	±1	16	15.96
	128	5640	15	±1	16	15.84
	100	5500	14	±1	15	
802.11 n 20MHz	112	5560	14	±1	15	
602.11 II ZUWINZ	116	5580	14	±1	15	
	128	5640	14	±1	15	
	102	5510	14	±1	15	
	110	5550	14	±1	15	Not required
802.11 n 40MHz	118	5590	14	±1	15	Not required
	126	5630	14	±1	15	
	134	5670	14	±1	15	
	106	5530	14	±1	15	
802.11 ac80	122	5610	14	±1	15	
	138	5690	14	±1	15	

U-NII-3 Chain0

Mode	Channel	Frequency	Chain0 Target power(dBm)	Turn up tolerance (dBm)	Maximum Turn up power (dBm)	Average power (dBm)
	149	5745	14	±1	15	14.95
802.11 a	157	5785	14	±1	15	14.94
	165	5825	14	±1	15	14.94
000.44	149	5745	13	±1	14	
802.11 n 20MHz	157	5785	13	±1	14	
2011112	165	5825	13	±1	14	Not required
802.11 n	151	5755	13	±1	14	Not required
40MHz	159	5795	13	±1	14	
802.11 ac80	155	5755	13	±1	14	



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

Bluetooth

Band	Mode	Channel	Frequency	Averaged Power (dBm)
	Divista eth DD	0	2402	5.57
	Bluetooth BR (GFSK)	39	2441	5.68
	(Of Oit)	78	2480	5.49
	Divista eth EDD0	0	2402	
	Bluetooth EDR2 (π/4-DQPSK)	39	2441	
2.4 GHz		78	2480	
2.4 GHZ	Divista eth EDD0	0	2402	
	Bluetooth EDR3 (8-DPSK)	39	2441	Not required
	(0-01 010)	78	2480	
		0	2402	
	Bluetooth LE	19	2440	
		39	2480	



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

10.5 SAR TEST CONFIGURATIONS

According to KDB 616217 D04, SAR testing for laptop PC is required for bottom surface. This EUT was tested in the base of EUT directly against the flat phantom.



Fig Illustration for Laptop Setup



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

10.6 STANDALONE SAR TEST EXCLUSION

According to KDB447498 D01:The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance,

mm)] $\cdot [\sqrt{f_{(GHz)}}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,24 where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation25
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below
- If the test separation distance (antenna-user) is < 5mm, 5mm is used for excluded SAR calculation

	Wireless Interface	Bluetooth		
Tı	6			
Tun	Tune-up Maximum rated power (mW)			
	Antenna to user (mm)	5		
Body	Frequency(GHz)	2441		
	SAR exclusion threshold	1.244		

Per KDB 447498 D01 exclusion thresholds is 1.244 < 3, Bluetooth RF exposure evaluation is not required.

According to RSS102-2015:

SAR evaluation for this device was performed with a separation distance of 5 mm. Observing the SAR evaluation exemption limit table (Table 1, see below) found in § 2.5.1 of RSS102:2015 , it was determined that the SAR exemption limit for this device is 4 mW for 2.4GHz transmission. No Wi-Fi mode qualified for test exemption as all power levels were above the stated thresholds. On the contrary, Bluetooth, with a frequency of 2441 MHz and a maximum output power of 9.036 mW (9.56 dBm, tune-up tolerance accounted for), is Higher than the exemption threshold and therefore exempt from SAR evaluation for either the intended user or bystanders. So Bluetooth RF exposure evaluation is required

Table 1: SAR evaluation – Exemption limits for routine evaluation based on frequency and separation distance


Frequency		Exemption Limits (mW)									
(MHz)	At separation	At separation	At separation	At separation	At separation						
	distance of	distance of	distance of	distance of	distance of						
	≤5 mm	10 mm	15 mm	20 mm	25 mm						
≤300	71 mW	101 mW	132 mW	162 mW	193 mW						
450	52 mW	70 mW	88 mW	106 mW	123 mW						
835	17 mW	30 mW	42 mW	55 mW	67 mW						
1900	7 mW	10 mW	18 mW	34 mW	60 mW						
2450	4 mW	7 mW	15 mW	30 mW	52 mW						
3500	2 mW	6 mW	16 mW	32 mW	55 mW						
5800	1 mW	6 mW	15 mW	27 mW	41 mW						



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

10.7 ANTENNA LOCATION

<Notebook>



Note: The distance between EUT bottom surface and Antenna position is 6 mm

Device dimensions (H x W): 290 x 200 mm

Antennas	Wireless Interface
Bluetooth & WLAN Antenna	WLAN 2.4GHz WLAN 5.2GHz WLAN 5.3GHz WLAN 5.5GHz WLAN 5.8GHz Bluetooth
Main Antenna	WLAN TX/RX
Aux Antenna	WLAN RX+ Bluetooth

Test Mode

IEEE 802.11 Data transmission mode(802.11a;b;GFSK)



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

10.8 SAR MEASUREMENT RESULTS

Note:

- 1. Per KDB 447498 D01, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. For WLAN: Reported SAR(W/kg)= Measured SAR(W/kg)* Duty Cycle scaling factor * Tune-up scaling factor
- 2. Per KDB 447498 D01, for each exposure position, if the highest output channel reported SAR ≤0.8W/kg, other channels SAR testing is not necessary.
- 3. Per KDB 447498 D01, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - · ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
 - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
 - · ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz

SAR Results for Test Records

Band	Mode	Configure	Test Position	Dist. (mm)	Freq. (MHZ)	Chain	measured Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	Power Drift (dB)	Duty Cycle Factor	SAR1g (mW/g)	Scaled SAR1g (mW/g)
WLAN 2.4Ghz	802.11b	NB	Bottom	0	2412	0	17.81	18	1.045	-0.14	1	0.603	0.630
WLAN 2.4Ghz	802.11b	NB	Bottom	0	2437	0	17.92	18	1.019	-0.08	1	0.627	0.639
WLAN 2.4Ghz	802.11b	NB	Bottom	0	2462	0	17.72	18	1.067	-0.06	1	0.705	0.752

Remark: SAR is not required for the following 2.4 GHz OFDM conditions.

- 1) When KDB Publication 447498 SAR test exclusion applies to the OFDM configuration.
- 2) When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

The highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg. So 2.4 GHz OFDM mode is not required.

Band	Mode	Configure	Test Position	Dist. (mm)	Freq. (MHZ)	Chain	measured Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	Power Drift (dB)	Duty Cycle Factor	SAR1g (mW/g)	Scaled SAR1g (mW/g)
	1	NB	Bottom	0	2402	0	5.57	6	1.104	0.02	1	0.104	0.115
2.4Ghz	BT GFSK	NB	Bottom	0	2441	0	5.68	6	1.076	0.16	1	0.120	0.129
	r .	NB	Bottom	0	2480	0	5.49	6	1.125	0.05	1	0.133	0.150



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

						,		,				,	
Band U-NII-2A	Mode	Configure	Test Position	Dist. (mm)	Freq. (MHZ)	Chain	measured Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	Power Drift (dB)	Duty Cycle Factor	SAR1g (mW/g)	Scaled SAR1g (mW/g)
U-NII-2A	802.11a	NB	Bottom	0	5260	0	16.69	17	1.074	0.02	1	0.794	0.853
U-NII-2A	802.11a	NB	Bottom	0	5280	0	17.00	17	1.000	0.07	1	0.986	0.986
U-NII-2A	802.11a	NB	Bottom	0	5320	0	16.83	17	1.040	0.13	1	1.11	1.154
U-NII-2C	802.11a	NB	Bottom	0	5500	0	15.85	16	1.035	0.09	1	1.10	1.139
U-NII-2C	802.11a	NB	Bottom	0	5580	0	15.96	16	1.009	0.03	1	1.09	1.100
U-NII-2C	802.11a	NB	Bottom	0	5640	0	15.84	16	1.038	0.03	1	1.13	1.172
U-NII-3 U-NII-3 U-NII-3	802.11a	NB	Bottom	0	5745	0	14.95	15	1.012	0.04	1	0.834	0.844
U-NII-3	802.11a	NB	Bottom	0	5785	0	14.94	15	1.014	80.0	1	0.885	0.897
U-NII-3	802.11a	NB	Bottom	0	5825	0	14.94	15	1.014	0.08	1	1.04	1.054

Remark: For devices that operate in both U-NII-1 and U-NII-2A bands using the same transmitter and antenna(s), SAR test reduction is determined according to the following

- 1) When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, each band is tested independently for SAR.
- 2) When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for the band with lower maximum output power in that test configuration; otherwise, each band is tested independently for SAR

The highest reported SAR for U-NII is adjusted by the ratio of U-NII-1 to U-NII-2A specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg. So U-NII-1 mode is not required.

Repeated SAR Test Records

Band	Mode	Configure	Test Position	Dist. (mm)	Freq. (MHZ)	Chain	measured Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	Power Drift (dB)	Duty Cycle Factor	SAR1g (mW/g)	Scaled SAR1g (mW/g)
U-NII-2A	802.11a	NB	Bottom	0	5320	0	16.83	17	1.040	0.01	1	1.08	1.123
U-NII-2C	802.11a	NB	Bottom	0	5640	0	15.84	16	1.038	0.05	1	1.10	1.141
U-NII-3	802.11a	NB	Bottom	0	5825	0	14.94	15	1.014	-0.07	1	1.02	1.034



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

10.9 REPEATED SAR MEASUREMENT

Note:

- 1. Per KDB 865664 D01v01r04,for each frequency band, repeated SAR measurement is required only when the measured SAR is \geq 0.8W/Kg
- 2. Per KDB 865664 D01v01r04,if the ratio of largest to smallest SAR for the original and first repeated measurement is ≤1.2 and the measured SAR <1.45W/Kg,only one repeated measurement is required.
- 3. The ratio is the difference in percentage between original and repeated measured SAR.

Band	Mode	Configure	Test Position	Freq (MHZ)	Original Measured SAR1g (mW/g)	1st Repeated SAR1g (mW/g)	Ratio	Original Measured SAR1g (mW/g)	2nd Repeated SAR1g (mW/g)	Ratio
U-NII-2A	802.11a	NB	Bottom	5320	1.10	1.08	1.019			
U-NII-2C	802.11a	NB	Bottom	5640	1.13	1.10	1.027		-	
U-NII-3	802.11a	NB	Bottom	5825	1.04	1.02	1.020		-	



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

10.10 SAR MULTI XMITER ASSESSMENT

	Position	Applicable Combination
Simultaneous Transmission	Body	WLAN Main Antenna + BT Aux Antenna

Note:

- 1. Main Antenna 2.4GHz WLAN and 5GHz share the same antenna, and cannot transmit simultaneously. The DUT does not support chain0 and chain1 WLAN simultaneous transmission
- 2. The reported SAR summation is calculated based on the same configuration and test position.
- 3. Per KDB 447498 D01v06, simultaneous transmission SAR is compliant if,
 - 1) Scalar SAR summation < 1.6W/kg.
 - 2) SPLSR = (SAR1 + SAR2)1.5 / (min. separation distance, mm), and the peak separation distance is determined from the square root of [(x1-x2)2 + (y1-y2)2 + (z1-z2)2], where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan
 - If SPLSR ≤ 0.04, simultaneously transmission SAR is compliant
 - 3) Simultaneously transmission SAR measurement, and the reported multi-band SAR < 1.6W/kg

SUM ∑SA	_			
Position	Distance	Stand alone S	SUM SAR(1g)[W/kg]	
	[mm]	Main Antenna WLAN 2.4G	Main ant WLAN 2.4+ Aux ant BT	
Bottom	0	0.752	0.150	0.902

SUM ∑SAF	_			
Position	Distance	Stand alone S	SUM SAR(1g)[W/kg]	
	[mm]	Main Antenna WLAN 5.3G	Aux Antenna Bluetooth	Main ant WLAN 5.3+ Aux ant BT
Bottom	0	1.154	0.150	1.304

SUM ∑SAI			
Position	Distance	Stand alone S	SUM SAR(1g)[W/kg]
	[mm]	Main Antenna WLAN 5.5G	Main ant WLAN 5.5+ Aux ant BT
Bottom	0	1.172	1.322

SUM ∑SA	_			
Position	Distance	Stand alone S	SUM SAR(1g)[W/kg]	
	[mm]	Main Antenna WLAN 5.8G	Main ant WLAN 5.8+ Aux ant BT	
Bottom	0	1.054	0.150	1.204



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

11. EQUIPMENT LIST & CALIBRATION STATUS

Name of Equipment	Manufacturer	Type/Model	Serial Number	Last Calibration	Calibration Due
PC	HP	Core(rm)3.16G	CZCO48171H	N/A	N/A
Signal Generator	Agilent	E8257C	US37101915	11/01/2016	10/31/2017
S-Parameter Network Analyzer	Agilent	E5071B	MY42301382	02/28/2017	02/27/2018
Power meter	Anritsu	ML2495A	1445010	02/28/2017	02/27/2018
Power sensor	Anritsu	MA2411B	1339220	02/28/2017	02/27/2018
E-field PROBE	SPEAG	EX3DV4	3798	07/27/2016	07/26/2017
DAE	SPEAG	DEA4	1245	07/26/2016	07/25/2017
DIPOLE 2450MHZ ANTENNA	SPEAG	D2450V2	817	05/31/2016	05/28/2019
DIPOLE 5GHZ ANTENNA	SPEAG	D5GHzV2	1095	05/25/2016	05/22/2019
DUMMY PROBE	SPEAG	DP_2	SPDP2001AA	N/A	N/A
SAM PHANTOM (ELI4 v4.0)	SPEAG	QDOVA001BB	1102	N/A	N/A
Twin SAM Phantom	SPEAG	QD000P40CD	1609	N/A	N/A
ROBOT	SPEAG	TX60	F10/5E6AA1/A101	N/A	N/A
ROBOT KRC	SPEAG	CS8C	F10/5E6AA1/C101	N/A	N/A
LIQUID CALIBRATION KIT	ANTENNESSA	41/05 OCP9	00425167	N/A	N/A



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

12. FACILITIES

All measurement facilities used to collect the measurement data are located at

No.10, Weiye Rd., Innovation Park, Eco & Tec. Development Part, Kunshan City, Jiangsu Province, China.

13. REFERENCES

- [1] Federal Communications Commission, \Report and order: Guidelines for evaluating the environ-mental effects of radiofrequency radiation", Tech. Rep. FCC 96-326, FCC, Washington, D.C. 20554, 1996.
- [2] David L. Means Kwok Chan, Robert F. Cleveland, \Evaluating compliance with FCC guidelines for human exposure to radiofrequency electromagnetic fields", Tech. Rep., Federal Communication Commission, O_ce of Engineering & Technology, Washington, DC, 1997.
- [3] Thomas Schmid, Oliver Egger, and Niels Kuster, \Automated E-_eld scanning system for dosimetric assessments", IEEE Transactions on Microwave Theory and Techniques, vol. 44, pp. 105{113, Jan. 1996.
- [4] Niels Kuster, Ralph K.astle, and Thomas Schmid, \Dosimetric evaluation of mobile communications equipment with known precision", IEICE Transactions on Communications, vol. E80-B, no. 5, pp. 645{652, May 1997.
- [5] CENELEC, \Considerations for evaluating of human exposure to electromagnetic fields (EMFs) from mobile telecommunication equipment (MTE) in the frequency range 30MHz 6GHz", Tech. Rep., CENELEC, European Committee for Electrotechnical Standardization, Brussels, 1997.
- [6] ANSI, ANSI/IEEE C95.1-1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz, The Institute of Electrical and Electronics Engineers, Inc., New York, NY 10017, 1992.
- [7] Katja Pokovic, Thomas Schmid, and Niels Kuster, \Robust setup for precise calibration of E-_eld probes in tissue simulating liquids at mobile communications frequencies", in ICECOM _ 97, Dubrovnik, October 15{17, 1997, pp. 120{124.
- [8] Katja Pokovic, Thomas Schmid, and Niels Kuster, \E-_eld probe with improved isotropy in brain simulating liquids", in Proceedings of the ELMAR, Zadar, Croatia, 23{25 June, 1996, pp. 172{175.
- [9] Volker Hombach, Klaus Meier, Michael Burkhardt, Eberhard K. uhn, and Niels Kuster, \The dependence of EM energy absorption upon human head modeling at 900 MHz", IEEE Transactions on Microwave Theory and Techniques, vol. 44, no. 10, pp. 1865{1873, Oct. 1996.
- [10] Klaus Meier, Ralf Kastle, Volker Hombach, Roger Tay, and Niels Kuster, \The dependence of EM energy absorption upon human head modeling at 1800 MHz", IEEE Transactions on Microwave Theory and Techniques, Oct. 1997, in press.
- [11] W. Gander, Computermathematik, Birkhaeuser, Basel, 1992.
- [12] W. H. Press, S. A. Teukolsky, W. T. Vetterling, and B. P. Flannery, Numerical Recepies in C, The Art of Scientific Computing, Second Edition, Cambridge University Press, 1992..Dosimetric Evaluation of Sample device, month 1998 9
- [13] NIS81 NAMAS, \The treatment of uncertainty in EMC measurement", Tech. Rep., NAMAS Executive, National Physical Laboratory, Teddington, Middlesex, England, 1994.
- [14] Barry N. Taylor and Christ E. Kuyatt, \Guidelines for evaluating and expressing the uncertainty of NIST measurement results", Tech. Rep., National Institute of Standards and Technology, 1994. Dosimetric Evaluation of Sample device, month 1998 10



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

APPENDIX A: DUT AND SAR SETUP PHOTO

APPENDIX B: PLOTS OF PERFORMANCE CHECK

The plots are showing as followings.



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

Date: 6/16/2017

Test Laboratory: Compliance Certification Services Inc.

SystemPerformanceCheck-Body D2450

DUT: Dipole 2450 MHz D2450V2; Type: D24500V2; Serial: 817

Communication System: UID 0, CW; Communication System Band: D2450 (2450.0 MHz);

Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used: f = 2450 MHz; $\sigma = 1.947 \text{ S/m}$; $\varepsilon_r = 51.938$; $\rho = 1000 \text{ kg/m}^3$

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 SN3798; ConvF(7.07, 7.07, 7.07); Calibrated: 7/27/2016;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/26/2016
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:xxxx
- DASY52 52.8.8(1222);
- SEMCAD X Version 14.6.10 (7331)


System Performance Check at Frequencies above 1 GHz/Pin=250 mW, dist=10mm (EX-Probe)/Area Scan (9x10x1): Measurement grid: dx=12mm, dy=12mm Maximum value of SAR (measured) = 17.4 W/kg

System Performance Check at Frequencies above 1 GHz/Pin=250 mW, dist=10mm (EX-Probe)/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 99.71 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 27.1 W/kg

SAR(1 g) = 13.0 W/kg; SAR(10 g) = 6.15 W/kg Maximum value of SAR (measured) = 19.7 W/kg



0 dB = 19.7 W/kg = 12.94 dBW/kg



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

Date: 6/18/2017

Test Laboratory: Compliance Certification Services Inc.

SystemPerformanceCheck-Body D5200

DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: 1095

Communication System: UID 0, CW (0); Communication System Band: D5GHz (5000.0 - 6000.0 MHz);

Frequency: 5200 MHz; Duty Cycle: 1:1

Medium parameters used: f = 5200 MHz; σ = 5.28 S/m; ε_r = 48.39; ρ = 1000 kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 SN3798; ConvF(4.77, 4.77, 4.77); Calibrated: 7/27/2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/26/2016
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:xxxx
- DASY52 52.8.8(1222);
- SEMCAD X Version 14.6.10 (7331)

System Performance Check with D5GHzV2 Dipole (graded grid)/d=10mm, Pin=100mW, f=5200 MHz 20/Area Scan (10x10x1): Measurement grid: dx=10mm, dy=10mm


Maximum value of SAR (measured) = 14.1 W/kg

System Performance Check with D5GHzV2 Dipole (graded grid)/d=10mm, Pin=100mW, f=5200 MHz 20/Zoom Scan (4x4x1.4mm, graded), dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dv=4mm, dz=1.4mm

Reference Value = 66.44 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 31.11 W/kg

SAR(1 g) = 7.66 W/kg; SAR(10 g) = 2.29 W/kg Maximum value of SAR (measured) = 17.9 W/kg



0 dB = 17.9 W/kq = 12.53 dBW/kq



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

Date: 6/18/2017

Test Laboratory: Compliance Certification Services Inc.

SystemPerformanceCheck-Body D5300

DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: 1095

Communication System: UID 0, CW (0); Communication System Band: D5GHz (5000.0 - 6000.0 MHz);

Frequency: 5300 MHz; Duty Cycle: 1:1

Medium parameters used: f = 5300 MHz; σ = 5.426 S/m; ε_r = 48.091; ρ = 1000 kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 SN3798; ConvF(4.6, 4.6, 4.6); Calibrated: 7/27/2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/26/2016
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:xxxx
- DASY52 52.8.8(1222);
- SEMCAD X Version 14.6.10 (7331)

System Performance Check with D5GHzV2 Dipole (graded grid)/d=10mm, Pin=100mW, f=5300 MHz 19.6/Area Scan (9x10x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 16.8 W/kg


System Performance Check with D5GHzV2 Dipole (graded grid)/d=10mm, Pin=100mW, f=5300 MHz 19.6/Zoom Scan (4x4x1.4mm, graded), dist=1.4mm (8x8x7)/Cube 0: Measurement grid:

dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 63.98 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 30.7 W/kg

SAR(1 g) = 7.72 W/kg; SAR(10 g) = 2.41 W/kg Maximum value of SAR (measured) = 18.9 W/kg



0 dB = 18.9 W/kq = 12.76 dBW/kq



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

Date: 6/18/2017

Test Laboratory: Compliance Certification Services Inc.

SystemPerformanceCheck-Body D5500

DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: 1095

Communication System: UID 0, CW (0); Communication System Band: D5GHz (5000.0 - 6000.0 MHz);

Frequency: 5500 MHz; Duty Cycle: 1:1

Medium parameters used: f = 5500 MHz; σ = 5.531 S/m; ε_r = 47.84; ρ = 1000 kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 SN3798; ConvF(4.23, 4.23, 4.23); Calibrated: 7/27/2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/26/2016
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:xxxx
- DASY52 52.8.8(1222);
- SEMCAD X Version 14.6.10 (7331)

System Performance Check with D5GHzV2 Dipole (graded grid)/d=10mm, Pin=100mW, f=5500 MHz/Area Scan (9x10x1): Measurement grid: dx=10mm, dy=10mm


Maximum value of SAR (measured) = 17.5 W/kg

System Performance Check with D5GHzV2 Dipole (graded grid)/d=10mm, Pin=100mW, f=5500 MHz/Zoom Scan (4x4x1.4mm, graded), dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dv=4mm, dz=1.4mm

Reference Value = 65.84 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 32.7 W/kg

SAR(1 g) = 7.82 W/kg; SAR(10 g) = 2.34 W/kg Maximum value of SAR (measured) = 19.2 W/kg



0 dB = 19.2 W/kq = 12.83 dBW/kq



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

Date: 6/18/2017

Test Laboratory: Compliance Certification Services Inc.

SystemPerformanceCheck-Body D5600

DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: 1095

Communication System: UID 0, CW (0); Communication System Band: D5GHz (5000.0 - 6000.0 MHz);

Frequency: 5600 MHz; Duty Cycle: 1:1

Medium parameters used: f = 5600 MHz; σ = 5.758 S/m; ε_r = 47.732; ρ = 1000 kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 SN3798; ConvF(4.18, 4.18, 4.18); Calibrated: 7/27/2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/26/2016
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:xxxx
- DASY52 52.8.8(1222);
- SEMCAD X Version 14.6.10 (7331)

System Performance Check with D5GHzV2 Dipole (graded grid)/d=10mm, Pin=100mW, f=5600 MHz/Area Scan (9x10x1): Measurement grid: dx=10mm, dy=10mm


Maximum value of SAR (measured) = 18.1 W/kg

System Performance Check with D5GHzV2 Dipole (graded grid)/d=10mm, Pin=100mW, f=5600 MHz/Zoom Scan (4x4x1.4mm, graded), dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dv=4mm, dz=1.4mm

Reference Value = 66.08 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 35.8 W/kg

SAR(1 g) = 7.89 W/kg; SAR(10 g) = 2.35 W/kg Maximum value of SAR (measured) = 19.8 W/kg



0 dB = 19.8 W/kq = 12.97 dBW/kq



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

Date: 6/18/2017

Test Laboratory: Compliance Certification Services Inc.

SystemPerformanceCheck-Body D5800

DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: 1095

Communication System: UID 0, CW (0); Communication System Band: D5GHz (5000.0 - 6000.0 MHz);

Frequency: 5800 MHz; Duty Cycle: 1:1

Medium parameters used: f = 5800 MHz; σ = 6.144 S/m; ε_r = 47.556; ρ = 1000 kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 SN3798; ConvF(4.34, 4.34, 4.34); Calibrated: 7/27/2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/26/2016
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:xxxx
- DASY52 52.8.8(1222);
- SEMCAD X Version 14.6.10 (7331)

System Performance Check with D5GHzV2 Dipole (graded grid)/d=10mm, Pin=100mW, f=5800 MHz/Area Scan (9x10x1): Measurement grid: dx=10mm, dy=10mm


Maximum value of SAR (measured) = 17.9 W/kg

System Performance Check with D5GHzV2 Dipole (graded grid)/d=10mm, Pin=100mW, f=5800 MHz/Zoom Scan (4x4x1.4mm, graded), dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dv=4mm, dz=1.4mm

Reference Value = 64.72 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 36.5 W/kg

SAR(1 g) = 7.59 W/kg; SAR(10 g) = 2.41 W/kg Maximum value of SAR (measured) = 20.1 W/kg



0 dB = 20.1 W/kq = 13.03 dBW/kq



Date of Issue: June 19, 2017 Report No .: C170412R01-B-SF

APPENDIX C: DASY CALIBRATION CERTIFICATE

The DASY Calibration Certificates are showing in the file named Appendix C DASY Calibration Certificate.

APPENDIX D: PLOTS OF SAR TEST RESULT

The plots are showing in the file named Appendix D Plots of SAR Test Result

END REPORT