



# FCC SAR TEST REPORT

FCC ID : TX2-RTL8822BE

: 802.11 a/b/g/n/ac RTL8822BE Combo module Equipment

**Brand Name** : Realtek

Model Name : RTL8822BE

**Applicant** : Realtek Semiconductor Corp.

No.2,Innovation Road II, Hsinchu Science

Park, Hsinchu300, Taiwan

Standard : FCC 47 CFR Part 2 (2.1093)

**ANSI/IEEE C95.1-1992** 

**IEEE 1528-2013** 

The product was installed into Notebook PC (Brand Name HP, Model Name: TPN-W141) during test.

The product was received on Dec. 07, 2018 and testing was started from Dec. 13, 2018 and completed on Dec. 17, 2018. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this variant report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Cona Huang / Deputy Manager

Qua Guang

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)

TEL: 886-3-327-3456 Page 1 of 37 FAX: 886-3-328-4978 Issued Date : Jan. 23, 2019

### Report No.: FA8D0418

# **Table of Contents**

1. Statement of Compliance	4
2. Guidance Applied	4
3. Equipment Under Test (EUT) Information	
3.1 General Information	
4. RF Exposure Limits	
4.1 Uncontrolled Environment	
4.2 Controlled Environment	
5. Specific Absorption Rate (SAR)	
5.1 Introduction	
5.2 SAR Definition	
6. System Description and Setup	
6.1 E-Field Probe	
6.2 Data Acquisition Electronics (DAE)	
6.3 Phantom	
6.4 Device Holder	
7. Measurement Procedures	
7.1 Spatial Peak SAR Evaluation	
7.2 Power Reference Measurement	
7.3 Area Scan	
7.4 Zoom Scan	
7.5 Volume Scan Procedures	
7.6 Power Drift Monitoring	
8. Test Equipment List	
9. System Verification	
9.1 Tissue Simulating Liquids	
9.2 Tissue Verification	
9.3 System Performance Check Results	
10. RF Exposure Positions	
10.1 SAR Testing for Tablet	18
11. Conducted RF Output Power (Unit: dBm)	
12. Bluetooth Exclusions Applied	
13. Antenna Location	
14. SAR Test Results	
14.1 Body SAR	
14.2 Repeated SAR Measurement	
15. Simultaneous Transmission Analysis	
15.1 Body Exposure Conditions	
15.2 SPLSR Evaluation and Analysis	
16. Uncertainty Assessment	
17. References	37
Appendix A. Plots of System Performance Check	
Appendix B. Plots of High SAR Measurement	
Appendix C. DASY Calibration Certificate	
Appendix D. Test Setup Photos	

# History of this test report

Report No.: FA8D0418

Report No.	Version	Description	Issued Date
FA8D0418	01	Initial issue of report	Jan. 23, 2019

TEL: 886-3-327-3456 Page 3 of 37
FAX: 886-3-328-4978 Issued Date: Jan. 23, 2019

## 1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for **Realtek Semiconductor Corp.**, **802.11** a/b/g/n/ac RTL8822BE Combo module, RTL8822BE, are as follows.

Report No.: FA8D0418

		Highest SAR Summary	Highaat Cimultanaaya
Equipment Class	Frequency Band	Body (Separation 0mm)	Highest Simultaneous Transmission 1g SAR (W/kg)
		1g SAR (W/kg)	3 , 3/
DTS	2.4GHz WLAN	0.55	1.03
NII	5GHz WLAN	1.20	1.35
Date of	Testing:	2018/12/13 -	- 2018/12/17

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC test. This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications.

Reviewed by: <u>Jason Wang</u> Report Producer: <u>Daisy Peng</u>

# 2. Guidance Applied

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2013
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB 865664 D02 SAR Reporting v01r02
- FCC KDB 447498 D01 General RF Exposure Guidance v06
- FCC KDB 248227 D01 802.11 Wi-Fi SAR v02r02
- FCC KDB 616217 D04 SAR for laptop and tablets v01r02

TEL: 886-3-327-3456 Page 4 of 37
FAX: 886-3-328-4978 Issued Date: Jan. 23, 2019

# 3. Equipment Under Test (EUT) Information

# 3.1 General Information

Product Feature & Specification			
<b>Equipment Name</b>	802.11 a/b/g/n/ac RTL8822BE Combo module		
Brand Name	Realtek		
Model Name	RTL8822BE		
FCC ID	TX2-RTL8822BE		
Wireless Technology and Frequency Range	WLAN 2.4GHz Band: 2412 MHz ~ 2472 MHz WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz WLAN 5.3GHz Band: 5260 MHz ~ 5320 MHz WLAN 5.5GHz Band: 5500 MHz ~ 5720 MHz WLAN 5.8GHz Band: 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz		
Mode	WLAN 2.4GHz : 802.11b/g/n HT20/HT40 WLAN 5GHz : 802.11a/n/ac HT20/HT40/VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE		

Report No.: FA8D0418

#### Remark:

- 1. Refer to tune-up procedure the channel 12 and 13 powers are low than others channel, measure power and SAR consideration is not necessary.
- 2. This device is convertible type notebook PC, and there are two mode as usage way, one is laptop mode, another is tablet mode, RF exposure will be evaluated two usage mode.

Host Information			
<b>Equipment Name</b>	Notebook PC		
Brand Name	HP		
Model Name	TPN-W141		
EUT Stage	Production Unit		

	Antenna Information (TB Mode)								
	Manufacturer	IN	PAQ		Manufacturer	rer INPAQ			
	Ant. Type	PIFA		PIFA		Ant. Type		PIFA	
	Part number 025.901H2.0001 (WA-P-LB-02-598)				Part number		5.901H3.0001 A-P-LB-02-599)		
Antenna 1	Antenna 1 Peak Gain (dBi)			Antenna 2	P	Peak Gain	(dBi)		
	2400~2483.5MHz	-2.46	5470~5725MHz	0.57		2400~2483.5MHz	-2.59	5470~5725MHz	-0.01
	5150~5250MHz	0.26	5725~5850MHz	-0.09		5150~5250MHz	-1.84	5725~5850MHz	-0.66
	5250~5350MHz	0.26				5250~5350MHz	-0.97		
Antenna Information				n (NB Mode	<del>e</del> )				
	Manufacturer	INPAQ			Manufacturer	INPAQ			
	Ant. Type	F	PIFA			Ant. Type	PIFA		
	Part number	025.901H2.0001 (WA-P-LB-02-598)			Part number		5.901H3.0001 A-P-LB-02-599)		
Antenna 1	Antenna 1 Peak Gain (dBi)			Antenna 2	-	Peak Gain	(dBi)		
	2400~2483.5MHz	-0.50	5470~5725MHz	-3.24		2400~2483.5MHz	-0.37	5470~5725MHz	-3.12
	5150~5250MHz	-3.60	5725~5850MHz	-4.20		5150~5250MHz	-2.43	5725~5850MHz	-3.84
	5250~5350MHz	-3.02				5250~5350MHz	-2.24		

TEL: 886-3-327-3456 Page 5 of 37
FAX: 886-3-328-4978 Issued Date: Jan. 23, 2019

## 4. RF Exposure Limits

### 4.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

Report No.: FA8D0418

### 4.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

#### Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

#### Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

1. Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

TEL: 886-3-327-3456 Page 6 of 37
FAX: 886-3-328-4978 Issued Date: Jan. 23, 2019

# 5. Specific Absorption Rate (SAR)

### 5.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

Report No.: FA8D0418

### 5.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (p). The equation description is as below:

$$SAR = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)


$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where:  $\sigma$  is the conductivity of the tissue,  $\rho$  is the mass density of the tissue and E is the RMS electrical field strength.

TEL: 886-3-327-3456 Page 7 of 37
FAX: 886-3-328-4978 Issued Date: Jan. 23, 2019

## 6. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:



Report No.: FA8D0418

- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

TEL: 886-3-327-3456 Page 8 of 37
FAX: 886-3-328-4978 Issued Date: Jan. 23, 2019

### 6.1 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

### <ES3DV3 Probe>

Construction	Symmetric design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – 4 GHz; Linearity: ±0.2 dB (30 MHz – 4 GHz)	
Directivity	±0.2 dB in TSL (rotation around probe axis)	
	±0.3 dB in TSL (rotation normal to probe axis)	
Dynamic Range	$5 \mu W/g - >100 \text{ mW/g};$	
j	Linearity: ±0.2 dB	
Dimensions	Overall length: 337 mm (tip: 20 mm)	
	Tip diameter: 3.9 mm (body: 12 mm)	
	Distance from probe tip to dipole centers: 3.0 mm	



Report No.: FA8D0418

#### <EX3DV4 Probe>

Construction	Symmetric design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic
Fragueney	solvents, e.g., DGBE)
Frequency	10 MHz – >6 GHz Linearity: ±0.2 dB (30 MHz – 6 GHz)
Directivity	±0.3 dB in TSL (rotation around probe axis)
	±0.5 dB in TSL (rotation normal to probe axis)
Dynamic Range	10 μW/g – >100 mW/g
	Linearity: ±0.2 dB (noise: typically <1 µW/g)
Dimensions	Overall length: 337 mm (tip: 20 mm)
	Tip diameter: 2.5 mm (body: 12 mm)
	Typical distance from probe tip to dipole centers: 1
	mm



### 6.2 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



Fig 5.1 Photo of DAE

TEL: 886-3-327-3456 FAX: 886-3-328-4978 Form version: 181113 Page 9 of 37 Issued Date : Jan. 23, 2019

### 6.3 Phantom

#### <SAM Twin Phantom>

Shell Thickness	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm	
Filling Volume	Approx. 25 liters	
Dimensions	Length: 1000 mm; Width: 500 mm; Height: adjustable feet	7 5
Measurement Areas	Left Hand, Right Hand, Flat Phantom	

Report No.: FA8D0418

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

### <ELI Phantom>

\LLIT Hantom>		
Shell Thickness	2 ± 0.2 mm (sagging: <1%)	
Filling Volume	Approx. 30 liters	
Dimensions	Major ellipse axis: 600 mm Minor axis: 400 mm	

The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

TEL: 886-3-327-3456 Page 10 of 37 FAX: 886-3-328-4978 Issued Date: Jan. 23, 2019

### 6.4 Device Holder

### <Mounting Device for Hand-Held Transmitter>

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). And upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm.







Report No.: FA8D0418

Mounting Device Adaptor for Wide-Phones

### <Mounting Device for Laptops and other Body-Worn Transmitters>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.



Mounting Device for Laptops

TEL: 886-3-327-3456 Page 11 of 37
FAX: 886-3-328-4978 Issued Date: Jan. 23, 2019

# 7. Measurement Procedures

The measurement procedures are as follows:

#### <Conducted power measurement>

(a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.

Report No.: FA8D0418

- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power

#### <SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

### 7.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values form the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

TEL: 886-3-327-3456 Page 12 of 37
FAX: 886-3-328-4978 Issued Date: Jan. 23, 2019

### 7.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

Report No.: FA8D0418

### 7.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB0 is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz		
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5 \text{ mm}$		
Maximum probe angle from probe axis to phantom surface normal at the measurement location	30° ± 1°	20° ± 1°		
	$\leq$ 2 GHz: $\leq$ 15 mm 2 – 3 GHz: $\leq$ 12 mm	$3 - 4 \text{ GHz:} \le 12 \text{ mm}$ $4 - 6 \text{ GHz:} \le 10 \text{ mm}$		
Maximum area scan spatial resolution: $\Delta x_{\text{Area}},\Delta y_{\text{Area}}$	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.			

TEL: 886-3-327-3456 Page 13 of 37
FAX: 886-3-328-4978 Issued Date: Jan. 23, 2019

### 7.4 Zoom Scan

Zoom scans are used assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube shoes base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Report No.: FA8D0418

Zoom scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum zoom scan s	patial reso	lution: Δx <sub>Zoom</sub> , Δy <sub>Zoom</sub>	$\leq$ 2 GHz: $\leq$ 8 mm 2 – 3 GHz: $\leq$ 5 mm <sup>*</sup>	$3 - 4 \text{ GHz: } \le 5 \text{ mm}^*$ $4 - 6 \text{ GHz: } \le 4 \text{ mm}^*$
	uniform grid: $\Delta z_{Zoom}(n)$		≤ 5 mm	$3 - 4 \text{ GHz: } \le 4 \text{ mm}$ $4 - 5 \text{ GHz: } \le 3 \text{ mm}$ $5 - 6 \text{ GHz: } \le 2 \text{ mm}$
Maximum zoom scan spatial resolution, normal to phantom surface	graded	Δz <sub>Zoom</sub> (1): between 1 <sup>st</sup> two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
	grid $\Delta z_{Zoom}(n>1)$ : between subsequent points		$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$	
Minimum zoom scan volume x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm	

Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.

### 7.5 Volume Scan Procedures

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

#### 7.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.

TEL: 886-3-327-3456 Page 14 of 37 FAX: 886-3-328-4978 Issued Date: Jan. 23, 2019

When zoom scan is required and the <u>reported</u> SAR from the area scan based 1-g SAR estimation procedures of KDB 447498 is  $\leq 1.4 \text{ W/kg}$ ,  $\leq 8 \text{ mm}$ ,  $\leq 7 \text{ mm}$  and  $\leq 5 \text{ mm}$  zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

## 8. Test Equipment List

Manufacturan	Name of Environment	Towns/Billington	Carial Number	Calib	ration	
Manufacturer	Name of Equipment	Type/Model	Serial Number	Last Cal.	Due Date	
SPEAG	2450MHz System Validation Kit	D2450V2	736	Aug. 31, 2018	Aug. 30, 2019	
SPEAG	5GHz System Validation Kit	D5GHzV2	1006	Sep. 27, 2018	Sep. 26, 2019	
SPEAG	Data Acquisition Electronics	DAE4	853	Jul. 24, 2018	Jul. 23, 2019	
SPEAG	Data Acquisition Electronics	DAE4	854	Jun. 14, 2018	Jun. 13, 2019	
SPEAG	Dosimetric E-Field Probe	EX3DV4	3931	Sep. 27, 2018	Sep. 26, 2019	
SPEAG	Dosimetric E-Field Probe	EX3DV4	7515	Oct. 03, 2018	Oct. 02, 2019	
RCPTWN	Thermometer	HTC-1	TM281-1	Mar. 16, 2018	Mar. 15, 2019	
RCPTWN	Thermometer	HTC-1	TM560-1	Mar. 16, 2018	Mar. 15, 2019	
SPEAG	Device Holder	N/A	N/A	N/A	N/A	
R&S	Signal Generator	SMA100A	101091	Jul. 09, 2018	Jul. 08, 2019	
Agilent	ENA Network Analyzer	E5071C	MY46316648	Jan. 17, 2018	Jan. 16, 2019	
SPEAG	Dielectric Probe Kit	DAK-3.5	1126	Sep. 19, 2018	Sep. 18, 2019	
LINE SEIKI	Digital Thermometer	DTM3000-spezial	3169	Sep. 11, 2018	Sep. 10, 2019	
Anritsu	Power Meter	ML2495A	1419002	May. 18, 2018	May. 17, 2019	
Anritsu	Power Sensor	MA2411B	1339124	May. 18, 2018	May. 17, 2019	
Anritsu	Power Meter	ML2495A	1240001	Sep. 13, 2018	Sep. 12, 2019	
Anritsu	Power Sensor	MA2411B	1207349	Sep. 13, 2018	Sep. 12, 2019	
Agilent	Spectrum Analyzer	E4408B	MY44211028	Aug. 28, 2018	Aug. 27, 2019	
Anritsu	Spectrum Analyzer	MS2830A	6201396378	Jun. 23, 2018	Jun. 22, 2019	
Mini-Circuits	Power Amplifier	ZVE-8G+	6382	Aug. 09, 2018	Aug. 08, 2019	
Mini-Circuits	Power Amplifier	ZHL-42W+	15542	Aug. 09, 2018	Aug. 08, 2019	
ATM	Dual Directional Coupler	C122H-10	P610410z-02	No	Note 1	
Woken	Attenuator 1	WK0602-XX	N/A	No	te 1	
PE	Attenuator 2	PE7005-10	N/A	No	te 1	
PE	Attenuator 3	PE7005- 3	N/A	No	te 1	

Report No.: FA8D0418

### **General Note:**

1. Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check source.

TEL: 886-3-327-3456 Page 15 of 37
FAX: 886-3-328-4978 Issued Date: Jan. 23, 2019

# 9. System Verification

### 9.1 Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 10.1. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 10.2.







Report No.: FA8D0418

Fig 10.2 Photo of Liquid Height for Body SAR

TEL: 886-3-327-3456 Page 16 of 37
FAX: 886-3-328-4978 Issued Date: Jan. 23, 2019

# 9.2 Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Report No.: FA8D0418

Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity (σ)	Permittivity (εr)		
	For Head									
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9		
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5		
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5		
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.40	40.0		
2450	55.0	0	0	0	0	45.0	1.80	39.2		
2600	54.8	0	0	0.1	0	45.1	1.96	39.0		
				For Body						
750	51.7	47.2	0	0.9	0.1	0	0.96	55.5		
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2		
900	50.8	48.2	0	0.9	0.1	0	1.05	55.0		
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3		
2450	68.6	0	0	0	0	31.4	1.95	52.7		
2600	68.1	0	0	0.1	0	31.8	2.16	52.5		

Simulating Liquid for 5GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	64~78%
Mineral oil	11~18%
Emulsifiers	9~15%
Additives and Salt	2~3%

### <Tissue Dielectric Parameter Check Results>


Frequency (MHz)	Tissue Type	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (ε <sub>r</sub> )	Conductivity Target (σ)	Permittivity Target (ε <sub>r</sub> )	Delta (σ) (%)	Delta (ε <sub>r</sub> ) (%)	Limit (%)	Date
2450	MSL	22.3	2.033	53.249	1.95	52.70	4.26	1.04	±5	2018/12/13
5250	MSL	22.5	5.395	48.860	5.36	48.95	0.65	-0.18	±5	2018/12/14
5250	MSL	22.4	5.383	48.920	5.36	48.95	0.43	-0.06	±5	2018/12/17
5600	MSL	22.5	5.777	48.372	5.77	48.50	0.12	-0.26	±5	2018/12/14
5600	MSL	22.4	5.765	48.432	5.77	48.50	-0.09	-0.14	±5	2018/12/17
5750	MSL	22.5	5.937	48.169	5.94	48.28	-0.05	-0.23	±5	2018/12/14
5750	MSL	22.4	5.924	48.228	5.94	48.28	-0.27	-0.11	±5	2018/12/17

TEL: 886-3-327-3456 Page 17 of 37
FAX: 886-3-328-4978 Issued Date: Jan. 23, 2019

### 9.3 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 1g SAR (W/kg)	Targeted 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Deviation (%)
2018/12/13	2450	MSL	250	D2450V2-736	EX3DV4 - SN3931	DAE4 Sn854	13.30	51.50	53.20	3.30
2018/12/14	5250	MSL	100	D5GHzV2-1006-5250	EX3DV4 - SN3931	DAE4 Sn854	7.82	78.30	78.20	-0.13
2018/12/17	5250	MSL	100	D5GHzV2-1006-5250	EX3DV4 - SN7515	DAE4 Sn853	7.86	78.30	78.60	0.38
2018/12/14	5600	MSL	100	D5GHzV2-1006-5600	EX3DV4 - SN3931	DAE4 Sn854	8.25	81.00	82.50	1.85
2018/12/17	5600	MSL	100	D5GHzV2-1006-5600	EX3DV4 - SN7515	DAE4 Sn853	8.13	81.00	81.30	0.37
2018/12/14	5750	MSL	100	D5GHzV2-1006-5750	EX3DV4 - SN3931	DAE4 Sn854	7.27	77.40	72.70	-6.07
2018/12/17	5750	MSL	100	D5GHzV2-1006-5750	EX3DV4 - SN7515	DAE4 Sn853	7.66	77.40	76.60	-1.03





Report No.: FA8D0418

Fig 8.3.1 System Performance Check Setup

Fig 8.3.2 Setup Photo

# 10. RF Exposure Positions

### 10.1 SAR Testing for Tablet

This device can be used also in full sized tablet exposure conditions, due to its size. Per FCC KDB 616217, the back surface and edges of the tablet should be tested for SAR compliance with the tablet touching the phantom. The SAR exclusion threshold in KDB 447498 D01v06 can be applied to determine SAR test exclusion for adjacent edge configurations. The closest distance from the antenna to an adjacent tablet edge is used to determine if SAR testing is required for the adjacent edges, with the adjacent edge positioned against the phantom and the edge containing the antenna positioned perpendicular to the phantom.

TEL: 886-3-327-3456 Page 18 of 37
FAX: 886-3-328-4978 Issued Date: Jan. 23, 2019

# 11. Conducted RF Output Power (Unit: dBm)

#### <WLAN Conducted Power>

#### **General Note:**

1. For each antenna, transmit power in SISO operation is larger than (or equal to) the power in MIMO operation, RF exposure compliance of MIMO mode can be deduced from the compliance simultaneous transmission of antennas operating in SISO mode.

Report No.: FA8D0418

- Per KDB 248227 D01v02r02, the simultaneous SAR provisions in KDB publication 447498 should be applied to
  determine simultaneous transmission SAR test exclusion for WiFi MIMO. If the sum of 1g single transmission chain
  SAR measurements is < 1.6W/kg and SAR peak to location ratio ≤ 0.04, no additional SAR measurements for
  MIMO.</li>
- 3. Per KDB 248227 D01v02r02, SAR test reduction is determined according to 802.11 transmission mode configurations and certain exposure conditions with multiple test positions. In the 2.4 GHz band, separate SAR procedures are applied to DSSS and OFDM configurations to simplify DSSS test requirements. For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration must be determined for each standalone and aggregated frequency band, according to the transmission mode configuration with the highest maximum output power specified for production units to perform SAR measurements. If the same highest maximum output power applies to different combinations of channel bandwidths, modulations and data rates, additional procedures are applied to determine which test configurations require SAR measurement. When applicable, an initial test position may be applied to reduce the number of SAR measurements required for next to the ear, UMPC mini-tablet or hotspot mode configurations with multiple test positions.
- 4. For 2.4 GHz 802.11b DSSS, either the initial test position procedure for multiple exposure test positions or the DSSS procedure for fixed exposure position is applied; these are mutually exclusive. For 2.4 GHz and 5 GHz OFDM configurations, the initial test configuration is applied to measure SAR using either the initial test position procedure for multiple exposure test position configurations or the initial test configuration procedures for fixed exposure test conditions. Based on the reported SAR of the measured configurations and maximum output power of the transmission mode configurations that are not included in the initial test configuration, the subsequent test configuration and initial test position procedures are applied to determine if SAR measurements are required for the remaining OFDM transmission configurations. In general, the number of test channels that require SAR measurement is minimized based on maximum output power measured for the test sample(s).
- 5. For OFDM transmission configurations in the 2.4 GHz and 5 GHz bands, When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel for each frequency band.
- 6. DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures.18 The initial test position procedure is described in the following:
  - a. When the reported SAR of the initial test position is ≤ 0.4 W/kg, further SAR measurement is not required for the other test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band.
  - b. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
  - c. For all positions/configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.

TEL: 886-3-327-3456 Page 19 of 37
FAX: 886-3-328-4978 Issued Date: Jan. 23, 2019

### <2.4GHz WLAN ANT 1>

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
		1	2412	16.91	17.00	
		6	2437	16.88	17.00	
	802.11b 1Mbps	11	2462	16.78	17.00	100.00
		12	2467	13.85	14.00	
		13	2472	10.82	11.00	
		1	2412	13.92	14.00	
	802.11g 6Mbps	6	2437	17.97	18.00	100.00
		11	2462	14.96	15.00	
2.4GHz WLAN		12	2467	11.81	12.00	
		13	2472	7.84	8.00	
		1	2412	13.83	14.00	
	<b></b> .	6	2437	17.75	18.00	
	802.11n-HT20 MCS0	11	2462	13.81	14.00	100.00
		12	2467	10.79	11.00	
		13	2472	7.92	8.00	
		3	2422	13.75	14.00	
		6	2437	16.69	17.00	
	802.11n-HT40 MCS0	9	2452	13.73	14.00	100.00
	WC30	10	2457	10.88	11.00	
		11	2462	7.76	8.00	

Report No.: FA8D0418

### <2.4GHz WLAN ANT 2>

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
		1	2412	16.85	17.00	
		6	2437	16.84	17.00	
	802.11b 1Mbps	11	2462	16.71	17.00	100.00
		12	2467	13.81	14.00	
		13	2472	10.76	11.00	
		1	2412	13.91	14.00	
	802.11g 6Mbps	6	2437	17.96	18.00	100.00
		11	2462	14.83	15.00	
2.4GHz WLAN		12	2467	11.77	12.00	
		13	2472	7.68	8.00	
		1	2412	13.92	14.00	
	000 44 11700	6	2437	17.97	18.00	
	802.11n-HT20 MCS0	11	2462	13.76	14.00	100.00
		12	2467	10.75	11.00	
		13	2472	7.88	8.00	
		3	2422	13.74	14.00	
	000 44 - UT40	6	2437	16.78	17.00	
	802.11n-HT40 MCS0	9	2452	13.73	14.00	100.00
		10	2457	10.91	11.00	
		11	2462	7.69	8.00	

TEL: 886-3-327-3456 Page 20 of 37
FAX: 886-3-328-4978 Issued Date: Jan. 23, 2019

### <2.4GHz WLAN ANT 1+2>

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
		1	2412	16.80	17.00	
		6	2437	19.95	20.00	
	802.11g 6Mbps	11	2462	16.86	17.00	100.00
		12	2467	13.86	14.00	
		13	2472	10.84	11.00	
	802.11n-HT20 MCS0	1	2412	16.72	17.00	100.00
2.4GHz WLAN		6	2437	19.94	20.00	
		11	2462	16.71	17.00	
		12	2467	13.78	14.00	
		13	2472	10.89	11.00	
		3	2422	15.96	16.00	
	000 44 117.12	6	2437	17.98	18.00	
	802.11n-HT40 MCS0	9	2452	16.77	17.00	100.00
	Wedo	10	2457	13.85	14.00	
		11	2462	10.69	11.00	

Report No.: FA8D0418

TEL: 886-3-327-3456 Page 21 of 37
FAX: 886-3-328-4978 Issued Date: Jan. 23, 2019

### <5GHz WLAN ANT1>

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
		36	5180	16.40	16.50	
	802.11a 6Mbps	40	5200	17.25	17.50	100.00
	602.11a 61VIDPS	44	5220	17.30	17.50	100.00
		48	5240	17.05	17.50	
		36	5180	16.35	16.50	
	802.11n-HT20 MCS0	40	5200	17.44	17.50	100.00
		44	5220	17.46	17.50	
5.2GHz WLAN		48	5240	17.48	17.50	
	802.11n-HT40	38	5190	12.18	12.50	100.00
	MCS0	46	5230	16.49	16.50	100.00
		36	5180	16.33	16.50	
	802.11ac-VHT20	40	5200	17.40	17.50	100.00
	MCS0	44	5220	17.42	17.50	100.00
		48	5240	17.46	17.50	
	802.11ac-VHT40	38	5190	12.15	12.50	100.00
	MCS0	46	5230	16.46	16.50	100.00
	802.11ac-VHT80 MCS0	42	5210	11.40	11.50	100.00

Report No.: FA8D0418

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
		52	5260	17.30	17.50	
	802.11a 6Mbps	56	5280	17.28	17.50	100.00
	602.11a bivibps	60	5300	17.42	17.50	100.00
		64	5320	15.43	15.50	
		52	5260	17.20	17.50	
	802.11n-HT20 MCS0	56	5280	17.16	17.50	100.00
		60	5300	17.48	17.50	
5.3GHz WLAN		64	5320	15.42	15.50	
	802.11n-HT40	54	5270	16.30	16.50	100.00
	MCS0	62	5310	13.32	13.50	100.00
		52	5260	17.17	17.50	
	802.11ac-VHT20	56	5280	17.13	17.50	100.00
	MCS0	60	5300	17.45	17.50	100.00
		64	5320	15.40	15.50	
	802.11ac-VHT40	54	5270	16.28	16.50	100.00
	MCS0	62	5310	13.30	13.50	100.00
	802.11ac-VHT80 MCS0	58	5290	11.37	11.50	100.00

TEL: 886-3-327-3456 Page 22 of 37
FAX: 886-3-328-4978 Issued Date: Jan. 23, 2019



	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
		100	5500	14.40	14.50	
		116	5580	17.22	17.50	
	802.11a 6Mbps	124	5620	17.15	17.50	100.00
		132	5660	17.11	17.50	1
		144	5720	15.40	15.50	
		100	5500	14.49	14.50	
		116	5580	17.13	17.50	
	802.11n-HT20 MCS0	124	5620	17.10	17.50	100.00
	IVICSU	132	5660	17.06	17.50	
		144	5720	14.42	14.50	
	802.11n-HT40 MCS0	102	5510	13.48	13.50	
		110	5550	16.46	16.50	
5.5GHz WLAN		126	5630	16.40	16.50	100.00
	IVICSU	134	5670	16.42	16.50	
		142	5710	16.32	16.50	
		100	5500	14.46	14.50	
		116	5580	17.10	17.50	
	802.11ac-VHT20 MCS0	124	5620	17.08	17.50	100.00
	IVICSU	132	5660	17.03	17.50	
		144	5720	14.40	14.50	
		102	5510	13.45	13.50	
		110	5550	16.43	16.50	
	802.11ac-VHT40	126	5630	16.37	16.50	100.00
	MCS0	134	5670	16.40	16.50	
		142	5710	16.31	16.50	
		106	5530	11.42	11.50	
	802.11ac-VHT80	122	5610	16.46	16.50	100.00
	MCS0	138	5690	16.18	16.50	

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
		149	5745	17.27	17.50	
	802.11a MCS0	157	5785	17.48	17.50	100.00
		165	5825	17.17	17.50	
		149	5745	17.30	17.50	
	802.11n-HT20 MCS0	157	5785	17.41	17.50	100.00
5.8GHz WLAN		165	5825	17.40	17.50	
	802.11n-HT40	151	5755	16.46	16.50	100.00
	MCS0	159	5795	16.40	16.50	100.00
		149	5745	17.28	17.50	
	802.11ac-VHT20 MCS0	157	5785	17.38	17.50	100.00
	Micco	165	5825	17.36	17.50	
	802.11ac-VHT40	151	5755	16.42	16.50	100.00
	MCS0	159	5795	16.36	16.50	100.00
	802.11ac-VHT80 MCS0	155	5775	16.40	16.50	100.00

TEL : 886-3-327-3456 FAX : 886-3-328-4978 Form version: 181113 Page 23 of 37 Issued Date : Jan. 23, 2019

Report No.: FA8D0418



Report No.: FA8D0418

<5GHz WLAN ANT2>
------------------

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
		36	5180	16.30	16.50	
	802.11a 6Mbps	40	5200	17.32	17.50	100.00
	002.11a 0ivibps	44	5220	17.35	17.50	100.00
		48	5240	17.30	17.50	
		36	5180	16.42	16.50	
	802.11n-HT20	40	5200	17.32	17.50	100.00
	MCS0	44	5220	17.35	17.50	100.00
5.2GHz WLAN		48	5240	17.47	17.50	
	802.11n-HT40	38	5190	12.45	12.50	100.00
	MCS0	46	5230	16.48	16.50	100.00
		36	5180	16.40	16.50	
	802.11ac-VHT20	40	5200	17.30	17.50	100.00
	MCS0	44	5220	17.32	17.50	100.00
		48	5240	17.45	17.50	
	802.11ac-VHT40	38	5190	12.43	12.50	100.00
	MCS0	46	5230	16.40	16.50	100.00
	802.11ac-VHT80 MCS0	42	5210	11.48	11.50	100.00

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
		52	5260	17.16	17.50	
	802.11a 6Mbps	56	5280	17.12	17.50	100.00
	602.11a 61VIDPS	60	5300	17.13	17.50	100.00
		64	5320	15.32	15.50	
		52	5260	17.13	17.50	
	802.11n-HT20	56	5280	17.08	17.50	100.00
	MCS0	60	5300	17.10	17.50	100.00
5.3GHz WLAN		64	5320	15.35	15.50	
	802.11n-HT40	54	5270	16.30	16.50	100.00
	MCS0	62	5310	13.13	13.50	100.00
		52	5260	17.10	17.50	
	802.11ac-VHT20	56	5280	17.05	17.50	100.00
	MCS0	60	5300	17.07	17.50	100.00
		64	5320	15.33	15.50	
	802.11ac-VHT40	54	5270	16.25	16.50	100.00
	MCS0	62	5310	13.10	13.50	100.00
	802.11ac-VHT80 MCS0	58	5290	11.10	11.50	100.00

TEL: 886-3-327-3456 Page 24 of 37
FAX: 886-3-328-4978 Issued Date: Jan. 23, 2019



TON LAB. FCC	SAR TEST R	Rep	ort No. : FA8D04			
	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
		100	5500	14.24	14.50	
		116	5580	17.28	17.50	
	802.11a 6Mbps	124	5620	17.20	17.50	100.00
		132	5660	17.19	17.50	
		144	5720	15.22	15.50	
		100	5500	14.46	14.50	
		116	5580	17.24	17.50	
	802.11n-HT20 MCS0	124	5620	17.22	17.50	100.00
	Micco	132	5660	17.20	17.50	
		144	5720	14.35	14.50	
		102	5510	13.27	13.50	
		110	5550	16.20	16.50	
5GHz WLAN	802.11n-HT40 MCS0	126	5630	16.18	16.50	100.00
	WIOGO	134	5670	16.24	16.50	
		142	5710	16.18	16.50	
		100	5500	14.42	14.50	
		116	5580	17.22	17.50	
	802.11ac-VHT20 MCS0	124	5620	17.20	17.50	100.00
	WiCOO	132	5660	17.18	17.50	
		144	5720	14.32	14.50	
		102	5510	13.25	13.50	
		110	5550	16.17	16.50	
	802.11ac-VHT40 MCS0	126	5630	16.15	16.50	100.00
	WOOO	134	5670	16.20	16.50	
		142	5710	16.15	16.50	
		106	5530	11.49	11.50	
	802.11ac-VHT80 MCS0	122	5610	16.42	16.50	100.00
	IVICOU	138	5690	16.08	16.50	

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
		149	5745	17.05	17.50	
	802.11a 6Mbps	157	5785	17.20	17.50	100.00
		165	5825	17.23	17.50	
		149	5745	17.28	17.50	
	802.11n-HT20 MCS0	157	5785	17.41	17.50	100.00
5.8GHz WLAN	Wieco	165	5825	17.13	17.50	
	802.11n-HT40	151	5755	16.35	16.50	100.00
	MCS0	159	5795	16.31	16.50	100.00
		149	5745	17.26	17.50	
	802.11ac-VHT20 MCS0	157	5785	17.39	17.50	100.00
	IVIOOO	165	5825	17.11	17.50	
	802.11ac-VHT40	151	5755	16.33	16.50	100.00
	MCS0	159	5795	16.28	16.50	100.00
	802.11ac-VHT80 MCS0	155	5775	16.20	16.50	100.00

TEL: 886-3-327-3456 FAX: 886-3-328-4978 Form version: 181113

Page 25 of 37 Issued Date : Jan. 23, 2019



Report No.: FA8D0418

<5GHz WLAN ANT1+2>						
	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
		36	5180	18.47	18.50	
	902 44a 6Mhna	40	5200	19.27	19.50	100.00
	802.11a 6Mbps	44	5220	19.30	19.50	100.00
		48	5240	19.34	19.50	
		36	5180	18.43	18.50	
	802.11n-HT20 MCS0	40	5200	19.23	19.50	100.00
		44	5220	19.26	19.50	
5.2GHz WLAN		48	5240	19.14	19.50	
	802.11n-HT40	38	5190	14.46	14.50	400.00
	MCS0	46	5230	19.14	19.50	100.00
		36	5180	18.41	18.50	
	802.11ac-VHT20	40	5200	19.21	19.50	400.00
	MCS0	44	5220	19.24	19.50	100.00
		48	5240	19.10	19.50	
	802.11ac-VHT40	38	5190	14.44	14.50	400.00
	MCS0	46	5230	19.12	19.50	100.00
	802.11ac-VHT80 MCS0	42	5210	13.42	13.50	100.00

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
		52	5260	19.25	19.50	
	802.11a 6Mbps	56	5280	19.10	19.50	100.00
	002.11a 0ivibps	60	5300	19.13	19.50	100.00
		64	5320	18.05	18.50	
		52	5260	19.29	19.50	
	802.11n-HT20	56	5280	19.28	19.50	100.00
	MCS0	60	5300	19.20	19.50	
5.3GHz WLAN		64	5320	18.24	18.50	
	802.11n-HT40	54	5270	19.17	19.50	100.00
	MCS0	62	5310	15.38	15.50	100.00
		52	5260	19.27	19.50	
	802.11ac-VHT20	56	5280	19.16	19.50	400.00
	MCS0	60	5300	19.18	19.50	100.00
		64	5320	18.22	18.50	
	802.11ac-VHT40	54	5270	19.15	19.50	100.00
	MCS0	62	5310	15.36	15.50	100.00
	802.11ac-VHT80 MCS0	58	5290	13.11	13.50	100.00

TEL: 886-3-327-3456 Page 26 of 37 FAX: 886-3-328-4978 Issued Date : Jan. 23, 2019



	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
		100	5500	17.39	17.50	
		116	5580	20.22	20.50	
	802.11a 6Mbps	124	5620	20.20	20.50	100.00
		132	5660	20.16	20.50	
		144	5720	17.18	17.50	
		100	5500	17.29	17.50	
		116	5580	20.31	20.50	
	802.11n-HT20 MCS0	124	5620	20.29	20.50	100.00
	Wiese	132	5660	20.25	20.50	
		144	5720	17.06	17.50	
		102	5510	15.23	15.50	
	802.11n-HT40 MCS0	110	5550	19.16	19.50	
5.5GHz WLAN		126	5630	19.12	19.50	100.00
		134	5670	19.13	19.50	
		142	5710	19.12	19.50	
		100	5500	17.27	17.50	
		116	5580	20.29	20.50	
	802.11ac-VHT20 MCS0	124	5620	20.27	20.50	100.00
	Wieco	132	5660	20.23	20.50	
		144	5720	17.05	17.50	
		102	5510	15.21	15.50	
		110	5550	19.13	19.50	
	802.11ac-VHT40 MCS0	126	5630	19.06	19.50	100.00
		134	5670	19.09	19.50	
		142	5710	19.10	19.50	
		106	5530	14.18	14.50	
	802.11ac-VHT80 MCS0	122	5610	19.46	19.50	100.00
	Wicco	138	5690	19.17	19.50	

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
		149	5745	20.23	20.50	
	802.11a MCS0	157	5785	20.13	20.50	100.00
		165	5825	20.12	20.50	
		149	5745	20.22	20.50	
	802.11n-HT20 MCS0	157	5785	20.15	20.50	100.00
5.8GHz WLAN	mees	165	5825	20.03	20.50	
	802.11n-HT40	151	5755	19.32	19.50	100.00
	MCS0	159	5795	19.44	19.50	100.00
		149	5745	20.20	20.50	
	802.11ac-VHT20 MCS0	157	5785	20.12	20.50	100.00
		165	5825	20.01	20.50	
	802.11ac-VHT40	151	5755	19.30	19.50	100.00
	MCS0	159	5795	19.41	19.50	100.00
	802.11ac-VHT80 MCS0	155	5775	19.16	19.50	100.00

TEL: 886-3-327-3456 FAX: 886-3-328-4978 Form version: 181113 Page 27 of 37 Issued Date : Jan. 23, 2019

Report No.: FA8D0418

# 12. Bluetooth Exclusions Applied

Mode Band	Max Average	power(dBm)
IVIOUE DAITU	BR/EDR	LE
2.4GHz Bluetooth	5.5	5.5

### Note:

1. Per KDB 447498 D01v06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  $\cdot [\sqrt{f(GHz)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR

Report No.: FA8D0418

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Bluetooth Max Power (dBm)	Separation Distance (mm)	Frequency (GHz)	exclusion thresholds
5.5	< 5	2.48	1.12

#### Note:


Per KDB 447498 D01v06, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. The test exclusion threshold is 1.12 which is <= 3, SAR testing is not required.

TEL: 886-3-327-3456 Page 28 of 37
FAX: 886-3-328-4978 Issued Date: Jan. 23, 2019

# 13. Antenna Location

### <For Tablet Mode>

### Edge1



Edge3 Front View


Report No.: FA8D0418

The separation distance for antenna to edge:

Antenna	To Edge1 (mm)	To Edge2 (mm)	To Edge3 (mm)	To Edge4 (mm)
WLAN Antenna 1	1.25	39.5	205.9	221.5
WLAN/BT Antenna 2	1.25	221.3	205.9	39.7

TEL: 886-3-327-3456 Page 29 of 37
FAX: 886-3-328-4978 Issued Date: Jan. 23, 2019

## <For Laptop Mode>





<Side View>

Report No.: FA8D0418

TEL: 886-3-327-3456 Page 30 of 37
FAX: 886-3-328-4978 Issued Date: Jan. 23, 2019

### <SAR test exclusion table>

#### **General Note:**

1. The below table, when the distance is < 50 mm exclusion threshold is "Ratio", when the distance is > 50 mm exclusion threshold is "mW"

Report No.: FA8D0418

- 2. Maximum power is the source-based time-average power and represents the maximum RF output power among production units
- 3. Per KDB 447498 D01v06, for larger devices, the test separation distance of adjacent edge configuration is determined by the closest separation between the antenna and the user.
- 4. Per KDB 447498 D01v06, standalone SAR test exclusion threshold is applied; If the test separation distance is < 5mm, 5mm is used to determine SAR exclusion threshold.
- 5. Per KDB 447498 D01v06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  $\cdot [\sqrt{f(GHz)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR

- f(GHz) is the RF channel transmit frequency in GHz
- · Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 6. Per KDB 447498 D01v06, at 100 MHz to 6 GHz and for *test separation distances* > 50 mm, the SAR test exclusion threshold is determined according to the following
  - a) [Threshold at 50 mm in step 1) + (test separation distance 50 mm)·(f(MHz)/150)] mW, at 100 MHz to 1500 MHz
  - b) [Threshold at 50 mm in step 1) + (test separation distance 50 mm) 10] mW at > 1500 MHz and ≤ 6 GHz

	Wireless Interface	2.4GHz WLAN ANT 1	2.4GHz WLAN ANT 2	5GHz WLAN ANT 1	5GHz WLAN ANT 2
Exposure Position	Calculated Frequency	2472MHz	2472MHz	5825MHz	5825MHz
Exposure Position	Maximum power (dBm)	18	18	17.5	17.5
	Maximum rated power(mW)	63.0	63.0	56.0	56.0
	Separation distance(mm)	5.0	5.0	5.0	5.0
Bottom Face	exclusion threshold	19.8	19.8	27.0	27.0
	Testing required?	Yes	Yes	Yes	Yes
	Separation distance(mm)	5.0	5.0	5.0	5.0
Edge 1	exclusion threshold	19.8	19.8	27.0	27.0
	Testing required?	Yes	Yes	Yes	Yes
	Separation distance(mm)	39.5	221.3	39.5	221.3
Edge 2	exclusion threshold	2.5	1808.0	3.4	1775.0
	Testing required?	No	No	Yes	No
	Separation distance(mm)	205.9	205.9	205.9	205.9
Edge 3	exclusion threshold	1654.0	1654.0	1621.0	1621.0
	Testing required?	No	No	No	No
	Separation distance(mm)	221.5	39.7	221.5	39.7
Edge 4	exclusion threshold	1810.0	2.5	1777.0	3.4
	Testing required?	No	No	No	Yes
	Separation distance(mm)	212.03	212.03	212.03	212.03
Bottom of Laptop	exclusion threshold	1716.0	1716.0	1682.0	1682.0
	Testing required?	No	No	No	No

TEL: 886-3-327-3456 Page 31 of 37 FAX: 886-3-328-4978 Issued Date: Jan. 23, 2019

### 14. SAR Test Results

#### **General Note:**

- 1. Per KDB 447498 D01v06, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
  - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.

Report No.: FA8D0418

- b. For SAR testing of WLAN signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)"
- c. For WLAN: Reported SAR(W/kg)= Measured SAR(W/kg)\* Duty Cycle scaling factor \* Tune-up scaling factor
- 2. Per KDB 447498 D01v06, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
  - ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
  - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
  - ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz
- Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥0.8W/kg.

#### **WLAN Note:**

- 1. Per KDB 248227 D01v02r02, for 2.4GHz 802.11g/n SAR testing is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.
- 2. Per KDB 248227 D01v02r02, U-NII-1 SAR testing is not required when the U-NII-2A band highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band.
- 3. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
- 4. For all positions / configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions / configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.
- For WLAN SAR testing was performed on single antenna RF power in SISO mode is larger or equal to the single antenna RF power in MIMO mode, and for RF exposure assessment of MIMO mode simultaneous transmission exclusion analysis was performed with SAR test results of each antenna in SISO mode.
- 6. Per KDB 248227 D01v02r02, the simultaneous SAR provisions in KDB publication 447498 should be applied to determine simultaneous transmission SAR test exclusion for 2.4GHz WiFi MIMO. If the sum of 1g single transmission chain SAR measurements is < 1.6W/kg and SAR peak to location ratio ≤ 0.04, no additional SAR measurements for MIMO.
- 7. During SAR testing the WLAN transmission was verified using a spectrum analyzer.

TEL: 886-3-327-3456 Page 32 of 37
FAX: 886-3-328-4978 Issued Date: Jan. 23, 2019

# 14.1 Body SAR

### <WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Bottom Face	0mm	Ant 1	1	2412	16.91	17.00	1.021	100	1.000	0.04	0.192	0.196
	WLAN2.4GHz	802.11b 1Mbps	Edge 1	0mm	Ant 1	1	2412	16.91	17.00	1.021	100	1.000	0.18	0.475	0.485
	WLAN2.4GHz	802.11b 1Mbps	Bottom Face	0mm	Ant 2	1	2412	16.85	17.00	1.035	100	1.000	0	0.244	0.253
01	WLAN2.4GHz	802.11b 1Mbps	Edge 1	0mm	Ant 2	1	2412	16.85	17.00	1.035	100	1.000	0.13	0.528	0.547
	WLAN2.4GHz	802.11b 1Mbps	Edge 1	0mm	Ant 2	6	2437	16.84	17.00	1.038	100	1.000	0.1	0.399	0.414
	WLAN2.4GHz	802.11b 1Mbps	Edge 1	0mm	Ant 2	11	2462	16.71	17.00	1.069	100	1.000	0.18	0.298	0.319
	WLAN5GHz	802.11a 6Mbps	Bottom Face	0mm	Ant 1	60	5300	17.42	17.50	1.019	100	1.000	-0.11	0.343	0.349
02	WLAN5GHz	802.11a 6Mbps	Edge 1	0mm	Ant 1	60	5300	17.42	17.50	1.019	100	1.000	0.17	1.150	1.171
	WLAN5GHz	802.11a 6Mbps	Edge 1	0mm	Ant 1	52	5260	17.30	17.50	1.047	100	1.000	0.18	0.932	0.976
	WLAN5GHz	802.11a 6Mbps	Edge 1	0mm	Ant 1	56	5280	17.28	17.50	1.052	100	1.000	0.16	1.100	1.157
	WLAN5GHz	802.11a 6Mbps	Edge 1	0mm	Ant 1	64	5320	15.43	15.50	1.016	100	1.000	0.16	0.804	0.817
	WLAN5GHz	802.11a 6Mbps	Edge 2	0mm	Ant 1	60	5300	17.42	17.50	1.019	100	1.000	-0.12	0.164	0.167
	WLAN5GHz	802.11a 6Mbps	Bottom Face	0mm	Ant 2	52	5260	17.16	17.50	1.081	100	1.000	-0.06	0.267	0.289
	WLAN5GHz	802.11a 6Mbps	Edge 1	0mm	Ant 2	52	5260	17.16	17.50	1.081	100	1.000	0.14	0.756	0.818
	WLAN5GHz	802.11a 6Mbps	Edge 1	0mm	Ant 2	56	5280	17.12	17.50	1.091	100	1.000	0.17	0.927	1.012
	WLAN5GHz	802.11a 6Mbps	Edge 1	0mm	Ant 2	60	5300	17.13	17.50	1.089	100	1.000	0.13	1.010	1.100
	WLAN5GHz	802.11a 6Mbps	Edge 1	0mm	Ant 2	64	5320	15.32	17.50	1.652	100	1.000	0.02	0.689	1.138
	WLAN5GHz	802.11a 6Mbps	Edge 4	0mm	Ant 2	52	5260	17.16	17.50	1.081	100	1.000	-0.1	0.098	0.106
	WLAN5GHz	802.11a 6Mbps	Bottom Face	0mm	Ant 1	116	5580	17.22	17.50	1.067	100	1.000	-0.15	0.160	0.171
03	WLAN5GHz	802.11a 6Mbps	Edge 1	0mm	Ant 1	116	5580	17.22	17.50	1.067	100	1.000	0.13	1.040	1.109
	WLAN5GHz	802.11a 6Mbps	Edge 1	0mm	Ant 1	124	5620	17.15	17.50	1.084	100	1.000	0.17	0.852	0.924
	WLAN5GHz	802.11a 6Mbps	Edge 1	0mm	Ant 1	132	5660	17.11	17.50	1.094	100	1.000	0.17	0.720	0.788
	WLAN5GHz	802.11a 6Mbps	Edge 1	0mm	Ant 1	100	5500	14.40	14.50	1.023	100	1.000	0.17	0.751	0.768
	WLAN5GHz	802.11a 6Mbps	Edge 1	0mm	Ant 1	144	5720	15.40	15.50	1.023	100	1.000	0.11	0.438	0.448
	WLAN5GHz	802.11a 6Mbps	Edge 2	0mm	Ant 1	116	5580	17.22	17.50	1.067	100	1.000	-0.15	0.203	0.217
	WLAN5GHz	802.11a 6Mbps	Bottom Face	0mm	Ant 2	116	5580	17.28	17.50	1.052	100	1.000	-0.04	0.361	0.380
	WLAN5GHz	802.11a 6Mbps	Edge 1	0mm	Ant 2	116	5580	17.28	17.50	1.052	100	1.000	0.11	0.980	1.031
	WLAN5GHz	802.11a 6Mbps	Edge 1	0mm	Ant 2	100	5500	14.24	14.50	1.062	100	1.000	0.16	0.470	0.499
	WLAN5GHz	802.11a 6Mbps	Edge 1	0mm	Ant 2	124	5620	17.20	17.50	1.072	100	1.000	0.18	0.922	0.988
	WLAN5GHz	802.11a 6Mbps	Edge 1	0mm	Ant 2	132	5660	17.19	17.50	1.074	100	1.000	0.08	0.941	1.011
	WLAN5GHz	802.11a 6Mbps	Edge 1	0mm	Ant 2	144	5720	15.22	15.50	1.067	100	1.000	0.13	0.678	0.723
	WLAN5GHz	802.11a 6Mbps	Edge 4	0mm	Ant 2	116	5580	17.28	17.50	1.052	100	1.000	-0.17	0.196	0.206
	WLAN5GHz	802.11a 6Mbps	Bottom Face	0mm	Ant 1	157	5785	17.48	17.50	1.005	100	1.000	-0.16	0.192	0.193
	WLAN5GHz	802.11a 6Mbps	Edge 1	0mm	Ant 1	157	5785	17.48	17.50	1.005	100	1.000	0.14	0.983	0.988
	WLAN5GHz	802.11a 6Mbps	Edge 1	0mm	Ant 1	149	5745	17.27	17.50	1.054	100	1.000	0.16	0.935	0.986
04	WLAN5GHz	802.11a 6Mbps	Edge 1	0mm	Ant 1	165	5825	17.17	17.50	1.079	100	1.000	0.02	1.110	1.198
	WLAN5GHz	802.11a 6Mbps	Edge 2	0mm	Ant 1	157	5785	17.48	17.50	1.005	100	1.000	-0.19	0.093	0.093
	WLAN5GHz	802.11a 6Mbps	Bottom Face	0mm	Ant 2	165	5825	17.23	17.50	1.064	100	1.000	0.06	0.184	0.196
	WLAN5GHz	802.11a 6Mbps	Edge 1	0mm	Ant 2	165	5825	17.23	17.50	1.064	100	1.000	0.12	0.895	0.952
	WLAN5GHz	802.11a 6Mbps	Edge 1	0mm	Ant 2	149	5745	17.05	17.50	1.109	100	1.000	-0.05	0.891	0.988
	WLAN5GHz	802.11a 6Mbps	Edge 1	0mm	Ant 2	157	5785	17.50	17.50	1.000	100	1.000	0.12	0.864	0.864
	WLAN5GHz	802.11a 6Mbps	Edge 4	0mm	Ant 2	165	5825	17.23	17.50	1.064	100	1.000	-0.13	0.141	0.150

Report No.: FA8D0418

TEL: 886-3-327-3456 Page 33 of 37 FAX: 886-3-328-4978 Issued Date: Jan. 23, 2019

### 14.2 Repeated SAR Measurement

No.	Band	Mode	Test Position	Gap (mm)	Antenna	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)		Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Ratio	Reported 1g SAR (W/kg)
1st	WLAN5GHz	802.11a 6Mbps	Edge 1	0mm	Ant 1	60	5300	17.42	17.50	1.019	100	1.000	0.17	1.150		1.171
2nd	WLAN5GHz	802.11a 6Mbps	Edge 1	0mm	Ant 1	60	5300	17.42	17.50	1.019	100	1.000	0.06	1.140	1.01	1.161
1st	WLAN5GHz	802.11a 6Mbps	Edge 1	0mm	Ant 1	116	5580	17.22	17.50	1.067	100	1.000	0.13	1.040		1.109
2nd	WLAN5GHz	802.11a 6Mbps	Edge 1	0mm	Ant 1	116	5580	17.22	17.50	1.067	100	1.000	0.14	1.030	1.01	1.099
1st	WLAN5GHz	802.11a 6Mbps	Edge 1	0mm	Ant 1	165	5825	17.17	17.50	1.079	100	1.000	0.02	1.110		1.198
2nd	WLAN5GHz	802.11a 6Mbps	Edge 1	0mm	Ant 1	165	5825	17.17	17.50	1.079	100	1.000	0.18	1.090	1.02	1.176

Report No.: FA8D0418

#### **General Note:**

- 1. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥0.8W/kg.
- 2. Per KDB 865664 D01v01r04, if the ratio among the repeated measurement is ≤ 1.2 and the measured SAR <1.45W/kg, only one repeated measurement is required.
- 3. The ratio is the difference in percentage between original and repeated *measured SAR*.
- 4. All measurement SAR result is scaled-up to account for tune-up tolerance and is compliant.

TEL: 886-3-327-3456 Page 34 of 37
FAX: 886-3-328-4978 Issued Date: Jan. 23, 2019

### 15. Simultaneous Transmission Analysis

NO.	Simultaneous Transmission Configurations	Body
1.	2.4GHz WLAN ANT 1 + 2.4GHz WLAN ANT 2	Yes
2.	5GHz WLAN ANT 1 + 5GHz WLAN ANT 2	Yes
3.	2.4GHz WLAN ANT 1+ Bluetooth ANT 2	Yes
4.	5GHz WLAN ANT 1 + Bluetooth ANT 2	Yes

#### **General Note:**

 For SAR testing was performed on single antenna RF power in SISO mode is larger or equal to the single antenna RF power in MIMO mode, and for RF exposure assessment of MIMO mode simultaneous transmission exclusion analysis was performed with SAR test results of each antenna in SISO mode.

Report No.: FA8D0418

- 2. WLAN and Bluetooth share the same antenna 2, and cannot transmit simultaneously.
- 3. EUT will choose either WLAN 2.4GHz or WLAN 5GHz according to the network signal condition; therefore, 2.4GHz WLAN and 5GHz WLAN will not operate simultaneously at any moment.
- 4. The Scaled SAR summation is calculated based on the same configuration and test position.
- 5. Per KDB 447498 D01v06, simultaneous transmission SAR is compliant if,
  - i) Scalar SAR summation < 1.6W/kg.
  - ii) SPLSR = (SAR1 + SAR2)^1.5 / (min. separation distance, mm), and the peak separation distance is determined from the square root of [(x1-x2)2 + (y1-y2)2 + (z1-z2)2], where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
  - iii) If SPLSR ≤ 0.04, simultaneously transmission SAR measurement is not necessary.
  - iv) Simultaneously transmission SAR measurement, and the reported multi-band SAR < 1.6W/kg.
- For simultaneous transmission analysis, Bluetooth SAR is estimated per KDB 447498 D01v06 based on the formula below.
  - i) (max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]·  $[\sqrt{f(GHz)/x}]$  W/kg for test separation distances  $\leq$  50 mm; where x = 7.5 for 1-g SAR, and x = 18.75 for 10-g SAR.
  - ii) When the minimum separation distance is < 5mm, the distance is used 5mm to determine SAR test exclusion.
  - iii) 0.4 W/kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distances is > 50 mm.
  - iv) Bluetooth estimated SAR is conservatively determined by 5mm separation, for all applicable exposure positions.

Bluetooth Max Power	Exposure Position	All Positions
5.5 dBm	Estimated SAR (W/kg)	0.149 W/kg

TEL: 886-3-327-3456 Page 35 of 37
FAX: 886-3-328-4978 Issued Date: Jan. 23, 2019

## 15.1 Body Exposure Conditions


	1	2	3	4	5					SPLSR	
Exposure Position	2.4GHz WLAN Ant 1	2.4GHz WLAN Ant 2	5GHz WLAN Ant 1	5GHz WLAN Ant 2	Bluetooth Ant 2	1+2 Summed 1g SAR	3+4 Summed 1g SAR (W/kg)	1+5 Summed 1g SAR (W/kg)	3+5 Summed 1g SAR (W/kg)		Case No
	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	Estimated 1g SAR (W/kg)	(W/kg)					
Bottom Face at 0mm	0.196	0.253	0.349	0.380	0.149	0.449	0.729	0.345	0.498		
Edge 1 at 0mm	0.485	0.547	1.198	1.138	0.149	1.032	2.336	0.634	1.347	0.02	Case1
Edge 2 at 0mm			0.217		0.149	0.000	0.217	0.149	0.366		
Edge 4 at 0mm				0.206	0.149	0.000	0.206	0.149	0.149		

Report No.: FA8D0418

### 15.2 SPLSR Evaluation and Analysis

#### **General Note:**

SPLSR = (SAR<sub>1</sub> + SAR<sub>2</sub>)<sup>1.5</sup> / (min. separation distance, mm). If SPLSR ≤ 0.04, simultaneously transmission SAR measurement is not necessary



Test Engineer: Andy Jiang, Ted Hsieh, Neil Hsiang, Nick Yu and Wilson Lin

TEL: 886-3-327-3456 Page 36 of 37
FAX: 886-3-328-4978 Issued Date: Jan. 23, 2019

## 16. Uncertainty Assessment

Per KDB 865664 D01 SAR measurement 100MHz to 6GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg and the measured 10-g SAR within a frequency band is < 3.75 W/kg. The expanded SAR measurement uncertainty must be  $\leq$  30%, for a confidence interval of k = 2. If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. For this device, the highest measured 1-g SAR is less 1.5W/kg. Therefore, the measurement uncertainty table is not required in this report.

Report No.: FA8D0418

## 17. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", Sep 2013
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 248227 D01 v02r02, "SAR Guidance for IEEE 802.11 (WiFi) Transmitters", Oct 2015.
- [6] FCC KDB 447498 D01 v06, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", Oct 2015
- [7] FCC KDB 616217 D04 v01r02, "SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers", Oct 2015
- [8] FCC KDB 865664 D01 v01r04, "SAR Measurement Requirements for 100 MHz to 6 GHz", Aug 2015.
- [9] FCC KDB 865664 D02 v01r02, "RF Exposure Compliance Reporting and Documentation Considerations" Oct 2015.

TEL: 886-3-327-3456 Page 37 of 37 FAX: 886-3-328-4978 Issued Date: Jan. 23, 2019