

# **FCC SAR Test Report**

Report No. : SA181129C17D

Applicant : Realtek Semiconductor Corp.

Address : No.2,Innovation Road II,Hsinchu Seience Park Hsinchu 300,Taiwan

Product : 802.11a/b/g/n/ac RTL8822BE Combo module

FCC ID : TX2-RTL8822BE

Brand : REALTEK

Model No. : RTL8822BE

Standards : FCC 47 CFR Part 2 (2.1093), IEEE C95.1:1992, IEEE Std 1528:2013

KDB 865664 D01 v01r04, KDB 865664 D02 v01r02, KDB 248227 D01 v02r02,

KDB 447498 D01 v06, KDB 616217 D04 v01r02

Sample Received Date : Nov. 29, 2018

Date of Testing : Dec. 25, 2018 ~ Dec. 28, 2018

Lab Address : No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan, R.O.C.

Test Location : No. 19, Hwa Ya 2nd Rd, Wen Hwa Vil, Kwei Shan Dist., Taoyuan City 33383, Taiwan (R.O.C)

**CERTIFICATION:** The above equipment have been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch – Lin Kou Laboratories**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's SAR characteristics under the conditions specified in this report. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by TAF or any government agencies.

Prepared By:

Rona Chen / Specialist

Approved By:

Gordon Lin / Assistant Manager



FCC Accredited No.: TW0003

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Report Format Version 5.0.0 Page No. : 1 of 38
Report No.: SA181129C17D Issued Date : Jan. 14, 2019



Page No.

: 2 of 38

Issued Date : Jan. 14, 2019

# **Table of Contents**

Rel	ease (	Control Record	3
1.	Sumi	mary of Maximum SAR Value	
2.	Desc	ription of Equipment Under Test	
3.		Measurement System	
	3.1	Definition of Specific Absorption Rate (SAR)	
	3.2	SPEAG DASY52 System	
	0	3.2.1 Robot	
		3.2.2 Probes	
		3.2.3 Data Acquisition Electronics (DAE)	
		3.2.4 Phantoms	
		3.2.5 Device Holder	
		3.2.6 System Validation Dipoles	
		3.2.7 Tissue Simulating Liquids	
	3.3	SAR System Verification	
	3.4	SAR Measurement Procedure	
		3.4.1 Area & Zoom Scan Procedure	
		3.4.2 Volume Scan Procedure	
		3.4.3 Power Drift Monitoring	
		3.4.4 Spatial Peak SAR Evaluation	
		3.4.5 SAR Averaged Methods	
4.	SAR	Measurement Evaluation	
	4.1	EUT Configuration and Setting	
	4.2	EUT Testing Position	
		4.2.1 Body Exposure Conditions	
		4.2.2 SAR Test Exclusion Evaluations	
	4.3	Tissue Verification	
	4.4	System Validation	
	4.5	System Verification	
	4.6	Maximum Output Power	
		4.6.1 Maximum Target Conducted Power	
		4.6.2 Measured Conducted Power Result	
	4.7	SAR Testing Results	
		4.7.1 SAR Test Reduction Considerations	27
		4.7.2 SAR Results for Body Exposure Condition (Test Separation Distance is 0 mm)	28
		4.7.3 SAR Measurement Variability	31
		4.7.4 Simultaneous Multi-band Transmission Evaluation	31
5.	Calib	ration of Test Equipment	
6.		surement Uncertainty	
7.		mation on the Testing Laboratories	

Appendix A. SAR Plots of System Verification Appendix B. SAR Plots of SAR Measurement Appendix C. Calibration Certificate for Probe and Dipole

Appendix D. Photographs of EUT and Setup



# **Release Control Record**

Report No.	Reason for Change	Date Issued
SA181129C17D	Initial release	Jan. 14, 2019

Report Format Version 5.0.0 Page No. : 3 of 38
Report No.: SA181129C17D Issued Date : Jan. 14, 2019



# 1. Summary of Maximum SAR Value

Equipment Class	Mode	Bo Tested	t SAR-1g ody at 0 mm //kg)
		Laptop PC Mode	Tablet PC Mode
DTS	2.4G WLAN	<mark>0.17</mark>	0.46
	5.3G WLAN	N/A	<mark>1.11</mark>
NII	5.6G WLAN	0.16	0.69
	5.8G WLAN	0.07	0.49
DSS	Bluetooth	N/A	N/A

Highest Simultaneous Transmission SAR	Bo Tested	SAR-1g ody at 0 mm /kg)
	Laptop PC Mode	Tablet PC Mode
	0.33	1.28

#### Note:

1. The SAR criteria (Head & Body: SAR-1g 1.6 W/kg, and Extremity: SAR-10g 4.0 W/kg) for general population / uncontrolled exposure is specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992.

 Report Format Version 5.0.0
 Page No.
 : 4 of 38

 Report No. : SA181129C17D
 Issued Date : Jan. 14, 2019



# 2. <u>Description of Equipment Under Test</u>

EUT Type	802.11a/b/g/n/ac RTL8822BE Combo module
FCC ID	TX2-RTL8822BE
Brand Name	REALTEK
Model Name	RTL8822BE
EUT Configurations	EUT 1: with High-Tek Antenna
EOT Comigurations	EUT 2: with Yageo Antenna
Tx Frequency Bands	WLAN : 2412 ~ 2472, 5180 ~ 5240, 5260 ~ 5320, 5500 ~ 5720, 5745 ~ 5825
(Unit: MHz)	Bluetooth : 2402 ~ 2480
	802.11b: DSSS
	802.11a/g/n/ac : OFDM
	Bluetooth : GFSK, π/4-DQPSK, 8-DPSK
Maximum Tune-up Conducted Power	Please refer to section 4.6.1 of this report
(Unit: dBm)	r lease relet to section 4.0.1 of this report
Antenna Type	Refer to Note as below
EUT Stage	Engineering Sample

#### Note:

1. The EUT was installed in a specific End-product.

Equipment Name	Brand Name	Model Name
	Lenovo	Lenovo IdeaPad C340-14IWL*******, 81N4******,
		Lenovo IdeaPad FLEX-14IWL*******, 81SQ*******,
Notaback Computer		Lenovo IdeaPad C340-14API*******, 81N6*******,
Notebook Computer		Lenovo IdeaPad FLEX-14API*******, 81SS*******
		(*=0~9, A~Z, a~z, "- " or blank, for marketing use only,
		with no impact on RF compliance of the product)

2. The antenna information is listed as below.

		Manufacturer Parts Number	Antenna Gain			
Antenna Type	Manufacturer		WLAN 2.4 GHz	WLAN 5.15~5.35 GHz	WLAN 5.47~5.725 GHz	WLAN 5.725~5.85 GHz
DIE	High-Tek Electronics Co., Ltd.	Main Ant.: 0ACCN018020N (DC330029800) Aux Ant.: 0ACCN018020N (DC330029800)	Main: 1.79 Aux.: -0.76	Main: 2.44 Aux.: -0.40	Main: 2.01 Aux.: -0.24	Main: 0.75 Aux.: 0.31
PIFA	Yageo Corporation	Main Ant.: ANTA0LC13162WLAN3 (DC330029J20) Aux Ant.: ANTA0LC13162WLAN3 (DC330029J20)	Main: -0.36 Aux.: -0.96	Main: 2.05 Aux.: 0.35	Main: 1.69 Aux.: 0.04	Main: 1.69 Aux.: 0.04

3. The above EUT information is declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or User's Manual.

# **List of Accessory of End-product:**

	Brand Name	Lenovo
Battery	Model Name	L18M4PF3
Daller y	Power Rating	15.36 Vdc, 2965 mAh
	Туре	Li-ion Li-ion

Report Format Version 5.0.0 Page No. : 5 of 38
Report No. : SA181129C17D Issued Date : Jan. 14, 2019



# 3. SAR Measurement System

# 3.1 Definition of Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (p). The equation description is as below:

$$SAR = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where:  $\sigma$  is the conductivity of the tissue,  $\rho$  is the mass density of the tissue and E is the RMS electrical field strength.

# 3.2 SPEAG DASY52 System

DASY52 system consists of high precision robot, probe alignment sensor, phantom, robot controller, controlled measurement server and near-field probe. The robot includes six axes that can move to the precision position of the DASY52 software defined. The DASY52 software can define the area that is detected by the probe. The robot is connected to controlled box. Controlled measurement server is connected to the controlled robot box. The DAE includes amplifier, signal multiplexing, AD converter, offset measurement and surface detection. It is connected to the Electro-optical coupler (ECO). The ECO performs the conversion form the optical into digital electric signal of the DAE and transfers data to the PC.

Report Format Version 5.0.0 Page No. : 6 of 38
Report No.: SA181129C17D Issued Date : Jan. 14, 2019






Fig-3.1 SPEAG DASY52 System Setup

#### 3.2.1 Robot

The DASY52 systems use the high precision robots from Stäubli SA (France). For the 6-axis controller system, the robot controller version of CS8c from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability ±0.035 mm)
- · High reliability (industrial design)
- · Jerk-free straight movements
- · Low ELF interference (the closed metallic construction shields against motor control fields)



Report Format Version 5.0.0 Report No. : SA181129C17D Reference No. : 181129C22 Page No. : 7 of 38
Issued Date : Jan. 14, 2019



#### 3.2.2 Probes

The SAR measurement is conducted with the dosimetric probe. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency.

Model	EX3DV4	
Construction	Symmetrical design with triangular core. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).	
Frequency	10 MHz to 6 GHz Linearity: ± 0.2 dB	
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)	
Dynamic Range	10 μW/g to 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μW/g)	
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

Model	ES3DV3	
Construction	Symmetrical design with triangular core. Interleaved sensors. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).	
Frequency	10 MHz to 4 GHz Linearity: ± 0.2 dB	
Directivity	± 0.2 dB in HSL (rotation around probe axis) ± 0.3 dB in tissue material (rotation normal to probe axis)	
Dynamic Range	5 μW/g to 100 mW/g Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 3.9 mm (Body: 12 mm) Distance from probe tip to dipole centers: 2.0 mm	

Model	ET3DV6	200
Construction	Symmetrical design with triangular core Built-in optical fiber for surface detection system.  Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz to 2.3 GHz; Linearity: ± 0.2 dB	
Directivity	± 0.2 dB in TSL (rotation around probe axis) ± 0.4 dB in TSL (rotation normal to probe axis)	
Dynamic Range	5 μW/g to 100 mW/g; Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (Tip: 16 mm) Tip diameter: 6.8 mm (Body: 12 mm) Distance from probe tip to dipole centers: 2.7 mm	

# 3.2.3 Data Acquisition Electronics (DAE)

Model	DAE3, DAE4		
Construction	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop.		
Measurement	-100 to +300 mV (16 bit resolution and two range settings: 4mV,		
Range	400mV)	Malbert Made	
Input Offset Voltage	< 5μV (with auto zero)		
Input Bias Current	< 50 fA		
Dimensions	60 x 60 x 68 mm		

Report Format Version 5.0.0 Report No. : SA181129C17D Reference No. : 181129C22 Page No. : 8 of 38 Issued Date : Jan. 14, 2019



# 3.2.4 Phantoms

=		
Model	Twin SAM	
Construction	The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.	
Material	Vinylester, glass fiber reinforced (VE-GF)	
Shell Thickness	2 ± 0.2 mm (6 ± 0.2 mm at ear point)	
Dimensions	Length: 1000 mm Width: 500 mm Height: adjustable feet	
Filling Volume	approx. 25 liters	



Model	ELI
Construction	Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.
Material	Vinylester, glass fiber reinforced (VE-GF)
Shell Thickness	$2.0 \pm 0.2$ mm (bottom plate)
Dimensions	Major axis: 600 mm Minor axis: 400 mm
Filling Volume	approx. 30 liters



Report Format Version 5.0.0 Report No. : SA181129C17D Reference No. : 181129C22 Page No. : 9 of 38
Issued Date : Jan. 14, 2019



# 3.2.5 Device Holder

Model	Mounting Device	
Construction	In combination with the Twin SAM Phantom or ELI4, the Mounting Device enables the rotation of the mounted transmitter device in spherical coordinates. Rotation point is the ear opening point. Transmitter devices can be easily and accurately positioned according to IEC, IEEE, FCC or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat).	
Material	POM	

Model	Laptop Extensions Kit	
Construction	Simple but effective and easy-to-use extension for Mounting Device that facilitates the testing of larger devices according to IEC 62209-2 (e.g., laptops, cameras, etc.). It is lightweight and fits easily on the upper part of the Mounting Device in place of the phone positioner.	
Material	POM, Acrylic glass, Foam	

# 3.2.6 System Validation Dipoles

Model	D-Serial	
<b>Construction</b> Symmetrical dipole with I/4 balun. Enables measurement of feed point impedance with NWA. Matched for use near flat phantoms filled with tissue simulating solutions.		
Frequency	750 MHz to 5800 MHz	
Return Loss	> 20 dB	
Power Capability	> 100 W (f < 1GHz), > 40 W (f > 1GHz)	


 Report Format Version 5.0.0
 Page No.
 : 10 of 38

 Report No.: SA181129C17D
 Issued Date
 : Jan. 14, 2019



### 3.2.7 Tissue Simulating Liquids

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5% are listed in Table-3.1.



The dielectric properties of the head tissue simulating liquids are defined in IEEE 1528, and KDB 865664 D01 Appendix A. For the body tissue simulating liquids, the dielectric properties are defined in KDB 865664 D01 Appendix A. The dielectric properties of the tissue simulating liquids were verified prior to the SAR evaluation using a dielectric assessment kit and a network analyzer.

 Report Format Version 5.0.0
 Page No. : 11 of 38

 Report No. : SA181129C17D
 Issued Date : Jan. 14, 2019



**Table-3.1 Targets of Tissue Simulating Liquid** 

Frequency	Frequency Target Range of Target Range of											
(MHz)	Target Permittivity	Range of ±5%	Target Conductivity	Range of ±5%								
		For Head										
750	41.9	39.8 ~ 44.0	0.89	0.85 ~ 0.93								
835	41.5	39.4 ~ 43.6	0.90	0.86 ~ 0.95								
900	41.5	39.4 ~ 43.6	0.97	0.92 ~ 1.02								
1450	40.5	38.5 ~ 42.5	1.20	1.14 ~ 1.26								
1640	40.3	38.3 ~ 42.3	1.29	1.23 ~ 1.35								
1750	40.1	38.1 ~ 42.1	1.37	1.30 ~ 1.44								
1800	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47								
1900	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47								
2000	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47								
2300	39.5	37.5 ~ 41.5	1.67	1.59 ~ 1.75								
2450	39.2	37.2 ~ 41.2	1.80	1.71 ~ 1.89								
2600	39.0	37.1 ~ 41.0	1.96	1.86 ~ 2.06								
3500	37.9	36.0 ~ 39.8	2.91	2.76 ~ 3.06								
5200	36.0	34.2 ~ 37.8	4.66	4.43 ~ 4.89								
5300	35.9	34.1 ~ 37.7	4.76	4.52 ~ 5.00								
5500	35.6	33.8 ~ 37.4	4.96	4.71 ~ 5.21								
5600	35.5	33.7 ~ 37.3	5.07	4.82 ~ 5.32								
5800	35.3	33.5 ~ 37.1	5.27	5.01 ~ 5.53								
		For Body	•	•								
750	55.5	52.7 ~ 58.3	0.96	0.91 ~ 1.01								
835	55.2	52.4 ~ 58.0	0.97	0.92 ~ 1.02								
900	55.0	52.3 ~ 57.8	1.05	1.00 ~ 1.10								
1450	54.0	51.3 ~ 56.7	1.30	1.24 ~ 1.37								
1640	53.8	51.1 ~ 56.5	1.40	1.33 ~ 1.47								
1750	53.4	50.7 ~ 56.1	1.49	1.42 ~ 1.56								
1800	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60								
1900	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60								
2000	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60								
2300	52.9	50.3 ~ 55.5	1.81	1.72 ~ 1.90								
2450	52.7	50.1 ~ 55.3	1.95	1.85 ~ 2.05								
2600	52.5	49.9 ~ 55.1	2.16	2.05 ~ 2.27								
3500	51.3	48.7 ~ 53.9	3.31	3.14 ~ 3.48								
5200	49.0	46.6 ~ 51.5	5.30	5.04 ~ 5.57								
5300	48.9	46.5 ~ 51.3	5.42	5.15 ~ 5.69								
5500	48.6	46.2 ~ 51.0	5.65	5.37 ~ 5.93								
5600	48.5	46.1 ~ 50.9	5.77	5.48 ~ 6.06								
5800	48.2	45.8 ~ 50.6	6.00	5.70 ~ 6.30								

Report Format Version 5.0.0 Page No. : 12 of 38
Report No.: SA181129C17D Issued Date : Jan. 14, 2019





The following table gives the recipes for tissue simulating liquids.

**Table-3.2 Recipes of Tissue Simulating Liquid** 

Tissue Type	Bactericide	DGBE	HEC	NaCl	NaCl Sucrose		Water	Diethylene Glycol Mono- hexylether
H750	0.2	-	0.2	1.5	56.0	-	42.1	-
H835	0.2	-	0.2	1.5	57.0	-	41.1	-
H900	0.2	-	0.2	1.4	58.0	-	40.2	-
H1450	-	43.3	-	0.6	-	-	56.1	-
H1640	-	45.8	-	0.5	-	-	53.7	-
H1750	-	47.0	-	0.4	-	-	52.6	-
H1800	-	44.5	-	0.3	-	-	55.2	-
H1900	-	44.5	-	0.2	-	-	55.3	-
H2000	-	44.5	-	0.1	-	-	55.4	-
H2300	-	44.9	-	0.1	-	-	55.0	-
H2450	-	45.0	-	0.1	-	-	54.9	-
H2600	-	45.1	-	0.1	-	-	54.8	-
H3500	-	8.0	-	0.2	-	20.0	71.8	-
H5G	-		-	-	-	17.2	65.5	17.3
B750	0.2	-	0.2	0.8	48.8	-	50.0	-
B835	0.2	-	0.2	0.9	48.5	-	50.2	-
B900	0.2	-	0.2	0.9	48.2	-	50.5	-
B1450	-	34.0	-	0.3	-	-	65.7	-
B1640	-	32.5	-	0.3	-	-	67.2	-
B1750	-	31.0	-	0.2	-	-	68.8	-
B1800	-	29.5	-	0.4	-	-	70.1	-
B1900	-	29.5	-	0.3	-	-	70.2	-
B2000	-	30.0	-	0.2	-	-	69.8	-
B2300	-	31.0	-	0.1	-	-	68.9	-
B2450	-	31.4	-	0.1	-	-	68.5	-
B2600	-	31.8	-	0.1	-	-	68.1	-
B3500	-	28.8	-	0.1	-	-	71.1	-
B5G	-	-	-	-	-	10.7	78.6	10.7


 Report Format Version 5.0.0
 Page No.
 : 13 of 38

 Report No. : SA181129C17D
 Issued Date : Jan. 14, 2019



# 3.3 SAR System Verification

The system check verifies that the system operates within its specifications. It is performed daily or before every SAR measurement. The system check uses normal SAR measurements in the flat section of the phantom with a matched dipole at a specified distance. The system verification setup is shown as below.



The validation dipole is placed beneath the flat phantom with the specific spacer in place. The distance spacer is touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The spectrum analyzer measures the forward power at the location of the system check dipole connector. The signal generator is adjusted for the desired forward power (250 mW is used for 700 MHz to 3 GHz, 100 mW is used for 3.5 GHz to 6 GHz) at the dipole connector and the power meter is read at that level. After connecting the cable to the dipole, the signal generator is readjusted for the same reading at power meter.

After system check testing, the SAR result will be normalized to 1W forward input power and compared with the reference SAR value derived from validation dipole certificate report. The deviation of system check should be within 10 %.

Report Format Version 5.0.0 Page No. : 14 of 38
Report No.: SA181129C17D Issued Date : Jan. 14, 2019



### 3.4 SAR Measurement Procedure

According to the SAR test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

The SAR measurement procedures for each of test conditions are as follows:

- (a) Make EUT to transmit maximum output power
- (b) Measure conducted output power through RF cable
- (c) Place the EUT in the specific position of phantom
- (d) Perform SAR testing steps on the DASY system
- (e) Record the SAR value

#### 3.4.1 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. According to KDB 865664 D01, the resolution for Area and Zoom scan is specified in the table below.

Items	<= 2 GHz	2-3 GHz	3-4 GHz	4-5 GHz	5-6 GHz
Area Scan (Δx, Δy)	<= 15 mm	<= 12 mm	<= 12 mm	<= 10 mm	<= 10 mm
Zoom Scan (Δx, Δy)	<= 8 mm	<= 5 mm	<= 5 mm	<= 4 mm	<= 4 mm
Zoom Scan (Δz)	<= 5 mm	<= 5 mm	<= 4 mm	<= 3 mm	<= 2 mm
Zoom Scan Volume	>= 30 mm	>= 30 mm	>= 28 mm	>= 25 mm	>= 22 mm

#### Note:

When zoom scan is required and report SAR is <= 1.4 W/kg, the zoom scan resolution of  $\Delta x / \Delta y$  (2-3GHz: <= 8 mm, 3-4GHz: <= 7 mm, 4-6GHz: <= 5 mm) may be applied.

#### 3.4.2 Volume Scan Procedure

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

Report Format Version 5.0.0 Page No. : 15 of 38
Report No.: SA181129C17D Issued Date : Jan. 14, 2019



#### 3.4.3 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

#### 3.4.4 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values form the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

#### 3.4.5 SAR Averaged Methods

In DASY, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.

Report Format Version 5.0.0 Page No. : 16 of 38
Report No.: SA181129C17D Issued Date : Jan. 14, 2019



# 4. SAR Measurement Evaluation

### 4.1 EUT Configuration and Setting

#### <Considerations Related to WLAN for Setup and Testing>

In general, various vendor specific external test software and chipset based internal test modes are typically used for SAR measurement. These chipset based test mode utilities are generally hardware and manufacturer dependent, and often include substantial flexibility to reconfigure or reprogram a device. A Wi-Fi device must be configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools for SAR measurement. The test frequencies established using test mode must correspond to the actual channel frequencies. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. In addition, a periodic transmission duty factor is required for current generation SAR systems to measure SAR correctly. The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

According to KDB 248227 D01, this device has installed WLAN engineering testing software which can provide continuous transmitting RF signal. During WLAN SAR testing, this device was operated to transmit continuously at the maximum transmission duty with specified transmission mode, operating frequency, lowest data rate, and maximum output power.

#### **Initial Test Configuration**

An initial test configuration is determined for OFDM transmission modes in 2.4 GHz and 5 GHz bands according to the channel bandwidth, modulation and data rate combination(s) with the highest maximum output power specified for production units in each standalone and aggregated frequency band. When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel in the initial test configuration, for each frequency band.

# **Subsequent Test Configuration**

SAR measurement requirements for the remaining 802.11 transmission mode configurations that have not been tested in the initial test configuration are determined separately for each standalone and aggregated frequency band, in each exposure condition, according to the maximum output power specified for production units. Additional power measurements may be required to determine if SAR measurements are required for subsequent highest output power channels in a subsequent test configuration. When the highest reported SAR for the initial test configuration according to the initial test position or fixed exposure position requirements, is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for that subsequent test configuration.

Report Format Version 5.0.0 Page No. : 17 of 38
Report No.: SA181129C17D Issued Date : Jan. 14, 2019



#### **SAR Test Configuration and Channel Selection**

When multiple channel bandwidth configurations in a frequency band have the same specified maximum output power, the initial test configuration is using largest channel bandwidth, lowest order modulation, lowest data rate, and lowest order 802.11 mode (i.e., 802.11a is chosen over 802.11n then 802.11ac or 802.11g is chosen over 802.11n). After an initial test configuration is determined, if multiple test channels have the same measured maximum output power, the channel chosen for SAR measurement is determined according to the following.

- 1) The channel closest to mid-band frequency is selected for SAR measurement.
- 2) For channels with equal separation from mid-band frequency; for example, high and low channels or two mid-band channels, the higher frequency (number) channel is selected for SAR measurement.

#### Test Reduction for U-NII-1 (5.2 GHz) and U-NII-2A (5.3 GHz) Bands

For devices that operate in both U-NII bands using the same transmitter and antenna(s), SAR test reduction is determined according to the following.

- 1) When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition).
- 2) When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is  $\leq 1.2$  W/kg, SAR is not required for the band with lower maximum output power in that test configuration.

### **4.2 EUT Testing Position**

#### 4.2.1 Body Exposure Conditions

For laptop PC, according to KDB 616217 D04, SAR evaluation is required for the bottom surface of the keyboard. This EUT was tested in the base of EUT directly against the flat phantom. The required minimum test separation distance for incorporating transmitters and antennas into laptop computer display is determined with the display screen opened at an angle of 90° to the keyboard compartment.




Fig-4.1 Illustration for Laptop Setup

 Report Format Version 5.0.0
 Page No.
 : 18 of 38

 Report No. : SA181129C17D
 Issued Date : Jan. 14, 2019

# **FCC SAR Test Report**

For full-size tablet, according to KDB 616217 D04, SAR evaluation is required for back surface and edges of the devices. The back surface and edges of the tablet are tested with the tablet touching the phantom. Exposures from antennas through the front surface of the display section of a tablet are generally limited to the user's hands. Exposures to hands for typical consumer transmitters used in tablets are not expected to exceed the extremity SAR limit; therefore, SAR evaluation for the front surface of tablet display screens are generally not necessary. When voice mode is supported on a tablet and it is limited to speaker mode or headset operations only, additional SAR testing for this type of voice use is not required.




Fig-4.2 Illustration for Tablet Setup

 Report Format Version 5.0.0
 Page No. : 19 of 38

 Report No. : SA181129C17D
 Issued Date : Jan. 14, 2019



#### 4.2.2 SAR Test Exclusion Evaluations

According to KDB 447498 D01, the SAR test exclusion condition is based on source-based time-averaged maximum conducted output power, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions. The SAR exclusion threshold is determined by the following formula.

1. For the test separation distance <= 50 mm

$$\frac{\text{Max. Tune up Power}_{(mW)}}{\text{Min. Test Separation Distance}_{(mm)}} \times \sqrt{f_{(GHz)}} \le 3.0 \text{ for SAR-1g,} \le 7.5 \text{ for SAR-10g}$$

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

2. For the test separation distance > 50 mm, and the frequency at 100 MHz to 1500 MHz

$$\left[ \text{(Threshold at 50 mm in Step 1)} + \text{(Test Separation Distance} - 50 mm) \times \left( \frac{f_{\text{(MHz)}}}{150} \right) \right]_{\text{(mW)}}$$

3. For the test separation distance > 50 mm, and the frequency at > 1500 MHz to 6 GHz  $[ (Threshold at 50 mm in Step 1) + (Test Separation Distance - 50 mm) \times 10 ]_{(mW)}$ 

#### **Laptop PC Mode**

### <For WLAN Ant-0>

	Max.	Max.		Bottom Side	
Mode	Tune-up Power (dBm)	Tune-up Power (mW)	Ant. to Surface (mm)		
WLAN 2.4G	17.2	52.0	16.92	4.82	Yes
WLAN 5.2G	13.5	22.0	16.92	2.98	No
WLAN 5.3G	13.5	22.0	16.92	3	No
WLAN 5.6G	13.5	22.0	16.92	3.11	Yes
WLAN 5.8G	13.5	22.0	16.92	3.14	Yes

#### <For BT/WLAN Ant-1>

	Max.	Max.		Bottom Side	
Mode	Tune-up Power (dBm)	Tune-up Power (mW)	Ant. to Surface (mm)	Calculated Result	Require SAR Testing?
WLAN 2.4G	17.2	52.0	16.92	4.82	Yes
WLAN 5.2G	13.5	22.0	16.92	2.98	No
WLAN 5.3G	13.5	22.0	16.92	3	No
WLAN 5.6G	13.5	22.0	16.92	3.11	Yes
WLAN 5.8G	13.5	22.0	16.92	3.14	Yes
ВТ	6.0	4.0	16.92	0.37	No

Report Format Version 5.0.0 Page No. : 20 of 38
Report No.: SA181129C17D Issued Date : Jan. 14, 2019



### <For WLAN Ant-0 + WLAN Ant-1>

	Max.	Max.		Bottom Side		
Mode	Tune-up Power (dBm)	Tune-up Power (mW)	Ant. to Surface (mm)			
WLAN 2.4G	18.0	63.0	16.92	5.84	Yes	
WLAN 5.2G	13.5	22.0	16.92	2.98	No	
WLAN 5.3G	13.5	22.0	16.92	3	No	
WLAN 5.6G	13.5	22.0	16.92	3.11	Yes	
WLAN 5.8G	13.5	22.0	16.92	3.14	Yes	

#### **Tablet PC Mode**

### <For WLAN Ant-0>

	Max.	Max.		Rear Face			Left Side			Right Side			Top Side			Bottom Side	
Mode	Tune-up Power (dBm)	Tune-up Power (mW)	Ant. to Surface (mm)	Calculated Result	Require SAR Testing?												
WLAN 2.4G	17.2	52.0	5	19.77	Yes	223.8	1834 mW	No	60.25	198 mW	No	210.76	1703 mW	No	5.02	19.69	Yes
WLAN 5.2G	13.5	22.0	5	10.07	Yes	223.8	1804 mW	No	60.25	168 mW	No	210.76	1673 mW	No	5.02	10.03	Yes
WLAN 5.3G	13.5	22.0	5	10.15	Yes	223.8	1803 mW	No	60.25	168 mW	No	210.76	1673 mW	No	5.02	10.11	Yes
WLAN 5.6G	13.5	22.0	5	10.52	Yes	223.8	1801 mW	No	60.25	165 mW	No	210.76	1670 mW	No	5.02	10.48	Yes
WLAN 5.8G	13.5	22.0	5	10.62	Yes	223.8	1800 mW	No	60.25	165 mW	No	210.76	1670 mW	No	5.02	10.58	Yes

### <For BT/WLAN Ant-1>

	Max.	Max.		Rear Face			Left Side		Right Side		Top Side		, and the second		Bottom Side		
Mode	Tune-up Power (dBm)	Tune-up Power (mW)	Ant. to Surface (mm)	Calculated Result	Require SAR Testing?												
WLAN 2.4G	17.2	52.0	5	19.77	Yes	69.2	288 mW	No	222.8	1824 mW	No	210.76	1703 mW	No	5.02	19.69	Yes
WLAN 5.2G	13.5	22.0	5	10.07	Yes	69.2	258 mW	No	222.8	1794 mW	No	210.76	1673 mW	No	5.02	10.03	Yes
WLAN 5.3G	13.5	22.0	5	10.15	Yes	69.2	257 mW	No	222.8	1793 mW	No	210.76	1673 mW	No	5.02	10.11	Yes
WLAN 5.6G	13.5	22.0	5	10.52	Yes	69.2	255 mW	No	222.8	1791 mW	No	210.76	1670 mW	No	5.02	10.48	Yes
WLAN 5.8G	13.5	22.0	5	10.62	Yes	69.2	254 mW	No	222.8	1790 mW	No	210.76	1670 mW	No	5.02	10.58	Yes
ВТ	6.0	4.0	5	1.26	No	69.2	288 mW	No	222.8	1824 mW	No	210.76	1703 mW	No	5.02	19.69	Yes

# <For WLAN Ant-0 + WLAN Ant-1>

	Max.	Max.		Rear Face			Left Side			Right Side			Top Side			Bottom Side	
Mode	Tune-up Power (dBm)	Tune-up Power (mW)	Ant. to Surface (mm)	Calculated Result	Require SAR Testing?												
WLAN 2.4G	18.0	63.0	5	19.77	Yes	69.2	288 mW	No	60.25	198 mW	No	210.76	1703 mW	No	5.02	19.69	Yes
WLAN 5.2G	13.5	22.0	5	10.07	Yes	69.2	258 mW	No	60.25	168 mW	No	210.76	1673 mW	No	5.02	10.03	Yes
WLAN 5.3G	13.5	22.0	5	10.15	Yes	69.2	257 mW	No	60.25	168 mW	No	210.76	1673 mW	No	5.02	10.11	Yes
WLAN 5.6G	13.5	22.0	5	10.52	Yes	69.2	255 mW	No	60.25	165 mW	No	210.76	1670 mW	No	5.02	10.48	Yes
WLAN 5.8G	13.5	22.0	5	10.62	Yes	69.2	254 mW	No	60.25	165 mW	No	210.76	1670 mW	No	5.02	10.58	Yes

 Report Format Version 5.0.0
 Page No.
 : 21 of 38

 Report No. : SA181129C17D
 Issued Date : Jan. 14, 2019



# 4.3 Tissue Verification

The measuring results for tissue simulating liquid are shown as below.

Test Date	Tissue Type	Frequency (MHz)	Liquid Temp. (℃)	Measured Conductivity (σ)	Measured Permittivity (ε <sub>r</sub> )	Target Conductivity (σ)	Target Permittivity (ε <sub>r</sub> )	Conductivity Deviation (%)	Permittivity Deviation (%)
Dec. 25, 2018	Body	2450	23.3	2.016	51.542	1.95	52.7	3.38	-2.20
Dec. 28, 2018	Body	2450	23.4	2.036	53.386	1.95	52.7	4.41	1.30
Dec. 25, 2018	Body	5250	23.3	5.254	50.751	5.36	48.9	-1.98	3.79
Dec. 28, 2018	Body	5250	23.4	5.346	49.359	5.36	48.9	-0.26	0.94
Dec. 25, 2018	Body	5600	23.3	5.628	50.217	5.77	48.5	-2.46	3.54
Dec. 28, 2018	Body	5600	23.4	5.852	48.685	5.77	48.5	1.42	0.38
Dec. 25, 2018	Body	5750	23.3	5.786	50.047	5.94	48.3	-2.59	3.62
Dec. 28, 2018	Body	5750	23.4	6.01	48.529	5.94	48.3	1.18	0.47

#### Note:

The dielectric properties of the tissue simulating liquid must be measured within 24 hours before the SAR testing and within  $\pm 5\%$  of the target values. Liquid temperature during the SAR testing must be within  $\pm 2\%$ .

# 4.4 System Validation

The SAR measurement system was validated according to procedures in KDB 865664 D01. The validation status in tabulated summary is as below.

Toot	Drobo	Probe		Measured	Measured	Va	lidation for C	w	Validation for Modulation		
Test Date	S/N	Calibrati	on Point	Conductivity (σ)	Permittivity $(\epsilon_r)$	Sensitivity Range	Probe Linearity	Probe Isotropy	Modulation Type	Duty Factor	PAR
Dec. 25, 2018	3650	Body	2450	2.016	51.542	Pass	Pass	Pass	OFDM	N/A	Pass
Dec. 28, 2018	7472	Body	2450	2.036	53.386	Pass	Pass	Pass	OFDM	N/A	Pass
Dec. 25, 2018	3650	Body	5250	5.254	50.751	Pass	Pass	Pass	OFDM	N/A	Pass
Dec. 28, 2018	7472	Body	5250	5.346	49.359	Pass	Pass	Pass	OFDM	N/A	Pass
Dec. 25, 2018	3650	Body	5600	5.628	50.217	Pass	Pass	Pass	OFDM	N/A	Pass
Dec. 28, 2018	7472	Body	5600	5.852	48.685	Pass	Pass	Pass	OFDM	N/A	Pass
Dec. 25, 2018	3650	Body	5750	5.786	50.047	Pass	Pass	Pass	OFDM	N/A	Pass
Dec. 28, 2018	7472	Body	5750	6.01	48.529	Pass	Pass	Pass	OFDM	N/A	Pass

Report Format Version 5.0.0 Page No. : 22 of 38
Report No.: SA181129C17D Issued Date : Jan. 14, 2019



# 4.5 System Verification

The measuring result for system verification is tabulated as below.

Test Date	Mode	Frequency (MHz)	1W Target SAR-1g (W/kg)	Measured SAR-1g (W/kg)	Normalized to 1W SAR-1g (W/kg)	Deviation (%)	Dipole S/N	Probe S/N	DAE S/N
Dec. 25, 2018	Body	2450	50.50	11.90	47.60	-5.74	737	3650	1277
Dec. 28, 2018	Body	2450	50.50	13.2	52.80	4.55	737	7472	1431
Dec. 25, 2018	Body	5250	74.90	7.68	76.80	2.54	1019	3650	1277
Dec. 28, 2018	Body	5250	74.90	7.58	75.80	1.20	1019	7472	1431
Dec. 25, 2018	Body	5600	79.30	7.82	78.20	-1.39	1019	3650	1277
Dec. 28, 2018	Body	5600	79.30	8.32	83.20	4.92	1019	7472	1431
Dec. 25, 2018	Body	5750	74.50	7.42	74.20	-0.40	1019	3650	1277
Dec. 28, 2018	Body	5750	74.50	7.8	78.00	4.70	1019	7472	1431

#### Note:

Comparing to the reference SAR value provided by SPEAG, the validation data should be within its specification of 10 %. The result indicates the system check can meet the variation criterion and the plots can be referred to Appendix A of this report.

 Report Format Version 5.0.0
 Page No.
 : 23 of 38

 Report No. : SA181129C17D
 Issued Date : Jan. 14, 2019



# 4.6 Maximum Output Power

# 4.6.1 Maximum Target Conducted Power

The maximum conducted average power (Unit: dBm) including tune-up tolerance is shown as below.

Mode	2.4G WLAN	5.2G WLAN	5.3G WLAN	5.6G WLAN	5.8G WLAN
802.11b	Ant-0 Ch 1: 17.2 Ch 6: 17.2 Ch 11: 16.0 Ch 12: 14.5 Ch 13: 11.5 Ant-1 Ch 1: 17.2 Ch 6: 17.2 Ch 11: 14.5 Ch 12: 14.5	N/A	N/A	N/A	N/A
802.11g	Ant-0 Ch 1: 16.0 Ch 6: 17.0 Ch 11: 16.0 Ch 12: 12.5 Ch 13: 9.5 Ant-1 Ch 1: 16.0 Ch 6: 17.0 Ch 11: 16.0 Ch 6: 17.0 Ch 11: 15.0 Ch 12: 12.5 Ch 13: 9.5 Ant-0+1 Ch 1: 15.0 Ch 6: 17.5 Ch 11: 18.0 Ch 12: 15.5 Ch 13: 12.5	N/A	N/A	N/A	N/A
802.11a	N/A	Ant-0:13.5 Ant-1:13.5 Ant-0+1:13.5	Ant-0:13.5 Ant-1:13.5 Ant-0+1:13.5	Ant-0:13.5 Ant-1:13.5 Ant-0+1:13.5	Ant-0:13.5 Ant-1:13.5 Ant-0+1:13.5
802.11n HT20	Ant-0 Ch 1: 16.0 Ch 6: 17.0 Ch 11: 14.5 Ch 12: 11.5 Ch 13: 8.5 Ant-1 Ch 1: 16.0 Ch 6: 17.0 Ch 11: 14.5 Ch 12: 11.5 Ch 13: 8.5 Ant-0+1 Ch 1: 17.5 Ch 6: 17.5 Ch 6: 17.5 Ch 11: 17.5 Ch 11: 15.5	Ant-0:13.5 Ant-1:13.5 Ant-0+1:13.5	Ant-0:13.5 Ant-1:13.5 Ant-0+1:13.5	Ant-0:13.5 Ant-1:13.5 Ant-0+1:13.5	Ant-0:13.5 Ant-1:13.5 Ant-0+1:13.5

 Report Format Version 5.0.0
 Page No.
 : 24 of 38

 Report No. : SA181129C17D
 Issued Date : Jan. 14, 2019



# FCC SAR Test Report

Mode	2.4G WLAN	5.2G WLAN	5.3G WLAN	5.6G WLAN	5.8G WLAN
802.11n HT40	Ant-0 Ch 3: 15.0 Ch 6: 17.5 Ch 9: 14.5 Ch 10: 11.5 Ch 11: 8.5 Ant-1 Ch 3: 15.0 Ch 6: 17.5 Ch 9: 14.5 Ch 10: 11.5 Ch 11: 8.5 Ant-0+1 Ch 3: 16.5 Ch 6: 17.0 Ch 9: 17.5 Ch 9: 17.5 Ch 10: 16 Ch 11: 14	Ant-0 Ch 38: 13.0 Ch 46: 13.5 Ant-1 Ch 38: 13.0 Ch 46: 13.5 Ant-0+1: 13.5	Ant-0:13.5 Ant-1:13.5 Ant-0+1:13.5	Ant-0:13.5 Ant-1:13.5 Ant-0+1:13.5	Ant-0:13.5 Ant-1:13.5 Ant-0+1:13.5
802.11ac VHT80	N/A	Ant-0:12.5 Ant-1:12.5 Ant-0+1:13.5	Ant-0:12.5 Ant-1:12.5 Ant-0+1:13.5	Ant-0 Ch 106: 12.5 Ch 122-138: 13.5 Ant-1 Ch 106: 12.5 Ch 122-138: 13.5 Ant-0+1 Ch 106: 13.5 Ch 122-138: 13.5	Ant-0:13.5 Ant-1:13.5 Ant-0+1:13.5

Mode	2.4G Bluetooth
Bluetooth DH	6.0
Bluetooth LE	6.0

 Report Format Version 5.0.0
 Page No.
 : 25 of 38

 Report No.: SA181129C17D
 Issued Date
 : Jan. 14, 2019



# 4.6.2 Measured Conducted Power Result

The measuring conducted average power (Unit: dBm) is shown as below.

### <WLAN 2.4G>

Mode	Channel	Frequency (MHz)	Average Power (Ant-0)	Average Power (Ant-1)	Average Power (Ant-0 + Ant-1)
	1	2412	17.02	17.10	-
	6	2437	16.97	17.02	-
802.11b	11	2462	15.73	15.96	-
	12	2467	13.81	13.68	-
	13	2472	10.82	10.95	-
	1	2412	-	-	14.85
	6	2437	-	-	17.24
802.11g	11	2462	-	-	17.79
	12	2467	-	-	14.75
	13	2472	-	-	11.68

# <WLAN 5.3G>

Mode	Channel	Frequency (MHz)	Average Power (Ant-0)	Average Power (Ant-1)	Average Power (Ant-0 + Ant-1)
802.11n (HT40)	54	5270	13.22	13.44	-
002.1111 (П140)	62	5310	13.45	13.24	-
802.11ac (VHT80)	58	5290	-	-	13.20

#### <WLAN 5.6G>

Mode	Channel	Frequency (MHz)	Average Power (Ant-0)	Average Power (Ant-1)	Average Power (Ant-0 + Ant-1)
	106	5530	12.37	12.38	13.32
802.11ac (VHT80)	122	5610	13.32	13.25	13.30
	138	5690	13.35	13.41	13.19

# <WLAN 5.8G>

Mode	Channel	Frequency (MHz)	Average Power (Ant-0)	Average Power (Ant-1)	Average Power (Ant-0 + Ant-1)
802.11ac (VHT80)	155	5775	13.22	13.32	13.45

### <Bluetooth>

Mode	Channel	Frequency (MHz)	Average Power
	0	2402	5.78
Bluetooth EDR	39	2441	5.87
	78	2480	5.81
	0	2402	5.74
Bluetooth LE	19	2440	5.80
	39	2480	5.84

 Report Format Version 5.0.0
 Page No.
 : 26 of 38

 Report No. : SA181129C17D
 Issued Date
 : Jan. 14, 2019



### 4.7 SAR Testing Results

#### 4.7.1 SAR Test Reduction Considerations

#### <KDB 447498 D01, General RF Exposure Guidance>

Testing of other required channels within the operating mode of a frequency band is not required when the reported SAR for the mid-band or highest output power channel is:

- (1) ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
- (2) ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
- (3) ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz

When SAR is not measured at the maximum power level allowed for production units, the measured SAR will be scaled to the maximum tune-up tolerance limit to determine compliance. The scaling factor for the tune-up power is defined as maximum tune-up limit (mW) / measured conducted power (mW). The reported SAR would be calculated by measured SAR x tune-up power scaling factor.

The SAR has been measured with highest transmission duty factor supported by the test mode tools for WLAN and/or Bluetooth. When the transmission duty factor could not achieve 100%, the reported SAR will be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up power. The scaling factor for the duty factor is defined as 100% / transmission duty cycle (%). The reported SAR would be calculated by measured SAR x tune-up power scaling factor x duty cycle scaling factor.

#### <KDB 248227 D01, SAR Guidance for Wi-Fi Transmitters>

- (1) For handsets operating next to ear, hotspot mode or mini-tablet configurations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When the reported SAR of initial test position is <= 0.4 W/kg, SAR testing for remaining test positions is not required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is <= 0.8 W/kg or all test positions are measured.
- (2) For WLAN 2.4 GHz, the highest measured maximum output power channel for DSSS was selected for SAR measurement. When the reported SAR is <= 0.8 W/kg, no further SAR testing is required. Otherwise, SAR is evaluated at the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel. For OFDM modes (802.11g/n), SAR is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and it is <= 1.2 W/kg.
- (3) For WLAN 5 GHz, the initial test configuration was selected according to the transmission mode with the highest maximum output power. When the reported SAR of initial test configuration is > 0.8 W/kg, SAR is required for the subsequent highest measured output power channel until the reported SAR result is <= 1.2 W/kg or all required channels are measured. For other transmission modes, SAR is not required when the highest reported SAR for initial test configuration is adjusted by the ratio of subsequent test configuration to initial test configuration specified maximum output power and it is <= 1.2 W/kg.

Report Format Version 5.0.0 Page No. : 27 of 38
Report No.: SA181129C17D Issued Date : Jan. 14, 2019





(4) For WLAN MIMO mode, the power-based standalone SAR test exclusion or the sum of SAR provision in KDB 447498 to determine simultaneous transmission SAR test exclusion should be applied. Otherwise, SAR for MIMO mode will be measured with all applicable antennas transmitting simultaneously at the specified maximum output power of MIMO operation.

# 4.7.2 SAR Results for Body Exposure Condition (Test Separation Distance is 0 mm)

# **Laptop PC Mode**

Plot No.	Band	Mode	Test Position	Ch.	EUT Config.	Tx Antenna	Duty Cycle	Crest Factor	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	WLAN2.4G	802.11b	Bottom	1	1	Ant 0	99.15	1.01	17.2	17.02	1.04	0.14	0.108	0.11
	WLAN2.4G	802.11b	Bottom	1	1	Ant 1	99.15	1.01	17.2	17.10	1.02	0.17	0.087	0.09
01	WLAN2.4G	802.11g	Bottom	11	1	Ant 0+1	96.05	1.04	18.0	17.79	1.05	-0.06	0.159	<mark>0.17</mark>
	WLAN2.4G	802.11g	Bottom	1	1	Ant 0+1	96.05	1.04	15.0	14.85	1.04	-0.07	0.059	0.06
	WLAN2.4G	802.11g	Bottom	6	1	Ant 0+1	96.05	1.04	17.5	17.24	1.06	-0.11	0.123	0.14
	WLAN2.4G	802.11g	Bottom	12	1	Ant 0+1	96.05	1.04	15.5	14.75	1.19	0.15	0.056	0.07
	WLAN2.4G	802.11g	Bottom	13	1	Ant 0+1	96.05	1.04	12.5	11.68	1.21	0.12	0.063	0.08
	WLAN2.4G	802.11g	Bottom	11	2	Ant 0+1	96.05	1.04	18.0	17.79	1.05	0.15	0.151	0.16
02	WLAN5.6G	802.11ac VHT80	Bottom	138	1	Ant 0	84.75	1.18	13.5	13.35	1.04	-0.13	0.128	<mark>0.16</mark>
	WLAN5.6G	802.11ac VHT80	Bottom	138	1	Ant 1	84.75	1.18	13.5	13.41	1.02	0.15	0.118	0.14
	WLAN5.6G	802.11ac VHT80	Bottom	122	1	Ant 0+1	84.75	1.18	13.5	13.35	1.04	0.13	0.061	0.07
	WLAN5.6G	802.11ac VHT80	Bottom	106	1	Ant 0	84.75	1.18	12.5	12.37	1.03	0.12	0.093	0.11
	WLAN5.6G	802.11ac VHT80	Bottom	122	1	Ant 0	84.75	1.18	13.5	13.32	1.04	0.16	0.121	0.15
	WLAN5.6G	802.11ac VHT80	Bottom	138	2	Ant 0	84.75	1.18	13.5	13.35	1.04	0.11	0.122	0.15
	WLAN5.8G	802.11ac VHT80	Bottom	155	1	Ant 0	84.75	1.18	13.5	13.22	1.07	0.11	0.036	0.05
03	WLAN5.8G	802.11ac VHT80	Bottom	155	1	Ant 1	84.75	1.18	13.5	13.32	1.04	-0.15	0.061	0.07
	WLAN5.8G	802.11ac VHT80	Bottom	155	1	Ant 0+1	84.75	1.18	13.5	13.45	1.01	0.15	0.029	0.03
	WLAN5.8G	802.11ac VHT80	Bottom	155	2	Ant 1	84.75	1.18	13.5	13.32	1.04	0.12	0.051	0.06

 Report Format Version 5.0.0
 Page No. : 28 of 38

 Report No. : SA181129C17D
 Issued Date : Jan. 14, 2019





#### **Tablet PC Mode**

Plot No.	Band	Mode	Test Position	Ch.	EUT Config.	Tx Antenna	Duty Cycle	Crest Factor	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	WLAN2.4G	802.11b	Rear Face	1	1	Ant 0	99.15	1.01	17.2	17.02	1.04	0.06	0.08	80.0
04	WLAN2.4G	802.11b	Bottom Side	1	1	Ant 0	99.15	1.01	17.2	17.02	1.04	-0.09	0.441	<mark>0.46</mark>
	WLAN2.4G	802.11b	Rear Face	1	1	Ant 1	99.15	1.01	17.2	17.10	1.02	0.11	0.022	0.02
	WLAN2.4G	802.11b	Bottom Side	1	1	Ant 1	99.15	1.01	17.2	17.10	1.02	0.07	0.289	0.30
	WLAN2.4G	802.11.11g	Rear Face	11	1	Ant 0+1	96.05	1.04	18.0	17.79	1.05	-0.03	0.056	0.06
	WLAN2.4G	802.11.11g	Bottom Side	11	1	Ant 0+1	96.05	1.04	18.0	17.79	1.05	-0.08	0.347	0.38
	WLAN2.4G	802.11.11g	Bottom Side	1	1	Ant 0+1	96.05	1.04	15.0	14.85	1.04	0.03	0.266	0.29
	WLAN2.4G	802.11.11g	Bottom Side	6	1	Ant 0+1	96.05	1.04	17.5	17.24	1.06	0.05	0.343	0.38
	WLAN2.4G	802.11.11g	Bottom Side	12	1	Ant 0+1	96.05	1.04	15.5	14.75	1.19	-0.11	0.155	0.19
	WLAN2.4G	802.11.11g	Bottom Side	13	1	Ant 0+1	96.05	1.04	12.5	11.68	1.21	-0.06	0.141	0.18
	WLAN2.4G	802.11b	Bottom Side	1	2	Ant 0	99.15	1.01	17.2	17.02	1.04	0.03	0.433	0.45
	WLAN5.3G	802.11n HT40	Rear Face	62	1	Ant 0	91.71	1.09	13.5	13.45	1.01	0.00	<0.001	0.00
	WLAN5.3G	802.11n HT40	Bottom Side	62	1	Ant 0	91.71	1.09	13.5	13.45	1.01	0.05	0.601	0.66
	WLAN5.3G	802.11n HT40	Rear Face	54	1	Ant 1	91.71	1.09	13.5	13.44	1.01	0.00	<0.001	0.00
05	WLAN5.3G	802.11n HT40	Bottom Side	54	1	Ant 1	91.71	1.09	13.5	13.44	1.01	-0.06	1.01	<mark>1.11</mark>
	WLAN5.3G	802.11ac VHT80	Rear Face	58	1	Ant 0+1	84.75	1.18	13.5	13.20	1.07	0.00	<0.001	0.00
	WLAN5.3G	802.11ac VHT80	Bottom Side	58	1	Ant 0+1	84.75	1.18	13.5	13.20	1.07	0.06	0.557	0.70
	WLAN5.3G	802.11n HT40	Bottom Side	62	1	Ant 1	91.71	1.09	13.5	13.24	1.06	-0.11	0.913	1.05
	WLAN5.3G	802.11n HT40	Bottom Side	54	2	Ant 1	91.71	1.09	13.5	13.44	1.01	-0.05	0.953	1.05
	WLAN5.3G	802.11n HT40	Bottom Side	54	1	Ant 1	91.71	1.09	13.5	13.44	1.01	0.03	0.983	1.08

 Report Format Version 5.0.0
 Page No.
 : 29 of 38

 Report No. : SA181129C17D
 Issued Date : Jan. 14, 2019



# FCC SAR Test Report

Plot No.	Band	Mode	Test Position	Ch.	EUT Config.	Tx Antenna	Duty Cycle	Crest Factor	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	WLAN5.6G	802.11ac VHT80	Rear Face	138	1	Ant 0	84.75	1.18	13.5	13.35	1.04	0.00	<0.001	0.00
	WLAN5.6G	802.11ac VHT80	Bottom Side	138	1	Ant 0	84.75	1.18	13.5	13.35	1.04	0.05	0.392	0.48
	WLAN5.6G	802.11ac VHT80	Rear Face	138	1	Ant 1	84.75	1.18	13.5	13.41	1.02	0.00	<0.001	0.00
	WLAN5.6G	802.11ac VHT80	Bottom Side	138	1	Ant 1	84.75	1.18	13.5	13.41	1.02	0.06	0.417	0.50
	WLAN5.6G	802.11ac VHT80	Rear Face	106	1	Ant 0+1	84.75	1.18	13.5	13.32	1.04	0	<0.001	0.00
	WLAN5.6G	802.11ac VHT80	Bottom Side	106	1	Ant 0+1	84.75	1.18	13.5	13.32	1.04	0.06	0.265	0.33
06	WLAN5.6G	802.11ac VHT80	Bottom Side	106	1	Ant 1	84.75	1.18	12.5	12.38	1.03	-0.07	0.571	<mark>0.69</mark>
	WLAN5.6G	802.11ac VHT80	Bottom Side	122	1	Ant 1	84.75	1.18	13.5	13.25	1.06	0.03	0.449	0.56
	WLAN5.6G	802.11ac VHT80	Bottom Side	106	2	Ant 1	84.75	1.18	12.5	12.38	1.03	0.09	0.517	0.63
	WLAN5.8G	802.11ac VHT80	Rear Face	155	1	Ant 0	84.75	1.18	13.5	13.22	1.07	0.00	<0.001	0.00
	WLAN5.8G	802.11ac VHT80	Bottom Side	155	1	Ant 0	84.75	1.18	13.5	13.22	1.07	0.03	0.196	0.25
	WLAN5.8G	802.11ac VHT80	Rear Face	155	1	Ant 1	84.75	1.18	13.5	13.32	1.04	0.00	<0.001	0.00
07	WLAN5.8G	802.11ac VHT80	Bottom Side	155	1	Ant 1	84.75	1.18	13.5	13.32	1.04	0.05	0.401	<mark>0.49</mark>
	WLAN5.8G	802.11ac VHT80	Rear Face	155	1	Ant 0+1	84.75	1.18	13.5	13.45	1.01	0.00	<0.001	0.00
	WLAN5.8G	802.11ac VHT80	Bottom Side	155	1	Ant 0+1	84.75	1.18	13.5	13.45	1.01	0.08	0.206	0.25
	WLAN5.8G	802.11ac VHT80	Bottom Side	155	2	Ant 1	84.75	1.18	13.5	13.32	1.04	-0.02	0.385	0.47

**Note:** The "< 0.001" means there is no SAR value or the SAR is too low to be measured.

Report Format Version 5.0.0 Page No. : 30 of 38
Report No. : SA181129C17D Issued Date : Jan. 14, 2019



#### 4.7.3 SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are  $\leq 1.45$  W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is  $\leq 1.10$ , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

Band	Mode	Test Position	Ch.	Original Measured SAR-1g (W/kg)	1st Repeated SAR-1g (W/kg)	L/S Ratio	2nd Repeated SAR-1g (W/kg)	L/S Ratio	3rd Repeated SAR-1g (W/kg)	L/S Ratio
WLAN5.3G	802.11n HT40	Bottom Side	54	1.010	0.983	1.03	N/A	N/A	N/A	N/A

#### 4.7.4 Simultaneous Multi-band Transmission Evaluation

Simultaneous TX Combination	Capable Transmit Configurations	Body Exposure Condition
1	WLAN (Ant-0) + BT	Yes

Note: The WLAN 2.4G and WLAN 5G cannot transmit simultaneously.

#### <Estimated SAR Calculation>

According to KDB 447498 D01, when standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR was estimated according to following formula to result in substantially conservative SAR values of <= 0.4 W/kg to determine simultaneous transmission SAR test exclusion.

$$\text{Estimated SAR} = \frac{\text{Max. Tune up Power}_{(mW)}}{\text{Min. Test Separation Distance}_{(mm)}} \times \frac{\sqrt{f_{(GHz)}}}{7.5}$$

If the minimum test separation distance is < 5 mm, a distance of 5 mm is used for estimated SAR calculation. When the test separation distance is > 50 mm, the 0.4 W/kg is used for SAR-1g.

Mode / Band	Frequency (GHz)	Max. Tune-up Power (dBm)	Test Position	Separation Distance (mm)	Estimated SAR (W/kg)
BT (DSS)	2.48	6.0	Body	0	0.17

### Note:

- 1. The separation distance is determined from the outer housing of the EUT to the user.
- 2. When standalone SAR testing is not required, an estimated SAR can be applied to determine simultaneous transmission SAR test exclusion.

 Report Format Version 5.0.0
 Page No.
 : 31 of 38

 Report No. : SA181129C17D
 Issued Date : Jan. 14, 2019



### <SAR Summation Analysis>

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of  $SAR_{1g}$  of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit ( $SAR_{1g}$  1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of  $SAR_{1g}$  is greater than the SAR limit ( $SAR_{1g}$  1.6 W/kg), SAR test exclusion is determined by the SPLSR.

### **Laptop PC Mode**

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
1	WLAN_Ant-0 (DTS) + BT (DSS)	Body	Bottom Side	0.11	0.17	0.28	Σ SAR < 1.6, Not required
2	WLAN_Ant-0 (NII) + BT (DSS)	Body	Bottom Side	0.16	0.17	0.33	Σ SAR < 1.6, Not required

#### **Tablet PC Mode**

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
	WLAN_Ant-0 (DTS)		Rear Face	0.08	0.17	0.25	Σ SAR < 1.6, Not required
1	+ BT (DSS)	Body	Bottom Side	0.46	0.17	0.63	Σ SAR < 1.6, Not required
	WLAN_Ant-0 (NII)	_	Rear Face	0.00	0.17	0.17	Σ SAR < 1.6, Not required
2	+ BT (DSS)	Body	Bottom Side	1.11	0.17	1.28	Σ SAR < 1.6, Not required

Test Engineer: James Chu, and Blake Wang

Report Format Version 5.0.0 Page No. : 32 of 38
Report No.: SA181129C17D Issued Date : Jan. 14, 2019



# 5. Calibration of Test Equipment

Equipment	Manufacturer	Model	SN	Cal. Date	Cal. Interval
System Validation Dipole	SPEAG	D2450V2	737	Aug. 24, 2018	1 Year
System Validation Dipole	SPEAG	D5GHzV2	1019	Mar. 22, 2018	1 Year
Dosimetric E-Field Probe	SPEAG	EX3DV4	3650	Jul. 27, 2018	1 Year
Dosimetric E-Field Probe	SPEAG	EX3DV4	7472	Aug. 29, 2018	1 Year
Data Acquisition Electronics	SPEAG	DAE3	579	Aug. 27, 2018	1 Year
Data Acquisition Electronics	SPEAG	DAE4	1277	Jan. 18, 2018	1 Year
Data Acquisition Electronics	SPEAG	DAE4	1431	Mar. 16, 2018	1 Year
Spectrum Analyzer	R&S	FSL6	102006	Mar. 23, 2018	1 Year
ENA Series Network Analyzer	Agilent	E5071C	MY46214281	Jun. 08, 2018	1 Year
MXG Analong Signal Generator	Agilent	N5181A	MY50143868	Jul. 03, 2018	1 Year
Vector Signal Generator	Anritsu	MG3710A	6201599977	Mar. 16, 2018	1 Year
Power Meter	Anritsu	ML2495A	1218009	Jul. 03, 2018	1 Year
Power Sensor	Anritsu	MA2411B	1207252	Jul. 03, 2018	1 Year
Thermometer	YFE	YF-160A	130504591	Mar. 23, 2018	1 Year

Report Format Version 5.0.0 Page No. : 33 of 38
Report No.: SA181129C17D Issued Date : Jan. 14, 2019



# 6. Measurement Uncertainty

Source of Uncertainty	Uncertainty (± %)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (± %, 1g)	Standard Uncertainty (± %, 10g)	Vi
Measurement System								
Probe Calibration	6.0	Normal	1	1	1	6.0	6.0	8
Axial Isotropy	4.7	Rectangular	√3	√0.5	√0.5	1.9	1.9	8
Hemispherical Isotropy	9.6	Rectangular	√3	√0.5	√0.5	3.9	3.9	8
Boundary Effect	1.0	Rectangular	√3	1	1	0.6	0.6	8
Linearity	4.7	Rectangular	√3	1	1	2.7	2.7	8
Detection Limits	0.25	Rectangular	√3	1	1	0.14	0.14	8
Probe Modulation Response	3.5	Rectangular	√3	1	1	2.0	2.0	8
Readout Electronics	0.3	Normal	1	1	1	0.3	0.3	8
Response Time	0.0	Rectangular	√3	1	1	0.0	0.0	8
Integration Time	1.7	Rectangular	√3	1	1	1.0	1.0	8
RF Ambient Conditions – Noise	3.0	Rectangular	√3	1	1	1.7	1.7	8
RF Ambient Conditions – Reflections	3.0	Rectangular	√3	1	1	1.7	1.7	8
Probe Positioner Mechanical Tolerance	0.4	Rectangular	√3	1	1	0.2	0.2	8
Probe Positioning with Respect to Phantom	2.9	Rectangular	√3	1	1	1.7	1.7	8
Post-processing	2.0	Rectangular	√3	1	1	1.2	1.2	8
Test Sample Related								
Test Sample Positioning	2.82 / 1.60	Normal	1	1	1	2.8	1.6	35
Device Holder Uncertainty	2.55 / 2.76	Normal	1	1	1	2.6	2.8	7
Power Drift of Measurement	5.0	Rectangular	√3	1	1	2.9	2.9	8
Power Scaling	0.0	Rectangular	√3	1	1	0.0	0.0	8
Phantom and Setup				_	_	_		
Phantom Uncertainty (Shape and Thickness Tolerances)	6.1	Rectangular	√3	1	1	3.5	3.5	8
Liquid Conductivity ( Temperature Uncertainty)	2.58	Rectangular	√3	0.78	0.71	1.2	1.1	8
Liquid Conductivity (Measured)	2.95	Normal	1	0.78	0.71	2.3	2.1	61
Liquid Permittivity (Temperature Uncertainty)	1.97	Rectangular	√3	0.23	0.26	0.3	0.3	∞
Liquid Permittivity (Measured)	3.04	Normal	1	0.23	0.26	0.7	0.8	47
Combined Standard Uncertainty						± 11.0 %	± 10.7 %	
Expanded Uncertainty (K=2)	Expanded Uncertainty (K=2)						± 21.4 %	

Head SAR Uncertainty Budget for Frequency Range of 300 MHz to 3 GHz

 Report Format Version 5.0.0
 Page No. : 34 of 38

 Report No. : SA181129C17D
 Issued Date : Jan. 14, 2019



# FCC SAR Test Report

Source of Uncertainty	Uncertainty (± %)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (± %, 1g)	Standard Uncertainty (± %, 10g)	Vi
Measurement System								
Probe Calibration	6.55	Normal	1	1	1	6.55	6.55	8
Axial Isotropy	4.7	Rectangular	√3	0.7	0.7	1.9	1.9	8
Hemispherical Isotropy	9.6	Rectangular	√3	0.7	0.7	3.9	3.9	∞
Boundary Effect	2.0	Rectangular	√3	1	1	1.2	1.2	8
Linearity	4.7	Rectangular	√3	1	1	2.7	2.7	8
Detection Limits	0.25	Rectangular	√3	1	1	0.14	0.14	8
Probe Modulation Response	3.5	Rectangular	√3	1	1	2.0	2.0	8
Readout Electronics	0.3	Normal	1	1	1	0.3	0.3	8
Response Time	0.0	Rectangular	√3	1	1	0.0	0.0	8
Integration Time	1.7	Rectangular	√3	1	1	1.0	1.0	8
RF Ambient Conditions – Noise	3.0	Rectangular	√3	1	1	1.7	1.7	8
RF Ambient Conditions – Reflections	3.0	Rectangular	√3	1	1	1.7	1.7	8
Probe Positioner Mechanical Tolerance	0.4	Rectangular	√3	1	1	0.2	0.2	8
Probe Positioning with Respect to Phantom	6.7	Rectangular	√3	1	1	3.9	3.9	8
Post-processing	4.0	Rectangular	√3	1	1	2.3	2.3	∞
Test Sample Related								
Test Sample Positioning	2.82 / 1.60	Normal	1	1	1	2.8	1.6	35
Device Holder Uncertainty	2.55 / 2.76	Normal	1	1	1	2.6	2.8	7
Power Drift of Measurement	5.0	Rectangular	√3	1	1	2.9	2.9	8
Power Scaling	0.0	Rectangular	√3	1	1	0.0	0.0	8
Phantom and Setup								
Phantom Uncertainty (Shape and Thickness Tolerances)	6.6	Rectangular	√3	1	1	3.8	3.8	8
Liquid Conductivity ( Temperature Uncertainty)	2.58	Rectangular	√3	0.78	0.71	1.2	1.1	8
Liquid Conductivity (Measured)	2.95	Normal	1	0.78	0.71	2.3	2.1	61
Liquid Permittivity (Temperature Uncertainty)	1.97	Rectangular	√3	0.23	0.26	0.3	0.3	8
Liquid Permittivity (Measured)	3.04	Normal	1	0.23	0.26	0.7	0.8	47
Combined Standard Uncertainty						± 12.1 %	± 11.9 %	
Expanded Uncertainty (K=2)						± 24.2 %	± 23.8 %	

Head SAR Uncertainty Budget for Frequency Range of 3 GHz to 6 GHz

 Report Format Version 5.0.0
 Page No. : 35 of 38

 Report No. : SA181129C17D
 Issued Date : Jan. 14, 2019



# FCC SAR Test Report

Source of Uncertainty	Uncertainty (± %)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (± %, 1g)	Standard Uncertainty (± %, 10g)	Vi
Measurement System								
Probe Calibration	6.0	Normal	1	1	1	6.0	6.0	8
Axial Isotropy	4.7	Rectangular	√3	√0.5	√0.5	1.9	1.9	8
Hemispherical Isotropy	9.6	Rectangular	√3	√0.5	√0.5	3.9	3.9	∞
Boundary Effect	1.0	Rectangular	√3	1	1	0.6	0.6	8
Linearity	4.7	Rectangular	√3	1	1	2.7	2.7	8
Detection Limits	0.25	Rectangular	√3	1	1	0.14	0.14	8
Probe Modulation Response	3.5	Rectangular	√3	1	1	2.0	2.0	8
Readout Electronics	0.3	Normal	1	1	1	0.3	0.3	8
Response Time	0.0	Rectangular	√3	1	1	0.0	0.0	8
Integration Time	1.7	Rectangular	√3	1	1	1.0	1.0	8
RF Ambient Conditions – Noise	3.0	Rectangular	√3	1	1	1.7	1.7	8
RF Ambient Conditions – Reflections	3.0	Rectangular	√3	1	1	1.7	1.7	8
Probe Positioner Mechanical Tolerance	0.4	Rectangular	√3	1	1	0.2	0.2	8
Probe Positioning with Respect to Phantom	2.9	Rectangular	√3	1	1	1.7	1.7	8
Post-processing	2.0	Rectangular	√3	1	1	1.2	1.2	∞
Test Sample Related								
Test Sample Positioning	3.68 / 1.73	Normal	1	1	1	3.7	1.7	29
Device Holder Uncertainty	2.55 / 2.76	Normal	1	1	1	2.6	2.8	7
Power Drift of Measurement	5.0	Rectangular	√3	1	1	2.9	2.9	8
Power Scaling	0.0	Rectangular	√3	1	1	0.0	0.0	8
Phantom and Setup								
Phantom Uncertainty (Shape and Thickness Tolerances)	7.2	Rectangular	√3	1	1	4.2	4.2	8
Liquid Conductivity ( Temperature Uncertainty)	2.58	Rectangular	√3	0.78	0.71	1.2	1.1	8
Liquid Conductivity (Measured)	2.95	Normal	1	0.78	0.71	2.3	2.1	61
Liquid Permittivity (Temperature Uncertainty)	1.97	Rectangular	√3	0.23	0.26	0.3	0.3	8
Liquid Permittivity (Measured)	3.04	Normal	1	0.23	0.26	0.7	0.8	47
Combined Standard Uncertainty						± 11.4 %	± 11.0 %	
Expanded Uncertainty (K=2)						± 22.8 %	± 22.0 %	

Body SAR Uncertainty Budget for Frequency Range of 300 MHz to 3 GHz

 Report Format Version 5.0.0
 Page No. : 36 of 38

 Report No. : SA181129C17D
 Issued Date : Jan. 14, 2019



# FCC SAR Test Report

Source of Uncertainty	Uncertainty (± %)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (± %, 1g)	Standard Uncertainty (± %, 10g)	Vi
Measurement System								
Probe Calibration	6.55	Normal	1	1	1	6.55	6.55	8
Axial Isotropy	4.7	Rectangular	√3	0.7	0.7	1.9	1.9	8
Hemispherical Isotropy	9.6	Rectangular	√3	0.7	0.7	3.9	3.9	8
Boundary Effect	2.0	Rectangular	√3	1	1	1.2	1.2	8
Linearity	4.7	Rectangular	√3	1	1	2.7	2.7	8
Detection Limits	0.25	Rectangular	√3	1	1	0.14	0.14	8
Probe Modulation Response	3.5	Rectangular	√3	1	1	2.0	2.0	8
Readout Electronics	0.3	Normal	1	1	1	0.3	0.3	8
Response Time	0.0	Rectangular	√3	1	1	0.0	0.0	∞
Integration Time	1.7	Rectangular	√3	1	1	1.0	1.0	8
RF Ambient Conditions – Noise	3.0	Rectangular	√3	1	1	1.7	1.7	8
RF Ambient Conditions – Reflections	3.0	Rectangular	√3	1	1	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	0.4	Rectangular	√3	1	1	0.2	0.2	8
Probe Positioning with Respect to Phantom	6.7	Rectangular	√3	1	1	3.9	3.9	8
Post-processing	4.0	Rectangular	√3	1	1	2.3	2.3	8
Test Sample Related								
Test Sample Positioning	3.68 / 1.73	Normal	1	1	1	3.7	1.7	29
Device Holder Uncertainty	2.55 / 2.76	Normal	1	1	1	2.6	2.8	7
Power Drift of Measurement	5.0	Rectangular	√3	1	1	2.9	2.9	8
Power Scaling	0.0	Rectangular	√3	1	1	0.0	0.0	8
Phantom and Setup								
Phantom Uncertainty (Shape and Thickness Tolerances)	7.6	Rectangular	√3	1	1	4.4	4.4	8
Liquid Conductivity ( Temperature Uncertainty)	2.58	Rectangular	√3	0.78	0.71	1.2	1.1	∞
Liquid Conductivity (Measured)	2.95	Normal	1	0.78	0.71	2.3	2.1	61
Liquid Permittivity (Temperature Uncertainty)	1.97	Rectangular	√3	0.23	0.26	0.3	0.3	8
Liquid Permittivity (Measured)	3.04	Normal	1	0.23	0.26	0.7	0.8	47
Combined Standard Uncertainty					± 12.5 %	± 12.1 %		
Expanded Uncertainty (K=2)						± 25.0 %	± 24.2 %	

Body SAR Uncertainty Budget for Frequency Range of 3 GHz to 6 GHz

 Report Format Version 5.0.0
 Page No. : 37 of 38

 Report No. : SA181129C17D
 Issued Date : Jan. 14, 2019

Reference No.: 181129C22



## 7. Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

#### Taiwan HwaYa EMC/RF/Safety Lab:

Add: No.19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, Taiwan, R.O.C.

Tel: 886-3-318-3232 Fax: 886-3-327-0892

#### Taiwan LinKo EMC/RF Lab:

Add: No. 47-2, 14th Ling, Chia Pau Vil., Linkou Dist., New Taipei City 244, Taiwan, R.O.C.

Tel: 886-2-2605-2180 Fax: 886-2-2605-1924

#### Taiwan HsinChu EMC/RF/Telecom Lab:

Add: E-2, No.1, Li Hsin 1<sup>st</sup> Road, Hsinchu Science Park, Hsinchu City 30078, Taiwan, R.O.C.

Tel: 886-3-666-8565 Fax: 886-3-666-8323

Email: <a href="mailto:service.adt@tw.bureauveritas.com">service.adt@tw.bureauveritas.com</a>
Web Site: <a href="mailto:www.bureauveritas-adt.com">www.bureauveritas-adt.com</a>

The road map of all our labs can be found in our web site also.

---END---

 Report Format Version 5.0.0
 Page No. : 38 of 38

 Report No. : SA181129C17D
 Issued Date : Jan. 14, 2019

Reference No.: 181129C22



# Appendix A. SAR Plots of System Verification

The plots for system verification with largest deviation for each SAR system combination are shown as follows.

Report Format Version 5.0.0 Issued Date : Jan. 14, 2019

Report No. : SA181129C17D Reference No. : 181129C22

#### System Check\_B2450\_181225

#### **DUT: Dipole 2450 MHz; Type: D2450V2; SN: 737**

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: B19T27N1 1225 Medium parameters used: f = 2450 MHz;  $\sigma = 2.016$  S/m;  $\varepsilon_r = 51.542$ ;  $\rho =$ 

Date: 2018/12/25

 $1000 \text{ kg/m}^3$ 

Ambient Temperature: 23.6°C; Liquid Temperature: 23.3°C


#### DASY5 Configuration:

- Probe: EX3DV4 SN3650; ConvF(7.61, 7.61, 7.61); Calibrated: 2018/07/27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2018/08/27
- Phantom: ELI Phantom 1206; Type: QDOVA002AA;
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

**Pin=250mW/Area Scan (81x81x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm Maximum value of SAR (interpolated) = 19.3 W/kg

**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 91.27 V/m; Power Drift = -0.14 dB Peak SAR (extrapolated) = 24.3 W/kg **SAR(1 g) = 11.9 W/kg; SAR(10 g) = 5.53 W/kg** 

SAR(1 g) = 11.9 W/kg; SAR(10 g) = 5.53 W/kg Maximum value of SAR (measured) = 19.9 W/kg



#### System Check\_B5250\_181225

## DUT: Dipole 5 GHz; Type: D5GHzV2; SN: 1019

Communication System: CW; Frequency: 5250 MHz; Duty Cycle: 1:1

Medium: B34T60N1 1225 Medium parameters used: f = 5250 MHz;  $\sigma = 5.254$  S/m;  $\varepsilon_r = 50.751$ ;  $\rho =$ 

Date: 2018/12/25

 $1000 \text{ kg/m}^3$ 

Ambient Temperature : 23.6 ℃; Liquid Temperature : 23.3 ℃


#### DASY5 Configuration:

- Probe: EX3DV4 SN3650; ConvF(4.85, 4.85, 4.85); Calibrated: 2018/07/27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2018/08/27
- Phantom: ELI Phantom 1206; Type: QDOVA002AA;
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

**Pin=100mW/Area Scan (91x91x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR (interpolated) = 17.4 W/kg

**Pin=100mW/Zoom Scan (7x7x12)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=2mm Reference Value = 69.57 V/m; Power Drift = 0.03 dB Peak SAR (extrapolated) = 30.9 W/kg

SAR(1 g) = 7.68 W/kg; SAR(10 g) = 2.17 W/kgMaximum value of SAR (measured) = 19.3 W/kg



#### System Check\_B5600\_181228

## DUT: Dipole 5 GHz; Type: D5GHzV2; SN: 1019

Communication System: CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: B34T60N2 1228 Medium parameters used: f = 5600 MHz;  $\sigma = 5.852$  S/m;  $\varepsilon_r = 48.685$ ;  $\rho =$ 

Date: 2018/12/28

 $1000 \text{ kg/m}^3$ 

Ambient Temperature: 23.7 °C; Liquid Temperature: 23.4 °C

#### DASY5 Configuration:


- Probe: EX3DV4 SN7472; ConvF(4.37, 4.37, 4.37); Calibrated: 2018/08/29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1431; Calibrated: 2018/03/16
- Phantom: ELI Phantom 1204; Type: QDOVA002AA;
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

**Pin=100mW/Area Scan (91x91x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR (interpolated) = 20.1 W/kg

**Pin=100mW/Zoom Scan (7x7x12)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=2mm Reference Value = 69.72 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 37.0 W/kg

SAR(1 g) = 8.32 W/kg; SAR(10 g) = 2.33 W/kgMaximum value of SAR (measured) = 21.7 W/kg



#### System Check\_B5750\_181228

## DUT: Dipole 5 GHz; Type: D5GHzV2; SN: 1019

Communication System: CW; Frequency: 5750 MHz; Duty Cycle: 1:1

Medium: B34T60N2\_1228 Medium parameters used: f = 5750 MHz;  $\sigma = 6.01$  S/m;  $\varepsilon_r = 48.529$ ;  $\rho =$ 

Date: 2018/12/28

 $1000 \text{ kg/m}^3$ 

Ambient Temperature: 23.7 °C; Liquid Temperature: 23.4 °C

#### DASY5 Configuration:

- Probe: EX3DV4 SN7472; ConvF(4.56, 4.56, 4.56); Calibrated: 2018/08/29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1431; Calibrated: 2018/03/16
- Phantom: ELI Phantom 1204; Type: QDOVA002AA;
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)


**Pin=100mW/Area Scan (91x91x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR (interpolated) = 19.4 W/kg

**Pin=100mW/Zoom Scan (7x7x12)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=2mm Reference Value = 62.67 V/m; Power Drift = -0.17 dB

Peak SAR (extrapolated) = 34.9 W/kg

SAR(1 g) = 7.8 W/kg; SAR(10 g) = 2.23 W/kg

Maximum value of SAR (measured) = 20.1 W/kg







# Appendix B. SAR Plots of SAR Measurement

The SAR plots for highest measured SAR in each exposure configuration, wireless mode and frequency band combination, and measured SAR > 1.5 W/kg are shown as follows.

Report Format Version 5.0.0 Issued Date : Jan. 14, 2019

Report No. : SA181129C17D Reference No. : 181129C22

## P01 WLAN2.4G\_802.11g\_Bottom\_0mm\_Ch11\_EUT 1\_Ant0+1

#### **DUT: 181129C22**

Communication System: WLAN 2.4G; Frequency: 2462 MHz; Duty Cycle: 1:1.04


Medium: B19T27N1\_1225 Medium parameters used: f = 2462 MHz;  $\sigma = 2.029$  S/m;  $\epsilon_r = 51.52$ ;  $\rho = 1.52$ 

Date: 2018/12/25

 $1000 \text{ kg/m}^3$ 

Ambient Temperature : 23.6 °C; Liquid Temperature : 23.3 °C

- Probe: EX3DV4 SN3650; ConvF(7.61, 7.61, 7.61); Calibrated: 2018/07/27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2018/08/27
- Phantom: ELI Phantom 1206; Type: QDOVA002AA;
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)
- **Area Scan (111x321x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm Maximum value of SAR (interpolated) = 0.135 W/kg
- Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 7.348 V/m; Power Drift = -0.06 dB Peak SAR (extrapolated) = 0.318 W/kg SAR(1 g) = 0.159 W/kg; SAR(10 g) = 0.077 W/kg Maximum value of SAR (measured) = 0.227 W/kg



## P02 WLAN5.6G\_802.11ac VHT80\_Bottom\_0mm\_Ch138\_EUT 1\_Ant0

#### **DUT: 181129C22**

Communication System: WLAN 5G; Frequency: 5690 MHz; Duty Cycle: 1:1.18


Medium: B34T60N1\_1225 Medium parameters used: f = 5690 MHz;  $\sigma = 5.715$  S/m;  $\epsilon_r = 50.043$ ;  $\rho = 5.715$  S/m;  $\epsilon_r = 50.043$ ;  $\epsilon_r = 50.043$ 

Date: 2018/12/25

 $1000 \text{ kg/m}^3$ 

Ambient Temperature : 23.6 °C; Liquid Temperature : 23.3 °C

- Probe: EX3DV4 SN3650; ConvF(4.6, 4.6, 4.6); Calibrated: 2018/07/27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2018/08/27
- Phantom: ELI Phantom 1206; Type: QDOVA002AA;
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)
- **Area Scan (131x381x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR (interpolated) = 0.191 W/kg
- Zoom Scan (6x6x12)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=2mm Reference Value = 4.969 V/m; Power Drift = -0.13 dB Peak SAR (extrapolated) = 0.525 W/kg SAR(1 g) = 0.128 W/kg; SAR(10 g) = 0.034 W/kg Maximum value of SAR (measured) = 0.332 W/kg



## P03 WLAN5.8G\_802.11ac VHT80\_Bottom\_0mm\_Ch155\_EUT 1\_Ant1

#### **DUT: 181129C22**

Communication System: WLAN 5G; Frequency: 5775 MHz; Duty Cycle: 1:1.18


Medium: B34T60N1\_1225 Medium parameters used: f = 5775 MHz;  $\sigma = 5.791$  S/m;  $\epsilon_r = 49.97$ ;  $\rho =$ 

Date: 2018/12/25

 $1000 \text{ kg/m}^3$ 

Ambient Temperature : 23.6 °C; Liquid Temperature : 23.3 °C

- Probe: EX3DV4 SN3650; ConvF(4.6, 4.6, 4.6); Calibrated: 2018/07/27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2018/08/27
- Phantom: ELI Phantom 1206; Type: QDOVA002AA;
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)
- Area Scan (131x381x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR (interpolated) = 0.399 W/kg
- Zoom Scan (6x6x12)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=2mm Reference Value = 4.414 V/m; Power Drift = -0.15 dB Peak SAR (extrapolated) = 0.316 W/kg SAR(1 g) = 0.061 W/kg; SAR(10 g) = 0.020 W/kg Maximum value of SAR (measured) = 0.195 W/kg



## P04 WLAN2.4G\_802.11b\_Bottom Side\_0mm\_Ch1\_EUT 1\_Ant0

#### **DUT: 181129C22**

Communication System: WLAN 2.4G; Frequency: 2412 MHz; Duty Cycle: 1:1.01


Medium: B19T27N1\_1225 Medium parameters used: f = 2412 MHz;  $\sigma = 1.973$  S/m;  $\epsilon_r = 51.663$ ;  $\rho = 1.973$  S/m;  $\epsilon_r = 1.973$ 

Date: 2018/12/25

 $1000 \text{ kg/m}^3$ 

Ambient Temperature : 23.6 °C; Liquid Temperature : 23.3 °C

- Probe: EX3DV4 SN3650; ConvF(7.61, 7.61, 7.61); Calibrated: 2018/07/27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2018/08/27
- Phantom: ELI Phantom 1206; Type: QDOVA002AA;
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)
- Area Scan (91x321x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm Maximum value of SAR (interpolated) = 0.648 W/kg
- Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 17.08 V/m; Power Drift = -0.09 dB Peak SAR (extrapolated) = 0.994 W/kg SAR(1 g) = 0.441 W/kg; SAR(10 g) = 0.199 W/kg Maximum value of SAR (measured) = 0.687 W/kg



## P05 WLAN5.3G\_802.11n HT40\_Bottom Side\_0mm\_Ch54\_EUT 1\_Ant1

#### **DUT: 181129C22**

Communication System: WLAN 5G; Frequency: 5270 MHz; Duty Cycle: 1:1.09

Medium: B34T60N1\_1225 Medium parameters used: f = 5270 MHz;  $\sigma = 5.282$  S/m;  $\varepsilon_r = 50.784$ ;  $\rho =$ 

Date: 2018/12/25


 $1000 \text{ kg/m}^3$ 

Ambient Temperature : 23.6  $^{\circ}$ C ; Liquid Temperature : 23.3  $^{\circ}$ C

#### DASY5 Configuration:

- Probe: EX3DV4 SN3650; ConvF(4.85, 4.85, 4.85); Calibrated: 2018/07/27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2018/08/27
- Phantom: ELI Phantom 1206; Type: QDOVA002AA;
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)
- **Area Scan (101x381x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR (interpolated) = 0.592 W/kg
- Zoom Scan (6x6x12)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=2mm Reference Value = 7.144 V/m; Power Drift = -0.06 dB Peak SAR (extrapolated) = 4.94 W/kg SAR(1 g) = 1.01 W/kg; SAR(10 g) = 0.232 W/kg

Maximum value of SAR (measured) = 0.232 W/kg



## P06 WLAN5.6G\_802.11ac VHT80\_Bottom Side\_0mm\_Ch106\_EUT 1\_Ant1

#### **DUT: 181129C22**

Communication System: WLAN 5G; Frequency: 5530 MHz; Duty Cycle: 1:1.18


Medium: B34T60N1\_1225 Medium parameters used: f = 5530 MHz;  $\sigma = 5.527$  S/m;  $\epsilon_r = 50.478$ ;  $\rho = 5.527$  S/m;  $\epsilon_r = 50.478$ ;  $\epsilon_r = 50.478$ 

Date: 2018/12/25

 $1000 \text{ kg/m}^3$ 

Ambient Temperature: 23.6 °C; Liquid Temperature: 23.3 °C

- Probe: EX3DV4 SN3650; ConvF(4.32, 4.32, 4.32); Calibrated: 2018/07/27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2018/08/27
- Phantom: ELI Phantom 1206; Type: QDOVA002AA;
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)
- **Area Scan (101x381x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR (interpolated) = 0.464 W/kg
- Zoom Scan (6x6x12)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=2mm Reference Value = 6.352 V/m; Power Drift = -0.07 dB Peak SAR (extrapolated) = 4.47 W/kg SAR(1 g) = 0.571 W/kg; SAR(10 g) = 0.144 W/kg Maximum value of SAR (measured) = 2.44 W/kg



## P07 WLAN5.8G\_802.11ac VHT80\_Bottom Side\_0mm\_Ch155\_EUT 1\_Ant1

#### **DUT: 181129C22**

Communication System: WLAN 5G; Frequency: 5775 MHz; Duty Cycle: 1:1.18


Medium: B34T60N1\_1225 Medium parameters used: f = 5775 MHz;  $\sigma = 5.791$  S/m;  $\epsilon_r = 49.97$ ;  $\rho = 6.791$  MHz;  $\sigma = 6.791$  S/m;  $\epsilon_r = 6.791$  S/m

Date: 2018/12/25

 $1000 \text{ kg/m}^3$ 

Ambient Temperature : 23.6  $^{\circ}$ C ; Liquid Temperature : 23.3  $^{\circ}$ C

- Probe: EX3DV4 SN3650; ConvF(4.6, 4.6, 4.6); Calibrated: 2018/07/27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2018/08/27
- Phantom: ELI Phantom 1206; Type: QDOVA002AA;
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)
- Area Scan (101x381x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR (interpolated) = 0.365 W/kg
- Zoom Scan (6x6x12)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=2mm Reference Value = 5.842 V/m; Power Drift = 0.05 dB Peak SAR (extrapolated) = 2.63 W/kg SAR(1 g) = 0.401 W/kg; SAR(10 g) = 0.111 W/kg Maximum value of SAR (measured) = 1.33 W/kg







# Appendix C. Calibration Certificate for Probe and Dipole

The SPEAG calibration certificates are shown as follows.

Report Format Version 5.0.0 Issued Date : Jan. 14, 2019

Report No. : SA181129C17D Reference No. : 181129C22

## Calibration Laboratory of Schmid & Partner Engineering AG

Zeughausstrasse 43, 8004 Zurich, Switzerland





Schweizerischer Kalibrierdienst
Service suisse d'étalonnage
Servizio svizzero di taratura
Swiss Calibration Service

Accreditation No.: SCS 0108

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Client

**B.V. ADT (Auden)** 

Certificate No: D2450V2-737\_Aug18

# **CALIBRATION CERTIFICATE**

Object **D2450V2 - SN:737** 

Calibration procedure(s) QA CAL-05.v10

Calibration procedure for dipole validation kits above 700 MHz

Calibration date: August 24, 2018

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID#	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-18 (No. 217-02672/02673)	Apr-19
Power sensor NRP-Z91	SN: 103244	04-Apr-18 (No. 217-02672)	Apr-19
Power sensor NRP-Z91	SN: 103245	04-Apr-18 (No. 217-02673)	Apr-19
Reference 20 dB Attenuator	SN: 5058 (20k)	04-Apr-18 (No. 217-02682)	Apr-19
Type-N mismatch combination	SN: 5047.2 / 06327	04-Apr-18 (No. 217-02683)	Apr-19
Reference Probe EX3DV4	SN: 7349	30-Dec-17 (No. EX3-7349_Dec17)	Dec-18
DAE4	SN: 601	26-Oct-17 (No. DAE4-601_Oct17)	Oct-18
Secondary Standards	ID#	Check Date (in house)	Scheduled Check
Power meter EPM-442A	SN: GB37480704	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: US37292783	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: MY41092317	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
RF generator R&S SMT-06	SN: 100972	15-Jun-15 (in house check Oct-16)	In house check: Oct-18
Network Analyzer Agilent E8358A	SN: US41080477	31-Mar-14 (in house check Oct-17)	In house check: Oct-18
	Name	Function	Signature
Calibrated by:	Manu Seitz	Laboratory Technician	and .
			V
Approved by:	Katja Pokovic	Technical Manager	eout

Issued: August 24, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: D2450V2-737\_Aug18

## **Calibration Laboratory of**

Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland





S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
Servizio svizzero di taratura
Swiss Calibration Service

Accreditation No.: SCS 0108

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA

Multilateral Agreement for the recognition of calibration certificates

#### Glossary:

TSL

tissue simulating liquid

ConvF N/A sensitivity in TSL / NORM x,y,z not applicable or not measured

## Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- b) IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- c) IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- d) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

#### **Additional Documentation:**

e) DASY4/5 System Handbook

#### **Methods Applied and Interpretation of Parameters:**

- Measurement Conditions: Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL: The dipole is mounted with the spacer to position its feed
  point exactly below the center marking of the flat phantom section, with the arms oriented
  parallel to the body axis.
- Feed Point Impedance and Return Loss: These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay: One-way delay between the SMA connector and the antenna feed point.
   No uncertainty required.
- SAR measured: SAR measured at the stated antenna input power.
- SAR normalized: SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters: The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

## **Measurement Conditions**

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.10.1
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	2450 MHz ± 1 MHz	

# **Head TSL parameters**

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	39.2	1.80 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	37.7 ± 6 %	1.86 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	OWNER.	( and a

## **SAR** result with Head TSL

SAR averaged over 1 cm³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	13.2 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	51.5 W/kg ± 17.0 % (k=2)

SAR averaged over 10 cm³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	6.13 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	24.2 W/kg ± 16.5 % (k=2)

# **Body TSL parameters**

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	52.7	1.95 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	51.8 ± 6 %	2.02 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C		****

## **SAR** result with Body TSL

SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	12.9 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	50.5 W/kg ± 17.0 % (k=2)

SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL	condition	
SAR measured	250 mW input power	6.01 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	23.8 W/kg ± 16.5 % (k=2)

Certificate No: D2450V2-737\_Aug18

## Appendix (Additional assessments outside the scope of SCS 0108)

## **Antenna Parameters with Head TSL**

Impedance, transformed to feed point	$55.6 \Omega + 4.1 j\Omega$
Return Loss	- 23.7 dB

#### **Antenna Parameters with Body TSL**

Impedance, transformed to feed point	49.4 Ω + 7.3 jΩ
Return Loss	- 22.7 dB

## **General Antenna Parameters and Design**

Electrical Delay (one direction)	1.162 ns

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

#### **Additional EUT Data**

Manufactured by	SPEAG
Manufactured on	August 26, 2003

Certificate No: D2450V2-737\_Aug18

#### **DASY5 Validation Report for Head TSL**

Date: 23.08.2018

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:737

Communication System: UID 0 - CW; Frequency: 2450 MHz

Medium parameters used: f = 2450 MHz;  $\sigma = 1.86 \text{ S/m}$ ;  $\varepsilon_r = 37.7$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

#### DASY52 Configuration:

• Probe: EX3DV4 - SN7349; ConvF(7.88, 7.88, 7.88) @ 2450 MHz; Calibrated: 30.12.2017

• Sensor-Surface: 1.4mm (Mechanical Surface Detection)

• Electronics: DAE4 Sn601; Calibrated: 26.10.2017

• Phantom: Flat Phantom 5.0 (front); Type: QD 000 P50 AA; Serial: 1001

• DASY52 52.10.1(1476); SEMCAD X 14.6.11(7439)

## Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 115.2 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 26.1 W/kg


SAR(1 g) = 13.2 W/kg; SAR(10 g) = 6.13 W/kg

Maximum value of SAR (measured) = 21.7 W/kg



0 dB = 21.7 W/kg = 13.36 dBW/kg

## Impedance Measurement Plot for Head TSL



## **DASY5 Validation Report for Body TSL**

Date: 24.08.2018

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:737

Communication System: UID 0 - CW; Frequency: 2450 MHz

Medium parameters used: f = 2450 MHz;  $\sigma = 2.02$  S/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

#### **DASY52 Configuration:**

Probe: EX3DV4 - SN7349; ConvF(8.01, 8.01, 8.01) @ 2450 MHz; Calibrated: 30.12.2017

• Sensor-Surface: 1.4mm (Mechanical Surface Detection)

• Electronics: DAE4 Sn601; Calibrated: 26.10.2017

• Phantom: Flat Phantom 5.0 (back); Type: QD 000 P50 AA; Serial: 1002

• DASY52 52.10.1(1476); SEMCAD X 14.6.11(7439)

# Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 107.8 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 25.5 W/kg


SAR(1 g) = 12.9 W/kg; SAR(10 g) = 6.01 W/kg

Maximum value of SAR (measured) = 20.9 W/kg



0 dB = 20.9 W/kg = 13.20 dBW/kg

## Impedance Measurement Plot for Body TSL



## Calibration Laboratory of

Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland





S Schweizerischer Kalibrierdienst
Service suisse d'étalonnage
Servizio svizzero di taratura
Swiss Calibration Service

Accreditation No.: SCS 0108

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Client

**BV ADT Korea (Auden)** 

Certificate No: D5GHzV2-1019\_Mar18

## **CALIBRATION CERTIFICATE**

Object

D5GHzV2 - SN:1019

Calibration procedure(s)

QA CAL-22.v3

Calibration procedure for dipole validation kits between 3-6 GHz

Calibration date:

March 22, 2018

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%,

Calibration Equipment used (M&TE critical for calibration)

Drimon: Standarda	ID#	Cal Date (Certificate No.)	Scheduled Calibration
Primary Standards			
Power meter NRP	SN: 104778	04-Apr-17 (No. 217-02521/02522)	Apr-18
Power sensor NRP-Z91	SN: 103244	04-Apr-17 (No. 217-02521)	Apr-18
Power sensor NRP-Z91	SN: 103245	04-Apr-17 (No. 217-02522)	Apr-18
Reference 20 dB Attenuator	SN: 5058 (20k)	07-Apr-17 (No. 217-02528)	Apr-18
Type-N mismatch combination	SN: 5047.2 / 06327	07-Apr-17 (No. 217-02529)	Apr-18
Reference Probe EX3DV4	SN: 3503	30-Dec-17 (No. EX3-3503_Dec17)	Dec-18
DAE4	SN: 601	26-Oct-17 (No. DAE4-601_Oct17)	Oct-18
	51		
Secondary Standards	ID#	Check Date (in house)	Scheduled Check
Power meter EPM-442A	SN: GB37480704	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: US37292783	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: MY41092317	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
RF generator R&S SMT-06	SN: 100972	15-Jun-15 (in house check Oct-16)	In house check: Oct-18
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-17)	In house check: Oct-18
	Name	Function	Signature
Calibrated by:	Jeton Kastrati	Laboratory Technician <	7-10
Approved by:	Katja Pokovic	Technical Manager	POM
	The state of the state of		1000es

Issued: March 26, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: D5GHzV2-1019\_Mar18

## **Calibration Laboratory of**

Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland





S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
Servizio svizzero di taratura
Swiss Calibration Service

Accreditation No.: SCS 0108

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

#### Glossary:

TSL

tissue simulating liquid

ConvF

sensitivity in TSL / NORM x,y,z

N/A

not applicable or not measured

## Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- b) IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- c) IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- d) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

#### **Additional Documentation:**

e) DASY4/5 System Handbook

#### Methods Applied and Interpretation of Parameters:

- Measurement Conditions: Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL: The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss: These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay: One-way delay between the SMA connector and the antenna feed point.
   No uncertainty required.
- SAR measured: SAR measured at the stated antenna input power.
- SAR normalized: SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters: The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Certificate No: D5GHzV2-1019\_Mar18 Page 2 of 15

#### **Measurement Conditions**

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.10.0
Extrapolation	Advanced Extrapolation	702.10.0
Phantom	Modular Flat Phantom V5.0	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, $dy = 4.0$ mm, $dz = 1.4$ mm	Graded Ratio = 1.4 (Z direction)
Frequency	5250 MHz ± 1 MHz 5600 MHz ± 1 MHz 5750 MHz ± 1 MHz 5800 MHz ± 1 MHz	

## **Head TSL parameters at 5250 MHz**

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.9	4.71 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	36.2 ± 6 %	4.58 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	(4444)	- days

## SAR result with Head TSL at 5250 MHz

SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	7.85 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	78.6 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL	condition	
SAR measured	100 mW input power	2.28 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	22.8 W/kg ± 19.5 % (k=2)

Certificate No: D5GHzV2-1019\_Mar18 Page 3 of 15

# Head TSL parameters at 5600 MHz The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.5	5.07 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	35.7 ± 6 %	4.94 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C		F-2244

# SAR result with Head TSL at 5600 MHz

SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	8.49 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	84.9 W / kg ± 19.9 % (k=2)

SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL	condition	
SAR measured	100 mW input power	2.43 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	24.3 W/kg ± 19.5 % (k=2)

# Head TSL parameters at 5750 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.4	5.22 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	35.5 ± 6 %	5.10 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C		

#### SAR result with Head TSL at 5750 MHz

SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	7.94 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	79.4 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL	condition	
SAR measured	100 mW input power	2.27 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	22.7 W/kg ± 19.5 % (k=2)

Certificate No: D5GHzV2-1019\_Mar18

# Head TSL parameters at 5800 MHz The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.3	5.27 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	35.4 ± 6 %	5.16 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	Hene:	****

# SAR result with Head TSL at 5800 MHz

SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	8.09 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	80.9 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL	condition	
SAR measured	100 mW input power	2.30 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	23.0 W/kg ± 19.5 % (k=2)

Certificate No: D5GHzV2-1019\_Mar18 Page 5 of 15

# **Body TSL parameters at 5250 MHz**

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	48.9	5.36 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	47.1 ± 6 %	5.49 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	(####)	

## SAR result with Body TSL at 5250 MHz

SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL	Condition	
SAR measured	100 mW input power	7.54 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	74.9 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL	condition	
SAR measured	100 mW input power	2.10 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	20.8 W/kg ± 19.5 % (k=2)

## Body TSL parameters at 5600 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	48.5	5.77 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	46.4 ± 6 %	5.97 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	10000	7.000

## SAR result with Body TSL at 5600 MHz

SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL	Condition	
SAR measured	100 mW input power	7.99 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	79.3 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL	condition	
SAR measured	100 mW input power	2.24 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	22.2 W/kg ± 19.5 % (k=2)

Certificate No: D5GHzV2-1019\_Mar18 Page 6 of 15

## Body TSL parameters at 5750 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	48.3	5.94 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	46.2 ± 6 %	6.18 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C		

## SAR result with Body TSL at 5750 MHz

SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL	Condition	
SAR measured	100 mW input power	7.50 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	74.5 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL	condition	
SAR measured	100 mW input power	2.10 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	20.8 W/kg ± 19.5 % (k=2)

## **Body TSL parameters at 5800 MHz**

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	48.2	6.00 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	46.1 ± 6 %	6.25 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C		(and and

# SAR result with Body TSL at 5800 MHz

SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL	Condition	
SAR measured	100 mW input power	7.58 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	75.2 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL	condition	
SAR measured	100 mW input power	2.11 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	20.9 W/kg ± 19.5 % (k=2)

# Appendix (Additional assessments outside the scope of SCS 0108)

## Antenna Parameters with Head TSL at 5250 MHz

Impedance, transformed to feed point	54.8 Ω - 3.5 jΩ
Return Loss	- 24.9 dB

## Antenna Parameters with Head TSL at 5600 MHz

Impedance, transformed to feed point	57.9 Ω + 0.9 jΩ
Return Loss	- 22.6 dB

#### Antenna Parameters with Head TSL at 5750 MHz

Impedance, transformed to feed point	$56.2 \Omega + 6.3 j\Omega$
Return Loss	- 21.6 dB

## Antenna Parameters with Head TSL at 5800 MHz

Impedance, transformed to feed point	$54.2~\Omega + 4.6~\mathrm{j}\Omega$
Return Loss	- 24.5 dB

#### Antenna Parameters with Body TSL at 5250 MHz

Impedance, transformed to feed point	54.8 Ω - 2.6 jΩ
Return Loss	- 25.6 dB

#### Antenna Parameters with Body TSL at 5600 MHz

Impedance, transformed to feed point	59.3 Ω + 0.7 jΩ
Return Loss	- 21.4 dB

#### Antenna Parameters with Body TSL at 5750 MHz

Impedance, transformed to feed point	$58.5~\Omega + 6.2~\mathrm{j}\Omega$
Return Loss	- 20.3 dB

## Antenna Parameters with Body TSL at 5800 MHz

Impedance, transformed to feed point	57.2 Ω + 4.4 jΩ
Return Loss	- 22.1 dB

Certificate No: D5GHzV2-1019\_Mar18

## **General Antenna Parameters and Design**

Electrical Delay (one direction)	1.206 ns

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

#### **Additional EUT Data**

Manufactured by	SPEAG
Manufactured on	February 05, 2004

Certificate No: D5GHzV2-1019\_Mar18 Page 9 of 15

## **DASY5 Validation Report for Head TSL**

Date: 21.03.2018

Test Laboratory: SPEAG, Zurich, Switzerland

## DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1019

Communication System: UID 0 - CW; Frequency: 5250 MHz, Frequency: 5600 MHz, Frequency: 5750 MHz,

Frequency: 5800 MHz

Medium parameters used: f = 5250 MHz;  $\sigma$  = 4.58 S/m;  $\epsilon_r$  = 36.2;  $\rho$  = 1000 kg/m³, Medium parameters used: f = 5600 MHz;  $\sigma$  = 4.94 S/m;  $\epsilon_r$  = 35.7;  $\rho$  = 1000 kg/m³, Medium parameters used: f = 5750 MHz;  $\sigma$  = 5.1 S/m;  $\epsilon_r$  = 35.5;  $\rho$  = 1000 kg/m³,

Medium parameters used: f = 5800 MHz;  $\sigma = 5.16$  S/m;  $\varepsilon_r = 35.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

#### DASY52 Configuration:

- Probe: EX3DV4 SN3503; ConvF(5.51, 5.51, 5.51); Calibrated: 30.12.2017,
   ConvF(5.05, 5.05, 5.05); Calibrated: 30.12.2017, ConvF(4.98, 4.98, 4.98); Calibrated: 30.12.2017,
   ConvF(4.96, 4.96, 4.96); Calibrated: 30.12.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601 (5GHz); Calibrated: 26.10.2017
- Phantom: Flat Phantom 5.0 (front); Type: QD 000 P50 AA; Serial: 1001
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

## Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5250 MHz/Zoom Scan, dist=1.4mm

(8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 73.01 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 27.4 W/kg

SAR(1 g) = 7.85 W/kg; SAR(10 g) = 2.28 W/kg

Maximum value of SAR (measured) = 18.1 W/kg

#### Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5600 MHz/Zoom Scan, dist=1.4mm

(8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 74.12 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 32.5 W/kg

SAR(1 g) = 8.49 W/kg; SAR(10 g) = 2.43 W/kg

Maximum value of SAR (measured) = 20.3 W/kg

#### Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5750 MHz/Zoom Scan, dist=1.4mm

(8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 71.18 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 31.2 W/kg

SAR(1 g) = 7.94 W/kg; SAR(10 g) = 2.27 W/kg

Maximum value of SAR (measured) = 19.0 W/kg

Certificate No: D5GHzV2-1019\_Mar18

# Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5800 MHz/Zoom Scan, dist=1.4mm


(8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 71.51 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 31.9 W/kg


SAR(1 g) = 8.09 W/kg; SAR(10 g) = 2.3 W/kg

Maximum value of SAR (measured) = 19.4 W/kg



0 dB = 19.4 W/kg = 12.88 dBW/kg

## Impedance Measurement Plot for Head TSL



## **DASY5 Validation Report for Body TSL**

Date: 22.03.2018

Test Laboratory: SPEAG, Zurich, Switzerland

## DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1019

Communication System: UID 0 - CW; Frequency: 5250 MHz, Frequency: 5600 MHz, Frequency: 5750 MHz,

Frequency: 5800 MHz

Medium parameters used: f = 5250 MHz;  $\sigma = 5.49 \text{ S/m}$ ;  $\varepsilon_r = 47.1$ ;  $\rho = 1000 \text{ kg/m}^3$ ,

Medium parameters used: f = 5600 MHz;  $\sigma$  = 5.97 S/m;  $\epsilon_r$  = 46.4;  $\rho$  = 1000 kg/m³ ,

Medium parameters used: f = 5750 MHz;  $\sigma = 6.18 \text{ S/m}$ ;  $\varepsilon_r = 46.2$ ;  $\rho = 1000 \text{ kg/m}^3$ ,

Medium parameters used: f = 5800 MHz;  $\sigma = 6.25 \text{ S/m}$ ;  $\varepsilon_r = 46.1$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

#### **DASY52 Configuration:**

- Probe: EX3DV4 SN3503; ConvF(5.26, 5.26, 5.26); Calibrated: 30.12.2017,
   ConvF(4.65, 4.65, 4.65); Calibrated: 30.12.2017, ConvF(4.57, 4.57, 4.57); Calibrated: 30.12.2017,
   ConvF(4.53, 4.53, 4.53); Calibrated: 30.12.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601 (5GHz); Calibrated: 26.10.2017
- Phantom: Flat Phantom 5.0 (back); Type: QD 000 P50 AA; Serial: 1002
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

#### Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5250 MHz/Zoom Scan, dist=1.4mm

(8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 65.68 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 29.3 W/kg

SAR(1 g) = 7.54 W/kg; SAR(10 g) = 2.1 W/kg

Maximum value of SAR (measured) = 17.3 W/kg

### Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5600 MHz/Zoom Scan, dist=1.4mm

(8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 66.11 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 33.6 W/kg

SAR(1 g) = 7.99 W/kg; SAR(10 g) = 2.24 W/kg

Maximum value of SAR (measured) = 18.9 W/kg

#### Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5750 MHz/Zoom Scan, dist=1.4mm

(8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 63.79 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 32.1 W/kg

SAR(1 g) = 7.5 W/kg; SAR(10 g) = 2.1 W/kg

Maximum value of SAR (measured) = 17.9 W/kg

## Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5800 MHz/Zoom Scan, dist=1.4mm


(8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 63.81 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 32.8 W/kg


SAR(1 g) = 7.58 W/kg; SAR(10 g) = 2.11 W/kg

Maximum value of SAR (measured) = 18.1 W/kg



0 dB = 18.1 W/kg = 12.58 dBW/kg

## Impedance Measurement Plot for Body TSL



### Calibration Laboratory of Schmid & Partner **Engineering AG**







Schweizerischer Kalibrierdienst S Service suisse d'étalonnage C Servizio svizzero di taratura **Swiss Calibration Service** 

Accreditation No.: SCS 0108

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Client

**B.V.ADT** (Auden)

Certificate No: EX3-3650\_Jul18

## **CALIBRATION CERTIFICATE**

Object

EX3DV4 - SN:3650

Calibration procedure(s)

QA CAL-01.v9, QA CAL-14.v4, QA CAL-23.v5, QA CAL-25.v6

Calibration procedure for dosimetric E-field probes

Calibration date:

July 27, 2018

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-18 (No. 217-02672/02673)	Apr-19
Power sensor NRP-Z91	SN: 103244	04-Apr-18 (No. 217-02672)	Apr-19
Power sensor NRP-Z91	SN: 103245	04-Apr-18 (No. 217-02673)	Apr-19
Reference 20 dB Attenuator	SN: S5277 (20x)	04-Apr-18 (No. 217-02682)	Apr-19
Reference Probe ES3DV2	SN: 3013	30-Dec-17 (No. ES3-3013_Dec17)	Dec-18
DAE4	SN: 660	21-Dec-17 (No. DAE4-660_Dec17)	Dec-18
Secondary Standards	ID	Check Date (in house)	Scheduled Check
Power meter E4419B	SN: GB41293874	06-Apr-16 (in house check Jun-18)	In house check: Jun-20
Power sensor E4412A	SN: MY41498087	06-Apr-16 (in house check Jun-18)	In house check: Jun-20
Power sensor E4412A	SN: 000110210	06-Apr-16 (in house check Jun-18)	In house check: Jun-20
RF generator HP 8648C	SN: US3642U01700	04-Aug-99 (in house check Jun-18)	In house check: Jun-20
Network Analyzer E8358A	SN: US41080477	31-Mar-14 (in house check Oct-17)	In house check: Oct-18

Calibrated by:

Name Claudio Leubler Function

Laboratory Technician

Approved by:

Katja Pokovic

Technical Manager

Issued: July 28, 2018

Signature

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: EX3-3650\_Jul18

Page 1 of 39

#### Calibration Laboratory of

Schmid & Partner **Engineering AG** Zeughausstrasse 43, 8004 Zurich, Switzerland





Schweizerischer Kalibrierdienst S Service suisse d'étalonnage

C Servizio svizzero di taratura S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates Accreditation No.: SCS 0108

#### Glossary:

**TSL** NORMx,y,z tissue simulating liquid sensitivity in free space

ConvF

sensitivity in TSL / NORMx.v.z

DCP

diode compression point

CF A, B, C, D crest factor (1/duty\_cycle) of the RF signal modulation dependent linearization parameters

Polarization φ

φ rotation around probe axis

Polarization 9

9 rotation around an axis that is in the plane normal to probe axis (at measurement center),

i.e., 9 = 0 is normal to probe axis

Connector Angle

information used in DASY system to align probe sensor X to the robot coordinate system

## Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- b) IEC 62209-1, ", "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from handheld and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- c) IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- d) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

### Methods Applied and Interpretation of Parameters:

- *NORMx,y,z:* Assessed for E-field polarization  $\vartheta = 0$  (f  $\leq 900$  MHz in TEM-cell; f > 1800 MHz: R22 waveguide). NORMx,y,z are only intermediate values, i.e., the uncertainties of NORMx,y,z does not affect the E2-field uncertainty inside TSL (see below ConvF).
- NORM(f)x,y,z = NORMx,y,z \* frequency\_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCPx,y,z: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- Ax,y,z; Bx,y,z; Cx,y,z; Dx,y,z; VRx,y,z: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters: Assessed in flat phantom using E-field (or Temperature Transfer Standard for f ≤ 800 MHz) and inside waveguide using analytical field distributions based on power measurements for f > 800 MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORMx,y,z \* ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100
- Spherical isotropy (3D deviation from isotropy): in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle: The angle is assessed using the information gained by determining the NORMx (no uncertainty required).

Certificate No: EX3-3650, Jul18

# Probe EX3DV4

SN:3650

Manufactured:

March 18, 2008

Calibrated:

July 27, 2018

Calibrated for DASY/EASY Systems (Note: non-compatible with DASY2 system!)

#### **Basic Calibration Parameters**

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm $(\mu V/(V/m)^2)^A$	0.40	0.40	0.40	± 10.1 %
DCP (mV) <sup>B</sup>	103.4	99.7	101.1	

**Modulation Calibration Parameters** 

UID	Communication System Name		Α	В	С	D	VR	Unc
			dB	dB√μV		dB	mV	(k=2)
0	CW	X	0.0	0.0	1.0	0.00	148.9	±3.3 %
		Y	0.0	0.0	1.0		131.8	
		Z	0.0	0.0	1.0		146.8	

Note: For details on UID parameters see Appendix.

#### **Sensor Model Parameters**

	C1 fF	C2 fF	α V <sup>-1</sup>	T1 ms.V <sup>-2</sup>	T2 ms.V <sup>-1</sup>	T3 ms	T4 V <sup>-2</sup>	T5 V-1	Т6
X	25.57	186.1	34.29	6.795	0.139	5.021	1.799	0.000	1.005
Υ	44.46	346.1	38.30	7.672	0.711	5.047	0.000	0.618	1.009
Z	45.96	341.9	35.52	11.21	0.385	5.066	1.556	0.255	1.008

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

A The uncertainties of Norm X,Y,Z do not affect the E2-field uncertainty inside TSL (see Pages 5 and 6).

B Numerical linearization parameter: uncertainty not required.
E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

## Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) <sup>C</sup>	Relative Permittivity <sup>F</sup>	Conductivity (S/m) <sup>F</sup>	ConvF X	ConvF Y	ConvF Z	Alpha <sup>G</sup>	Depth <sup>G</sup> (mm)	Unc (k=2)
750	41.9	0.89	10.34	10.34	10.34	0.50	0.80	± 12.0 %
835	41.5	0.90	9.88	9.88	9.88	0.47	0.80	± 12.0 %
900	41.5	0.97	9.64	9.64	9.64	0.42	0.84	± 12.0 %
1450	40.5	1.20	8.79	8.79	8.79	0.39	0.80	± 12.0 %
1640	40.2	1.31	8.62	8.62	8.62	0.33	0.85	± 12.0 %
1750	40.1	1.37	8.60	8.60	8.60	0.36	0.80	± 12.0 %
1900	40.0	1.40	8.28	8.28	8.28	0.42	0.80	± 12.0 %
2300	39.5	1.67	8.03	8.03	8.03	0.34	0.95	± 12.0 %
2450	39.2	1.80	7.64	7.64	7.64	0.38	0.90	± 12.0 %
2600	39.0	1.96	7.48	7.48	7.48	0.34	0.95	± 12.0 %
3500	37.9	2.91	7.23	7.23	7.23	0.25	1.25	± 13.1 %
5250	35.9	4.71	5.46	5.46	5.46	0.40	1.80	± 13.1 %
5600	35.5	5.07	5.05	5.05	5.05	0.40	1.80	± 13.1 %
5750	35.4	5.22	5.33	5.33	5.33	0.40	1.80	± 13.1 %

 $<sup>^{\</sup>rm C}$  Frequency validity above 300 MHz of  $\pm$  100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to  $\pm$  50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is  $\pm$  10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to  $\pm$  110 MHz.

F At frequencies below 3 GHz, the validity of tissue parameters (ε and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ε and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConyF uncertainty for indicated target tissue parameters.

the ConvF uncertainty for indicated target tissue parameters.

Galpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

## Calibration Parameter Determined in Body Tissue Simulating Media

f (MHz) <sup>C</sup>	Relative Permittivity <sup>F</sup>	Conductivity (S/m) F	ConvF X	ConvF Y	ConvF Z	Alpha <sup>G</sup>	Depth <sup>G</sup> (mm)	Unc (k=2)
750	55.5	0.96	9.91	9.91	9.91	0.44	0.82	± 12.0 %
835	55.2	0.97	9.74	9.74	9.74	0.35	0.97	± 12.0 %
1640	53.7	1.42	8.59	8.59	8.59	0.38	0.84	± 12.0 %
1750	53.4	1.49	8.20	8.20	8.20	0.29	1.03	± 12.0 %
1900	53.3	1.52	7.89	7.89	7.89	0.38	0.85	± 12.0 %
2300	52.9	1.81	7.77	7.77	7.77	0.38	0.90	± 12.0 %
2450	52.7	1.95	7.61	7.61	7.61	0.33	0.96	± 12.0 %
2600	52.5	2.16	7.48	7.48	7.48	0.16	1.08	± 12.0 %
3500	51.3	3.31	7.10	7.10	7.10	0.26	1.20	± 13.1 %
5250	48.9	5.36	4.85	4.85	4.85	0.50	1.90	± 13.1 %
5600	48.5	5.77	4.32	4.32	4.32	0.50	1.90	± 13.1 %
5750	48.3	5.94	4.60	4.60	4.60	0.50	1.90	± 13.1 %


 $<sup>^{\</sup>rm C}$  Frequency validity above 300 MHz of  $\pm$  100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to  $\pm$  50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is  $\pm$  10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to  $\pm$  110 MHz.

F At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to  $\pm$  10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to  $\pm$  5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

the ConvF uncertainty for indicated target tissue parameters.


Galpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.


# Frequency Response of E-Field (TEM-Cell:ifi110 EXX, Waveguide: R22)



Uncertainty of Frequency Response of E-field: ± 6.3% (k=2)


## Receiving Pattern ( $\phi$ ), $\vartheta = 0^{\circ}$






Uncertainty of Axial Isotropy Assessment: ± 0.5% (k=2)


## Dynamic Range f(SAR<sub>head</sub>) (TEM cell , f<sub>eval</sub>= 1900 MHz)






Uncertainty of Linearity Assessment: ± 0.6% (k=2)

## **Conversion Factor Assessment**



## Deviation from Isotropy in Liquid Error (φ, θ), f = 900 MHz




50

20 30

10

√ [qe∂]



270

315

## **Other Probe Parameters**

Sensor Arrangement	Triangular
Connector Angle (°)	-19.6
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	9 mm
Tip Diameter	2.5 mm
Probe Tip to Sensor X Calibration Point	1 mm
Probe Tip to Sensor Y Calibration Point	1 mm
Probe Tip to Sensor Z Calibration Point	1 mm
Recommended Measurement Distance from Surface	1.4 mm

EX3DV4- SN:3650 July 27, 2018

**Appendix: Modulation Calibration Parameters** 

UID	Communication System Name		A dB	B dBõV	С	D dB	VR mV	Max Unc <sup>E</sup> (k=2)
0	CW	Х	0.00	0.00	1.00	0.00	148.9	± 3.3 %
		Υ	0.00	0.00	1.00		131.8	
		Z	0.00	0.00	1.00		146.8	
10010- CAA	SAR Validation (Square, 100ms, 10ms)	Х	1.63	63.01	7.97	10.00	20.0	± 9.6 %
0,00		Υ	1.81	62.85	8.32		20.0	
		Z	2.61	67.64	11.02		20.0	
10011- CAB	UMTS-FDD (WCDMA)	X	2.17	83.31	22.35	0.00	150.0	± 9.6 %
		Υ	0.88	66.40	14.12		150.0	
		Z	1.21	71.04	17.38	2.11	150.0	0.004
10012- CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps)	X	1.21	66.64	17.22	0.41	150.0	± 9.6 %
		Y	1.03	63.09	14.69		150.0	
40040		Z	1.18	64.84	16.17	4.40	150.0	1000
10013- CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS- OFDM, 6 Mbps)	X	4.52	67.54	17.39	1.46	150.0	± 9.6 %
		Y	4.72	66.42	16.97		150.0 150.0	
10021- DAC	GSM-FDD (TDMA, GMSK)	X	4.85 100.00	66.87 106.28	17.28 23.05	9.39	50.0	± 9.6 %
D/ 10		Υ	36.94	97.20	21.84		50.0	
		Z	100.00	113.90	27.05		50.0	
10023- DAC	GPRS-FDD (TDMA, GMSK, TN 0)	Х	100.00	105.41	22.71	9.57	50.0	± 9.6 %
		Υ	15.19	86.91	19.04		50.0	
		Z	100.00	113.36	26.86		50.0	
10024- DAC	GPRS-FDD (TDMA, GMSK, TN 0-1)	Х	100.00	107.19	22.33	6.56	60.0	± 9.6 %
		Υ	100.00	105.32	21.93		60.0	
		Z	100.00	115.23	26.58		60.0	
10025- DAC	EDGE-FDD (TDMA, 8PSK, TN 0)	X	4.91	78.32	30.95	12.57	50.0	± 9.6 %
		Y	3.44	64.47	22.44		50.0	
10000	EDOE EDD (TDMA ODOK TNO 4)	Z	5.40	79.71	31.67	0.50	50.0	1000
10026- DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1)	X	6.20	86.65	31.56	9.56	60.0	± 9.6 %
10024- DAC 10025- DAC		Z	7.20 9.84	86.71 95.91	30.49 34.81		60.0	
10027-	GPRS-FDD (TDMA, GMSK, TN 0-1-2)	X	100.00	112.47	23.80	4.80	80.0	± 9.6 %
DAC		Y	100.00	102.75	19.99		80.0	
		Z	100.00	118.55	27.23		80.0	
10028- DAC	GPRS-FDD (TDMA, GMSK, TN 0-1-2-3)	X	100.00	126.41	28.80	3.55	100.0	± 9.6 %
_,,,_		Y	100.00	99.28	17.84		100.0	
		Z	100.00	123.95	28.78		100.0	
10029- DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1-2)	Х	4.09	76.79	26.19	7.80	80.0	± 9.6 %
		Υ	4.70	77.62	25.75		80.0	
10030-	IEEE 802.15.1 Bluetooth (GFSK, DH1)	Z X	5.74 100.00	82.73 104.97	28.46 20.86	5.30	80.0 70.0	± 9.6 %
CAA		\ \ \	400.00	100.00	20.44		70.0	
		Y	100.00	102.38	20.14		70.0 70.0	
10031- CAA	IEEE 802.15.1 Bluetooth (GFSK, DH3)	X	100.00	114.55 148.10	25.80 35.31	1.88	100.0	± 9.6 %
UAA		Υ	0.25	60.00	4.02		100.0	
		Z	100.00	128.83	29.15		100.0	

Certificate No: EX3-3650\_Jul18

10032- CAA	IEEE 802.15.1 Bluetooth (GFSK, DH5)	X	100.00	347.83	106.42	1.17	100.0	± 9.6 %
		Y	37.79	305.76	4.63		100.0	
		Z	100.00	154.91	38.00	1	100.0	
10033- CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH1)	Х	100.00	118.24	28.40	5.30	70.0	± 9.6 %
		Y	7.89	88.17	22.60		70.0	
		Z	100.00	131.66	35.63		70.0	
10034- CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH3)	Х	27.51	98.14	20.81	1.88	100.0	± 9.6 %
		Υ	1.99	72.14	15.28		100.0	
40005		Z	12.16	99.03	25.67		100.0	
10035- CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH5)	X	7.77	85.82	17.22	1.17	100.0	± 9.6 %
		Y	1.38	68.68	13.49		100.0	
40000	IFFE 000 45 4 Pt 1 11 (0 PPO)( PV)	Z	4.78	86.52	21.62		100.0	
10036- CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH1)	X	100.00	118.94	28.70	5.30	70.0	± 9.6 %
		Υ	11.67	94.17	24.52		70.0	
40007	LIFEE 000 45 4 PL	Z	100.00	132.20	35.88		70.0	
10037- CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH3)	X	7.16	84.89	17.39	1.88	100.0	± 9.6 %
		Υ	1.85	71.35	14.92		100.0	
10000		Z	9.68	95.89	24.76		100.0	
10038- CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH5)	×	14.31	92.43	19.20	1.17	100.0	± 9.6 %
		Υ	1.40	69.11	13.80		100.0	
		Z	4.95	87.43	22.06		100.0	
10039- CAB	CDMA2000 (1xRTT, RC1)	Х	1.61	71.97	12.34	0.00	150.0	± 9.6 %
		Y	1.26	67.65	12.53		150.0	
		Z	3.32	80.95	19.15		150.0	
10042- CAB	IS-54 / IS-136 FDD (TDMA/FDM, PI/4- DQPSK, Halfrate)	Х	100.00	102.88	20.78	7.78	50.0	± 9.6 %
		Υ	3.94	72.53	12.92		50.0	
		Z	100.00	110.47	24.72		50.0	
10044- CAA	IS-91/EIA/TIA-553 FDD (FDMA, FM)	X	0.00	122.94	1.65	0.00	150.0	± 9.6 %
		Υ	0.32	131.17	3.74		150.0	
		Z	0.00	113.60	4.10		150.0	
10048- CAA	DECT (TDD, TDMA/FDM, GFSK, Full Slot, 24)	Х	7.36	74.14	15.01	13.80	25.0	± 9.6 %
		Υ	6.43	73.09	15.81		25.0	
		Z	100.00	110.21	26.94		25.0	
10049- CAA	DECT (TDD, TDMA/FDM, GFSK, Double Slot, 12)	X	11.64	81.72	16.59	10.79	40.0	± 9.6 %
		Υ	6.45	75.81	15.65		40.0	
40050	LINETO TOD (TT. C.C.)	Z	100.00	111.69	26.44		40.0	
10056- CAA	UMTS-TDD (TD-SCDMA, 1.28 Mcps)	×	82.79	112.74	27.70	9.03	50.0	± 9.6 %
		Υ	13.48	89.97	23.17		50.0	
40050	7707 -77	Z	100.00	124.98	33.80		50.0	
10058- DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1-2-3)	X	3.36	72.94	23.66	6.55	100.0	± 9.6 %
		Y	3.73	73.43	23.20		100.0	
10059- CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2	Z X	4.39 1.24	77.09 67.96	25.26 17.95	0.61	100.0 110.0	± 9.6 %
	Mbps)		4.05	04.00	45.00		445.5	
		Y	1.05	64.03	15.22		110.0	
10060-	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5	Z	1.23	66.19	16.95	4.00	110.0	
CAB	Mbps)	X	100.00	153.88	41.81	1.30	110.0	± 9.6 %
		Y	13.60	107.18	27.29		110.0	
		Z	100.00	146.23	39.07		110.0	

10061-	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11	X	4.25	92.64	27.51	2.04	110.0	± 9.6 %
CAB	Mbps)					2.04		1 5.0 %
		Υ	2.24	78.00	21.09		110.0	
10000		Z	4.44	90.66	26.75		110.0	
10062- CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps)	X	4.34	67.60	16.88	0.49	100.0	± 9.6 %
		Y	4.53	66.41	16.40		100.0	
		Z	4.66	66.90	16.72		100.0	
10063- CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps)	Х	4.35	67.71	16.98	0.72	100.0	± 9.6 %
	- <del>** **</del>	Y	4.54	66.49	16.49		100.0	
		Z	4.68	67.00	16.83		100.0	
10064- CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps)	Х	4.55	67.82	17.12	0.86	100.0	± 9.6 %
		Y	4.82	66.76	16.73		100.0	
		Z	4.96	67.24	17.04		100.0	
10065- CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps)	X	4.42	67.59	17.17	1.21	100.0	± 9.6 %
		Y	4.68	66.63	16.81		100.0	
		Z	4.82	67.13	17.14		100.0	
10066- CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps)	Х	4.41	67.50	17.26	1.46	100.0	± 9.6 %
		Υ	4.70	66.64	16.97		100.0	
		Z	4.84	67.15	17.31		100.0	
10067- CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps)	Х	4.65	67.64	17.64	2.04	100.0	± 9.6 %
		Y	4.99	66.84	17.42		100.0	
		Z	5.12	67.29	17.73		100.0	
10068- CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps)	X	4.71	67.67	17.88	2.55	100.0	± 9.6 %
	1 '	Y	5.02	66.84	17.62		100.0	
		Z	5.16	67.31	17.95		100.0	
10069- CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps)	Х	4.74	67.57	17.98	2.67	100.0	± 9.6 %
		Y	5.10	66.86	17.81		100.0	
		Z	5.24	67.30	18.13		100.0	
10071- CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 9 Mbps)	Х	4.61	67.57	17.66	1.99	100.0	± 9.6 %
		Y	4.81	66.49	17.26		100.0	
		Z	4.94	66.94	17.57		100.0	
10072- CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 12 Mbps)	X	4.54	67.71	17.82	2.30	100.0	± 9.6 %
		Y	4.78	66.78	17.46		100.0	
		Z	4.92	67.27	17.80		100.0	
10073- CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 18 Mbps)	Х	4.60	67.94	18.17	2.83	100.0	± 9.6 %
		Y	4.83	66.92	17.77		100.0	
		Z	4.97	67.41	18.13		100.0	
10074- CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 24 Mbps)	Х	4.64	67.99	18.37	3.30	100.0	± 9.6 %
		Υ	4.82	66.80	17.90		100.0	
		Z	4.94	67.28	18.26		100.0	
10075- CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 36 Mbps)	Х	4.66	67.99	18.60	3.82	90.0	± 9.6 %
		Υ	4.85	66.88	18.18		90.0	
		Z	4.97	67.36	18.57		90.0	
10076- CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 48 Mbps)	Х	4.69	67.80	18.74	4.15	90.0	± 9.6 %
		Υ	4.86	66.68	18.30		90.0	
		Z	4.98	67.12	18.67		90.0	
10077- CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 54 Mbps)	Х	4.73	67.92	18.87	4.30	90.0	± 9.6 %
		Y	4.89	66.75	18.40		90.0	
		Z	5.00	67.19	18.77		90.0	

10081- CAB	CDMA2000 (1xRTT, RC3)	X	0.50	63.84	8.40	0.00	150.0	± 9.6 %
		Y	0.57	62.65	9.30		150.0	
		Z	1.10	70.49	14.72		150.0	
10082- CAB	IS-54 / IS-136 FDD (TDMA/FDM, PI/4- DQPSK, Fullrate)	Х	0.58	60.00	3.17	4.77	80.0	± 9.6 %
		Y	0.64	60.00	3.55		80.0	
		Z	0.66	60.00	4.29		80.0	
10090- DAC	GPRS-FDD (TDMA, GMSK, TN 0-4)	X	100.00	107.19	22.35	6.56	60.0	± 9.6 %
		Y	100.00	105.44	22.01		60.0	
40007	LIMITO FRE (LICERA)	Z	100.00	115.27	26.61		60.0	
10097- CAB	UMTS-FDD (HSDPA)	X	2.95	78.41	19.79	0.00	150.0	± 9.6 %
		Y	1.67	67.12	15.03		150.0	
40000	LIMTO EDD (LICHEA COLLON	Z	1.98	69.69	16.84	0.00	150.0	
10098- CAB	UMTS-FDD (HSUPA, Subtest 2)	X	2.90	78.46	19.84	0.00	150.0	± 9.6 %
		Y	1.64	67.06	14.99		150.0	
40000	FDOE EDD (TDLL) ADDIT TO THE	Z	1.94	69.67	16.83		150.0	
10099- DAC	EDGE-FDD (TDMA, 8PSK, TN 0-4)	X	6.25	86.84	31.63	9.56	60.0	± 9.6 %
		Y	7.25	86.82	30.53		60.0	
40405	LTE EDD (00 == : : :	Z	9.93	96.12	34.88		60.0	
10100- CAE	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	Х	3.31	73.67	18.74	0.00	150.0	± 9.6 %
		Y	2.92	69.59	16.23		150.0	
		Z	3.34	71.87	17.57		150.0	
10101- CAE	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM)	X	3.14	69.05	16.94	0.00	150.0	± 9.6 %
		Y	3.08	67.04	15.65		150.0	
		Z	3.29	68.18	16.39		150.0	
10102- CAE	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)	X	3.23	69.02	17.01	0.00	150.0	± 9.6 %
		Y	3.19	67.05	15.77		150.0	
		Z	3.39	68.10	16.46		150.0	
10103- CAF	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	Х	5.55	76.81	21.34	3.98	65.0	± 9.6 %
		Y	5.31	73.56	19.61		65.0	
		Z	6.43	77.06	21.32		65.0	
10104- CAF	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM)	Х	5.16	72.90	20.23	3.98	65.0	± 9.6 %
		Y	5.44	71.84	19.66		65.0	
		Z	6.12	74.09	20.85		65.0	
10105- CAF	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)	Х	4.87	71.48	19.86	3.98	65.0	± 9.6 %
		Y	5.06	70.23	19.23		65.0	
		Z	5.67	72.37	20.38		65.0	
10108- CAF	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	X	2.90	73.75	18.88	0.00	150.0	± 9.6 %
		Υ	2.54	68.92	16.08		150.0	
		Z	2.91	71.12	17.43		150.0	
10109- CAF	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)	Х	2.85	69.86	17.09	0.00	150.0	± 9.6 %
		Y	2.73	66.91	15.51		150.0	
		Z	2.96	68.17	16.37		150.0	
10110- CAF	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, QPSK)	X	2.52	74.77	18.94	0.00	150.0	± 9.6 %
		Y	2.02	68.04	15.58		150.0	
		Z	2.37	70.41	17.15		150.0	
10111- CAF	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM)	X	3.06	74.22	18.33	0.00	150.0	± 9.6 %
		Y	2.44	67.80	15.70		150.0	