

FCC Test Report (BT-EDR)

Report No.: RF200522E04-2

FCC ID: TX2-RTL8852AE

Test Model: RTL8852AE

Received Date: May 22, 2020

Test Date: June 25 to Sep. 01, 2020

Issued Date: Sep. 24, 2020

Applicant: Realtek Semiconductor Corp.

Address: No. 2, Innovation Road II, Hsinchu Science Park, Hsinchu 300, Taiwan

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan

**FCC Registration /
Designation Number:** 723255 / TW2022



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	4
1 Certificate of Conformity	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty	6
2.2 Modification Record	6
3 General Information	7
3.1 General Description of EUT (BT-EDR)	7
3.2 Description of Test Modes	9
3.2.1 Test Mode Applicability and Tested Channel Detail	10
3.3 Duty Cycle of Test Signal	12
3.4 Description of Support Units	13
3.4.1 Configuration of System under Test	14
3.5 General Description of Applied Standards and references	15
4 Test Types and Results	16
4.1 Radiated Emission and Bandedge Measurement	16
4.1.1 Limits of Radiated Emission and Bandedge Measurement	16
4.1.2 Test Instruments	17
4.1.3 Test Procedures	19
4.1.4 Deviation from Test Standard	20
4.1.5 Test Setup	20
4.1.6 EUT Operating Conditions	21
4.1.6 Test Results (Mode 1)	22
4.1.7 Test Results (Mode 2)	38
4.2 Conducted Emission Measurement	54
4.2.1 Limits of Conducted Emission Measurement	54
4.2.2 Test Instruments	54
4.2.3 Test Procedures	55
4.2.4 Deviation From Test Standard	55
4.2.5 Test Setup	55
4.2.6 EUT Operating Condition	55
4.2.7 Test Results (Mode 1)	56
4.2.8 Test Results (Mode 2)	58
4.3 Number of Hopping Frequency Used	60
4.3.1 Limits of Hopping Frequency Used Measurement	60
4.3.2 Test Setup	60
4.3.3 Test Instruments	60
4.3.4 Test Procedure	60
4.3.5 Deviation from Test Standard	60
4.3.6 Test Results (Mode 1)	61
4.3.7 Test Results (Mode 2)	62
4.4 Dwell Time on Each Channel	63
4.4.1 Limits of Dwell Time on Each Channel Measurement	63
4.4.2 Test Setup	63
4.4.3 Test Instruments	63
4.4.4 Test Procedures	63
4.4.5 Deviation from Test Standard	63
4.4.6 Test Results (Mode 1)	64
4.4.7 Test Results (Mode 2)	68
4.5 Channel Bandwidth	72
4.5.1 Limits of Channel Bandwidth Measurement	72
4.5.2 Test Setup	72
4.5.3 Test Instruments	72
4.5.4 Test Procedure	72

4.5.5	Deviation from Test Standard	72
4.5.6	EUT Operating Condition	72
4.5.7	Test Results (Mode 1).....	73
4.5.8	Test Results (Mode 2).....	73
4.6	Hopping Channel Separation.....	74
4.6.1	Limits of Hopping Channel Separation Measurement.....	74
4.6.2	Test Setup.....	74
4.6.3	Test Instruments	74
4.6.4	Test Procedure	74
4.6.5	Deviation from Test Standard	74
4.6.6	Test Results (Mode 1).....	75
4.6.7	Test Results (Mode 2).....	76
4.7	Maximum Output Power	77
4.7.1	Limits of Maximum Output Power Measurement	77
4.7.2	Test Setup.....	77
4.7.3	Test Instruments	77
4.7.4	Test Procedure	77
4.7.5	Deviation from Test Standard	77
4.7.6	EUT Operating Condition	77
4.7.7	Test Results (Mode 1).....	78
4.7.8	Test Results (Mode 2).....	78
4.8	Conducted Out of Band Emission Measurement	79
4.8.1	Limits of Conducted Out of Band Emission Measurement.....	79
4.8.2	Test Instruments	79
4.8.3	Test Procedure	79
4.8.4	Deviation from Test Standard	79
4.8.5	EUT Operating Condition	79
4.8.6	Test Results	79
4.8.7	Test Results (Mode 2).....	80
4.8.8	Test Results (Mode 2).....	82
5	Pictures of Test Arrangements.....	84
	Annex A - Band-Edge Measurement.....	85
	Annex A.1 - Test Results (Mode 1).....	85
	Annex A.2 - Test Results (Mode 2).....	89
	Appendix – Information of the Testing Laboratories	93

Release Control Record

Issue No.	Description	Date Issued
RF200522E04-2	Original release.	Sep. 24, 2020

1 Certificate of Conformity

Product: 11ax RTL8852AE Combo module

Brand: REALTEK

Test Model: RTL8852AE


Sample Status: ENGINEERING SAMPLE

Applicant: Realtek Semiconductor Corp.

Test Date: June 25 to Sep. 01, 2020

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)
ANSI C63.10: 2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :	 _____ Joyce Kuo / Specialist	Date:	Sep. 24, 2020 _____
Approved by :	 _____ Clark Lin / Technical Manager	Date:	Sep. 24, 2020 _____

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (SECTION 15.247)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -14.83dB at 0.17754MHz.
15.247(a)(1)(iii)	Number of Hopping Frequency Used	PASS	Meet the requirement of limit.
15.247(a)(1)(iii)	Dwell Time on Each Channel	PASS	Meet the requirement of limit.
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power	PASS	Meet the requirement of limit.
15.205 & 209 & 15.247(d)	Radiated Emissions & Band Edge Measurement	PASS	Meet the requirement of limit. Minimum passing margin is -4.8dB at 287.50MHz.
15.247(d)	Antenna Port Emission	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	Antenna connector is i-pex(MHF) not a standard connector.

NOTE:

1. If The Frequency Hopping System operating in 2400-2483.5MHz band and the output power less than 125mW. The hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of hopping channel whichever is greater.
2. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

2.2 Modification Record

There were no modifications required for compliance.

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150kHz ~ 30MHz	1.9 dB
Conducted emissions	-	2.5 dB
Radiated Emissions up to 1 GHz	9kHz ~ 30MHz	3.1 dB
	30MHz ~ 1GHz	5.1 dB
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	5.1 dB
	18GHz ~ 40GHz	5.3 dB

3 General Information

3.1 General Description of EUT (BT-EDR)

Product	11ax RTL8852AE Combo module
Brand	REALTEK
Test Model	RTL8852AE
Status of EUT	ENGINEERING SAMPLE
Power Supply Rating	3.3Vdc from host equipment
Modulation Type	GFSK, $\pi/4$ -DQPSK, 8DPSK
Modulation Technology	FHSS
Transfer Rate	Up to 3Mbps
Operating Frequency	2402MHz ~ 2480MHz
Number of Channel	79
Output Power	19.724 mW
Antenna Type	Refer to Note
Antenna Connector	Refer to Note
Accessory Device	NA
Data Cable Supplied	NA

Note:

1. The EUT has below HW SKU configuration, as below table:

SKU No.	Interface	Description
1	PCIe + USB	Single antenna port
2	PCIe + USB	Dual antenna port
3	PCIe + UART	Dual antenna port

Note: From the above HW SKUs, **SKU No.: 3** was selected as representative model for the test and its data was recorded in this report.

2. Simultaneously transmission condition.

Condition	Technology		
1	WLAN 2.4GHz	WLAN 5GHz	Bluetooth
2	WLAN 2.4GHz	WLAN 5GHz	-
3	WLAN 5GHz	Bluetooth	-

Note: The emission of the simultaneous operation has been evaluated and no non-compliance was found.

3. The antennas provided to the EUT, please refer to the following table:

Antenna Set	Chain No.	Brand	Model	Antenna Gain (dBi)	Frequency range (GHz)	Antenna Type	Connector Type	Cable Length (mm)
1	Chain 0	LYNwave	ALA110-222050-300011	3.5	2.4~2.5	PIFA	i-pex(MHF)	300
				5	5.15~5.85			
	Chain 1	LYNwave	ALA110-222050-300011	3.5	2.4~2.5	PIFA	i-pex(MHF)	300
				5	5.15~5.85			
2	Chain 0	PSA	RFDPA171320EMLB301	3.14	2.4~2.5	Dipole	i-pex(MHF)	200
				5	5.15~5.85			
	Chain 1	PSA	RFDPA171320EMLB301	3.14	2.4~2.5	Dipole	i-pex(MHF)	200
				5	5.15~5.85			

Note:

1. The Bluetooth technology will fix transmission on Chain 1.
2. Max. gain was selected for the final test, except for the radiated emissions test.
4. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.
5. The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

3.2 Description of Test Modes

79 channels are provided for BT-EDR mode:

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE $\geq$ 1G	RE<1G	PLC	APCM	
1	√	√	√	√	Low power
2	√	√	√	√	High power

Where **RE $\geq$ 1G**: Radiated Emission above 1GHz

RE<1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

Note: The EUT's PIFA antenna had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on Z-plane.

Radiated Emission Test (Above 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

Radiated Emission Test (Below 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	39	FHSS	GFSK	DH5

Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	39	FHSS	GFSK	DH5

Antenna Port Conducted Measurement:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

Test Condition:


APPLICABLE TO	ENVIRONMENTAL CONDITIONS	Input Power (System)	TESTED BY
RE _≥ 1G	25deg. C, 75%RH	120Vac, 60Hz	Tom Yang
RE _{<} 1G	25deg. C, 75%RH	120Vac, 60Hz	Tom Yang
PLC	25deg. C, 75%RH	120Vac, 60Hz	Sampson Chen
APCM	25deg. C, 60%RH	120Vac, 60Hz	Kevin Ko

3.3 Duty Cycle of Test Signal

For Low power

GFSK: Duty cycle = 2.873 ms/2.897 ms = 0.992


8DPSK: Duty cycle = 2.876 ms/2.9 ms = 0.992



For High power

GFSK: Duty cycle = 2.872 ms/2.899 ms = 0.991

8DPSK: Duty cycle = 2.881 ms/2.909 ms = 0.99



3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Laptop	DELL	Latitude 5490	4LFTNV2	NA	Provided by Lab
B.	Test Tool	Realtek	NA	NA	NA	Supplied by client
C.	Adapter	DELL	FA65NE0-00	NA	NA	Provided by Lab

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	DC Cable	1	1.6	No	1	Provided by Lab
2.	AC Cable	1	1	No	0	Provided by Lab


Note: The core is originally attached to the cable.

3.4.1 Configuration of System under Test

For AC Power Conducted Emissions test:



For Radiated Emissions test:



Under Table

3.5 General Description of Applied Standards and references

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards and references:

Test standard:

FCC Part 15, Subpart C (15.247)

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

References Test Guidance:

KDB 558074 D01 15.247 Meas Guidance v05r02

All test items have been performed as a reference to the above KDB test guidance.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 Test Instruments

For Radiated Emission and Bandedge test:

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver R&S	ESR7	102026	Apr. 22, 2020	Apr. 21, 2021
Spectrum Analyzer Keysight	N9030B	MY57141948	May 22, 2020	May 21, 2021
Pre-Amplifier EMCI	EMC001340	980142	May 25, 2020	May 24, 2021
Loop Antenna Electro-Metrics	EM-6879	264	Feb. 18, 2020	Feb. 17, 2021
RF Cable	NA	LOOPCAB-001	Jan. 08, 2020	Jan. 07, 2021
RF Cable	NA	LOOPCAB-002	Jan. 08, 2020	Jan. 07, 2021
Pre-Amplifier EMCI	EMC330N	980538	Apr. 28, 2020	Apr. 27, 2021
Trilog Broadband Antenna SCHWARZBECK	VULB9168	9168-0842	Nov. 08, 2019	Nov. 07, 2020
RF Cable	8D	966-5-1	Apr. 29, 2020	Apr. 28, 2021
RF Cable	8D	966-5-2	Apr. 29, 2020	Apr. 28, 2021
RF Cable	8D	966-5-3	Apr. 29, 2020	Apr. 28, 2021
Fixed attenuator Mini-Circuits	UNAT-5+	PAD-ATT5-02	Jan. 14, 2020	Jan. 13, 2021
Horn_Antenna SCHWARZBECK	BBHA 9120D	9120D-1819	Nov. 24, 2019	Nov. 23, 2020
Pre-Amplifier EMCI	EMC12630SE	980509	Apr. 29, 2020	Apr. 28, 2021
RF Cable EMCI	EMC104-SM-SM-1500	180503	Apr. 29, 2020	Apr. 28, 2021
RF Cable EMCI	EMC104-SM-SM-2000	180501	Apr. 29, 2020	Apr. 28, 2021
RF Cable EMCI	EMC104-SM-SM-6000	180506	Apr. 29, 2020	Apr. 28, 2021
Pre-Amplifier EMCI	EMC184045SE	980387	Jan. 15, 2020	Jan. 14, 2021
Horn_Antenna SCHWARZBECK	BBHA 9170	BBHA9170519	Nov. 24, 2019	Nov. 23, 2020
RF Cable	EMC102-KM-KM-1200	160924	Jan. 15, 2020	Jan. 14, 2021
RF Cable	EMC-KM-KM-4000	200214	Mar. 11, 2020	Mar. 10, 2021
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Boresight Antenna Tower & Turn Table Max-Full	MF-7802BS	MF780208530	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in 966 Chamber No. 5.
3. Tested Date: June 25 to Aug. 17, 2020

For other test items:

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Spectrum Analyzer R&S	FSV40	100964	May 29, 2020	May 28, 2021
Power meter Anritsu	ML2495A	1529002	July 22, 2020	July 21, 2021
Power sensor Anritsu	MA2411B	1339443	July 22, 2020	July 21, 2021
Fixed Attenuator Mini-Circuits	MDCS18N-10	MDCS18N-10-01	Apr. 14, 2020	Apr. 13, 2021
Software	ADT_RF Test Software V6.6.5.4	NA	NA	NA

- NOTE:**
1. The test was performed in Oven room 2.
 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 3. Tested Date: Aug. 31 to Sep. 01, 2020

4.1.3 Test Procedures

For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Both Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard


No deviation.

4.1.5 Test Setup


For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

- Placed the EUT on the testing table.
- Controlling software (RF test tool.exe (5.3.1.42)) has been activated to set the EUT under transmission condition continuously at specific channel frequency.

4.1.6 Test Results (Mode 1)

Dipole Antenna

Above 1GHz Data:

BT_GFSK

Channel	TX Channel 0	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 25GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2389.30	56.4 PK	74.0	-17.6	1.27 H	86	59.5	-3.1
2	2389.30	44.3 AV	54.0	-9.7	1.27 H	86	47.4	-3.1
3	*2402.00	95.4 PK			1.27 H	86	98.5	-3.1
4	*2402.00	94.2 AV			1.27 H	86	97.3	-3.1
5	4804.00	44.7 PK	74.0	-29.3	1.81 H	228	43.7	1.0
6	4804.00	38.1 AV	54.0	-15.9	1.81 H	228	37.1	1.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2373.50	57.6 PK	74.0	-16.4	1.20 V	8	60.7	-3.1
2	2373.50	44.7 AV	54.0	-9.3	1.20 V	8	47.8	-3.1
3	*2402.00	101.8 PK			1.20 V	8	104.9	-3.1
4	*2402.00	101.1 AV			1.20 V	8	104.2	-3.1
5	4804.00	44.1 PK	74.0	-29.9	1.46 V	1	43.1	1.0
6	4804.00	37.4 AV	54.0	-16.6	1.46 V	1	36.4	1.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

Channel	TX Channel 39	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 25GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2441.00	94.3 PK			1.28 H	90	97.3	-3.0
2	*2441.00	93.1 AV			1.28 H	90	96.1	-3.0
3	4882.00	45.3 PK	74.0	-28.7	1.74 H	218	44.4	0.9
4	4882.00	38.6 AV	54.0	-15.4	1.74 H	218	37.7	0.9
5	7323.00	45.7 PK	74.0	-28.3	1.48 H	74	38.7	7.0
6	7323.00	33.2 AV	54.0	-20.8	1.48 H	74	26.2	7.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2441.00	101.6 PK			1.20 V	16	104.6	-3.0
2	*2441.00	100.9 AV			1.20 V	16	103.9	-3.0
3	4882.00	43.9 PK	74.0	-30.1	1.55 V	4	43.0	0.9
4	4882.00	37.2 AV	54.0	-16.8	1.55 V	4	36.3	0.9
5	7323.00	45.3 PK	74.0	-28.7	1.41 V	33	38.3	7.0
6	7323.00	31.9 AV	54.0	-22.1	1.41 V	33	24.9	7.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

Channel	TX Channel 78	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 25GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	95.5 PK			1.22 H	90	98.6	-3.1
2	*2480.00	94.3 AV			1.22 H	90	97.4	-3.1
3	2491.61	57.1 PK	74.0	-16.9	1.22 H	90	60.2	-3.1
4	2491.61	44.2 AV	54.0	-9.8	1.22 H	90	47.3	-3.1
5	4960.00	44.9 PK	74.0	-29.1	1.78 H	215	43.8	1.1
6	4960.00	38.2 AV	54.0	-15.8	1.78 H	215	37.1	1.1
7	7440.00	45.4 PK	74.0	-28.6	1.53 H	74	38.3	7.1
8	7440.00	32.8 AV	54.0	-21.2	1.53 H	74	25.7	7.1
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	104.0 PK			1.08 V	16	107.1	-3.1
2	*2480.00	103.3 AV			1.08 V	16	106.4	-3.1
3	2491.71	58.0 PK	74.0	-16.0	1.08 V	16	61.1	-3.1
4	2491.71	44.2 AV	54.0	-9.8	1.08 V	16	47.3	-3.1
5	4960.00	44.3 PK	74.0	-29.7	1.50 V	8	43.2	1.1
6	4960.00	37.4 AV	54.0	-16.6	1.50 V	8	36.3	1.1
7	7440.00	45.4 PK	74.0	-28.6	1.44 V	44	38.3	7.1
8	7440.00	32.3 AV	54.0	-21.7	1.44 V	44	25.2	7.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

BT_8DPSK

Channel	TX Channel 0	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 25GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2385.15	56.8 PK	74.0	-17.2	1.28 H	88	59.9	-3.1
2	2385.15	44.7 AV	54.0	-9.3	1.28 H	88	47.8	-3.1
3	*2402.00	97.0 PK			1.28 H	88	100.1	-3.1
4	*2402.00	93.0 AV			1.28 H	88	96.1	-3.1
5	4804.00	45.1 PK	74.0	-28.9	1.74 H	228	44.1	1.0
6	4804.00	38.3 AV	54.0	-15.7	1.74 H	228	37.3	1.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2382.92	56.8 PK	74.0	-17.2	1.19 V	7	59.9	-3.1
2	2382.92	44.6 AV	54.0	-9.4	1.19 V	7	47.7	-3.1
3	*2402.00	102.5 PK			1.19 V	7	105.6	-3.1
4	*2402.00	99.6 AV			1.19 V	7	102.7	-3.1
5	4804.00	44.2 PK	74.0	-29.8	1.43 V	8	43.2	1.0
6	4804.00	37.4 AV	54.0	-16.6	1.43 V	8	36.4	1.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

Channel	TX Channel 39	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 25GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2441.00	97.2 PK			1.26 H	86	100.2	-3.0
2	*2441.00	93.0 AV			1.26 H	86	96.0	-3.0
3	4882.00	45.2 PK	74.0	-28.8	1.80 H	227	44.3	0.9
4	4882.00	38.7 AV	54.0	-15.3	1.80 H	227	37.8	0.9
5	7323.00	45.5 PK	74.0	-28.5	1.53 H	69	38.5	7.0
6	7323.00	32.7 AV	54.0	-21.3	1.53 H	69	25.7	7.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2441.00	102.3 PK			1.25 V	1	105.3	-3.0
2	*2441.00	99.6 AV			1.25 V	1	102.6	-3.0
3	4882.00	44.3 PK	74.0	-29.7	1.48 V	5	43.4	0.9
4	4882.00	37.3 AV	54.0	-16.7	1.48 V	5	36.4	0.9
5	7323.00	45.6 PK	74.0	-28.4	1.48 V	56	38.6	7.0
6	7323.00	32.6 AV	54.0	-21.4	1.48 V	56	25.6	7.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

Channel	TX Channel 78	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 25GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	97.5 PK			1.20 H	91	100.6	-3.1
2	*2480.00	93.0 AV			1.20 H	91	96.1	-3.1
3	2497.42	56.9 PK	74.0	-17.1	1.20 H	91	60.0	-3.1
4	2497.42	44.5 AV	54.0	-9.5	1.20 H	91	47.6	-3.1
5	4960.00	44.7 PK	74.0	-29.3	1.80 H	235	43.6	1.1
6	4960.00	38.0 AV	54.0	-16.0	1.80 H	235	36.9	1.1
7	7440.00	44.7 PK	74.0	-29.3	1.49 H	86	37.6	7.1
8	7440.00	32.3 AV	54.0	-21.7	1.49 H	86	25.2	7.1
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	106.6 PK			1.03 V	13	109.7	-3.1
2	*2480.00	102.4 AV			1.03 V	13	105.5	-3.1
3	2484.35	56.8 PK	74.0	-17.2	1.03 V	13	59.9	-3.1
4	2484.35	45.7 AV	54.0	-8.3	1.03 V	13	48.8	-3.1
5	4960.00	44.5 PK	74.0	-29.5	1.46 V	2	43.4	1.1
6	4960.00	37.5 AV	54.0	-16.5	1.46 V	2	36.4	1.1
7	7440.00	46.1 PK	74.0	-27.9	1.48 V	64	39.0	7.1
8	7440.00	32.9 AV	54.0	-21.1	1.48 V	64	25.8	7.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

Below 1GHz Data:


GFSK

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	96.20	38.0 QP	43.5	-5.5	3.10 H	345	55.6	-17.6
2	155.60	37.2 QP	43.5	-6.3	1.96 H	216	49.7	-12.5
3	204.30	37.3 QP	43.5	-6.2	1.00 H	236	53.4	-16.1
4	290.30	40.4 QP	46.0	-5.6	1.07 H	338	52.6	-12.2
5	392.40	37.5 QP	46.0	-8.5	1.04 H	128	47.2	-9.7
6	682.10	38.4 QP	46.0	-7.6	1.14 H	257	42.2	-3.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




CHANNEL	TX Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	102.90	32.7 QP	43.5	-10.8	3.98 V	114	49.3	-16.6
2	163.00	29.5 QP	43.5	-14.0	2.02 V	112	42.0	-12.5
3	295.50	36.6 QP	46.0	-9.4	1.97 V	273	48.7	-12.1
4	433.00	32.9 QP	46.0	-13.1	1.12 V	310	41.4	-8.5
5	669.50	34.5 QP	46.0	-11.5	1.27 V	344	38.6	-4.1
6	707.10	34.3 QP	46.0	-11.7	2.01 V	244	37.8	-3.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



PIFA Antenna

Above 1GHz Data:

BT_GFSK

Channel	TX Channel 0	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 25GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2372.04	57.3 PK	74.0	-16.7	1.87 H	220	60.4	-3.1
2	2372.04	43.7 AV	54.0	-10.3	1.87 H	220	46.8	-3.1
3	*2402.00	102.3 PK			1.87 H	220	105.4	-3.1
4	*2402.00	102.0 AV			1.87 H	220	105.1	-3.1
5	4804.00	44.7 PK	74.0	-29.3	1.64 H	195	43.7	1.0
6	4804.00	38.3 AV	54.0	-15.7	1.64 H	195	37.3	1.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2369.98	56.2 PK	74.0	-17.8	1.50 V	215	59.3	-3.1
2	2369.98	43.6 AV	54.0	-10.4	1.50 V	215	46.7	-3.1
3	*2402.00	100.0 PK			1.50 V	215	103.1	-3.1
4	*2402.00	99.3 AV			1.50 V	215	102.4	-3.1
5	4804.00	44.6 PK	74.0	-29.4	1.43 V	30	43.6	1.0
6	4804.00	37.8 AV	54.0	-16.2	1.43 V	30	36.8	1.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

Channel	TX Channel 39	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 25GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2441.00	101.5 PK			1.81 H	222	104.5	-3.0
2	*2441.00	101.1 AV			1.81 H	222	104.1	-3.0
3	4882.00	44.5 PK	74.0	-29.5	1.74 H	196	43.6	0.9
4	4882.00	37.6 AV	54.0	-16.4	1.74 H	196	36.7	0.9
5	7323.00	45.0 PK	74.0	-29.0	1.56 H	59	38.0	7.0
6	7323.00	32.3 AV	54.0	-21.7	1.56 H	59	25.3	7.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2441.00	98.2 PK			1.56 V	216	101.2	-3.0
2	*2441.00	97.7 AV			1.56 V	216	100.7	-3.0
3	4882.00	44.8 PK	74.0	-29.2	1.45 V	19	43.9	0.9
4	4882.00	37.8 AV	54.0	-16.2	1.45 V	19	36.9	0.9
5	7323.00	45.5 PK	74.0	-28.5	1.49 V	45	38.5	7.0
6	7323.00	32.9 AV	54.0	-21.1	1.49 V	45	25.9	7.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

Channel	TX Channel 78	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 25GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	102.2 PK			1.80 H	221	105.3	-3.1
2	*2480.00	101.8 AV			1.80 H	221	104.9	-3.1
3	2487.26	56.8 PK	74.0	-17.2	1.80 H	221	59.9	-3.1
4	2487.26	43.8 AV	54.0	-10.2	1.80 H	221	46.9	-3.1
5	4960.00	44.7 PK	74.0	-29.3	1.70 H	205	43.6	1.1
6	4960.00	38.1 AV	54.0	-15.9	1.70 H	205	37.0	1.1
7	7440.00	45.2 PK	74.0	-28.8	1.52 H	56	38.1	7.1
8	7440.00	32.7 AV	54.0	-21.3	1.52 H	56	25.6	7.1
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	99.2 PK			1.58 V	217	102.3	-3.1
2	*2480.00	98.8 AV			1.58 V	217	101.9	-3.1
3	2496.27	56.4 PK	74.0	-17.6	1.58 V	217	59.5	-3.1
4	2496.27	43.7 AV	54.0	-10.3	1.58 V	217	46.8	-3.1
5	4960.00	44.6 PK	74.0	-29.4	1.48 V	20	43.5	1.1
6	4960.00	37.5 AV	54.0	-16.5	1.48 V	20	36.4	1.1
7	7440.00	45.4 PK	74.0	-28.6	1.50 V	32	38.3	7.1
8	7440.00	32.8 AV	54.0	-21.2	1.50 V	32	25.7	7.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

BT_8DPSK

Channel	TX Channel 0	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 25GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2387.33	56.8 PK	74.0	-17.2	1.65 H	222	59.9	-3.1
2	2387.33	44.0 AV	54.0	-10.0	1.65 H	222	47.1	-3.1
3	*2402.00	104.9 PK			1.65 H	222	108.0	-3.1
4	*2402.00	100.5 AV			1.65 H	222	103.6	-3.1
5	4804.00	44.8 PK	74.0	-29.2	1.68 H	201	43.8	1.0
6	4804.00	38.8 AV	54.0	-15.2	1.68 H	201	37.8	1.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2337.16	56.4 PK	74.0	-17.6	1.49 V	215	59.2	-2.8
2	2337.16	43.9 AV	54.0	-10.1	1.49 V	215	46.7	-2.8
3	*2402.00	102.5 PK			1.49 V	215	105.6	-3.1
4	*2402.00	98.0 AV			1.49 V	215	101.1	-3.1
5	4804.00	44.8 PK	74.0	-29.2	1.43 V	8	43.8	1.0
6	4804.00	37.8 AV	54.0	-16.2	1.43 V	8	36.8	1.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

Channel	TX Channel 39	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 25GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2441.00	104.8 PK			1.82 H	230	107.8	-3.0
2	*2441.00	100.6 AV			1.82 H	230	103.6	-3.0
3	4882.00	44.6 PK	74.0	-29.4	1.74 H	221	43.7	0.9
4	4882.00	37.9 AV	54.0	-16.1	1.74 H	221	37.0	0.9
5	7323.00	45.7 PK	74.0	-28.3	1.49 H	63	38.7	7.0
6	7323.00	33.1 AV	54.0	-20.9	1.49 H	63	26.1	7.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2441.00	101.9 PK			1.46 V	230	104.9	-3.0
2	*2441.00	97.7 AV			1.46 V	230	100.7	-3.0
3	4882.00	44.4 PK	74.0	-29.6	1.44 V	12	43.5	0.9
4	4882.00	37.3 AV	54.0	-16.7	1.44 V	12	36.4	0.9
5	7323.00	45.0 PK	74.0	-29.0	1.54 V	31	38.0	7.0
6	7323.00	32.6 AV	54.0	-21.4	1.54 V	31	25.6	7.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

Channel	TX Channel 78	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 25GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	104.7 PK			1.81 H	220	107.8	-3.1
2	*2480.00	100.3 AV			1.81 H	220	103.4	-3.1
3	2497.53	56.9 PK	74.0	-17.1	1.81 H	220	60.0	-3.1
4	2497.53	43.9 AV	54.0	-10.1	1.81 H	220	47.0	-3.1
5	4960.00	44.8 PK	74.0	-29.2	1.66 H	207	43.7	1.1
6	4960.00	38.5 AV	54.0	-15.5	1.66 H	207	37.4	1.1
7	7440.00	45.0 PK	74.0	-29.0	1.57 H	54	37.9	7.1
8	7440.00	32.2 AV	54.0	-21.8	1.57 H	54	25.1	7.1
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	102.0 PK			1.56 V	217	105.1	-3.1
2	*2480.00	97.6 AV			1.56 V	217	100.7	-3.1
3	2498.63	56.9 PK	74.0	-17.1	1.56 V	217	60.0	-3.1
4	2498.63	43.7 AV	54.0	-10.3	1.56 V	217	46.8	-3.1
5	4960.00	45.3 PK	74.0	-28.7	1.49 V	9	44.2	1.1
6	4960.00	38.0 AV	54.0	-16.0	1.49 V	9	36.9	1.1
7	7440.00	46.0 PK	74.0	-28.0	1.45 V	29	38.9	7.1
8	7440.00	33.2 AV	54.0	-20.8	1.45 V	29	26.1	7.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

Below 1GHz Data:


BT_GFSK

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	99.50	37.7 QP	43.5	-5.8	3.07 H	341	54.8	-17.1
2	158.20	37.7 QP	43.5	-5.8	2.05 H	251	50.1	-12.4
3	200.30	38.2 QP	43.5	-5.3	1.07 H	241	54.3	-16.1
4	287.70	40.7 QP	46.0	-5.3	1.13 H	360	52.9	-12.2
5	390.70	37.9 QP	46.0	-8.1	1.00 H	142	47.7	-9.8
6	666.40	37.7 QP	46.0	-8.3	1.25 H	254	41.8	-4.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




CHANNEL	TX Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	99.30	32.3 QP	43.5	-11.2	3.91 V	91	49.4	-17.1
2	159.30	29.6 QP	43.5	-13.9	2.00 V	114	42.1	-12.5
3	299.30	36.5 QP	46.0	-9.5	2.07 V	293	48.5	-12.0
4	424.30	31.5 QP	46.0	-14.5	1.12 V	322	40.3	-8.8
5	666.60	34.2 QP	46.0	-11.8	1.22 V	308	38.3	-4.1
6	697.10	34.0 QP	46.0	-12.0	1.98 V	221	37.6	-3.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



4.1.7 Test Results (Mode 2)

Dipole Antenna

Above 1GHz Data:

BT_GFSK

Channel	TX Channel 0	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 25GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2387.49	57.3 PK	74.0	-16.7	1.28 H	91	60.4	-3.1
2	2387.49	44.4 AV	54.0	-9.6	1.28 H	91	47.5	-3.1
3	*2402.00	101.4 PK			1.28 H	91	104.5	-3.1
4	*2402.00	100.7 AV			1.28 H	91	103.8	-3.1
5	4804.00	45.2 PK	74.0	-28.8	1.73 H	212	44.2	1.0
6	4804.00	38.7 AV	54.0	-15.3	1.73 H	212	37.7	1.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2366.04	57.3 PK	74.0	-16.7	1.15 V	9	60.3	-3.0
2	2366.04	44.2 AV	54.0	-9.8	1.15 V	9	47.2	-3.0
3	*2402.00	107.4 PK			1.15 V	9	110.5	-3.1
4	*2402.00	107.0 AV			1.15 V	9	110.1	-3.1
5	4804.00	43.7 PK	74.0	-30.3	1.53 V	51	42.7	1.0
6	4804.00	37.1 AV	54.0	-16.9	1.53 V	51	36.1	1.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

Channel	TX Channel 39	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 25GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2441.00	101.5 PK			1.31 H	88	104.5	-3.0
2	*2441.00	100.5 AV			1.31 H	88	103.5	-3.0
3	4882.00	45.5 PK	74.0	-28.5	1.77 H	211	44.6	0.9
4	4882.00	38.5 AV	54.0	-15.5	1.77 H	211	37.6	0.9
5	7323.00	46.0 PK	74.0	-28.0	1.42 H	78	39.0	7.0
6	7323.00	33.3 AV	54.0	-20.7	1.42 H	78	26.3	7.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2441.00	107.6 PK			1.14 V	22	110.6	-3.0
2	*2441.00	107.2 AV			1.14 V	22	110.2	-3.0
3	4882.00	43.3 PK	74.0	-30.7	1.51 V	46	42.4	0.9
4	4882.00	36.9 AV	54.0	-17.1	1.51 V	46	36.0	0.9
5	7323.00	46.0 PK	74.0	-28.0	1.40 V	50	39.0	7.0
6	7323.00	32.6 AV	54.0	-21.4	1.40 V	50	25.6	7.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

Channel	TX Channel 78	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 25GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	102.1 PK			1.25 H	95	105.2	-3.1
2	*2480.00	101.4 AV			1.25 H	95	104.5	-3.1
3	2484.35	56.9 PK	74.0	-17.1	1.25 H	95	60.0	-3.1
4	2484.35	44.5 AV	54.0	-9.5	1.25 H	95	47.6	-3.1
5	4960.00	45.3 PK	74.0	-28.7	1.72 H	233	44.2	1.1
6	4960.00	38.9 AV	54.0	-15.1	1.72 H	233	37.8	1.1
7	7440.00	45.8 PK	74.0	-28.2	1.43 H	78	38.7	7.1
8	7440.00	33.3 AV	54.0	-20.7	1.43 H	78	26.2	7.1
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	110.8 PK			1.08 V	16	113.9	-3.1
2	*2480.00	110.4 AV			1.08 V	16	113.5	-3.1
3	2493.36	57.6 PK	74.0	-16.4	1.08 V	16	60.7	-3.1
4	2493.36	45.3 AV	54.0	-8.7	1.08 V	16	48.4	-3.1
5	4960.00	44.0 PK	74.0	-30.0	1.51 V	60	42.9	1.1
6	4960.00	37.4 AV	54.0	-16.6	1.51 V	60	36.3	1.1
7	7440.00	45.7 PK	74.0	-28.3	1.42 V	50	38.6	7.1
8	7440.00	32.4 AV	54.0	-21.6	1.42 V	50	25.3	7.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

BT_8DPSK

Channel	TX Channel 0	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 25GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2362.06	56.8 PK	74.0	-17.2	1.28 H	90	59.8	-3.0
2	2362.06	44.9 AV	54.0	-9.1	1.28 H	90	47.9	-3.0
3	*2402.00	101.3 PK			1.28 H	90	104.4	-3.1
4	*2402.00	100.6 AV			1.28 H	90	103.7	-3.1
5	4804.00	45.2 PK	74.0	-28.8	1.73 H	205	44.2	1.0
6	4804.00	38.7 AV	54.0	-15.3	1.73 H	205	37.7	1.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2365.21	57.3 PK	74.0	-16.7	1.13 V	7	60.3	-3.0
2	2365.21	45.3 AV	54.0	-8.7	1.13 V	7	48.3	-3.0
3	*2402.00	108.3 PK			1.13 V	7	111.4	-3.1
4	*2402.00	107.5 AV			1.13 V	7	110.6	-3.1
5	4804.00	42.7 PK	74.0	-31.3	1.48 V	45	41.7	1.0
6	4804.00	36.6 AV	54.0	-17.4	1.48 V	45	35.6	1.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

Channel	TX Channel 39	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 25GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2441.00	101.4 PK			1.22 H	104	104.4	-3.0
2	*2441.00	100.4 AV			1.22 H	104	103.4	-3.0
3	4882.00	45.7 PK	74.0	-28.3	1.72 H	215	44.8	0.9
4	4882.00	38.8 AV	54.0	-15.2	1.72 H	215	37.9	0.9
5	7323.00	45.8 PK	74.0	-28.2	1.46 H	85	38.8	7.0
6	7323.00	33.2 AV	54.0	-20.8	1.46 H	85	26.2	7.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2441.00	109.3 PK			1.03 V	25	112.3	-3.0
2	*2441.00	105.5 AV			1.03 V	25	108.5	-3.0
3	4882.00	43.6 PK	74.0	-30.4	1.48 V	58	42.7	0.9
4	4882.00	37.1 AV	54.0	-16.9	1.48 V	58	36.2	0.9
5	7323.00	45.9 PK	74.0	-28.1	1.41 V	49	38.9	7.0
6	7323.00	32.2 AV	54.0	-21.8	1.41 V	49	25.2	7.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

Channel	TX Channel 78	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 25GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	100.3 PK			1.21 H	92	103.4	-3.1
2	*2480.00	96.3 AV			1.21 H	92	99.4	-3.1
3	2484.91	57.9 PK	74.0	-16.1	1.21 H	92	61.0	-3.1
4	2484.91	44.5 AV	54.0	-9.5	1.21 H	92	47.6	-3.1
5	4960.00	44.6 PK	74.0	-29.4	1.75 H	214	43.5	1.1
6	4960.00	38.2 AV	54.0	-15.8	1.75 H	214	37.1	1.1
7	7440.00	46.1 PK	74.0	-27.9	1.48 H	84	39.0	7.1
8	7440.00	33.7 AV	54.0	-20.3	1.48 H	84	26.6	7.1
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	109.7 PK			1.02 V	14	112.8	-3.1
2	*2480.00	105.7 AV			1.02 V	14	108.8	-3.1
3	2486.11	56.8 PK	74.0	-17.2	1.02 V	14	59.9	-3.1
4	2486.11	45.3 AV	54.0	-8.7	1.02 V	14	48.4	-3.1
5	4960.00	42.9 PK	74.0	-31.1	1.51 V	51	41.8	1.1
6	4960.00	36.6 AV	54.0	-17.4	1.51 V	51	35.5	1.1
7	7440.00	46.3 PK	74.0	-27.7	1.36 V	61	39.2	7.1
8	7440.00	33.1 AV	54.0	-20.9	1.36 V	61	26.0	7.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

Below 1GHz Data:


BT_GFSK

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	99.60	38.3 QP	43.5	-5.2	2.04 H	326	55.4	-17.1
2	158.50	37.9 QP	43.5	-5.6	1.69 H	249	50.4	-12.5
3	200.00	37.7 QP	43.5	-5.8	1.03 H	250	53.8	-16.1
4	286.60	41.0 QP	46.0	-5.0	1.19 H	359	53.2	-12.2
5	390.50	38.2 QP	46.0	-7.8	1.10 H	142	48.1	-9.9
6	666.90	37.6 QP	46.0	-8.4	1.13 H	248	41.7	-4.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




CHANNEL	TX Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	95.60	32.4 QP	43.5	-11.1	1.69 V	81	50.2	-17.8
2	159.60	28.7 QP	43.5	-14.8	2.10 V	95	41.1	-12.4
3	299.10	36.1 QP	46.0	-9.9	1.70 V	286	48.1	-12.0
4	424.60	30.6 QP	46.0	-15.4	1.16 V	326	39.4	-8.8
5	666.80	34.5 QP	46.0	-11.5	1.21 V	314	38.6	-4.1
6	703.50	34.4 QP	46.0	-11.6	1.26 V	210	37.9	-3.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



PIFA Antenna

Above 1GHz Data:

BT_GFSK

Channel	TX Channel 0	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 25GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2374.17	56.8 PK	74.0	-17.2	1.68 H	220	59.9	-3.1
2	2374.17	43.9 AV	54.0	-10.1	1.68 H	220	47.0	-3.1
3	*2402.00	106.7 PK			1.68 H	220	109.8	-3.1
4	*2402.00	106.4 AV			1.68 H	220	109.5	-3.1
5	4804.00	45.2 PK	74.0	-28.8	1.74 H	188	44.2	1.0
6	4804.00	38.4 AV	54.0	-15.6	1.74 H	188	37.4	1.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2387.39	55.5 PK	74.0	-18.5	1.19 V	203	58.6	-3.1
2	2387.39	44.3 AV	54.0	-9.7	1.19 V	203	47.4	-3.1
3	*2402.00	101.3 PK			1.19 V	203	104.4	-3.1
4	*2402.00	101.0 AV			1.19 V	203	104.1	-3.1
5	4804.00	44.9 PK	74.0	-29.1	1.42 V	15	43.9	1.0
6	4804.00	38.0 AV	54.0	-16.0	1.42 V	15	37.0	1.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

Channel	TX Channel 39	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 25GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2441.00	106.5 PK			1.71 H	212	109.5	-3.0
2	*2441.00	106.2 AV			1.71 H	212	109.2	-3.0
3	4882.00	44.6 PK	74.0	-29.4	1.77 H	185	43.7	0.9
4	4882.00	38.1 AV	54.0	-15.9	1.77 H	185	37.2	0.9
5	7323.00	44.4 PK	74.0	-29.6	1.65 H	83	37.4	7.0
6	7323.00	31.8 AV	54.0	-22.2	1.65 H	83	24.8	7.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2441.00	101.4 PK			1.23 V	213	104.4	-3.0
2	*2441.00	100.8 AV			1.23 V	213	103.8	-3.0
3	4882.00	44.9 PK	74.0	-29.1	1.42 V	10	44.0	0.9
4	4882.00	37.8 AV	54.0	-16.2	1.42 V	10	36.9	0.9
5	7323.00	45.3 PK	74.0	-28.7	1.50 V	42	38.3	7.0
6	7323.00	33.0 AV	54.0	-21.0	1.50 V	42	26.0	7.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

Channel	TX Channel 78	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 25GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	105.0 PK			1.24 H	210	108.1	-3.1
2	*2480.00	104.7 AV			1.24 H	210	107.8	-3.1
3	2494.78	56.3 PK	74.0	-17.7	1.24 H	210	59.4	-3.1
4	2494.78	44.1 AV	54.0	-9.9	1.24 H	210	47.2	-3.1
5	4960.00	45.0 PK	74.0	-29.0	1.80 H	180	43.9	1.1
6	4960.00	38.5 AV	54.0	-15.5	1.80 H	180	37.4	1.1
7	7440.00	44.4 PK	74.0	-29.6	1.61 H	69	37.3	7.1
8	7440.00	31.9 AV	54.0	-22.1	1.61 H	69	24.8	7.1
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	101.1 PK			1.24 V	193	104.2	-3.1
2	*2480.00	100.7 AV			1.24 V	193	103.8	-3.1
3	2493.00	55.8 PK	74.0	-18.2	1.24 V	193	58.9	-3.1
4	2493.00	43.8 AV	54.0	-10.2	1.24 V	193	46.9	-3.1
5	4960.00	44.9 PK	74.0	-29.1	1.37 V	4	43.8	1.1
6	4960.00	37.6 AV	54.0	-16.4	1.37 V	4	36.5	1.1
7	7440.00	45.1 PK	74.0	-28.9	1.55 V	37	38.0	7.1
8	7440.00	32.9 AV	54.0	-21.1	1.55 V	37	25.8	7.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

BT_8DPSK

Channel	TX Channel 0	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 25GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2354.22	56.9 PK	74.0	-17.1	1.70 H	220	59.9	-3.0
2	2354.22	44.9 AV	54.0	-9.1	1.70 H	220	47.9	-3.0
3	*2402.00	108.1 PK			1.70 H	220	111.2	-3.1
4	*2402.00	106.2 AV			1.70 H	220	109.3	-3.1
5	4804.00	45.4 PK	74.0	-28.6	1.81 H	205	44.4	1.0
6	4804.00	38.6 AV	54.0	-15.4	1.81 H	205	37.6	1.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	56.5 PK	74.0	-17.5	1.21 V	208	59.6	-3.1
2	2390.00	44.1 AV	54.0	-9.9	1.21 V	208	47.2	-3.1
3	*2402.00	103.5 PK			1.21 V	208	106.6	-3.1
4	*2402.00	99.6 AV			1.21 V	208	102.7	-3.1
5	4804.00	45.1 PK	74.0	-28.9	1.51 V	15	44.1	1.0
6	4804.00	38.1 AV	54.0	-15.9	1.51 V	15	37.1	1.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

Channel	TX Channel 39	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 25GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2441.00	109.2 PK			1.22 H	217	112.2	-3.0
2	*2441.00	106.8 AV			1.22 H	217	109.8	-3.0
3	4882.00	45.0 PK	74.0	-29.0	1.73 H	198	44.1	0.9
4	4882.00	38.4 AV	54.0	-15.6	1.73 H	198	37.5	0.9
5	7323.00	44.3 PK	74.0	-29.7	1.71 H	85	37.3	7.0
6	7323.00	32.1 AV	54.0	-21.9	1.71 H	85	25.1	7.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2441.00	102.9 PK			1.33 V	194	105.9	-3.0
2	*2441.00	100.1 AV			1.33 V	194	103.1	-3.0
3	4882.00	44.8 PK	74.0	-29.2	1.41 V	29	43.9	0.9
4	4882.00	38.2 AV	54.0	-15.8	1.41 V	29	37.3	0.9
5	7323.00	45.9 PK	74.0	-28.1	1.52 V	44	38.9	7.0
6	7323.00	33.5 AV	54.0	-20.5	1.52 V	44	26.5	7.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

Channel	TX Channel 78	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 25GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	109.3 PK			1.28 H	213	112.4	-3.1
2	*2480.00	106.9 AV			1.28 H	213	110.0	-3.1
3	2484.47	56.8 PK	74.0	-17.2	1.28 H	213	59.9	-3.1
4	2484.47	45.1 AV	54.0	-8.9	1.28 H	213	48.2	-3.1
5	4960.00	45.3 PK	74.0	-28.7	1.76 H	207	44.2	1.1
6	4960.00	38.5 AV	54.0	-15.5	1.76 H	207	37.4	1.1
7	7440.00	44.9 PK	74.0	-29.1	1.73 H	99	37.8	7.1
8	7440.00	32.7 AV	54.0	-21.3	1.73 H	99	25.6	7.1
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	103.9 PK			1.25 V	198	107.0	-3.1
2	*2480.00	100.3 AV			1.25 V	198	103.4	-3.1
3	2489.00	56.6 PK	74.0	-17.4	1.25 V	198	59.7	-3.1
4	2489.00	44.7 AV	54.0	-9.3	1.25 V	198	47.8	-3.1
5	4960.00	45.1 PK	74.0	-28.9	1.41 V	25	44.0	1.1
6	4960.00	38.2 AV	54.0	-15.8	1.41 V	25	37.1	1.1
7	7440.00	44.7 PK	74.0	-29.3	1.49 V	32	37.6	7.1
8	7440.00	33.1 AV	54.0	-20.9	1.49 V	32	26.0	7.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

Below 1GHz Data:


BT_GFSK

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	99.70	38.2 QP	43.5	-5.3	2.01 H	340	55.3	-17.1
2	158.70	37.7 QP	43.5	-5.8	1.71 H	239	50.2	-12.5
3	200.00	37.7 QP	43.5	-5.8	1.09 H	239	53.8	-16.1
4	287.50	41.2 QP	46.0	-4.8	1.16 H	360	53.4	-12.2
5	390.30	37.4 QP	46.0	-8.6	1.15 H	132	47.3	-9.9
6	665.90	37.0 QP	46.0	-9.0	1.15 H	252	41.1	-4.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




CHANNEL	TX Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	95.60	32.0 QP	43.5	-11.5	1.67 V	100	49.8	-17.8
2	159.60	28.2 QP	43.5	-15.3	2.04 V	94	40.6	-12.4
3	299.10	36.7 QP	46.0	-9.3	1.68 V	291	48.7	-12.0
4	424.60	30.3 QP	46.0	-15.7	1.15 V	302	39.1	-8.8
5	666.80	34.0 QP	46.0	-12.0	1.18 V	315	38.1	-4.1
6	703.50	34.5 QP	46.0	-11.5	1.28 V	228	38.0	-3.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver R&S	ESCS 30	847124/029	Oct. 23, 2019	Oct. 22, 2020
Line-Impedance Stabilization Network (for EUT) R&S	ESH3-Z5	848773/004	Oct. 23, 2019	Oct. 22, 2020
Line-Impedance Stabilization Network (for Peripheral) R&S	ESH3-Z5	835239/001	Mar. 19, 2020	Mar. 18, 2021
50 ohms Terminator	50	3	Oct. 23, 2019	Oct. 22, 2020
RF Cable	5D-FB	COCCAB-001	Sep. 27, 2019	Sep. 26, 2020
Fixed attenuator EMCI	STI02-2200-10	005	Aug. 30, 2019	Aug. 29, 2020
Software BVADT	BVADT_Cond_ V7.3.7.4	NA	NA	NA

1. The calibration interval of the above test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Conduction 1.
- 3 Tested Date: Aug. 13, 2020

4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

4.2.4 Deviation From Test Standard

No deviation.

4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Condition

Same as 4.1.6.


4.2.7 Test Results (Mode 1)

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	----------	-------------------	--------------------------------

No	Freq. [MHz]	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16953	9.97	36.51	9.95	46.48	19.92	64.98	54.98	-18.50	-35.06
2	0.18125	9.97	36.90	14.46	46.87	24.43	64.43	54.43	-17.56	-30.00
3	0.38047	9.98	23.65	8.16	33.63	18.14	58.27	48.27	-24.64	-30.13
4	14.43750	10.74	18.65	11.35	29.39	22.09	60.00	50.00	-30.61	-27.91
5	15.97656	10.82	22.37	15.86	33.19	26.68	60.00	50.00	-26.81	-23.32
6	19.14063	11.00	26.22	19.07	37.22	30.07	60.00	50.00	-22.78	-19.93

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	-------------	-------------------	--------------------------------

No	Freq. [MHz]	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.17344	9.97	39.94	15.14	49.91	25.11	64.79	54.79	-14.88	-29.68
2	0.18516	9.97	38.68	17.13	48.65	27.10	64.25	54.25	-15.60	-27.15
3	0.19297	9.97	37.89	17.09	47.86	27.06	63.91	53.91	-16.05	-26.85
4	0.39219	9.98	26.33	11.14	36.31	21.12	58.02	48.02	-21.71	-26.90
5	0.91953	10.01	26.48	11.53	36.49	21.54	56.00	46.00	-19.51	-24.46
6	17.23828	10.69	21.31	15.50	32.00	26.19	60.00	50.00	-28.00	-23.81

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




4.2.8 Test Results (Mode 2)

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	----------	-------------------	--------------------------------

No	Freq. [MHz]	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.18185	9.97	36.40	14.21	46.37	24.18	64.40	54.40	-18.03	-30.22
2	0.19657	9.97	34.56	15.29	44.53	25.26	63.75	53.75	-19.22	-28.49
3	0.39625	9.98	23.37	9.25	33.35	19.23	57.93	47.93	-24.58	-28.70
4	0.68946	10.00	20.50	5.45	30.50	15.45	56.00	46.00	-25.50	-30.55
5	0.90020	10.01	22.60	8.27	32.61	18.28	56.00	46.00	-23.39	-27.72
6	20.58223	11.07	22.75	16.72	33.82	27.79	60.00	50.00	-26.18	-22.21

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	-------------	-------------------	--------------------------------

No	Freq. [MHz]	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.17754	9.97	39.80	16.65	49.77	26.62	64.60	54.60	-14.83	-27.98
2	0.20449	9.97	37.39	17.13	47.36	27.10	63.43	53.43	-16.07	-26.33
3	0.37240	9.98	25.40	8.70	35.38	18.68	58.45	48.45	-23.07	-29.77
4	0.52877	9.99	25.35	6.88	35.34	16.87	56.00	46.00	-20.66	-29.13
5	15.55870	10.62	21.44	15.12	32.06	25.74	60.00	50.00	-27.94	-24.26
6	19.92180	10.80	21.40	14.98	32.20	25.78	60.00	50.00	-27.80	-24.22

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




4.3 Number of Hopping Frequency Used

4.3.1 Limits of Hopping Frequency Used Measurement

At least 15 channels frequencies, and should be equally spaced.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure


- Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- Set the SA on View mode and then plot the result on SA screen.
- Repeat above procedures until all frequencies measured were complete.

4.3.5 Deviation from Test Standard

No deviation.

4.3.6 Test Results (Mode 1)

There are 79 hopping frequencies in the hopping mode. Please refer to next page for the test result. On the plots, it shows that the hopping frequencies are equally spaced.



4.3.7 Test Results (Mode 2)

There are 79 hopping frequencies in the hopping mode. Please refer to next page for the test result. On the plots, it shows that the hopping frequencies are equally spaced.




4.4 Dwell Time on Each Channel

4.4.1 Limits of Dwell Time on Each Channel Measurement

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.4.2 Test Setup



4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.4 Test Procedures

- Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- Adjust the center frequency of SA on any frequency to be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- Repeat above procedures until all different time-slot modes have been completed.

4.4.5 Deviation from Test Standard

No deviation.


4.4.6 Test Results (Mode 1)

GFSK


Mode	Number of transmission in a 31.6 (79Hopping*0.4)	Length of transmission time (msec)	Result (msec)	Limit (msec)
DH1	50 (times / 5 sec) * 6.32 = 316 times	0.42	132.72	400
DH3	25 (times / 5 sec) * 6.32 = 158 times	1.69	267.02	400
DH5	16 (times / 5 sec) * 6.32 = 102 times	2.992	305.18	400

NOTE: Test plots of the transmitting time slot are shown on next page.


DH1



DH3



DH5




8DPSK


Mode	Number of transmission in a 31.6 (79Hopping*0.4)	Length of transmission time (msec)	Result (msec)	Limit (msec)
3DH1	50 (times / 5 sec) * 6.32 = 316 times	0.438	138.41	400
3DH3	26 (times / 5 sec) * 6.32 = 165 times	1.7	280.5	400
3DH5	18 (times / 5 sec) * 6.32 = 114 times	3.056	348.38	400

NOTE: Test plots of the transmitting time slot are shown on next page.


3DH1



3DH3



3DH5




4.4.7 Test Results (Mode 2)

GFSK


Mode	Number of transmission in a 31.6 (79Hopping*0.4)	Length of transmission time (msec)	Result (msec)	Limit (msec)
DH1	51 (times / 5 sec) * 6.32 = 323 times	0.462	149.23	400
DH3	27 (times / 5 sec) * 6.32 = 171 times	1.74	297.54	400
DH5	18 (times / 5 sec) * 6.32 = 114 times	2.96	337.44	400

NOTE: Test plots of the transmitting time slot are shown on next page.


DH1



DH3



DH5




8DPSK


Mode	Number of transmission in a 31.6 (79Hopping*0.4)	Length of transmission time (msec)	Result (msec)	Limit (msec)
3DH1	51 (times / 5 sec) * 6.32 = 323 times	0.438	141.47	400
3DH3	26 (times / 5 sec) * 6.32 = 165 times	1.7	280.5	400
3DH5	18 (times / 5 sec) * 6.32 = 114 times	2.96	337.44	400

NOTE: Test plots of the transmitting time slot are shown on next page.


3DH1



3DH3



3DH5




4.5 Channel Bandwidth

4.5.1 Limits of Channel Bandwidth Measurement

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dB bandwidth of hopping channel shall be a minimum limit for the hopping channel separation.

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedure

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- Repeat above procedures until all frequencies measured were complete.

4.5.5 Deviation from Test Standard


No deviation.

4.5.6 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.


4.5.7 Test Results (Mode 1)

Channel	Frequency (MHz)	20dB Bandwidth (MHz)	
		GFSK	8DPSK
0	2402	0.96	1.3
39	2441	0.96	1.29
78	2480	0.96	1.29



4.5.8 Test Results (Mode 2)

Channel	Frequency (MHz)	20dB Bandwidth (MHz)	
		GFSK	8DPSK
0	2402	0.96	1.31
39	2441	0.96	1.29
78	2480	0.96	1.3




4.6 Hopping Channel Separation

4.6.1 Limits of Hopping Channel Separation Measurement

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

4.6.2 Test Setup



4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.6.4 Test Procedure

Measurement Procedure REF

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
- c. By using the MaxHold function record the separation of two adjacent channels.
- d. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
- e. Repeat above procedures until all frequencies measured were complete.


4.6.5 Deviation from Test Standard

No deviation.

4.6.6 Test Results (Mode 1)

Channel	Frequency (MHz)	Adjacent Channel Separation (MHz)		20dB Bandwidth (MHz)		Minimum Limit (MHz)		Pass / Fail
		GFSK	8DPSK	GFSK	8DPSK	GFSK	8DPSK	
0	2402	1	1	0.96	1.3	0.64	0.87	Pass
39	2441	1	1	0.96	1.29	0.64	0.86	Pass
78	2480	1	1	0.96	1.29	0.64	0.86	Pass


NOTE: The minimum limit is two-third 20dB bandwidth.



4.6.7 Test Results (Mode 2)

Channel	Frequency (MHz)	Adjacent Channel Separation (MHz)		20dB Bandwidth (MHz)		Minimum Limit (MHz)		Pass / Fail
		GFSK	8DPSK	GFSK	8DPSK	GFSK	8DPSK	
0	2402	1	1	0.96	1.31	0.64	0.88	Pass
39	2441	1	1	0.96	1.29	0.64	0.86	Pass
78	2480	1	1	0.96	1.3	0.64	0.87	Pass

NOTE: The minimum limit is two-third 20dB bandwidth.




4.7 Maximum Output Power

4.7.1 Limits of Maximum Output Power Measurement

The Maximum Output Power Measurement is 125mW.

4.7.2 Test Setup



4.7.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.7.4 Test Procedure

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

4.7.5 Deviation from Test Standard

No deviation.

4.7.6 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.7.7 Test Results (Mode 1)

FOR PEAK POWER

Channel	Frequency (MHZ)	GFSK		8DPSK		Power Limit (mW)	Pass / Fail
		Output Power (mW)	Output Power (dBm)	Output Power (mW)	Output Power (dBm)		
0	2402	4.295	6.33	8.356	9.22	125	Pass
39	2441	4.169	6.20	8.913	9.50	125	Pass
78	2480	4.365	6.40	8.61	9.35	125	Pass

FOR AVERAGE POWER

Channel	Frequency (MHZ)	GFSK		8DPSK	
		Average Power (mW)	Average Power (dBm)	Average Power (mW)	Average Power (dBm)
0	2402	4.111	6.14	3.999	6.02
39	2441	4.009	6.03	4.266	6.30
78	2480	4.159	6.19	4.14	6.17

4.7.8 Test Results (Mode 2)

FOR PEAK POWER

Channel	Frequency (MHZ)	GFSK		8DPSK		Power Limit (mW)	Pass / Fail
		Output Power (mW)	Output Power (dBm)	Output Power (mW)	Output Power (dBm)		
0	2402	17.258	12.37	19.724	12.95	125	Pass
39	2441	18.239	12.61	18.664	12.71	125	Pass
78	2480	17.66	12.47	19.498	12.90	125	Pass

FOR AVERAGE POWER

Channel	Frequency (MHZ)	GFSK		8DPSK	
		Average Power (mW)	Average Power (dBm)	Average Power (mW)	Average Power (dBm)
0	2402	16.558	12.19	9.727	9.88
39	2441	17.378	12.40	9.12	9.60
78	2480	17.022	12.31	9.683	9.86

4.8 Conducted Out of Band Emission Measurement

4.8.1 Limits of Conducted Out of Band Emission Measurement

Below 20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.8.2 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.8.3 Test Procedure

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz and 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

4.8.4 Deviation from Test Standard

No deviation.

4.8.5 EUT Operating Condition


The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.8.6 Test Results

The spectrum plots are attached on the following images. D1 line indicates the highest level, D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.



4.8.7 Test Results (Mode 2)

GFSK





8DPSK



Hopping disabled Low Channel





Hopping disabled High Channel



Hopping enabled Low Channel




Hopping enabled High Channel





4.8.8 Test Results (Mode 2)

GFSK





8DPSK



Hopping disabled Low Channel





Hopping disabled High Channel



Hopping enabled Low Channel



Hopping enabled High Channel



5 Pictures of Test Arrangements


Please refer to the attached file (Test Setup Photo).

Annex A - Band-Edge Measurement


Annex A.1 - Test Results (Mode 1)

Dipole Antenna

BT_GFSK




BT_8DPSK




PIFA Antenna

BT_GFSK




BT_8DPSK




Annex A.2 - Test Results (Mode 2)

Dipole Antenna

BT_GFSK




BT_8DPSK




PIFA Antenna

BT_GFSK



BT_8DPSK



Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---