

Regulatory WLAN Antenna Information (Template)

English Language Required for Intel Regulatory Review / Approval

**(OEM/ODM or antenna vendor is required to complete this document with platform antenna information.
Remove Intel references and make this your own document)**

Platform information											
Brand	ODM	****End product model name			Intel platform (ex: Yes, No or NA)	Platform type (ex: regular NB, convertible PC, AIO...etc)		*SAR minimum separation (mm)			
Lenovo	Compal Electronics Inc.	ThinkBook 15 G4 ABA ThinkBook 15 G5 IRL ThinkBook 15 G5 ABP			Yes	Regular NB		7.91			
*****Please fill in exact product model name and make sure the model name is visible on product cover or any parts for end users recognize for authority inspection.											
Antenna information											
Vendor		Type			Antenna Part number (Main)		Antenna Part number (Aux)				
SOUTHSTAR TECHNOLOGY CO. ,LTD		PIFA			DC330020200 (N12-7953-R0A)		DC330020210 (N12-7954-R0A)				
Peak gain w/ cable loss (dBi)*											
	2.4GHz 2400-2483.5 MHz	5.2GHz 5150-5250MHz	5.3GHz 5250-5350MHz	5.6GHz 5470-5725MHz	5.8GHz 5725-5850MHz	5.9GHz 5850-5895MHz	6.2GHz 5925-6425MHz	6.5GHz 6425-6525MHz	6.7GHz 6525-6875MHz	7.0 GHz 6875-7125MHz	
Main	1.32	2.38	2.38	2.55	2.80	2.54	2.54	2.65	2.65	2.79	
Aux	0.92	2.42	2.42	2.37	2.35	2.33	2.30	2.30	1.91	2.76	
Intel Reference Gain/Type/ Separation distance											
Antenna Type	Antenna Peak gain (In dBi)*										Distance to the end user (mm)
	2.4GHz 2400-2483.5 MHz	5.2GHz 5150-5250MHz	5.3GHz 5250-5350MHz	5.6GHz 5470-5725MHz	5.8GHz 5725-5850MHz	5.9GHz 5850-5895MHz	6.2GHz 5925-6425MHz	6.5GHz 6425-6525MHz	6.7GHz 6525-6875MHz	7.0GHz 6875-7125MHz	Generic: refer to modular FCC SAR report Mid-power: ≥ 8 mm Low power: ≥ 5 mm
Design	3.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	
PIFA	3.24	3.64	3.73	4.77	4.97	4.72	4.83	4.30	5.37	5.59	
Dipole	2.89	2.92	3.19	4.41	4.22	4.22	4.83	4.30	4.49	5.34	
Notes (marked with *) * SAR minimum separation (mm) - Regular NB: Minimum antenna-to-body (from antenna bottom to the bottom of the device) - Tablet / Convertible PC: Minimum antenna-to-edge (5 sides of the device) - Mini-tablet: Minimum antenna-to-edge (6 sides of the device) * 3D Peak Antenna gain should be equal or greater than -2 dBi - If a host integrator plans to use a lower gain antenna of the same type, additional CBP(FCC)/EDT(EU) testing need to be performed while the module is installed in the host.											

Table of contents

1. Applicable test method
2. Test & System Description
 - a. Test setup
 - b. Equipment list
3. Setup photo

[Section 1. Antenna Assembly Specifications](#)

[Section 2. Dimensioned Photos or Drawings of Antennas](#)

[Section 3. Radiation characteristics of antenna loaded in Host Platform](#)

[Section 4. Antenna Host Platform Location Information](#)

[Section 5. Antenna dimensional information for SAR evaluation](#)

[Section 6. Diagram Example of Co-Location Antenna Separation](#)

1. Applicable test methods


<insert test description here for test method>

[example] This test report is prepared for host antenna testing under a Full Anechoic Chamber. The radiation pattern of antenna is measured in both horizontal polarization and vertical polarization. The radiation pattern measurements are performed in the three-dimensional anechoic chamber. The chamber provides less than - 30dB reflectivity from 800MHz through 8GHz. The chamber is calibrated using both standard dipole antenna and horn antenna. The Gain here is expressed as dBi that standardizes the isotropic antenna. The Gain measurements and antenna radiation pattern are also performed in the same chamber described previously.


2. Test & System Description

a. Test setup

<insert test diagram here for test site utilized>



Radiated Setup 1 GHz – 6.4 GHz



b. Equipment list

<insert test diagram here for test site utilized>

Device	Type/Model	Manufacturer	Cal.Date	Cal.Date
Customized Switch Module	-	BWant	N/A	N/A
Programmable Attenuator	PATT-121-4	BWant	N/A	N/A
Horn Antenna	700MHz-10GHz	BWant	2021.11.19	2023.11.19
Network Analyzer	ZNB 20	ROHDE&SCHWARZ	2022.1.10	2024.1.10
Cable	LL142	Fairview Microwave	2022.3.17	2023.9.17
Turn table	-	BWant	N/A	N/A
Anechoic Chamber	-	BWant	2022.5.10	2023.5.10

Antenna Information

Section 1. Antenna Assembly Specifications

1A Antenna Part Number	1B Manufacturer	1C Antenna Type	1D Cable Assembly Part Number and Information	Freq Range MHz	1E * Peak Gain W/ Cable loss (dBi)	1F Peak Gain w/o Cable Loss (dBi)	1G Max VSWR	1H Cable Loss (dB)
DC33002O200 (N12-7953-R0A) Main Antenna	Shenzhen South Star Technology Ltd	PIFA	50 ohm Coaxial length: 273cm diameter : 1.13mm_LLS Connector : I-PEX4 Kangshuo MHF-B13-N-01	2400-2483.5	1.32	2.08	3	0.76
				5150-5250	2.38	3.51	3	1.13
				5250-5350	2.38	3.54	3	1.16
				5470-5725	2.55	3.73	3	1.18
				5725-5850	2.80	4.04	3	1.24
				5850-5895	2.54	3.80	3	1.26
				5925-6425	2.54	3.80	3	1.26
				6425-6525	2.65	3.94	3	1.29
				6525-6875	2.65	3.98	3	1.33
				6875-7125	2.79	4.12	3	1.33
DC33002O210 (N12-7954-R0A) Aux Antenna	Shenzhen South Star Technology Ltd	PIFA	50 ohm Coaxial length: 363cm diameter : 1.13mm_LLS Connector : I-PEX4 Kangshuo MHF-B13-N-01	2400-2483.5	0.92	1.93	3	1.01
				5150-5250	2.42	3.92	3	1.50
				5250-5350	2.42	3.97	3	1.55
				5470-5725	2.37	3.94	3	1.57
				5725-5850	2.35	4.00	3	1.65
				5850-5895	2.33	4.01	3	1.68
				5925-6425	2.30	3.98	3	1.68
				6425-6525	2.30	4.01	3	1.72
				6525-6875	1.91	3.63	3	1.72
				6875-7125	2.76	4.53	3	1.77

- 3D Antenna Peak Gain required being test in system basis.