

Appendix C. Maximum Permissible Exposure

1. Maximum Permissible Exposure

1.1. Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d}$$

$$\text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

1.3. Calculated Result and Limit

1.3.1. For WLAN Function:

<For Main Source – EUT 2 (Mode 1 with Dipole Antenna)>:

Antenna Type : Dipole Antenna

Max Peak Output Power for IEEE 802.11g: 26.21 dBm

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
2.00	1.5849	26.2100	417.8304	0.131811	1	Complies

<For Main Source – EUT 2 (Mode 2 with PIFA Antenna)>:

Antenna Type : PIFA Antenna

Max Conducted Power for IEEE 802.11g: 26.21 dBm

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
3.90	2.4547	26.2100	417.8304	0.204150	1	Complies

<For Second Source – EUT 2 (Mode 1 with Dipole Antenna)>:

Antenna Type : Dipole Antenna

Max Conducted Power for IEEE 802.11g: 26.01 dBm

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
2.00	1.5849	26.0100	399.0249	0.125878	1	Complies

<For Second Source – EUT 2 (Mode 2 with PIFA Antenna)>:

Antenna Type : PIFA Antenna

Max Conducted Power for IEEE 802.11g: 26.01 dBm

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
3.90	2.4547	26.0100	399.0249	0.194962	1	Complies

1.3.2. For Bluetooth Function:

<For Main Source – EUT 2 (Mode 1 with Dipole Antenna)>:

Antenna Type : Dipole Antenna

Max Peak Output Power for bluetooth: 11.69 dBm

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
2.00	1.5849	11.6900	14.7571	0.004655	1	Complies

<For Main Source – EUT 2 (Mode 2 with PIFA Antenna)>:

Antenna Type : PIFA Antenna

Max Conducted Power for bluetooth: 11.69 dBm

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
3.95	2.4831	11.6900	14.7571	0.007294	1	Complies

<For Second Source – EUT 2 (Mode 1 with Dipole Antenna)>:

Antenna Type : Dipole Antenna

Max Conducted Power for bluetooth: 11.63 dBm

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
2.00	1.5849	11.6300	14.5546	0.004591	1	Complies

<For Second Source – EUT 2 (Mode 2 with PIFA Antenna)>:

Antenna Type : PIFA Antenna

Max Conducted Power for bluetooth: 11.63 dBm

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
3.95	2.4831	11.6300	14.5546	0.007194	1	Complies

1.3.3. For Co-Location:

CONCLUSION:

Both of the WLAN and Bluetooth can transmit simultaneously, the formula of calculated the MPE is:

$$\text{CPD1 / LPD1} + \text{CPD2 / LPD2} + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

Therefore, the worst-case situation is $0.204150 / 1 + 0.007294 / 1 = 0.211444$, which is less than "1". This confirmed that the device comply with FCC 1.1310 MPE limit.