

EMF TEST REPORT

Test Report No. : OT-253-RWD-011
Reception No. : 2412004627
Applicant : Remote Solution Co., Ltd.
Address : 92, Chogokri, Nammyun, Kimchon City, Kyungbuk, 740-871, South Korea
Manufacturer : Remote Solution Co., Ltd.
Address : 326-14, Apo-daero, Nam-myeon, Gimcheon-si, Gyeongsangbuk-do, 39662, South Korea
Type of Equipment : RF MODULE
FCC ID. : TX4EE30
Model Name : EE30
Multiple Model Name : N/A
Serial number : N/A
Total page of Report : 6 pages (including this page)
Date of Incoming : December 14, 2024
Date of issue : March 18, 2025


SUMMARY

The equipment complies with the regulation; **FCC CFR 47 PART 2.1093**

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.

This report is not correlated with the "KS Q ISO/IEC 17025 and KOLAS accreditation" of Korean Laboratory Accreditation Scheme.



Tested by
Yun-Bok, Wi / Engineer
ONETECH Corp.

Reviewed by
Tae-Ho, Kim / Chief Engineer
ONETECH Corp.

Approved by
Jae-Ho, Lee / Chief Engineer
ONETECH Corp.

CONTENTS

	PAGE
1. VERIFICATION OF COMPLIANCE	4
2. GENERAL INFORMATION	5
2.1 PRODUCT DESCRIPTION.....	5
2.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.....	5
3. EUT MODIFICATIONS.....	5
4. RF EXPOSURE EVALUATION	6
4.1 STANDARD APPLICABLE	6
4.2 EUT DESCRIPTION.....	6
4.3 TEST RESULT OF SAR EXCLUSION FOR PORTABLE DEVICES	6

Revision History

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-253-RWD-011	March 18, 2025	Initial Release	All

1. VERIFICATION OF COMPLIANCE

Applicant : Remote Solution Co., Ltd.

Address : 92, Chogokri, Nammyun, Kimchon City, Kyungbuk, 740-871, South Korea

Contact Person : Byung-Cheol, Kim / Manager

Telephone No. : +82-54-420-4517

FCC ID : TX4EE30

Model Name : EE30

Brand Name : Remotesolution

Serial Number : N/A

Date : March 18, 2025

EQUIPMENT CLASS	DTS – DIGITAL TRNSMISSION SYSTEM
E.U.T. DESCRIPTION	RF MODULE
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	KDB 447498 D01 General RF Exposure Guidance v06
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT	
AUTHORIZATION REQUESTED	Certification
Modifications on the Equipment to Achieve Compliance	None

- The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. GENERAL INFORMATION

2.1 Product Description

The Remote Solution Co., Ltd., Model EE30 (referred to as the EUT in this report) is a RF MODULE. The product specification described herein was obtained from product data sheet or user's manual.

DEVICE TYPE	RF MODULE
OPERATING FREQUENCY	2 425 MHz ~ 2 475 MHz
NUMBER OF CHANNEL	3 Channel
MODULATION TYPE	DSSS
RF OUTPUT POWER	3.02 dBm
ANTENNA TYPE	PCB Antenna
ANTENNA GAIN	1.39 dBi
List of each Osc. or crystal Freq.(Freq. >= 1 MHz)	24 MHz
RATED SUPPLY VOLTAGE	DC 3.0 V

2.2 Alternative type(s)/model(s); also covered by this test report.

- None

3. EUT MODIFICATIONS

- None

4. RF Exposure Evaluation

4.1 Standard Applicable

According to 1.1307 (b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to the procedure, KDB 447498 D06, the standalone SAR test exclusion threshold is

$$[(\text{Max. Power of channel, including tune-up tolerance, mW}) / (\text{Min. test separation distance, mm})] \times [\sqrt{f(\text{GHz})}] < 3$$

4.2 EUT Description

Kind of EUT	RF MODULE
Device Category	<input type="checkbox"/> Portable (< 20 cm separation) <input type="checkbox"/> Mobile (> 20 cm separation) <input checked="" type="checkbox"/> Others
Exposure	<input type="checkbox"/> MPE
Evaluation Applied	<input type="checkbox"/> SAR <input checked="" type="checkbox"/> SAR Exemption

4.3 Test Result of SAR Exclusion for Portable Devices

$$[(\text{Max. Power of channel, including tune-up tolerance, mW}) / (\text{Min. test separation distance, mm})] \times [\sqrt{f(\text{GHz})}] \\ = (3.48/5) \times \sqrt{2.475} = 1.093 < 3$$

Conclusion: The SAR test exclusion threshold is less than 3, so the device meets the RF Exposure Requirement and excluded SAR Test.

Frequency (MHz)	Target Power W/tolerance (dBm)	Max tune up power (dBm)	Antenna Gain (dBi)	E.I.R.P power (dBm)	E.I.R.P power (mW)	Separation distance (mm)	RF exposure
2 475.00	3.02 ± 1.0	4.02	1.39	5.41	3.48	5	1.093