



HCT.CO., LTD.

Product Compliance Division, EMC Team

SAN 136-1, AMI-RI, BUBAL-EUP, ICHEON-SI, KYOUNKI-DO, 467-701, KOREA

TEL : +82 31 639 8518 FAX : +82 31 639 8525

## CERTIFICATE OF COMPLIANCE

### FCC PART 15.247 Certification

**Applicant Name:**

CASIO HITACHI Mobile Communications Co., Ltd.

**Address:**

2-229-1, SAKURAGAOKA, HIGASHIYAMATO-SHI,  
TOKYO 207-8501, JAPAN

**Date of Testing:**

Apr. 02, 2008

**Test Site/Location:**

HCT.CO., LTD., San 136-1 Ami-ri, Bubal-eup, Icheon-si,  
Kyungki-do, Korea

**Test Report No.:** HCT-R08-039

**HCT FRN:** 0005866421

**FCC ID:** **TYKNX9230**

**APPLICANT:** **CASIO HITACHI Mobile Communications Co., Ltd.**

**Model(s):** G'zOne Boulder

**EUT Type:** Dual-Band CDMA/EVDO Phone with Bluetooth

**Max. RF Output Power:** 2.72 dBm(1.87 mW)

**Frequency Range:** 2402 - 2480 MHz (Bluetooth)

**Modulation type** GFSK, PSK

**FCC Classification:** FCC Part 15 Frequency Hopping Spread Spectrum Transceiver

**FCC Rule Part(s):** Part 15 subpart C 15.247

Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

**HCT.CO., LTD.** Certifies that no party to this application has been denied FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S.C. 853(a)

Youn Seok Jung

Report prepared by

: Youn Seok Jung

Test engineer of RF Part

Sang Jun Lee

Approved by

: Sang Jun Lee

Manager of RF Part

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 1 of 51	
HCT-R08-039	Apr. 02, 2008	Dual-Band CDMA/EVDO Phone with Bluetooth	TYKNX9230		



# Table of Contents

1. GENERAL INFORMATION .....	3
2. EUT DESCRIPTION .....	3
3. TEST METHODOLOGY .....	4
3.1 EUT CONFIGURATION .....	4
3.2 EUT EXERCISE .....	4
3.3 GENERAL TEST PROCEDURES .....	4
3.4 DESCRIPTION OF TEST MODES .....	4
4. INSTRUMENT CALIBRATION .....	5
5. FACILITIES AND ACCREDITATIONS .....	6
5.1 FACILITIES .....	6
5.2 EQUIPMENT .....	6
6. ANTENNA REQUIREMENTS .....	7
7. FCC PART 15.247 REQUIREMENTS .....	8
7.1 PEAK POWER .....	8
7.2 BAND EDGES MEASUREMENT .....	12
7.2.1 BAND EDGES MEASUREMENT (RADIATED)) .....	15
7.3 FREQUENCY SEPARATION .....	24
7.4 NUMBER OF HOPPING FREQUENCY .....	29
7.5 TIME OF OCCUPANCY (DWELL TIME) .....	32
7.6 SPURIOUS EMISSIONS .....	36
7.6.1 Conducted Spurious Measurement .....	36
7.6.2 Radiated Spurious Emissions .....	40
7.7 POWERLINE CONDUCTED EMISSIONS .....	48
8. LIST OF TEST EQUIPMENT .....	51

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCT-R08-039	Test Dates: Apr. 02, 2008	EUT Type: Dual-Band CDMA/EVDO Phone with Bluetooth	FCC ID: TYKKNX9230	Page 2 of 51	



## 1. GENERAL INFORMATION

**Applicant:** CASIO HITACHI Mobile Communications Co., Ltd.  
2-229-1, SAKURAGAOKA, HIGASHIYAMATO-SHI,  
TOKYO 207-8501, JAPAN

**FCC ID:** TYKNX9230

**EUT:** Dual-Band CDMA/EVDO Phone with Bluetooth

**Model:** G'zOne Boulder

**Date of Test:** March 27, 2008

**Contact person:** Name: Eui –Soon Park  
Phone #: +82-2-2033-1113  
Fax #: +82-2-2033-1222

## 2. EUT DESCRIPTION

<b>Product</b>	Dual-Band CDMA/EVDO Phone with Bluetooth
<b>Model Name</b>	G'zOne Boulder
<b>Power Supply</b>	DC 3.7 V
<b>Battery type</b>	Standard
<b>Frequency Range</b>	2402 ~ 2480 MHz
<b>Transmit Power</b>	2.72 dBm(1.87 mW)
<b>Modulation Type</b>	GFSK(Normal), PSK(EDR)
<b>Modulation Technique</b>	FHSS
<b>Number of Channels</b>	79 Channels
<b>Antenna Specification</b>	Manufacturer: Casio Hitachi Mobile Communication Co., Ltd. Antenna type: Chip Antenna Gain : -0.47 dBi

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCT-R08-039	Test Dates: Apr. 02, 2008	EUT Type: Dual-Band CDMA/EVDO Phone with Bluetooth	FCC ID: TYKNX9230	Page 3 of 51	



### 3. TEST METHODOLOGY

The measurement procedure described in the American National Standard for Methods of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz(ANSI C63.4-2003) and FCC Public Notice DA 00-705 dated March 30, 2000 entitled "Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems" were used in the measurement of the **CASIO HITACHI Mobile Communications Co., Ltd. Dual-Band CDMA/EVDO Phone with Bluetooth FCC ID: TYKNX9230**

#### 3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

#### 3.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

#### 3.3 GENERAL TEST PROCEDURES

##### Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4. (Version :2003) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

##### Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.4. (Version: 2003)

#### 3.4 DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Channel low, mid and high with highest data rate (worst case) is chosen for full testing.

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCT-R08-039	Test Dates: Apr. 02, 2008	EUT Type: Dual-Band CDMA/EVDO Phone with Bluetooth	FCC ID: TYKNX9230	Page 4 of 51	



#### 4. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipments, which is traceable to recognized national standards.

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCT-R08-039	Test Dates: Apr. 02, 2008	EUT Type: Dual-Band CDMA/EVDO Phone with Bluetooth	FCC ID: TYKKNX9230	Page 5 of 51



## 5. FACILITIES AND ACCREDITATIONS

### 5.1 FACILITIES

The open area test site and conducted measurement facility used to collect the radiated data are located at the 254-1, Maekok-Ri, Hobup-Myun, Ichon-Si, Kyoungki-Do, 467-701, KOREA. The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2003) and CISPR Publication 22. Detailed description of test facility was submitted to the Commission and accepted dated July 6, 2006(Registration Number: 90661)

### 5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements. Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCT-R08-039	Test Dates: Apr. 02, 2008	EUT Type: Dual-Band CDMA/EVDO Phone with Bluetooth	FCC ID: TYKKNX9230	Page 6 of 51	



## 6. ANTENNA REQUIREMENTS

### According to FCC 47 CFR §15.203:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

\* The antennas of this E.U.T are permanently attached.

\*The E.U.T Complies with the requirement of §15.203

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCT-R08-039	Test Dates: Apr. 02, 2008	EUT Type: Dual-Band CDMA/EVDO Phone with Bluetooth	FCC ID: TYKKNX9230	Page 7 of 51	

## 7. FCC PART 15.247 REQUIREMENTS


### 7.1 PEAK POWER

#### LIMIT

The maximum peak output power of the intentional radiator shall not exceed the following:

1. For systems using digital modulation in the bands of 902 ~ 928 MHz, 2400 ~ 2483.5 MHz, and 5725 ~ 5850 MHz: 1 watt.
2. Except as shown in paragraphs (b)(3) (i), (ii) and (iii) of this section, if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### Test Configuration



#### TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer. The Spectrum Analyzer is set to the peak detector mode.

1. Span = 2 MHz
2. RBW = 1 MHz
3. VBW = 1 MHz
4. Sweep = auto

#### TEST RESULTS

*No non-compliance noted*

#### Test Data

##### (Normal)


Channel	Frequency (MHz)	Output Power(GFSK)		Output Power(8DPSK)		Limit (W)	Result
		(dBm)	(mW)	(dBm)	(mW)		
Low	2402	-0.76	0.83	1.91	1.55	1	PASS
Mid	2441	0.20	1.04	2.51	1.78		PASS
High	2480	0.80	1.20	2.72	1.87		PASS

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT				<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 8 of 51	
HCT-R08-039	Apr. 02, 2008	Dual-Band CDMA/EVDO Phone with Bluetooth	TYKNX9230		

## Test Plots


(GFSK)

### Peak Power ( Low CH )



Date: 26.MAR.2008 16:02:27


### Peak Power ( Mid CH )



Date: 26.MAR.2008 16:02:51

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 9 of 51	
HCT-R08-039	Apr. 02, 2008	Dual-Band CDMA/EVDO Phone with Bluetooth	TYKNX9230		


## Peak Power ( High CH )



Date: 26.MAR.2008 16:03:23

## (8DPSK)


### Peak Power ( Low CH )



Date: 26.MAR.2008 16:05:46


HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 10 of 51	
HCT-R08-039	Apr. 02, 2008	Dual-Band CDMA/EVDO Phone with Bluetooth	TYKNX9230		

## Peak Power ( Mid CH )



Date: 26.MAR.2008 16:05:12

## Peak Power ( High CH )



Date: 26.MAR.2008 16:04:36


HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCT-R08-039	Test Dates: Apr. 02, 2008	EUT Type: Dual-Band CDMA/EVDO Phone with Bluetooth	FCC ID: TYKNX9230	Page 11 of 51	

## 7.2 BAND EDGES MEASUREMENT

### LIMIT

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

### Test Configuration



### TEST PROCEDURE

The spectrum analyzer is set to :

1. Span = 8 MHz
2. RBW = 100 kHz
3. VBW = 300 kHz
4. Sweep = auto
5. Detector Mode = Peak


### TEST RESULTS

See attached.

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCT-R08-039	Test Dates: Apr. 02, 2008	EUT Type: Dual-Band CDMA/EVDO Phone with Bluetooth	FCC ID: TYKKNX9230	Page 1 2	of 51


## Test Data (GFSK)

### Band Edges (Low- CH)



Date: 26.MAR.2008 16:07:51

### Band Edges (High-CH)




Date: 26.MAR.2008 16:08:32

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 1 3 of 51	
HCT-R08-039	Apr. 02, 2008	Dual-Band CDMA/EVDO Phone with Bluetooth	TYKNX9230		


## Test Data (8DPSK)

### Band Edges (Low- CH)



Date: 26.MAR.2008 16:07:09

### Band Edges (High-CH)



Date: 26.MAR.2008 16:09:39


HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 14 of 51	
HCT-R08-039	Apr. 02, 2008	Dual-Band CDMA/EVDO Phone with Bluetooth	TYKNX9230		

### 7.2.1 BAND EDGES MEASUREMENT (RADIATED))

#### LIMIT

According to §15.247(c), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

#### Test Configuration



#### TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8m above the ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
  - (a) PEAK: RBW = VBW = 1 MHz / Sweep = AUTO
  - (b) AVERAGE: RBW = 1 MHz / VBW = 10 Hz / Sweep = AUTO
5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.

#### TEST RESULTS

Refer to attach spectrum analyzer data chart.

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCT-R08-039	Test Dates: Apr. 02, 2008	EUT Type: Dual-Band CDMA/EVDO Phone with Bluetooth	FCC ID: TYKKNX9230	Page 15 of 51	


## Test Data

### Test Plots(GFSK)

(Low- CH)


Polarity: Vertical

Detector mode: Peak



Date: 27.MAR.2008 06:33:44

Detector mode: Average




Date: 27.MAR.2008 06:35:07

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 16 of 51	
HCT-R08-039	Apr. 02, 2008	Dual-Band CDMA/EVDO Phone with Bluetooth	TYKNX9230		

(Low- CH)


Polarity: Horizontal

Detector mode: Peak




Date: 27.MAR.2008 06:47:58

Detector mode: Average




Date: 27.MAR.2008 06:51:58

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 17 of 51	
HCT-R08-039	Apr. 02, 2008	Dual-Band CDMA/EVDO Phone with Bluetooth	TYKNX9230		

**Test Plots, (High- CH)**
**Polarity: Vertical**
**Detector mode: Peak**


Date: 27.MAR.2008 07:03:55

**Detector mode: Average**



Date: 27.MAR.2008 07:05:42

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 18 of 51	
HCT-R08-039	Apr. 02, 2008	Dual-Band CDMA/EVDO Phone with Bluetooth	TYKNX9230		

(High- CH)


Polarity: Horizontal

Detector mode: Peak



Date: 27.MAR.2008 06:57:50

Detector mode: Average



Date: 27.MAR.2008 06:59:35


HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>	
Test Report No. HCT-R08-039	Test Dates: Apr. 02, 2008	EUT Type: Dual-Band CDMA/EVDO Phone with Bluetooth		FCC ID: TYKKNX9230	Page 19	of 51

## Test Plots (8DPSK)

(Low- CH)


Polarity: Vertical

Detector mode: Peak



Date: 27.MAR.2008 07:28:28

Detector mode: Average




Date: 27.MAR.2008 07:30:02

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 20 of 51	
HCT-R08-039	Apr. 02, 2008	Dual-Band CDMA/EVDO Phone with Bluetooth	TYKNX9230		

(Low- CH)


Polarity: Horizontal

Detector mode: Peak



Date: 27.MAR.2008 07:23:44

Detector mode: Average




Date: 27.MAR.2008 07:25:08

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 21 of 51	
HCT-R08-039	Apr. 02, 2008	Dual-Band CDMA/EVDO Phone with Bluetooth	TYKNX9230		

## Test Plots, (High- CH)


## Polarity: Vertical

### Detector mode: Peak



Date: 27.MAR.2008 07:09:39

### Detector mode: Average




Date: 27.MAR.2008 07:11:11

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 2 of 51	
HCT-R08-039	Apr. 02, 2008	Dual-Band CDMA/EVDO Phone with Bluetooth	TYKNX9230		

(High- CH)


Polarity: Horizontal

Detector mode: Peak



Date: 27.MAR.2008 07:16:17

Detector mode: Average



Date: 27.MAR.2008 07:18:59


HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 2 3 of 51	
HCT-R08-039	Apr. 02, 2008	Dual-Band CDMA/EVDO Phone with Bluetooth	TYKNX9230		

### 7.3 FREQUENCY SEPARATION

#### LIMIT

According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

#### Test Configuration



#### TEST PROCEDURE

The spectrum analyzer is set to :

1. Span = 3 MHz
2. RBW = 30 kHz
3. VBW = 100 kHz
4. Sweep = auto

The trace was allowed to stabilize. The marker-delta function was used to determine the separation between the peaks of the adjacent channels.

#### TEST RESULTS

*No non-compliance noted*


#### Test Data

Channel Separation (kHz)		20dB Bandwidth (kHz)			Limit (kHz)	Result
GFSK	8DPSK	Channel	GFSK	8DPSK		
876	990	Low CH	930	1290	>25	Pass
		Middle CH	984	1284		
		High CH	930	1278		

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:		Page 24 of 51
HCT-R08-039	Apr. 02, 2008	Dual-Band CDMA/EVDO Phone with Bluetooth	TYKNX9230		


## Test Plot

### Measurement of Channel Separation(GFSK)



Date: 26.MAR.2008 16:12:46

### Measurement of Channel Separation(8DPSK)



Date: 26.MAR.2008 16:11:19


HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 25 of 51	
HCT-R08-039	Apr. 02, 2008	Dual-Band CDMA/EVDO Phone with Bluetooth	TYKNX9230		



## Test Plot (GFSK)


## 20 dB bandwidth

**(Low CH)**




Date: 26.MAR.2008 16:23:01

( Mid CH)




Date: 26.MAR.2008 16:23:52

<b>FCC CERTIFICATION REPORT</b>		<a href="http://www.hct.co.kr">www.hct.co.kr</a>
<b>Test Report No.</b> HCT-R08-039	<b>Test Dates:</b> Apr. 02, 2008	<b>EUT Type:</b> Dual-Band CDMA/EVDO Phone with Bluetooth


**(High CH)**


Date: 26.MAR.2008 16:24:39


**Test Plot (8DPSK)**
**20 dB bandwidth**
**(Low CH)**


Date: 26.MAR.2008 16:27:48

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 27 of 51	
HCT-R08-039	Apr. 02, 2008	Dual-Band CDMA/EVDO Phone with Bluetooth	TYKNX9230		

**( Mid CH)**


Date: 26.MAR.2008 16:26:40

**(High CH)**


Date: 26.MAR.2008 16:25:14


HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 28 of 51	
HCT-R08-039	Apr. 02, 2008	Dual-Band CDMA/EVDO Phone with Bluetooth	TYKNX9230		

## 7.4 NUMBER OF HOPPING FREQUENCY

### LIMIT

According to §15.247(a)(1)(ii), Frequency hopping systems operating in the 2400 MHz ~ 2483.5 MHz bands shall use at least 15 hopping frequencies.

### Test Configuration



### TEST PROCEDURE

The Bluetooth frequency hopping function of the EUT was enabled. The spectrum analyzer was set to :

1. Span = the frequency band of operation ( Start = 2400 MHz, Stop = 2483.5 MHz )
2. RBW = 300 kHz
3. VBW = 300 kHz
4. Sweep = auto

The trace was allowed to stabilize.

### TEST RESULTS

*No non-compliance noted*

### Test Data


Result (No. of CH)	Limit (No. of CH)	Result
79	>75	Pass

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCT-R08-039	Test Dates: Apr. 02, 2008	EUT Type: Dual-Band CDMA/EVDO Phone with Bluetooth	FCC ID: TYKKNX9230	Page 29 of 51

## Test Plot


### Number of Channels (GFSK)

2.4 GHz – 2.441 GHz



Date: 26.MAR.2008 16:14:39

2.441 GHz – 2.4835 GHz




Date: 26.MAR.2008 16:22:15

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 30 of 51	
HCT-R08-039	Apr. 02, 2008	Dual-Band CDMA/EVDO Phone with Bluetooth	TYKNX9230		


## Number of Channels (8DPSK)

2.4 GHz – 2.441 GHz



Date: 26.MAR.2008 16:17:03

2.441 GHz – 2.4835 GHz



Date: 26.MAR.2008 16:21:04


HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCT-R08-039	Test Dates: Apr. 02, 2008	EUT Type: Dual-Band CDMA/EVDO Phone with Bluetooth	FCC ID: TYKNX9230	Page 31 of 51	

## 7.5 TIME OF OCCUPANCY (DWELL TIME)

### LIMIT

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400 MHz ~ 2483.5 MHz bands. The average time of occupancy on any channels shall not greater than 0.4 s within a period 0.4 s multiplied by the number of hopping channels employed.

### Test Configuration



### TEST PROCEDURE

EUT was set to transmit the longest packet type (DH5)

1. Span = zero span
2. RBW = 1 MHz
3. VBW = 1 MHz
4. Sweep = as necessary to capture the entire dwell time per channel

The marker-delta function was used to determine the dwell time.

### TEST RESULTS

See the table.

#### DH 5(The longest packet type for GFSK)

CH Mid :  $2.890 * (1600/6)/79 * 31.6 = 308.26$  (ms)

#### 3-DH 5(The longest packet type for 8DPSK)

CH Mid :  $2.890 * (1600/6)/79 * 31.6 = 308.26$  (ms)


Channel	Pulse Time (ms)		Total of Dwell (ms)		Period Time (s)	Limit (ms)	Result
	GFSK	8DPSK	GFSK	8DPSK			
Low	2.900	2.890	309.33	308.26	31.6	400	PASS
Mid	2.890	2.890	308.26	308.26	31.6		PASS
High	2.900	2.890	309.33	308.26	31.6		PASS

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:		Page 32 of 51
HCT-R08-039	Apr. 02, 2008	Dual-Band CDMA/EVDO Phone with Bluetooth	TYKKNX9230		

## Test Plots (GFSK)


**DH 5**

( Low CH )





Date: 26.MAR.2008 16:42:40

( Mid CH )




Date: 26.MAR.2008 16:43:38


HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 33 of 51	
HCT-R08-039	Apr. 02, 2008	Dual-Band CDMA/EVDO Phone with Bluetooth	TYKNX9230		

**(CH High)**

**Test Plots (8DPSK)**
**3-DH 5**
**( Low CH )**


HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 34 of 51	
HCT-R08-039	Apr. 02, 2008	Dual-Band CDMA/EVDO Phone with Bluetooth	TYKNX9230		

**( Mid CH )**


Date: 26.MAR.2008 16:45:56

**(CH High)**


Date: 26.MAR.2008 16:45:01

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 35 of 51	
HCT-R08-039	Apr. 02, 2008	Dual-Band CDMA/EVDO Phone with Bluetooth	TYKNX9230		


## 7.6 SPURIOUS EMISSIONS

### 7.6.1 Conducted Spurious Measurement

#### LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

#### Test Configuration



#### TEST PROCEDURE

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 100 kHz.

Detector Mode is set to a peak detector Mode.

Measurements are made over the 30 MHz to 26 GHz range with the transmitter set to the lowest, middle, and highest channels.


#### TEST RESULTS

*No non-compliance noted*

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCT-R08-039	Test Dates: Apr. 02, 2008	EUT Type: Dual-Band CDMA/EVDO Phone with Bluetooth	FCC ID: TYKKNX9230	Page 36 of 51	


## Test Plots (GFSK)

### ( Low CH )



Date: 26.MAR.2008 16:52:43


### (Mid CH )



Date: 26.MAR.2008 16:51:29

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 37 of 51	
HCT-R08-039	Apr. 02, 2008	Dual-Band CDMA/EVDO Phone with Bluetooth	TYKNX9230		


## ( High CH )



Date: 26.MAR.2008 16:50:33


## Test Plots (8DPSK)

### ( Low CH )




Date: 26.MAR.2008 16:47:45

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 38 of 51	
HCT-R08-039	Apr. 02, 2008	Dual-Band CDMA/EVDO Phone with Bluetooth	TYKNX9230		

**(Mid CH )**


Date: 26.MAR.2008 16:48:35

**( High CH )**


Date: 26.MAR.2008 16:49:21

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 39 of 51	
HCT-R08-039	Apr. 02, 2008	Dual-Band CDMA/EVDO Phone with Bluetooth	TYKNX9230		



### 7.6.2 Radiated Spurious Emissions

#### LIMIT


1. 20dBc in any 100kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed

Frequency (MHz)	Field Strength (mV/m)	Measurement Distance (m)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3


HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCT-R08-039	Test Dates: Apr. 02, 2008	EUT Type: Dual-Band CDMA/EVDO Phone with Bluetooth	FCC ID: TYKKNX9230	Page 40 of 51

## Test Configuration

### Below 30 MHz




### 30 MHz - 1 GHz



HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCT-R08-039	Test Dates: Apr. 02, 2008	EUT Type: Dual-Band CDMA/EVDO Phone with Bluetooth	FCC ID: TYKNX9230	Page 41 of 51	

## Above 1 GHz



## TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8 m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCT-R08-039	Test Dates: Apr. 02, 2008	EUT Type: Dual-Band CDMA/EVDO Phone with Bluetooth	FCC ID: TYKNX9230	Page 42 of 51	



## TEST RESULTS

9 kHz – 30MHz

**Operation Mode:** Normal Link (Standard Battery)

### Notes:

1. Measuring frequencies from 9 kHz to the 30MHz.
2. The reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
3. Distance extrapolation factor =  $40 \log (\text{specific distance} / \text{test distance})$  (dB)
4. Limit line = specific Limits (dBuV) + Distance extrapolation factor

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCT-R08-039	Test Dates: Apr. 02, 2008	EUT Type: Dual-Band CDMA/EVDO Phone with Bluetooth	FCC ID: TYKKNX9230	Page 43 of 51	



## TEST RESULTS

### Below 1 GHz

**Operation Mode:** Normal Link

Frequency MHz	Read Level dBuV	Ant. Factor dB/m	Cable Loss dB	ANT POL (H/V)	Result Level dBuV/m	Limit dBuV/m	Margin dB
268.8	17.4	11.7	3.9	H	33.0	46.0	13.0
456.2	12.1	16.3	5.0	H	33.4	46.0	12.6
480.6	15.7	16.6	5.2	H	37.5	46.0	8.5
504.4	12.4	17.0	5.3	H	34.7	46.0	11.3
552.6	13.3	17.9	5.5	H	36.7	46.0	9.3
552.6	12.1	17.9	5.5	V	35.5	46.0	10.5

#### Notes:

1. Measuring frequencies from 30 MHz to the 1 GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Quasi peak detector mode.

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>	
Test Report No. HCT-R08-039	Test Dates: Apr. 02, 2008	EUT Type: Dual-Band CDMA/EVDO Phone with Bluetooth		FCC ID: TYKKNX9230	Page 44	of 51



## Above 1 GHz

### Operation Mode: CH Low (EDR)

Frequency [MHz]	Level [dBm]	AN. CL. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4804	-101.88	58.68	V	53.56	74	20.44	PK
4804	-103.05	44.60	V	40.65	54	13.35	AV

### Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
  - a. Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MHz.
  - b. AV Setting 1 GHz- 26 GHz, RBW = 1 MHz, VBW = 10 Hz.

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCT-R08-039	Test Dates: Apr. 02, 2008	EUT Type: Dual-Band CDMA/EVDO Phone with Bluetooth	FCC ID: TYKKNX9230	Page 45 of 51

**Operation Mode: CH Mid (EDR)**

Frequency [MHz]	Level [dBm]	AN. CL. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4882	-96.82	61.96	V	51.78	74	22.22	PK
4882	-99.70	45.67	V	38.37	54	15.63	AV

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000 MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
  - a. Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MHz.
  - b. AV Setting 1 GHz- 26 GHz, RBW = 1 MHz, VBW = 10 Hz.

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 46 of 51	
HCT-R08-039	Apr. 02, 2008	Dual-Band CDMA/EVDO Phone with Bluetooth	TYKNX9230		

**Operation Mode: CH High (EDR)**

Frequency [MHz]	Level [dBm]	AN. CL. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4960	-92.27	63.12	V	48.39	74	25.61	PK
4960	-97.07	45.83	V	35.90	54	18.10	AV

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
  - a. Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MHz.
  - b. AV Setting 1 GHz- 26 GHz, RBW = 1 MHz, VBW = 10 Hz.

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 47 of 51	
HCT-R08-039	Apr. 02, 2008	Dual-Band CDMA/EVDO Phone with Bluetooth	TYKNX9230		



## 7.7 POWERLINE CONDUCTED EMISSIONS

### LIMIT

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolt (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dB $\mu$ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

### Test Configuration

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

### TEST PROCEDURE

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors – Quasi Peak and Average Detector.

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 48 of 51	
HCT-R08-039	Apr. 02, 2008	Dual-Band CDMA/EVDO Phone with Bluetooth	TYKKNX9230		

## Test Data

### Conducted emissions (Line 1)


HCT

EMC TEST LAB.

EUT: Boulder  
 Manufacturer: CHMC  
 Operating Condition: Bluetooth Mode  
 Test Site: SHIELD ROOM  
 Operator: YH.LEE  
 Test Specification: CISPR 22 CLASS B  
 Comment: N

**SCAN TABLE: "CISPR 22 Voltage"**

CISPR 22 Voltage						
Start	Stop	Step	Detector	Meas.	IF	Transducer
150.1 kHz	500.0 kHz	2.5 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			
500.0 kHz	5.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			
5.0 MHz	30.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			



**MEASUREMENT RESULT: "Phone\_fin\_QP"**

4/2/2008 4:27PM	Frequency	Level	Transd	Limit	Margin	Line	PE
	MHz	dB $\mu$ V	dB	dB $\mu$ V	dB		
	0.500000	40.20	10.1	56	15.8	---	---
	1.844000	56.40	10.3	56	-0.4	---	---
	5.000000	42.20	10.6	56	13.8	---	---

**MEASUREMENT RESULT: "Phone\_fin\_AV"**

4/2/2008 4:27PM	Frequency	Level	Transd	Limit	Margin	Line	PE
	MHz	dB $\mu$ V	dB	dB $\mu$ V	dB		
	0.465100	25.10	10.1	47	21.5	---	---
	1.848000	42.20	10.3	46	3.8	---	---
	5.000000	28.40	10.6	46	17.6	---	---

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 49 of 51	
HCT-R08-039	Apr. 02, 2008	Dual-Band CDMA/EVDO Phone with Bluetooth	TYKNX9230		

## Conducted emissions (Line 2)

HCT


EMC TEST LAB.

EUT: Boulder  
 Manufacturer: CHMC  
 Operating Condition: Bluetooth Mode  
 Test Site: SHIELD ROOM  
 Operator: YH.LEE  
 Test Specification: CISPR 22 CLASS B  
 Comment: H

### SCAN TABLE: "CISPR 22 Voltage"

Short Description: CISPR 22 Voltage

Start Frequency	Stop Frequency	Step Width	Detector	Meas.	IF Time	Transducer Bandw.
150.1 kHz	500.0 kHz	2.5 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			
500.0 kHz	5.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			
5.0 MHz	30.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			



### MEASUREMENT RESULT: "Phone\_fin\_QP"

4/2/2008 4:31PM

Frequency MHz	Level dB $\mu$ V	Transd dB	Limit dB $\mu$ V	Margin dB	Line	PE
0.500000	39.80	10.1	56	16.2	---	---
1.840000	58.50	10.3	56	-2.5	---	---
5.000000	44.40	10.6	56	11.6	---	---

### MEASUREMENT RESULT: "Phone\_fin\_AV"

4/2/2008 4:31PM

Frequency MHz	Level dB $\mu$ V	Transd dB	Limit dB $\mu$ V	Margin dB	Line	PE
0.455100	25.90	10.1	47	20.9	---	---
1.832000	41.80	10.3	46	4.2	---	---
5.000000	29.90	10.6	46	16.1	---	---

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 50 of 51	
HCT-R08-039	Apr. 02, 2008	Dual-Band CDMA/EVDO Phone with Bluetooth	TYKNX9230		



## 8. LIST OF TEST EQUIPMENT

Manufacturer	Model / Equipment	Calibration Date	Cal Interval	Calibration Due	Serial No.
Rohde & Schwarz	ESCI/ EMI Test Receiver	08/24/ 2007	Annual	08/24/ 2008	100033
Rohde & Schwarz	ESH2-Z5/ LISN	04/20/2007	Annual	04/20/2008	861741/013
Rohde & Schwarz	ESH3-Z6/ LISN	06/13/2007	Annual	06/13/2008	100329
Schwarzbeck	VULB 9160/ TRILOG Antenna	04/20/2007	Biennial	04/20/2008	9160-3150
HD	MA240/ Antenna Position Tower	N/A	N/A	N/A	556
EMCO	1050/ Turn Table	N/A	N/A	N/A	114
HD GmbH	HD 100/ Controller	N/A	N/A	N/A	13
HD GmbH	KMS 560/ SlideBar	N/A	N/A	N/A	12
Rohde & Schwarz	ESH3-Z2/ PULSE LIMITER	10/03/2007	Annual	10/03/2008	375.8810.352
MITEQ	AMF-60-0010 1800-35-20P	01/15/2008	Annual	01/15/2009	1200937
MITEQ	AMF-6D-01180-35-20P	04/25/2007	Annual	04/25/2008	990893
Schwarzbeck	BBHA 9120D/ Horn Antenna	03/30/2007	Biennial	03/30/2009	147
Schwarzbeck	BBHA9170/ SHF-EHF Horn Antenna	03/20/2007	Biennial	03/20/2009	BBHA9170342
Rohde & Schwarz	6502/Loop Antenna	12/26/2007	Biennial	12/26/2009	9009-2536
Rohde & Schwarz	FSP30/Spectrum Analyzer	06/28/2007	Annual	06/28/2008	839117/011
Agilent	E4440A/Spectrum Analyzer	01/08/2008	Annual	01/08/2009	US45303008
Agilent	E4416A /Power Meter	01/22/2008	Annual	01/22/2009	GB41291412
Wainwright Instrument	WHF3.3/18G-10EF / High Pass Filter	06/28/2007	Annual	06/28/2008	1
Hewlett Packard	11636B/Power Divider	01/14/2008	Annual	01/14/2009	11377
DIGITAL	EP-3010 /DC POWER SUPPLY	01/10/2008	Annual	01/10/2009	3110117

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCT-R08-039	Test Dates: Apr. 02, 2008	EUT Type: Dual-Band CDMA/EVDO Phone with Bluetooth	FCC ID: TYKNX9230	Page 51 of 51