

Project: 11CA49640

File: TC8316

Report: 08CA48859-FCCP24-A1

Date: Nov. 15, 2011 Model: XT DUAL

FCC Test Report

Satellite/GSM Mobile Hand Held Terminal Model: XT DUAL

For

Asia Pacific Satellite Industries Co., Ltd.

9FL, Lotte IT Castle 2-Dong, #550-1,Gasan-Dong, GeumCheon-Gu, Seoul, Korea, 153-768

UL Korea Ltd.

33 Fl. GFC Tower, 737 Yeoksam-Dong, Gangnam-Gu, Seoul, 135-984, Korea Underwriters Laboratories Inc. authorizes the above-named company to reproduce this Report provided it is reproduced in its entirety.

File Number: TC8316 Date of Issue: Nov. 15, 2011

Report Directory

1.	G E	N E R A L - Product Description	5
	1.1	Equipment Description	5
	2.1	Technical Data	5
	3.1	Equipment Type:	6
	4.1	FCC ID Label Info	6
	2.1	Equipment Used During Test	7
	2.2	Input/Output Ports	7
	2.3	Power Interface	7
	2.4	EUT Operating Mode and Frequencies	7
	2.5	Test Signal Source	8
	2.6	EUT Configurations	8
	2.7	Test Lab Environmental Condition	9
	2.8	Test Specifications	9
	2.9	Test Laboratory Details	9
3.	Ove	rview of Technical requirements	10
	3.1	RF Output Power	10
	3.2	Occupied Bandwidth	10
	3.3	Emission Limitations – Spurious Emission at Antenna Terminal	10
	3.4	Emission Limitations – Radiated Spurious Emission	11
	3.5	Frequency Stability	11
4.	Test	Results	12
	4.1	Test Conditions and Results – RF Power Output	12
	4.2	Test Conditions and Results - Occupied Bandwidth	14
	4.3	Test Conditions and Results – Spurious Emission at Antenna Terminal	16
	4.4	Test Conditions and Results – Radiated Spurious Emission	18
	4.5	Test Conditions and Results – Frequency Stability	21

Annex 1. Test Plots

Annex 2. Test Setup Photos

File Number: TC8316 Date of Issue: Nov. 15, 2011

Test Report Details:

Tests Performed By: UL Korea Ltd.

33rd FL. Star Tower 737 Yeoksam-dong, Kangnam-ku, Seoul, 135-984, Korea

Test Site: Chungbuk Technopark EMC Center

685-3 Yangcheong-ri, Ochang-eub, Cheongwon-kun, Chungbuk-province,

Republic of Korea.

FCC Registration No.: 94696

Tests Performed For: Asia Pacific Satellite Industries Co., Ltd.

9FL, Lotte IT Castle 2-Dong, #550-1, Gasan-Dong,

GeumCheon-Gu, Seoul, Korea, 153-768

Applicant Contact: WonJae Jung

Title: Manager of R&D Center

Phone: +82 2-2026-7780 Fax: +82 2-2026-7771 E-mail: jwjung@apsat.co.kr

Test Report Number: 08CA48859-FCCP24-A1

Test Report Date: Nov.25, 2009

Equipment Class: TNE - Licensed Non-Broadcast Transmitter Held to Ear

Product Type: Sat/GSM Mobile Hand Held Terminal

Model Number: XT DUAL

FCC ID: TZ5XT DUAL

Test standards 47 CFR Part 2, Part 24 Subpart E Broadband PCS

Sample Serial Number: Prototype

Sample Receive Date: 2008-10-04

Testing Start Date: 2008-11-25

Date Testing Complete: 2009-04-02
Test Report Reissue Date: 2011-11-15
Overall Results: Complied

UL Korea as an affiliate of Underwriters Laboratories Inc. EMC report apply only to the specific test samples and test results submitted for UL's review. All samples tested were in good operating condition throughout the entire test program. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. UL Korea Ltd. shall have no liability for any deductions, inferences or generalizations drawn by the client or others from UL Korea Ltd. issued reports. This report shall not be used to claim, constitute or imply product certification, approval, or any agency of the National Authorities. This report may contain test results that are not covered by the NVLAP or KOLAS accreditation.

File Number: TC8316 Date of Issue: Nov. 15, 2011

Summary of Testing:

The following tests were performed on a sample submitted for evaluation of compliance with 47 CFR Part 22 Subpart H and Part 15 Subpart B.

Test	Test Name	Compliant	Not	See
#	Test Requirement/Specification	Compliant	Compliant	Remark
1	RF Power Output - § 2.1046, § 24.232(b)	X		
2	Occupied Bandwidth - § 2.1049(i)	X		
3	Spurious Emission at antenna terminal - § 2.1051, § 24.238(a)	X		
4	Radiated Spurious Emission - § 2.1053, § 24.238(a)	X		
5	Frequency Stability - § 2.1055, § 24.235	X		
6	Band Edge - § 24.238(a)	X		

Remarks:

Modifications to EUT required for compliance: NONE.

Conclusion:

The tests listed in the Summary of Testing section of this report have been performed and the results recorded by UL Korea Ltd. in accordance with the procedures stated in each test requirement and specification. The test list was determined by the Applicant as being applicable to the Equipment Under Test. As a result, the subject product has been verified to comply or not comply as noted in the Summary of Testing with each test specification. The test results relate only to the items tested.

Tested by

Sung Hoon Baek, Project Engineer

hughdoon

Conformity Assessment Services – 3014ASEO

UL Korea Ltd.

Reviewed by

Jeawoon, Choi, Senior Project Engineer

Conformity Assessment Services – 3014ASEO

UL Korea Ltd.

File Number: TC8316 Date of Issue: Nov. 15, 2011

1. GENERAL - Product Description

1.1 Equipment Description

XT DUALis the **Satellite/GSM Mobile Hand Held Terminal** for Thuraya satellite mobile communication service based on GMR-1 and GMPRS-1.

Details of Test Equipment (EUT)

• Equipment Type : Sat/GSM Mobile Hand Held Terminal

Model No. : XT DUALTrade name : Thuraya

• Type of test Equipment : Portable Equipment

• Operating characteristic : MES(Mobile Earth Station) used in the Satellite Communication Services

• Manufacturer : Asia Pacific Satellite Industries Co., Ltd.

9FL, Lotte IT Castle 2-Dong, #550-1,

Gasan-dong, Geumcheon-gu, Seoul, Korea, 153-768

• Equipment Configuration

The EUT is consisted of the following component provided by the manufacturer.

No.	Product Type	Manufacturer	Model	Comments
1	Satellite Mobile Terminal	Asia Pacific Satellite Industries Co., Ltd.	XT DUAL	EUT
2	Travel Charger	Phihong Technology Co Ltd.	PSC11R-050	EUT
3	Ear Set	Cresyin	EMB-ATS 106TKA	EUT

2.1 Technical Data

Frequency Ranges : GSM 1900 Transmitter 1850.2 – 1909.8 MHz

Emission Designation : 250KGXW Number of Channel : 300 (PCS1900)

Output power : Max. 30.0 dBm (Peak) Power Class 1 (1W)

Supply Voltage : Battery 3.7 V, 2520mAh

Charger Power Rating : Input 100 - 240 Vac, 50/60 Hz, 0.3A Output 5-12

Vdc, 2 - 0.71 A

Note;

1. All the technical data described above were provided by the manufacturer.

File Number: TC8316 Date of Issue: Nov. 15, 2011

Int Type: cillary equipment for fix cillary equipment for vel cillary equipment for por	hicular mounted use
☐ Host connected	☐ Host connected
d single unit	☐ Module with associated connection or interface
Label Info	Equipment Marking Plate
F	THURAYA XT DUAL CC ID:TZ5XTDUAL N270 APSI CE0983
	cillary equipment for fix cillary equipment for vel cillary equipment for por Host connected d single unit

File Number: TC8316 Date of Issue: Nov. 15, 2011

2. Test Conditions

2.1 Equipment Used During Test

Use*	Product Type	Manufacturer	Model	Comments
EUT	Satellite Phone	Asia Pacific Satellite Industries Co., Ltd.	XT DUAL	
EUT	AC Adapter	Phihong Technology Co Ltd.	PSC11R-050	
SIM	Universal Radio Communication tester	National Instruments	CMU200	GSM Signal generator

2.2 Input/Output Ports

Port #	Name	Type*	Cable Max. >3m (Y/N)	Cable Shielded (Y/N)	Comments
0	Enclosure	-	=	=	Non-metal enclosure
1	DC Input port	DC	< 3m	Unshield	Connected to Charger
2	Ear set	I/O	< 3m	Unshield	Connected to Mono Ear set

Note:

-. AC = AC Power Port

DC = DC Power Port

N/E = Non-Electrical

2.3 Power Interface

Mode #	Voltage (V)	Current (A)	Power (W)	Frequency (DC/AC-Hz)	Phases (#)	Comments
Rated	3.7 V	1	1	DC	1	Internal Battery Rating
1	3.7 V	-	-	DC	-	Normal operating voltage
2	3.5 V	ı	ı	DC	ı	Battery End Point
3	4.2 V	-	-	DC	-	Battery Full charged voltage

Note

2.4 EUT Operating Mode and Frequencies

Mode #	Description
1	GSM 1900 : 3 frequencies (Low, Mid, High channels) for assigned frequency band Bottom channel : 1850.2 MHz Mid channel : 1880.2 MHz Top channel : 1909.8 MHz

^{-.} I/O = Signal Input or Output Port (Not Involved in Process Control)

^{-.} All the interface cables and Power Cable have been provided by the manufacturer

^{-.} UDC port is not user interface port for data download purpose only.

^{-.} For Input voltage change, dummy battery pack which was connected to external dc power supply was used.

File Number: TC8316 Date of Issue: Nov. 15, 2011

2.5 Test Signal Source


The carrier from the signal generator applied to the repeater was standard signal.

GSM

-. Data format : Pattern , Bits/Symbol :1, Data : PN23 -. Modulation Type : MSK, Sym rate : 270.833333 kSPS

-. GSM : Standard -. Filter : 0.3 Gaussian -. I/Q Scaling : 100%

2.6 EUT Configurations



File Number: TC8316 Date of Issue: Nov. 15, 2011

2.7 Test Lab Environmental Condition

Parameters required prior to the test	Laboratory Ambient Temperature	10 to 40 °C
	Relative Humidity	10 to 90 %
Parameters recorded during the test	Laboratory Ambient Temperature	20 °C
	Relative Humidity	40 %

2.8 Test Specifications

Standard Number	Standard Name	Standard Date
CFR 47 Part 24 Subpart E	Personal Communications Services – Broadband PCS	2008
ANSI C63.4-2003	Methods of Measurements of Radio-Noise Emission from Low voltage and electrical equipment in the range of 9kHz~40GHz	2003
EIA/TIA-603 Edition C 2004	Land Mobile FM or PM communication equipment measurement and performance standards	2004

2.9 Test Laboratory Details

All the testing has been performed by UL Korea engineer at both test laboratories described below. The radiated spurious emission measurements were performed in a 10 meter open site which has been filed to the commission in accordance with section 2.948 at Chungbuk Technopark EMC Center.

Persons who have been presented during the test: Wonjae-Jung / Senior Engineer from APSI.

Measurement Uncertainties

Test	Uncertainty
Radiated Emissions	± 2.93 [dB], k=2 (Trust level 95%)
Conducted Emissions	± 2.93 [dB], k=2 (Trust level 95%)

File Number: TC8316 Date of Issue: Nov. 15, 2011

3. Overview of Technical requirements

The following test items show that the correspondence of test items and the performance of output power and its spectrum transmission are in accordance to the technical description.

The test results shows No deviations to the technical requirements were ascertained during the tests performed. Deviations as specified in this report were ascertained during the tests performed.
3.1 RF Output Power Reference: FCC 47 CFR Part 24 Subpart E Personal Communications Services – Broadband PCS _Oct. 01, 2008 Clause: Section 24.232(c) Power Limit
Technical requirements Mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.
Result of test Pass Fail Already tested(refer to test report no) Not applicable Remarks: None
3.2 Occupied Bandwidth Reference: FCC 47 CFR Part 24 Subpart E Personal Communications Services – Broadband PCS _Oct. 01, 2008 Clause: Section 24.238(b) Emission limitations Section 2.1049
Technical requirements Measurement bandwidth of at least 1% of the occupied bandwidth. For ca. 300.0 kHz, this equates to a resolution bandwidth of at least 3.0 kHz. For this testing, a resolution bandwidth 3.0 kHz was used. No technical Requirement exist. Just reference report purpose.
Result of test Pass Fail Already tested(refer to test report no) Not applicable Remarks: None

3.3 Emission Limitations – Spurious Emission at Antenna Terminal

Reference: FCC 47 CFR Part 24 Subpart E Personal Communications Services - Broadband PCS _Oct. 01, 2008

Clause : Section 25.238(a) Emission limitations

Section 2.1051

Technical requirements The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB. Result of test Pass Fail Already tested(refer to test report no) Not applicable Remarks: None
3.4 Emission Limitations – Radiated Spurious Emission
Reference: FCC 47 CFR Part 24 Subpart E Personal Communications Services – Broadband PCS _Oct. 01, 2008 Clause: Section 25.238(a) Emission limitations Section 2.1053
Technical requirements The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB. Result of test Pass Fail
Already tested(refer to test report no) Not applicable Remarks: None
3.5 Frequency Stability Reference: FCC 47 CFR Part 24 Subpart E Personal Communications Services – Broadband PCS _Oct. 01, 2008
Clause : Section 24.235 Section 2.1055
Technical requirements The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.
Result of test Pass Fail Already tested(refer to test report no) Not applicable Remarks: None

Test Report No: 08CA48859-FCCP24-A1

Date of Issue: Nov. 15, 2011

Project Number: 11CA49640

File Number: TC8316

File Number: TC8316 Date of Issue: Nov. 15, 2011

4. Test Results

4.1 Test Conditions and Results – RF Power Output

Test Description	Measurements were made in the laboratory environment and 10meter semi anechoic chamber. For conducted measurement, all calculations and methods used by the applicant for determining carrier power or peak envelope power, as appropriate, on the basis of measured power in the radio frequency load attached to the transmitter output terminals shall be shown. The EUT was adjusted to produce maximum power rating of the product specification. The measurements were made at the EUT RF output ports in downlink transmit operation mode at B,M,T channels. For radiated measurement, the substitution measurement method in accordance with in TIA/EIA-603-A-2003 was used.					
Basic Standa	Basic Standard 47 CFR § 2.1046, § 24.232(c)					
		RF Power output Limit				
		are limited to 2 watts EIRP and the equipment for successful communications.	t must employ a means for			
Parameters r	equired prior to the test	Laboratory Ambient Temperature	10 to 40 °C			
Relative Humidity 10 to 90 %						
Parameters recorded during the test		Laboratory Ambient Temperature	23 °C			
		Relative Humidity	42 %			

RF output power Configuration Settings

Power Interface Mode # (See Section 2.3)	EUT Configurations Mode # (See Section 2.6)	EUT Operation Mode # (See 2.4)				
1	1,2	1				
Supplementary information: None						

Test Equipment

Description	Manufacturer	Model	Identifier	Cal. Due
Spectrum Analyzer	Agilent Technologies	E4440A	MY46186519	2009.03.29
RF Power Meter	Agilent Technologies	E4418B	MY45105913	2009.03.29
Power Sensor	Agilent Technologies	8481H	MY41092319	2009.03.29
Coaxial Attenuator	Agilent Technologies	8491B	90466	2009.03.29
High Pass Filter	Wainwright	WHK3.3/18G-10EF	10Z	2009.08.20
Test Receiver	Rohde & Schwarz	ESIB26	100359	2009.05.26
Horn Antenna	EMCO	3115	00056768	2010.03.24
Horn Antenna	Rohde & Schwarz	BBHA9120D	539	2009.03.24
Position controller	Inn-co	CO 2000	11261105/L	-
Antenna Mast	Inn-co	MA 4000	-	-
Turntable	Inn-co	DT 3000	-	-

File Number: TC8316 Date of Issue: Nov. 15, 2011

RF output power data - Conducted Measurement

Modulation	Frequency (MHz)	Voice (dBm)	GPRS Data 1 TX Slot	GPRS Data 2 TX Slot	GPRS Data 3 TX Slot	GPRS Data 4 TX Slot
	(MHZ)	(ubiii)	(dBm)	(dBm)	(dBm)	(dBm)
GSM 1900	1850.2	29.75	29.65	29.63	29.62	29.61
(GMSK)	1880.2	29.78	29.72	29.71	29.69	29.67
(OMSK)	1909.8	29.72	29.70	29.67	29.65	29.63

Supplementary information:

- -. Tx mode
- -. Modulated RF output power
- -. Power measurement : Channel power w/ peak value
- -. Before the measurement, the system calibration for compensation of cable loss and attenuator has been made and included as an offset value in every measurement.

RF output power data - Radiated Measurement (EIRP)

Frequency (MHz)	Ant. Polarity	S.G Level (dBm)	Cable loss (dB)	Ant. Gain (dB)	EIRP Level (dBm)	EIRP Level (W)
1850.2	V	25.95	5.50	9.10	29.55	0.901
1880.2	V	26.46	5.60	9.20	30.06	1.164
1909.8	V	26.25	5.70	9.30	29.85	0.966

Supplementary information:

- -. EIRP Level = Signal Generator output level Cable loss + Antenna Gain(Substitution)
- -. EIRP measurement has been performed with three orthogonal position of the EUT. The reported data is the worst case position of Z axis(phone vertical position).
- -. Voice call mode was selected as a worst case operating mode which was the highest RF output power at the conducted measurement.

Remarks: None		
Result of test In accordance with Technical requ	irement of FCC Rules secti	ion 47 CFR § 2.1046, § § 24.232(c)
		☐ Failed

File Number: TC8316 Date of Issue: Nov. 15, 2011

4.2 Test Conditions and Results - Occupied Bandwidth

Test Description	Measurements were made in the laboratory environment. The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. The modulated carrier signal with maximum RF level was applied to the up and down link input of the repeater and resulting output was compared against the original signal.					
Basic Standa	Basic Standard 47 CFR § 2.1049					
	Occupied Bandwidth Limits					
Parameters re	equired prior to the test	Laboratory Ambient Temperature	10 to 40 °C			
	Relative Humidity 10 to 90 %					
Parameters re	Parameters recorded during the test					
		Relative Humidity	40 %			

Occupied Bandwidth Configuration Settings

Power Interface Mode # (See Section 2.3)	EUT Configurations Mode # (See Section 2.6)	EUT Operation Mode # (See 2.4)					
1	2	1					
Supplementary information: None							

Occupied Bandwidth Spectrum Analyzer Settings

		Occupied Bandwidth Requirements				
Span	Resolution Bandwidth	dBc	%			
2 MHz (GSM)	-26	99				
Supplementary information: 99% bandwidth was applied.						

Occupied Bandwidth Test Equipment

Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Signal Generator	Agilent	E4438C	MY45095542	2008-11-28	2009-11-28
Signal Generator	Agilent	E4438C	MY45093570	2009-04-24	2010-04-30
Spectrum Analyzer	Agilent	E4440A	MY42510388	2009-11-11	2010-11-11
Fixed Attenuator	HP	8496A - 30 dB	3318A07585	-	-
Fixed Attenuator	INMET	30 dB	992310-29	-	-

File Number: TC8316 Date of Issue: Nov. 15, 2011

Occupied Bandwidth results

	Occupied bandwidth			
Modulation	Frequency (MHz)	99%	26dB	
	1850.2	250.9 kHz	324.8 kHz	
GSM	1880.2	246.9.kHz	321.1 kHz	
	1909.8	245.5 kHz	317.1 kHz	

Supplementary information:

- -. Modulated RF signal applied, 99% bandwidth
- -. Part 24.238 (a) requires a measurement bandwidth of at least 1% of the occupied bandwidth. For ca. 300.0 kHz, This equates to a resolution bandwidth of at least 3.0 kHz.

Remarks: Refer to the Measurement Plots provided in Annex 1 no.: 1 - 2

Result of test

In accordance with Technical requirement of FCC Rules section 47 CFR § 2.1049

∇	Complied	Failed
\triangle	Compnea	raned

File Number: TC8316 Date of Issue: Nov. 15, 2011

4.3 Test Conditions and Results - Spurious Emission at Antenna Terminal

1	esi			
Γ	es)	cri	pti	or

Measurements were made in the laboratory environment. Conducted spurious emission measurement was made using a direct connection between RF output of the EUT and spectrum analyzer via RFattenuator. A modulated carrier signal from the donor was applied to the optic input port of the EUT. Measurement has been performed with the EUT set to maximum output level at low, mid and high channel frequencies. The spectrum was investigated from 30 MHz to up to 10^{th} harmonics of the carrier frequencies.

Basic Standard 47 CFR § 2.1051, § 24.238(a)

Emission Limits

§ 24.238 Emission limitations for broadband PCS equipment

(a) Out of band emissions: The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P) dB$.

Emission Mask Configuration Settings

Power Interface Mode # (See Section 2.3)	EUT Configurations Mode # (See Section 2.6)	EUT Operation Mode # (See 2.4)				
1	2	1				
Supplementary information: None						

Conducted spurious emission Spectrum Analyzer Settings

Frequency Range (MHz)	Resolution Bandwidth	Video Bandwidth		
30 MHz ~ 1 GHz	100 kHz	300 kHz		
1 GHz ~ 10 GHz	1 MHz	3 MHz		
Supplementary information:				

Conducted Spurious Emission Test Equipment

Description	Manufacturer	Model	Identifier	Cal. Due
Spectrum Analyzer	Agilent Technologies	E4440A	MY46186519	2009.03.29
RF Power Meter	Agilent Technologies	E4418B	MY45105913	2009.03.29
Power Sensor	Agilent Technologies	8481H	MY41092319	2009.03.29
Coaxial Attenuator	Agilent Technologies	8491B	90466	2009.03.29
High Pass Filter	Wainwright	WHK3.3/18G-10EF	10Z	2009.08.20
Test Receiver	Rohde & Schwarz	ESIB26	100359	2009.05.26

File Number: TC8316 Date of Issue: Nov. 15, 2011

Out of band emission - Spurious emissions results

Tuned Frequency (MHz)	Emission Frequency (MHz)	Loss offset (dB)	Spurious emission measured (dBm)	Limit (dBm)	Margin (dB)
	3700.4	-	-	-13	-
Low Channel	5550.6	-	-	-13	-
(1850.2 MHz)	7400.8	-	-	-13	-
	-	-	-	-13	-
Mid Channel (1880.2 MHz)	869.4	-	-	-13	-
	880.2	-	-	-13	-
	891.4	-	-	-13	-
	ī	-	-	-13	-
	869.4	-	-	-13	-
High Channel (1909.8 MHz)	880.2	-	-	-13	-
	891.4	-	-	-13	-
	-		-	-13	-

Supplementary information:

- -. no spurious or more than 20 dB under limit
- -. Power measurement : Peak power measured
- -. For each tuned carrier frequency, the maximum spurious emission detected was recorded.

Remarks:

Refer to the Measurement Plots p	provided in Annex 1	no.: 13 - 66
----------------------------------	---------------------	--------------

Result of test

				~				
In accordance with Technical	roquiromont	of ECC Dulge	coction 17	ひじひょ	3 7 1051	V+ >	: 74 729	(0)
m accordance with recinical	1 Cuuli Cili Cili (of LCC Kates	Section 47		2.IUJI	∞	₹ 24.230	(a)

Complied Fa	il	e	d
-------------	----	---	---

File Number: TC8316 Date of Issue: Nov. 15, 2011

4.4 Test Conditions and Results - Radiated Spurious Emission

Test Description	Measurements were made in a 10-meter open field test site that complies to CISPR 16/ANSI C63.4. Preliminary (peak) measurements were performed at semi-anechoic chamber with an antenna to EUT separation distance of 3 meter. The EUT was rotated 360° about its azimuth with the receive antenna located at various heights in both horizontal and vertical polarities. The EUT's RF output port was terminated with 50 ohm load. The EUT was set to transmit at low, mid and high channel frequencies with max output power condition. Final measurements (quasi-peak or average as noted) were then performed by rotating the EUT about 360° and adjusting the receive antenna height from 1 to 4-meters in accordance with procedure of substitution method specified in TIA/EIA-603-A-2003. All frequencies up to 10 GHz were investigated in both horizontal and vertical antenna polarity, where applicable. The maximum EIRP of the emissions were reported.

Basic Standard § 2.1053 , § 24.238(a)

Radiated Spurious Emission LIMITS

§ 22.917 Emission limitations for cellular equipment

(a) Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P) dB$.

Laboratory Ambient Temperature	10 to 40 °C				
Relative Humidity	10 to 90 %				
Laboratory Ambient Temperature	27 °C				
Relative Humidity	47 %				
Frequency range	Measurement Point				
1GHz – 20GHz	(3 meter measurement distance)				
Limits – EIRP					
Limit (dBm EIRP)					
Peak	Average				
-13 dBm	NA				
_	Relative Humidity Laboratory Ambient Temperature Relative Humidity Frequency range 1GHz – 20GHz Limits – EIRP Limit (dl)				

Spectrum Analyzer Settings

Supplementary information: -(43+10LogP) = -43.65dBc

Frequency Range (MHz)	Resolution Bandwidth	Video Bandwidth			
1 GHz ~ 20 GHz	1 MHz	3 MHz			
Supplementary information: Peak measurement					

File Number: TC8316 Date of Issue: Nov. 15, 2011

Radiated Emissions EUT Configuration Settings

Power Interface Mode #	EUT Configurations Mode #	EUT Operation Mode #
(See Section 2.3)	(See Section 2.6)	(See 2.4)
1	1	1
Supplementary information:		

Radiated Emissions Test Equipment

Description	Manufacturer	Model	Identifier	Cal. Due
Spectrum Analyzer	Agilent Technologies	E4440A	MY46186519	2009.03.29
Signal Generator	Agilent	E4438C	MY45095542	2009.04.24
High Pass Filter	Wainwright	WHK3.3/18G-10EF	10Z	2009.08.20
Test Receiver	Rohde & Schwarz	ESIB26	100359	2009.05.26
Horn Antenna	EMCO	3115	00056768	2010.03.24
Horn Antenna	Rohde & Schwarz	BBHA9120D	539	2009.03.24
Position controller	Inn-co	CO 2000	11261105/L	-
Antenna Mast	Inn-co	MA 4000	-	-
Turntable	Inn-co	DT 3000	-	-

File Number: TC8316 Date of Issue: Nov. 15, 2011

Table 6 Spurious Radiated Emissions Data Points

Frequency (MHz)	Ant. Polarity	S.G Level (dBm)	Cable loss (dB)	Ant. Gain (dB)	EIRP Level (dBm)	dBc			
Low Channel (1	Low Channel (1850.2 MHz)								
3700.4	V	-48.5	9.5	11.8	-46.2	-76.2			
3700.4	Н	-46.4	9.5	11.8	-44.1	-74.1			
Mid Channel (1	Mid Channel (1880.2 MHz)								
3760.0	V	-46.5	9.5	11.8	-44.2	-74.2			
3760.0	Н	-45.6	9.5	11.8	-43.3	-73.3			
High Channel (1909.8 MHz)								
3819.6	V	-44.8	9.5	12.0	-42.3	-72.3			
3819.6	Н	-45.2	9.5	12.0	-42.7	-72.7			

Supplementary information:

Result of test

In accordance with	Technical requirement	of FCC Rules	section 47	CFR § 2.105	3 & § 24.238(a)
		Complied		☐ Failed	

^{-.} EIRP Level = Signal Generator output level - Cable loss + Antenna Gain(Substitution)

^{-.} EIRP measurement has been performed with three orthogonal position of the EUT. The reported data is the worst case position of Z axis(phone vertical position).

^{-.} Voice call mode was selected as a worst case operating mode which was the highest RF output power at the conducted measurement.

File Number : TC8316 Date of Issue : Nov. 15, 2011

4.5 Test Conditions and Results – Frequency Stability

Test Description	environmental chamber and t The frequency drift of the fur Supply Frequency Stability, i	Stability, measurements were made with the product placed in an he temperature varied from –30°C to +50°C at the normal supply voltage. Indamental frequency was measured with a spectrum analyzer. For Power measurements were made in a laboratory environment and the supply 15%. The ambient temperature was 20°C.			
Basic Standa	Basic Standard 47 CFR § 2.1055, § 24.235				
		Frequency Stability Limits			
-		nt to ensure that the fundamental emission stays within the authorized			

Frequency Stability Configuration Settings

Power Interface Mode # (See Section 2.3)	EUT Configurations Mode # (See Section 2.6)	EUT Operation Mode # (See 2.4)
1,2,3	2	1
Supplementary information: None		

Frequency Stability Test Equipment

Description	Manufacturer	Model	Identifier	Cal. Due
SpectrumAnalyzer	Agilent Tecnologies	E4440A	MY46186519	2009.03.29
Rf Power Meter	Agilent Tecnologies	E4418B	MY45105913	2009.03.29
Power Sensor	Agilent Tecnologies	8481H	MY41092319	2009.03.29
Coaxial Attenuator	Agilent Tecnologies	8491B	90466	2009.03.29
High Pass Filter	Wainwright	WHK3.3/18G-10EF	10Z	2009.08.20
Programmable DC Power Supply	GW Instek	PSH-2050A	EH160824	2009.03.30
Temp & Humid Test Chamber	Climats	EX2213-HA	7558	2009.06.23

File Number: TC8316 Date of Issue: Nov. 15, 2011

Table 7 Frequency Stability Test results

Frequency Stability with variation of Ambient Temperature

Carrier Band	Temperature (°C)	Assigned Frequency (Hz)	Measured Frequency (Hz)	Drift (ppm)	Limit (ppm)
	50	1,880,200,000.000	1,880,200,015.000	0.000798	2.5
	40	1,880,200,000.000	1,880,200,010.000	0.000532	2.5
	30	1,880,200,000.000	1,880,200,020.000	0.001064	2.5
	20	Reference			
GSM	10	1,880,200,000.000	1,880,200,025.000	0.001330	2.5
	0	1,880,200,000.000	1,880,200,005.000	0.000266	2.5
	-10	1,880,200,000.000	1,880,200,010.000	0.000532	2.5
	-20	1,880,200,000.000	1,880,200,010.000	0.000532	2.5
	-30	1,880,200,000.000	1,880,200,015.000	0.000798	2.5

Supplementary information:

- -. No modulation,
- -. Before the testing, the signal generator and spectrum analyzer were synchronized by using the external sync. Frequency measurement was made by spectrum analyzer
- -. Reference input voltage: 3.7Vdc

Frequency Stability with variation of Input voltage

Carrier Band	Input voltage (V)	Assigned Frequency (Hz)	Measured Frequency (Hz)	Drift (ppm)	Limit (ppm)
GSM	3.5 Vdc	1,880,200,000.000	1,880,200,005.000	0.002659	2.5
	4.2 Vdc	1,880,200,000.000	1,880,200,005.000	0.002659	2.5

Supplementary information:

- -. No modulation,
- -. Before the testing, the signal generator and spectrum analyzer were synchronized by using the external sync. Frequency measurement was made by spectrum analyzer
- -. Reference temperature : 20°C

Result of test

In a	accordan	ce with	Technical	requirement	of FCC	Rules section	า 47	$CFR \otimes$	8 2 1055 -	s 24 235
------	----------	---------	-----------	-------------	--------	---------------	------	---------------	------------	----------