


Receiver and Transmitter include the following:

- Bodypack Transmitter/1.5VAA Batteries
- Receiver/1.5VAA Batteries
- User manual

S1690R Receiver Features:




- 1 Volume Control
- 2 Earphone Jack
- 3 Battery Indicator
Green: Power On
Red Flashing: Battery Low
- 4 Antenna
- 5 Battery Cover
- 6 Channel Selector:
Select from 16 channels.
Receiver and Transmitter
must be on same channel.

This device complies with Part 15 of the FCC Rules.
Operation is subject to the following two conditions:

- (1) this device may not cause harmful interference.
- (2) this device must accept any interference received, including interference that may cause undesired operation.


MADE IN CHINA- AMPLIVOX

Wearing the Bodypack Transmitter:




Clip the transmitter to a belt through the transmitter clip as show. For best result, slide the transmitter until the belt is pressed against the base of the clip.

PV60T Transmitter Features:



- 1 Battery Indicator
Green: Power On
Red Flashing: Battery Low
- 2 Microphone Jack
- 3 Power Switch: ON / STANDBY / OFF
- 4 Antenna
- 5 Battery cover
- 6 Channel Selector:
Select from 16 channels.
Receiver and Transmitter
must be on same channel.

Battery Replacement :



A fresh alkaline battery lasts up to 6 hours. When the LED flashed RED, the battery should be replaced.

Specifications

Frequency Range and Transmitter Output level

Band	Range	Transmitter RF level
UA	470.200-607.800MHz	13dBm

Operating Range under Typical Condition

50m (150 ft.)

Note: actual range depends on RF signals absorption, reflection, and interference.

Audio Frequency Response (+/- 3 dB)

60Hz~16KHz

Total Harmonic Distortion (+/- 30 KH

deviation, 1 KHz tone) <1%

Dynamic Range

>90 dB (A - weighted)

Operating Temperature Range

-10°C to +50°C

Note: battery characteristics may limit the range

Receiver

Audio Output Level Maximum

(ref. +/-30 Khz, 1 KHz) 50mW

Audio Noise Output

<-90 dBm for 30dB SINAD, typical

Image Rejection

> 55 dB

Dimensions

3 1/4" H x 2 1/8" W x 3/4" D

Weight

2.1oz without batteries

Battery

One "AA" size alkaline or rechargeable batteries

Battery life

>6 hours (Alkaline)

Body pack Transmitter

Audio Input Level Maximum

>300MV

Input Impedance

10KΩ

Dimensions

3 1/4" H x 2 1/8" W x 3/4" D

Weight

2.1oz without batteries

Battery

One "AA" size alkaline or rechargeable batteries

Battery life

>6 hours (Alkaline)