





BNetzA-CAB-02/21-102

SAR Test exclusion documentation according to FCC KDB 447498, RSS-102

Report identification number: 1-6128/18-01-13 Exclusion (FCC_IC)

Product: Aurora miniRITE 312 T Rc (Hearing Aid Module)				
contains the module with the following certification numbers				
FCC ID	U28AUMRTRC			
IC number	1350B-AUMRTRC			
HVIN (Hardware Version Identification Number)	Aurora miniRITE 312 T Rc			
PMN (Product Marketing Name)	Aurora miniRITE 312 T Rc			
FVIN (Firmware Version Identification Number)	-/-			
HMN (Host Marketing Name)	-/-			

This report is electronically signed and valid without handwriting signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Document authorised:	
Thomas Vogler Lab Manager	Marco Scigliano Testing Manager
Radio Communications & EMC	Radio Communications & EMC

Test report no.: 1-6128/18-01-13



EUT technologies:

Technologies:	Max. rated power: (Peak)	Max. gain:	Min. pathloss:
Bluetooth LE	Measured: max -2.0 dBm	3.3 dBi	0 dB (if applicable)

Note: Bluetooth LE test results see CTC advanced test report 1-6128/18-01-05

SAR test exclusion according to KDB447498 (General RF Exposure Guidance v06)

Equation from Chapter 4.3.1: Standalone SAR test exclusion considerations page 11 and ff.

(1) Standalone SAR test exclusion for 100 MHz to 6 GHz at test separation distances ≤ 50mm

(Threshold_{1-q;10-q}) \times d_{seperation} / f ^{0.5}

where

Threshold_{1-g;10-g} is 3 for 1-g; 7.5 for 10-g

d_{seperation} is the min. test separation distance; 5mm is used if the distance is less

f is the RF channel transmit frequency

The table below gives the calculated maximal power that could be used for source based time averaged conducted or radiated power, adjusted for tune up tolerance. If this is at or below the calculated value the DUT is exempted from SAR evaluation.

ı	frequency	d _{separation}	Threshold _{1-g}	Powerlimit	P _{max-declared}		Exclusion
ı	[MHz]	[mm]		[mW]	[dBm]	[mW]	LACIUSION
	2450.00	5	3	9.58	1.30	1.35	yes

SAR test exclusion according to RSS-102 Issue 5 Section 2.5.1/Table 1

The table below gives the calculated maximal power that could be used for source based time averaged conducted or radiated power, adjusted for tune up tolerance. If this is at or below the calculated value the DUT is exempted from SAR evaluation.

frequency	d _{separation}	tissue volume	Powerlimit	P _{max} -	declared	Exclusion
[MHz]	[mm]	tissue volume	[mW]	[dBm]	[mW]	LXCIUSION
2450.00	5	1 g	4.00	1.30	1.35	yes