



FCC RF Test Report

APPLICANT : Zoombak, LLC
EQUIPMENT : Pet Locator
BRAND NAME : HOLUX
MODEL NAME : GR-520
FCC ID : U2I-ZB101
STANDARD : FCC 47 CFR Part 2, 24(E)
CLASSIFICATION : PCS Licensed Transmitter (PCB)
Tx/Rx FREQUENCY RANGE : GSM1900 : 1850.2 ~ 1909.8 MHz /
1930.2 ~ 1989.8 MHz
MAX. ERP/EIRP POWER : GSM1900 (GPRS 10) : 0.70 W
EMISSION DESIGNATOR : 246KGXW

The product was received on Jul. 01, 2010 and completely tested on Jul. 10, 2010. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA / EIA-603-C-2004 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:

Roy Wu / Manager



Testing Laboratory
1190

SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.



TABLE OF CONTENTS

| | |
|---|-----------|
| REVISION HISTORY..... | 3 |
| SUMMARY OF TEST RESULT | 4 |
| 1 GENERAL DESCRIPTION..... | 5 |
| 1.1 Applicant..... | 5 |
| 1.2 Manufacturer | 5 |
| 1.3 Feature of Equipment Under Test..... | 5 |
| 1.4 Testing Site..... | 6 |
| 1.5 Applied Standards | 6 |
| 1.6 Ancillary Equipment List | 6 |
| 2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST..... | 7 |
| 2.1 Test Mode..... | 7 |
| 2.2 Connection Diagram of Test System | 7 |
| 3 TEST RESULT..... | 8 |
| 3.1 Conducted Output Power Measurement..... | 8 |
| 3.2 Effective Isotropic Radiated Power Measurement | 10 |
| 3.3 Occupied Bandwidth Measurement | 13 |
| 3.4 Band Edge Measurement..... | 15 |
| 3.5 Conducted Emission Measurement | 17 |
| 3.6 Field Strength of Spurious Radiation Measurement | 21 |
| 3.7 Frequency Stability Measurement..... | 25 |
| 4 LIST OF MEASURING EQUIPMENT | 28 |
| 5 UNCERTAINTY OF EVALUATION..... | 29 |

APPENDIX A. PHOTOGRAPHS OF EUT

APPENDIX B. SETUP PHOTOGRAPHS



REVISION HISTORY



SUMMARY OF TEST RESULT

| Report Section | FCC Rule | IC Rule | Description | Limit | Result | Remark |
|----------------|-----------------------|----------------------------------|---|-------------------------------------|--------|--|
| 3.1 | §2.1046 | N/A | Conducted Output Power | N/A | PASS | - |
| 3.2 | §24.232(c) | RSS-133 (6.4) SRSP-510(5.1.2) | Equivalent Isotropic Radiated Power | < 2 Watts | PASS | - |
| 3.3 | §2.1049 §24.238(a) | N/A | Occupied Bandwidth | N/A | PASS | - |
| 3.4 | §2.1051 §24.238(a) | RSS-133 (6.5.1) | Band Edge Measurement | $< 43+10\log_{10}(P[\text{Watts}])$ | PASS | - |
| 3.5 | §2.1051 §24.238(a) | RSS-133 (6.5.1) | Conducted Emission | $< 43+10\log_{10}(P[\text{Watts}])$ | PASS | - |
| 3.6 | §2.1053 §24.238(a) | RSS-133 (6.5.1) | Field Strength of Spurious Radiation | $< 43+10\log_{10}(P[\text{Watts}])$ | PASS | Under limit 6.57 dB at 3760.00 MHz |
| 3.7 | §2.1055 §24.235 | RSS-133(6.3) | Frequency Stability for Temperature & Voltage | < 2.5 ppm | PASS | - |



1 General Description

1.1 Applicant

Zoombak, LLC

1000 Chesterbrook Boulevard, Suite 200 Beerwyn PA 19312-1084 USA

1.2 Manufacturer

HOLUX Technology Inc.

No. 1-1, Innovation Road 1, Science-Based Industrial Park, Hsinchu, Taiwan

1.3 Feature of Equipment Under Test

| Product Feature & Specification | |
|---------------------------------|--|
| Equipment | Pet Locator |
| Brand Name | HOLUX |
| Model Name | GR-520 |
| FCC ID | U2I-ZB101 |
| Tx Frequency | 1850 MHz ~ 1910 MHz |
| Rx Frequency | 1930 MHz ~ 1990 MHz |
| Maximum Output Power to Antenna | 29.27 dBm |
| Maximum ERP/EIRP | GSM1900 (GPRS 10) : 0.70 W (28.45 dBm) |
| Antenna Type | Fixed Internal Antenna |
| HW Version | V01 |
| SW Version | 10.00 |
| Type of Modulation | GMSK |
| Type of Emission | 246KGXW |
| EUT Stage | Production Unit |

Remark:

1. For other wireless features of this EUT, the test report will be issued separately.
2. This test report recorded only product characteristics and test results of PCS Licensed Transmitter (PCB).
3. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



1.4 Testing Site

| | | | |
|---------------------------|---|-----------|--------------------------------|
| Test Site | SPORTON INTERNATIONAL INC. | | |
| Test Site Location | No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978 | | |
| Test Site No. | Sporton Site No. | | FCC/IC Registration No. |
| | TH02-HY | 03CH07-HY | TW1022/4086B-1 |

1.5 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR Part 2, 24(E)
- ♦ ANSI / TIA / EIA-603-C-2004
- ♦ IC RSS-133 Issue 5

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B (DoC), recorded in a separate test report.

1.6 Ancillary Equipment List

| Item | Equipment | Trade Name | Model No. | FCC ID | Data Cable | Power Cord |
|------|------------------|------------|-------------|---------|------------|--|
| 1. | System Simulator | R&S | CMU200 | N/A | N/A | Unshielded, 1.8 m |
| 2. | Notebook | Dell | Vostro 1510 | FCC DoC | N/A | AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m |

2 Test Configuration of Equipment Under Test

2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range.

Frequency range investigated for radiated emission is as follows:

1. 30 MHz to 19000 MHz for GSM1900.

| Test Modes | | |
|------------|----------------|----------------|
| Band | Radiated TCs | Conducted TCs |
| GSM 1900 | ■ GPRS 10 Link | ■ GPRS 10 Link |


Note:

1. The maximum power levels are GPRS multi-slot class 10 mode for GMSK link, only these modes were used for all tests.

The conducted power tables are as follows:

| Conducted Power (*Unit: dBm) | | | |
|------------------------------|---------|--------|--------|
| Band | GSM1900 | | |
| Channel | 512 | 661 | 810 |
| Frequency | 1850.2 | 1880.0 | 1909.8 |
| GPRS 8 | 29.21 | 29.21 | 29.21 |
| GPRS 10 | 29.23 | 29.27 | 29.17 |

2.2 Connection Diagram of Test System



3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to base station.
2. Set EUT at maximum power through base station.
3. Select lowest, middle, and highest channels for each band and different modulation.

3.1.4 Test Setup



**3.1.5 Test Result of Conducted Output Power**

| PCS Band | | | | |
|-------------------|------------|-----------------|-----------------------|-------------------------|
| Modes | Channel | Frequency (MHz) | Conducted Power (dBm) | Conducted Power (Watts) |
| GSM1900 (GPRS 10) | 512 (Low) | 1850.2 | 29.23 | 0.84 |
| | 661 (Mid) | 1880.0 | 29.27 | 0.85 |
| | 810 (High) | 1909.8 | 29.17 | 0.83 |



3.2 Effective Isotropic Radiated Power Measurement

3.2.1 Description of the EIRP Measurement

EIRP is measured by substitution method according to ANSI / TIA / EIA-603-C-2004. The EIRP of mobile transmitters are limited to 2 Watts.


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The EUT was placed on an non-conductive rotating platform with 0.8 meter height in a semi-anechoic chamber. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and a spectrum analyzer with RBW= 3MHz, VBW= 3MHz, and peak detector settings.
2. During the measurement, the EUT was enforced in maximum power and linked with a base station. The highest emission was recorded from analyzer power level (LVL) from the 360 degrees rotation of the turntable and the test antenna raised and lowered over a range from 1 to 4 meters in both horizontally and vertically polarized orientations.
3. Effective Isotropic Radiated Power (EIRP) was measured by substitution method according to TIA/EIA-603-C. The EUT was replaced by dipole antenna (substitution antenna) at same location, and then a known power from S.G. was applied into the dipole antenna through a Tx cable, and then recorded the maximum Analyzer reading through raised and lowered the test antenna. The correction factor (in dB) = S.G. - Tx Cable loss + Substitution antenna gain - Analyzer reading. Then the EUT's EIRP was calculated with the correction factor, $EIRP = LVL + \text{Correction factor}$ and $ERP = EIRP - 2.15$.

3.2.4 Test Setup





3.2.5 Test Result of EIRP

| GSM1900 (GPRS 10) Radiated Power EIRP | | | | |
|---------------------------------------|-----------|------------------------|------------|----------|
| Horizontal Polarization | | | | |
| Frequency (MHz) | LVL (dBm) | Correction Factor (dB) | EIRP (dBm) | EIRP (W) |
| 1850.2 | -12.94 | 41.24 | 28.30 | 0.68 |
| 1880.0 | -13.01 | 41.46 | 28.45 | 0.70 |
| 1909.8 | -13.28 | 41.21 | 27.93 | 0.62 |

| Vertical Polarization | | | | |
|-----------------------|-----------|------------------------|------------|----------|
| Frequency (MHz) | LVL (dBm) | Correction Factor (dB) | EIRP (dBm) | EIRP (W) |
| 1850.2 | -21.54 | 41.52 | 19.98 | 0.10 |
| 1880.0 | -20.69 | 43.10 | 22.41 | 0.17 |
| 1909.8 | -20.64 | 42.73 | 22.09 | 0.16 |

* EIRP = LVL (dBm) + Correction Factor (dB)

3.3 Occupied Bandwidth Measurement

3.3.1 Description of Occupied Bandwidth Measurement

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures


1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The 99% and 26 dB occupied bandwidth (BW) of the middle channel for the highest RF powers were measured.

3.3.4 Test Setup




3.3.5 Test Result (Plots) of Occupied Bandwidth

| | | | |
|--------------------|--------------|----------------------|------|
| Band : | GSM 1900 | Power Stage : | High |
| Test Mode : | GPRS 10 Link | | |

99% Occupied Bandwidth Plot on Channel 661


Date: 9.JUL.2010 09:41:38

26dB Bandwidth Plot on Channel 661


Date: 9.JUL.2010 09:40:19

3.4 Band Edge Measurement

3.4.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

3.4.2 Measuring Instruments


See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The band edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100.

3.4.4 Test Setup


<Conducted Band Edge >



3.4.5 Test Result (Plots) of Conducted Band Edge


| | | | |
|--------------------|--------------|----------------------|------|
| Band : | GSM1900 | Power Stage : | High |
| Test Mode : | GPRS 10 Link | | |

Lower Band Edge Plot on Channel 512



Date: 9.JUL.2010 09:43:51

Higher Band Edge Plot on Channel 810



Date: 9.JUL.2010 09:44:18

3.5 Conducted Emission Measurement

3.5.1 Description of Conducted Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.


3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Test Procedures

1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The middle channel for the highest RF power within the transmitting frequency was measured.
3. The conducted spurious emission for the whole frequency range was taken.


3.5.4 Test Setup



3.5.5 Test Result (Plots) of Conducted Emission


| | | | |
|--------------------|--------------|------------------|-------|
| Band : | GSM1900 | Channel : | CH661 |
| Test Mode : | GPRS 10 Link | | |

Conducted Emission Plot between 30MHz ~ 1GHz




Date: 9.JUL.2010 10:13:03


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 9.JUL.2010 10:16:24

Conducted Emission Plot between 3GHz ~ 7GHz



Date: 9.JUL.2010 10:13:31

Conducted Emission Plot between 7GHz ~ 13.6GHz


Date: 9.JUL.2010 10:13:44



Conducted Emission Plot between 13.6GHz ~ 19.1GHz



Date: 9.JUL.2010 10:13:58



3.6 Field Strength of Spurious Radiation Measurement

3.6.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI / TIA / EIA-603-C-2004. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.


3.6.2 Measuring Instruments

See list of measuring instruments of this test report.

3.6.3 Test Procedures

1. The EUT was placed on a rotatable wooden table with 0.8 meter about ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
11. ERP (dBm) = EIRP - 2.15

3.6.4 Test Setup





3.6.5 Test Result of Field Strength of Spurious Radiated

| Band : | GSM1900 | | Temperature : | 25~26°C | | | | | |
|-------------------|--|------------------|---------------------|-------------------|------------------|--------------------|-----------------------|--------------------|--------|
| Test Mode : | GPRS 10 Link + USB Cable (Charging from Notebook) | | Relative Humidity : | 49~52% | | | | | |
| Test Engineer : | Cona Huang | | Polarization : | Horizontal | | | | | |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | | | | | | | |
| 0 | Level (dBm) | Date: 2010-07-10 | | | | | | | |
| -35 | | FCC PART22/24 | | | | | | | |
| -70 | | 6dB | | | | | | | |
| 30 | 3824. | 7618. | 11412. | 15206. 19000 | | | | | |
| | Frequency (MHz) | | | | | | | | |
| Trace: (Discrete) | | | | | | | | | |
| Site Condition | 03CH07-HV | | | | | | | | |
| Project Mode | FCC PART22/24 HF-ETRP(080306) HORIZONTAL | | | | | | | | |
| Mode | FG 070125 | | | | | | | | |
| Mode I | | | | | | | | | |
| Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
| 3760 | -19.57 | -13 | -6.57 | -34.95 | -25.87 | 2.51 | 8.81 | H | Pass |
| 5636 | -28.43 | -13 | -15.43 | -48.97 | -36.14 | 2.99 | 10.70 | H | Pass |
| 7520 | -36.10 | -13 | -23.10 | -64.07 | -44.63 | 3.59 | 12.12 | H | Pass |



| Band : | GSM1900 | Temperature : | 25~26°C | | | | | | |
|---|--|---------------------|-----------------|-------------------|------------------|--------------------|-----------------------|--------------------|--------|
| Test Mode : | GPRS 10 Link + USB Cable (Charging from Notebook) | Relative Humidity : | 49~52% | | | | | | |
| Test Engineer : | Cona Huang | Polarization : | Vertical | | | | | | |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | | | | | | | |
| <p>Level (dBm)</p> <p>Date: 2010-07-10</p> <p>FCC PART22/24</p> <p>6dB</p> <p>1 2 3 4</p> <p>Frequency (MHz)</p> <p>Trace: (Discrete)</p> <p>Site Condition : 03CH07-HV</p> <p>Project : FCC PART22/24 HF-ETRP(060306) VERTICAL</p> <p>Mode : FG 070125</p> <p>Mode 1</p> | | | | | | | | | |
| Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
| 3760 | -25.12 | -13 | -12.12 | -42.17 | -31.42 | 2.51 | 8.81 | V | Pass |
| 5636 | -32.16 | -13 | -19.16 | -53.25 | -39.87 | 2.99 | 10.70 | V | Pass |
| 7520 | -33.63 | -13 | -20.63 | -61.05 | -42.16 | 3.59 | 12.12 | V | Pass |
| 9396 | -38.57 | -13 | -25.57 | -66.09 | -47.67 | 4.1 | 13.20 | V | Pass |

3.7 Frequency Stability Measurement

3.7.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.7.2 Measuring Instruments

See list of measuring instruments of this test report.


3.7.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized for three hours. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.
4. If the EUT can not be turned on at -30°C , the testing lowest temperature will be raised in 10°C step until the EUT can be turned on.

3.7.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at $25\pm 5^\circ\text{C}$ and connected with the base station.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

3.7.5 Test Setup





3.7.6 Test Result of Temperature Variation

| Band : | GSM 1900 | Channel : | 661 |
|---------------------|--------------------|--------------------|----------------|
| Limit (ppm) : | 2.5 | | |
| Temperature (°C) | GPRS 10 | | Result PASS |
| | Freq. Dev. (Hz) | Deviation (ppm) | |
| -30 | N/A | N/A | |
| -20 | N/A | N/A | |
| -10 | 93 | 0.05 | |
| 0 | 100 | 0.05 | |
| 10 | 97 | 0.05 | |
| 20 | 104 | 0.05 | |
| 30 | 107 | 0.06 | |
| 40 | 94 | 0.05 | |
| 50 | 98 | 0.05 | |

Note:

1. The EUT stops transmitting at temperatures -20°C and -30°C.
2. The manufacturer declared that the EUT could work properly between temperatures -10°C~55°C.



3.7.7 Test Result of Voltage Variation

| Band & Channel | Mode | Voltage (Volt) | Freq. Dev. (Hz) | Deviation (ppm) | Limit (ppm) | Result |
|-------------------|---------|----------------|-----------------|-----------------|-------------|--------|
| GSM 1900 CH661 | GPRS 10 | 3.7 | 98 | 0.05 | 2.5 | PASS |
| | | BEP | 87 | 0.05 | | |
| | | 4.2 | 80 | 0.04 | | |

Note:

1. Normal Voltage = 3.7V.
2. Battery End Point (BEP) = 3.65 V.



4 List of Measuring Equipment

| Instrument | Manufacturer | Model No. | Serial No. | Characteristics | Calibration Date | Due Date | Remark |
|---------------------------|--------------|-----------|-----------------|--------------------------|------------------|---------------|-----------------------|
| System Simulator | R&S | CMU200 | 117995 | N/A | Mar. 19, 2009 | Mar. 18, 2011 | Conducted (TH02-HY) |
| Spectrum Analyzer | R&S | FSP30 | 101329 | 9kHz~30GHz | Apr. 26, 2010 | Apr. 25, 2011 | Conducted (TH02-HY) |
| Thermal Chamber | TEN BILLION | TTH-D35P | TBN-930701 | N/A | Jul. 29, 2009 | Jul. 28, 2010 | Conducted (TH02-HY) |
| Bilog Antenna | SCHAFFNER | CBL6111C | 2726 | 30MHz ~ 1GHz | Oct. 31, 2009 | Oct. 30, 2010 | Radiation (03CH07-HY) |
| Spectrum Analyzer | R&S | FSP | 101067 | 9KHz ~ 30GHz | Dec. 04, 2009 | Dec. 03, 2010 | Radiation (03CH07-HY) |
| Double Ridge Horn Antenna | ESCO | 3117 | 00075962 | 1GHz ~ 18GHz | Aug. 20, 2009 | Aug. 19, 2010 | Radiation (03CH07-HY) |
| SHF-EHF Horn Antenna | SCHWARZBECK | BBHA 9170 | BBHA917025 1 | 15GHz- 40GHz | Oct. 14, 2009 | Oct. 13, 2010 | Radiation (03CH07-HY) |
| Pre Amplifier | Agilent | 8449B | 3008A02362 | 1GHz~ 26.5GHz | Dec.09,2009 | Dec. 08, 2010 | Radiation (03CH07-HY) |
| Pre Amplifier | COM-POWER | PA-103A | 161241 | 10-1000MHz.32dB, GAIN | Mar. 27, 2010 | Mar. 26, 2011 | Radiation (03CH07-HY) |
| System Simulator | R&S | CMU200 | 117997 | N/A | May 14, 2009 | May 13, 2011 | - |



5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

| Contribution | Uncertainty of X_i | | $u(X_i)$ |
|--|----------------------|--------------------------|----------|
| | dB | Probability Distribution | |
| Receiver Reading | 0.41 | Normal (k=2) | 0.21 |
| Antenna Factor Calibration | 0.83 | Normal (k=2) | 0.42 |
| Cable Loss Calibration | 0.25 | Normal (k=2) | 0.13 |
| Pre-Amplifier Gain Calibration | 0.27 | Normal (k=2) | 0.14 |
| RCV/SPA Specification | 2.50 | Rectangular | 0.72 |
| Antenna Factor Interpolation for Frequency | 1.00 | Rectangular | 0.29 |
| Site Imperfection | 1.43 | Rectangular | 0.83 |
| Mismatch | +0.39 / -0.41 | U-Shape | 0.28 |
| Combined Standard Uncertainty $U_c(y)$ | 1.27 | | |
| Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$) | 2.54 | | |

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

| Contribution | Uncertainty of X_i | | $u(X_i)$ | C_i | $C_i * u(X_i)$ |
|--|----------------------|--------------------------|----------|-------|----------------|
| | dB | Probability Distribution | | | |
| Receiver Reading | ±0.10 | Normal (k=2) | 0.10 | 1 | 0.10 |
| Antenna Factor Calibration | ±1.70 | Normal (k=2) | 0.85 | 1 | 0.85 |
| Cable Loss Calibration | ±0.50 | Normal (k=2) | 0.25 | 1 | 0.25 |
| Receiver Correction | ±2.00 | Rectangular | 1.15 | 1 | 1.15 |
| Antenna Factor Directional | ±1.50 | Rectangular | 0.87 | 1 | 0.87 |
| Site Imperfection | ±2.80 | Triangular | 1.14 | 1 | 1.14 |
| Mismatch Receiver VSWR $\Gamma 1 = 0.197$ Antenna VSWR $\Gamma 2 = 0.194$ Uncertainty = $20\log(1-\Gamma 1 * \Gamma 2)$ | +0.34 / -0.35 | U-Shape | 0.244 | 1 | 0.244 |
| Combined Standard Uncertainty $U_c(y)$ | 2.36 | | | | |
| Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$) | 4.72 | | | | |



Appendix A. Photographs of EUT

Please refer to Sporton report number EP070125 as below.