



# FCC RF Test Report

**APPLICANT** : HOLUX Technology, Inc.  
**EQUIPMENT** : Locator  
**BRAND NAME** : HOLUX  
**MODEL NAME** : ZB-110  
**FCC ID** : U2I-ZB110  
**STANDARD** : FCC 47 CFR Part 2, 22(H), 24(E)  
**CLASSIFICATION** : PCS Licensed Transmitter (PCB)  
**Tx/Rx FREQUENCY RANGE** : GSM850 : 824.2 ~ 848.8 MHz /  
869.2 ~ 893.8 MHz  
GSM1900 : 1850.2 ~ 1909.8 MHz /  
1930.2 ~ 1989.8 MHz  
**MAX. ERP/EIRP POWER** : GSM850 (GPRS 8) : 0.90 W  
GSM1900 (GPRS 8) : 0.90 W  
**EMISSION DESIGNATOR** : 242KGXW

The product was received on Jan. 06, 2009 and completely tested on Dec. 02, 2009. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA / EIA-603-C-2004 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:

Roy Wu / Manager



**SPORTON INTERNATIONAL INC.**  
No. 52, Hwa Ya 1<sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.



## TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT .....	4
<b>1 GENERAL DESCRIPTION.....</b>	<b>5</b>
1.1    Applicant.....	5
1.2    Manufacturer .....	5
1.3    Feature of Equipment Under Test.....	5
1.4    Testing Site.....	7
1.5    Applied Standards .....	7
1.6    Ancillary Equipment List .....	7
<b>2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....</b>	<b>8</b>
2.1    Test Mode.....	8
2.2    Connection Diagram of Test System .....	8
<b>3 TEST RESULT.....</b>	<b>9</b>
3.1    Conducted Output Power Measurement.....	9
3.2    Effective Radiated Power and Effective Isotropic Radiated Power Measurement .....	11
3.3    Occupied Bandwidth Measurement .....	15
3.4    Band Edge Measurement.....	20
3.5    Conducted Emission Measurement .....	25
3.6    Field Strength of Spurious Radiation Measurement .....	31
3.7    Frequency Stability Measurement.....	37
<b>4 LIST OF MEASURING EQUIPMENT .....</b>	<b>40</b>
<b>5 UNCERTAINTY OF EVALUATION.....</b>	<b>41</b>
<b>6 CERTIFICATION OF TAF ACCREDITATION .....</b>	<b>42</b>

### APPENDIX A. PHOTOGRAPHS OF EUT

### APPENDIX B. SETUP PHOTOGRAPHS



## REVISION HISTORY



## SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	§2.1046	N/A	Conducted Output Power	N/A	PASS	
3.2	§22.913(a)(2)	RSS-132(4.4) SRSP-503(5.1.3)	Effective Radiated Power	< 7 Watts	PASS	-
3.2	§24.232(c)	RSS-133 (6.4) SRSP-510(5.1.2)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.3	§2.1049 §22.917(a) §24.238(a)	N/A	Occupied Bandwidth	N/A	PASS	-
3.4	§2.1051 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Band Edge Measurement	$< 43+10\log_{10}(P[\text{Watts}])$	PASS	-
3.5	§2.1051 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Conducted Emission	$< 43+10\log_{10}(P[\text{Watts}])$	PASS	-
3.6	§2.1053 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Field Strength of Spurious Radiation	$< 43+10\log_{10}(P[\text{Watts}])$	PASS	Under limit 4.52 dB at 3760 MHz
3.7	§2.1055 §22.355 §24.235	RSS-132(4.3) RSS-133(6.3)	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-



## 1 General Description

### 1.1 Applicant

**HOLUX Technology, Inc.**

No. 1-1, Innovation Road 1, Science-Based Industrial Park, Hsinchu Taiwan (ROC)

### 1.2 Manufacturer

**HOLUX Technology, Inc.**

No. 1-1, Innovation Road 1, Science-Based Industrial Park, Hsinchu Taiwan (ROC)

### 1.3 Feature of Equipment Under Test

Product Feature & Specification	
<b>Equipment</b>	Locator
<b>Brand Name</b>	HOLUX
<b>Model Name</b>	ZB-110
<b>FCC ID</b>	U2I-ZB110
<b>Tx Frequency</b>	GSM850 : 824 MHz ~ 849 MHz GSM1900 : 1850 MHz ~ 1910 MHz
<b>Rx Frequency</b>	GSM850 : 869 MHz ~ 894 MHz GSM1900 : 1930 MHz ~ 1990 MHz
<b>Maximum Output Power to Antenna</b>	GSM850 : 32.01 dBm GSM1900 : 29.10 dBm
<b>Maximum ERP/EIRP</b>	GSM850 (GPRS 8) : 0.90 W (29.56 dBm) GSM1900 (GPRS 8) : 0.90 W (29.56 dBm)
<b>Antenna Type</b>	PIFA Antenna
<b>HW Version</b>	GR-521_VA4
<b>SW Version</b>	DPS 20.11
<b>Type of Modulation</b>	GMSK
<b>Type of Emission</b>	242KGXW
<b>EUT Stage</b>	Identical Prototype

**Remark:**

1. For other wireless features of this EUT, the test report will be issued separately.
2. This test report recorded only product characteristics and test results of PCS Licensed Transmitter (PCB).

**List of Accessory:**

Specification of Accessory		
<b>Battery</b>	<b>Brand Name</b>	LICO
	<b>Model Name</b>	LP523436D
	<b>Power Rating</b>	3.7Vdc, 800mAh
	<b>Type</b>	Li-ion

**Remark:**

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. For accessories equipped with this EUT, please refer to the appendix of the external photo.



## 1.4 Testing Site

<b>Test Site</b>	SPORTON INTERNATIONAL INC.		
<b>Test Site Location</b>	No. 52, Hwa Ya 1 <sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978		
<b>Test Site No.</b>	<b>Sporton Site No.</b>		<b>FCC/IC Registration No.</b>
	TH02-HY	03CH07-HY	TW1022/4086B-1

## 1.5 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR Part 2, 22(H), 24(E)
- ♦ ANSI / TIA / EIA-603-C-2004
- ♦ IC RSS-132 Issue 2
- ♦ IC RSS-133 Issue 5

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B (DoC), recorded in a separate test report.

## 1.6 Ancillary Equipment List

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU200	N/A	N/A	Unshielded, 1.8 m
2.	Notebook	DELL	Vostro 1510	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m

## 2 Test Configuration of Equipment Under Test

### 2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range.

Frequency range investigated for radiated emission is as follows:

1. 30 MHz to 9000 MHz for GSM850.
2. 30 MHz to 19000 MHz for GSM1900.

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	■ GPRS 8 Link	■ GPRS 8 Link
GSM 1900	■ GPRS 8 Link	■ GPRS 8 Link


Note:

1. The maximum power levels are GPRS multi-slot class 8 mode for GMSK link, only these modes were used for all tests.

The conducted power tables are as follows:

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GPRS 8	31.65	31.80	32.01	28.23	28.64	29.10
GPRS 10	31.90	31.68	31.87	28.21	28.61	29.08

### 2.2 Connection Diagram of Test System



## 3 Test Result

### 3.1 Conducted Output Power Measurement

#### 3.1.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.


#### 3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.1.3 Test Procedures

1. The transmitter output port was connected to base station.
2. Set EUT at maximum power through base station.
3. Select lowest, middle, and highest channels for each band and different modulation.

#### 3.1.4 Test Setup





### 3.1.5 Test Result of Conducted Output Power

Cellular Band				
Modes	Channel	Frequency (MHz)	Conducted Power (dBm)	Conducted Power (Watts)
GSM850 (GPRS 8)	128 (Low)	824.2	31.65	1.46
	189 (Mid)	836.4	31.80	1.51
	251 (High)	848.8	32.01	1.59

PCS Band				
Modes	Channel	Frequency (MHz)	Conducted Power (dBm)	Conducted Power (Watts)
GSM1900 (GPRS 8)	512 (Low)	1850.2	28.23	0.67
	661 (Mid)	1880.0	28.64	0.73
	810 (High)	1909.8	29.10	0.81



## **3.2 Effective Radiated Power and Effective Isotropic Radiated Power Measurement**

### **3.2.1 Description of the ERP/EIRP Measurement**

ERP/EIRP is measured by substitution method according to

ANSI / TIA / EIA-603-C-2004. The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.


### **3.2.2 Measuring Instruments**

See list of measuring instruments of this test report.

### **3.2.3 Test Procedures**

1. The EUT was placed on an non-conductive rotating platform with 0.8 meter height in a semi-anechoic chamber. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and a spectrum analyzer with RBW= 3MHz, VBW= 3MHz, and peak detector settings.
2. During the measurement, the EUT was enforced in maximum power and linked with a base station. The highest emission was recorded from analyzer power level (LVL) from the 360 degrees rotation of the turntable and the test antenna raised and lowered over a range from 1 to 4 meters in both horizontally and vertically polarized orientations.
3. Effective Isotropic Radiated Power (EIRP) was measured by substitution method according to TIA/EIA-603-C. The EUT was replaced by dipole antenna (substitution antenna) at same location, and then a known power from S.G. was applied into the dipole antenna through a Tx cable, and then recorded the maximum Analyzer reading through raised and lowered the test antenna. The correction factor (in dB) = S.G. - Tx Cable loss + Substitution antenna gain - Analyzer reading. Then the EUT's EIRP was calculated with the correction factor,  $EIRP = LVL + \text{Correction factor}$  and  $ERP = EIRP - 2.15$ .

### 3.2.4 Test Setup





### 3.2.5 Test Result of ERP

GSM850 (GPRS 8) Radiated Power ERP				
Horizontal Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (W)
824.2	-5.03	32.04	24.86	0.31
836.4	-5.12	32.91	25.64	0.37
848.8	-6.15	32.84	24.54	0.28

Vertical Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (W)
824.2	-4.39	36.1	29.56	0.90
836.4	-3.74	34.41	28.52	0.71
848.8	-4.53	34.65	27.97	0.63

\* ERP = LVL (dBm) + Correction Factor (dB) – 2.15



### 3.2.6 Test Result of EIRP

GSM1900 (GPRS 8) Radiated Power EIRP				
Horizontal Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (W)
1850.2	-15.20	40.91	25.71	0.37
1880.0	-15.31	42.38	27.07	0.51
1909.8	-15.72	42.3	26.58	0.45
Vertical Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (W)
1850.2	-14.07	43.63	29.56	0.90
1880.0	-15.46	43.55	28.09	0.64
1909.8	-16.43	44.84	28.41	0.69

\* EIRP = LVL (dBm) + Correction Factor (dB)

### 3.3 Occupied Bandwidth Measurement

#### 3.3.1 Description of Occupied Bandwidth Measurement

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


#### 3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.3.3 Test Procedures


1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The 99% and 26 dB occupied bandwidth (BW) of the middle channel for the highest RF powers were measured.

#### 3.3.4 Test Setup




### 3.3.5 Test Result (Plots) of Occupied Bandwidth

<b>Band :</b>	GSM 850	<b>Power Stage :</b>	High
<b>Test Mode :</b>	GPRS 8 Link		

**99% Occupied Bandwidth Plot on Channel 189**



Date: 2.DEC.2009 14:08:10



Date: 2.DEC.2009 14:08:44



## 26dB Bandwidth Plot on Channel 189




Date: 2.DRC.2009 14:04:31




Band :	GSM 1900	Power Stage :	High
Test Mode :	GPRS 8 Link		

## 99% Occupied Bandwidth Plot on Channel 661




Date: 2.DRC.2009 14:28:26



Date: 2.DRC.2009 14:29:14



## 26dB Bandwidth Plot on Channel 661



Date: 2.DRC.2009 14:26:05

## 3.4 Band Edge Measurement

### 3.4.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

### 3.4.2 Measuring Instruments


See list of measuring instruments of this test report.

### 3.4.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The band edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100.


### 3.4.4 Test Setup

#### <Conducted Band Edge >




### 3.4.5 Test Result (Plots) of Conducted Band Edge



<b>Band :</b>	GSM850	<b>Power Stage :</b>	High
<b>Test Mode :</b>	GPRS 8 Link		

**Lower Band Edge Plot on Channel 128**


Date: 2.DRC.2009 14:09:46



Date: 2.DRC.2009 14:10:14


**Higher Band Edge Plot on Channel 251**


Date: 2.DEC.2009 14:11:16




Band :	GSM1900	Power Stage :	High
Test Mode :	GPRS 8 Link		


## Lower Band Edge Plot on Channel 512




Date: 2.DRC.2009 14:30:14



Date: 2.DRC.2009 14:30:50

**Higher Band Edge Plot on Channel 810**


Date: 2.DEC.2009 14:32:24



Date: 2.DEC.2009 14:31:41

### 3.5 Conducted Emission Measurement

#### 3.5.1 Description of Conducted Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10<sup>th</sup> harmonic.


#### 3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.5.3 Test Procedures


1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The middle channel for the highest RF power within the transmitting frequency was measured.
3. The conducted spurious emission for the whole frequency range was taken.

#### 3.5.4 Test Setup





### 3.5.5 Test Result (Plots) of Conducted Emission

<b>Band :</b>	GSM850	<b>Channel :</b>	CH189
<b>Test Mode :</b>	GPRS 8 Link		


**Conducted Emission Plot between 30MHz ~ 1GHz**


Date: 2.DRC.2009 14:13:24

**Conducted Emission Plot between 1GHz ~ 3GHz**


**Conducted Emission Plot between 3GHz ~ 7GHz**


Date: 2.DEC.2009 14:15:37


**Conducted Emission Plot between 7GHz ~ 9GHz**


Date: 2.DEC.2009 14:16:13




Band :	GSM1900	Channel :	CH661
Test Mode :	GPRS 8 Link		

## Conducted Emission Plot between 30MHz ~ 1GHz




Date: 2.DEC.2009 14:21:33


## Conducted Emission Plot between 1GHz ~ 3GHz



Date: 2.DEC.2009 14:20:48

**Conducted Emission Plot between 3GHz ~ 7GHz**



Date: 2.DEC.2009 14:19:02

**Conducted Emission Plot between 7GHz ~ 13.6GHz**


Date: 2.DEC.2009 14:18:30



## Conducted Emission Plot between 13.6GHz ~ 19.1GHz



Date: 2.DEC.2009 14:17:43



## 3.6 Field Strength of Spurious Radiation Measurement

### 3.6.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI / TIA / EIA-603-C-2004. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.


### 3.6.2 Measuring Instruments

See list of measuring instruments of this test report.

### 3.6.3 Test Procedures


1. The EUT was placed on a rotatable wooden table with 0.8 meter about ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10.  $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
11.  $ERP \text{ (dBm)} = EIRP - 2.15$

### 3.6.4 Test Setup





## 3.6.5 Test Result of Field Strength of Spurious Radiated

Band :	GSM850		Temperature :	24~25°C					
Test Mode :	GPRS 8 Link		Relative Humidity :	51~54%					
Test Engineer :	Kay Wu		Polarization :	Horizontal					
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
		Date: 2009-11-25							
<p>Trace: (Discrete)</p> <p>Site : 03CH07-HV Condition : FCC PART22/24 HF-ETRP(080306) HORIZONTAL Project : FG 910601 Memo : Mode 1 Power : From Battery</p>									
Frequency	ERP	Limit	Over Limit	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
( MHz )	( dBm )	( dBm )	( dB )	( dBm )	( dBm )	( dB )	( dBi )	( H/V )	
1669	-43.86	-13	-30.86	-52.02	-43.71	3.39	5.39	H	Pass
2509	-49.40	-13	-36.40	-59.54	-49.66	3.71	6.12	H	Pass




<b>Band :</b>	GSM850		<b>Temperature :</b>	24~25°C					
<b>Test Mode :</b>	GPRS 8 Link		<b>Relative Humidity :</b>	51~54%					
<b>Test Engineer :</b>	Kay Wu		<b>Polarization :</b>	Vertical					
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
<b>Level (dBm)</b>				<b>Date: 2009-11-25</b>					
0									
-35				<b>FCC PART22/24</b>					
-70				<b>6dB</b>					
30	1824.	3618.	5412.	7206.					
				9000					
<b>Frequency (MHz)</b>									
<b>Trace: (Discrete)</b>									
Site	03CH07-HV								
Condition	FCC PART22/24 HF-EIRP(080306) VERTICAL								
Project	FG 910601								
Memo	Mode 1								
Power	From Battery								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
( MHz )	( dBm )	( dBm )	Limit	Reading	Power	loss	Gain	( H/V )	
1669	-36.85	-13	-23.85	-45.78	-36.7	3.39	5.39	V	Pass
2509	-46.04	-13	-33.04	-56.58	-46.3	3.71	6.12	V	Pass



Band :	GSM1900		Temperature :	24~25°C					
Test Mode :	GPRS 8 Link		Relative Humidity :	51~54%					
Test Engineer :	Kay Wu		Polarization :	Horizontal					
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Level (dBm)				Date: 2009-11-25					
0									
-35				FCC PART22/24					
-70				6dB					
30	3624.	7218.	10812.	14406.					
				18000					
Frequency (MHz)									
Trace: (Discrete)									
Site Condition	03CH07-HV								
Project	FCC PART22/24 HF-ETRP(060306) HORIZONTAL								
Memo	FG 910601								
Power	Mode 1 From Battery								
Frequency	EIRP	Limit	Over Limit	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
( MHz )	( dBm )	( dBm )	( dB )	( dBm )	Power	loss	Gain		
3760	-21.43	-13	-8.43	-36.37	-23.95	4.88	7.40	H	Pass
5636	-38.77	-13	-25.77	-58.48	-42.03	5.55	8.81	H	Pass
9396	-39.00	-13	-26.00	-62.04	-42.81	6.91	10.72	H	Pass



<b>Band :</b>	GSM1900		<b>Temperature :</b>	24~25°C					
<b>Test Mode :</b>	GPRS 8 Link		<b>Relative Humidity :</b>	51~54%					
<b>Test Engineer :</b>	Kay Wu		<b>Polarization :</b>	Vertical					
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
			Date: 2009-11-25						
<b>Trace: (Discrete)</b> Site : 03CH07-HV Condition : FCC PART22/24 HF-ETRP(080306) VERTICAL Project : FG 910601 Memo : Mode I Power : From Battery									
Frequency	EIRP	Limit	Over Limit	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
( MHz )	( dBm )	( dBm )	( dB )	( dBm )	Power	loss	Gain		
3760	-17.52	-13	-4.52	-33.35	-20.55	4.88	7.91	V	Pass
5636	-39.66	-13	-26.66	-59.81	-43.88	5.55	9.77	V	Pass
9396	-36.79	-13	-23.79	-63.75	-41.4	6.91	11.52	V	Pass

## 3.7 Frequency Stability Measurement

### 3.7.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within  $\pm 0.00025\%$  ( $\pm 2.5\text{ppm}$ ) of the center frequency.

### 3.7.2 Measuring Instruments

See list of measuring instruments of this test report.


### 3.7.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to  $-30^\circ\text{C}$  and the EUT was stabilized for three hours. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in  $10^\circ\text{C}$  step up to  $50^\circ\text{C}$ . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.
4. If the EUT can not be turned on at  $-30^\circ\text{C}$ , the testing lowest temperature will be raised in  $10^\circ\text{C}$  step until the EUT can be turned on.

### 3.7.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at  $25\pm 5^\circ\text{C}$  and connected with the base station.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

### 3.7.5 Test Setup





### 3.7.6 Test Result of Temperature Variation

Band :	GSM 850	Channel :	189
Limit (ppm) :	2.5		

Temperature (°C)	GPRS 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	N/A	N/A	PASS
-20	N/A	N/A	
-10	-15	-0.02	
0	-21	-0.02	
10	-22	-0.03	
20	-24	-0.03	
30	-18	-0.02	
40	-23	-0.03	
50	-26	-0.03	

**Note:** The manufacturer declared that the EUT could work properly between temperatures -10°C~55°C.

Band :	GSM 1900	Channel :	661
Limit (ppm) :	2.5		

Temperature (°C)	GPRS 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	N/A	N/A	PASS
-20	N/A	N/A	
-10	13	0.01	
0	-14	-0.01	
10	-33	-0.02	
20	-31	-0.02	
30	-14	-0.01	
40	-15	-0.01	
50	-21	-0.01	

**Note:** The manufacturer declared that the EUT could work properly between temperatures -10°C~55°C.



### 3.7.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Freq. Dev. (Hz)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GPRS 8	3.7	-22	-0.03	2.5	PASS
		BEP	-28	-0.03		
		4.2	-35	-0.04		
GSM 1900 CH661	GPRS 8	3.7	-17	-0.01		
		BEP	23	0.01		
		4.2	16	0.01		

**Note:**

1. Normal Voltage = 3.7V.
2. Battery End Point (BEP) = 3.65 V.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Due Date	Remark
System Simulator	R&S	CMU200	116456	N/A	Jun. 05, 2008	Jun. 04, 2010	Conducted (TH02-HY)
Spectrum Analyzer	R&S	FSP40	100055	9kHz~40GHz	Jun. 23, 2009	Jun. 22, 2010	Conducted (TH02-HY)
Thermal Chamber	TEN BILLION	TTH-D35P	TBN-930701	N/A	Jul. 29, 2009	Jul. 28, 2010	Conducted (TH02-HY)
Bilog Antenna	SCHAFFNER	CBL6111C	2726	30MHz ~ 1GHz	Oct. 31, 2009	Oct. 30, 2010	Radiation (03CH07-HY)
Spectrum Analyzer	R&S	FSP	101067	9KHz ~ 30GHz	Dec. 04, 2009	Dec. 03, 2010	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	00075962	1GHz ~ 18GHz	Aug. 20, 2009	Aug. 19, 2010	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA917025 1	15GHz- 40GHz	Oct. 14, 2009	Oct. 13, 2010	Radiation (03CH07-HY)
Pre Amplifier	Agilent	8449B	3008A02362	1GHz~ 26.5GHz	Dec. 17, 2008	Dec. 16, 2009	Radiation (03CH07-HY)
Pre Amplifier	COM-POWER	PA-103A	161241	10-1000MHz.32dB. GAIN	Mar. 27, 2009	Mar. 26, 2010	Radiation (03CH07-HY)
Loop Antenna	R&S	HFH2-Z2	860004/001	9 KHz~30 MHz	May 22, 2008	May 21, 2010	Radiation (03CH07-HY)
System Simulator	R&S	CMU200	117997	N/A	May 14, 2009	May 13, 2011	-



## 5 Uncertainty of Evaluation

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Contribution	Uncertainty of $X_i$		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.41	Normal (k=2)	0.21
Antenna Factor Calibration	0.83	Normal (k=2)	0.42
Cable Loss Calibration	0.25	Normal (k=2)	0.13
Pre-Amplifier Gain Calibration	0.27	Normal (k=2)	0.14
RCV/SPA Specification	2.50	Rectangular	0.72
Antenna Factor Interpolation for Frequency	1.00	Rectangular	0.29
Site Imperfection	1.43	Rectangular	0.83
Mismatch	+0.39 / -0.41	U-Shape	0.28
<b>Combined Standard Uncertainty <math>U_c(y)</math></b>	<b>1.27</b>		
<b>Measuring Uncertainty for a Level of Confidence of 95% (<math>U = 2U_c(y)</math>)</b>	<b>2.54</b>		

### Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Contribution	Uncertainty of $X_i$		$u(X_i)$	$C_i$	$C_i * u(X_i)$
	dB	Probability Distribution			
Receiver Reading	±0.10	Normal (k=2)	0.10	1	0.10
Antenna Factor Calibration	±1.70	Normal (k=2)	0.85	1	0.85
Cable Loss Calibration	±0.50	Normal (k=2)	0.25	1	0.25
Receiver Correction	±2.00	Rectangular	1.15	1	1.15
Antenna Factor Directional	±1.50	Rectangular	0.87	1	0.87
Site Imperfection	±2.80	Triangular	1.14	1	1.14
Mismatch Receiver VSWR $\Gamma 1 = 0.197$ Antenna VSWR $\Gamma 2 = 0.194$ Uncertainty = $20\log(1-\Gamma 1 * \Gamma 2)$	+0.34 / -0.35	U-Shape	0.244	1	0.244
<b>Combined Standard Uncertainty <math>U_c(y)</math></b>	<b>2.36</b>				
<b>Measuring Uncertainty for a Level of Confidence of 95% (<math>U = 2U_c(y)</math>)</b>	<b>4.72</b>				



## 6 Certification of TAF Accreditation



Certificate No. : L1190-090417

財團法人全國認證基金會  
Taiwan Accreditation Foundation

### Certificate of Accreditation

This is to certify that

**Sportun International Inc.**  
**EMC & Wireless Communications Laboratory**  
No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,  
Taiwan, R.O.C.

is accredited in respect of laboratory

**Accreditation Criteria** : ISO/IEC 17025:2005  
**Accreditation Number** : 1190  
**Originally Accredited** : December 15, 2003  
**Effective Period** : January 10, 2007 to January 09, 2010  
**Accredited Scope** : Testing Field, see described in the Appendix  
**Specific Accreditation Program** : Accreditation Program for Designated Testing Laboratory  
for Commodities Inspection  
Accreditation Program for Telecommunication Equipment  
Testing Laboratory  
Accreditation Program for BSMI Mutual Recognition  
Arrangement with Foreign Authorities

Jay-San Chen  
President, Taiwan Accreditation Foundation  
Date : April 17, 2009

P1, total 20 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when use without the Appendix



## **Appendix A. Photographs of EUT**

Please refer to Sporton report number EP910601 as below.